SAR: State Aware Retrieval for Iterative Retrieval Augmented Generation

A Project Report Submitted in

partial fulfillment of requirements for the degree of

Bachelor of Technology

In

Computer Engineering

By

Kunal Dahal (22CSEC17)

Aniket Manger (22CSEC23)

Suman Chettri (22CSEC44)

Under the supervision of

Mr. Anmol Pandey

Assistant Professor

Computer Engineering Department



Department Of Computer Engineering

Sikkim Institute of Science and Technology

(A constituent college of Sikkim University)

2026

ABSTRACT

Retrieval-Augmented Generation (RAG) systems rely on effective retrieval of external information to support language models in answering questions that may require knowledge beyond their internal parameters. While conventional retrieval methods primarily focus on the relevance of documents to the original query, this objective becomes less sufficient in iterative retrieval settings, where some of the required information may already have been collected, and subsequent retrieval needs to focus on what is still missing. In such settings, repeatedly retrieving documents that are similar to previously obtained evidence can lead to redundancy and limit the usefulness of later retrieval steps.

This project explores **State Aware Retrieval**, a retrieval approach developed for iterative information retrieval. The approach considers not only the relevance of a document to the question, but also the extent to which it is related to information that is currently missing and to evidence that has already been collected. These signals are used to guide retrieval toward documents that can provide useful complementary information.

The proposed approach is integrated into the MIGRES framework, where missing information is identified during the retrieval process and used to guide subsequent information seeking. State Aware Retrieval focuses on the document selection step, with the broader objective of making iterative retrieval more targeted, less redundant, and better aligned with the information that remains necessary for answering a question.

Keywords: Retrieval-Augmented Generation, Information Retrieval, Iterative Retrieval, Multi-Hop Question Answering.

TABLE OF CONTENTS

CHP NO.	TOPICS	PAGE NO.
	ABSTRACT	i
	TABLE OF CONTENTS	ii
	LIST OF TABLES	iii
	LIST OF FIGURES	iii
1.	INTRODUCTION	1
2.	LITERATURE SURVEY	2–6
3.	PROBLEM DEFINITION	7
4.	OBJECTIVES	8
5.	SOLUTION STRATEGY / METHODOLOGY	9–24
6.	SOFTWARE AND HARDWARE REQUIREMENTS	25–26
7.	APPLICATIONS	27
8.	GANTT CHART	28
9.	CONCLUSION	29
	REFERENCES	30

LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
2.1	Literature Survey 1	2
2.2	Literature Survey 2	3
2.3	Literature Survey 3	4
2.4	Literature Survey 4	5
2.5	Literature Survey 5	6
5.1	State Aware Retrieval Settings	16
5.2	State Aware Retrieval hyperparameters	16
5.3	State Aware Retrieval settings	16
5.4	State Aware Retrieval Hyperparameters	18
5.5	State Aware Retrieval Parameters	18
5.6	Information Retrieval Baseline Comparison	19
6.1	Software Requirements	25
6.2	Modules Description	26

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
5.1	Architecture of State Aware Retrieval	11
5.2	Operational Flow of State Aware Retrieval	12
5.3	Sentence Transformer Based Retrieval Representation	17
8.1	Gantt Chart	28

CHAPTER 1

INTRODUCTION

Retrieval-Augmented Generation (RAG) is a technique that combines information retrieval with large language models to improve question answering. Instead of depending only on the information stored in a language model, RAG retrieves relevant information from external documents and uses it to generate an answer [1]. This makes RAG useful for tasks where the required information may be spread across different documents.

However, answering complex questions is not always as simple as finding documents that are related to the question. Some questions require multiple pieces of information, and the first retrieval step may provide only part of what is needed. Multi-hop question answering benchmarks and iterative retrieval methods show that solving such questions can require evidence from multiple passages or documents and repeated retrieval steps [2, 3, 4]. If the retrieval system continues to select documents mainly because they are related to the original question, it may repeatedly retrieve similar information instead of finding the missing evidence.

MIGRES (Missing Information Guided Retrieve-Extraction-Solving) provides a framework for handling this type of iterative information retrieval. It keeps track of the information already collected and identifies information that is still required to answer the question [5]. This creates an opportunity to improve the retrieval stage by considering not only the original question, but also the current information gap and the evidence already collected. Related work on relevant information gain also motivates reducing redundant evidence while preserving useful information for RAG [6].

This project proposes a State Aware Retrieval for improving document selection in such iterative RAG systems. The main idea is to select documents based on their relevance to the question, their usefulness for covering the missing information, and the amount of new information they can provide compared with the evidence already collected.

The proposed approach will be studied within the MIGRES framework and evaluated on question-answering datasets. It will be compared with existing retrieval approaches to examine its effect on retrieval quality, answer quality, and retrieval efficiency. The study will also investigate the importance of the different factors considered by the proposed approach.

The overall aim of this project is to explore whether making the retrieval process aware of the current information gap can help RAG systems retrieve more useful and complementary evidence for complex questions.

CHAPTER 2

LITERATURE SURVEY

Table 2.1: Literature Survey 1

Name of paper	Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks [1]
Authors	Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela
Publication Details	Advances in Neural Information Processing Systems 33 (NeurIPS), 2020, pp. 9459–9474.
Research Findings	• RAG combines information stored in a language model with information retrieved from external documents. • Retrieved passages help the model answer questions that require outside knowledge. • The approach shows that retrieval can improve the performance of language generation for knowledge-intensive tasks. • The work provides a basic foundation for modern retrieval-augmented generation systems.
Research Gap	• The main retrieval process is based on finding passages relevant to the given question. • It does not mainly focus on identifying which information is still missing after previous evidence has been retrieved. • The work does not specifically study how retrieval can change according to the information already collected.
Relevance with Our Work	• This paper provides the basic RAG background for our project. • It supports the use of external documents to provide additional information to language models. • Our work builds on this general retrieval setting by studying retrieval in a more iterative information-seeking process.

Table 2.2: Literature Survey 2

Name of paper	Leveraging Passage Retrieval with Generative Models for Open Domain Question Answering [7]
Authors	Gautier Izacard and Edouard Grave
Publication Details	Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics (EACL), 2021, pp. 874–880.
Research Findings	• The method retrieves multiple passages and provides them to a generative model. • The model can use information from several passages to answer a question. • Using useful information from multiple retrieved passages can improve question-answering performance. • The work shows the importance of selecting and using several relevant pieces of evidence.
Research Gap	• The focus is mainly on how a generative model uses multiple retrieved passages. • It does not mainly study how the retrieval process should identify information that is missing from earlier evidence. • The retrieved passages are not selected according to a changing information state across multiple retrieval steps.
Relevance with Our Work	• This work supports the importance of collecting multiple useful pieces of evidence. • It is indirectly related to our goal of improving the usefulness of retrieved documents. • Our project further considers how the current information need can be used when selecting documents during iterative retrieval.

Table 2.3: Literature Survey 3

Name of paper	LLMs Know What They Need: Leveraging a Missing Information Guided Framework to Empower Retrieval-Augmented Generation [5]
Authors	Keheng Wang, Feiyu Duan, Peiguang Li, Sirui Wang, and Xunliang Cai
Publication Details	Proceedings of the 31st International Conference on Computational Linguistics (COLING), 2025, pp. 2379–2400.
Research Findings	• MIGRES identifies information that is still missing after processing the retrieved evidence. • The identified missing information is used to guide the next retrieval step. • The framework performs retrieval and evidence processing in multiple steps. • The approach is designed for questions that require several pieces of information.
Research Gap	• The framework mainly focuses on identifying missing information and guiding the next retrieval query. • There is still room to study how candidate documents can be ranked using both the missing information and the evidence already collected. • Different document-ranking strategies may affect which evidence is selected during the iterative process.
Relevance with Our Work	• MIGRES provides an important background for understanding missing information during iterative RAG. • It supports the idea that later retrieval should focus on information that is still required. • Our project uses this general idea as motivation for studying a gap-aware retrieval and reranking approach. • The paper provides the main framework in which our proposed approach can be investigated.

Table 2.4: Literature Survey 4

Name of paper	Unsupervised Alignment-based Iterative Evidence Retrieval for Multi-hop Question Answering [4]
Authors	Vikas Yadav, Steven Bethard, and Mihai Surdeanu
Publication Details	Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL), 2020, pp. 4514–4525.
Research Findings	• AIR is an iterative method designed to retrieve evidence for multi-hop questions. • The retrieval process changes after each step instead of using the same query throughout. • Later retrieval focuses on information that is not already covered by the available evidence. • The work shows that iterative retrieval can help collect complementary evidence.
Research Gap	• The method mainly focuses on changing the retrieval query based on previously collected information. • It does not fully explore a separate ranking stage that considers relevance, missing information, and existing evidence together. • There is room to investigate other ways of selecting complementary documents during iterative retrieval.
Relevance with Our Work	• AIR is closely related to the idea of avoiding already-covered information. • It supports the importance of retrieving complementary evidence in multi-step question answering. • This provides useful background for studying a retrieval method that considers the current information state.

Table 2.5: Literature Survey 5

Name of paper	Better RAG using Relevant Information Gain [6]
Authors	Marc Pickett, Jeremy Hartman, Ayan Kumar Bhowmick, Raquib-ul Alam, and Aditya Vempaty
Publication Details	arXiv preprint, 2024, arXiv:2407.12101.
Research Findings	• The paper studies how relevant information gain can be used to improve document selection in RAG. • It aims to reduce redundant information while keeping the retrieved information relevant. • The approach gives importance to documents that provide useful information not already present in the selected evidence. • The work highlights the importance of balancing relevance with the usefulness of new information.
Research Gap	• The main focus is on selecting useful and non-redundant information from retrieved passages. • It does not mainly focus on a changing information need across several retrieval steps. • The current missing information can provide an additional signal for deciding which document should be selected next.
Relevance with Our Work	• This work provides useful background for reducing repeated or unnecessary evidence. • It supports the idea that document selection should consider more than simple relevance. • The concept of useful new information is indirectly related to our goal of selecting documents that help cover the current information gap.

CHAPTER 3

PROBLEM DEFINITION

1. In iterative Retrieval-Augmented Generation (RAG), some useful information may already be retrieved in earlier steps. However, the next retrieval may return similar information instead of focusing on what is still missing.
2. In conventional retrieval, documents are mainly selected according to their relevance to the query. This may favor information that has already been collected instead of information that is still missing.
3. Previous evidence is not fully considered when selecting documents for later retrieval. As a result, redundant documents may be selected while useful and complementary documents may be missed.
4. Therefore, there is a need for a state aware retrieval approach that considers the query, missing information, and previously collected evidence to select more useful documents for the next retrieval step.

CHAPTER 4

OBJECTIVES

1. To study existing RAG and iterative retrieval methods and identify the limitations of relevance-based retrieval in later retrieval steps.
2. To study how missing information can be used to guide document retrieval in an iterative setting.
3. To study how previously collected evidence can be used to reduce redundant information and select complementary documents.
4. To experimentally evaluate and verify the effectiveness of the proposed State Aware Retrieval for improving document retrieval in iterative RAG.

CHAPTER 5

SOLUTION STRATEGY / METHODOLOGY

The proposed methodology introduces **State Aware Retrieval** as a direct retrieval algorithm within the MIGRES framework [5]. The main reasoning, evidence extraction, and information gap update steps of MIGRES remain unchanged. Only the document retrieval step is replaced by the proposed method.

At each iteration t, the method uses the original question q, the collected evidence E_t, the current information gaps G_t, and the document corpus $\mathcal{D}$. The documents are embedded using a fixed Sentence Transformer model, and the embeddings are stored for reuse. The question, gaps, and evidence are also converted into embeddings.

Each document is compared with the question, all current gaps, and the collected evidence using semantic similarity. These similarity values are then combined to give a final state aware score for each document. The exact scoring equation will be finalized during implementation and experimentation.

The documents are ranked by their final scores, and the top-K documents are selected. The value of K can be set by the user for each retrieval setting.

The methodology therefore follows five main stages:

1. **Corpus embedding:** encode the complete document corpus using the fixed Sentence Transformer model and store the document embeddings for reuse. When new documents are added, encode their embeddings and add them to the stored corpus.

2. **MIGRES state preparation:** use the MIGRES framework to maintain the question, collected evidence, and current missing information during the iterative process.

3. **State aware document scoring:** compare each document in the corpus with the question, each current information-gap requirement, and the evidence collected so far.

4. **Top-K retrieval:** use the resulting state aware score to rank the corpus documents and retrieve the highest-scoring K documents.

5. **Iterative state update:** pass the selected documents to MIGRES for filtering and evidence extraction, update the evidence and information-gap state, and repeat the retrieval process when more information is required.

5.1 Proposed Solution

The main problem is that in iterative retrieval, a document may be relevant to the original question but may not provide the information that is still missing. It may also contain information that has already been collected. This can lead to repeated retrieval and less useful evidence [4, 6, 8].

To address this problem, we propose **State Aware Retrieval**, a direct retrieval method that uses the current retrieval state when selecting documents. The current state includes the original question q, the information gaps G_t, and the evidence collected so far E_t. Instead of selecting documents only by their similarity to the original question, the proposed method considers all three parts of the current state.

The complete document corpus $\mathcal{D}$ is used as the searchable corpus. The documents are represented using a fixed Sentence Transformer model. At each iteration, the question, current gaps, and collected evidence are also represented in the same semantic space. Each document is compared with these state elements using semantic similarity.

The resulting similarity information is used by the State Aware Retrieval method to assign a final score to each document. The documents are ranked using this score, and the top-K documents are selected for retrieval.

The selected documents are then passed to MIGRES for its existing filtering, evidence extraction, and information gap update process. The updated state is used in the next retrieval iteration. In this way, the proposed method changes its retrieval decisions as the available information changes.

5.1.1 Architecture Diagram

The proposed system uses MIGRES to manage the iterative retrieval process. At each iteration, MIGRES provides the question, current evidence, and information gaps. These inputs are embedded using a Sentence Transformer and compared with the document embeddings. State Aware Retrieval combines the similarity information to score the documents and selects the top-K documents. The selected documents are then passed back to MIGRES for filtering, evidence extraction, and state update.




Figure 5.1: Architecture of State Aware Retrieval

5.1.2 Operational Flow

The operational flow describes how the proposed system performs retrieval at each iteration. MIGRES provides the current question, evidence, and information gaps. These inputs are embedded and compared with the document corpus. State Aware Retrieval then scores and selects the top-K documents, which are passed to MIGRES for filtering, evidence extraction, and state update. The updated state is used in the next iteration.




Figure 5.2: Operational Flow of State Aware Retrieval

5.2 Mathematical Formulation

At iteration t, the retrieval state contains the question q, the collected evidence E_t, the current information gap G_t, and the complete corpus $\mathcal{D}$. The retrieval method uses this state to assign one final score to every document in the corpus.

5.2.1 Notation

Let

$$E_t = \{e_1, e_2, \ldots, e_n\}$$

be the evidence collected before iteration t, and let

$$G_t = \{g_1, g_2, \ldots, g_m\}$$

be the information gaps identified by MIGRES. The searchable document corpus is:

$$\mathcal{D} = \{d_1, d_2, \ldots, d_N\}.$$

The current retrieval state is represented as:

$$\boxed{(q, E_t, G_t, \mathcal{D})}.$$

5.2.2 Corpus Embedding

Before retrieval begins, all documents in the corpus are encoded using the selected Sentence Transformer model. The resulting document embeddings are stored and reused during retrieval:

$$\phi(d) \leftarrow \text{Sentence Transformer}(d).$$

At the end of each retrieval iteration, the system checks for new or updated documents in the corpus. New documents are encoded using the same model and added to the stored embeddings. Updated documents are re-encoded and replaced with their new embeddings. This keeps the searchable embedding collection up to date without re-embedding unchanged documents.

5.2.3 State Embedding

At each iteration, the question, current gaps, and collected evidence are encoded using the same Sentence Transformer:

$$\phi(q), \qquad \phi(g_i), \qquad \phi(e_j).$$

This places the question, gaps, evidence, and documents in the same semantic space.

5.2.4 Sentence Similarity

The semantic similarity between two text items x and y is measured using cosine similarity:

$$\cos(x, y) = \frac{\phi(x)^T \phi(y)}{\|\phi(x)\|_2 \|\phi(y)\|_2}.$$

For the proposed scoring method, the value can be normalized to the range $[0, 1]$ using:

$$\boxed{s(x, y) = \frac{1 + \cos(x, y)}{2}} \tag{1}$$

A higher value means that the two representations are more semantically similar.

5.2.5 Question Relevance

Question relevance measures how closely a document matches the original question:

$$\boxed{R(d, q) = s(d, q)} \tag{2}$$

A higher value means that the document is more related to the main question.

5.2.6 Gap Coverage

The document is compared with every current information gap:

$$\boxed{c(d, g_i) = s(d, g_i)} \tag{3}$$

The gap coverage score combines the similarity values for the current gaps:

$$\boxed{C(d, G_t) = \frac{1}{m} \sum_{i=1}^{m} c(d, g_i)} \tag{4}$$

A higher value means that the document is more closely related to the information that is currently missing. At the first iteration, $G_0 = \emptyset$ and the gap-coverage value is defined as $C(d, G_0) = 0$. If no valid gap remains after a completed iteration, MIGRES can stop the retrieval process.

5.2.7 Evidence Novelty

The document is compared with all previously collected evidence. The novelty score is based on the document's strongest similarity with existing evidence:

$$\boxed{N(d, E_t) = 1 - \max_{e_j \in E_t} s(d, e_j)} \tag{5}$$

A document that is very similar to previous evidence receives a lower novelty value. A document that is less similar to the existing evidence receives a higher novelty value. At the first iteration, when no evidence has been collected:

$$\boxed{N(d, E_0) = 1.} \tag{6}$$

5.2.8 State Aware Document Score

The three signals are combined to give one final score to every document:

$$\boxed{S_t(d \mid q, E_t, G_t) = \alpha R(d, q) + \beta C(d, G_t) + \gamma N(d, E_t)} \tag{7}$$

where:

$$\boxed{\alpha, \beta, \gamma \geq 0, \qquad \alpha + \beta + \gamma = 1.} \tag{8}$$

Here, α controls the importance of question relevance, β controls the importance of current gap coverage, and γ controls the importance of new information compared with previous evidence.

5.2.9 Top-K Retrieval

After the final score is calculated for the documents in the corpus, they are ranked from highest to lowest score. The final retrieval result is:

$$\boxed{T_t = \mathrm{TopK}_{d \in \mathcal{D}} \, S_t(d \mid q, E_t, G_t)} \tag{9}$$

The parameter K defines how many documents are returned. No fixed similarity threshold is used before Top-K selection.

5.2.10 Iterative State Update

The selected documents T_t are passed to MIGRES for filtering and information extraction. The useful extracted information is added to the evidence state, and MIGRES identifies the remaining gap for the next iteration:

$$\boxed{(q, E_t, G_t, \mathcal{D}) \rightarrow T_t \rightarrow (E_{t+1}, G_{t+1}) \rightarrow T_{t+1}} \tag{10}$$

The process continues until MIGRES determines that enough information has been collected or the configured iteration limit is reached.

5.3 State Aware Retrieval Configurations

The following settings define the main configuration used for the proposed State Aware Retrieval system. They specify the models, similarity method, retrieval space, document embedding setup, and other tools used in the project.

Table 5.1: State Aware Retrieval Settings

Setting	**Value**	**Purpose**
Embedding model	multi-qa-mpnet-base-cos-v1	Creates common semantic representations for questions, documents, gaps, and evidence.
Similarity function	Cosine similarity	Measures semantic similarity between embedding vectors.
Retrieval space	Complete document corpus $\mathcal{D}$	Every document is considered during State Aware Retrieval.
Document embeddings	Precomputed and maintained	Stored once and updated when new or changed documents appear.
Framework	MIGRES	Provides the iterative evidence and information-gap state.
LLM API	Gemini 3.8 Flash	Used for the language-model parts of the project through the Gemini API.

The State Aware Retrieval method uses a small number of hyperparameters and retrieval settings. The hyperparameters control the scoring process, while the retrieval settings define how the system operates during each experiment.The scoring weights will be selected using the validation data and fixed before the final test evaluation. The weights will follow the normalization constraint defined in the final scoring formulation.

Table 5.2: State Aware Retrieval hyperparameters

Hyperparameter	**Role**	**Selection**
α	Question relevance weight	Selected using validation data.
β	Gap coverage weight	Selected using validation data.
γ	Evidence novelty weight	Selected using validation data.

Table 5.3: State Aware Retrieval settings

Setting	**Role**	**Selection**
K	Number of documents retrieved	Configurable for each experiment.
$T_{\max}$	Maximum number of retrieval cycles	Fixed for each experiment and used with the MIGRES stopping condition.

5.4 Datasets and Model

5.4.1 Datasets

The evaluation uses six question-answering datasets used in the MIGRES setting. They cover multi-hop reasoning, information gathering, and evidence-based question answering:

- **WikiHop:** A multi-document question-answering dataset requiring information from multiple documents [9].
- **HotpotQA:** A multi-hop question-answering dataset with supporting facts [2].
- **MuSiQue:** A multi-hop dataset designed for compositional reasoning [3].
- **Natural Questions:** A question-answering dataset based on real search queries [10].
- **TriviaQA:** A question-answering dataset with independently collected evidence documents [11].
- **StrategyQA:** A question-answering dataset requiring implicit reasoning over supporting information [12].

Official training, development, and test splits are kept separate wherever available. Validation data are used for system development and parameter selection, while the final test data are kept for the final comparison.

5.4.2 Model

The proposed State Aware Retrieval method uses the `sentence-transformers/multi-qa-mpnet-base-cos-v1` model. It is a Sentence Transformer model designed for semantic search. It converts text into 768-dimensional dense vectors. The same model is used for questions, documents, information gaps, and evidence [13, 14].

The document corpus is embedded before retrieval and the embeddings are stored for reuse. At each iteration, the current question, gaps, and evidence are embedded using the same model. The resulting vectors are then compared using cosine similarity.




Figure 5.3: Sentence Transformer Based Retrieval Representation

5.5 Experimental Design

The experiments are designed to evaluate the proposed State Aware Retrieval method from different perspectives. The study includes retrieval performance evaluation, ablation analysis, parameter and hyperparameter selection, comparison with existing information retrieval methods, downstream RAG evaluation, and computational cost analysis. The experiments are first conducted using the validation data, and the selected configuration is then fixed for the final test evaluation.

5.6 Experimental Design

The experiments are designed to evaluate State Aware Retrieval from different perspectives. The study includes parameter and hyperparameter selection, comparison with existing retrieval methods, ablation testing, retrieval evaluation, iterative state analysis, downstream RAG and robustness evaluation, and computational cost analysis.

The validation data are used for system selection and parameter tuning. The selected configuration is then fixed before the final test evaluation.

5.6.1 Parameter and Hyperparameter Selection

The proposed State Aware Retrieval method uses both hyperparameters and retrieval parameters. Hyperparameters control the contribution of the state signals to the final document score, while retrieval parameters control the retrieval process.

Table 5.4: State Aware Retrieval Hyperparameters

Hyperparameter	**Role**	**Selection**
α	Question relevance weight	Selected using Bayesian optimization on validation data.
β	Gap coverage weight	Selected using Bayesian optimization on validation data.
γ	Evidence novelty weight	Selected using Bayesian optimization on validation data.

Table 5.5: State Aware Retrieval Parameters

Parameter	**Role**	**Selection**
K	Number of documents retrieved at each iteration	Selected from predefined values using validation data.
$T_{\max}$	Maximum number of retrieval iterations	Fixed for the experiment and used with the MIGRES stopping condition.

The hyperparameters α, β, and γ are selected using Bayesian optimization on the validation data and fixed before the final test evaluation [15].

Two scoring settings are also compared. In the static setting, the same weights are used at all retrieval iterations:

$$\alpha_t = \alpha, \qquad \beta_t = \beta, \qquad \gamma_t = \gamma$$

In the dynamic setting, the weights may change according to the current retrieval state:

$$\alpha_t, \qquad \beta_t, \qquad \gamma_t$$

Both settings use the same corpus, embedding model, retrieval depth, and evaluation protocol.

5.6.2 Baseline Comparison

The proposed State Aware Retrieval method is compared with established information retrieval methods. All methods are evaluated on the same document corpus and use the same evaluation questions and final retrieval depth where applicable.

Table 5.6: Information Retrieval Baseline Comparison

System	**Type**	**Main Retrieval Basis**
BM25	Sparse lexical	Term frequency, inverse document frequency, and document length [16]
DPR	Dense	Question and passage embeddings learned with a dual encoder [17]
Contriever	Dense	Unsupervised dense representations for semantic retrieval [18]
SPLADE	Sparse neural	Sparse learned representations with lexical expansion [19]
ColBERTv2	Late interaction	Token-level document and query representations with late interaction [20]
Sentence Transformer Search	Dense semantic	Sentence embeddings and cosine similarity with Top-K retrieval [13]
State Aware Retrieval	Hybrid	Question relevance, gap coverage, and evidence novelty

The comparison is used to determine how State Aware Retrieval performs against lexical, dense, sparse-neural, late-interaction, and standard semantic retrieval methods.

5.6.3 Ablation Study

The ablation study measures the contribution of each state signal used by State Aware Retrieval. The full SAR configuration is compared with versions where individual signals are removed.

- **SAR-Full:** question relevance, gap similarity, and evidence similarity.
- **SAR-Without-Relevance:** removes question relevance.
- **SAR-Without-Gap:** removes gap similarity.

- **SAR-Without-Evidence:** removes evidence similarity.
- **Question-Only:** uses only document-question semantic similarity.

All ablation settings use the same corpus, embedding model, retrieval depth K, and evaluation protocol. The results are compared using the retrieval and downstream metrics defined in the evaluation study.

5.6.4 Retrieval Performance Evaluation

The main retrieval experiment evaluates the quality of the documents selected by State Aware Retrieval. The selected SAR configuration is fixed after validation and compared with the baseline methods.

Let R_q be the set of relevant documents for question q, and let $T_K(q)$ be the Top-K retrieved documents.

Recall@K

$$\text{Recall@K}(q) = \frac{|T_K(q) \cap R_q|}{|R_q|}$$

Recall@K measures how much of the relevant evidence is retrieved.

Precision@K

$$\text{Precision@K}(q) = \frac{|T_K(q) \cap R_q|}{K}$$

Precision@K measures the proportion of retrieved documents that are relevant.

Hit@K

$$\text{Hit@K}(q) = \begin{cases} 1, & T_K(q) \cap R_q \neq \emptyset, \\ 0, & \text{otherwise.} \end{cases}$$

Hit@K measures whether at least one relevant document is retrieved.

Mean Reciprocal Rank

If r_q is the rank of the first relevant document:

$$\text{RR}(q) = \frac{1}{r_q}$$

$$\text{MRR} = \frac{1}{N} \sum_{q=1}^{N} \text{RR}(q)$$

MRR measures how early the first relevant document appears.

nDCG@K

$$\text{DCG@K} = \sum_{i=1}^{K} \frac{2^{rel_i} - 1}{\log_2(i+1)}$$

$$\text{nDCG@K} = \frac{\text{DCG@K}}{\text{IDCG@K}}$$

where rel_i is the relevance value at rank i and IDCG@K is the ideal DCG [21].

Only metrics supported by the ground-truth relevance information of a dataset are reported.

5.6.5 Iterative State Analysis

State Aware Retrieval is intended to change its retrieval behavior as the evidence and information gap change. This experiment studies the retrieval results across successive iterations.

Let T_t be the documents retrieved at iteration t.

Cumulative Recall

$$U_t = \bigcup_{i=1}^{t} T_i$$

$$\text{CumulativeRecall}_t = \frac{|U_t \cap R_q|}{|R_q|}$$

This measures the relevant evidence collected up to iteration t.

Marginal Recall Gain

$$\Delta R_t = \text{CumulativeRecall}_t - \text{CumulativeRecall}_{t-1}$$

This measures the additional relevant evidence found at the current iteration.

New Document Rate

$$\text{NewRate}_t = \frac{\left|T_t \setminus \bigcup_{i=1}^{t-1} T_i\right|}{|T_t|}$$

This measures the proportion of newly retrieved documents.

Retrieval Overlap

$$J(T_t, T_{t-1}) = \frac{|T_t \cap T_{t-1}|}{|T_t \cup T_{t-1}|}$$

This measures the overlap between successive retrieval sets.

These measures are used to determine whether the changing evidence and information gap lead to different and complementary retrieval results.

5.6.6 Downstream RAG and Robustness Evaluation

State Aware Retrieval is evaluated within the MIGRES framework to measure its effect on the final answer. The same MIGRES configuration and language model are used for SAR and the baseline retrieval methods.

Answer Evaluation

Final answer quality is measured using the official metrics of each dataset where available.

Exact Match:

$$\text{EM} = \frac{\#\text{exactly correct answers}}{N}$$

Accuracy:

$$\text{Accuracy} = \frac{\#\text{correct answers}}{N}$$

For token-level F1:

$$P = \frac{|\text{tokens}(A_p) \cap \text{tokens}(A_g)|}{|\text{tokens}(A_p)|}$$

$$R = \frac{|\text{tokens}(A_p) \cap \text{tokens}(A_g)|}{|\text{tokens}(A_g)|}$$

$$F1 = \frac{2PR}{P + R}$$

RGB Robustness

The Retrieval-Augmented Generation Benchmark (RGB) is used to test robustness under four settings: noise robustness, negative rejection, information integration, and counterfactual robustness [22].

For noise robustness:

$$\text{Accuracy}(\rho) = \frac{\#\text{correct answers at noise level } \rho}{N}$$

For negative rejection:

$$\text{RejectionRate} = \frac{\#\text{correctly rejected cases}}{\#\text{negative cases}}$$

For counterfactual error detection:

$$\text{ED} = \frac{\#\text{correctly detected counterfactual cases}}{\#\text{counterfactual cases}}$$

For counterfactual correction:

$$\text{CR} = \frac{\#\text{correctly corrected detected cases}}{\#\text{detected error cases}}$$

The same evaluation settings are used for SAR and the selected baseline methods.

5.6.7 Computational Cost Evaluation

The computational cost of State Aware Retrieval is measured because the method scores the complete document corpus at each retrieval iteration.

Retrieval Latency

Let L_i be the retrieval time for question i.

$$L_{\text{avg}} = \frac{1}{N} \sum_{i=1}^{N} L_i$$

Documents Scored

If the corpus contains $|\mathcal{D}|$ documents and the system performs T retrieval iterations:

$$N_{\text{scored}} = |\mathcal{D}| \times T$$

Similarity Calculations

If each document is compared with one question, m gaps, and n evidence items:

$$N_{\text{similarity}} = |\mathcal{D}|(1 + m + n)$$

Retrieval Overhead

$$\text{Overhead}(\%) = \frac{L_{\text{SAR}} - L_{\text{baseline}}}{L_{\text{baseline}}} \times 100$$

The experiment records retrieval time, total iteration time, embedding time, number of documents scored, and memory usage.

5.7 Experimental Environment and Reproducibility

The project uses a Python-based environment for dataset processing, document embedding, State Aware Retrieval, MIGRES integration, and evaluation. The dataset versions, model versions, software packages, hardware, and experiment settings are recorded for reproducibility.

The document corpus is embedded before retrieval and the embeddings are stored for reuse. At the end of each retrieval iteration, the corpus is checked for new or updated documents. New documents are embedded and added to the stored collection, while updated documents are re-embedded.

The main experimental pipeline is:

$$\begin{aligned}\text{Document Corpus} &\rightarrow \text{Document Embeddings}\\ &\rightarrow \text{MIGRES State} \rightarrow \text{State Aware Retrieval}\\ &\rightarrow \text{Top-}K \rightarrow \text{MIGRES State Update.}\end{aligned}$$

The scoring hyperparameters are selected using validation data, while the retrieval settings are fixed according to the experimental design. The selected configuration is frozen before the final test evaluation.

5.8 Chapter Solution Summary

This chapter presented State Aware Retrieval (SAR) as a direct retrieval method within the MIGRES framework. SAR uses the current question, information gaps, and collected evidence to guide document selection from the complete document corpus.

The documents are represented using a common Sentence Transformer embedding space. At each iteration, the documents are compared with the current retrieval state, and a final score is used to select the top-K documents. The selected documents are then passed to MIGRES for filtering, evidence extraction, and state update.

The proposed method does not use a separate BM25 candidate stage or a fixed retrieval threshold. The final scoring formulation is developed and evaluated during implementation. The experiments evaluate the contribution of the state signals, compare SAR with existing retrieval methods, measure retrieval and downstream RAG performance, study its behaviour across iterations, and measure its computational cost.

CHAPTER 6

SOFTWARE AND HARDWARE REQUIREMENTS

The proposed solution uses a Python-based environment for dataset preparation, document embedding, State Aware Retrieval, hyperparameter selection, MIGRES integration, and evaluation. Jupyter Notebook is used for experiment development and analysis, while LaTeX is used for preparing the research document. The main software and hardware requirements are described below.

6.1 Software Requirements

The main software tools required for the implementation are shown in Table 6.1.

Table 6.1: Software Requirements

Software / Tool	**Version**	**Purpose**
Python	3.14.7	Main programming environment for data processing, document embedding, retrieval, and evaluation.
Jupyter Notebook	7.6.2	Experiment development, execution, and result analysis.
PyTorch	2.13.0	Tensor computation and neural model execution.
Sentence Transformers	5.6.1	Generates semantic embeddings for questions, documents, information gaps, and evidence using `multi-qa-mpnet-base-cos-v1`.
Pinecone	9.1.0	Stores document embeddings and metadata as the persistent vector database for the document corpus.
Bayesian Optimization	3.3.0	Selects the State Aware Retrieval scoring hyperparameters using validation data.
LaTeX	Overleaf	Preparation of the research document.
Gemini API	Gemini 3.8 Flash	Provides the language model used by MIGRES for information-gap processing and response generation.

The primary embedding model is `sentence-transformers/multi-qa-mpnet-base-cos-v1`. It converts questions, documents, information gaps, and collected evidence into a common semantic vector space. The model produces 768-dimensional normalized embeddings and supports cosine similarity [13, 14].

The document embeddings are stored in Pinecone and reused during retrieval. When a new document is added or an existing document is changed, its embedding is generated using the same Sentence Transformer

model and the corresponding vector is added or updated in Pinecone. The embedding model remains fixed and is not fine-tuned during the main experiments.

6.2 Modules Description

The proposed State Aware Retrieval methodology is divided into three main modules: the Embedding and Corpus Module, the Scoring Module, and the Selection Module. Their responsibilities are shown in Table 6.2.

Table 6.2: Modules Description

Module	**Responsibility**
Embedding and Corpus Module	Encodes the document corpus using the Sentence Transformer model and stores the document embeddings and metadata in Pinecone. At the end of each retrieval iteration, the corpus is checked for new or changed documents. Their embeddings are then added or updated in Pinecone.
Scoring Module	Represents the current question, information gaps, and collected evidence using the same Sentence Transformer model. It compares the document embeddings with these state elements using semantic similarity and produces the values required for State Aware Retrieval scoring.
Selection Module	Uses the final State Aware Retrieval score to rank the documents and select the Top-K documents. The selected documents are passed to MIGRES for filtering and evidence extraction. The updated evidence and information-gap state are then used for the next retrieval iteration.

6.3 Hardware Requirements

The proposed system can be implemented on a standard computer system with internet access. The main hardware requirements are:

- **Processor:** Intel Core i5 / AMD Ryzen 5 or equivalent.
- **RAM:** Minimum 16 GB.
- **Storage:** At least 20 GB of available SSD storage.
- **GPU:** Optional; an NVIDIA GPU with 8 GB VRAM may be used for faster local embedding computation.

CHAPTER 7

APPLICATIONS

1. **Complex Question Answering:** Can support AI systems in answering complex questions where the required information is spread across multiple documents and cannot be obtained through a single retrieval step.

2. **Multi-Step Information Retrieval:** Can be applied to systems that repeatedly search for information, helping each retrieval step focus on information that has not yet been obtained.


3. **Research and Knowledge Discovery:** Can assist in collecting information from large document collections by prioritizing useful and complementary evidence instead of repeatedly retrieving similar content.

4. **Evidence-Based RAG Applications:** Can be integrated into RAG-based applications where the system needs to build a complete set of evidence before generating an answer, such as question answering, document analysis, and knowledge-based assistants.

CHAPTER 8

GANTT CHART

Figure 8.1: Gantt Chart



CHAPTER 9

CONCLUSION

This methodology presents **State Aware Retrieval (SAR)** as a direct retrieval method within the MIGRES framework. The proposed method uses the current question, information gaps, and previously collected evidence to guide document selection from the complete document corpus. The selected documents are then passed to MIGRES for filtering, evidence extraction, and further state updates.

The study will examine whether making retrieval aware of the current information state can improve the quality and usefulness of retrieved evidence during iterative retrieval. The contribution of each state signal will be studied through ablation experiments, while comparisons with established retrieval methods will measure the overall retrieval performance of SAR. The effect on final RAG performance, behaviour across iterations, robustness, and computational cost will also be evaluated.

Overall, this methodology provides a clear framework for testing whether State Aware Retrieval can make iterative retrieval more focused on the information that is relevant, still missing, and not already covered by previous evidence. The main MIGRES framework remains unchanged, allowing the study to directly examine the effect of the proposed retrieval method. The final experimental results will determine the effectiveness and practical value of SAR for iterative retrieval-augmented generation.

REFERENCES

[1] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal, H. K"uttler, M. Lewis, W.-t. Yih, T. Rockt"aschel, S. Riedel, and D. Kiela, "Retrieval-augmented generation for knowledge-intensive nlp tasks," in *Advances in Neural Information Processing Systems 33*, 2020, pp. 9459–9474. [Online]. Available: https://papers.nips.cc/paper/2020/hash/6b493230205f780e1bc26945df7481e5-Abstract.html

[2] Z. Yang, P. Qi, S. Zhang, Y. Bengio, W. Cohen, R. Salakhutdinov, and C. D. Manning, "Hotpotqa: A dataset for diverse, explainable multi-hop question answering," in *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, 2018, pp. 2369–2380.

[3] H. Trivedi, N. Balasubramanian, T. Khot, and A. Sabharwal, "Musique: Multihop questions via single-hop question composition," *Transactions of the Association for Computational Linguistics*, vol. 10, pp. 539–554, 2022.

[4] V. Yadav, S. Bethard, and M. Surdeanu, "Unsupervised alignment-based iterative evidence retrieval for multi-hop question answering," in *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, 2020, pp. 4514–4525.

[5] K. Wang, F. Duan, P. Li, S. Wang, and X. Cai, "Llms know what they need: Leveraging a missing information guided framework to empower retrieval-augmented generation," in *Proceedings of the 31st International Conference on Computational Linguistics*, 2025, pp. 2379–2400.

[6] M. Pickett, J. Hartman, A. K. Bhowmick, R. ul Alam, and A. Vempaty, "Better rag using relevant information gain," *arXiv preprint arXiv:2407.12101*, 2024.

[7] G. Izacard and E. Grave, "Leveraging passage retrieval with generative models for open domain question answering," in *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, 2021, pp. 874–880.

[8] Z. Wang, Z. Liang, Z. Shao, Y. Ma, H. Dai, B. Chen, L. Mao, C. Lei, Y. Ding, and H. Li, "Infogain-rag: Boosting retrieval-augmented generation through document information gain-based reranking and filtering," in *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, 2025, pp. 7190–7204.

[9] J. Welbl, P. Stenetorp, and S. Riedel, "Constructing datasets for multi-hop reading comprehension across documents," *Transactions of the Association for Computational Linguistics*, vol. 6, pp. 287–302, 2018.

[10] T. Kwiatkowski, J. Palomaki, O. Redfield, M. Collins, A. Parikh, C. Alberti, D. Epstein, I. Polosukhin, J. Devlin, K. Lee, K. Toutanova, L. Jones, M. Kelcey, M.-W. Chang, J. Uszkoreit, Q. Le, and S. Petrov, "Natural questions: A benchmark for question answering research," *Transactions of the Association for Computational Linguistics*, vol. 7, pp. 452–466, 2019.

[11] M. Joshi, E. Choi, D. Weld, and L. Zettlemoyer, "Triviaqa: A large scale distantly supervised challenge dataset for reading comprehension," in *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics*, 2017, pp. 1601–1611.

[12] M. Geva, D. Khashabi, E. Segal, T. Khot, D. Roth, and J. Berant, "Did aristotle use a laptop? a question answering benchmark with implicit reasoning strategies," *Transactions of the Association for Computational Linguistics*, vol. 9, pp. 346–361, 2021.

[13] N. Reimers and I. Gurevych, "Sentence-bert: Sentence embeddings using siamese bert-networks," in *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing*, 2019, pp. 3982–3992.

[14] Sentence Transformers, "multi-qa-mpnet-base-cos-v1," Hugging Face model card, 2020, 768-dimensional sentence-transformers model designed for semantic search.

[15] J. Snoek, H. Larochelle, and R. P. Adams, "Practical bayesian optimization of machine learning algorithms," in *Advances in Neural Information Processing Systems*, vol. 25, 2012.

[16] S. Robertson and H. Zaragoza, "The probabilistic relevance framework: Bm25 and beyond," *Foundations and Trends in Information Retrieval*, vol. 3, no. 4, pp. 333–389, 2009.

[17] V. Karpukhin, B. Oguz, S. Min, P. Lewis, L. Wu, S. Edunov, D. Chen, and W. tau Yih, "Dense passage retrieval for open-domain question answering," in *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing*, 2020, pp. 6769–6781.

[18] G. Izacard, M. Caron, L. Hosseini, S. Riedel, P. Bojanowski, A. Joulin, and E. Grave, "Unsupervised dense information retrieval with contrastive learning," in *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, 2022, pp. 2665–2679.

[19] T. Formal, C. Lassance, B. Piwowarski, and S. Clinchant, "Splade: Sparse lexical and expansion model for first stage ranking," in *arXiv preprint arXiv:2107.05720*, 2021.

[20] K. Santhanam, O. Khattab, J. Saad-Falcon, C. Potts, and M. Zaharia, "Colbertv2: Effective and efficient retrieval via lightweight late interaction," in *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics*, 2022, pp. 3715–3734.

[21] K. Järvelin and J. Kekäläinen, "Cumulated gain-based evaluation of ir techniques," *ACM Transactions on Information Systems*, vol. 20, no. 4, pp. 422–446, 2002.

[22] J. Chen, H. Lin, X. Han, and L. Sun, "Benchmarking large language models in retrieval-augmented generation," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 38, no. 16, 2024, pp. 17 754–17 762.