PDF Upload — Successful Response



Primary Key — Answer and Sources

Curl

```
curl -X 'POST' \
  'http://localhost:8001/ask' \
  -H 'accept: */*' \
  -H 'Content-Type: application/json' \
  -d '{
  "question": "What is a primary key?"
}'
```

Request URL

```
http://localhost:8001/ask
```

Server response

Code	Details
200	Response body


```
{
  "question": "What is a primary key?",
  "answer": "A primary key is the candidate key selected to identify rows.",
  "answer_type": "Extractive answer",
  "retrieval_method": "Haystack BM25 with answer-focused reranking",
  "message": "Answer extracted from uploaded study notes.",
  "sources": [
    {
      "filename": "campusmind_sample_study_notes.pdf",
      "page": 2,
      "relevance_score": 8.7915,
      "bm25_score": 3.2935,
      "relevant_text": "Topic 2: Relational Model The relational model represents data using relations, commonly displayed as tables. A table contains rows and columns. A row is also called a tuple, and a column is also called an attribute. Each attribute has a domain that defines its permitted values. Keys in a relational database A super key is any set of attributes that uniquely identifies a row. A candidate key is a minimal super key. A primary key is the candidate key selected to identify rows. A foreign key is an attribute or set of attributes that references a key in another table and helps maintain referential integrity. Example Consider a STUDENT table with StudentID, StudentName, and DepartmentID. StudentID can be the primary key. DepartmentID can be a foreign key referencing the DEPARTMENT table."
    },
    {
      "filename": "campusmind_sample_study_notes.pdf",
      "page": 3,
      "relevance_score": 8.3784,
      "bm25_score": 3.3784,
      "relevant_text": "Topic 3: SQL Basics SQL stands for Structured Query Language. It is used to define, manipulate, query, and control data in relational database systems. Common SQL command categories DDL (Data Definition Language): CREATE, ALTER, DROP. DML (Data Manipulation Language): INSERT, UPDATE, DELETE. DQL (Data Query Language): SELECT. DCL (Data Control Language): GRANT, REVOKE. TCL (Transaction Control Language): COMMIT, ROLLBACK. Example query SELECT StudentName FROM STUDENT WHERE DepartmentID = 10; This query returns the names of students whose DepartmentID is 10. Quick revision question Question: What is the difference between a primary key and a foreign key? Answer: A primary key uniquely identifies a row in its own table.
```


Download

Foreign Key — Answer and Sources

Curl

```
curl -X 'POST' \
  'http://localhost:8001/ask' \
  -H 'accept: */*' \
  -H 'Content-Type: application/json' \
  -d '{
  "question": "Explain foreign key"
}'
```

Request URL

```
http://localhost:8001/ask
```

Server response

Code	Details
200	Response body


```
{
  "question": "Explain foreign key",
  "answer": "A foreign key is an attribute or set of attributes that references a key in another table and helps maintain referential integrity.",
  "answer_type": "Extractive answer",
  "retrieval_method": "Haystack BM25 with answer-focused reranking",
  "message": "Answer extracted from uploaded study notes.",
  "sources": [
    {
      "filename": "campusmind_sample_study_notes.pdf",
      "page": 2,
      "relevance_score": 8.2231,
      "bm25_score": 1.7233,
      "relevant_text": "Topic 2: Relational Model The relational model represents data using relations, commonly displayed as tables. A table contains rows and columns. A row is also called a tuple, and a column is also called an attribute. Each attribute has a domain that defines its permitted values. Keys in a relational database A super key is any set of attributes that uniquely identifies a row. A candidate key is a minimal super key. A primary key is the candidate key selected to identify rows. A foreign key is an attribute or set of attributes that references a key in another table and helps maintain referential integrity. Example Consider a STUDENT table with StudentID, StudentName, and DepartmentID. StudentID can be the primary key. DepartmentID can be a foreign key referencing the DEPARTMENT table."
    },
    {
      "filename": "campusmind_sample_study_notes.pdf",
      "page": 3,
      "relevance_score": 3.6501,
      "bm25_score": 1.6501,
      "relevant_text": "Topic 3: SQL Basics SQL stands for Structured Query Language. It is used to define, manipulate, query, and control data in relational database systems. Common SQL command categories DDL (Data Definition Language): CREATE, ALTER, DROP. DML (Data Manipulation Language): INSERT, UPDATE, DELETE. DQL (Data Query Language): SELECT. DCL (Data Control Language): GRANT, REVOKE. TCL (Transaction Control Language): COMMIT, ROLLBACK. Example query SELECT StudentName FROM STUDENT WHERE DepartmentID = 10; This query returns the names of students whose DepartmentID is 10. Quick revision question Question: What is the difference between a primary key and a foreign key? Answer: A primary key uniquely identifies a row in its own table.
```


Download