

Scientific Programming with Python

Collections: Lists, Tuples, Aliasing

UNIVERSITY of
HOUSTON

DIVISION OF RESEARCH
HEWLETT PACKARD ENTERPRISE DATA SCIENCE INSTITUTE

Collections

collection are data type composed of smaller pieces

- **Strings**
- **Lists**
- **Tuples**
- **Dictionaries**
- **Sets**

Lists

- A list is a linear data structure, meaning that its elements have a linear ordering.
- List is a sequential collection of data objects
- Items in a list can be accessed by indexing, and sublists can be accessed by slicing.
- Lists are mutable; individual items or entire slices can be replaced through assignment statements.
- Lists support a number of convenient and frequently used methods.
- Lists will grow and shrink as needed. With append, access insert, update, concatenate and delete operations.

Lists: Review

- A **list** is a **linear data structure**, meaning that its elements have a linear ordering.
- An example of a list is sequence of daily temperatures for a given week:

0:	68.8
1:	70.2
2:	67.2
3:	71.8
4:	73.2
5:	75.6
6:	74.0

The location at index 0 stores the temperature for Sunday, the location at index 1 stored the temperature for Monday, and so on. It is customary in programming languages to begin numbering sequences of items with an index value of 0 rather than 1. This is referred to as **zero-based indexing**.

Lists: Review

- A **list traversal** is a means of accessing, one-by-one, each element of a list.
- List traversal may be used, for example, to:
 - **search** for a particular item in a list
 - **add up** all the elements of a list

Lists: Review

- List can be accessed in loops

- Directly with items

```
listofnames = ['Mary', 'Susan', 'John']  
for name in listofnames:
```

...

- Or through indices

```
for i in range(len(listofnames)):  
    name = listofnames[i]
```

...

Lists (Sequences) in Python

- A **list** in Python is a **mutable**, **linear** data structure of **variable length**, allowing **mixed-type elements**.
- By **mutable** is meant that the contents of the list may be altered. **Lists in Python use zero-based indexing**. Thus, all lists have index values 0..n-1, where n is the number of elements in the list.

Lists (Sequences) in Python

- Lists are denoted by a comma-separated list of elements within square brackets,

[1, 2, 3] ['one', 'two', 'three'] ['apples', 50, True]

- An empty list is denoted by an empty pair of square brackets, []. Elements of a list are accessed by use of an index value within square brackets,

lst = [1, 2, 3]

lst[0] → 1 access of first element

lst[1] → 2 access of second element

lst[2] → 3 access of third element

- For example, the following prints the first element of list `lst`,
`print (lst[0])`

- The elements of `lst` can be summed as follows,

`sum = lst[0] + lst[2] + lst[2]`

- To update, `lst[2] = 4` replacement of 3 with 4
-
- To delete, `del lst[2]` removal of 4 at index 2
- To insert, `lst.insert(1,3)` insertion of 3 at index 1
- To append, `lst.append(4)` appends 4 to end of list

Operation	fruit = ['banana', 'apple', 'cherry']	
Replace	fruit[2] = 'coconut'	['banana', 'apple', 'coconut']
Delete	del fruit[0]	['apple', 'cherry']
Insert	fruit.insert(2, 'pear')	['banana', 'apple', 'pear', 'cherry']
Append	fruit.append('peach')	['banana', 'apple', 'cherry', 'peach']
Sort	fruit.sort()	['apple', 'banana', 'cherry']
Reverse	fruit.reverse()	['cherry', 'apple', 'banana']

Let's Try It

From the Python Shell, enter the following and observe the results.

From the Python Shell, enter the following and observe the results.

```
>>> lst = [10, 20, 30]
>>> lst
???
```

```
>>> lst[0]
???
```

```
>>> lst[0] = 5
>>> lst
???
```

```
>>> del lst[2]
>>> lst
???
```

```
>>> lst.insert(1, 15)
>>> lst
???
```

```
>>> lst.append(40)
>>> lst
???
```

Tuples

- A **tuple** is an *immutable linear data structure*. Thus, in contrast to lists, once a tuple is defined it cannot be altered. Otherwise, tuples and lists are essentially the same.
- To distinguish tuples from lists, *tuples are denoted by parentheses instead of square brackets* as given below,

```
nums = (10, 20, 30)
```

```
student = ('John Smith', 48, 'Computer Science', 3.42)
```

One element Tuple

- Another difference of tuples and lists is that **tuples of one element must include a comma following the element**. Otherwise, the parenthesized element will not be made into a tuple, as shown below,

- **CORRECT**

```
>>> (1,)
(1)
```

- **WRONG**

```
>>> (1)
1
```

Empty Tuple, and Accessing Tuples

- An **empty tuple** is represented by a **set of empty parentheses, ()**.
- The elements of tuples are accessed the same as lists, with square brackets,
nums = (10, 20, 30)
student = ('John Smith', 48, 'Computer Science', 3.42)

```
>>> nums[0]
```

```
10
```

```
>>> student[0]
```

```
'John Smith'
```

- **Any attempt to alter a tuple is invalid.** Thus, delete, update, insert and append operations are not defined on tuples.

Sequences

- A **sequence** in Python is a **linearly-ordered set of elements accessed by index number**.
- Lists, tuples and strings are all sequences. **Strings, like tuples, are immutable, therefore they cannot be altered.**

Operation		String s = 'hello' w = '!'	Tuple s = (1,2,3,4) w = (5,6)	List s = [1,2,3,4] w = [5,6]
Length	len(s)	5	4	4
Select	s[0]	'h'	1	1
Slice	s[1:4] s[1:]	'ell' 'ello'	(2, 3, 4) (2, 3, 4)	[2, 3, 4] [2, 3, 4]
Count	s.count('e')	1	--	--
	s.count(4)	--	1	1
Index	s.index('e')	1	--	--
	s.index(3)	--	2	2
Membership	'h' in s	True	False	False
Concatenation	s + w	'hello!'	(1, 2, 3, 4, 5, 6)	[1, 2, 3, 4, 5, 6]
Minimum Value	min(s)	'e'	1	1
Maximum Value	max(s)	'o'	4	4
Sum	sum(s)	n/a	10	10

Let's Try It

From the Python Shell, enter the following and observe the results.

```
>>> s = 'coconut'  
>>> s[4:7]  
???
```

```
>>> s.count('o')  
???
```

```
>>> s.index('o')  
???
```

```
>>> s + ' juice'  
???
```

```
>>> s = (10, 30, 20, 10)  
>>> s[1:3]  
???
```

```
>>> s.count(10)  
???
```

```
>>> s.index(10)  
???
```

```
>>> s + (40, 50)  
???
```

```
>>> s = [10, 30 ,20, 10]  
>>> s[1:3]  
???
```

```
>>> s.count(10)  
???
```

```
>>> s.index(10)  
???
```

```
>>> s + [40, 50]  
???
```

Nested Lists

- **Lists and tuples can contain elements of any type,** including other sequences.
- **Thus, lists and tuples can be nested** to create arbitrarily complex data structures

```
class_grades = [ [85, 91, 89], [78, 81, 86], [62, 75, 77], ...]
```

This list stores three exam grades for each student.

```
class_grades[0] equals [85, 91, 89]
```

```
class_grades[1] equals [78, 81, 86]
```

To access the first exam grade of the first student in the list,

```
student1_grades = class_grades[0] → [85, 91, 89]
```

```
student1_exam1 = student1_grades[0] → 85
```

OR

```
class_grades[0][0] → 85
```

To calculate the average on the first exam for group of students, a while loop can be constructed that iterates over the first grade of each student's list of grades,

```
sum = 0
k = 0

while k < len(class_grades):
    sum = sum + class_grades[k][0]
    k = k + 1

average_exam1 = sum / float(len(grades))
```


To produce a new list names `exam_avgs` containing the exam average for each student in the class,

```
exam_avgs = []
k = 0

while k < len(class_grades):
    avg = (class_grades[k][0] + \
           class_grades[k][1] + \
           class_grades[k][2]) / 3.0

    exam_avgs.append(avg)
    k = k + 1
```

Let's Try It

From the Python Shell, enter the following and observe the results.

```
>>> lst = [[1, 2 ,3], [4, 5, 6], [7, 8, 9]]
>>> lst[0]
???
```

```
>>> lst[0][1]
???
```

```
>>> for k in lst:
    print k
```

```
???
```

```
>>> for k in lst[0]:
    print k
```

Storage of Objects

```
x    =  'myname'
```

```
y    =  'myname'
```

How many copies of the string in memory?


```
x == y    (The values of the variables is same)
```

```
x is y?    (it is the same object in memory)
```

Storage of List Objects

1x = [1, 2, 3]

1y = [1, 2, 3]




Storage of List Objects

```
lx = [1, 2, 3]
```

```
ly = lx          (Aliasing)
```

```
lz = lx[:]       (Cloning)
```



Passing Lists as Parameters

```
def listfun (lpar):
```


```
    lpar[1]=100
```

```
    return lpar
```


```
lx = [1, 2, 3]
```

```
ly = listfun(lx)
```

```
print (ly)
```



```
print (lx)
```



Pure Functions

Function Side Effects: Changes to variable values in the calling program as a result of function call


A pure function has no side effects!

(Functions should preferably not have side effects but there are exceptions)

Pure Function?

```
def listfun (lpar):  
    lpar[1]=100  
    return lpar
```


```
lx = [1, 2, 3]  
ly = listfun(lx)  
print (ly)  
print (lx)
```



Pure Function?

```
def listfun (lpar):  
    loclist = lpar(:)  
    loclist[1]=100  
    return loclist
```

```
lx = [1, 2, 3]  
ly = listfun(lx)  
print (ly)  
print (lx)
```



Self-Test Questions

1. For `nums = [10, 30, 20, 40]`, what does the following for loop output?

```
for k in nums:  
    print(k)
```

- | | | |
|--------|--------|--------|
| (a) 10 | (b) 10 | (c) 10 |
| 20 | 30 | 30 |
| 30 | 20 | 20 |
| 40 | 40 | |

2. For `nums = [10, 30, 20, 40]`, what does the following for loop output?

```
for k in range(1, 4):  
    print (nums[k])
```

- | | | |
|--------|--------|--------|
| (a) 10 | (b) 30 | (c) 10 |
| 30 | 20 | 30 |
| 20 | 40 | 20 |
| | | 40 |

3. For `fruit = 'strawberry'`, what does the following for loop output?

```
for k in range(0, len(fruit), 2):  
    print (fruit[k])
```

- (a) srwer (b) tabry

4. For `nums = [12, 4, 11, 23, 18, 41, 27]`, what is the value of `k` when the while loop terminates?

```
k = 0  
while k < len(nums) and nums[k] != 18:  
    k = k + 1
```

- (a) 3 (b) 4 (c) 5

ANSWERS: 1. (a)

Self-Test Questions

1. For `nums = [10, 30, 20, 40]`, what does the following for loop output?

```
for k in nums:  
    print(k)
```

- | | | |
|--------|--------|--------|
| (a) 10 | (b) 10 | (c) 10 |
| 20 | 30 | 30 |
| 30 | 20 | 20 |
| 40 | 40 | |

2. For `nums = [10, 30, 20, 40]`, what does the following for loop output?

```
for k in range(1, 4):  
    print (nums[k])
```

- | | | |
|--------|--------|--------|
| (a) 10 | (b) 30 | (c) 10 |
| 30 | 20 | 30 |
| 20 | 40 | 20 |
| | | 40 |

3. For `fruit = 'strawberry'`, what does the following for loop output?

```
for k in range(0, len(fruit), 2):  
    print (fruit[k])
```

- | | |
|-----------|-----------|
| (a) srwer | (b) tabry |
|-----------|-----------|

4. For `nums = [12, 4, 11, 23, 18, 41, 27]`, what is the value of `k` when the while loop terminates?

```
k = 0  
while k < len(nums) and nums[k] != 18:  
    k = k + 1
```

- | | | |
|-------|-------|-------|
| (a) 3 | (b) 4 | (c) 5 |
|-------|-------|-------|

ANSWERS: 1. (b)

UNIVERSITY of
HOUSTON

DIVISION OF RESEARCH
HEWLETT PACKARD ENTERPRISE DATA SCIENCE INSTITUTE

Self-Test Questions

1. For `nums = [10, 30, 20, 40]`, what does the following for loop output?

```
for k in nums:  
    print(k)
```

- | | | |
|--------|--------|--------|
| (a) 10 | (b) 10 | (c) 10 |
| 20 | 30 | 30 |
| 30 | 20 | 20 |
| 40 | 40 | |

2. For `nums = [10, 30, 20, 40]`, what does the following for loop output?

```
for k in range(1, 4):  
    print (nums[k])
```

- | | | |
|--------|--------|--------|
| (a) 10 | (b) 30 | (c) 10 |
| 30 | 20 | 30 |
| 20 | 40 | 20 |
| | | 40 |

3. For `fruit = 'strawberry'`, what does the following for loop output?

```
for k in range(0, len(fruit), 2):  
    print (fruit[k])
```

- | | |
|-----------|-----------|
| (a) srwer | (b) tabry |
|-----------|-----------|

4. For `nums = [12, 4, 11, 23, 18, 41, 27]`, what is the value of `k` when the while loop terminates?

```
k = 0  
while k < len(nums) and nums[k] != 18:  
    k = k + 1
```

- | | | |
|-------|-------|-------|
| (a) 3 | (b) 4 | (c) 5 |
|-------|-------|-------|

ANSWERS: 1. (b), 2. (b),

UNIVERSITY of
HOUSTON

DIVISION OF RESEARCH
HEWLETT PACKARD ENTERPRISE DATA SCIENCE INSTITUTE

Self-Test Questions

1. For `nums = [10, 30, 20, 40]`, what does the following for loop output?

```
for k in nums:  
    print(k)
```

- | | | |
|--------|--------|--------|
| (a) 10 | (b) 10 | (c) 10 |
| 20 | 30 | 30 |
| 30 | 20 | 20 |
| 40 | 40 | |

2. For `nums = [10, 30, 20, 40]`, what does the following for loop output?

```
for k in range(1, 4):  
    print (nums[k])
```

- | | | |
|--------|--------|--------|
| (a) 10 | (b) 30 | (c) 10 |
| 30 | 20 | 30 |
| 20 | 40 | 20 |
| | | 40 |

3. For `fruit = 'strawberry'`, what does the following for loop output?

```
for k in range(0, len(fruit), 2):  
    print (fruit[k])
```

- | | |
|-----------|-----------|
| (a) srwer | (b) tabry |
|-----------|-----------|

4. For `nums = [12, 4, 11, 23, 18, 41, 27]`, what is the value of `k` when the while loop terminates?

```
k = 0  
while k < len(nums) and nums[k] != 18:  
    k = k + 1
```

- | | | |
|-------|-------|-------|
| (a) 3 | (b) 4 | (c) 5 |
|-------|-------|-------|

ANSWERS: 1. (b), 2. (b), 3. (a), 4. b

UNIVERSITY of
HOUSTON

DIVISION OF RESEARCH
HEWLETT PACKARD ENTERPRISE DATA SCIENCE INSTITUTE

Self-Test Questions

1. For `nums = [10, 30, 20, 40]`, what does the following for loop output?

```
for k in nums:  
    print(k)
```

- | | | |
|--------|--------|--------|
| (a) 10 | (b) 10 | (c) 10 |
| 20 | 30 | 30 |
| 30 | 20 | 20 |
| 40 | 40 | |

2. For `nums = [10, 30, 20, 40]`, what does the following for loop output?

```
for k in range(1, 4):  
    print (nums[k])
```

- | | | |
|--------|--------|--------|
| (a) 10 | (b) 30 | (c) 10 |
| 30 | 20 | 30 |
| 20 | 40 | 20 |
| | | 40 |

3. For `fruit = 'strawberry'`, what does the following for loop output?

```
for k in range(0, len(fruit), 2):  
    print (fruit[k])
```

- | | |
|-----------|-----------|
| (a) srwer | (b) tabry |
|-----------|-----------|

4. For `nums = [12, 4, 11, 23, 18, 41, 27]`, what is the value of `k` when the while loop terminates?

```
k = 0  
while k < len(nums) and nums[k] != 18:  
    k = k + 1
```

- | | | |
|-------|-------|-------|
| (a) 3 | (b) 4 | (c) 5 |
|-------|-------|-------|

ANSWERS: 1. (b), 2. (b), 3. (a), 4. (b)

UNIVERSITY of
HOUSTON

DIVISION OF RESEARCH
HEWLETT PACKARD ENTERPRISE DATA SCIENCE INSTITUTE

List Comprehensions

- The range function allows for the generation of sequences of integers in fixed increments.
- **List comprehensions** in Python can be used to generate more varied sequences.

List Comprehensions

Example List Comprehensions	Resulting List
(a) <code>[x**2 for x in [1, 2, 3]]</code>	<code>[1, 4, 9]</code>
(b) <code>[x**2 for x in range(5)]</code>	<code>[0, 1, 4, 9, 16]</code>
(c) <code>nums = [-1, 1, -2, 2, -3, 3, -4, 4]</code> <code>[x for x in nums if x >= 0]</code>	<code>[1, 2, 3, 4]</code>
(d) <code>[ord(ch) for ch in 'Hello']</code>	<code>[72, 101, 108, 108, 111]</code>
(e) <code>vowels = ('a', 'e', 'i', 'o', 'u')</code> <code>w = 'Hello'</code> <code>[ch for ch in w if ch in vowels]</code>	<code>['e', 'o']</code>

Let's Try It

From the Python Shell, enter the following and observe the results.

```
>>> temperatures = [88, 94, 97, 89, 101, 98, 102, 95, 100]
>>> [t for t in temperatures if t >= 100]
???
```

```
>>> [(t - 32) * 5/9.0 for t in temps]
???
```

Classwork

- Write a program to take a number K as input, reads K names (one at a time), store them in a list, and then print them in reverse (prefer not to use the reverse method)