Date:12.09.2022

Final Year B. Tech., Sem VII 2021-22

High Performance Computing Lab

Assignment submission

PRN No: 2019BTECS00064

Full name: Kunal Santosh Kadam

Batch: B3

Assignment: 3

Title of assignment: Study and Implementation of schedule, nowait, reduction, ordered and collapse clauses

1. Analyse and implement a Parallel code for below program using openMP

```
// C Program to find the minimum scalar product of two vectors (dot
product)
#include<stdio.h>
int sort(int arr[], int n)
{
        int i, j;
        for (i = 0; i < n-1; i++)
                for (j = 0; j < n-i-1; j++)
                        if (arr[j] > arr[j+1])
                        {
                                int temp = arr[j];
                                arr[j] = arr[j+1];
                                arr[j+1] = temp;
```

```
                        }
}

int sort_des(int arr[], int n)
{
        int i,j;
        for (i = 0; i < n; ++i)
        {
                for (j = i + 1; j < n; ++j)
                {
                        if (arr[i] < arr[j])
                        {
                                int a = arr[i];
                                arr[i] = arr[j];
                                arr[j] = a;
                        }
                }
        }
}

int main()
{
        //fill the code;
        int n;
        scanf("%d",&n);
        int arr1[n], arr2[n];
        int i;
        for(i = 0; i < n ; i++)
        {
                scanf("%d",&arr1[i]);
        }
        for(i = 0; i < n ; i++)
        {
                scanf("%d",&arr2[i]);
        }
```

```
        sort(arr1, n);
        sort_des(arr2, n);
        int sum = 0;
        for(i = 0; i < n ; i++)
        {
                sum = sum + (arr1[i] * arr2[i]);
        }
        printf("%d",sum);
        return 0;
}
```

Ans:

Code:

```
// C Program to find the minimum scalar product of two vectors (dot
product)
#include<bits/stdc++.h>
#include <omp.h>

using namespace std;

int sort(int arr[], int n)
{
        int i, j;
        #pragma omp parallel shared(arr) private(j)
        #pragma omp for schedule(dynamic)
        for (i = 0; i < n-1; i++)
                for (j = 0; j < n-i-1; j++)
                        if (arr[j] > arr[j+1])
                        {
                                int temp = arr[j];
                                arr[j] = arr[j+1];
                                arr[j+1] = temp;
                        }
```

```
}

int sort_des(int arr[], int n)
{
	int i,j;
	#pragma omp parallel shared(arr) private(j)
	#pragma omp for schedule(dynamic)
	for (i = 0; i < n; ++i)
	{
		for (j = i + 1; j < n; ++j)
		{
			if (arr[i] < arr[j])
			{
				int a = arr[i];
				arr[i] = arr[j];
				arr[j] = a;
			}
		}
	}
}

int main()
{
	//fill the code;
	int i,tid,n,psum;
	int threads = 4;
	cout<<"Enter Size of Array: ";
	cin>>n;
	int arr1[n], arr2[n];
	cout<<"Enter Elements of First Array:\n";
	for(i = 0; i < n ; i++)
	{
		cin>>arr1[i];
	}
	cout<<"Enter Elements of Second Array:\n";
```

```
        for(i = 0; i < n ; i++)
        {
                cin>>arr2[i];
        }
        sort(arr1, n);
        sort_des(arr2, n);
        int sum = 0;
        #pragma omp parallel private(i,tid,psum) num_threads(threads)
        {
                psum=0;
                tid = omp_get_thread_num();
                #pragma omp for reduction(+:sum)
                for(int i=0; i<n; i++)
                {
                        sum += arr1[i] * arr2[i];
                        psum+=sum;
                }
                printf("Thread %d partial sum = %d\n",tid,psum);
        }
        cout<<"Sum: "<<sum<<endl;

        return 0;
}
```

Output:


G:\Kunal\Sem-7\HPC Assignments\Assignment - 3\Q1.exe
Enter Size of Array: 8
Enter Elements of First Array:
1
2
4
6
3
7
4
8
Enter Elements of Second Array:
9
4
7
7
0
5
4
6
Thread 3 partial sum = 56
Thread 0 partial sum = 32
Thread 1 partial sum = 66
Thread 2 partial sum = 64
Sum: 140

Process exited after 33.17 seconds with return value 0
Press any key to continue . . .

2. Write OpenMP code for two 2D Matrix addition, vary the size of your matrices from 250, 500, 750, 1000, and 2000 and measure the runtime with one thread (Use functions in C in calculate the execution time or use GPROF)
    i. For each matrix size, change the number of threads from 2,4,8., and plot the speedup versus the number of threads.
    ii. Explain whether or not the scaling behaviour is as expected.

Ans:

Code:

```
#include <bits/stdc++.h>
#include <omp.h>

using namespace std;

int main()
{

        int tid, nthreads , i, j;
        int n=100;
        while(1){
                if(n==500)
                        break;
                else
                        n+=100;
                nthreads=4;
                int a[n][n], b[n][n], c[n][n];

                int index = 0;

                for (i = 0; i < n; i++)
                {

                        for (j = 0; j < n; j++)
```

```
                {
                        a[i][j] = b[i][j] = (i+j);
                }
        }

        printf("Time Required to do Matrix Multiplication of size
%d\nUsing Threads: %d",n,nthreads);

        double time = omp_get_wtime();

        #pragma omp parallel shared(a, b, c, nthreads) private(tid, i,
j) num_threads(nthreads)
        {
                # pragma omp parallel for
                for (int i = 0; i < n; i++)
                {
                        for (int j = 0; j < n; j++)
                        {
                                c[i][j] = a[i][j] + b[i][j];
                        }
                }
        }

        printf("\nDone In %f Seconds\n\n", omp_get_wtime() -
time);

    }
    return 0;
}
```

Output:


G:\Kunal\Sem-7\HPC Assignments\Assignment - 3\Q2.exe
Time Required to do Matrix Multiplication of size 200
Using Threads: 2
Done In 0.002000 Seconds
Time Required to do Matrix Multiplication of size 300
Using Threads: 2
Done In 0.001000 Seconds
Time Required to do Matrix Multiplication of size 400
Using Threads: 2
Done In 0.005000 Seconds

Process exited after 6.986 seconds with return value 3221225725
Press any key to continue . . .


G:\Kunal\Sem-7\HPC Assignments\Assignment - 3\Q2.exe
Time Required to do Matrix Multiplication of size 200
Using Threads: 4
Done In 0.003000 Seconds
Time Required to do Matrix Multiplication of size 300
Using Threads: 4
Done In 0.001000 Seconds
Time Required to do Matrix Multiplication of size 400
Using Threads: 4
Done In 0.004000 Seconds

Process exited after 6.82 seconds with return value 3221225725
Press any key to continue . . .

3. For 1D Vector (size=200) and scalar addition, Write a OpenMP code with the following:
    i. Use STATIC schedule and set the loop iteration chunk size to various sizes when changing the size of your matrix. Analyze the speedup.
    ii. Use DYNAMIC schedule and set the loop iteration chunk size to various sizes when changing the size of your matrix. Analyze the speedup.
    iii. Demonstrate the use of nowait clause

Ans:

Use of Static Schedule

Code:

```
#include <omp.h>
#include <stdio.h>
#include <stdlib.h>
#include <time.h>

int main(){
   int n = 200, i ,j=99;

   int arr1[n], answer[n];

        for(i = 0; i < n; i++){
      arr1[i] = rand()%100;
   }

   double time = omp_get_wtime();
   #pragma omp parallel for schedule(static,20) shared(arr1, answer,j)
private(i)

        for(i = 0; i < n; i++)
   {
```

```
        answer[i] = arr1[i] + j;
    }

    printf("\nDone In %f Seconds\n\n", omp_get_wtime() - time);

    printf("\nArray 1: \n");
    for(i = 0; i < n; i++){
        printf("\t %d", arr1[i]);
    }

    printf("\nAnswer: \n");
    for(i = 0; i < n; i++){
        printf("\t %d", answer[i]);
    }
    return 0;
}
```

Output:





Use of Dynamic Schedule

Code:

```
#include <omp.h>
#include <stdio.h>
#include <stdlib.h>
#include <time.h>

int main(){
   int n = 200, i ,j=99;

         int arr1[n], answer[n];

         for(i = 0; i < n; i++)
         {
      arr1[i] = rand()%100;
   }
```

```
   double time = omp_get_wtime();

        #pragma omp parallel for schedule(dynamic,20) shared(arr1,
answer,j) private(i)
   for(i = 0; i < n; i++)
   {
      answer[i] = arr1[i] + j;
   }

   printf("\nDone In %f Seconds\n\n", omp_get_wtime() - time);

        printf("\nArray 1: \n");
   for(i = 0; i < n; i++)
        {
      printf("\t %d", arr1[i]);
   }

        printf("\nAnswer: \n");
   for(i = 0; i < n; i++)
        {
      printf("\t %d", answer[i]);
   }
   return 0;
}
```

Output:





Use of Nowait Clause

Code:

```
#include <omp.h>
#include <stdio.h>
#include <stdlib.h>
#include <time.h>

int main()
```

```
{
   int n = 200, i ,j=99;

   int arr1[n], answer[n];

         for(i = 0; i < n; i++)
         {
      arr1[i] = rand()%100;
   }

   double time = omp_get_wtime();

         #pragma omp parallel
   {
            #pragma omp for nowait
            for(i = 0; i < n; i++)
            {
               answer[i] = arr1[i] + j;
            }
   }

   printf("\nDone In %f Seconds\n\n", omp_get_wtime() - time);

   printf("\nArray 1: \n");
   for(i = 0; i < n; i++){
      printf("\t %d", arr1[i]);
   }

   printf("\nAnswer: \n");
   for(i = 0; i < n; i++){
      printf("\t %d", answer[i]);
   }
   return 0;
}
```

Output:


G:\Kunal\Sem-7\HPC Assignments\Assignment - 3\Q3C.exe
Done In 0.000000 Seconds
Array 1:
41 67 34 0 69 24 78 58 62 64 5 45 81 27
61 91 95 42 27 36 91 4 2 53 92 82 21 16 18
95 47 26 71 38 69 12 67 99 35 94 3 11 22 33
73 64 41 11 53 68 47 44 62 57 37 59 23 41 29
78 16 35 90 42 88 6 40 42 64 48 46 5 90 29
70 50 6 1 93 48 29 23 84 54 56 40 66 76 31
8 44 39 26 23 37 38 18 82 29 41 33 15 39 58
4 30 77 6 73 86 21 45 24 72 70 29 77 73 97
12 86 90 61 36 55 67 55 74 31 52 50 50 41 24
66 30 7 91 7 37 57 87 53 83 45 9 9 58 21
88 22 46 6 30 13 68 0 91 62 55 10 59 24 37
48 83 95 41 2 50 91 36 74 20 96 21 48 99 68
84 81 34 53 99 18 38 0 88 27 67 28 93 48 83
7 21 10 17 13 14


G:\Kunal\Sem-7\HPC Assignments\Assignment - 3\Q3C.exe
Answer:
140 166 133 99 168 123 177 157 161 163 104 144 180 126
160 190 194 141 126 135 190 103 101 152 191 181 120 115 117
194 146 125 170 137 168 111 166 198 134 193 102 110 121 132
172 163 140 110 152 167 146 143 161 156 136 158 122 140 128
177 115 134 189 141 187 105 139 141 163 147 145 104 189 128
169 149 105 100 192 147 128 122 183 153 155 139 165 175 130
107 143 138 125 122 136 137 117 181 128 140 132 114 138 157
103 129 176 105 172 185 120 144 123 171 169 128 176 172 196
111 185 189 160 135 154 166 154 173 130 151 149 149 140 123
165 129 106 190 106 136 156 186 152 182 144 108 108 157 120
187 121 145 105 129 112 167 99 190 161 154 109 158 123 136
147 182 194 140 101 149 190 135 173 119 195 120 147 198 167
183 180 133 152 198 117 137 99 187 126 166 127 192 147 182
106 120 109 116 112 113
Process exited after 3.023 seconds with return value 0
Press any key to continue . . .