

1. NAS/SAN Storage

1.1

NAS/SAN Storage System with RAID 6 configuration shall be used to record video streams based on the configuration assigned by administrator. Workstations & Servers within the LAN should be able to access the recorded video streams. The Storage device shall support simultaneous playback and recording at full duplex operation.

1.2

It shall provide a high-quality recording storage and playback of images. It shall support integration with LAN to provide Centralized Management and shall operate on Windows/Linux/UNIX OS. Support of user management for security level control and authentication is required. These Storage devices shall have the following features and specifications:

Parameter	Proposed Specifications
Controller	Dual Active-Active Controllers in active failover mode with no single point of failure
Onboard Cache	128 GB Mirrored and scalable to 256 GB
Storage Disk	7.2K/10K rpm SAS/NL-SAS disk for 30 days
Host Interface	At least Four 10G Ethernet and Four 32G FC Ports
HDD Type Support (Any one)	SAS, SSD, NL-SAS
Inbuilt RAID Support	RAID – Double Disk Failure Support / RAID-6
Network Transport Protocols	TCP/IP
Server/Storage Protocol Support (As per solution) (Any one)	CIFS, NFS, iSCSI, FCP, HTTP/HTTPS, FTP, NTP, SNMP, SMTP, DHCP and DNS
Operating System (OS)	Single unified built-in Storage OEM OS for all the protocols, compatible with MS Windows/Linux/Unix
Power Supply	Hot Pluggable Redundant Power Supply
Storage File Management Software	Inbuilt CLI & Web-Based GUI administration management software
Mounting Arrangement	Rack mountable
Scalability	The storage offered shall be scalable to add additional 50% usable capacity at site within the same storage.
Storage System should be provided with	No other upgrades should be required for desired scalability except for Disk Array enclosures and Disk Drives as required. Once data is stored in Storage, no client/operator should be able to delete or modify data.