

UniSwitch US-16M

16-Port Managed L2 Switch

SKU: US-16M



PRODUCT OVERVIEW

The Indio Networks 16-Port Managed switch is a Layer-2 cloud managed switch equipped with 16 gigabit RJ-45 ports and 2 SFP slots.

The switch is designed to provide high throughput in demanding situations and forms a backbone for the edge devices. It is designed exclusively for networking needs of enterprise and carrier grade networks. US-16M offers abundant L2 management features needed for supporting growing management and security needs for modern enterprises. It comes with 8 IEEE RJ-45 compliant ports and 2 SFP gigabit uplink ports.



**36 Gbps
Switching**



**Layer 2+
Managed**



**Cloud
Management**



**Open Switching
Technology**



**3-Year
Warranty**

KEY FEATURES

- | | |
|--------------------------------|-----------------------------|
| ✓ 16 x Gigabit Ethernet Ports | ✓ L2+ Managed Switching |
| ✓ 2 x Gigabit SFP Uplink Ports | ✓ Advanced VLAN Support |
| ✓ Advanced QoS | ✓ Enterprise Grade Security |
| ✓ Multicast Management | ✓ Compact Design |
| ✓ Intelligent Diagnostics | ✓ High Switching Capacity |
| ✓ Flexible Deployments | ✓ 20W Power Consumption |

USE CASES

- | | |
|---------------------|-----------------------|
| ✓ Corporate Offices | ✓ IP Surveillance |
| ✓ Campus Networks | ✓ Government Projects |

SWITCH SPECIFICATIONS

Interface Configuration	
Ethernet Ports	Port 1-16, support 10/100/1000 Base-T(Tx), auto-sensing, full/half duplex
	MDI/MDI-X self-adaption
Fixed Ports	16 x 10/100/1000 Mbps RJ-45 ports
	2 x 10/100/1000 Mbps SFP ports (Optical)
	1 x RJ-45 Console Port
Optical Ports	2 SFP Gigabit Uplink Ports (single mode/multi-mode) No Optical module included
Network Media	10Base-T: UTP category 3, 4, 5 RJ-45 cable
	100Base-TX / 1000Base-T: UTP category 5, 5E or above cable
Optical Media	Multi-mode: 850nm / 0-550m,
	Single mode: 1310nm / 0-40km, 1550nm / 0-120km
Ports	16 x RJ-45 10/100/1000 Kbps ports
Switch Configuration	
Switching Capacity	36 Gbps
Packet Forwarding Rate	41.7 Mbps
MAC Address Table	8K
Packet Buffer	4.1 MB
Jumbo Frame	15 KB
LED Indicators	Power: PWR (Yellow), System: SYS(Yellow), Network: Link (Yellow) (Green), Fiber Port: (Green)
Reset Switch	Yes, Factory Reset
Fans	Included (3 internal)
Network Management Features	
Quality of Service	802.1p CoS / DSCP Priority
	8 priority queues
	Queue Scheduling: SP, WRR, SP+WRR
	Voice VLAN
	Port/Flow-based Rate Limiting
L2 Features	IGMP Snooping v1/v2/v3
	MLD v1/v2 Snooping
	802.3ad LACP

	Spanning Tree STP/RSTP/MSTP
	EAPS Ring Network Protocol
	Port Isolation
	BPDU Filtering/Guard
	LLDP
	802.3x Flow Control
	Loop back Detection
VLAN	Support 4K VLAN
	IEEE 802.1q, Management VLAN
Access Control List	L2-L4 package filtering based on source and destination MAC address, IP, TCP/UDP ports, DSCP, protocol and VLAN ID
Security	256 ACL Groups
	ACL on IP or MAC
	4 different priorities per port
	802.1x Port-based Authentication
	RADIUS support
	Port Isolation
Management	Web-based GUI and CLI management
	SNMP v2c / v3
	RMON (1,2,3,9 groups)
	DHCP / BOOTP client, DHCP Snooping
	DHCP Option-82
	CPU Monitoring
	Port Mirroring
	SNTP – Time Setting
	Firmware Upgrade – TFTP / Web
	Syslog
	Event logs (local and remote)
Supported Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1x, IEEE 802.1p, IEEE 802.3af, IEEE 802.3at

HARDWARE SPECIFICATIONS

Power Supply	
Ports	Port 1 – 16
Power Supply Pin	1 / 2 (+) 3 / 6 (-)
Power Consumption	30W
Power Supply Specification	100 – 240V AC, 50/60 Hz, 5 A

Physical & Environmental	
Form Factor	1-U Rackmount
Dimensions (mm)	440 × 290 × 45 mm
Weight	≤ 3600 g
Operating Temp	-10°C to 55°C (Indoor)
Storage Temp	-40°C to 70°C
Humidity	5% – 95% non-condensing
Ingress Protection	IP40 (Indoor)
Mounting	1-U Rackmount

REGULATORY & CERTIFICATIONS

Certifications	CE / RoHS
IPv6	IPv6 Ready
TEC/MTCTE	Certified
Trusted Telecom	Listed
OpenLAN Switching	Certified
EN-60950-1 (Safety)	Certified

ORDERING INFORMATION

Part Numbers	
US-16M	16-Port, Managed Switch with AC port cord
Optical Module is not included	

IN THE BOX

- 1× US-16M Switch
- 1× Power Cable
- 1× Quick Start Guide
- 1× Warranty card

WARRANTY & SUPPORT

Hardware Warranty	3 Years limited hardware warranty
Firmware Support	Active firmware releases (Indio builds)
RMA Process	Contact support@indionetworks.com
Support Email	support@indionetworks.com
Documentation	www.indionetworks.com/docs

COMPANY INFORMATION

Company Name	Indio Networks Private Limited
Address	C-410, Teerth Technospace IT Park, Baner, Pune – 411045, India
Phone (Sales)	+91-20-6715-7377 / +91-86980-07222
Email (Sales)	sales@indionetworks.com

For technical specifications, datasheets, and partner pricing, contact: sales@indionetworks.com
Specifications subject to change without notice. All rights reserved.