

UniSwitch US-24M

24-Port Managed L2 Switch

SKU: US-24M



PRODUCT OVERVIEW

The Indio Networks 24-Port Managed Switch 24M is a 24 port Gigabit cloud managed network switch, with 24 port Gigabit self-adaptive network port, 2 or 4 SFP gigabit uplink ports. It is designed for enterprise networks which need high performance and reliable switch for connecting the clients together.

The switch comes with 2/4 SFP ports that can be used for connecting to the fiber network along with two additional Gigabit LAN port for uplink. These ports provide easy stacking options to the network administrators.



**56 Gbps
Switching**



**Layer 2 Managed
Switch**



**Cloud
Management**



**Open Switching
Technology**



**3-Year
Warranty**

KEY FEATURES

- | | |
|----------------------------------|-----------------------------|
| ✓ 24 x Gigabit Ethernet Ports | ✓ L2+ Managed Switching |
| ✓ 2-4 x Gigabit SFP Uplink Ports | ✓ Advanced VLAN Support |
| ✓ 20W Power Consumption | ✓ Enterprise Grade Security |
| ✓ Advanced QoS | ✓ Compact Design |
| ✓ Multicast Management | ✓ High Switching Capacity |
| ✓ Intelligent Diagnostics | ✓ Flexible Deployments |

USE CASES

- | | |
|---------------------|-----------------------|
| ✓ Corporate Offices | ✓ IP Surveillance |
| ✓ Campus Networks | ✓ Government Projects |

SWITCH SPECIFICATIONS

Interface Configuration	
Ethernet Ports	Port 1-24, support 10/100/1000 Base-T(Tx), auto-sensing, full/half duplex MDI/MDI-X self-adaption
Fixed Ports	24 x 10/100/1000 Mbps RJ-45 ports
	2 - 4 x 10/100/1000 Mbps SFP ports (Optical)
	1 x RJ-45 Console Port
Optical Ports	2/4 SFP Gigabit Uplink Ports (single mode/multi-mode) No Optical module included
Network Media	10Base-T: UTP category 3, 4, 5 RJ-45 cable
	100Base-TX / 1000Base-T: UTP category 5, 5E or above cable
Optical Media	Multi-mode: 850nm / 0-550m, Single mode: 1310nm / 0-40km, 1550nm / 0-120km
Ports	24 x RJ-45 10/100/1000 kbps ports
Switch Configuration	
Switching Capacity	56 Gbps
Packet Forwarding Rate	41.7 Mbps
MAC Address Table	8K
Packet Buffer	4.1 MB
Jumbo Frame	15 KB
LED Indicators	Power: PWR (Yellow), System: SYS(Yellow), Network: Link (Yellow), (Green), Fiber Port: (Green)
Reset Switch	Yes, Factory Reset
Fans	Included (3 internal)
Network Management Features	
Quality of Service	802.1p CoS / DSCP Priority
	8 priority queues
	Queue Scheduling: SP, WRR, SP+WRR
	Voice VLAN
	Port/Flow-based Rate Limiting
L2 Features	IGMP Snooping v1/v2/v3
	MLD v1/v2 Snooping
	802.3ad LACP

	Spanning Tree STP/RSTP/MSTP
	EAPS Ring Network Protocol
	Port Isolation
	BPDU Filtering/Guard
	LLDP
	802.3x Flow Control
	Loop back Detection
VLAN	Support 4K VLAN
	IEEE 802.1q, Management VLAN
Access Control List	L2-L4 package filtering based on source and destination MAC address, IP, TCP/UDP ports, DSCP, protocol and VLAN ID
Security	256 ACL Groups
	ACL on IP or MAC
	4 different priorities per port
	802.1x Port-based Authentication
	RADIUS support
	Port Isolation
Management	Web-based GUI and CLI management
	SNMP v2c / v3
	RMON (1,2,3,9 groups)
	DHCP / BOOTP client, DHCP Snooping
	DHCP Option-82
	CPU Monitoring
	Port Mirroring
	SNTP – Time Setting
	Firmware Upgrade – TFTP / Web
	Syslog
	Event logs (local and remote)
Supported Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1x, IEEE 802.1p, IEEE 802.3af, IEEE 802.3at

HARDWARE SPECIFICATIONS

Power Supply	
Power Supply Pin	1 / 2 (+) 3 / 6 (-)
Power Consumption	30W
Power Supply Specification	100 – 240V AC, 50/60 Hz, 5 A

Physical & Environmental	
Form Factor	1-U Rackmount
Dimensions (mm)	440 × 290 × 45 mm
Weight	≤ 4700 g
Operating Temp	-10°C to 55°C (Indoor)
Storage Temp	-40°C to 70°C
Humidity	5% – 95% non-condensing
Ingress Protection	IP40 (Indoor)
Mounting	1-U Rackmount

REGULATORY & CERTIFICATIONS

Certifications	CE / RoHS
IPv6	IPv6 Ready
TEC/MTCTE	Certified
Trusted Telecom	Listed
OpenLAN Switching	Certified
EN-60950-1 (Safety)	Certified

ORDERING INFORMATION

Part Numbers	
US-24M	24-Port, Managed Switch with power cord
Optical Module is not included	

IN THE BOX

- 1× US-24M Switch
- 1× Power Cable
- 1× Quick Start Guide
- 1× Warranty card

WARRANTY & SUPPORT

Hardware Warranty	3 Years limited hardware warranty
Firmware Support	Active firmware releases (Indio builds)
RMA Process	Contact support@indionetworks.com
Support Email	support@indionetworks.com
Documentation	www.indionetworks.com/docs

COMPANY INFORMATION

Company Name	Indio Networks Private Limited
Address	C-410, Teerth Technospace IT Park, Baner, Pune – 411045, India
Phone (Sales)	+91-20-6715-7377 / +91-86980-07222
Email (Sales)	sales@indionetworks.com

For technical specifications, datasheets, and partner pricing, contact: sales@indionetworks.com
Specifications subject to change without notice. All rights reserved.