

UniSwitch US-8MP

8-Port Managed PoE L2+ Switch

SKU: US-8MP



PRODUCT OVERVIEW

The Indio Networks 8-Port Managed PoE Switch is a high-performance Layer 2 switching solution designed for enterprise, SMB, hospitality, campus, surveillance and other demanding network environments. It features 8 Gigabit Ethernet RJ-45 ports with IEEE 802.3af/at PoE+ support and 2 Gigabit SFP uplink ports, enabling reliable connectivity and power delivery to devices such as Wi-Fi access points, IP cameras, IP phones and other PoE-enabled devices.

With a 120W total PoE power budget and up to 30W per PoE port, the switch provides flexible deployment options while reducing the need for separate power infrastructure. Advanced network management capabilities, including 802.1Q VLAN, QoS, STP/RSTP/MSTP, LACP, IGMP Snooping, port mirroring, loopback detection and PoE management, enable efficient traffic management, network segmentation and improved network reliability.

The switch is an ideal choice for organizations looking for a compact, secure and scalable managed switching solution for modern wired and PoE-powered network deployments.



**20 Gbps
Switching**



**120 W Power
Budget**



**Cloud
Management**



**Open Switching
Technology**



**3-Year
Warranty**

KEY FEATURES

- | | |
|-----------------------------------|-----------------------------|
| ✓ 8 x Gigabit Ethernet PoE+ Ports | ✓ L2+ Managed Switching |
| ✓ 2 x Gigabit SFP Uplink Ports | ✓ Advanced VLAN Support |
| ✓ 120W PoE Power Budget | ✓ Enterprise Grade Security |
| ✓ Advanced QoS | ✓ Compact Design |
| ✓ Multicast Management | ✓ High Switching Capacity |
| ✓ Intelligent Diagnostics | ✓ Flexible Deployments |

USE CASES

- ✓ Corporate Offices
- ✓ IP Surveillance
- ✓ Campus Networks
- ✓ Government Projects

SWITCH SPECIFICATIONS

Radio Configuration	
Port Type	8-Port PoE Managed Switch
PoE Ports	8 802.3 at/at PoE ports
PoE Power	120W with 30W per Port
Switching Capacity	20 Gbps
Packet Forwarding Rate	12 Mbps
MAC Address Table	4K
Packet Buffer	1.5 MB
Jumbo Frame	15 KB
Quality of Service	802.1p CoS / DSCP Priority
	8 priority queues
	Queue Scheduling: SP, WRR, SP+WRR
	Voice VLAN
	Port/Flow-based Rate Limiting
L2 Features	IGMP Snooping v1/v2/v3
	MLD v1/v2 Snooping
	802.3ad LACP
	Spanning Tree STP/RSTP/MSTP
	EAPS Ring Network Protocol
	Port Isolation
	BPDU Filtering/Guard
	LLDP
	802.3x Flow Control
	Loop back Detection
VLAN	Support 4K VLAN
	Management VLAN

Access Control List	L2-L4 package filtering based on source and destination MAC address, IP, TCP/UDP ports, DSCP, protocol and VLAN ID
Security	256 ACL Groups
	ACL on IP or MAC
	4 different priorities per port
	802.1x Port-based Authentication
	RADIUS support
Management	Web-based GUI and CLI management
	SNMP v2c / v3
	RMON (1,2,3,9 groups)
	DHCP / BOOTP client, DHCP Snooping
	DHCP Option-82
	CPU Monitoring
	Port Mirroring
	SNTP – Time Setting
	Firmware Upgrade – TFTP / Web
	Syslog
	Event logs (local and remote)
Port Type	Gigabit Ethernet

HARDWARE SPECIFICATIONS

Switch Hardware	
Port Type	Gigabit Ethernet
Switch Type	L2+ Managed Switch
Supported Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1x, IEEE 802.1p, IEEE 802.3af, IEEE 802.3at
Interfaces	8 x 10/100/1000 Mbps RJ-45 ports (all PoE+)
	2 x 10/100/1000 Mbps SFP ports (Fiber)
	1 x RJ-45 Console Port
SFP Ports	2 SFP Gigabit Ports
Network Media	10Base-T: UTP category 3, 4, 5 RJ-45 cable
	100Base-TX / 1000Base-T: UTP category 5, 5E or above cable
Fanless Operation	Yes

Power Supply	
Power Supply Specification	100 – 240V AC, 50/60 Hz
Power Consumption	120W
Physical & Environmental	
Form Factor	Tablemount
Dimensions (mm)	210 × 140 × 45 mm
Weight	≤ 1167 g
Operating Temp	-10°C to 55°C (Indoor)
Storage Temp	-40°C to 70°C
Humidity	5% – 95% non-condensing
Ingress Protection	IP40 (Indoor)
Mounting	Tablemount or Rackmount (with extended ears)

REGULATORY & CERTIFICATIONS

Certifications	CE / RoHS
IPv6	IPv6 Ready
TEC/MTCTE	Certified
Trusted Telecom	Listed
OpenLAN Switching	Certified
EN-60950-1 (Safety)	Certified

ORDERING INFORMATION

Part Numbers	
US-8MP	8-Port, Managed PoE Switch
IN-SW-ER	Extended Ears for rackmount

IN THE BOX

- 1× US-8MP PoE Switch
- 1× Power Cable
- 1× Quick Start Guide
- 1× Warranty card

WARRANTY & SUPPORT

Hardware Warranty	3 Years limited hardware warranty
Firmware Support	Active firmware releases (Indio builds)
RMA Process	Contact support@indionetworks.com
Support Email	support@indionetworks.com
Documentation	www.indionetworks.com/docs

COMPANY INFORMATION

Company Name	Indio Networks Private Limited
Address	C-410, Teerth Technospace IT Park, Baner, Pune – 411045, India
Phone (Sales)	+91-20-6715-7377 / +91-86980-07222
Email (Sales)	sales@indionetworks.com

For technical specifications, datasheets, and partner pricing, contact: sales@indionetworks.com
Specifications subject to change without notice. All rights reserved.