


NAV - I - 4R2S - X

4GE + 2 x 1/10G SFP+ Web Smart Industrial PoE Switch



Product Description

The NAV - I - 4R2S - X series is a Gigabit industrial Ethernet PoE fiber switch designed to meet the needs of industrial fields and systems and to operate stably for long periods in harsh usage environments. It provides 4 Gigabit Ethernet adaptive electrical ports and 2 x 1/10G SFP+ fiber ports, of which all 4 electrical ports support PoE, and every port supports full wire-speed forwarding. The switch offers excellent adaptability to industrial environments (mechanical stability, climate and electromagnetic environment adaptability), IP30 protection, three redundant power inputs, low-power fanless cooling and a simple plug-and-play management model that requires no configuration. It is suitable for intelligent transportation, rail transportation, power, mining, oil, shipping, metallurgy, green energy construction and other industrial scenarios, delivering a cost-effective, stable and reliable communication network.

Key Features

- Full Gigabit Ethernet ports
- 2 x 1/10G SFP+ uplink ports
- IEEE 802.3af/at PoE standards
- Supports 802.1Q VLAN
- Supports port mirroring
- Supports port-based / 802.1p / DSCP priority QoS
- Supports storm control
- Supports STP/RSTP Spanning Tree Protocol; interworks with Huawei/Cisco
- Three redundant 12/24/48 VDC power inputs
- -40 C to 75 C wide operating temperature range
- DIN-rail / wall mounting
- Web-based user interface
- Supports port isolation

Hardware Specifications

Protocol Standards	IEEE 802.3, 802.3i, 802.3u, 802.3x, 802.3af, 802.3at
Ports	4 x 10/100/1000Mbps RJ45 PoE ports + 2 x 1/10Gbps SFP+ ports
Indicator Light	4 x 10/100M Link/Act indicators, 4 x 1000M Link/Act indicators, 2 SFP port indicators (Link), PWR
Power Input	DC input voltage 44-57 VDC, input current 2A (MAX)
Fan Quantity	Fanless
Performance	Store-and-forward support, MAC address table depth 2K
Dimensions	136 x 108 x 38.5 mm
Switching Capacity	12 Gbps
Forwarding Rate	8.928 Mpps

NAV - I - 4R2S - X

4GE + 2 x 1/10G SFP+ Web Smart Industrial PoE Switch

Hardware Specifications - Continued

MAC Address Table	2K
Packet Buffer Memory	1.5 Mb
Installation	DIN-rail / wall mount
Operating Temperature	-40 C to 75 C (-40 F to 167 F)
Storage Temperature	-40 C to 85 C (-40 F to 185 F)
Operating Humidity	10%-90% non-condensing
Storage Humidity	5%-95% non-condensing
Certification (EMS)	IEC/EN 61000-4-2 Level 4, -4-3 Level 4, -4-4 Level 4, -4-5 Level 3, -4-6 Level 3, -4-8 Level 5, -4-9 Level 5, -4-10 Level 5
Packaging Accessories	One NAV - I - 4R2S - X industrial grade switch, warranty card, user manual

Software Features

L2 Switching	• IGMP Snooping - supports 128 groups • Link Aggregation - static, 8 groups, up to 4 ports/group • Port Mirroring - one-to-one, many-to-many • DHCP snooping anti-secondary route IP assignment (optional) • Port isolation and port grouping
VLAN	• Supports up to 32 VLANs (out of 4K VLAN IDs) • Supports Port VLAN and 802.1Q VLAN • Supports port-based / 802.1p / DSCP priority
QoS	• 4 priority queues • Port speed limit • Storm control
Management	• Web network management, IP: 192.168.1.199 • Default username and password: admin
Ethernet Protocols	• IEEE 802.3 10BASE-T • IEEE 802.3u 100BASE-TX/FX • IEEE 802.3ab 1000BASE-T • IEEE 802.3x Flow Control • IEEE 802.1Q VLAN tagging • IEEE 802.1p QoS