

# UniSwitch US-4MP

## 4-Port Managed PoE L2+ Switch

SKU: US-4MP



### PRODUCT OVERVIEW

The Indio Networks 4-Port Managed PoE Switch is a high-performance Layer 2 switching solution designed for small offices, SMB, home office, surveillance and other small network environments. It features 4 Gigabit Ethernet RJ-45 ports with IEEE 802.3af/at PoE+ support and 2 Gigabit SFP uplink ports, enabling reliable connectivity and power delivery to devices such as Wi-Fi access points, IP cameras, IP phones and other PoE-enabled devices.

With a 65W total PoE power budget and up to 30W per PoE port, the switch provides flexible deployment options while reducing the need for separate power infrastructure. Advanced network management capabilities, including 802.1Q VLAN, QoS, STP/RSTP/MSTP, LACP, IGMP Snooping, port mirroring, loopback detection and PoE management, enable efficient traffic management, network segmentation and improved network reliability.

The switch is an ideal choice for organizations looking for a compact, secure and scalable managed switching solution for modern wired and PoE-powered network deployments.



**12 Gbps  
Switching**



**65 W Power  
Budget**



**Cloud  
Management**



**Open Switching  
Technology**



**3-Year  
Warranty**

### KEY FEATURES

- |                                   |                             |
|-----------------------------------|-----------------------------|
| ✓ 4 x Gigabit Ethernet PoE+ Ports | ✓ L2+ Managed Switching     |
| ✓ 2 x Gigabit SFP Uplink Ports    | ✓ Advanced VLAN Support     |
| ✓ 65W PoE Power Budget            | ✓ Enterprise Grade Security |
| ✓ Advanced QoS                    | ✓ Compact Design            |
| ✓ Multicast Management            | ✓ High Switching Capacity   |
| ✓ Intelligent Diagnostics         | ✓ Flexible Deployments      |

## USE CASES

- ✓ Corporate Offices
- ✓ IP Surveillance
- ✓ Campus Networks
- ✓ Government Projects

## SWITCH SPECIFICATIONS

| Radio Configuration    |                                   |
|------------------------|-----------------------------------|
| Port Type              | 4-Port PoE Managed Switch         |
| PoE Ports              | 4 802.3 at/at PoE ports           |
| PoE Power              | 65W with 30W per Port             |
| Switching Capacity     | 12 Gbps                           |
| Packet Forwarding Rate | 9 Mbps                            |
| MAC Address Table      | 8K                                |
| Packet Buffer          | 4 MB                              |
| Jumbo Frame            | 10 KB                             |
| Quality of Service     | 802.1p CoS / DSCP Priority        |
|                        | 8 priority queues                 |
|                        | Queue Scheduling: SP, WRR, SP+WRR |
|                        | Voice VLAN                        |
|                        | Port/Flow-based Rate Limiting     |
| L2 Features            | IGMP Snooping v1/v2/v3            |
|                        | MLD v1/v2 Snooping                |
|                        | 802.3ad LACP                      |
|                        | Spanning Tree STP/RSTP/MSTP       |
|                        | EAPS Ring Network Protocol        |
|                        | Port Isolation                    |
|                        | BPDU Filtering/Guard              |
|                        | LLDP                              |
|                        | 802.3x Flow Control               |
|                        | Loop back Detection               |
| VLAN                   | Support 4K VLAN                   |
|                        | Management VLAN                   |

|                            |                                                                                                                    |
|----------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Access Control List</b> | L2-L4 package filtering based on source and destination MAC address, IP, TCP/UDP ports, DSCP, protocol and VLAN ID |
| <b>Security</b>            | 256 ACL Groups                                                                                                     |
|                            | ACL on IP or MAC                                                                                                   |
|                            | 4 different priorities per port                                                                                    |
|                            | 802.1x Port-based Authentication                                                                                   |
|                            | RADIUS support                                                                                                     |
| <b>Management</b>          | Web-based GUI and CLI management                                                                                   |
|                            | SNMP v2c / v3                                                                                                      |
|                            | RMON (1,2,3,9 groups)                                                                                              |
|                            | DHCP / BOOTP client, DHCP Snooping                                                                                 |
|                            | DHCP Option-82                                                                                                     |
|                            | CPU Monitoring                                                                                                     |
|                            | Port Mirroring                                                                                                     |
|                            | SNTP – Time Setting                                                                                                |
|                            | Firmware Upgrade – TFTP / Web                                                                                      |
|                            | Syslog                                                                                                             |
|                            | Event logs (local and remote)                                                                                      |
| <b>Port Type</b>           | Gigabit Ethernet                                                                                                   |

## HARDWARE SPECIFICATIONS

| Switch Hardware            |                                                                                                                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Port Type</b>           | Gigabit Ethernet                                                                                                                                                                        |
| <b>Switch Type</b>         | L2+ Managed Switch                                                                                                                                                                      |
| <b>Supported Protocols</b> | IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1x, IEEE 802.1p, IEEE 802.3af, IEEE 802.3at |
| <b>Interfaces</b>          | 4 x 10/100/1000 Mbps RJ-45 ports (all PoE+)                                                                                                                                             |
|                            | 2 x 10/100/1000 Mbps SFP ports (Fiber)                                                                                                                                                  |
|                            | 1 x RJ-45 Console Port                                                                                                                                                                  |
| <b>SFP Ports</b>           | 2 SFP Gigabit Ports                                                                                                                                                                     |
| <b>Network Media</b>       | 10Base-T: UTP category 3, 4, 5 RJ-45 cable                                                                                                                                              |
|                            | 100Base-TX / 1000Base-T: UTP category 5, 5E or above cable                                                                                                                              |
| <b>Fanless Operation</b>   | Yes                                                                                                                                                                                     |

| Power Supply               |                                              |
|----------------------------|----------------------------------------------|
| Power Supply Specification | 100 – 240V AC, 50/60 Hz                      |
| Power Consumption          | 65W                                          |
| Physical & Environmental   |                                              |
| Form Factor                | Tablemount                                   |
| Dimensions (mm)            | 145 × 134 × 47 mm                            |
| Weight                     | ≤ 900 g                                      |
| Operating Temp             | -10°C to 55°C (Indoor)                       |
| Storage Temp               | -40°C to 70°C                                |
| Humidity                   | 5% – 95% non-condensing                      |
| Ingress Protection         | IP40 (Indoor)                                |
| Mounting                   | Tablemount or Rackmount (with extended ears) |

## REGULATORY & CERTIFICATIONS

|                     |            |
|---------------------|------------|
| Certifications      | CE / RoHS  |
| IPv6                | IPv6 Ready |
| TEC/MTCTE           | Certified  |
| Trusted Telecom     | Listed     |
| OpenLAN Switching   | Certified  |
| EN-60950-1 (Safety) | Certified  |

## ORDERING INFORMATION

| Part Numbers |                             |
|--------------|-----------------------------|
| US-8MP       | 4-Port, Managed PoE Switch  |
| IN-SW-ER     | Extended Ears for rackmount |

## IN THE BOX

- 1× US-4MP PoE Switch
- 1× Power Cable
- 1× Quick Start Guide
- 1× Warranty card

## WARRANTY & SUPPORT

|                   |                                                                            |
|-------------------|----------------------------------------------------------------------------|
| Hardware Warranty | 3 Years limited hardware warranty                                          |
| Firmware Support  | Active firmware releases (Indio builds)                                    |
| RMA Process       | Contact support@indionetworks.com                                          |
| Support Email     | <a href="mailto:support@indionetworks.com">support@indionetworks.com</a>   |
| Documentation     | <a href="http://www.indionetworks.com/docs">www.indionetworks.com/docs</a> |

## COMPANY INFORMATION

|               |                                                                      |
|---------------|----------------------------------------------------------------------|
| Company Name  | Indio Networks Private Limited                                       |
| Address       | C-410, Teerth Technospace IT Park, Baner, Pune – 411045, India       |
| Phone (Sales) | +91-20-6715-7377 / +91-86980-07222                                   |
| Email (Sales) | <a href="mailto:sales@indionetworks.com">sales@indionetworks.com</a> |

For technical specifications, datasheets, and partner pricing, contact: [sales@indionetworks.com](mailto:sales@indionetworks.com)  
*Specifications subject to change without notice. All rights reserved.*