

UniBox

HSIA Hotspot Gateway/Network Controller

SKU: U-50



PRODUCT OVERVIEW

UniBox is an intelligent, on-premise hotspot gateway and network controller appliance purpose-built for High-Speed Internet Access (HSIA) deployments in venues such as hotels, airports, universities, and large public hot zones. It consolidates the functions of a network gateway, AAA server, captive portal server, load balancer, web logger, VPN server, policy server, and firewall into a single appliance, eliminating the need for multiple discrete network components. UniBox provides all the functions needed to configure, manage, and monetize Wi-Fi hotspots and can be deployed alongside Indio's UniMax access points or any third-party APs, making it suitable for networks of any scale.

UniBox enables venues to centrally manage both wired and wireless networks while maintaining full control over user access, authentication, and traffic visibility, all without relying on a cloud dependency. Available in multiple hardware tiers (U-50, U-100, U-500, U-1000 and beyond), the UniBox scales from small-venue deployments to enterprise-grade installations handling hundreds of concurrent HSIA sessions, making it a flexible and cost-effective gateway choice for operators seeking an all-in-one on-premise solution.



**All-in-One
Hardware**



**Vendor Neutral
Deployments**



**Built-in
Monetization**



**Compliance
Ready**



**High
Performance**

KEY FEATURES

- | | |
|------------------------|--|
| ✓ All-in-One Appliance | ✓ Vendor Neutral |
| ✓ Hotspot Controller | ✓ OAuth, GSuite, Azure Authentication |
| ✓ Captive Portals | ✓ SD-WAN / Multi-WAN |
| ✓ Access Policies | ✓ Voucher / Coupons |
| ✓ Compliance Ready | ✓ AAA Server / 802.1X Authentication |
| ✓ Basic Firewall | ✓ PMS / HMS Integration |
| ✓ Online Charging | ✓ High Performance and High Availability |

USE CASES

- ✓ Hotels / Resorts
- ✓ Colleges / Universities
- ✓ Enterprise/Office Networks
- ✓ Public Wi-Fi Hotspots
- ✓ Hospitals
- ✓ Government Projects

TECHNICAL SPECIFICATIONS

Networking	
Ethernet Ports	4 x 10/100/1000 base (T/Tx) – RJ 45 ports
WAN	Multi-WAN with intelligent Failover
	Supports Static, Dynamic and PPPoE
	Link Status Check
	Dynamic DNS Service
	VLAN Support
LAN	Multiple LAN Configuration
	Virtual LAN Interfaces
	Independent DHCP Service for each interface
	DHCP Relay
	DNS Cache
	Device Monitoring
	VLAN Support
USB	2 x USB 3.0 ports
Routing	Static Routing
	Group based Routing
	Port Forwarding for LAN clients
DHCP / DNS	Built-in DHCP and DNS service
VLAN Support	IEEE 802.1Q VLAN tagging
VPN Support	OpenVPN, WireGuard, GRE
Protocols	L2 Isolation, NTP (RFC 1305), SNMP v2c
NAT Mapping	Yes
Group Routing	Yes
Device Monitoring	Yes
Port Forwarding	Yes

Tunnels	OpenVPN
	WireGuard
	GRE
Multi-WAN	
Multi-WAN Support	Yes
Load Balancing on WAN	Yes
WAN Load Distribution	Yes
Intelligent WAN Failover	Yes
Secure Session Persistence	Yes
NAT	SNAT (Masquerade), DNAT (Port Forwarding)
VLAN Support	802.1Q
IGMP	IGMP v2, IGMP Snooping
Network Tools	Ping, Traceroute, ARP Scan, Nslookup, Speed Test
Remote SSH	Web SSH
Diagnostics Tools	PCAP Capture, RF scanning, Spectrum Analyzer
Remote Syslog	Yes
Hotspot Service	
Multiple Hotspot Controllers	Yes
Captive Portal	Separate Captive Portal per Hotspot
Built-in RADIUS Server	Yes
MAC Authentication	Yes
RADIUS Attributes	Yes
802.1X Authentication	Yes
Passpoint/Hotspot 2.0 Support	Yes
Supported Devices	50 clients

HARDWARE SPECIFICATIONS

Platform & Interfaces	
Interface	3 LAN Port (RJ-45) – 10/100/1000 base T/Tx
	1 WAN Port (RJ-45) – 10/100/1000 base T/Tx

	1 Console (RJ-45) – 10/100/1000 base T/Tx
USB	2 USB Ports
Serial Port	Yes
Reset	Yes
Power	
Input Voltage	12V DC
Power Consumption	20W
Heat Dissipation	200 BTU
Physical & Environmental	
Form Factor	Standalone
Dimensions (mm)	176 x 174 x 30 mm
Weight	≤ 500 g
Operating Temperature	-10°C to 55°C
Storage Temp	-40°C to 70°C
Humidity	8% - 90% non-condensing
Ingress Protection	IP40 (indoor)

SOFTWARE & MANAGEMENT

Captive Portals	
Portal Templates	25+
Multiple Login Methods	Username / Password
	Mobile Number / Email with OTP
	Vouchers / Coupons
	Social Media Verification
	Click-through and Data Capture
	802.1x authentication
	AD / LDAP / GSuite / Azure Account verification
Approval Based Onboarding	Yes
Multi-Lingual Portals	Yes
Local Captive Portals	Yes
SSL Support	Yes
Custom Branding	Yes

Guest Access Management	
On-board User Database	Yes
User Management	Complete user lifecycle management
Multiple Provisioning Options	Yes
User Grouping	Yes
User Activity Tracking	Yes
Usage and Payment History	Yes
Bandwidth Control & Policies	
Per User Bandwidth Control	Yes
Group Based Policies	Yes
Quota Limits	Time, Data, Clients, Device, Internet Speed
Fair Usage Policy	Yes
Week Day / Time of Day Limits	Yes
Billing & Monetization	
Payment Gateway Integration	Yes
Custom Billing Plans	Yes
Paid Vouchers	Yes
Tiered Billing	Yes
Transaction History	Yes
Hyper-local Advertisement	Yes
Ads for Access	Yes
Security	
Website Filtering	Filtering websites based on categories
Group-based URL Filtering	Yes
Port Blocking	Yes
IPDR and CDR Logs (TRAI Compliance)	Yes
Web Browsing Logs	Yes

Client Isolation	Yes
MAC Blacklisting	Yes
Audit Trails	Yes
Reliability	
High Availability	Active - Active
	Active - Passive
Automated Backups	Yes
Multiple WLAN with Load-balancing	Yes
Third Party Integrations	
SMS Gateway services	Multiple (Gupshup, SMSMantra, Twilio, Clickatell, SMSWave, TextNation, more)
Active Directory / LDAP Services	Yes
Google GSuite / Microsoft Azure	Yes
Hotel PMS systems	Multiple (Oracle Opera, IDS Fortune, WinHMS, Innkey, HotelLogix, WinHMS, Hotelier and more)
External Databases/APIs	Yes
Social Media Handles	Multiple (Google, Facebook, Twitter, LinkedIn)
Reporting & Analytics	
Real-time Dashboard	Yes
Bandwidth Consumption	Yes
User Revenue	Yes
Network Health	Yes
Advertisement Statistics	Yes
System Logs	Yes
Automated Email Reporting	Yes

ORDERING INFORMATION

Part Numbers	
UniBox U-50	HSIA Hotspot Gateway / Network Controller

IN THE BOX

- 1 × U-50 UniBox Network Controller
- 1 × Power cable
- 1 × Quick Start Guide
- 1 × Warranty card

WARRANTY & SUPPORT

Hardware Warranty	1 year standard hardware warranty
Firmware Support	Active firmware releases (Indio builds)
RMA Process	Contact support@indionetworks.com
Support Email	support@indionetworks.com
Documentation	www.indionetworks.com/docs

COMPANY INFORMATION

Company Name	Indio Networks Private Limited
Address	C-410, Teerth Technospace IT Park, Baner, Pune – 411045, India
Phone (Sales)	+91-20-6715-7377 / +91-86980-07222
Email (Sales)	sales@indionetworks.com

For technical specifications, datasheets, and partner pricing, contact: sales@indionetworks.com
Specifications subject to change without notice. All rights reserved.