

UM-325AX

Wi-Fi 6, Indoor Access Point

SKU: UM-325AX



PRODUCT OVERVIEW

The Indio Networks UM-325AX is an enterprise-grade Wi-Fi 6 access point designed for corporates, hospitality, MDU, and ISP/MSP deployments for modern wireless networks. It supports Wi-Fi 6 features like MU-MIMO for higher throughput, aggregate throughput of 3 Gbps and over 150 concurrent devices for enterprise deployments.

Built on the TIP OpenWiFi architecture, it integrates seamlessly with Indio's Cloud management platform enabling zero-touch provisioning, device management, multi-tenant control, and real-time analytics at scale.



3 Gbps Speed



2.5 GbE PoE



Dual-Band Wi-Fi



2x2 MU-MIMO



3-Year Warranty

KEY FEATURES

- | | |
|--------------------------------------|-----------------------------------|
| ✓ Wi-Fi 6 802.11ac/ax | ✓ TIP OpenWiFi Compatible |
| ✓ Dual-Band Radio, 3 Gbps throughput | ✓ Zero-Touch Provisioning (ZTP) |
| ✓ MU-MIMO Support | ✓ Multi-Tenant Cloud Management |
| ✓ 256 Concurrent Clients | ✓ WPA3 / WPA2 Enterprise Security |
| ✓ PoE+ Powered (802.3af/at) | ✓ RADIUS / 802.1X Authentication |
| ✓ Cloud / Controller Managed | ✓ Captive Portal & Hotspot 2.0 |
| ✓ Real-Time WLAN Analytics | ✓ Band Steering & Load Balancing |

USE CASES

- | | |
|---------------------|-----------------------|
| ✓ Corporate Offices | ✓ Wi-Fi Hotspots |
| ✓ Campus Networks | ✓ Government Projects |

RADIO SPECIFICATIONS

Radio Configuration		
Standard	2.4 GHz - IEEE 802.11a/n/ac/ax	
	5 GHz - IEEE 802.11a/n/ac/ax	
Radio Architecture	2x2:2 MU-MIMO - Dual-Band	
Operating Mode	Access Point, Router, Mesh Node	
Networking	IPv4 and IPv6 Support, Gateway Mode (NAT), Bridge Mode	
Frequency Bands (country specific)	2.4 GHz	2.4 GHz ~ 2.484 GHz
	5 GHz	5.150 GHz ~ 5.850 GHz
Max Data Rate	5 GHz	802.11ax @ 160 MHz – 2400 Mbps 802.11ax @ 80 MHz – 2400 Mbps 802.11ax @ 40 MHz – 1120 Mbps 802.11ax @ 20 MHz – 576 Mbps
	2.4 GHz	802.11ax @ 40 MHz – 578 Mbps 802.11ax @ 20 MHz – 286 Mbps
Maximum Receiver Sensitivity	5 GHz	-97 dBm
	2.4 GHz	-93 dBm
Transmit Power	5 GHz	26 dBm
	2.4 GHz	24 dBm
Modulation	BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM	
Spatial Streams	5 GHz	2x2:2 – OFDMA (802.11ax) & OFDM (802.11ac) MU-MIMO
	2.4 GHz	2x2:2 – OFDM (802.11a/g/n) and DSSS with MU-MIMO
Supported Channels	5 GHz	36-64, 100-144, 149-165 (UNII-1, UNII-2, UNII-2e, UNII- 3 compliant) (As per country)
	2.4 GHz	1 – 13 (As per country)
Wireless Security	WPA3-AES personal, enhanced open (OWE)	
	WPA3-Enterprise (802.1x/EAP-TLS, EAP-TTLS)	
	WPA3-WPA2 Mixed- AES personal, Open	
	WPA2-TKIP/AES personal, Open	
	WPA2-Enterprise (802.1x/EAP-PEAP, EAP-TLS, EAP-TTLS)	
	WPA personal, WPA Mixed-Enterprise (802.1x/EAP-PEAP)	
	WEP-64, WEP-128	
	802.11w MFP (Management Frame Protection)	
	MAC-based authentication	
	Captive portal-based authentication	

	802.11i
Meshing	Wireless (single and multi-hop)
Radio Management	DTIM interval
	OFDM only
	BSS Rate and Management Rate
	RTS/CTS Threshold
	UAPSD (Power Saving)
Concurrent Devices	256 clients
SSID	16 SSIDs (8 SSIDs per Radio)

NETWORK SPECIFICATIONS

Networking	
WAN	DHCP / Static / PPPoE
Tunneling	GRE, Wireguard, OpenVPN
DHCP Server	DHCP lease, DNS proxy
PPP Interface	PPPoE, L2TP
DNS	Static, Caching, Dynamic DNS
NAT	SNAT (Masquerade), DNAT (Port Forwarding)
VLAN Support	802.1Q
IGMP	IGMP v2, IGMP Snooping
Diagnostics	
Network Tools	Ping, Traceroute, ARP Scan, Nslookup, Speed Test
Remote SSH	Web SSH
Diagnostics Tools	PCAP Capture, RF scanning, Spectrum Analyzer

HARDWARE SPECIFICATIONS

Platform & Interfaces	
CPU	Qualcomm 1 GHz Quad-Core CPU with dedicated NSS
RAM	512 MB DDR4
Flash Storage	32 MB NAND
Physical Interfaces	1 × 2.5 Gbps WAN port, support 802.3af/at input
	1 × 10/100/1000 Mbps LAN port
LEDs	Multi-color status LED (Power, Wi-Fi, LAN, WAN, SFP)

Reset	Factory reset button
Antenna	Internal, Omni Directional 4 dBi Antennas
Power	
PoE Standard	802.3af/at (PoE+, 30W)
DC Input	DC2.0 12V/2A DC, optional power adapter
Max Power Draw	≤ 24W (fully loaded)
Physical & Environmental	
Form Factor	Ceiling-mount
Dimensions (mm)	194 × 194 × 49 mm (ceiling)
Weight	≤ 1211 g
Operating Temp	-10°C to 55°C (Indoor)
Storage Temp	-40°C to 70°C
Humidity	5% – 95% non-condensing
Ingress Protection	IP40 (Indoor)
Mounting	Ceiling Mounting Plate (included)

SOFTWARE & MANAGEMENT

Firmware & Protocols	
OS / Firmware	TIP OpenWiFi uCentral Agent
Management Protocol	uCentral
Controller	Local SSH/CLI
	Indio Cloud (Public/Private Cloud)
	Indio UniController (On-premise Appliance)
Provisioning	Zero-Touch Provisioning (ZTP)
VLAN Support	802.1Q - up to 16 SSIDs with per-SSID
QoS	WMM, 802.1p
	DSCP marking
	per-SSID rate limiting
	Wi-Fi Calling
Security	WPA3-Personal, WPA3-Enterprise, WPA2, OWE (Enhanced Open)
Authentication	802.1X EAP (PEAP, TLS, TTLS), RADIUS, RadSec, MAC ACL
Guest Access	Captive Portal (local / cloud redirect), Hotspot 2.0 / Passpoint
Monitoring	Syslog, telemetry

Certificates	X.509 device certificates
OTA Updates	Automated firmware updates via Indio Cloud
Advanced Wi-Fi Features	
Roaming	802.11r (Fast BSS Transition)
	802.11k/v (RRM & BSS Transition)
Client Management	Band Steering
	Load Balancing
	Airtime Fairness
	ARP Proxy
	Client Isolation
Mesh	802.11s mesh backhaul support
Channel / TX Power Management	Auto / Manual Channel Selection
	Channel Switching for RF optimization
	Automatic Transmit Power Management
Guest Access	WISPr – Captive Portals
	Hotspot 2.0
RADIUS Integration	Dynamic VLAN
	CoA
	MAC Authentication
Beam Forming	Transmit Beam-forming for increased signal reliability and range
External Integrations	
PMWANI	Compatible
NMS	Zabbix, PRTG, OpenNMS
Open Roaming	Supported

REGULATORY & CERTIFICATIONS

Radio Certifications	ETA / WPC
IPv6	IPv6 Ready
TEC/MTCTE	Certified
Trusted Telecom	Listed
OpenWiFi	Certified
EN-60950-1 (Safety)	Certified
Open Roaming	Certified

ORDERING INFORMATION

Part Numbers	
UM-325AX	2x2 MU-MIMO, Dual-Band, Indoor Ceiling Mount AP
IN-POEINJ-30W	802.3af/at PoE Injector [Optional]
IN-MNT-CEIL	Wall Mount Bracket Kit

IN THE BOX

- 1 × UM-325AX Wi-Fi Access Point
- 1 × Mounting bracket + hardware
- 1 × Quick Start Guide
- 1 × Warranty card

WARRANTY & SUPPORT

Hardware Warranty	3 Years limited hardware warranty
Firmware Support	Active firmware releases (Indio builds)
RMA Process	Contact support@indionetworks.com
Support Email	support@indionetworks.com
Documentation	www.indionetworks.com/docs

COMPANY INFORMATION

Company Name	Indio Networks Private Limited
Address	C-410, Teerth Technospace IT Park, Baner, Pune – 411045, India
Phone (Sales)	+91-20-6715-7377 / +91-86980-07222
Email (Sales)	sales@indionetworks.com

For technical specifications, datasheets, and partner pricing, contact: sales@indionetworks.com
Specifications subject to change without notice. All rights reserved.