

CJ Information

S – AP CS A

IC – Arrays in Java

HW - none

A – 2024.12.19 Thu – TEST(???)




Arrays in Java



Outline:

- Arrays in general and in Java
- Arrays as a multiple container
- Example




BASIS
INTERNATIONAL™
SCHOOLS · CHINA



BASIS
BILINGUAL™
SCHOOLS · CHINA

What we learn today:

- What is an Array in Java
- How to store and retrieve information from an Array
- Examples



BASIS
INTERNATIONAL™
SCHOOLS · CHINA



BASIS
BILINGUAL™
SCHOOLS · CHINA

Arrays in Java

Creating and Access



An **array** is a block of memory that stores a collection of data items (**elements**) of the same type under **one name**. Arrays are useful whenever you have many elements of data of the same type that you want to keep track of, but you don't need to name each one. Instead you use the array name and a number (called an **index**) for the position of an item in the array. You can make arrays of ints, doubles, Strings, and even classes

40	55	63	17	22	68	89	97	89
0	1	2	3	4	5	6	7	8

<- Array Indices

Array Length = 9
First Index = 0
Last Index = 8




Arrays in Java

Declaring and Creating Array

```
// Declaration for a single int variable  
int score;  
// Declaration for an array of ints  
int[] scores;
```

The declarations do not create the array. **Arrays are objects in Java**, so any variable that declares an array holds a reference to an object. If the array hasn't been created yet and you try to print the value of the variable, it will print **null** (meaning it doesn't reference any object yet).

There are two ways to create an array. You can use the **keyword new to get new memory** or use an **initializer list** to set up the values in the array.



BASIS
INTERNATIONAL™
SCHOOLS · CHINA



BASIS
BILINGUAL™
SCHOOLS · CHINA


Arrays in Java

Declaring and Creating Array

```
// Declaration for a single int variable  
int score;  
// Declaration for an array of ints  
int[] scores;
```

The declarations do not create the array. Arrays are **objects** in Java, so any variable that declares an array holds a reference to an object. If the array hasn't been created yet and you try to print the value of the variable, it will print **null** (meaning it doesn't reference any object yet).

There are two ways to create an array. You can use the **keyword new** to get new memory or use an **initializer list** to set up the values in the array.



BASIS
INTERNATIONAL™
SCHOOLS · CHINA



BASIS
BILINGUAL™
SCHOOLS · CHINA

Arrays in Java

Using **new** to create an array



To create an empty array after declaring the variable, use the **new keyword** with the type and the size of the array (the number of elements it can hold). This will actually create the array in memory. You can do the declaration and the creation all in one step, see the String array names below. The size of an array is set at the time of creation and cannot be changed after that.

```
//declare an array variable  
int[] highScores;  
// create the array  
highScores = new int[5];  
// declare and create array in 1 step!  
String[] names = new String[5];
```



BASIS
INTERNATIONAL™
SCHOOLS · CHINA



BASIS
BILINGUAL™
SCHOOLS · CHINA

Arrays in Java

Using **new** to create an array


IMPORTANT

Array elements are initialized to default values like the following.

- 0 for elements of type **int**
- 0.0 for elements of type **double**
- false for elements of type **boolean**
- null for elements of type **String**



	0	1	2	3	4
highScores	0	0	0	0	0
	0	1	2	3	4
names	null	null	null	null	null




Arrays in Java

Using **initializer list** to create an array



Another way to create an array is to use an **initializer list**. You can initialize (set) the values in the array to a list of values in curly braces (**{}**) when you create it, like below. In this case you don't specify the size of the array, it will be determined from the number of values that you specify.

```
int[ ] highScores = {99,98,98,88,68};  
String[ ] names = {"Jamal", "Emily", "Destiny", "Mateo", "Sofia"};
```



BASIS
INTERNATIONAL™
SCHOOLS · CHINA



BASIS
BILINGUAL™
SCHOOLS · CHINA

Arrays in Java

Using array length




Arrays know their length (how many elements they can store). It is a public read-only instance variable so you can use **dot-notation** to access the instance variable (**arrayName.length**).

Example

```
int[] highScores = {99, 98, 98, 88, 68};  
System.out.println(highScores.length);
```



What is the result
???



BASIS
INTERNATIONAL™
SCHOOLS · CHINA



BASIS
BILINGUAL™
SCHOOLS · CHINA

Arrays in Java


Access and Modify Array Values

To access an element of the array, we use an **index**, a variable that identify a specific position inside the array.

```
// assign a new value 99 to the first element in the array  
highScores[0] = 99;  
// print the first element of the array  
System.out.println( highScores[0] );
```

Note

The first value in an array is stored at index 0 and the index of the last value is the length of the array minus one (since the first index is 0). Use `arrayname[index]` to access or modify array items.



BASIS
INTERNATIONAL™
SCHOOLS · CHINA



BASIS
BILINGUAL™
SCHOOLS · CHINA

Arrays in Java


Access and Modify Array Values



WARNING !!!!!!!

Q : What happens if you try to access an element at position that is not present in the array????

A : you will get an error message called **ArrayIndexOutOfBoundsException.** and your program **stops** working !!!!!!!!!!!!!!!



BASIS
INTERNATIONAL™
SCHOOLS · CHINA



BASIS
BILINGUAL™
SCHOOLS · CHINA

Arrays in Java



Array of Objects.

Array can contain also complex data structures as objects.
Have a look at the following example to better understand how it works:

```
// Creating a student class with
// id and name as attributes
class Student {

    public int id;
    public String name;

    // Student class constructor
    Student(int id, String name)
    {
        this.id = id;
        this.name = name;
    }

    // display() method to display
    // the student data
    public void display()
    {
        System.out.println("Student id is: " + id + " "
                           + "and Student name is: "
                           + name);
        System.out.println();
    }
}
```

```
class GFG {

    public static void main(String args[])
    {

        // Declaring an array of student
        Student[] arr;

        // Allocating memory for 2 objects
        // of type student
        arr = new Student[2];

        // Initializing the first element
        // of the array
        arr[0] = new Student(1701289270, "Satyabrata");


        // Initializing the second element
        // of the array
        arr[1] = new Student(1701289219, "Omm Prasad");

        // Displaying the student data
        System.out.println(
            "Student data in student arr 0: ");
        arr[0].display();

        System.out.println(
            "Student data in student arr 1: ");
        arr[1].display();
    }
}
```

Student data in student arr 0:
Student id is: 1701289270 and Student name is: Satyabrata

Student data in student arr 1:
Student id is: 1701289219 and Student name is: Omm Prasad




Arrays in Java

Access and Modify Array Values

SUMMARY

- Arrays represent collections of related data all of the same data type.
- The size of an array is established at the time of creation and cannot be changed.
- Arrays can store either primitive data or object reference data.
- When an array is created using the keyword `new`, all of its elements are initialized with a specific value based on the type of elements:
 - Elements of type `int` are initialized to 0
 - Elements of type `double` are initialized to 0.0
 - Elements of type `boolean` are initialized to `false`
 - Elements of a reference type are initialized to the reference value `null`. No objects are automatically created.
- Initializer lists can be used to create and initialize arrays.
- Square brackets (`[]`) are used to access and modify an element in an array using an index. The indexed array variable, for example `array[index]`, can be used anywhere a regular variable can be used, for example to get or assign values.
- The valid index values for an array are 0 through one less than the number of elements in the array, inclusive. Using an index value outside of this range will result in an `ArrayIndexOutOfBoundsException` being thrown.



Arrays in Java


Access and Modify Array Values



Exercise

Create a Java program that implements the following points:

- 1) Create a **Car** class with the following ATTRIBUTES : **power** (of type int), **color** (of type string) , **fuel** (of type string) and the **toString()** method that prints out the information about the car
- 2) Create a **TestingCar** class containing an array of 2 objects of type Car.
- 3) Initialize the two objects and insert them inside the array
- 4) Using a for loop, you print out the information for every element of the array.



BASIS
INTERNATIONAL™
SCHOOLS · CHINA



BASIS
BILINGUAL™
SCHOOLS · CHINA