```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
```

```
x=np.array([95,85,80,70,60])
y=np.array([85,95,70,65,70])
```

```
model= np.polyfit(x, y, 1)
model
```

```
array([ 0.64383562, 26.78082192])
```

```
predict = np.poly1d(model)
predict(65)
```

```
68.63013698630135
```

```
y_pred= predict(x)
y_pred
```

```
array([87.94520548, 81.50684932, 78.28767123, 71.84931507, 65.4109589 ])
```

```
from sklearn.metrics import r2_score
```

```
r2_score(y, y_pred)
```

```
0.4803218090889323
```

```
y_line = model[1] + model[0]* x
plt.plot(x, y_line, c = 'r')
plt.scatter(x, y_pred)
plt.scatter(x,y,c='r')
```

```
<matplotlib.collections.PathCollection at 0x7f2592725000>
```




```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
```

```
from sklearn.datasets import fetch_california_housing

# Load the California housing dataset
california = fetch_california_housing()

# Access the feature data
X = california.data

# Access the target data (median house values)
y = california.target



data = pd.DataFrame(california.data)


data.head()
```

	0	1	2	3	4	5	6	7
0	8.3252	41.0	6.984127	1.023810	322.0	2.555556	37.88	-122.23
1	8.3014	21.0	6.238137	0.971880	2401.0	2.109842	37.86	-122.22
2	7.2574	52.0	8.288136	1.073446	496.0	2.802260	37.85	-122.24
3	5.6431	52.0	5.817352	1.073059	558.0	2.547945	37.85	-122.25
4	3.8462	52.0	6.281853	1.081081	565.0	2.181467	37.85	-122.25

Next steps: Generate code with data | View recommended plots

```
data.columns
```

```
RangeIndex(start=0, stop=8, step=1)
```

```
data['PRICE'] = california.target



data.isnull().sum()
```

```
0        0
1        0
2        0
3        0
4        0
5        0
6        0
7        0
PRICE    0
dtype: int64
```

```
 x = data.drop(['PRICE'], axis = 1)
 y = data['PRICE']


from sklearn.model_selection import train_test_split
xtrain, xtest, ytrain, ytest =train_test_split(x, y, test_size = 0.2,random_state = 0)


import sklearn
from sklearn.linear_model import LinearRegression
lm = LinearRegression()
model=lm.fit(xtrain, ytrain)


ytrain_pred = lm.predict(xtrain)
ytest_pred = lm.predict(xtest)


df=pd.DataFrame(ytrain_pred,ytrain)
df=pd.DataFrame(ytest_pred,ytest)


from sklearn.metrics import mean_squared_error, r2_score
mse = mean_squared_error(ytest, ytest_pred)
print(mse)
mse = mean_squared_error(ytrain_pred,ytrain)
```

```
print(mse)
```

```
0.5289841670367209
0.5234413607125448
```

```
mse = mean_squared_error(ytest, ytest_pred)
print(mse)
```

```
0.5289841670367209
```

```
plt.scatter(ytrain ,ytrain_pred,c='blue',marker='o',label='Training data')
plt.scatter(ytest,ytest_pred ,c='lightgreen',marker='s',label='Test data')
plt.xlabel('True values')
plt.ylabel('Predicted')
plt.title("True value vs Predicted value")
plt.legend(loc= 'upper left')
#plt.hlines(y=0,xmin=0,xmax=50)
plt.plot()
plt.show()
```



Start coding or generate with AI.