

Multi-prototype Fuzzy Clustering with Fuzzy K-Nearest Neighbor for Off-line Human Action Recognition

Ritipong Wongkhuenkaew,
Computer Engineering Department,
Faculty of Engineering,
Chiang Mai University,
Chiang Mai, Thailand
520631132@cmu.ac.th

Sansanee Auephanwiriyaikul,
Senior Member, IEEE,
Computer Engineering Department,
Faculty of Engineering,
Biomedical Engineering Center,
Chiang Mai University,
Chiang Mai, Thailand
sansanee@ieee.org

Nipon Theera-Umpon,
Senior Member, IEEE,
Electrical Engineering Department,
Faculty of Engineering,
Biomedical Engineering Center,
Chiang Mai University,
Chiang Mai, Thailand
nipon@ieee.org

Abstract—Fall detection of elderly in home environment is an important research area. The fall detection is a part of the human action recognition. In this paper, a human action detection using the fuzzy clustering algorithm with the fuzzy K-nearest neighbor from view-invariant human motion analysis is implemented. In particular, the Hu moment invariant features are computed. Then principal component analysis is utilized to select the principal components. The fuzzy clustering algorithm (either fuzzy C-means, Gustafson and Kessel, or Gath and Geva) is implemented on each class to select the prototypes representing the class. From the results, we found that the best classification rate on the validation set is around 99.33% to 100%, and the classification rate on the blind test data set is around 90%. We also compare the result from fuzzy K-nearest neighbor with that from K-nearest neighbor. The fuzzy K-nearest neighbor result is better as expected.

Keywords—Fall detection; Hu moment invariants; Fuzzy C-means; Gustafson and Kessel clustering; Gath and Geva clustering; Fuzzy K-nearest neighbor

I. INTRODUCTION

Human action recognition is one of the processes that are needed in view-invariant human motion analysis [1, 2]. One of the important application areas for this motion analysis is to detect the fall of elderly in home environment. There are more than 50% of injury-related hospitalizations in people aged over 65. Consequently, some of injury deaths (almost 40%) are from falls [3]. Even though there are several works in view-invariant human motion analysis [4–30], none of them focus on fall detection. There are some research works involving view-invariant fall detection system [31–36], however, the accuracy of these systems is approximately 90–97%. Although, there are some other related works with approximately 100%, those systems either use several cameras [37–47] or the accuracy reported is based on only one subject [48] or the detection systems are built based on 2-class detection that might not be appropriate for daily live [50].

In this paper, we use a fuzzy clustering and fuzzy K-nearest neighbor to detect human action with the data set from [33]. In

particular, we utilize features extracted from the Hu moment invariants and then the principal component analysis is computed. Then a fuzzy clustering algorithm (Fuzzy C-Means, Gustafson and Kessel Clustering, or Gath and Geva Clustering) is used to create multi-prototypes for each action. Finally, the fuzzy K nearest neighbor is utilized to detect human action.

II. BACKGROUND THEORIES

A. Hu Moment Invariants

The Hu moment invariants [50, 51] is now briefly described. For a 2-dimensional binary image, $(p + q)^{th}$ order geometrical moments m_{pq} is

$$m_{pq} = \sum_y \sum_x x^p y^q f(x, y), \quad p, q = 0, 1, 2, \dots, \quad (1)$$

where $f(x, y)$ is either 0 or 1 value at coordinate (x, y) . Then the central moments (μ_{pq}) are computed by

$$\mu_{pq} = \sum_y \sum_x (x - \bar{x})^p (y - \bar{y})^q f(x, y), \quad (2)$$

where $\bar{x} = \frac{m_{10}}{m_{00}}$ and $\bar{y} = \frac{m_{01}}{m_{00}}$. Since the object center is shifted to the center of image, μ_{pq} is translation invariant. The normalized central moments are defined as follow:

$$\eta_{pq} = \frac{\mu_{pq}}{\mu_{00}^r}, \quad \text{for } p + q = 2, 3, \dots, \quad (3)$$

where $r = \frac{p + q}{2} + 1$. Then the extracted features are

$$\varphi_1 = \eta_{20} + \eta_{02} \quad (4)$$

$$\varphi_2 = (\eta_{20} - \eta_{02})^2 + 4\eta_{11}^2 \quad (5)$$

$$\varphi_3 = (\eta_{30} - 3\eta_{12})^2 + (3\eta_{21} - \eta_{03})^2 \quad (6)$$

$$\varphi_4 = (\eta_{30} - \eta_{12})^2 + (\eta_{21} + \eta_{03})^2 \quad (7)$$

$$\varphi_5 = (\eta_{30} - 3\eta_{12})(\eta_{30} + \eta_{12})[(\eta_{30} + \eta_{12})^2 - 3(\eta_{21} + \eta_{03})^2] \\ + (3\eta_{21} - \eta_{03})(\eta_{21} + \eta_{03})[3(\eta_{30} + \eta_{12})^2 - (\eta_{21} + \eta_{03})^2] \quad (8)$$

$$\varphi_6 = (\eta_{20} - \eta_{02})[(\eta_{30} + \eta_{12})^2 - (\eta_{21} + \eta_{03})^2] \\ + 4\eta_{11}(\eta_{30} + \eta_{12})(\eta_{21} + \eta_{03}) \quad (9)$$

$$\varphi_7 = (3\eta_{21} - \eta_{03})(\eta_{30} + \eta_{12})[(\eta_{30} + \eta_{12})^2 - 3(\eta_{21} + \eta_{03})^2] \\ - (\eta_{30} - 3\eta_{12})(\eta_{21} + \eta_{03})[3(\eta_{30} + \eta_{12})^2 - (\eta_{21} + \eta_{03})^2] \quad (10)$$

Since these features are non-orthogonal, i.e., their basis functions are correlated, we use the principal component analysis to solve this problem.

B. Principal Component Analysis (PCA)

Now, we briefly describe the principal component analysis (PCA) [52]. Suppose $\mathbf{X} \in \mathbb{R}^{n \times p}$ contains n samples with p dimensions. The covariance matrix Σ is

$$\Sigma = \mathbf{V}\mathbf{\Lambda}\mathbf{V}^t, \quad (11)$$

where \mathbf{V} is an orthogonal matrix with eigenvectors as its column vectors. $\mathbf{\Lambda}$ is a diagonal matrix with eigenvalues sorted in decreasing order ($\lambda_1 \leq \lambda_2 \leq \dots \leq \lambda_p$) as its diagonal elements. The transformation matrix $\mathbf{P} \in \mathbb{R}^{p \times a}$ is used to select a eigenvectors (principal components (PCs)). The cumulative percent variance (CPV) [36, 37] is used to measure the percent variance captures by the first a PCs. The CPV is calculated as

$$\text{CPV}(a) = \frac{\sum_{k=1}^a \lambda_k}{\text{trace}(\mathbf{\Lambda})} \times 100, \text{ for } a \leq p. \quad (12)$$

Then the uncorrelated data set \mathbf{Y} is

$$\mathbf{Y} = \mathbf{X}\mathbf{P}. \quad (13)$$

This data set is used in the clustering.

C. Fuzzy Clustering Algorithm

In this paper, we use the fuzzy C-means clustering, Gustafson and Kessel clustering and Gath and Geva clustering. We first briefly review the Fuzzy C-means (FCM) algorithm [53, 54] here. Let $\mathbf{X} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N\}$ be a set of vectors, where each vector is a p -dimensional vector. The update equation for FCM is as follows [54]

$$u_{ij} = \frac{1}{\sum_{k=1}^C \left[\frac{\|\mathbf{x}_i - \mathbf{c}_j\|}{\|\mathbf{x}_i - \mathbf{c}_k\|} \right]^{\frac{2}{m-1}}}, \quad (14)$$

$$\mathbf{c}_j = \frac{\sum_{i=1}^N u_{ij}^m \mathbf{x}_i}{\sum_{i=1}^N u_{ij}^m}, \quad (15)$$

where, u_{ij} is the membership value of vector \mathbf{x}_i belonging to cluster j , \mathbf{c}_j is the center of cluster j , and m is the fuzzifier. The following is the summarization of the FCM algorithm.

Fix the number of clusters C

Initiate prototypes

Do {

Update membership using (14)

Update prototypes using (15)

} Until prototypes stabilize

Now, we briefly explain the Gustafson and Kessel clustering (GK) [55, 56]. The center and membership update equations are similar to equations (14) and (15), but the distance is computed as

$$d^2(\mathbf{x}_j, \mathbf{c}_i) = |\Sigma_i|^{\frac{1}{p}} (\mathbf{x}_j - \mathbf{c}_i)^t \Sigma_i^{-1} (\mathbf{x}_j - \mathbf{c}_i), \quad (16)$$

$$\text{where } \Sigma_i = \frac{\sum_{j=1}^n u_{ji}^m (\mathbf{x}_j - \mathbf{c}_i)^t (\mathbf{x}_j - \mathbf{c}_i)}{\sum_{j=1}^n u_{ji}^m}. \quad (17)$$

However, for some data sets, the covariance matrix might be singular. Hence, the covariance is updated as [57]

$$\Sigma_i = (1 - \gamma)\Sigma_i + \gamma|\Sigma_0|^{\frac{1}{p}} \mathbf{I}, \quad (18)$$

where Σ_0 is a covariance matrix of the whole data set. Then eigenvectors and eigenvalues are computed from Σ_i . Suppose $\lambda_{ik}^{\max} = \max(\lambda_{ik})$, for $k = 1, 2, \dots, p$, set

$$\lambda_{ik}^{\text{new}} = \frac{\lambda_{ik}^{\max}}{\beta}, \quad \forall_k \text{ for which } \frac{\lambda_{ik}^{\max}}{\lambda_{ik}} > \beta. \quad (19)$$

Finally, Σ_i is recomputed using

$$\Sigma = \mathbf{V}\mathbf{\Lambda}^{\text{new}}\mathbf{V}^t. \quad (20)$$

In our experiment, we set $\gamma = 0.5$ and $\beta = 10^{15}$. The GK algorithm is similar to that of the FCM.

Again, for the Gath and Geva clustering (GG) [58], the center and membership update equations are similar to equations (14) and (15). The distance is computed as

$$d^2(\mathbf{x}_j, \mathbf{c}_i) = \frac{|\Sigma_i|^{\frac{1}{2}}}{P_i} \exp\left(\frac{(\mathbf{x}_j - \mathbf{c}_i)^t \Sigma_i^{-1} (\mathbf{x}_j - \mathbf{c}_i)}{2}\right), \quad (21)$$

where P_i is a priori probability of cluster i . Again, the covariance matrix might be singular, we use the same strategy as in equations (17) to (20). We also set $\gamma = 0.5$ and $\beta = 10^{15}$. The GG algorithm is similar to the FCM algorithm. For all three algorithms we set $m = 2$.

D. Fuzzy K-Nearest Neighbor

After, we create multi-prototypes, i.e., $\mathbf{C} = \{\mathbf{c}_1^1, \dots, \mathbf{c}_{N_1}^1, \mathbf{c}_1^2, \dots, \mathbf{c}_{N_2}^2, \dots, \mathbf{c}_1^C, \dots, \mathbf{c}_{N_C}^C\}$ where \mathbf{c}_k^j is prototype k in class j and N_j is the number of prototypes in class j , for each action class. We implement the fuzzy K-nearest neighbor [59]. In the algorithm, after the K nearest neighbors are found for vector \mathbf{x} , the membership value of \mathbf{x} in class i is computed as

$$u_i(\mathbf{x}) = \frac{\sum_{j=1}^K u_{ij} \left(\frac{1}{\|\mathbf{x} - \mathbf{c}_j^i\|} \right)^{\frac{2}{m-1}}}{\sum_{j=1}^K \left(\frac{1}{\|\mathbf{x} - \mathbf{c}_j^i\|} \right)^{\frac{2}{m-1}}}, \quad (22)$$

where u_{ij} is the membership value of prototype \mathbf{c}_j^i in class i . Then, the decision is as follow:

\mathbf{x} is assigned to class i if $u_i(\mathbf{x}) > u_j(\mathbf{x})$ for $j \neq i$.

In our experiment, since we know that the prototype represents which class, we set $u_{jq} = 1$ for \mathbf{c}_j^q in class q and 0 for all the other classes. Also, we set $m = 1.5$ in our experiment.

III. EXPERIMENTAL RESULTS

The data set used in this paper is from [33, 60]. The data set consists of several video contents recorded from 4 subjects who perform 4 actions, i.e., standing or walking, sitting or bending, lying and lying forward. Since lying and lying forward are considered as an action of falling, we collapse both actions into one action. We extract several frames from videos and segment the region of interest manually. Then pixels in the region of interest (called silhouette) are set to 1 and the rest is set to 0. Example of the selected frames and their corresponding silhouette images are shown in figure 1. Hence, there are three classes in our experiment, i.e., stand, sit, and lying, each class with 510 manually selected frames. Therefore there are 1530 frames in total. We randomly select 500 frames from each class (1500 frames in total) to be our training data set and the rest 30 frames to be our blind test data set. We implement 10-fold cross validation on the training data set.

The seven features in equations (4) to (10) are computed from manually created silhouette image in each frame. Then, the PCA is implemented with 3PCs and 7PCs selected. The 3PCs is selected based on the CPV $\geq 85\%$ whereas 7PCs is chosen based on CPV $\geq 100\%$. This work is actually inspired by the work of Banerjee *et al.* [61, 62]. They tried to find the sitting and standing frame using fuzzy clustering algorithm. Here, we implement each fuzzy clustering algorithm with 40, 45, 50, 55, and 60 clusters on each class separately to create multi-prototypes for each class. Because PCA features are overlapped between classes and they are spreading within class as shown in figure 2. The multi-prototype algorithm is

chosen to capture a small cluster and cover all the feature vectors in each class.




Fig. 1. Examples of selected frames and their corresponding silhouette images




Fig. 2. (a) First 3 moments and (b) 3 features from PCA (red is for stand, green is for sit and blue is for lying)

Then the FKNN with $K = 1, 3, 5$, and 7 is implemented as a classifier on each set of created multi-prototypes. Tables 1 to 4 show the best and the average correct classification on the validation set for 1, 3, 5, and 7 FKNN, respectively. It can be

seen that the best classification (100%) on the validation set is from the GG with 60 clusters on 3PCs with 5 FKNN (called GG1) and from the GK with 50 clusters on 7 PCs with 1 FKNN (called GK1). The next highest correct classification (99.33%) is from the FCM with 60 clusters on 7PCs with 7 FKNN (called FCM1) and from the GK with 50 clusters on 7 PCs with 7 FKNN (called GK2) as well. We use the set from the four best results on the validation set with the blind test data set shown in tables 5 to 8. The correct classification rates of the blind test data set from the GG1 and GK1 are 80% and 86.67%, respectively, whereas those from the FCM1 and GK2 are 90%. As we expect, the GG1 and GK1 might be overtrained somehow. From [32], they report that the correct classification on the training data set is around 98.06%. Although, we cannot directly compare the result, our result is still comparable with that.

TABLE I. CORRECT CLASSIFICATION ON VALIDATION SET USING FKNN WITH 1 NN

#PCs	# of prototypes in each class	FCM		GK		GG	
		Avg.	Best	Avg.	Best	Avg.	Best
3	40	93.13	<u>97.33</u>	93.67	96.00	93.73	96.00
	45	93.20	96.00	93.40	96.00	93.40	96.67
	50	94.00	95.33	93.80	96.00	93.67	96.67
	55	93.80	96.67	94.20	96.67	93.67	96.00
	60	94.40	96.00	94.07	<u>98.00</u>	94.13	<u>97.33</u>
7	40	95.33	98.00	95.47	98.00	95.40	97.33
	45	95.20	<u>98.67</u>	95.80	97.33	95.47	96.67
	50	95.87	96.67	95.87	<u>100.00</u>	95.67	98.67
	55	95.93	97.33	95.87	98.00	95.93	<u>99.33</u>
	60	95.93	<u>98.67</u>	96.00	97.33	96.20	<u>99.33</u>

TABLE II. CORRECT CLASSIFICATION ON VALIDATION SET USING FKNN WITH 3 NN

#PCs	# of prototypes in each class	FCM		GK		GG	
		Avg.	Best	Avg.	Best	Avg.	Best
3	40	93.33	95.33	93.53	96.00	93.47	96.00
	45	93.27	96.67	93.80	96.00	93.73	96.00
	50	93.73	96.67	94.07	<u>97.33</u>	93.87	95.33
	55	93.87	<u>97.33</u>	94.40	<u>97.33</u>	93.87	<u>98.00</u>
	60	94.44	96.00	94.33	96.67	94.53	<u>98.00</u>
7	40	95.53	<u>98.00</u>	95.93	98.00	96.13	97.33
	45	95.53	<u>98.00</u>	95.73	98.00	95.80	97.33
	50	96.27	<u>98.00</u>	96.27	<u>98.67</u>	95.93	98.00
	55	96.20	97.33	96.27	<u>98.67</u>	96.27	98.00
	60	95.93	<u>98.00</u>	96.33	98.00	96.67	<u>99.33</u>

For one's curiosity, we also implement this multi-prototype setting with the regular K-nearest neighbor (KNN) with 1, 3, 5, and 7. However, 1 FKNN is actually 1KNN because of the method we set the membership u_{ij} in equation (22). Therefore, the GK1 is also the best in the validation set but gives 86.67% on the blind test data set. Hence, the next best algorithm is from the GG with 40 clusters on 7 PCs with 3 KNN (called GG2) and from the GK with 55 clusters on 7 PCs with 3 KNN (called GK3). Tables 9 and 10 show the confusion matrices from GG2 and GK3 on the blind test data set, respectively. The GG2 and GK3 yield 83.33% and 86.67% correct classification rates on blind test data set, respectively. As we expect, the FKNN performs better than the KNN.

TABLE III. CORRECT CLASSIFICATION ON VALIDATION SET USING FKNN WITH 5 NN

#PCs	# of prototypes in each class	FCM		GK		GG	
		Avg.	Best	Avg.	Best	Avg.	Best
3	40	93.33	95.33	93.60	96.00	93.67	97.33
	45	93.27	96.67	93.67	96.67	93.67	99.33
	50	93.53	96.00	94.07	96.00	93.67	98.67
	55	94.00	<u>97.33</u>	94.27	97.33	93.87	98.00
	60	94.80	96.67	94.27	<u>98.00</u>	94.33	<u>100.00</u>
7	40	95.47	98.00	95.80	<u>98.67</u>	95.93	96.00
	45	95.53	<u>98.67</u>	95.93	<u>98.67</u>	96.00	97.33
	50	96.13	98.00	96.40	<u>98.67</u>	96.07	96.67
	55	96.13	98.00	96.40	98.67	96.47	96.00
	60	96.00	98.00	96.40	98.00	96.60	<u>98.00</u>

TABLE IV. CORRECT CLASSIFICATION ON VALIDATION SET USING FKNN WITH 7 NN

#PCs	# of prototypes in each class	FCM		GK		GG	
		Avg.	Best	Avg.	Best	Avg.	Best
3	40	93.13	95.33	93.53	96.00	93.53	96.00
	45	93.07	96.00	93.80	96.67	93.47	97.33
	50	93.60	96.00	93.93	<u>97.33</u>	93.60	95.33
	55	93.93	<u>96.67</u>	94.20	96.67	93.87	96.00
	60	94.27	96.00	94.20	<u>97.33</u>	93.93	<u>98.00</u>
7	40	95.47	98.67	95.73	98.67	95.73	97.33
	45	95.40	98.00	95.93	98.00	95.87	97.33
	50	96.07	98.00	96.20	<u>99.33</u>	95.80	<u>99.33</u>
	55	96.13	97.33	96.33	98.67	96.53	98.67
	60	96.00	<u>99.33</u>	96.27	98.67	96.60	98.67

TABLE V. CONFUSION MATRIX OF THE BLIND TEST DATA SET FROM GG WITH 60 CLUSTERS ON 3PCs WITH 5 FKNN \rightarrow 80%

Actual action	Algorithm's output		
	Stand(including walk)	Sit(including bend)	Lying
Stand (including walk)	9	0	1
Sit (including bend)	0	10	0
Lying	5	0	5

TABLE VI. CONFUSION MATRIX OF THE BLIND TEST DATA SET FROM GK WITH 50 CLUSTERS ON 7PCs WITH 1 FKNN \rightarrow 86.67%

Actual action	Algorithm's output		
	Stand (including walk)	Sit (including bend)	Lying
Stand (including walk)	10	0	0
Sit (including bend)	0	10	0
Lying	4	0	6

TABLE VII. CONFUSION MATRIX OF THE BLIND TEST DATA SET FROM FCM WITH 60 CLUSTERS ON 7PCs WITH 7 FKNN \rightarrow 90%

Actual action	Algorithm's output		
	Stand (including walk)	Sit (including bend)	Lying
Stand (including walk)	10	0	0
Sit (including bend)	0	9	1
Lying	2	0	8

TABLE VIII. CONFUSION MATRIX OF THE BLIND TEST DATA SET FROM GK WITH 50 CLUSTERS ON 7PCs WITH 7 FKNN \rightarrow 90%

Actual action	Algorithm's output		
	Stand (including walk)	Sit (including bend)	Lying
Stand (including walk)	10	0	0
Sit (including bend)	0	10	0
Lying	3	0	7

TABLE IX. CONFUSION MATRIX OF THE BLIND TEST DATA SET FROM GG WITH 40 CLUSTERS ON 7PCs WITH 3 KNN \rightarrow 83.33%

Actual action	Algorithm's output		
	Stand (including walk)	Sit (including bend)	Lying
Stand (including walk)	10	0	0
Sit (including bend)	0	10	0
Lying	5	0	5

TABLE X. CONFUSION MATRIX OF THE BLIND TEST DATA SET FROM GK WITH 55 CLUSTERS ON 7PCs WITH 3 KNN \rightarrow 86.67%

Actual action	Algorithm's output		
	Stand (including walk)	Sit (including bend)	Lying
Stand (including walk)	10	0	0
Sit (including bend)	0	10	0
Lying	6	0	4

IV. CONCLUSION

In this paper, we implement a human detection system using the fuzzy clustering algorithm with the fuzzy K-nearest neighbor. In particular, the seven features ($\phi_1 - \phi_7$) of the Hu moment invariants are computed. Then principal component analysis is utilized to select the principal components. The fuzzy clustering algorithm (either the fuzzy C-means (FCM), Gustafson and Kessel (GK), or Gath and Geva (GG)) is implemented on each class to select prototypes representing the class. Finally, the fuzzy K-nearest neighbor (FKNN) is utilized as a classifier. From the result, we found that the GG with 60 clusters on 3PCs with 5 FKNN and the GK with 50 clusters on 7 PCs with 1 FKNN produce 100% correct classification on the validation set. But, they yield 80% and 86.67% on the blind test data set. This might be because of the overtraining. However, the FCM with 60 clusters on 7PCs with 7 FKNN and the GK with 50 clusters on 7 PCs with 7 FKNN give 99.33% correct classification. They also produce 90% correct classification on the blind test data set. When the K-nearest neighbor is utilized instead of fuzzy K-nearest neighbor, the result is deteriorated.

Although, this system can detect standing or walking, sitting or bending and lying or lying forward in each frame, it is not a complete human action detection system. We are expecting to embed this system into our fully automated system in the future work.

REFERENCES

- [1] X. Ji, and H. Liu, "Advance in view-invariant human motion analysis: A review," *IEEE Transaction on System, Man, and Cybernetic, Part C: Applications and Reviews*, Vol. 40, No. 1, pp. 13-24, January 2010.
- [2] D. Weinland, R. Ronfrad, and E. Boyer, "A server of vision-baed methods of action representation, segmntation and recognition," *Computer Vision and Image Understanding*, Vol. 115, No. 2, pp. 224-241, February 2011.
- [3] "WHO Global Report on Falls Prevention in Older Age", *World Health Organization*, 2007.
- [4] J. Yamato, J. Ohya, and K. Ishii, "Recognition human action in time-sequential images using hidden mokov model," in *Proceedings IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pp. 379-385, 1992.
- [5] Q. Zhou, S. Yu, X. Wu, Q. Gao, C. Li, and Y. Xu, "HMMs-based human action recognition for an intelligent household surveillance robot," in *Proceedings of IEEE International Conference on Robotics and Biomimetics*, pp. 2295-2300, 2009.
- [6] L. Wang, and D. Suter, "Recognizing human activities from silhouettes: Motion subspace and factorial discriminative graphical model," in *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1-8, 2007.

- [7] H. Yu, G. Sun, W. Song, and X. Li, "Human motion recognition based on neural network," in *Proceedings International Conference on Communications, Circuits and Systems*, pp. 979-982, 2005.
- [8] J. Rittscher, and A. Blake, "Classification of human body motion," in *Proceeding International Conference on Computer Vision*, pp. 634-639, 1999.
- [9] R. V. Babu, and K. R. Ramakrishnan, "Recognition of human actions using motion history information extracted from the compressed video," *Image and Vision Computing*, Vol. 22, No. 8, pp. 597-607, August 2004.
- [10] S. Danafar, and N. Gheissari, "Action recognition for surveillance applications using optic flow and SVM," *Proceedings Asian Conference on Computer Vision*, pp. 457-466, 2007.
- [11] Y. Wang, K. Huang, and T. Tan, "Human activity recognition based on R transform," in *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1-8, 2007.
- [12] A. F. Bobick, and J. W. Davis, "The recognition of human movement using temporal templates," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol. 23, No. 3, pp. 257-267, March 2001.
- [13] A. Karahoca, and M. Nurullahoglu, "Human motion analysis and action recognition," in *1st WSEAS International Conference on Multivariate Analysis and its Application in Science and Engineering*, pp. 156-161, 2008.
- [14] H. Meng, N. Pears, and C. Bailey, "A human action recognition system for embedded computer vision application," in *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1-6, 2007.
- [15] D. Weinland, R. Ronfard, and E. Boyer, "Free viewpoint action recognition using motion history volumes," *Computer Vision and Image Understanding*, Vol. 104, No. 2, pp. 249-257, November 2006.
- [16] D. Weinland, R. Ronfard, and E. Boyer, "Automatic discovery of action taxonomies from multiple views," in *IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pp. 1639-1645, 2006.
- [17] M. C. Roh, H. K. Shin, and S. W. Lee, "View-independent human action recognition with Volume Motion Templateon single stereo camera," *Pattern Recognition Letters*, Vol. 31, No. 7, pp. 639-647, May 2010.
- [18] M. Blank, L. Gorelick, E. Shechtman, M. Irani, and R. Basri, "Actions as space-time shapes," in *IEEE International Conference on Computer Vision*, pp. 1395-1402, 2005.
- [19] A. Yilmaz, and M. Shah Actions, "A differential geometric approach to representing the human actions," *Computer Vision and Image Understanding*, Vol. 109, No. 3, pp. 335-351, March 2008.
- [20] F. Lv, and R. Nevatia, "Single view human action recognition using key pose matching and Viterbi Path searching," in *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1-8, 2007.
- [21] D. Weinland, E. Boyer, and R. Ronfard, "Action recognition from arbitrary views using 3D exemplars," in *IEEE International Conference on Computer Vision*, pp. 1-7, 2007.
- [22] A. S. Ogale, A. Karapurkar, G. G. Filho, and Y. Aloimonos, "View invariant identification of pose sequences for action recognition," in *VACE*, 2004.
- [23] M. A. Naiel, M. M. Abdelwahab, and W. B. Mikhael, "Human action recognition employing 2DPCA and VQ in the spatio-temporal domain," in *IEEE International NEWCAS Conference*, pp. 381-384, 2010.
- [24] M. A. Naiel, M. M. Abdelwahab, and W. B. Mikhael, "Human action recognition employing TD2DPCA and VQ," in *IEEE International Midwest Symposium on Circuits and Systems*, pp. 624-627, 2010.
- [25] M. A. Naiel, M. M. Abdelwahab, and M. El-Saban, "Multi-view human action recognition system employing 2DPCA," in *Proceedings IEEE Workshop on Applications of Computer Vision*, pp. 270-275, 2011.
- [26] L. Liu, L. Shao, and P. Rockett, "Human action recognition based on boosted feature selection and naive Bayes nearest-neighbor classification," *Signal Processing*, July 2012.
- [27] L. Liu, L. Shao, and P. Rockett, "Boosted key-frame selection and correlated pyramidal motion-feature representation for human action recognition," *Pattern Recognition*, October 2012.
- [28] S. Pehlivan, and P. Duygulu, "A new pose-based representation for recognizing actions from multiple cameras," *Computer Vision and Image Understanding*, Vol. 115, No. 2, pp. 140-151, February 2011.
- [29] M. B. Holte, T. B. Moeslund, N. Nikolaidis, and I. Pitas, "3D human action recognition for multi-view camera systems," in *International Conference on 3D Imaging, Modeling, Processing, Visualization and Transmission*, pp. 342-349, 2011.
- [30] C. Chan and H. Liu, "Fuzzy Qualitative Human Motion Analysis," *IEEE Transactions of Fuzzy Systems*, Vol 17, No. 4, pp. 851 – 862, August 2009.
- [31] Z. A. Khan, and W. Sohn "Feature extraction and dimensions reduction using R transform and Principal Component Analysis for abnormal human activity recognition," in *International Conference on Advanced Information Management and Service*, pp. 253-258, 2010.
- [32] Z. A. Khan, and W. Sohn, "Abnormal human activity recognition system based on R-transform and kernel discriminant technique for elderly home care," *IEEE Transactions on Consumer Electronics*, Vol. 57, No. 4, pp. 1843-1850, 2011.
- [33] M. Shoaib, R. Dragon, and J. Ostermann, "View-invariant fall detection for elderly in real home environment," in *Fourth Pacific-Rim Symposium on Image and Video Technology*, pp. 52-57, 2010.
- [34] D. H. Hung and H. Saito, "Fall detection with two cameras based on occupied area", *Proc. of 18th Japan and Korea Joint Workshop Frontiers in Computer Vision*, pp. 33 - 39, Yokohama, Japan, Feb. 2012.
- [35] Z. Z. Htike, S. Egerton, and K. Y. Chow, "A monocular view-invariant fall detection system for the elderly in assisted home environments," *2011 Seventh International Conference on Intelligent Environments*, pp. 40 – 46., 2011.
- [36] B. Mirmahboub, S. samavi, N. Karimi, and S. Shirani, "Automatic monocular system for human fall detection based on variations in silhouette area", *IEEE Transactions on Biomedical Engineering*, Vol. 60 (2), pp. 427 – 436, 2013.
- [37] E. Auvinet, F. Multon, A. Saint-Arnaud, J. Rousseau, and J. Meunier, "Fall detection with multiple cameras: An occlusion-resistant method based on 3-D silhouette vertical distribution", *IEEE Transactions on Information Technology in Biomedicine*, Vol. 15, No. 2, pp. 290 – 300, March 2011.
- [38] L. Hazelhoff, J. Han, and P. H. With, "Video-based fall detection in the home using principal component analysis," in *Proceedings of the 10th International Conference on Advanced Concepts for Intelligent Vision Systems (ACIVS)*, Juan-les-Pins, France, pp. 298-309, Oct. 2008
- [39] G. Wu, "Distinguishing fall activities from normal activities by velocity characteristics," *Journal of Biomechanics*, Vol. 33, No. 11, pp. 1497–1500, 2000.
- [40] J. Tao, M. Turjo, M-F.Wong, M. Wang, and Y-P. Tan, "Fall incidents detection for intelligent video surveillance," in *Fifth International Conference on Information, Communications and Signal Processing (ICICS)*, Bangkok, Thailand, pp. 1590-1594, Dec. 2005,
- [41] B. Huang, G. Tian, and X. Li, "A method for fast fall detection," in *Proceedings of the 7th World Congress on Intelligent Control and Automation (WCICA)*, Chongqing, China, pp. 3619-3623, Jun. 2008.
- [42] M. Yu, S. M. Naqvi, J. Chambers, "A robust fall detection system for the elderly in a Smart Room," in *IEEE International Conference on Acoustics Speech and Signal Processing (ICASSP)*, Dallas, TX, USA, pp. 1666-1669, Mar. 2010.
- [43] A. Zweng, S. Zambanini, and M. Kampel, "Introducing a statistical behavior model into camera-based fall detection," in *Proceedings of the 6th international conference on Advances in visual computing (ISVC)*, Las Vegas, NV, USA, pp. 163-172, Nov. 2010.
- [44] M. Yu, S. M. Naqvi, A. Rhuma, and J. Chambers, "Fall detection in a smart room by using a fuzzy one class support vector machine and imperfect training data," in *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, Prague, Czech Republic, pp. 1833-1836, May 2011.
- [45] G. Debard, P. Karsmakers, M. Deschodt, E. Vlaeyen, J. V. D. Bergh, E. Dejaeger, K. Milisen, T. Goedemé, T. Tuytelaars, and B. Vanrumste, "Camera based fall detection using multiple features validated with real life video," in *7th International Conference on Intelligent Environments*, Nottingham, UK, pp. 441-450, Jul. 2011.
- [46] D. Anderson, R. H. Luke, J. M. Keller, M. Skubic, M. J. Rantz, and M. A. Aud, "Linguistic summarization of video for fall detection using

- voxel person and fuzzy logic”, *Computer Vision and Image Understanding*, Vol 113, pp. 80 – 89, 2009.
- [47] D. Anderson, R. H. Luke, J. M. Keller, M. Skubic, M. J. Rantz, and M. A. Aud, “Modeling human activity from voxel person using fuzzy logic”, *IEEE Transactions on Fuzzy Systems*, Vol. 17, No. 1, pp 39 – 49, 2009.
- [48] A. Iosifidis, A. Tefas, N. Nikolaidis, and I. Pitas, “Multi-view human movement recognition based on fuzzy distances and linear discriminant analysis,” *Computer Vision and Image Understanding*, Vol. 116, No. 3, pp. 347-360, March 2012.
- [49] B. Mirmahboub, S. Samavi, and N. Karimi, “View-invariant fall detection system based on silhouette area and orientation”, *2012 IEEE International Conference on Multimedia and Expo*, pp. 176 – 181, 2012.
- [50] M. K. Hu, “Visual pattern recognition by moment invariants,” *IRE Trans. on Infomation Theory*, Vol. 8, No. 2, pp. 179-187, Febuary 1962.
- [51] J. S. NOH, and K. H. RHEE, “Palmpoint identification algorithm using Hu invariant moments and Otsu binarization,” in *Annual International Conference on Computer and Information Science*, 2005, pp. 94- 99.
- [52] D. Garcia-Alvarez, “Fault detection using principal component analysis (PCA) in a wastewater treatment plant (WWTP),” in *International Student's Scientific Conference*, pp. 55-59, 2009.
- [53] J. C. Dunn, “A fuzzy relative of the ISODATA process and its use in detecting compact well-separated clusters,” *Journal of Cybernetics* 3, pp. 32-57, 1973.
- [54] J. C. Bezdek, *Pattern Recognition with Fuzzy Objective Function Algoritms*, Plenum Press, New York, 1981.
- [55] D. E. Gustafson, and W. C. Kessel, “Fuzzy clustering with a fuzzy covariance matrix,” *In Proc. IEEE Conf. Decision Contr.*, pp. 761-766, 1979.
- [56] H-C. Liu, B-C.Jeng, J-M.Yih, and Y-K. Yu, “Fuzzy C-means algorithm based on standard Mahalanobis distances,” in *Proceedings of the International Symposium on Information Processing*, pp. 422-427, 2009.
- [57] R. Babuka, P. J. van der Veen, and U Kaymak, “Improved covariance estimation for Gustafson-Kessel clustering,” in *Proceedings IEEE International Conference on Fuzzy Systems*, pp. 1081-1085, 2009.
- [58] I. Gath, and G. Geva, “Unsupervised optimal fuzzy clustering,” *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol. 11, pp. 773-781, Jul. 1989.
- [59] J.M. Keller, M.R. Gray and J.A. Givens, “A fuzzy K-nearest neighbor algorithm”, *IEEE Transactions on Systems, man and Cybernetics*, Vol. SMC-15 (4), pp. 580 – 585, 1985.
- [60] <http://www.tnt.uni-hannover.de/~shoaib/fall.html>.
- [61] T. Banerjee, J. M. Keller, M. Skubic, and C. Abbott, “Sit-to-stand detection using fuzzy clustering techniques,” in *IEEE International Conference on Fuzzy Systems*, pp. 1-8, 2010.
- [62] T. Banerjee, J. M. Keller, Z. Zhou, M. Skubic, and E. Stone, “Activity Segmentation of Infared Images Using Fuzzy Clustering Techniques”, *Proceedings, World Conference on Soft Computing*, San Francisco, CA, May, 2011, pp. 133-138.