Contextualizing Fairness: Extending p-Mean Social Welfare to Linear Bandits

CS6106 Multi-Agent Machine Learning, Course Project Report (Team XX)
Kunj Bhesaniya (23B0995), Dhruvraj Merchant (23B1041), IIT Bombay
November 2026

Code: https://github.com/KunjBhesaniya10/pmean-linear-bandits

1. Introduction

In a normal multi-armed bandit the goal is to maximise total reward, i.e. minimise the average regret. When every round is a different person (a patient in a trial, a user getting a recommendation) this objective does not care who gets a bad round. An algorithm can give a few people very bad arms early on and still have small average regret.

p-mean social welfare fixes this by replacing the arithmetic mean of the per-round expected rewards with the power mean M_p. With $p = 1$ we get back the usual utilitarian objective, $p = 0$ gives the geometric mean (Nash social welfare), and $p \to -\infty$ only looks at the worst-off round (Rawlsian / egalitarian). So one parameter covers the whole range of fairness notions.

Our base paper is Sarkar, Pandey and Ray Chowdhury (2025), *"Revisiting Social Welfare in Bandits: UCB is (Nearly) All You Need"*. They show that a very simple algorithm, Welfarist-UCB (uniform exploration with a data-adaptive stopping rule, then plain UCB), gets near-optimal p-mean regret for every p, with weaker assumptions than earlier work (Barman et al. 2023, Krishna et al. 2025).

That paper is for plain multi-armed bandits, where arms have no features. In most real uses like recommendation, each option comes with side information and the set of options changes with the user. So in this project we did two things:

1. **Reproduced** the Welfarist-UCB experiments (a)–(f) of the base paper from scratch.
2. **Tried to extend** the explore-then-UCB idea to *contextual* linear bandits, where the candidate set changes every round, and compared two ways of doing the exploration phase on synthetic data and on MovieLens-1M.

While we were working on this, the same authors put out FairLinBandit (Sarkar et al. 2026), which extends Welfarist-UCB to linear bandits with a *fixed* arm set. Their method needs a John ellipsoid and a D-optimal design computed over the whole arm set before the start. That cannot be done when the candidate set is new every round, which is the case we look at. So our work should be read as an empirical study of the contextual case, not as a new algorithm with guarantees. We do not have a regret bound for our adaptations.

2. Problem Setup

2.1 Multi-armed bandit with p-mean regret

There are k arms with unknown means $\mu_1, \ldots, \mu_k \geq 0$ and σ^2-sub-Gaussian rewards. Let $\mu^\star = \max_i \mu_i$. At round $t = 1..T$ the learner pulls I_t using only past observations. The p-mean regret is

$$R_T^p = \mu^\star - \left(\frac{1}{T}\sum_{t=1}^{T}\mathbb{E}[\mu_{I_t}]^p\right)^{1/p}, \qquad NR_T = \mu^\star - \left(\prod_{t=1}^{T}\mathbb{E}[\mu_{I_t}]\right)^{1/T} \ (p=0).$$

R_T^p increases as p decreases, so smaller p is a harder (fairer) objective. For $p \le 0$ one round with expected reward close to zero can push the welfare towards zero, and this is exactly why plain UCB has no guarantee here.

2.2 Linear contextual bandit

In round t a user u_t arrives and is shown a candidate set $\mathcal{C}_t$ of K items. The feature of item i for user u is $x = z_u \otimes y_i$ (Kronecker product of user and item features) and the expected reward is $\langle x, \theta^\star \rangle$ for an unknown $\theta^\star \in \mathbb{R}^d$. Since the best reward now changes every round, we measure regret against the per-round optimum:

$$R_T^p = M_p(r_1^\star, \ldots, r_T^\star) - M_p(\mathbb{E}[r_1], \ldots, \mathbb{E}[r_T]), \qquad r_t^\star = \max_{a \in \mathcal{C}_t} \langle x_a, \theta^\star \rangle.$$

When there is one user and a fixed arm set this is the same as the normal linear bandit p-mean regret. On MovieLens we also report a **normalised group utility** for each demographic group g: the sum of $\mathbb{E}[r_t]$ over rounds where a member of g arrived, divided by the same sum for the optimal policy (1.0 is perfect). The group welfare is M_{-2} of these 30 group utilities.

3. Approach

3.1 Welfarist-UCB (base paper)

- **Phase I:** in every block of k rounds pull the arms in a fresh random permutation. Each round has expected reward at least $\mu^\star/k$, so welfare never collapses.
- **Stopping rule:** with $w_i = 2\sqrt{2\sigma^2 \log T/n_i}$, stop the first time some arm has $\hat{\mu}_i > w_i$ and $n_i > 192\, p_a^2 \sigma^2 \log T/(\hat{\mu}_i - w_i)^2$, where $p_a = 1$ for $p \ge -1$ and $p_a = p$ otherwise. Basically: the best arm's LCB must be positive and large compared to its own width. For $p < -1$ exploration grows like p^2.
- **Phase II:** standard UCB with index $\hat{\mu}_i + w_i$.

Baselines from the paper: NCB (Barman et al. 2023) for Nash regret and Explore-then-UCB (Krishna et al. 2025), which explores for a fixed p-dependent number of rounds.

3.2 Why the direct linear version is not obvious

FairLinBandit handles the linear case by mixing (i) samples from a distribution centred at the John ellipsoid of the arm set, which guarantees a reward floor of about $\mu^\star/(d+1)$, and (ii) a D-optimal design, which makes all directions equally well estimated. Both are computed once over the fixed arm set. In our setting the arm set $\mathcal{C}_t$ depends on the user and is new each round, so neither object exists in advance. Also, uniform sampling over arms is no longer uniform over *feature directions*: if only a few items use some coordinate, that direction is rarely seen.

So the question we tried to answer was: how should Phase I and the stopping rule look when we cannot precompute any geometry?

3.3 Adaptation 1: uniform transfer (Welfarist-UCB unchanged)

This is the most direct copy of Welfarist-UCB.

- **Phase I:** pick $a_t \sim \text{Uniform}(\mathscr{C}_t)$.
- **Stopping:** using the ridge estimate $\hat{\theta}_t$ and design matrix $V_t = \lambda I + \sum_s x_s x_s^\top$, stop as soon as some candidate satisfies

$$\text{LCB}(x_a) = \langle x_a, \hat{\theta}_t \rangle - \beta \| x_a \|_{V_t^{-1}} > 0 \quad \text{and} \quad \text{LCB}(x_a) \geq \kappa |p_a| \beta \| x_a \|_{V_t^{-1}} .$$

  The width $\sqrt{1/n_i}$ just becomes $\beta \| x_a \|_{V_t^{-1}}$. We use $\beta = \sigma\sqrt{2 \log T} + \sqrt{\lambda} S$ (the Abbasi-Yadkori radius without the $d \log t$ term, as most practical LinUCB code does; with that term nothing ever stops in our horizons).
- **Phase II:** LinUCB, warm-started with V_τ and $\hat{\theta}_\tau$ from Phase I.

3.4 Adaptation 2: 50/50 with greedy D-optimal steps

Same stopping rule and same Phase II, only Phase I changes. In each exploration round, with probability 1/2 we take a uniform candidate (to keep some reward floor like in Welfarist-UCB), and with probability 1/2 we take

$$a_t = \arg \max_{a \in \mathscr{C}_t} \| x_a \|_{V_t^{-1}} ,$$

the candidate whose prediction we are least sure about. Adding this x_a gives the largest increase of $\det V_t$, so it is a greedy one-step D-optimal design over whatever candidates we have right now. The idea is the same as the D-optimal half of FairLinBandit, but it needs nothing precomputed. The intuition is that the most uncertain candidates are usually the ones lying in rare feature directions, so the algorithm learns those directions on purpose rather than waiting to hit them by chance.

The cost is that the max-width candidate can have low reward, so in easy instances where uniform sampling already covers everything, the extra steps are just wasted rounds.

4. Implementation

Everything is written from scratch in Python (package `pmlb`), with the inner loops compiled by Numba (`@njit`), since experiment (a) alone is 50×10^7 rounds per algorithm.

- `src/pmlb/welfare.py`: p-mean, running p-mean, p-mean regret curves, contextual regret and group utilities.
- `src/pmlb/mab/algorithms.py`: Welfarist-UCB, NCB and Explore-then-UCB kernels. Constants follow the authors' public code (e.g. the stopping constant is $800 p_a^2 \sigma^2 \log T$ in their code, vs 192 in the paper text).
- `src/pmlb/linear/algorithms.py`: the two adaptations and LinUCB. V_t^{-1} is kept with $O(d^2)$ Sherman–Morrison updates instead of re-inverting. Widths skip zero coordinates, which matters for MovieLens where x is sparse ($d = 180$).
- `src/pmlb/linear/lin_nash.py`, `fair_lin_bandit.py`: our implementations of LinNash (Sawarni et al. 2023) and FairLinUCB (Sarkar et al. 2026) for fixed arm sets. They are in the repo and tested, but they are not in the final experiments because they cannot run when the candidate set changes per round (see Section 6).
- `src/pmlb/data/movielens.py`: builds the semi-synthetic MovieLens bandit (below).
- `experiments/`: one script per set of results; `scripts/run_all_experiments.py` runs everything.

- `tests/`: 44 pytest tests (p-mean identities and monotonicity in p, Sherman–Morrison against direct inversion, kernels only pick real candidates and are reproducible under a seed, exploration grows as p decreases, MovieLens group encoding). All pass in about 20 s.

All runs are seeded and we checked that rerunning gives exactly the same numbers.


MovieLens-1M environment. Reward is "user likes the movie" (rating ≥ 4), a Bernoulli reward. User features z (30-dim) are one-hot gender (2), age band (7) and occupation (21), so every demographic group has its own coordinates and small groups (e.g. 17 farmers, 0.3% of rounds) are rare feature directions. Item features y (6-dim) are a bias, the movie's like rate, and a rank-4 SVD embedding of the centred like matrix. $\theta^{\star}$ (180-dim) is the ridge fit of like $\sim z_u \otimes y_i$ over all ratings of the 300 most-rated movies, so the environment is exactly linear and its expected rewards are the fitted like probabilities (all inside (0,1), the code checks this). Each round a uniformly random user arrives with 20 random candidate movies, $T = 50,000$, 20 runs.

5. Results

5.1 Reproduction of Welfarist-UCB (k = 50, 50 runs each)

Instances are drawn exactly like the authors' code (`np.random.seed(42)`), so the arm means are the same as theirs.

Expt	Setting	Algorithm	Regret at T	Phase I length τ
(a)	Bernoulli, $p = 0$, $T = 10^7$	NCB	0.225	3,349,088
		Welfarist-UCB	**0.062**	828,816
(b)	Gaussian $\sigma = 20$, $p = 0$, $T = 10^6$	NCB	1.75	2,487
		Welfarist-UCB	**0.182**	266
(c)	Gaussian, $p = 0.5$	Explore-then-UCB	45.3	79,955
		Welfarist-UCB	**0.16**	266
(d)	Gaussian, $p = -0.5$	Explore-then-UCB	18.1	22,365
		Welfarist-UCB	**0.22**	266
(e)	Gaussian, $p = -1.5$	Explore-then-UCB	3.85	3,163
		Welfarist-UCB	**0.72**	592




Experiment (a): Nash regret of Welfarist-UCB vs NCB on Bernoulli arms.

Our numbers match the paper's figures: Welfarist-UCB beats NCB by about 4x in (a) and 10x in (b), and beats Explore-then-UCB at all three p, by two orders of magnitude for $p \geq -0.5$. The gap gets smaller at $p = -1.5$ because the stopping rule now has $p_a^2 = 2.25$ and explores longer.

Effect of p (experiment f).

p	**1**	**0**	**−1**	**−2**	**−5**
Regret at T	0.13	0.17	0.24	1.29	27.0
τ	276	273	275	1,010	5,922

For $p \geq -1$ the stopping rule does not depend on p, so τ is basically constant. Below −1 it scales with p^2 (3.7x at $p = -2$, 21x at $p = -5$), which is the "no free fairness" cost the paper predicts.




Experiment (f): Welfarist-UCB regret for different p.

5.2 Synthetic linear experiments (Nash regret, $p = 0$, $\kappa = 10$, 15 runs)

Experiment 1, benign arms ($d = 6$, $K = 50$, $T = 50,000$). Features and $\theta^\star$ are positive and random, so every direction is common; means lie in [0.65, 0.96].

	τ	Nash regret at $t = 10^4$	Nash regret at T
Adaptation 1 (uniform)	2,661	0.045	**0.0146**
Adaptation 2 (50/50 D-opt)	2,812	0.057	0.0169

Both stop early and the regret goes to near zero after the switch to LinUCB. Adaptation 1 is slightly better here. This is what we expected: when all directions are already covered by uniform sampling, the max-width steps just pick lower-reward arms during Phase I, which shows up as the higher plateau of Adaptation 2 before τ.




Experiment 1: benign feature arms.

Experiment 2, rare direction ($d = 6$, $K = 100$, $T = 30,000$). 98 "common" arms only use the first four coordinates and have mediocre means (0.21 to 0.33). Only two arms have weight on the fifth coordinate, and the optimum (0.95) is one of them.

	τ	Nash regret at $t = 10^4$	Nash regret at T
Adaptation 1 (uniform)	15,478	0.645	0.419
Adaptation 2 (50/50 D-opt)	**10,973**	**0.526**	**0.242**

Here Adaptation 2 has about 1.7x lower final regret and stops about 4,500 rounds earlier. With uniform sampling the rare direction is seen in only 2 of every 100 pulls, so no arm becomes certified for a long time (the common arms are too low for the LCB condition with $\kappa = 10$). The max-width steps go straight to the rare direction, so the optimum's LCB grows faster and the rule fires earlier.




Experiment 2: rare niche features.

5.3 MovieLens-1M ($d = 180$, $K = 20$, $T = 50,000$, $\kappa = 1$, 20 runs)

With the paper's $\kappa = 10$ the stopping rule did not fire within 50,000 rounds on MovieLens ($d = 180$ is much bigger than the synthetic $d = 6$), so here we use $\kappa = 1$.

	p used in rule	τ	Aggregate utility	Regret $p = 1$	Regret $p = 0$	Regret $p = -2$	Group welfare M_{-2}
Adaptation 1	0	1,205	0.9494	0.0447	0.0489	0.0650	0.9353
Adaptation 2	0	1,251	0.9500	0.0442	0.0485	0.0633	0.9358
Adaptation 1	−2	2,708	0.9451	0.0485	0.0527	0.0654	0.9318
Adaptation 2	−2	2,681	0.9465	0.0473	0.0521	0.0674	0.9329




MovieLens: Nash regret over time (left) and final p-mean regret (right; $p = -2$ bars use the run with $p = -2$ in the stopping rule).

Both adaptations leave Phase I after a little over 1,000 rounds and then behave almost the same under LinUCB. Adaptation 2 is a tiny bit better on most numbers when run with $p = 0$, and a tiny bit worse on the $p = -2$ regret when run with $p = -2$. Honestly these differences (third decimal) are small and we did not run significance tests, so we read this as "about the same".

Groups. The smallest group, farmers (0.33% of rounds, about 165 rounds per run), gets 0.862 with Adaptation 2 vs 0.855 with Adaptation 1, and is the worst-off group under both. But across all 30 groups Adaptation 2 is

higher on 18 and lower on 12, so it is not a uniform improvement. The worst-off groups for both are small occupations (farmer, unemployed, homemaker, tradesman) and older users, i.e. exactly the rare feature directions.



MovieLens: normalised utility for some demographic groups.

5.4 Summary

- The reproduction works and matches the paper.
- In the contextual linear case, a direct transfer of Welfarist-UCB (Adaptation 1) is already fine when every feature direction is common. Adding greedy D-optimal steps (Adaptation 2) costs a bit there.
- When the good arm sits in a rare direction, Adaptation 2 learns it faster and gets about 1.7x lower Nash regret.
- On MovieLens both are almost tied; the small groups are worst-off under both.

6. Challenges and Learnings

- **Concurrent paper.** Midway through, we found FairLinBandit (Sarkar et al. 2026) by the base paper's authors, which already does the fixed-arm linear case with proofs. We had to rethink what we can actually claim. We decided to keep our goal (p-mean in the contextual setting) and use the paper as related work instead of switching to it, and to be clear that our part is an empirical study without guarantees.
- **Baselines.** At first we also compared against plain UCB / LinUCB, which often had lower p-mean regret on the paper's instances (all arm means are far from zero, so the worst case that Welfarist-UCB protects against never happens). The base paper does not compare with plain UCB, so we removed it and kept comparisons that match the paper's structure. We learned to be careful about what the baseline is supposed to show.
- **LinNash and FairLinUCB need a fixed arm set.** We implemented both, but their design/ellipsoid steps are computed once over the arm set, so they cannot be run on the contextual experiments without changing them into something else. We left them out of the final comparison rather than adapt them ourselves and call it their method.
- **Constants.** The paper-text constant (192) and the reference code constant (800) differ; we followed the code since we were reproducing their figures. $\kappa = 10$ never stops on MovieLens, so we had to use $\kappa = 1$ there, which is a tuning choice, not something we can justify theoretically.

- **Is the 50/50 change justified?** Before the presentation, our first draft results showed the plain transfer beating the 50/50 version, and we did not want to present a change that looked ad hoc. The rare-direction experiment is what justifies it: the extra steps only pay off when some direction is rare. On benign instances they cost a little. We think this trade-off is the honest result.
- **Practical stuff.** Long horizons (10^7) needed Numba; the official MovieLens site was down / blocked for us, so the download script falls back to a GitHub mirror and checks the dataset size (1,000,209 ratings, 6,040 users).
- **Open problem.** A regret bound for p-mean welfare in contextual linear bandits with arbitrary changing candidate sets is still open as far as we know.

7. Team Contributions

[To be filled in by the team: who did what, e.g. paper reading and reproduction, linear adaptations, MovieLens pipeline, experiments, slides, report.]

8. References

1. D. Sarkar, N. Pandey, S. Ray Chowdhury. *Revisiting Social Welfare in Bandits: UCB is (Nearly) All You Need.* arXiv:2510.21312, 2025. Code: github.com/NP-Hardest/UCBisAllYouNeed.
2. D. Sarkar, N. Pandey, S. Ray Chowdhury. *Improved Algorithms for Nash Welfare in Linear Bandits.* ICML 2026, arXiv:2601.22969.
3. S. Barman, A. Khan, A. Maiti, A. Sawarni. *Fairness and Welfare Quantification for Regret in Multi-Armed Bandits.* AAAI 2023.
4. A. Krishna, P. G. John, A. Barik, V. Y. F. Tan. *p-Mean Regret for Stochastic Bandits.* AAAI 2025.
5. A. Sawarni, S. Pal, S. Barman. *Nash Regret Guarantees for Linear Bandits.* NeurIPS 2023.
6. Y. Abbasi-Yadkori, D. Pál, Cs. Szepesvári. *Improved Algorithms for Linear Stochastic Bandits.* NeurIPS 2011.
7. L. Li, W. Chu, J. Langford, R. E. Schapire. *A Contextual-Bandit Approach to Personalized News Article Recommendation.* WWW 2010.
8. T. Lattimore, Cs. Szepesvári. *Bandit Algorithms.* Cambridge University Press, 2020 (Ch. 21–22, optimal design).
9. H. Moulin. *Fair Division and Collective Welfare.* MIT Press, 2004.
10. F. M. Harper, J. A. Konstan. *The MovieLens Datasets: History and Context.* ACM TiiS, 2015.

Appendix A: AI Prompts Used

We used Claude (Anthropic) as an assistant during the project, mainly through a shared project workspace connected to our GitHub repo. Below are the prompts we gave it, copied from the chat history with dates. We cut long pasted parts and a few off-topic bits, but did not reword anything, so spelling is as typed. They are grouped by what they were for. The AI's answers are not included, only short notes in brackets where context is needed.

[Team: prompts used outside this workspace (e.g. other chats used for the final slides or the final code changes, and any prompts by Dhruvraj) still need to be added here.]

A.1 Research and planning

1. (24 Oct) “we are starting with this project, understand and summarize the plan here first”
2. (24 Oct) “which paper implements p mean welfare ?”
3. (24 Oct) “either of berman or sarkar is our base” *[asked it to find and summarise the exact algorithm, stopping rule and experiments of the candidate papers]*
4. (26 Oct) “so our base paper is sarkar at el, and we dont have any github repo, we will have to create a fresh one, and also what dataset will we use ?”
5. (26 Oct) “is movie lens dataset is for linear bandits or normal phase 1 ?”
6. (26 Oct) “cool so phase1 would be reproducing the results, and then extending it to linear setting, then test using both synthetic and actual datasets”
7. (27 Oct) “linear bandits are exlored for only nash regret as per our prof”
8. (28 Oct) “but let’s be honest, if it could be extended then it would already had been done by some researcher, and we wouldn’t just discover something new in 2 day project, we are just doing our independent study of extending it to p means, it will not work most probably as per me”
9. (28 Oct) “can you also start another thread to review this paper and if it is relevant to our extension” *[uploaded arXiv:2601.22969, FairLinBandit]*
10. (28 Oct) “NO, our project’s goal is clear we would not change it, i just want to know how similar is their algorithm to what we did by extending their algorithm, and if the paper’s algo is doing better, we can use it and cite it, but do not change any work just answer the question first”
11. (29 Oct) “Dont just assume or speculate anything, what does it mean that it only handle one fixed arm? The algorithm is for general linear bandits right?”
12. (29 Oct) “I still dont get it what’s the difference bw contextual bandits amd linear bandits”

A.2 Code

13. (27 Oct) “complete the remaining things also, maintain proper directory structure for results, plots etc”
14. (27 Oct) “what is njit(cache=true)”
15. (27 Oct) “dont use phase* names in the code/directory these were just for the planning it should not be in the project dircetory, and also we are implementing the welfarist UCB right ?”
16. (27 Oct) “also how are we implementing linucb from the welfarist algorithm ? and what exactly we are changing in it ? are we following any other reference paper ?”
17. (28 Oct) “what is the plain LinUCB ? is it average reward regret ? and for the normal ucb also the average regret would give better results may be but we are doing the nash regret right ? so why are we comparing it with normal ucb or linucb ? we need to verify the fairness of both right?”
18. (28 Oct) “so is LinUCB’s nash regret better than what we extended ?”
19. (28 Oct) “but then why have they introduced welfarist UCB if the plain UCB is performing better ?”
20. (28 Oct) “so why are we inserting plain UCB ourselved who told you to do that ?”
21. (28 Oct) “yes if paper is not comparing the results with plain UCB why are we ? it does not make sense, and if we remove it, with what will we compare the linear extension results ?” *[then uploaded the LinNash paper so it would be implemented from the paper and not from memory]*
22. (29 Oct) “and who told you to make 2 algorithms ?”
23. (29 Oct) “ok just keep it and labelled as welfarist-UCB unchanged”

A.3 Testing and checking results

24. (26 Oct) “what is this why are there test plan ?” *[about the test plan section in the first PR]*

25. (27 Oct) “why is there a test directory”
26. (27 Oct) “some updates are needed i will clone the repo, review the code and then will follow up from there”
27. (27 Oct) “which movielens data set should i donwload from the source to replace your script method” / “1M enough ?”
28. (27 Oct) “The official MovieLens download is blocked here, so the script falls back to a GitHub mirror of the same 1M ratings. that;s why i was downloading” / “the official movielens website is down that is why i am unable to download from there”
29. (27 Oct) “are all results as expected ?”

A.4 Presentation

30. (29 Oct) “what do we do in the project now for the presentation ? i am confused of what will we present ? what will we show that we did new/different/experimental study type etc given this paper also exists now”
31. (29 Oct) “plain LinUCB does not have fairness right ?? our idea was to extend this fairness p mean to contextual linear bandits at the start, and we also need to provide intuition or idea behind how we tweaked the algorithm and why in that way particularly,”
32. (29 Oct) “why would i even describe this in presentation ? there is no relation of linUCB here ? i would compare it with linNash no ? for p =0? are you even understanding the overall goal of the project, what will we experiment ? what will we compare the results with ? what will we justify etc ?”
33. (29 Oct) “what;s the naive transfer ?”
34. (30 Oct) “this is a DRAFT PRESENTATION (NOT FINAL), the results show that the naive transfer algorithm without introducing any other changes performs better than the 50% probability changes, why is this the case ? and then why did we introduce this changes if the naive is giving better regret ? please research on this honestly, i dont want to present any changes which are not well backed and are ad hoc”

A.5 Report and submission

35. (5 Nov) “review the final code that i have pushed on the remote repo, this is the final code and also review the project presentation pdf that we have already presented to the TA and Profs, so now only report and repo submission is remaining” *[pasted the course submission instructions]* “first review the final code and topics we have kept, and then make a report, and then add some prompts in appendix”