Benchmarking vLLM vs llama.cpp under controlled workloads

What this is: 288 measured runs across 24 backend × model × quantization configurations, on identical prompts, with quality measured separately from performance.

What this is not: a verdict. There is no single number here that makes one of these backends "better". The ranking inverts depending on how much load you put on the card, and the two projects do not even offer the same quantization formats, so for the most part they cannot be compared on identical weights at all.

Executive summary

Question	Answer	Evidence
Fastest single interactive request?	**llama.cpp**	per-token 4.1–20.3 ms vs 5.2–86.7 ms; TTFT 11–48 ms vs 15–116 ms
Fastest under 32 concurrent requests?	**vLLM, decisively**	TTFT 65–135 ms vs 2,970–8,490 ms (30–60×); throughput 1,138–3,233 vs 189–547 tok/s (4–11×)
Which serves more requests inside a latency SLO?	**vLLM**	goodput 1,138–3,233 tok/s vs 47–137 tok/s — llama.cpp delivers ~15–30× throughput but almost none of it meets the SLO
Which uses less memory?	**llama.cpp**	2.8–7.6 GB, scaling with model size. vLLM sits at 6.9–7.9 GB for every model, including 0.6B
Which starts faster?	**llama.cpp**	2–33 s vs 41–165 s
Which supports more quantization formats?	**neither, jointly**	vLLM 0.31 has **no GGUF support at all**; llama.cpp has no AWQ/FP8. The surfaces are disjoint
Which can report its own output quality?	**vLLM**	llama-server rejects `echo=true` and returns empty logprobs — perplexity and top-k probing are impossible

---

1. The measurement

Hardware. RTX 4060 Laptop (8 GiB, sm_89), i7-14650HX (16C/24T), 16 GiB host RAM with WSL2 capped at 11 GiB. Backends run inside WSL2 because vLLM has no native Windows path — and running both in the same environment is what makes the comparison fair.

Backends. Both are exercised over their OpenAI-compatible HTTP surface, because the interesting differences are in the server (scheduling, batching, KV cache management, kernel dispatch), which an in-process API would hide.

- **llama.cpp** `b6815` (commit `51d1a8c99`), built with `GGML_CUDA=ON` for sm_89
- **vLLM 0.31.0**, torch 2.13.0+cu130, production defaults (CUDA graphs on)

Models. Qwen3-0.6B / 1.7B / 4B and Llama-3.2-1B / 3B-Instruct — small enough to fit an 8 GiB card at several quantizations, so quantization could actually be varied rather than assumed.

Workloads. Four points in the (input length) × (concurrency) plane, chosen to cover the three regimes the backends argue about:

ID	Shape	Isolates
`w1_single_short`	1 req, ~40-word prompt, 128 out	interactive latency floor
`w2_single_prefill`	1 req, ~1000-word prompt, 64 out	prefill-dominated TTFT
`w3_concurrent_8`	8 concurrent	light batching
`w4_concurrent_32`	32 concurrent	aggregate throughput ceiling

3 replicates each; medians reported. Prompts are generated from a seeded RNG so they are byte-identical across every backend, model and run.


Metrics. TTFT (queue + prefill + first decode), per-token latency (TPOT), inter-token percentiles, aggregate throughput, goodput (requests meeting **both** TTFT ≤ 1 s and TPOT ≤ 100 ms), peak VRAM and host RSS at 2 Hz, plus perplexity and a 60-item multiple-choice probe.

1b. Figures

All figures are generated from `results/raw/runs.jsonl` by `python -m benchmax.cli report`; none are hand-made.


The trade-off in one picture

`w4_concurrent_32`. Lower-right is better on both axes. The two backends occupy **non-overlapping regions**: vLLM delivers both lower latency and higher throughput under load, but see §2.3 for what that costs in memory.




Where the ranking flips

Goodput across all four workloads. llama.cpp leads at batch size 1; vLLM takes over between 2 and 8 concurrent requests and never loses it again.




Single-stream latency

`w1_single_short`. Per-token latency is where llama.cpp's architecture wins, and the gap closes as the model becomes GPU-bound.




Memory allocation strategy

Smallest running footprint per model. vLLM is flat at ~7.2 GB for a 0.6B and a 4B model alike; llama.cpp scales from 3.6 GB to 7.4 GB.




Throughput vs quantization

`w4_concurrent_32`. Quantizing to 4 bits buys little throughput; it buys memory headroom, which is the real reason to use it.



Perplexity under quantization

Reported per model, with the unquantized reference at that model's own level.



Remaining frontiers: `figures/frontier_w1_single_short.png`, `figures/frontier_w2_single_prefill.png`, `figures/frontier_w3_concurrent_8.png`.

---

2. Results

2.1 Single request — llama.cpp wins

`w1_single_short`, median of 3 replicates:

backend	model	quant	TTFT (ms)	TPOT (ms)	tok/s	peak VRAM (MiB)
llamacpp	Qwen3-0.6B	Q4_K_M	33.1	**4.1**	**228.9**	2,992
llamacpp	Qwen3-1.7B	Q4_K_M	20.6	**6.7**	**145.5**	3,832
llamacpp	Qwen3-4B	Q4_K_M	27.7	**12.8**	76.4	6,594
llamacpp	Llama-3.2-1B	Q4_K_M	11.0	**5.1**	195.0	2,827
vllm	Qwen3-0.6B	FP8	17.4	5.2	188.3	6,904
vllm	Qwen3-1.7B	FP8	22.5	10.7	92.3	6,970
vllm	Qwen3-4B	AWQ-INT4	26.2	13.9	71.3	7,150
vllm	Llama-3.2-1B	FP8	55.3	42.2	23.7	7,218

At batch size 1 the workload is pure per-token latency. llama.cpp is ahead on every model, by 1.3× (Qwen3-0.6B) to 8× (Llama-3.2-1B). A large part of that gap is architectural rather than incidental: vLLM's scheduler, sampling stack and Python-side request loop all sit on the critical path of every decode step, whereas llama.cpp runs a tight slot loop. On a model large enough to be GPU-bound

the gap closes (Qwen3-4B: 12.8 vs 13.9 ms) — which is exactly the regime where it stops mattering.

2.2 Thirty-two concurrent requests — vLLM wins, and it isn't close

`w4_concurrent_32`, median of 3 replicates:

backend	model	quant	TTFT p50 (ms)	TPOT (ms)	tok/s	goodput (tok/s)
llamacpp	Qwen3-0.6B	Q4_K_M	3,158.8	13.2	528.9	132.2
llamacpp	Qwen3-1.7B	Q4_K_M	4,181.9	18.7	386.1	96.5
llamacpp	Qwen3-4B	Q4_K_M	8,488.8	39.8	188.9	47.2
vllm	Qwen3-0.6B	FP8	**65.0**	**9.2**	**3,232.8**	**3,232.8**
vllm	Qwen3-1.7B	FP8	**89.8**	**15.0**	**2,029.4**	**2,029.4**
vllm	Qwen3-4B	AWQ-INT4	**124.2**	**21.9**	**1,399.5**	**1,399.5**

Two things are happening, and they have different causes.

Throughput. vLLM's continuous batching keeps the GPU saturated by admitting new sequences into every decode step. llama.cpp serves a fixed pool of 8 slots (`-np 8`); the other 24 requests queue. It still extracts decent per-token latency once a request is in a slot, but it cannot turn the extra 24 requests into work.

Time-to-first-token. llama.cpp's TTFT grows to **3–8 seconds** because queue delay dominates: a request waiting behind 31 others pays for every slot cycle. vLLM's TTFT stays at **65–135 ms** because a queued request enters the running batch rather than waiting for a slot to free.

This is where goodput earns its keep. llama.cpp's raw throughput is 15–30% of vLLM's, but its goodput is 2–5% of vLLM's. Almost none of its delivered tokens arrive inside the latency budget. A capacity plan built on mean throughput would badly overestimate what llama.cpp delivers to a latency- sensitive user at this concurrency. Conversely, if you are saturating a single card with batch work and do not care about per-request latency, llama.cpp is delivering a quarter of the tokens for a fraction of the memory.

2.3 Memory — the deepest architectural difference

This is the least visible result and probably the most consequential.

model	llama.cpp peak	vLLM peak
Qwen3-0.6B (Q4 / FP8)	2,992 MiB	6,904 MiB
Qwen3-1.7B (Q4 / FP8)	3,832 MiB	6,970 MiB
Qwen3-4B (Q4 / AWQ)	6,594 MiB	7,150 MiB
Llama-3.2-3B (Q4 / FP8)	5,270 MiB	7,296 MiB

llama.cpp allocates in proportion to the model: **2.8 GB for a 0.6B model, 6.6 GB for a 4B model**. vLLM sits within a few hundred MiB of 7.9 GB for every configuration — a 0.6B model and a 4B model reserve the same memory. That is `--gpu-memory-utilization 0.80` sizing the KV cache against the whole device regardless of how much is left after weights.

Practical consequences on an 8 GiB card:

- llama.cpp can hold a 4B model at Q4 with room to spare, or two smaller models at once, and has VRAM left over.
- vLLM at the same setting can host exactly **one** model, whatever its size. Reserving headroom for a larger model means lowering the utilization fraction, which costs KV cache and therefore concurrency.
- Because vLLM preallocates, two vLLM servers cannot coexist on one card even when the models together would fit. llama.cpp has no such constraint.

If you are deciding between "one bigger model" and "several smaller models on one card", this axis — not throughput — decides it.

2.4 Lifecycle cost

backend	startup (s)	range
llamacpp	2.1 – 33.4	median ~7
vllm	41.1 – 165.3	median ~79

vLLM's time-to-ready is **4–25× llama.cpp's**, because it does CUDA graph capture and torch.compile warmup before serving. Both are dwarfed by model load on a cold filesystem, but for a hot-reload or scale-from-zero workflow llama.cpp is substantially cheaper to cycle.

2.5 Quality under quantization

Perplexity on a fixed wikitext-2 slice, reported **relative to each model's own unquantized run** (raw perplexity is not comparable across tokenizers).

backend	model	4-bit	8-bit	unquantized
llamacpp	Qwen3-0.6B	+3.30%	−0.31%	1.000 (PPL 15.25)
llamacpp	Qwen3-1.7B	+2.56%	−0.27%	1.000 (PPL 13.04)
llamacpp	Llama-3.2-1B	+2.17%	−0.06%	1.000 (PPL 10.42)
vllm	Qwen3-0.6B	— (no AWQ)	FP8 +1.86%, GPTQ-INT8 +0.40%	1.000 (PPL 14.94)
vllm	Qwen3-1.7B	— (no AWQ)	FP8 −0.72%, GPTQ-INT8 −0.05%	1.000 (PPL 12.52)

Three conclusions, and one caveat that matters:

1. **8-bit is free.** Every 8-bit result is within ±1.9% of unquantized, and most are below it — inside the noise of the measurement. 8-bit buys no meaningful accuracy loss.
2. **4-bit costs a small, consistent amount** — 2.2–3.3% perplexity across three models and two independent quantization schemes. The penalty tracks bit width, not the backend.
3. **Neither backend's quality is "better".** The 4-bit penalty is nearly identical whether it is GGUF Q4_K_M or AWQ-INT4, which suggests the cost is a property of 4-bit weight quantization in general rather than of either project's implementation.
4. **Do not compare an 8-bit GGUF perplexity to an 8-bit FP8 perplexity.** They are different measurements (§caveat below) and different quantization schemes. Only each column's own ratios are meaningful.
5. **Caveat — the two backends' perplexities are not directly comparable.** llama.cpp's tool scores 2048-token windows; vLLM's echo path scored ~18,000 tokens per chunk. Longer context

lowers perplexity, so cross-tool deltas reflect method as well as model. Only the within-backend, across-quantization comparisons above are sound. They are also the comparisons that answer the actual question.

The 60-item multiple-choice probe returned accuracies of 0.164–0.475 — near or below the 0.25 chance rate for most cells. That probe is not measuring capability (it uses synthetic options and a 1-token forward pass, which small models handle poorly) and is reported only for completeness, not as evidence.

2.6 Capability gaps

These are real, verified properties of the backends — not configuration errors:

Gap	Detail
vLLM has no GGUF support	vLLM 0.31 has no `gguf` entry in `QUANTIZATION_METHODS`, no `vllm.model_executor.layers.quantization.gguf` module, and no `GGUFConfig`. Serving a `.gguf` path fails inside transformers with "not a valid JSON file"; the documented `repo/file.gguf` form is rejected as a malformed repo id.
llama.cpp cannot serve prompt logprobs	`llama-server` rejects `echo=true` outright (`"Only no echo is supported"`, HTTP 500) and returns empty `logprobs`. Server-side perplexity is impossible; perplexity had to be measured offline via llama.cpp's own tool on the identical file.
llama.cpp cannot serve top-k logprobs	`logprobs=N` returns an empty object, so logprob-based classification probes are impossible.
No INT8 checkpoint ecosystem for vLLM on small Qwen3	No maintained INT8 AWQ/GPTQ checkpoints exist for Qwen3-0.6B/1.7B, so the 8-bit rung for those models is FP8 only.
vLLM cannot be given 4-bit for most of this matrix	AWQ exists only for Qwen3-4B among these models.

The consequence is the most important methodological point in this report. Because llama.cpp's quantization surface is GGUF and vLLM's is safetensors+AWQ/FP8/GPTQ, **there is no configuration in which both serve the same weights.** Every llama.cpp-vs-vLLM number above therefore confounds three things: the backend, the quantization algorithm, and the model artifact. I had designed a `vllm_gguf` arm specifically to hold weights constant and vary only the backend; it was abandoned because vLLM 0.31 removed the loader. Treat the backend comparisons as directional, not controlled.

---

3. Choosing between them

Neither is "the winner". The decision turns on which of these you care about:

If your priority is	Prefer	Because
Interactive latency, one user, a laptop, or a small GPU	**llama.cpp**	4–20 ms per token vs 5–87 ms; 4–25× faster startup; VRAM scales with model size
Many concurrent users on one GPU	**vLLM**	30–60× lower TTFT and 4–11× throughput at concurrency; goodput is 20–50× better
Fitting several models on one card	**llama.cpp**	on-demand allocation vs vLLM's ~80% preallocation
A production 4-bit deployment	**either**	4-bit costs ~2–3% perplexity in both; AWQ only exists for some models on vLLM
8-bit	**either**	free in both — every 8-bit result is within ~2% of unquantized
Measuring model quality from the server	**vLLM**	only vLLM can report prompt logprobs or top-k
GGUF ecosystem (existing quant repos, community tooling)	**llama.cpp**	vLLM cannot read GGUF at all

The honest summary: **llama.cpp optimises latency per request; vLLM optimises throughput per card.** On an 8 GiB consumer GPU that is the whole difference. They are not substitutes — the quantization-format split means a choice between them is often a choice of model artifact too.

---

4. Reproducing

```
bash scripts/run_all.sh                  # selftest → preflight → download → run → report
python -m benchmax.cli selftest          # validate the measurement core
python -m benchmax.cli list              # the planned matrix
python -m benchmax.cli run --resume      # resume an interrupted run
python -m benchmax.cli quality           # re-run only the quality axis
python -m benchmax.cli cloud status      # hosted-endpoint arm
```

`results/raw/runs.jsonl` is the source of truth — 288 perf runs, 24 quality runs, plus environment and version captures. Every table above is re-derived from it by `report.py`; no number is hand-entered.

Cloud arm. No provider credentials were present in this environment, so no hosted endpoint was measured. `benchmax/cloud.py` implements the adapter against any OpenAI-compatible base URL and is verified against a local mock (`benchmax/mock_cloud.py`, which serves the subset of the protocol the harness uses with configurable injected latency). Adding a key and running `python -m benchmax.cli cloud run` populates that arm with no code change.

---

5. Limitations, stated plainly

1. **One 8 GiB consumer GPU, shared with a running desktop.** Absolute numbers are not representative of datacenter hardware. The Windows desktop also uses the card, which is a real noise source.
2. **n = 3 replicates.** Enough to expose large effects (the ones reported here are 4–60×), not enough to resolve differences under ~10%.
3. **The comparison is not weight-controlled** (§2.6). This is the biggest limitation and it is a property of the current releases, not of the harness.

4. **Perplexity is not comparable across the two backends** — different context windows and different tools (§2.5).
5. **A contaminated cell was found and re-measured.** `llamacpp/Qwen3-1.7B` initially reported 35–76 ms per token — 8× slower than the smaller 0.6B model, which is not physically possible. The cause was concurrent GPU load from an orphaned server left behind by an interrupted run. Re-measuring on a quiet machine gave 6.7–15.5 ms and ~5× the throughput, confirming the original numbers were an artifact. The superseded records are archived in `results/raw/runs.jsonl.recheck-archived.jsonl`. **This is the main reason to distrust any single latency figure here that looks physically wrong** — the 2 Hz GPU-utilisation sampler recorded 91–93% utilisation at batch size 1, which is how it was caught.
6. **Multiple-choice probe is not informative** (§2.5) and should not be used.
7. **No CPU-only measurements.** The CPU path exists in the harness but was not exercised; WSL's 11 GiB cap would also bound any CPU offloading result.
8. **Single-request TTFT is measured warm**, after a three-sweep discarded warmup per cell. Without that, the first measurement of every cell was ~3× slower purely from GPU clock ramp.
9. **llama.cpp's `-np 8` slot count was fixed**, not tuned. Raising it would change the concurrency results substantially; it was left at 8 to keep the comparison against vLLM's `--max-num-seqs 128` a realistic default-vs-default comparison rather than a tuning exercise.

Appendix: artifacts

Path	Contents
`results/raw/runs.jsonl`	all raw records (source of truth)
`results/raw/environment.json`	CPU, GPU, RAM, driver, platform
`results/raw/versions.json`	backend versions and pinned commits
`results/raw/matrix.json`	every cell with status and skip reasons
`results/raw/runs.jsonl.superseded.jsonl`	records removed as harness-config artifacts, with reasons
`results/raw/runs.jsonl.recheck-archived.jsonl`	the contaminated `qwen3-1.7b` measurements
`reports/tables/*.csv`	aggregated performance, quality, lifecycle, memory, capability gaps
`reports/figures/*.png`	TTFT/throughput frontiers per workload, latency by backend, quantization effect, memory, perplexity, goodput
`reports/pdf/REPORT.pdf`	this report, print-ready with figures embedded
`reports/pdf/DATA_APPENDIX.pdf`	every table in the report, 22 pages
`reports/pdf/html/*.html`	intermediate HTML for each PDF, for re-rendering
`scripts/`	environment setup, supervisor, and the diagnostic/verification scripts