

ON MULTI-CLASS COST-SENSITIVE LEARNING

ZHI-HUA ZHOU AND XU-YING LIU

National Key Laboratory for Novel Software Technology, Nanjing University

Rescaling is possibly the most popular approach to cost-sensitive learning. This approach works by rebalancing the classes according to their costs, and it can be realized in different ways, for example, re-weighting or resampling the training examples in proportion to their costs, moving the decision boundaries of classifiers faraway from high-cost classes in proportion to costs, etc. This approach is very effective in dealing with two-class problems, yet some studies showed that it is often not so helpful on multi-class problems. In this article, we try to explore why the rescaling approach is often helpless on multi-class problems. Our analysis discloses that the rescaling approach works well when the costs are *consistent*, while directly applying it to multi-class problems with *inconsistent* costs may not be a good choice. Based on this recognition, we advocate that before applying the rescaling approach, the *consistency* of the costs must be examined at first. If the costs are consistent, the rescaling approach can be conducted directly; otherwise it is better to apply rescaling after decomposing the multi-class problem into a series of two-class problems. An empirical study involving 20 multi-class data sets and seven types of cost-sensitive learners validates our proposal. Moreover, we show that the proposal is also helpful for class-imbalance learning.

Key words: machine learning, data mining, cost-sensitive learning, multi-class problems, rescaling, class-imbalance learning.

1. INTRODUCTION

In classical machine learning and data mining settings, the classifiers generally try to minimize the number of mistakes they will make in classifying new instances. Such a setting is valid only when the costs of different types of mistakes are equal. Unfortunately, in many real-world applications the costs of different types of mistakes are often unequal. For example, in medical diagnosis, the cost of mistakenly diagnosing a patient to be healthy may be much larger than that of mistakenly diagnosing a healthy person as being sick, because the former type of mistake may result in the loss of a life that could be saved.

Cost-sensitive learning has attracted much attention from the machine learning and data mining communities. As it has been stated in the Technological Roadmap of the MLnetII project (European Network of Excellence in Machine Learning) (Saitta 2000), the inclusion of costs into learning is one of the most relevant topics of machine learning research. During the past few years, many efforts have been devoted to cost-sensitive learning. The learning process may involve many kinds of costs, such as the test cost, teacher cost, intervention cost, etc. (Turney 2000). There are many recent studies on the test cost (Chai et al. 2004; Ling et al. 2004; Cebe and Gunduz-Demir 2007), yet the most studied cost is the misclassification cost.

Studies on misclassification cost can be categorized into two types further, that is, *example-dependent cost* (Zadrozny and Elkan 2001; Zadrozny, Langford, and Abe 2002; Brefeld, Geibel, and Wyszotzki 2003; Abe, Zadrozny, and Langford 2004; Lozano and Abe 2008) and *class-dependent cost* (Breiman et al. 1984; Domingos 1999; Elkan 2001; Margineantu 2001; Ting 2002; Drummond and Holte 2003; Maloof 2003; Liu and Zhou 2006; Masnadi-Shirazi and Vasconcelos 2007; Zhang and Zhou 2008). The former assumes that the costs are associated with examples, that is, every example has its own misclassification cost; the latter assumes that the costs are associated with classes, that is, every class has its own misclassification cost. It is noteworthy that in most real-world applications, it is feasible to ask a domain expert to specify the cost of misclassifying a class to another class,

Address correspondence to Zhi-Hua Zhou, National Key Laboratory for Novel Software Technology, Nanjing University, Nanjing 210093, China; e-mail: zhouzh@nju.edu.cn

yet only in some special tasks it is easy to get the cost for every example. In this article, we will focus on class-dependent costs and hereafter *class-dependent* will not be mentioned explicitly for convenience.

The most popular approach to cost-sensitive learning, possibly, is *rescaling*. This approach tries to rebalance the classes such that the influences of different classes on the learning process are in proportion to their costs. A typical process is to assign different weights to training examples of different classes in proportion to their misclassification costs; then, the weighted examples are given to a cost-blind learning algorithm such as C4.5 decision tree to train a model which can be used in future predictions (Elkan 2001; Ting 2002). In addition to reweighting the training examples, the rescaling approach can also be realized in many other ways, such as resampling the training examples (Elkan 2001; Drummond and Holte 2003; Maloof 2003), moving the decision thresholds (Domingos 1999; Elkan 2001), etc.

The rescaling approach has been found effective on two-class problems (Breiman et al. 1984; Domingos 1999; Elkan 2001; Ting 2002; Drummond and Holte 2003; Maloof 2003). However, some studies (Zhou and Liu 2006b) showed that it is often not so useful when applied to multi-class problems directly. In fact, most previous studies on cost-sensitive learning focused on two-class problems, and although some research involved multi-class data sets (Breiman et al. 1984; Domingos 1999; Ting 2002), only a few studies dedicated to the investigation of multi-class cost-sensitive learning (Abe et al. 2004; Zhou and Liu 2006b; Lozano and Abe 2008; Zhang and Zhou 2008) where Abe et al. (2004) and Lozano and Abe (2008) worked on example-dependent cost while Zhou and Liu (2006b) and Zhang and Zhou (2008) worked on class-dependent cost.

In this article, we try to explore why the rescaling approach is often ineffective on multi-class problems. Our analysis suggests that the rescaling approach could not work well with *inconsistent* costs, while many multi-class problems are with inconsistent costs. Based on this recognition, we advocate that we must examine the *consistency* of the costs before applying rescaling. If the costs are consistent, we can apply rescaling directly; otherwise if we really want to apply rescaling, we should apply after decomposing the multi-class problem into a series of two-class problems. To distinguish our proposal from the traditional process which executes rescaling without any sanity checking, we call it RESCALE_{new} . An empirical study involving 20 multi-class data sets and seven types of cost-sensitive learners validates the effectiveness of our proposal. Moreover, we show that RESCALE_{new} is also helpful for class-imbalance learning.

The remaining of this article is organized as follows. Section 2 analyzes why the rescaling approach is often ineffective on multi-class problems. Section 3 presents RESCALE_{new} . Section 4 reports on our empirical study. Finally, Section 5 concludes.

2. ANALYSIS

Assume that a correct classification costs zero. Let $cost_{ij}$ ($i, j \in \{1..c\}, cost_{ii} = 0$) denote the cost of misclassifying an example of the i th class to the j th class, where c is the number of classes. It is evident that these costs can be organized into a *cost matrix* where the element at the i th row and the j th column is $cost_{ij}$. Let n_i denote the number of training examples of the i th class, and n denotes the total number of training examples. To simplify the discussion, assume there is no class-imbalance, that is, $n_i = n/c$ ($i \in \{1..c\}$).

Rescaling is a general approach to make any cost-blind learning algorithm cost-sensitive. The principle is to enable the influences of the higher-cost classes to be larger than that of the lower-cost classes. On two-class problems, the optimal prediction is the first class if and only if the expected cost of this prediction is no larger than that of predicting the second class, as shown in equation (1) where $p = P(class = 1|x)$.

$$p \times cost_{11} + (1 - p) \times cost_{21} \leq p \times cost_{12} + (1 - p) \times cost_{22}. \quad (1)$$

If the inequality in equation (1) becomes equality, predicting either class is optimal. Therefore, the threshold p^* for making optimal decision should satisfy equation (2).

$$p^* \times cost_{11} + (1 - p^*) \times cost_{21} = p^* \times cost_{12} + (1 - p^*) \times cost_{22}. \quad (2)$$

Theorem 1 (Elkan 2001). *To make a target probability threshold p^* correspond to a given probability threshold p_0 , the number of the second class examples in the training set should be multiplied by $\frac{p^*}{1-p^*} \frac{1-p_0}{p_0}$.*

When the classifier is not biased to any class, the threshold p_0 is 0.5. Considering equation (2), Theorem 1 tells that the second class should be rescaled against the first class according to $\frac{p^*}{(1-p^*)} = \frac{cost_{21}}{cost_{12}}$ (remind that $cost_{11} = cost_{22} = 0$), which implies that the influence of the first class should be $\frac{cost_{12}}{cost_{21}}$ times of that of the second class. Generally speaking, the optimal *rescaling ratio* of the i th class against the j th class can be defined as equation (3), which indicates that the classes should be rescaled in the way that the influence of the i th class is $\tau_{opt}(i, j)$ times of that of the j th class. For example, if the weight assigned to the training examples of the j th class after rescaling (via reweighting the training examples) is w_j , then that of the i th class will be $w_i = \tau_{opt}(i, j) \times w_j$ ($w_i > 0$).

$$\tau_{opt}(i, j) = \frac{cost_{ij}}{cost_{ji}}. \quad (3)$$

In the traditional rescaling approach (Breiman et al. 1984; Domingos 1999; Ting 2002), a quantity $cost_i$ is derived according to equation (4) at first.

$$cost_i = \sum_{j=1}^c cost_{ij}. \quad (4)$$

Then, a weight w_i is assigned to the i th class after rescaling (via reweighting the training examples), computed according to equation (5).

$$w_i = \frac{(n \times cost_i)}{\sum_{k=1}^c (n_k \times cost_k)}. \quad (5)$$

Reminding the assumption that $n_i = n/c$, equation (5) becomes:

$$w_i = \frac{(c \times cost_i)}{\sum_{k=1}^c cost_k}. \quad (6)$$

So, it is evident that in the traditional rescaling approach, the rescaling ratio of the i th class against the j th class is

$$\tau_{old}(i, j) = \frac{w_i}{w_j} = \frac{(c \times cost_i) / \sum_{k=1}^c cost_k}{(c \times cost_j) / \sum_{k=1}^c cost_k} = \frac{cost_i}{cost_j}. \quad (7)$$

When $c = 2$,

$$\begin{aligned} \tau_{old}(i, j) &= \frac{cost_i}{cost_j} = \frac{\sum_{k=1}^2 cost_{ik}}{2} = \frac{cost_{i1} + cost_{i2}}{cost_{j1} + cost_{j2}} \\ &= \frac{cost_{i2}}{cost_{j1}} = \frac{cost_{ij}}{cost_{ji}} = \tau_{opt}(i, j). \end{aligned}$$

This explains that why the traditional rescaling approach can be effective in dealing with the unequal misclassification costs on two-class problems, as shown by previous studies (Breiman et al. 1984; Domingos 1999; Ting 2002).

Unfortunately, when $c > 2$, $\tau_{old}(i, j)$ becomes equation (8), which is usually unequal to $\tau_{opt}(i, j)$. This explains that why the traditional rescaling approach is often ineffective in dealing with the unequal misclassification costs on multi-class problems.

$$\tau_{old}(i, j) = \frac{cost_i}{cost_j} = \frac{\sum_{k=1}^c cost_{ik}}{\sum_{k=1}^c cost_{jk}} \quad (8)$$

3. RESCALE_{new}

Suppose each class can be assigned with a weight w_i ($w_i > 0$) after rescaling (via reweighting the training examples). To appropriately rescale all the classes simultaneously, according to the analysis presented in the previous section, it is desired that the weights satisfy $\frac{w_i}{w_j} = \tau_{opt}(i, j)$ ($i, j \in \{1..c\}$), which implies the following $\binom{c}{2}$ number of constraints:

$$\begin{aligned} \frac{w_1}{w_2} &= \frac{cost_{12}}{cost_{21}}, \frac{w_1}{w_3} = \frac{cost_{13}}{cost_{31}}, \dots, \frac{w_1}{w_c} = \frac{cost_{1c}}{cost_{c1}} \\ \frac{w_2}{w_3} &= \frac{cost_{23}}{cost_{32}}, \dots, \frac{w_2}{w_c} = \frac{cost_{2c}}{cost_{c2}} \\ &\dots \dots \dots \\ \frac{w_{c-1}}{w_c} &= \frac{cost_{c-1,c}}{cost_{c,c-1}}. \end{aligned}$$

These constraints can be transformed into the equations shown in equation (9). If nontrivial solution $\mathbf{w} = [w_1, w_2, \dots, w_c]^T$ can be solved from equation (9) (the solution will be unique, up to a multiplicative factor), then the classes can be appropriately rescaled simultaneously; this implies that the multi-class cost-sensitive learning problem can be solved by applying the rescaling approach directly.

$$\begin{cases} w_1 \times cost_{21} - w_2 \times cost_{12} + w_3 \times 0 & + \dots + w_c \times 0 & = 0 \\ w_1 \times cost_{31} + w_2 \times 0 & - w_3 \times cost_{13} + \dots + w_c \times 0 & = 0 \\ \dots & \dots & \dots & \dots & = 0 \\ w_1 \times cost_{c1} + w_2 \times 0 & + w_3 \times 0 & + \dots - w_c \times cost_{1c} & = 0 \\ w_1 \times 0 & + w_2 \times cost_{32} - w_3 \times cost_{23} + \dots + w_c \times 0 & = 0 \\ \dots & \dots & \dots & \dots & = 0 \\ w_1 \times 0 & + w_2 \times cost_{c2} + w_3 \times 0 & + \dots - w_c \times cost_{2c} & = 0 \\ \dots & \dots & \dots & \dots & = 0 \\ \dots & \dots & \dots & \dots & = 0 \\ w_1 \times 0 & + w_2 \times 0 & + w_3 \times 0 & + \dots - w_c \times cost_{c-1,c} & = 0 \end{cases} \quad (9)$$

Equation (9) has nontrivial solution if and only if the rank of its coefficient matrix (which is a $\frac{c(c-1)}{2} \times c$ matrix) shown in equation (10) is smaller than c , which is equivalent to the condition that the determinant $|A|$ of any $c \times c$ sub-matrix A of equation (10) is zero. Note that for a $(\frac{c(c-1)}{2} \times c)$ matrix ($c > 2$), the rank is at most c .

$$\begin{bmatrix} cost_{21} & -cost_{12} & 0 & \dots & 0 \\ cost_{31} & 0 & -cost_{13} & \dots & 0 \\ \dots & \dots & \dots & \dots & 0 \\ cost_{c1} & 0 & 0 & \dots & -cost_{1c} \\ 0 & cost_{32} & -cost_{23} & \dots & 0 \\ \dots & \dots & \dots & \dots & 0 \\ 0 & cost_{c2} & 0 & \dots & -cost_{2c} \\ \dots & \dots & \dots & \dots & \dots \\ \dots & \dots & \dots & \dots & \dots \\ 0 & \dots & 0 & \dots & -cost_{c-1,c} \end{bmatrix}. \quad (10)$$

For example, when all classes are with equal costs, unit vector will be solved from equation (9) as a nontrivial solution of \mathbf{w} , and thus the classes should be equally rescaled (in this case the problem degenerates to a common equal-cost multi-class learning problem).

It is noteworthy that when the rank of the coefficient matrix is c , equation (9) does not have nontrivial solution; this implies that there will be no proper weight assignment for rescaling all the classes simultaneously. Therefore, rescaling could not work well if applied directly, and to use rescaling, the multi-class problem has to be decomposed into a series of two-class problems to address, and the final prediction can be made by voting.

Based on the aforementioned analysis, the $RESCALE_{new}$ approach is proposed and summarized in Algorithm 1. In detail, for a given cost matrix, the coefficient matrix in the form of equation (10) is generated at first. If the rank of the co-efficient matrix is smaller than c (in this case, the cost matrix is called as a *consistent* cost matrix), \mathbf{w} is solved from equation (9) and used to rescale the classes simultaneously, and the rescaled data set is then passed to any cost-blind classifier; otherwise (the cost matrix is called as an *inconsistent* cost matrix), the multi-class problem is decomposed into $\binom{c}{2}$ number of two-class problems, and each two-class data set is rescaled and passed to any cost-blind classifier, while the final prediction is made by voting the class labels predicted by the two-class classifiers.

Note that our main contribution of this work is the argument that before applying rescaling, the sanity check on the consistency of the cost matrix must be conducted. The $RESCALE_{new}$ approach is presented to validate our proposal. There are many alternative ways to realize our proposal; for example, there are many alternative methods for decomposing

ALGORITHM 1 The RESCALE_{new} approach

```

1: Input: Training set  $D$  (with  $c$  classes), cost matrix  $cost$ , cost-blind learner  $G$ 
2:  $M \leftarrow Matrix(cost)$   %% Generate the coefficient matrix for  $cost$  by equation (10)
3: if  $Rank(M) < c$  then
4:   Solve  $w$  from equation (9);
5:    $D^* \leftarrow Rescale(D, w)$ ;  %% Rescale classes in  $D$  using  $w$  to derive data set  $D^*$ 
6:    $H \leftarrow G(D^*)$ ;  %% Generate  $H$  on data set  $D^*$  using the cost-blind learner  $G$ 
7: else
8:   for  $i = 1$  to  $c - 1$  do
9:     for  $j = i + 1$  to  $c$  do
10:       $D_{ij} \leftarrow Subset(D, i, j)$ ;  %% Derive the two-class data set  $D_{ij}$  from  $D$ ,
      which contains only the examples belonging to the  $i$ th and the  $j$ th classes
11:       $h_{ij} \leftarrow Traditional\_Rescaling(D_{ij}, \begin{bmatrix} cost_{ii} & cost_{ij} \\ cost_{ji} & cost_{jj} \end{bmatrix}, G)$   %% Apply
      the traditional Rescaling approach to  $D_{ij}$ 
12:    end for
13:  end for
14:   $H(x) \leftarrow \arg \max_{y \in \{1, \dots, c\}} \sum_{i=1}^{c-1} \sum_{j=i+1}^c I(h_{ij}(x) = y)$   %% The prediction on  $x$  is
  obtained by voting the class labels predicted by  $h_{ij}$ 's
15: end if
16: Output: Cost-sensitive classifier  $H$ .

```

multi-class problems into a series of two-class problems (Allwein, Schapire, and Singer 2000). Here, we adopt the popular pairwise coupling (that is, every equation in equation (9) corresponds to a two-class problem).

4. EMPIRICAL STUDY

4.1. Methods

In the empirical study we compare RESCALE_{new} (denoted by NEW) with the traditional rescaling approach (denoted by OLD) (Breiman et al. 1984; Domingos 1999; Ting 2002). Here, three ways are used to realize the rescaling process.

The first way is *instance-weighting*, that is, reweighting the training examples in proportion to their costs. Because C4.5 decision tree can deal with weighted examples, we use it as the cost-blind learner (denoted by BLIND-C45). Here we use the J48 implementation in WEKA with default settings (Witten and Frank 2005). The rescaling approaches are denoted by OLD-IW and NEW-IW, respectively. Note that in this way, the OLD-IW approach reassembles the C4.5CS method (Ting 2002).

The second way is *resampling*. Both over-sampling and under-sampling are studied. A C4.5 decision tree is trained after the resampling process. Thus, the cost-blind learner is still BLIND-C45. By using over-sampling and under-sampling, the traditional rescaling approaches are denoted by OLD-OS and OLD-US, respectively, and the new rescaling approaches are denoted by NEW-OS and NEW-US, respectively.

The third way is *threshold-moving*. Here, the cost-sensitive neural networks described in Zhou and Liu (2006b) is used. After training a standard neural network, the decision threshold is adjusted to favor examples with higher cost. Thus, standard BP neural network

TABLE 1. Methods Used in the Experiments.

	Cost-Blind Learner	RESCALE _{old}	RESCALE _{new}
Instance-weighting	[BLIND-C45]	[OLD-IW]	[NEW-IW]
Over-sampling	BLIND-C45	[OLD-OS]	[NEW-OS]
Under-sampling	BLIND-C45	[OLD-US]	[NEW-US]
NN	[BLIND-NN]	[OLD-NN]	[NEW-NN]
PETs	[BLIND-PETs]	[OLD-PETs]	[NEW-PETs]
Hard-ensemble	BLIND-HE	OLD-HE	NEW-HE
Soft-ensemble	BLIND-SE	OLD-SE	NEW-SE

is used as cost-blind learner (denoted by BLIND-NN). The rescaling approaches are denoted by OLD-NN and NEW-NN, respectively. In addition, another threshold-moving method is used, which first utilizes PETs (Provost and Domingos 2003) to estimate the probabilities of examples belonging to each class and then gets cost-sensitivity by threshold-moving. The cost-blind learner (denoted by BLIND-PETs) uses PETs to predict examples. The rescaling approaches are denoted by OLD-PETs and NEW-PETs, respectively. In the experiments, the BP network has one hidden layer containing 10 units, and it is trained with 200 epochs. PETs performs 20 iterations.

Moreover, two ensemble methods presented by Zhou and Liu (2006b) are evaluated. *Hard-ensemble* takes the individual learner's outputs as input and predicts by 0-1 vote, while *soft-ensemble* accumulates probabilities provided by the individual learners and predicts the class with the maximum value. BLIND-C45, BLIND-NN and BLIND-PETs form the ensembles for both cost-blind hard-ensemble and soft-ensemble (denoted by BLIND-HE and BLIND-SE, respectively). Note that the cost-blind learners used in the sampling methods are also BLIND-C45, so BLIND-C45 is only included in the ensemble once. OLD-IW, OLD-OS, OLD-US, OLD-NN, and OLD-PETs form the ensemble for both ensemble-based old rescaling methods (denoted by OLD-HE and OLD-SE, respectively). NEW-IW, NEW-OS, NEW-US, NEW-NN, and NEW-PETs form the ensemble for both ensemble-based new rescaling methods (denoted by NEW-HE and NEW-SE, respectively).

All methods evaluated in the empirical study and their abbreviations are summarized in Table 1, where methods in "[]" are used in ensemble-based methods.

4.2. Configuration

Twenty multi-class data sets are used in the experiments, where the first 10 data sets are without class-imbalance while the remaining ones are imbalanced. There are 14 UCI data sets (Blake, Keogh, and Merz 1998) and 6 synthetic data sets. The synthetic ones are generated as follows. Each synthetic data set has two attributes, three or five classes, and its examples are generated randomly from normal distributions under the following constraints: the mean value and standard deviation of each attribute are random real values in $[0, 10]$, and the coefficients are random real values in $[-1, +1]$. Information on the experimental data sets are summarized in Table 2.

On each data set, two series of experiments are performed. The first series of experiments deal with consistent cost matrices while the second series deal with inconsistent ones. Here the consistent matrices are generated as follows: a c -dimensional real value vector is randomly generated and regarded as the root of equation (9), then a real value is randomly generated for $cost_{ij}(i, j \in [1, c] \text{ and } i \neq j)$ such that $cost_{ji}$ can be solved from equation (9). All these real values are in $[1, 10]$, $cost_{ii} = 0$ and at least one $cost_{ij}$ is 1.0. Note that in generating

TABLE 2. Experimental Data Sets (A: # attributes, C: # classes).

Data Set	Size	A	C	Class Distribution
<i>mfeat-fouri</i>	2,000	76	10	[200*10]
<i>segment</i>	2,310	19	7	[330 * 7]
<i>syn-a</i>	1,500	2	3	[500 * 3]
<i>syn-b</i>	3,000	2	3	[1,000 * 3]
<i>syn-c</i>	6,000	2	3	[2,000 * 3]
<i>syn-d</i>	2,500	2	5	[500 * 5]
<i>syn-e</i>	5,000	2	5	[1,000 * 5]
<i>syn-f</i>	10,000	2	5	[2,000 * 5]
<i>vowel</i>	990	13	11	[90 * 11]
<i>waveform</i>	3,000	40	3	[1,000 * 3]
<i>abalone</i>	4,177	8	3	[1,307; 1,342; 1,528]
<i>ann</i>	7,200	21	3	[166; 368; 6,666]
<i>balance</i>	625	4	3	[49; 288; 288]
<i>car</i>	1,728	6	4	[65; 69; 384; 1,210]
<i>cmc</i>	1,473	9	3	[333; 511; 629]
<i>connect4</i>	67,557	42	3	[6,449; 16,635; 44,473]
<i>page</i>	5,473	10	5	[28; 88; 115; 329; 4,913]
<i>satellite</i>	6,435	36	6	[626; 703; 707; 1358; 1508; 1533]
<i>solarflare2</i>	1,066	11	6	[43; 95; 147; 211; 239; 331]
<i>splice</i>	3,190	60	3	[767; 768; 1,655]

cost matrices for imbalanced data sets, it is constrained that the cost of misclassifying the smallest class to the largest class is the largest while the cost of misclassifying the largest class to the smallest class is the smallest. This owes to the fact that when misclassifying the largest class is with the largest cost, classical machine learning and data mining approaches are good enough and therefore this situation is not concerned in the research of cost-sensitive learning and class-imbalance learning. The inconsistent matrices are generated in a similar way except that one $cost_{ji}$ solved from equation (9) is replaced by a random value. The ranks of the coefficient matrices corresponding to those cost matrices have been examined to guarantee that they are smaller or not smaller than c , respectively.

In each series of experiments, ten times 10-fold cross validation are performed. Concretely, 10-fold cross validation is repeated for ten times with randomly generated cost matrices belonging to the same type (i.e., consistent or inconsistent), and the average results are recorded.

There are some powerful tools such as ROC and cost curves (Drummond and Holte 2000) for visually evaluating the performance of two-class cost-sensitive learning approaches. Unfortunately, they could not be applied to multi-class problems directly. So, the *misclassification costs* are compared here.

4.3. Results

The influences of the traditional rescaling approach and the new rescaling approach on instance-weighting-based cost-sensitive C4.5, over-sampling-based cost-sensitive C4.5, under-sampling-based cost-sensitive C4.5, threshold-moving-based cost-sensitive neural network, threshold-moving-based cost-sensitive PETs, hard-ensemble and soft-ensemble are reported separately.

TABLE 3. Comparison of Misclassification Costs on Consistent Cost Matrices, with Instance-Weighting-Based Cost-Sensitive C4.5.

	BLIND-C45	OLD-IW	NEW-IW
<i>mfeat-fouri</i>	519.234 \pm 149.108	0.894 \pm 0.136	0.821 \pm 0.183
<i>segment</i>	49.705 \pm 21.601	1.030 \pm 0.170	1.025 \pm 0.123
<i>syn-a</i>	183.307 \pm 114.119	0.925 \pm 0.147	0.830 \pm 0.184
<i>syn-b</i>	401.059 \pm 267.163	0.910 \pm 0.202	0.833 \pm 0.157
<i>syn-c</i>	265.313 \pm 259.115	0.913 \pm 0.117	0.884 \pm 0.135
<i>syn-d</i>	328.491 \pm 124.408	0.963 \pm 0.051	0.898 \pm 0.120
<i>syn-e</i>	772.547 \pm 262.066	0.921 \pm 0.089	0.857 \pm 0.105
<i>syn-f</i>	1,697.866 \pm 529.724	0.911 \pm 0.076	0.828 \pm 0.078
<i>vowel</i>	134.036 \pm 19.500	1.059 \pm 0.102	1.102 \pm 0.105
<i>waveform</i>	243.195 \pm 102.328	0.911 \pm 0.133	0.908 \pm 0.139
avg.	459.475 \pm 457.202	0.944 \pm 0.053	0.899 \pm 0.089
<i>abalone</i>	638.828 \pm 191.028	0.788 \pm 0.220	0.728 \pm 0.212
<i>ann</i>	4.806 \pm 1.517	0.975 \pm 0.106	0.991 \pm 0.069
<i>balance</i>	71.045 \pm 43.063	1.016 \pm 0.231	0.826 \pm 0.171
<i>car</i>	43.287 \pm 13.971	0.888 \pm 0.206	0.766 \pm 0.172
<i>cmc</i>	243.007 \pm 137.347	0.888 \pm 0.165	0.798 \pm 0.179
<i>connect4</i>	5,032.208 \pm 3,447.362	0.928 \pm 0.143	0.895 \pm 0.152
<i>page</i>	122.133 \pm 106.107	0.983 \pm 0.100	0.972 \pm 0.085
<i>satellite</i>	502.146 \pm 150.719	0.970 \pm 0.056	0.950 \pm 0.064
<i>solarflare2</i>	194.899 \pm 91.457	0.876 \pm 0.236	0.819 \pm 0.202
<i>splice</i>	56.124 \pm 26.992	0.983 \pm 0.093	0.929 \pm 0.091
avg.	690.848 \pm 1,460.572	0.930 \pm 0.066	0.867 \pm 0.087

NOTE: For the cost-blind approach BLIND-C45, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

4.3.1. On Instance-Weighting-Based Cost-Sensitive C4.5. Tables 3 and 4 present the performance of the traditional rescaling approach and the new rescaling approach on instance-weighting-based cost-sensitive C4.5 on consistent and inconsistent cost matrices, respectively. In both tables, total costs are in the form of “mean \pm standard deviation,” and the best performance of each row is boldfaced. Note that for the cost-blind approach BLIND-C45, the absolute misclassification costs are reported; while for the traditional rescaling approach OLD-IW and new rescaling approach NEW-IW, the ratios of their misclassification costs against that of the cost-blind approach are presented.

Tables 3 and 4 reveal that no matter on balanced or imbalanced data sets and on consistent or inconsistent cost matrices, the new rescaling approach NEW-IW performs apparently better than the traditional approach OLD-IW.

In detail, pairwise *t*-tests at 95% significance level indicate that on consistent cost matrices, the traditional rescaling approach OLD-IW is effective on only 9 data sets, that is, *mfeat-fouri*, *syn-b* to *syn-f*, *waveform*, *abalone* and *car*, while the new rescaling approach NEW-IW is effective on 16 data sets, that is, *mfeat-fouri*, *syn-a* to *syn-f*, *waveform*, *abalone*, *balance*, *car*, *cmc*, *connect4*, *satellite*, *solarflare2* and *splice*; on inconsistent cost matrices, the traditional rescaling approach OLD-IW is effective on only 8 data sets, that is,

TABLE 4. Comparison of Misclassification Costs on Inconsistent Cost Matrices, with Instance-Weighting-Based Cost-Sensitive C4.5.

	BLIND-C45	OLD-IW	NEW-IW
<i>mfeat-fouri</i>	263.160 \pm 33.881	0.999 \pm 0.036	0.833 \pm 0.077
<i>segment</i>	36.970 \pm 9.976	1.058 \pm 0.100	1.046 \pm 0.176
<i>syn-a</i>	298.570 \pm 70.731	0.973 \pm 0.103	0.889 \pm 0.085
<i>syn-b</i>	630.370 \pm 144.257	0.875 \pm 0.156	0.716 \pm 0.183
<i>syn-c</i>	321.080 \pm 99.375	0.998 \pm 0.060	0.937 \pm 0.047
<i>syn-d</i>	310.660 \pm 31.072	1.008 \pm 0.035	0.938 \pm 0.042
<i>syn-e</i>	945.850 \pm 98.469	0.964 \pm 0.052	0.910 \pm 0.087
<i>syn-f</i>	1,932.570 \pm 270.314	1.035 \pm 0.080	0.919 \pm 0.069
<i>vowel</i>	99.610 \pm 6.757	1.117 \pm 0.074	1.089 \pm 0.053
<i>waveform</i>	385.690 \pm 51.752	0.921 \pm 0.099	0.823 \pm 0.085
<i>avg.</i>	522.453 \pm 530.594	0.995 \pm 0.065	0.910 \pm 0.102
<i>abalone</i>	1,035.280 \pm 137.578	0.643 \pm 0.114	0.548 \pm 0.114
<i>ann</i>	7.760 \pm 2.606	0.927 \pm 0.199	1.234 \pm 0.364
<i>balance</i>	72.770 \pm 10.371	0.919 \pm 0.125	0.930 \pm 0.081
<i>car</i>	71.820 \pm 16.628	0.974 \pm 0.143	0.769 \pm 0.084
<i>cmc</i>	369.410 \pm 80.939	0.882 \pm 0.091	0.870 \pm 0.130
<i>connect4</i>	7,135.720 \pm 716.498	0.942 \pm 0.074	0.952 \pm 0.081
<i>page</i>	99.150 \pm 13.520	1.007 \pm 0.061	0.902 \pm 0.084
<i>satellite</i>	479.250 \pm 62.999	0.982 \pm 0.038	0.870 \pm 0.060
<i>solarflare2</i>	153.460 \pm 21.653	0.995 \pm 0.063	0.940 \pm 0.090
<i>splice</i>	71.210 \pm 20.969	0.983 \pm 0.042	0.913 \pm 0.068
<i>avg.</i>	949.583 \pm 2,082.987	0.925 \pm 0.101	0.893 \pm 0.161

NOTE: For the cost-blind approach BLIND-C45, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

syn-b, *syn-e*, *waveform*, *abalone*, *ann*, *balance*, *cmc* and *connect4*, while the new rescaling approach NEW-IW is effective on 17 data sets, that is, except on *segment*, *vowel* and *ann*. Moreover, on consistent cost matrices, NEW-IW performs significantly better than OLD-IW on 12 data sets, that is, *mfeat-fouri*, *syn-b* to *syn-f*, *abalone*, *balance*, *cmc*, *connect4*, *solarflare2* and *splice*; on inconsistent cost matrices, NEW-IW also performs significantly better than OLD-IW on 14 data sets, that is, *mfeat-fouri*, *syn-a* to *syn-f*, *waveform*, *abalone*, *car*, *page*, *satellite*, *solarflare2* and *splice*. These comparisons are summarized in Table 5, which presents the win/tie/loss counts of the approach on the row over the approach on the column.

Note that the performance of the new rescaling approach NEW-IW is almost always significantly better than or at least comparable to that of the traditional rescaling approach OLD-IW, except that on inconsistent cost matrices NEW-IW degenerates the performance on *ann*. It can be found from Table 2 that the *ann* data set is seriously imbalanced, where the largest class is over 40 times bigger than the smallest one. This may suggest that in dealing with data sets with unequal misclassification costs and serious class imbalance, using only the cost information to rescale the classes may not be sufficient. This issue will be investigated in future work.

TABLE 5. Summary of the Comparisons (Win/Tie/Loss) of the Approach on the Row over the Approach on the Column, with Instance-Weighting-Based Cost-Sensitive C4.5 under Pairwise t -Tests at 95% Significance Level (CCM: Consistent Cost Matrices, ICM: Inconsistent Cost Matrices).

	On CCM		On ICM	
	BLIND-C45	OLD-IW	BLIND-C45	OLD-IW
OLD-IW	9/11/0	–	8/11/1	–
NEW-IW	16/3/1	12/8/0	17/1/2	14/5/1

TABLE 6. Comparison of Misclassification Costs on Consistent Cost Matrices, with Over-Sampling-Based Cost-Sensitive C4.5.

	BLIND-C45	OLD-OS	NEW-OS
<i>mfeat-fouri</i>	519.234 ± 149.108	1.067 ± 0.086	1.058 ± 0.112
<i>segment</i>	49.705 ± 21.601	0.977 ± 0.150	0.941 ± 0.132
<i>syn-a</i>	183.307 ± 114.119	0.985 ± 0.105	0.975 ± 0.064
<i>syn-b</i>	401.059 ± 267.163	0.937 ± 0.167	0.895 ± 0.115
<i>syn-c</i>	265.313 ± 259.115	0.961 ± 0.108	0.982 ± 0.096
<i>syn-d</i>	328.491 ± 124.408	1.067 ± 0.108	1.094 ± 0.106
<i>syn-e</i>	772.547 ± 262.066	1.072 ± 0.067	1.025 ± 0.050
<i>syn-f</i>	1,697.866 ± 529.724	1.001 ± 0.077	0.969 ± 0.045
<i>vowel</i>	134.036 ± 19.500	1.041 ± 0.093	0.996 ± 0.117
<i>waveform</i>	243.195 ± 102.328	1.003 ± 0.056	1.016 ± 0.043
<i>avg.</i>	459.475 ± 457.202	1.011 ± 0.046	0.995 ± 0.054
<i>abalone</i>	638.828 ± 191.028	0.952 ± 0.055	0.936 ± 0.067
<i>ann</i>	4.806 ± 1.517	1.080 ± 0.115	1.025 ± 0.164
<i>balance</i>	71.045 ± 43.063	1.017 ± 0.203	0.861 ± 0.164
<i>car</i>	43.287 ± 13.971	0.788 ± 0.132	0.730 ± 0.148
<i>cmc</i>	243.007 ± 137.347	0.953 ± 0.083	0.926 ± 0.089
<i>connect4</i>	5,032.208 ± 3,447.362	0.966 ± 0.102	0.949 ± 0.099
<i>page</i>	122.133 ± 106.107	0.974 ± 0.067	0.968 ± 0.072
<i>satellite</i>	502.146 ± 150.719	1.009 ± 0.048	1.007 ± 0.043
<i>solarflare2</i>	194.899 ± 91.457	0.904 ± 0.193	0.871 ± 0.180
<i>splice</i>	56.124 ± 26.992	1.020 ± 0.053	1.044 ± 0.058
<i>avg.</i>	690.848 ± 1,460.572	0.966 ± 0.075	0.932 ± 0.088

NOTE: For the cost-blind approach BLIND-C45, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

4.3.2. *On Over-Sampling-Based Cost-Sensitive C4.5.* The performance of the traditional rescaling approach and the new rescaling approach on over-sampling-based cost-sensitive C4.5 on consistent cost matrices and inconsistent ones are summarized in Tables 6 and 7, respectively. The tables reveal that traditional rescaling approach OLD-OS often performs worse than cost-blind learner BLIND-C45, no matter on balanced or imbalanced data sets and on consistent or inconsistent cost matrices. This may owe to the fact that

TABLE 7. Comparison of Misclassification Costs on Inconsistent Cost Matrices, with Over-Sampling-Based Cost-Sensitive C4.5.

	BLIND-C45	OLD-OS	NEW-OS
<i>mfeat-fouri</i>	263.160 \pm 33.881	1.044 \pm 0.047	0.897 \pm 0.065
<i>segment</i>	36.970 \pm 9.976	1.020 \pm 0.119	1.013 \pm 0.156
<i>syn-a</i>	298.570 \pm 70.731	1.033 \pm 0.055	0.921 \pm 0.056
<i>syn-b</i>	630.370 \pm 144.257	0.950 \pm 0.107	0.758 \pm 0.131
<i>syn-c</i>	321.080 \pm 99.375	1.086 \pm 0.092	0.942 \pm 0.038
<i>syn-d</i>	310.660 \pm 31.072	1.094 \pm 0.070	0.947 \pm 0.037
<i>syn-e</i>	945.850 \pm 98.469	1.039 \pm 0.082	0.909 \pm 0.082
<i>syn-f</i>	1,932.570 \pm 270.314	1.090 \pm 0.084	0.918 \pm 0.067
<i>vowel</i>	99.610 \pm 6.757	1.028 \pm 0.068	0.976 \pm 0.056
<i>waveform</i>	385.690 \pm 51.752	1.014 \pm 0.057	0.984 \pm 0.052
<i>avg.</i>	522.453 \pm 530.594	1.040 \pm 0.041	0.926 \pm 0.066
<i>abalone</i>	1,035.280 \pm 137.578	0.916 \pm 0.031	0.715 \pm 0.076
<i>ann</i>	7.760 \pm 2.606	1.079 \pm 0.237	1.243 \pm 0.364
<i>balance</i>	72.770 \pm 10.371	0.895 \pm 0.106	0.930 \pm 0.052
<i>car</i>	71.820 \pm 16.628	0.909 \pm 0.099	0.679 \pm 0.104
<i>cmc</i>	369.410 \pm 80.939	0.947 \pm 0.074	0.915 \pm 0.060
<i>connect4</i>	7,135.720 \pm 716.498	0.965 \pm 0.058	0.972 \pm 0.035
<i>page</i>	99.150 \pm 13.520	1.038 \pm 0.064	0.908 \pm 0.064
<i>satellite</i>	479.250 \pm 62.999	1.027 \pm 0.050	0.946 \pm 0.029
<i>solarflare2</i>	153.460 \pm 21.653	1.034 \pm 0.038	0.958 \pm 0.088
<i>splice</i>	71.210 \pm 20.969	1.053 \pm 0.073	0.977 \pm 0.101
<i>avg.</i>	949.583 \pm 2,082.987	0.986 \pm 0.064	0.924 \pm 0.146

NOTE: For the cost-blind approach BLIND-C45, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

over-sampling often suffers from over-fitting because it duplicates examples (Drummond and Holte 2003). The problem will become serious when there are large differences between costs. However, the new rescaling approach NEW-OS can reduce total cost effectively on both consistent and inconsistent cost matrices.

In detail, pairwise *t*-tests at 95% significance level indicate that on consistent cost matrices, the traditional rescaling approach OLD-OS is effective on only two data sets, that is, *abalone* and *car*, while the new rescaling approach NEW-OS is effective on six data sets, that is, *syn-b*, *syn-f*, *abalone*, *balance*, *car*, and *cmc*; on inconsistent cost matrices, the traditional rescaling approach OLD-OS is effective on only five data sets, that is, *abalone*, *balance*, *car*, *cmc* and *connect4*, while the new rescaling approach NEW-OS is effective on 14 data sets, that is, *mfeat-fouri*, *syn-a* to *syn-f*, *abalone*, *balance*, *car*, *cmc*, *connect4*, *page*, and *satellite*. Moreover, on consistent cost matrices, NEW-OS performs significantly better than OLD-OS on five data sets, that is, *abalone*, *balance*, *cmc*, *connect4*, and *solarflare2*; on inconsistent cost matrices, NEW-OS also performs significantly better than OLD-OS on 15 data sets, that is, except on *segment*, *waveform*, *ann*, *balance*, and *connect4*. These comparisons are summarized in Table 8, which presents the win/tie/loss counts of the approach on the row over

TABLE 8. Summary of the Comparisons (Win/Tie/Loss) of the Approach on the Row over the Approach on the Column, with Over-Sampling-Based Cost-Sensitive C4.5 under Pairwise t -Tests at 95% Significance Level (CCM: Consistent Cost Matrices, ICM: Inconsistent Cost Matrices).

	On CCM		On ICM	
	BLIND-OS	OLD-OS	BLIND-OS	OLD-OS
OLD-OS	2/15/3	—	5/8/7	—
NEW-OS	6/13/1	5/15/0	14/5/1	15/4/1

the approach on the column. In contrast to traditional rescaling approach OLD-OS, NEW-OS only degenerates the performance on the severely imbalanced data set *ann* on inconsistent cost matrix. This is similar to the observation of instance-weighting methods (Table 5).

4.3.3. On Under-Sampling-Based Cost-Sensitive C4.5. Results of the traditional rescaling approach and the new rescaling approach on under-sampling-based cost-sensitive C4.5 on consistent cost matrices and inconsistent ones are summarized in Tables 9 and 10. The results are similar to that of over-sampling methods. The traditional rescaling approach OLD-US often performs worse than or undistinguishable with cost-blind learner BLIND-C45, no matter on balanced or imbalanced data sets and on consistent or inconsistent cost matrices. While the new rescaling approach NEW-US can reduce total cost effectively on both consistent and inconsistent cost matrices.

In detail, pairwise t -tests at 95% significance level indicate that on consistent cost matrices, the traditional rescaling approach OLD-US is effective on only four data sets, that is, *syn-d* to *syn-f* and *abalone*, while the new rescaling approach NEW-US is effective on 11 data sets, that is, *mfeat-fouri*, *syn-a* to *syn-f*, *abalone*, *balance*, *cmc*, and *solarflare2*; on inconsistent cost matrices, the traditional rescaling approach OLD-US is effective on only four data sets, that is, *syn-b*, *waveform*, *abalone*, and *cmc*, while the new rescaling approach NEW-US is effective on 13 data sets, that is, *mfeat-fouri*, *syn-b* to *syn-f*, *waveform*, *abalone*, *balance*, *cmc*, *page*, *satellite*, and *solarflare2*. Moreover, on consistent cost matrices, NEW-US performs significantly better than OLD-US on 14 data sets, that is, except on *segment*, *syn-a*, *ann*, *car*, *satellite*, and *splice*; on inconsistent cost matrices, NEW-US also performs significantly better than OLD-US on 12 data sets, that is, *mfeat-fouri*, *syn-b* to *syn-f*, *waveform*, *abalone*, *car*, *page*, *satellite*, and *splice*. These comparisons are summarized in Table 11, which presents the win/tie/loss counts of the approach on the row over the approach on the column.

Note that the performance of the new rescaling approach NEW-US is almost always significantly better than or at least comparable to that of the traditional rescaling approach OLD-US, except that on inconsistent cost matrices NEW-US degenerates the performance on *vowel*, which has the largest number of classes in Table 2.

4.3.4. On Threshold-Moving-Based Cost-Sensitive Neural Networks. Results of the traditional rescaling approach and the new rescaling approach on threshold-moving-based cost-sensitive neural networks on consistent cost matrices and inconsistent ones are summarized in Tables 12 and 13, respectively. Note that, data sets of *connect4* and *splice* are excluded because the training time costs are too expensive. The results show that no matter on balanced or imbalanced data sets and on consistent or inconsistent cost matrices, the

TABLE 9. Comparison of Misclassification Costs on Consistent Cost Matrices, with Under-Sampling-Based Cost-Sensitive C4.5.

	BLIND-C45	OLD-US	NEW-US
<i>mfeat-fouri</i>	519.234 \pm 149.108	0.983 \pm 0.143	0.898 \pm 0.155
<i>segment</i>	49.705 \pm 21.601	1.396 \pm 0.255	1.391 \pm 0.197
<i>syn-a</i>	183.307 \pm 114.119	0.946 \pm 0.144	0.837 \pm 0.169
<i>syn-b</i>	401.059 \pm 267.163	0.908 \pm 0.207	0.839 \pm 0.157
<i>syn-c</i>	265.313 \pm 259.115	0.941 \pm 0.121	0.895 \pm 0.114
<i>syn-d</i>	328.491 \pm 124.408	0.975 \pm 0.034	0.932 \pm 0.090
<i>syn-e</i>	772.547 \pm 262.066	0.929 \pm 0.084	0.876 \pm 0.101
<i>syn-f</i>	1,697.866 \pm 529.724	0.919 \pm 0.068	0.846 \pm 0.077
<i>vowel</i>	134.036 \pm 19.500	1.388 \pm 0.113	1.283 \pm 0.117
<i>waveform</i>	243.195 \pm 102.328	0.952 \pm 0.142	0.926 \pm 0.138
<i>avg.</i>	459.475 \pm 457.202	1.034 \pm 0.180	0.972 \pm 0.187
<i>abalone</i>	638.828 \pm 191.028	0.813 \pm 0.195	0.753 \pm 0.198
<i>ann</i>	4.806 \pm 1.517	1.124 \pm 0.206	1.183 \pm 0.156
<i>balance</i>	71.045 \pm 43.063	1.080 \pm 0.159	0.903 \pm 0.151
<i>car</i>	43.287 \pm 13.971	1.472 \pm 0.363	1.357 \pm 0.317
<i>cmc</i>	243.007 \pm 137.347	0.919 \pm 0.156	0.825 \pm 0.176
<i>connect4</i>	5,032.208 \pm 3,447.362	0.993 \pm 0.150	0.935 \pm 0.153
<i>page</i>	122.133 \pm 106.107	0.998 \pm 0.093	0.929 \pm 0.090
<i>satellite</i>	502.146 \pm 150.719	1.027 \pm 0.053	1.013 \pm 0.066
<i>solarflare2</i>	194.899 \pm 91.457	0.873 \pm 0.226	0.831 \pm 0.210
<i>splice</i>	56.124 \pm 26.992	1.089 \pm 0.086	1.143 \pm 0.192
<i>avg.</i>	690.848 \pm 1,460.572	1.039 \pm 0.172	0.987 \pm 0.179

NOTE: For the cost-blind approach BLIND-C45, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

new rescaling approach NEW-NN performs apparently better than the traditional approach OLD-NN.

In detail, pairwise *t*-tests at 95% significance level indicate that on consistent cost matrices, the traditional rescaling approach OLD-NN is effective on 10 data sets, that is, *mfeat-fouri*, *syn-a*, *syn-b*, *syn-d* to *syn-f*, *vowel*, *waveform*, *abalone*, and *satellite*, while the new rescaling approach NEW-US is effective on 12 data sets, that is, *mfeat-fouri*, *syn-a*, *syn-b*, *syn-d* to *syn-f*, *vowel*, *waveform*, *abalone*, *cmc*, *page*, and *satellite*; on inconsistent cost matrices, the traditional rescaling approach OLD-NN is effective on 10 data sets, that is, *syn-b*, *syn-c*, *syn-e*, *waveform*, *abalone*, *ana*, *balance*, *cmc*, *page*, and *satellite*; while the new rescaling approach NEW-NN is effective on 16 data sets, that is, except on *syn-a* and *waveform*. Moreover, on consistent cost matrices, NEW-NN performs significantly better than OLD-NN on 11 data sets, that is, *mfeat-fouri*, *syn-b*, *syn-c*, *syn-e*, *syn-f*, *waveform*, *abalone*, *balance*, *cmc*, *page*, and *solarflare2*; on inconsistent cost matrices, NEW-NN also performs significantly better than OLD-NN on 14 data sets, that is, except on *syn-a*, *waveform*, *abalone* and *cmc*. These comparisons are summarized in Table 14, which presents the win/tie/loss counts of the approach on the row over the approach on the column. Note that

TABLE 10. Comparison of Misclassification Costs on Inconsistent Cost Matrices, with Under-Sampling-Based Cost-Sensitive C4.5.

	BLIND-C45	OLD-US	NEW-US
<i>mfeat-fouri</i>	263.160 \pm 33.881	1.031 \pm 0.053	0.885 \pm 0.058
<i>segment</i>	36.970 \pm 9.976	1.179 \pm 0.200	1.236 \pm 0.195
<i>syn-a</i>	298.570 \pm 70.731	0.981 \pm 0.104	0.921 \pm 0.130
<i>syn-b</i>	630.370 \pm 144.257	0.866 \pm 0.156	0.719 \pm 0.178
<i>syn-c</i>	321.080 \pm 99.375	1.003 \pm 0.072	0.943 \pm 0.056
<i>syn-d</i>	310.660 \pm 31.072	1.010 \pm 0.023	0.982 \pm 0.031
<i>syn-e</i>	945.850 \pm 98.469	0.983 \pm 0.058	0.920 \pm 0.086
<i>syn-f</i>	1,932.570 \pm 270.314	1.038 \pm 0.074	0.931 \pm 0.072
<i>vowel</i>	99.610 \pm 6.757	1.199 \pm 0.104	1.273 \pm 0.117
<i>waveform</i>	385.690 \pm 51.752	0.927 \pm 0.093	0.849 \pm 0.090
avg.	522.453 \pm 530.594	1.022 \pm 0.096	0.966 \pm 0.160
<i>abalone</i>	1,035.280 \pm 137.578	0.662 \pm 0.095	0.557 \pm 0.115
<i>ann</i>	7.760 \pm 2.606	1.272 \pm 0.527	1.114 \pm 0.369
<i>balance</i>	72.770 \pm 10.371	0.968 \pm 0.121	0.944 \pm 0.082
<i>car</i>	71.820 \pm 16.628	1.248 \pm 0.196	0.886 \pm 0.191
<i>cmc</i>	369.410 \pm 80.939	0.890 \pm 0.106	0.869 \pm 0.127
<i>connect4</i>	7,135.720 \pm 716.498	1.012 \pm 0.069	1.006 \pm 0.108
<i>page</i>	99.150 \pm 13.520	0.989 \pm 0.065	0.899 \pm 0.061
<i>satellite</i>	479.250 \pm 62.999	1.002 \pm 0.046	0.908 \pm 0.059
<i>solarflare2</i>	153.460 \pm 21.653	0.997 \pm 0.057	0.936 \pm 0.097
<i>splice</i>	71.210 \pm 20.969	1.127 \pm 0.107	0.977 \pm 0.092
avg.	949.583 \pm 2,082.987	1.017 \pm 0.166	0.910 \pm 0.136

NOTE: For the cost-blind approach BLIND-C45, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

TABLE 11. Summary of the Comparisons (Win/Tie/Loss) of the Approach on the Row over the Approach on the Column, with Under-Sampling-Based Cost-Sensitive C4.5 under Pairwise *t*-Tests at 95% Significance Level (CCM: Consistent Cost Matrices, ICM: Inconsistent Cost Matrices).

	On CCM		On ICM	
	BLIND-US	OLD-US	BLIND-US	OLD-US
OLD-US	4/12/4	—	4/11/5	—
NEW-US	11/5/4	14/6/0	13/5/2	12/7/1

the performance of the new rescaling approach NEW-NN is always significantly better than or at least comparable to that of the traditional rescaling approach OLD-NN.

4.3.5. On Threshold-Moving-Based Cost-Sensitive PETs. Results of the traditional rescaling approach and the new rescaling approach on threshold-moving-based cost-sensitive PETs on consistent cost matrices and inconsistent ones are summarized in Tables 15 and 16, respectively. Note that *splice* has been excluded for expensive training cost. The results show

TABLE 12. Comparison of Misclassification Costs on Consistent Cost Matrices, with Threshold-Moving-Based Cost-Sensitive Neural Networks.

	BLIND-NN	OLD-NN	NEW-NN
<i>mfeat-fouri</i>	448.927 \pm 127.321	0.929 \pm 0.047	0.897 \pm 0.058
<i>segment</i>	66.516 \pm 55.500	1.009 \pm 0.124	1.009 \pm 0.152
<i>syn-a</i>	170.932 \pm 106.006	0.913 \pm 0.114	0.827 \pm 0.134
<i>syn-b</i>	403.054 \pm 285.367	0.864 \pm 0.160	0.832 \pm 0.156
<i>syn-c</i>	351.051 \pm 385.771	0.872 \pm 0.188	0.842 \pm 0.202
<i>syn-d</i>	326.244 \pm 124.987	0.899 \pm 0.077	0.862 \pm 0.121
<i>syn-e</i>	721.096 \pm 234.199	0.922 \pm 0.096	0.861 \pm 0.117
<i>syn-f</i>	1,671.320 \pm 611.758	0.923 \pm 0.072	0.830 \pm 0.112
<i>vowel</i>	106.110 \pm 13.855	0.938 \pm 0.084	0.922 \pm 0.083
<i>waveform</i>	160.247 \pm 67.895	0.932 \pm 0.089	0.907 \pm 0.099
<i>avg.</i>	442.550 \pm 449.336	0.920 \pm 0.038	0.879 \pm 0.054
<i>abalone</i>	629.272 \pm 173.747	0.740 \pm 0.273	0.683 \pm 0.234
<i>ana</i>	63.101 \pm 24.587	0.993 \pm 0.038	0.978 \pm 0.042
<i>balance</i>	19.029 \pm 10.530	1.188 \pm 0.305	1.035 \pm 0.196
<i>car</i>	3.706 \pm 1.989	1.018 \pm 0.375	1.045 \pm 0.364
<i>cmc</i>	234.423 \pm 134.851	0.936 \pm 0.111	0.857 \pm 0.146
<i>page</i>	185.597 \pm 152.299	0.908 \pm 0.113	0.876 \pm 0.115
<i>satellite</i>	423.719 \pm 140.078	0.967 \pm 0.044	0.956 \pm 0.057
<i>solarflare2</i>	197.231 \pm 88.437	0.912 \pm 0.160	0.884 \pm 0.163
<i>avg.</i>	219.510 \pm 200.843	0.958 \pm 0.118	0.914 \pm 0.110

NOTE: For the cost-blind approach BLIND-NN, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

that no matter on balanced or imbalanced data sets and on consistent or inconsistent cost matrices, the new rescaling approach NEW-PETS often performs better than the traditional approach OLD-PETS.

In detail, pairwise t -tests at 95% significance level indicate that on consistent cost matrices, the traditional rescaling approach OLD-PETS is effective on only 8 data sets, that is, *mfeat-fouri*, *syn-a*, *syn-c* to *syn-f*, *abalone* and *satellite*, while the new rescaling approach NEW-PETS is effective on 14 data sets, that is, *mfeat-fouri*, *syn-a* to *syn-f*, *waveform*, *abalone*, *ana*, *balance*, *cmc*, *satellite*, and *solarflare2*; on inconsistent cost matrices, the traditional rescaling approach OLD-PETS is effective on 9 data sets, that is, *syn-b*, *syn-c*, *syn-e*, *waveform*, *abalone*, *ana*, *balance*, *cmc*, and *satellite*; while the new rescaling approach NEW-PETS is effective on 14 data sets, that is, except on *segment*, *syn-a*, *vowel*, *balance*, and *splice*. Moreover, on consistent cost matrices, NEW-PETS performs significantly better than OLD-PETS on 9 data sets, that is, *syn-b* to *syn-f*, *waveform*, *abalone*, *cmc*, and *solarflare2*; on inconsistent cost matrices, NEW-PETS also performs significantly better than OLD-PETS on 12 data sets, that is, *mfeat-fouri*, *syn-b* to *syn-f*, *waveform*, *abalone*, *car*, *page*, *satellite*, and *solarflare2*. These comparisons are summarized in Table 17, which presents the win/tie/loss counts of the approach on the row over the approach on the column.

Note that the performance of the new rescaling approach NEW-PETS is almost always significantly better than or at least comparable to that of the traditional rescaling approach

TABLE 13. Comparison of Misclassification Costs on Inconsistent Cost Matrices, with Threshold-Moving-Based Cost-Sensitive Neural Networks.

	BLIND-NN	OLD-NN	NEW-NN
<i>mfeat-fouri</i>	225.920 \pm 34.994	0.997 \pm 0.010	0.769 \pm 0.068
<i>segment</i>	45.180 \pm 13.617	0.996 \pm 0.044	0.664 \pm 0.104
<i>syn-a</i>	275.360 \pm 73.258	0.977 \pm 0.141	1.036 \pm 0.277
<i>syn-b</i>	576.470 \pm 163.870	0.870 \pm 0.139	0.767 \pm 0.174
<i>syn-c</i>	354.430 \pm 117.165	0.961 \pm 0.066	0.838 \pm 0.106
<i>syn-d</i>	305.510 \pm 36.737	0.979 \pm 0.048	0.923 \pm 0.082
<i>syn-e</i>	886.860 \pm 121.234	0.959 \pm 0.054	0.907 \pm 0.059
<i>syn-f</i>	1,945.720 \pm 324.002	1.018 \pm 0.036	0.902 \pm 0.160
<i>vowel</i>	79.760 \pm 7.415	1.002 \pm 0.030	0.201 \pm 0.043
<i>waveform</i>	251.240 \pm 32.211	0.937 \pm 0.074	0.961 \pm 0.078
<i>avg.</i>	494.645 \pm 536.216	0.970 \pm 0.040	0.797 \pm 0.223
<i>abalone</i>	1,056.720 \pm 177.200	0.514 \pm 0.132	0.505 \pm 0.109
<i>ann</i>	159.590 \pm 53.319	0.865 \pm 0.078	0.566 \pm 0.172
<i>balance</i>	18.990 \pm 5.064	0.880 \pm 0.106	0.672 \pm 0.544
<i>car</i>	6.650 \pm 1.814	0.990 \pm 0.093	0.236 \pm 0.136
<i>cmc</i>	359.880 \pm 76.709	0.900 \pm 0.067	0.924 \pm 0.097
<i>page</i>	135.470 \pm 20.785	0.986 \pm 0.020	0.835 \pm 0.066
<i>satellite</i>	392.520 \pm 54.484	0.981 \pm 0.021	0.797 \pm 0.044
<i>solarflare2</i>	163.660 \pm 22.006	0.983 \pm 0.035	0.926 \pm 0.061
<i>avg.</i>	286.685 \pm 318.933	0.887 \pm 0.149	0.683 \pm 0.223

NOTE: For the cost-blind approach BLIND-NN, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

TABLE 14. Summary of the Comparisons (Win/Tie/Loss) of the Approach on the Row over the Approach on the Column, with Threshold-Moving-Based Cost-Sensitive Neural Networks under Pairwise t -Tests at 95% Significance Level (CCM: Consistent Cost Matrices, ICM: Inconsistent Cost Matrices).

	On CCM		On ICM	
	BLIND-NN	OLD-NN	BLIND-NN	OLD-NN
OLD-NN	10/7/1	—	10/8/0	—
NEW-NN	12/6/0	11/7/0	16/2/0	14/4/0

OLD-PETs, except that on consistent cost matrix NEW-PETs degenerates the performance on *vowel*, and on inconsistent cost matrix NEW-PETs degenerates the performance on *segment*, *vowel*, and *balance*.

4.3.6. On Hard-Ensemble. Results of the traditional rescaling approach and the new rescaling approach on hard-ensemble on consistent cost matrices and inconsistent ones are summarized in Tables 18 and 19, respectively. Note that the data sets of *connect4* and *splice* are excluded due to large training costs. The results show that no matter on balanced or

TABLE 15. Comparison of Misclassification Costs on Consistent Cost Matrices, with Threshold-Moving-Based Cost-Sensitive PETs.

	BLIND-PETs	OLD-PETs	NEW-PETs
<i>mfeat-fouri</i>	418.733 \pm 132.237	0.766 \pm 0.177	0.750 \pm 0.187
<i>segment</i>	37.964 \pm 16.736	1.065 \pm 0.148	1.063 \pm 0.134
<i>syn-a</i>	177.656 \pm 109.686	0.902 \pm 0.111	0.833 \pm 0.155
<i>syn-b</i>	384.189 \pm 257.609	0.924 \pm 0.200	0.854 \pm 0.158
<i>syn-c</i>	268.297 \pm 272.123	0.886 \pm 0.132	0.860 \pm 0.144
<i>syn-d</i>	325.016 \pm 122.656	0.916 \pm 0.044	0.869 \pm 0.091
<i>syn-e</i>	749.290 \pm 245.784	0.917 \pm 0.091	0.846 \pm 0.115
<i>syn-f</i>	1,655.351 \pm 518.293	0.910 \pm 0.080	0.829 \pm 0.088
<i>vowel</i>	49.091 \pm 8.360	1.616 \pm 0.865	1.870 \pm 0.789
<i>waveform</i>	180.887 \pm 74.479	0.927 \pm 0.153	0.899 \pm 0.135
<i>avg.</i>	424.647 \pm 454.649	0.983 \pm 0.222	0.967 \pm 0.310
<i>abalone</i>	623.453 \pm 195.308	0.802 \pm 0.246	0.719 \pm 0.211
<i>ann</i>	5.562 \pm 1.715	0.941 \pm 0.158	0.900 \pm 0.106
<i>balance</i>	56.768 \pm 28.060	1.014 \pm 0.216	0.895 \pm 0.177
<i>car</i>	31.631 \pm 11.008	1.678 \pm 1.034	1.562 \pm 0.951
<i>cmc</i>	244.490 \pm 141.046	0.907 \pm 0.259	0.792 \pm 0.210
<i>page</i>	107.752 \pm 96.702	0.963 \pm 0.172	0.926 \pm 0.143
<i>satellite</i>	355.520 \pm 114.963	0.938 \pm 0.083	0.929 \pm 0.075
<i>solarflare2</i>	196.000 \pm 86.847	0.873 \pm 0.256	0.817 \pm 0.218
<i>splice</i>	56.620 \pm 31.991	1.396 \pm 0.439	1.183 \pm 0.202
<i>avg.</i>	186.422 \pm 188.436	1.057 \pm 0.271	0.969 \pm 0.242

NOTE: For the cost-blind approach BLIND-PETs, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

imbalanced data sets and on consistent or inconsistent cost matrices, the new rescaling approach NEW-HE often performs better than the traditional approach OLD-HE.

In detail, pairwise *t*-tests at 95% significance level indicate that on consistent cost matrices, the traditional rescaling approach OLD-HE is effective on only 7 data sets, that is, *mfeat-fouri*, *syn-a*, *syn-c* to *syn-f*, and *abalone*, while the new rescaling approach NEW-HE is effective on 13 data sets, that is, *mfeat-fouri*, *segment*, *syn-a* to *syn-f*, *abalone*, *cmc*, *page*, *satellite*, and *solarflare2*; on inconsistent cost matrices, the traditional rescaling approach OLD-HE is effective on only 6 data sets, that is, *syn-b*, *syn-c*, *syn-e*, *abalone*, *ann*, and *cmc*; while the new rescaling approach NEW-HE is effective on 14 data sets, that is, except on *segment*, *syn-a*, *vowel*, and *balance*. Moreover, on consistent cost matrices, NEW-HE performs significantly better than OLD-HE on 8 data sets, that is, *mfeat-fouri*, *syn-b*, *syn-c*, *syn-e*, *syn-f*, *abalone*, *balance*, and *cmc*; on inconsistent cost matrices, NEW-HE also performs significantly better than OLD-HE on 12 data sets, that is, *mfeat-fouri*, *syn-b* to *syn-f*, *waveform*, *abalone*, *car*, *page*, *satellite*, and *solarflare2*. These comparisons are summarized in Table 20, which presents the win/tie/loss counts of the approach on the row over the approach on the column.

Note that the performance of the new rescaling approach NEW-HE is almost always significantly better than or at least comparable to that of the traditional rescaling approach

TABLE 16. Comparison of Misclassification Costs on Inconsistent Cost Matrices, with Threshold-Moving-Based Cost-Sensitive PETs.

	BLIND-PETs	OLD-PETs	NEW-PETs
<i>mfeat-fouri</i>	205.610 \pm 32.906	1.006 \pm 0.031	0.900 \pm 0.070
<i>segment</i>	28.510 \pm 5.251	0.972 \pm 0.063	1.105 \pm 0.158
<i>syn-a</i>	294.560 \pm 67.730	0.957 \pm 0.134	0.913 \pm 0.204
<i>syn-b</i>	605.650 \pm 131.970	0.863 \pm 0.142	0.718 \pm 0.178
<i>syn-c</i>	316.090 \pm 99.284	0.965 \pm 0.059	0.919 \pm 0.061
<i>syn-d</i>	308.570 \pm 30.130	0.980 \pm 0.040	0.918 \pm 0.043
<i>syn-e</i>	920.450 \pm 97.264	0.966 \pm 0.048	0.900 \pm 0.076
<i>syn-f</i>	1,885.890 \pm 272.657	1.054 \pm 0.091	0.906 \pm 0.052
<i>vowel</i>	36.750 \pm 4.191	1.130 \pm 0.148	2.129 \pm 0.290
<i>waveform</i>	287.500 \pm 36.583	0.924 \pm 0.115	0.827 \pm 0.086
<i>avg.</i>	488.958 \pm 528.092	0.982 \pm 0.068	1.023 \pm 0.379
<i>abalone</i>	989.080 \pm 134.838	0.614 \pm 0.132	0.565 \pm 0.121
<i>ann</i>	9.270 \pm 3.149	0.771 \pm 0.233	0.752 \pm 0.176
<i>balance</i>	60.610 \pm 9.091	0.886 \pm 0.116	0.973 \pm 0.171
<i>car</i>	53.720 \pm 10.473	1.088 \pm 0.328	0.694 \pm 0.112
<i>cmc</i>	369.040 \pm 75.675	0.830 \pm 0.155	0.830 \pm 0.119
<i>page</i>	84.440 \pm 9.597	0.989 \pm 0.040	0.925 \pm 0.051
<i>satellite</i>	327.770 \pm 43.759	0.958 \pm 0.063	0.916 \pm 0.069
<i>solarflare2</i>	161.720 \pm 22.767	1.002 \pm 0.071	0.918 \pm 0.089
<i>splice</i>	69.270 \pm 20.981	1.022 \pm 0.089	1.702 \pm 1.440
<i>avg.</i>	236.102 \pm 291.535	0.907 \pm 0.140	0.919 \pm 0.303

NOTE: For the cost-blind approach BLIND-PETs, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

TABLE 17. Summary of the Comparisons (Win/Tie/Loss) of the Approach on the Row over the Approach on the Column, with Threshold-Moving-Based Cost-Sensitive PETs under Pairwise *t*-Tests at 95% Significance Level (CCM: Consistent Cost Matrices, ICM: Inconsistent Cost Matrices).

	On CCM		On ICM	
	BLIND-PETs	OLD-PETs	BLIND-PETs	OLD-PETs
OLD-PETs	8/8/3	—	9/8/2	—
NEW-PETs	14/3/2	9/9/1	14/3/2	12/4/3

OLD-HE, except that on inconsistent cost matrix NEW-HE degenerates the performance on *vowel* and *balance*. This may due to the bad performance of NEW-PETs on these two data sets.

4.3.7. On Soft-Ensemble. Results of the traditional rescaling approach and the new rescaling approach on soft-ensemble on consistent cost matrices and inconsistent ones are

TABLE 18. Comparison of Misclassification Costs on Consistent Cost Matrices, with Hard Ensemble.

	BLIND-HE	OLD-HE	NEW-HE
<i>mfeat-fouri</i>	440.897 \pm 131.414	0.797 \pm 0.090	0.727 \pm 0.144
<i>segment</i>	38.822 \pm 17.798	0.971 \pm 0.166	0.933 \pm 0.076
<i>syn-a</i>	179.693 \pm 112.241	0.908 \pm 0.129	0.818 \pm 0.173
<i>syn-b</i>	393.070 \pm 269.940	0.911 \pm 0.222	0.841 \pm 0.163
<i>syn-c</i>	272.346 \pm 280.122	0.899 \pm 0.143	0.860 \pm 0.141
<i>syn-d</i>	322.880 \pm 125.611	0.933 \pm 0.058	0.891 \pm 0.115
<i>syn-e</i>	742.669 \pm 249.527	0.928 \pm 0.090	0.854 \pm 0.111
<i>syn-f</i>	1644.759 \pm 524.431	0.922 \pm 0.077	0.837 \pm 0.091
<i>vowel</i>	61.599 \pm 12.972	1.137 \pm 0.209	1.130 \pm 0.193
<i>waveform</i>	171.874 \pm 71.724	0.957 \pm 0.151	0.946 \pm 0.163
<i>avg.</i>	426.861 \pm 450.460	0.936 \pm 0.080	0.884 \pm 0.101
<i>abalone</i>	635.580 \pm 181.127	0.760 \pm 0.244	0.698 \pm 0.221
<i>ann</i>	5.078 \pm 1.583	0.952 \pm 0.137	0.936 \pm 0.157
<i>balance</i>	54.578 \pm 32.800	1.161 \pm 0.362	0.886 \pm 0.226
<i>car</i>	29.380 \pm 10.467	0.973 \pm 0.218	0.899 \pm 0.164
<i>cmc</i>	242.139 \pm 141.374	0.898 \pm 0.180	0.798 \pm 0.189
<i>page</i>	115.079 \pm 103.127	0.901 \pm 0.118	0.874 \pm 0.098
<i>satellite</i>	369.969 \pm 125.912	0.941 \pm 0.095	0.938 \pm 0.097
<i>solarflare2</i>	197.014 \pm 89.608	0.845 \pm 0.220	0.809 \pm 0.190
<i>avg.</i>	206.102 \pm 198.611	0.929 \pm 0.108	0.855 \pm 0.076

NOTE: For the cost-blind approach BLIND-HE, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

summarized in Tables 21 and 22, respectively. Similar to hard-ensemble, the data sets of *connect4* and *splice* are also excluded due to large training costs. The results show that no matter on balanced or imbalanced data sets and on consistent or inconsistent cost matrices, the new rescaling approach NEW-SE often performs better than the traditional approach OLD-SE.

In detail, pairwise *t*-tests at 95% significance level indicate that on consistent cost matrices, the traditional rescaling approach OLD-SE is effective on 9 data sets, that is, *mfeat-fouri*, *syn-a*, *syn-c* to *syn-f*, *abalone*, *page* and *satellite*, while the new rescaling approach NEW-SE is effective on 12 data sets, that is, *mfeat-fouri*, *segment*, *syn-a* to *syn-f*, *abalone*, *cmc*, *satellite*, and *solarflare2*; on inconsistent cost matrices, the traditional rescaling approach OLD-SE is effective on only 5 data sets, that is, *syn-b*, *abalone*, *ann*, *cmc*, and *solarflare2*; while the new rescaling approach NEW-SE is effective on 15 data sets, that is, except on *vowel*, *balance*, and *car*. Moreover, on consistent cost matrices, NEW-SE performs significantly better than OLD-SE on 10 data sets, that is, *mfeat-fouri*, *syn-b* to *syn-f*, *abalone*, *balance*, *cmc*, and *solarflare2*; on inconsistent cost matrices, NEW-SE also performs significantly better than OLD-SE on 16 data sets, that is, except on *vowel* and *ann*. These comparisons are summarized in Table 23, which presents the win/tie/loss counts of the approach on the row over the approach on the column. The performance of the new rescaling approach NEW-SE is always significantly better than or at least comparable to that of the traditional rescaling approach OLD-SE.

TABLE 19. Comparison of Misclassification Costs on Inconsistent Cost Matrices, with Hard Ensemble.

	BLIND-HE	OLD-HE	NEW-HE
<i>mfeat-fouri</i>	203.470 \pm 33.931	0.993 \pm 0.026	0.869 \pm 0.088
<i>segment</i>	28.630 \pm 6.521	1.032 \pm 0.127	1.023 \pm 0.143
<i>syn-a</i>	289.370 \pm 67.958	0.973 \pm 0.123	0.925 \pm 0.178
<i>syn-b</i>	598.060 \pm 140.337	0.888 \pm 0.163	0.737 \pm 0.181
<i>syn-c</i>	315.530 \pm 97.097	0.974 \pm 0.040	0.926 \pm 0.053
<i>syn-d</i>	301.640 \pm 34.250	0.998 \pm 0.036	0.940 \pm 0.052
<i>syn-e</i>	911.780 \pm 98.200	0.966 \pm 0.043	0.919 \pm 0.078
<i>syn-f</i>	1,865.960 \pm 277.697	1.050 \pm 0.083	0.923 \pm 0.067
<i>vowel</i>	40.540 \pm 5.022	1.254 \pm 0.179	1.690 \pm 0.282
<i>waveform</i>	271.570 \pm 36.239	0.973 \pm 0.109	0.896 \pm 0.122
<i>avg.</i>	482.655 \pm 522.796	1.010 \pm 0.091	0.985 \pm 0.245
<i>abalone</i>	1,045.530 \pm 147.300	0.574 \pm 0.124	0.532 \pm 0.113
<i>ann</i>	8.650 \pm 3.278	0.861 \pm 0.183	0.887 \pm 0.181
<i>balance</i>	57.010 \pm 9.399	0.938 \pm 0.144	1.039 \pm 0.181
<i>car</i>	48.960 \pm 9.381	1.123 \pm 0.078	0.901 \pm 0.158
<i>cmc</i>	362.320 \pm 78.018	0.873 \pm 0.089	0.870 \pm 0.109
<i>page</i>	87.650 \pm 11.293	1.011 \pm 0.054	0.922 \pm 0.064
<i>satellite</i>	341.050 \pm 41.437	0.978 \pm 0.061	0.908 \pm 0.069
<i>solarflare2</i>	158.640 \pm 21.785	0.969 \pm 0.056	0.909 \pm 0.104
<i>avg.</i>	263.726 \pm 320.718	0.916 \pm 0.150	0.871 \pm 0.137

NOTE: For the cost-blind approach BLIND-HE, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

TABLE 20. Summary of the Comparisons (Win/Tie/Loss) of the Approach on the Row over the Approach on the Column, with Hard Ensemble under Pairwise *t*-Tests at 95% Significance Level (CCM: Consistent Cost Matrices, ICM: Inconsistent Cost Matrices).

	On CCM		On ICM	
	BLIND-HE	OLD-HE	BLIND-HE	OLD-HE
OLD-HE	7/11/0	-	6/9/3	-
NEW-HE	13/5/0	8/10/0	14/3/1	12/4/2

4.3.8. Summary. The results presented in this section lead to the following observations: (1) the traditional rescaling approach often fails to reduce total cost on multi-class problems; (2) the new rescaling approach is always significantly better than both the cost-blind learner and the traditional rescaling approach on multi-class problems; (3) it is better to implement rescaling approach by reweighting and threshold-moving, rather than re-sampling; (4) NEW-NN and NEW-SE are better choices because they are always better than or at least comparable to the traditional rescaling approach; (5) severe class-imbalance often has larger influence on the new rescaling approach than on the traditional approach.

TABLE 21. Comparison of Misclassification Costs on Consistent Cost Matrices, with Soft Ensemble.

	BLIND-SE	OLD-SE	NEW-SE
<i>mfeat-fouri</i>	417.914 \pm 129.608	0.885 \pm 0.092	0.813 \pm 0.157
<i>segment</i>	41.699 \pm 22.844	0.945 \pm 0.155	0.916 \pm 0.099
<i>syn-a</i>	176.953 \pm 112.094	0.928 \pm 0.112	0.873 \pm 0.133
<i>syn-b</i>	399.396 \pm 286.315	0.910 \pm 0.223	0.843 \pm 0.162
<i>syn-c</i>	266.583 \pm 267.039	0.914 \pm 0.132	0.876 \pm 0.133
<i>syn-d</i>	322.836 \pm 123.024	0.947 \pm 0.063	0.915 \pm 0.082
<i>syn-e</i>	736.488 \pm 247.209	0.948 \pm 0.070	0.882 \pm 0.094
<i>syn-f</i>	1,643.114 \pm 515.857	0.931 \pm 0.065	0.856 \pm 0.077
<i>vowel</i>	73.628 \pm 14.725	1.050 \pm 0.145	1.017 \pm 0.223
<i>waveform</i>	172.007 \pm 73.724	0.975 \pm 0.128	0.964 \pm 0.161
<i>avg.</i>	425.062 \pm 448.662	0.943 \pm 0.042	0.895 \pm 0.057
<i>abalone</i>	621.336 \pm 186.558	0.815 \pm 0.195	0.754 \pm 0.210
<i>ann</i>	5.177 \pm 1.452	0.918 \pm 0.163	0.935 \pm 0.166
<i>balance</i>	46.590 \pm 24.133	1.288 \pm 0.259	1.007 \pm 0.237
<i>car</i>	12.493 \pm 4.372	1.886 \pm 0.464	1.695 \pm 0.292
<i>cmc</i>	235.005 \pm 132.978	0.910 \pm 0.135	0.824 \pm 0.167
<i>page</i>	120.512 \pm 109.471	0.886 \pm 0.104	0.873 \pm 0.091
<i>satellite</i>	389.222 \pm 127.422	0.929 \pm 0.080	0.917 \pm 0.079
<i>solarflare2</i>	194.285 \pm 88.661	0.868 \pm 0.199	0.825 \pm 0.184
<i>avg.</i>	203.077 \pm 199.210	1.062 \pm 0.339	0.979 \pm 0.280

NOTE: For the cost-blind approach BLIND-SE, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

4.4. On Class-Imbalance Learning

Cost-sensitive learning approaches have been deemed as good solutions to class-imbalance learning (Chawla et al. 2002; Weiss 2004). Therefore, it is interesting to see whether the RESCALE_{new} approach can work well on learning from imbalanced multi-class data sets. Actually, although class-imbalance learning is an important topic, few work has been devoted to the study of multi-class class-imbalance learning.

We conduct experiments on the ten imbalanced data sets shown in the second half of Table 2. Note that equal misclassification costs are used here. In other words, the experiments are conducted to evaluate the performance of RESCALE_{new} on pure class-imbalance learning.

In the experiments C4.5 decision tree is still used as the baseline which does not take into account the class-imbalance information (still denoted by BLIND-C45). For the RESCALE_{new} approach, considering that the influences of the smaller classes should be increased while that of the larger classes should be decreased by the rescaling process, the reciprocals of the sizes of the classes are used as the rescaling information. For example, if the i th class has n_i number of examples, then cost_{ij} ($j \in \{1..c\}$ and $j \neq i$) in equation (9) is set to $1/n_i$. Note that because $\text{cost}_{ij} = \text{cost}_{ik}$ ($j, k \in \{1..c\}$ and $j, k \neq i$), the resulting equation (10) always has nontrivial solutions; this is somewhat similar to the case of cost-sensitive learning with consistent cost matrices.

TABLE 22. Comparison of Misclassification Costs on Inconsistent Cost Matrices, with Soft Ensemble.

	BLIND-SE	OLD-SE	NEW-SE
<i>mfeat-fouri</i>	204.080 \pm 30.955	1.002 \pm 0.031	0.844 \pm 0.078
<i>segment</i>	30.990 \pm 7.388	0.965 \pm 0.072	0.796 \pm 0.130
<i>syn-a</i>	286.040 \pm 68.429	0.984 \pm 0.118	0.860 \pm 0.132
<i>syn-b</i>	593.970 \pm 125.057	0.900 \pm 0.154	0.731 \pm 0.179
<i>syn-c</i>	314.810 \pm 96.160	0.987 \pm 0.040	0.921 \pm 0.058
<i>syn-d</i>	302.370 \pm 33.879	1.010 \pm 0.031	0.937 \pm 0.038
<i>syn-e</i>	911.240 \pm 99.053	0.975 \pm 0.044	0.892 \pm 0.069
<i>syn-f</i>	1,882.180 \pm 277.663	1.054 \pm 0.075	0.897 \pm 0.061
<i>vowel</i>	53.300 \pm 6.315	1.095 \pm 0.135	1.062 \pm 0.157
<i>waveform</i>	271.410 \pm 33.421	0.987 \pm 0.090	0.899 \pm 0.125
<i>avg.</i>	485.039 \pm 525.794	0.996 \pm 0.049	0.884 \pm 0.083
<i>abalone</i>	1,004.630 \pm 133.650	0.669 \pm 0.125	0.509 \pm 0.081
<i>ann</i>	9.200 \pm 3.299	0.813 \pm 0.184	0.775 \pm 0.188
<i>balance</i>	46.700 \pm 8.703	1.147 \pm 0.197	0.927 \pm 0.135
<i>car</i>	25.720 \pm 7.435	1.886 \pm 0.284	1.451 \pm 0.331
<i>cmc</i>	360.390 \pm 79.887	0.887 \pm 0.088	0.797 \pm 0.125
<i>page</i>	91.240 \pm 11.665	0.988 \pm 0.047	0.868 \pm 0.046
<i>satellite</i>	359.390 \pm 47.972	0.976 \pm 0.060	0.819 \pm 0.073
<i>solarflare2</i>	157.380 \pm 20.148	0.973 \pm 0.048	0.893 \pm 0.085
<i>avg.</i>	256.831 \pm 311.578	1.042 \pm 0.345	0.880 \pm 0.247

NOTE: For the cost-blind approach BLIND-SE, the absolute misclassification costs are reported; for the rescaling approaches, the ratios of their misclassification costs against that of the cost-blind approach are presented. The best performance of each row is boldfaced.

TABLE 23. Summary of the Comparisons (Win/Tie/Loss) of the Approach on the Row over the Approach on the Column, with Soft Ensemble under Pairwise *t*-Tests at 95% Significance Level (CCM: Consistent Cost Matrices, ICM: Inconsistent Cost Matrices).

	On CCM		On ICM	
	BLIND-SE	OLD-SE	BLIND-SE	OLD-SE
OLD-SE	9/7/2	—	5/9/4	—
NEW-SE	12/5/1	10/8/0	15/2/1	16/2/0

The MAUC measure (Hand and Till 2001) is used to evaluate the performance, which is a variant of AUC designed for multi-class class-imbalance learning. The larger the MAUC value, the better the performance. Ten times 10-fold cross validation are executed and the results in the form of “mean \pm standard deviation” are tabulated in Table 24, where the best performance of each row is boldfaced.

Pairwise *t*-tests at 95% significance level indicate that the performance of RESCALE_{new} is significantly better than that of the standard C4.5 decision tree on 6 data sets, that is, *abalone*, *ann*, *cmc*, *page*, *satellite*, and *solarflare2*, worse on *car* and *connect4*, and there is

TABLE 24. Comparison on MAUC Values on Pure Class-Imbalance Learning.

Data Set	BLIND-C45	RESCALE _{new}
<i>abalone</i>	0.707 \pm 0.005	0.713 \pm 0.005
<i>ann</i>	0.995 \pm 0.001	0.999 \pm 0.000
<i>balance</i>	0.752 \pm 0.013	0.757 \pm 0.011
<i>car</i>	0.975 \pm 0.003	0.968 \pm 0.006
<i>cmc</i>	0.679 \pm 0.010	0.690 \pm 0.008
<i>connect4</i>	0.843 \pm 0.001	0.824 \pm 0.003
<i>page</i>	0.969 \pm 0.005	0.977 \pm 0.003
<i>satellite</i>	0.962 \pm 0.002	0.964 \pm 0.002
<i>solarflare2</i>	0.878 \pm 0.003	0.903 \pm 0.004
<i>splice</i>	0.975 \pm 0.001	0.975 \pm 0.001
<i>ave.</i>	0.874 \pm 0.116	0.877 \pm 0.114

NOTE: The best performance of each row is boldfaced.

no significant difference on *balance* and *splice*. This suggests that RESCALE_{new} can also be used to address pure class-imbalance learning on multi-class problems.

5. CONCLUSION

This article extends our preliminary work (Zhou and Liu 2006a) which tries to explore why rescaling, a general and the most popular cost-sensitive learning approach, is effective on two-class problems yet ineffective on multi-class problems. Our analysis discloses that applying rescaling directly to multi-class problems can obtain good performance only when the costs are consistent. Although costs in real-world applications are not random and consistent costs do appear in many practical tasks, many problems are with inconsistent costs. We advocate that the examination of the cost consistency should be taken as a sanity check for the rescaling approach. When the check is passed, rescaling can be executed directly; otherwise rescaling should be executed after decomposing the multi-class problem into a series of two-class problems. Empirical study shows that our proposal is not only helpful to multi-class cost-sensitive learning, but also useful in multi-class class-imbalance learning.

Unequal misclassification costs and class-imbalance often occur simultaneously. How to rescale the classes under this situation, however, remains an open problem (Liu and Zhou 2006). Our empirical results coincide with Liu and Zhou (2006) on that when the class-imbalance is not serious, using the cost information to rescale the classes can work well on most data sets; but this could not apply to seriously imbalanced data sets. Exploring the ground under this observation and designing appropriate rescaling schemes for such cases are important future issues.

This article focuses on the rescaling approach. Note that in addition to rescaling, there are also other kinds of cost-sensitive learning approaches. However, as mentioned before, only a few studies dedicated to multi-class cost-sensitive learning (Abe et al. 2004; Zhou and Liu 2006b; Lozano and Abe 2008; Zhang and Zhou 2008). Although multi-class problems can be converted into a series of two-class problems to solve, users usually favor a more direct solution. So, investigating multi-class cost-sensitive learning approaches without decomposition is an important future work. In most cost-sensitive learning studies, the cost

matrices are usually fixed, while in some real-world tasks the costs may change due to many reasons. Designing effective methods for cost-sensitive learning with variable cost matrices is another interesting issue for future work. Furthermore, developing powerful tools for visually evaluating multi-class cost-sensitive learning approaches, such as the ROC and cost curves for two-class cases, is also an interesting future issue.

ACKNOWLEDGMENTS

We want to thank anonymous reviewers for helpful comments and suggestions, and Qi Qian for proof-reading the article. This work was supported by the National Science Foundation of China (60635030, 60721002), the National Fundamental Research Program of China (2010CB327903) and the Jiangsu Science Foundation (BK2008018).

REFERENCES

- ABE, N., B. ZADROZNY, and J. LANGFORD. 2004. An iterative method for multi-class cost-sensitive learning. *In* Proceedings of the 10th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. Seattle, WA, pp. 3–11.
- ALLWEIN, E. L., R. E. SCHAPIRE, and Y. SINGER. 2000. Reducing multiclass to binary: A unifying approach for margin classifiers. *Journal of Machine Learning Research*, **1**:113–141.
- BLAKE, C., E. KEOGH, and C. J. MERZ. 1998. UCI repository of machine learning databases. [<http://www.ics.uci.edu/~mllearn/MLRepository.html>], Department of Information and Computer Science, University of California, Irvine, CA.
- BREFELD, U., P. GEIBEL, and F. WYSOTZKI. 2003. Support vector machines with example dependent costs. *In* Proceedings of the 14th European Conference on Machine Learning. Cavtat-Dubrovnik, Croatia, pp. 23–34.
- BREIMAN, L., J. H. FRIEDMAN, R. A. OLSEN, and C. J. STONE. 1984. Classification and Regression Trees. Wadsworth, Belmont, CA.
- CEBE, M., and C. GUNDUZ-DEMIR. 2007. Test-cost sensitive classification based on conditioned loss functions. *In* Proceeding of the 18th European Conference on Machine Learning. Warsaw, Poland, pp. 551–558.
- CHAI, X., L. DENG, Q. YANG, and C. X. LING. 2004. Test-cost sensitive naive Bayes classification. *In* Proceeding of the 4th IEEE International Conference on Data Mining. Brighton, UK, pp. 51–58.
- CHAWLA, N. V., K. W. BOWYER, L. O. HALL, and W. P. KEGELMEYER. 2002. SMOTE: Synthetic minority over-sampling technique. *Journal of Artificial Intelligence Research*, **16**:321–357.
- DOMINGOS, P. 1999. MetaCost: A general method for making classifiers cost-sensitive. *In* Proceedings of the 5th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. San Diego, CA, pp. 155–164.
- DRUMMOND, C., and R. C. HOLTE. 2000. Explicitly representing expected cost: An alternative to ROC representation. *In* Proceedings of the 6th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. Boston, MA, pp. 198–207.
- DRUMMOND, C., and R. C. HOLTE. 2003. C4.5, class imbalance, and cost sensitivity: Why under-sampling beats over-sampling. *In* Working Notes of the ICML'03 Workshop on Learning from Imbalanced Data Sets. Washington, DC.
- ELKAN, C. 2001. The foundations of cost-sensitive learning. *In* Proceedings of the 17th International Joint Conference on Artificial Intelligence. Seattle, WA, pp. 973–978.
- HAND, D. J., and R. J. TILL. 2001. A simple generalisation of the area under the ROC curve for multiple class classification problems. *Machine Learning*, **45**(2):171–186.

- LING, C. X., Q. YANG, J. WANG, and S. ZHANG. 2004. Decision trees with minimal costs. *In* Proceedings of the 21st International Conference on Machine Learning. Banff, Canada, pp. 69–76.
- LIU, X.-Y., and Z.-H. ZHOU. 2006. The influence of class imbalance on cost-sensitive learning: An empirical study. *In* Proceedings of the 6th IEEE International Conference on Data Mining. Hong Kong, China, pp. 970–974.
- LOZANO, A. C., and N. ABE. 2008. Multi-class cost-sensitive boosting with p-norm loss functions. *In* Proceedings of the 14th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. Las Vegas, NV, pp. 506–514.
- MALOOF, M. A. 2003. Learning when data sets are imbalanced and when costs are unequal and unknown. *In* Working Notes of the ICML'03 Workshop on Learning from Imbalanced Data Sets. Washington, DC.
- MARGINEANTU, D. 2001. Methods for cost-sensitive learning. Ph.D. Thesis, Department of Computer Science, Oregon State University, Corvallis, OR.
- MASNADI-SHIRAZI, H., and N. VASCONCELOS. 2007. Asymmetric boosting. *In* Proceeding of the 24th International Conference on Machine Learning. Corvallis, OR, pp. 609–619.
- PROVOST, F., and P. DOMINGOS. 2003. Tree induction for probability-based ranking. *Machine Learning*, **52**(3):199–215.
- SAITTA, L. (Ed.). 2000. *Machine Learning—A Technological Roadmap*. University of Amsterdam, Amsterdam, the Netherlands.
- TING, K. M. 2002. An instance-weighting method to induce cost-sensitive trees. *IEEE Transactions on Knowledge and Data Engineering*, **14**(3):659–665.
- TURNEY, P. D. 2000. Types of cost in inductive concept learning. *In* Proceedings of the ICML'2000 Workshop on Cost-Sensitive Learning. Stanford, CA, pp. 15–21.
- WEISS, G. M. 2004. Mining with rarity—problems and solutions: A unifying framework. *SIGKDD Explorations*, **6**(1):7–19.
- WITTEN, I. H., and E. FRANK. 2005. *Data Mining: Practical Machine Learning Tools and Techniques with Java Implementations* (2nd ed.). Morgan Kaufmann, San Francisco, CA.
- ZADROZNY, B., and C. ELKAN. 2001. Learning and making decisions when costs and probabilities are both unknown. *In* Proceedings of the 7th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. San Francisco, CA, pp. 204–213.
- ZADROZNY, B., J. LANGFORD, and N. ABE. 2002. A simple method for cost-sensitive learning. Technical Report, IBM.
- ZHANG, Y., and Z.-H. ZHOU. 2008. Cost-sensitive face recognition. *In* Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition. Anchorage, AK.
- ZHOU, Z.-H., and X.-Y. LIU. 2006a. On multi-class cost-sensitive learning. *In* Proceeding of the 21st National Conference on Artificial Intelligence. Boston, MA, pp. 567–572.
- ZHOU, Z.-H., and X.-Y. LIU. 2006b. Training cost-sensitive neural networks with methods addressing the class imbalance problem. *IEEE Transactions on Knowledge and Data Engineering*, **18**(1):63–77.