

C3100-24F



Specification

Hardware	Description
Performance	- Switching Capacity: 128 Gbps - Forwarding rate: 95.2 Mpps
Interface	24 port 100/1000 Base-X 4 port 1G/10G
Memory	- DRAM 512 MB - Flash 256 MB
FAN	Dual Fixed FANs
Management	1-port RJ-45 Console 1-port USB
Power Supply	- Dual Fixed power supplies - Power Consumption: 38W - Heat Dissipation: 129.7 BTU/h
Environment	- Operating Temperature: 0~50°C - Operating Humidity: 10~90% (Non-condensing)
Dimension	440(W) x 320(D) x 44(H) mm 1 RU

Software	Description
Virtualization	- VS: Virtual Stacking - Max 8 Units Stack - MAD: Multi-Active Detection - MVS: Mixed Virtual Stacking
Entry	16K MAC Table 512 IPv4 routes 4K Active VLAN 12KB Jumbo frame
VLAN	- MAC / Protocol / IP Subnet based - QinQ 802.1Q - Private VLAN / Super-VLAN - Voice VLAN - GVRP
STP / Ring Protocol and LP	- Standard STP / RSTP / MSTP - PVSTP+ Compatible protocol - Loop Detection and Prevention - ERPS - BPDUGuard / BPDUGuard Filter / Root Guard - Link Flap Detection
Aggregation	- Static Link Aggregation - Dynamic Link Aggregation(LACP) - Member per group: 8

Software	Description	
Multicast	• IGMP Snooping(with Querier and Fast Leave)	• Multicast VLAN
	• IGMP Filter	• IGMP Snooping static group
IPv6	• IPv4/IPv6 dual stack	• IPv6 Management
	• IPv6 ACL	
L3 Features	• Support full L3 features without additional license	
	• Static / RIP / OSPF	• PBR(Policy-based Routing)
Security	• VRRP	• Gateway Keepalive
	• L2~L4-based ACL	• Port ACL, VLAN ACL, Global ACL
	• Time-based ACL	• 802.1x authentication
	• Port Security	• DHCP Snooping
	• Dynamic ARP Inspection	• IP Source Guard
	• DoS/DDoS Protection	• Anti-ARP Spoofing prevention
	• CPP(CPU Protection Policy)	• MAC Address Limiting
	• Enforced Password Change Upon First Login	• Strong Password Policy and Encryption Mechanism
	• ID/PW authentication *	• User isolation after APT prevention system interoperability *
	• MAC based authentication *	• Checking the required security configuration *
	• Network segmentation *	• User control by schedule *
QoS	• 8 Queues	• Queue Scheduling: SP / WRR / SP+WRR
	• Classification and Marking with DSCP /802.1p	• Traffic Shaping and Policing
	• Policy-Based QoS	• Tail-drop and WRED(Weighted Random Early Detection)
	• Buffer Management	• Upload / download bandwidth control per user *
SDN	• Netconf	
Reliability	• OS Image Redundancy	• Configuration Redundancy
	• Hot Patch	• Hardware Watchdog
Management Features	• Ping and Traceroute	• Console, Telnet and SSHv2
	• SNMPv1/2c/3 and RMON	• LLDP / LLDP-MED
	• Mirroring / Remote mirroring / VLAN mirroring	• 1:1, N:N Mirroring
	• NTP	• DHCP Server/Relay/Client
	• AAA(Authentication, Authorization, Accounting)	• RADIUS & TACACS+
	• Syslog	• Configuration Rollback

* CoreEdge Smart Controller required.

Software	Description
Management Features	• DDM(Digital Diagnostic Monitoring)
	• ULFD (Uni-Directional Link Fault Detection)
	• Flow Monitoring
	• RBAC(Role-Based Access Control)
	• RTR(Response Time Reporter) for quality checking
	• BSM features for switch diagnostics
	• Embedded Event Script
	• FTP / SFTP
	• CSS is a sophisticated suite of management tools that provides a simplified approach.
	• ZTP(Zero Touch Provisioning) *
Test Report	• Sanity Report for switch and terminal *
	• Scheduled firmware upgrade *
	• Scheduled config backup *
	• Auto-Backup/Upgrade/Provisioning/Recovery *
	• End Device Management *
	• Switch Shaped Panel *
	• System Health Monitoring *
Certification	• IP & Asset Management *
	• Terminal Vulnerability Scanning *
	• Dynamic Policy Enforcement *
Test Report	• Performance Test Report – Electronics and Telecommunications Research Institute(ETRI)
	• KC Electro-Magnetic Compatibility – National Radio Research Agency(NRRA)
Certification	• Security Functionality Certificate – National Intelligence Service(NIS)

* CoreEdge Smart Controller required.

Standards	Description
IEEE	• IEEE 802.3ab 1000BASE-T
	• IEEE 802.3z 1000BASE-X
	• IEEE 802.3ae 10G BASE-X
	• IEEE 802.3an 10G BASE-T
	• IEEE 802.3az EEE(Energy Efficient Ethernet)
	• IEEE 802.3x Flow Control
	• IEEE 802.3ad Link Aggregation Control Protocol
	• IEEE 802.1AX Link Aggregation
	• IEEE 802.3ah (Ethernet in the First Mile)
	• IEEE 802.1ag CFM(Connectivity Fault Management)
IEEE	• IEEE 802.1D STP(Spanning Tree Protocol)
	• IEEE 802.1w RSTP(Rapid Spanning Tree Protocol)
	• IEEE 802.1s MSTP(Multiple Spanning Tree Protocol)
	• IEEE 802.1x(Port-Based Network Access Control)
IEEE	• IEEE 802.1ad Provider Bridges(Q-in-Q)
	• IEEE 802.1Q VLAN Tagging
IEEE	• IEEE 802.1v VLAN Classification by Protocol & Port
IEEE	• IEEE 802.1AB LLDP(Link Layer Discovery Protocol)

Standards	Description
RFC	• RFC 768 UDP (User Datagram Protocol)
	• RFC 791 IP (Internet Protocol)
	• RFC 792 ICMP (Internet Control Message Protocol)
	• RFC 793 TCP (Transmission Control Protocol)
	• RFC 826 ARP (Address Resolution Protocol)
	• RFC 854/855 Telnet and Tenet options
	• RFC 894 Core IP Implementation for Ethernet
	• RFC 919 IP Subnet Broadcasting
	• RFC 950 & RFC 951 Internet Standard Subnetting Procedure & BootP
	• RFC 1027 Proxy ARP
	• RFC 1035 DNS Client
	• RFC 1042 IP over IEEE 802 Networks
	• RFC 1058 RIP (Routing Information Protocol)
	• RFC 1071 Internet Checksum Calculation
	• RFC 1122 Internet Host Requirements
	• RFC 1157 SNMP
	• RFC 1191 Path MTU Discovery
	• RFC 1213 MIB-II
	• RFC 1239 Standard MIB
	• RFC 1350 TFTP (Trivial File Transfer Protocol)
	• RFC 1591 DNS (Domain Name System)
	• RFC 1724 RIPv2 MIB Extension
	• RFC 1812 Requirements for IPv4 Routers
	• RFC 1918 IP Addressing
	• RFC 1981 Path MTU Discovery for IPv6
	• RFC 2082 RIP-2 MD5 Authentication
	• RFC 2131 DHCPv4 Client
	• RFC 2328 OSPF Version 2
	• RFC 2453 RIPv2
	• RFC 2460 IPv6 Specification
	• RFC 2464 Transmission of IPv6 Packets over Ethernet Networks
	• RFC 2578 SMIv2
	• RFC 2581 TCP Congestion Control
	• RFC 2711 IPv6 Router Alert Option
	• RFC 2819 RMON MIB (groups 1,2,3 & 9)
	• RFC 2863 Interfaces Group MIB
	• RFC 2865 RADIUS Authentication
	• RFC 2866 RADIUS Accounting
	• RFC 3021 Using 31-Bit Prefixes on IPv4 Point-to-Point Links
	• RFC 3046 DHCP Relay Agent Information Option
	• RFC 3315 DHCPv6 Client
	• RFC 3411 SNMP Architecture
	• RFC 3414 USM for SNMPv3
	• RFC 3416 v2 of the Protocol Operations for the SNMP
	• RFC 3418 MIB for SNMP
	• RFC 3587 IPv6 Global Unicast Address Format
	• RFC 3484 Default Address Selection for IPv6
	• RFC 3596 DNS Extensions for IPv6
	• RFC 3646 DNS Configuration Options for DHCPv6
	• RFC 3768 VRRP
	• RFC 4007 IPv6 Scoped Address Architecture
	• RFC 4022 TCP (MIB for the Transmission Control Protocol)
	• RFC 4113 MIB for the UDP (User Datagram Protocol)
	• RFC 4213 Transition Mechanisms for IPv6 Hosts & Routers
	• RFC 4291 IPv6 Addressing Architecture
	• RFC 4292 IP Forwarding Table MIB
	• RFC 4293 MIB for the IP (Internet Protocol)
	• RFC 4318 Definitions of Managed Objects for Bridges with RSTP
	• RFC 4330 SNTP version 4
	• RFC 4443 ICMPv6
	• RFC 4861 Neighbor Discovery for IPv6
	• RFC 5014 IPv6 Socket API for Source Address Selection
	• RFC 5095 Deprecation of Type 0 Routing Headers in IPv6
	• RFC 5424 Syslog Protocol
	• RFC 5905 NTP version 4