

# CS2000-8P



## Specification

| Hardware                          | Description                             |                                                                 |
|-----------------------------------|-----------------------------------------|-----------------------------------------------------------------|
| <b>Performance</b>                | • Switching Capacity: 20 Gbps           | • Forwarding rate: 14.8 Mpps                                    |
| <b>Interface</b>                  | • 8 port 10/100/1000 Base-T             | • 2 port 1000 Base-X (SFP)                                      |
| <b>Memory</b>                     | • DRAM 128 MB                           | • Flash 32 MB                                                   |
| <b>PoE</b>                        | • PoE/PoE+ supported                    | • Max 140W PoE supported                                        |
| <b>FAN</b>                        | • Fanless                               |                                                                 |
| <b>Management</b>                 | • 1-port RJ-45 Console                  |                                                                 |
| <b>Power Supply</b>               | • Single Fixed Power Supply             |                                                                 |
|                                   | • Power Consumption: 11 / 151W with PoE | • Heat Dissipation: 37.5 / 515.4 BTU/h with PoE                 |
| <b>Environment</b>                | • Operating Temperature: 0°C~50°C       | • Operating Humidity: 10~90% (Non-condensing)                   |
| <b>Dimension</b>                  | • 280(W) x 180(D) x 44(H) mm            |                                                                 |
| Software                          | Description                             |                                                                 |
| <b>Entry</b>                      | • 8K MAC Table                          | • 4K Active VLAN                                                |
|                                   | • 9KB Jumbo frame                       |                                                                 |
| <b>VLAN</b>                       | • MAC / Protocol / IP Subnet based      | • QinQ                                                          |
|                                   | • 802.1Q                                | • Private VLAN                                                  |
|                                   | • Voice VLAN                            | • GVRP                                                          |
| <b>STP / Ring Protocol and LP</b> | • Standard STP / RSTP / MSTP            | • ERPS                                                          |
|                                   | • Loop Detection and Prevention         | • BPDU Guard / BPDU Filter / Root Guard                         |
| <b>Aggregation</b>                | • Static Link Aggregation               | • Dynamic Link Aggregation(LACP)                                |
| <b>Multicast</b>                  | • IGMP Snooping v1/2/3                  | • IGMP Fast Leave                                               |
| <b>IPv6</b>                       | • IPv4/IPv6 dual stack                  | • IPv6 Management & ACL                                         |
| <b>QoS</b>                        | • 8 Queues                              | • Trust COS / DSCP                                              |
|                                   | • Queue Scheduling: SP / WRR / WDRR     | • Classification & Marking with DSCP/802.1p                     |
|                                   | • Per-Port Rate Limiting                | • Storm Control: Broadcast, Multicast & Unknown Unicast Control |

| Software                   | Description                                                                                                                    |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| <b>Security</b>            | <ul style="list-style-type: none"> <li>• Port ACL</li> <li>• 802.1X Authentication</li> </ul>                                  |
|                            | <ul style="list-style-type: none"> <li>• Port Security</li> <li>• DHCP Snooping</li> </ul>                                     |
|                            | <ul style="list-style-type: none"> <li>• Dynamic ARP Inspection</li> <li>• MAC Address Limiting</li> </ul>                     |
| <b>Management Features</b> | <ul style="list-style-type: none"> <li>• Ping and Traceroute</li> <li>• Mirroring</li> </ul>                                   |
|                            | <ul style="list-style-type: none"> <li>• Console, Telnet and SSHv2</li> <li>• SNMPv1/2c/3 and RMON</li> </ul>                  |
|                            | <ul style="list-style-type: none"> <li>• LLDP / LLDP-MED</li> <li>• NTP</li> </ul>                                             |
|                            | <ul style="list-style-type: none"> <li>• DHCP Server/Relay/Client</li> <li>• Http / Https</li> </ul>                           |
|                            | <ul style="list-style-type: none"> <li>• Flow Monitoring</li> <li>• Syslog</li> </ul>                                          |
|                            | <ul style="list-style-type: none"> <li>• AAA(Authentication, Authorization, Accounting)</li> <li>• RADIUS / TACACS+</li> </ul> |
|                            | <ul style="list-style-type: none"> <li>• KC Electro-Magnetic Compatibility – National Radio Research Agency(NRRA)</li> </ul>   |
| <b>Certification</b>       | <ul style="list-style-type: none"> <li>• KC Safety – Korean Agency for Technology and Standards(KATS)</li> </ul>               |

| Standards   | Description                                                                                                                                                            |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>IEEE</b> | <ul style="list-style-type: none"> <li>• IEEE 802.3 10BASE-T</li> <li>• IEEE 802.3u 100BASE-T</li> </ul>                                                               |
|             | <ul style="list-style-type: none"> <li>• IEEE 802.3ab 1000BASE-T</li> <li>• IEEE 802.3z 1000BASE-X</li> </ul>                                                          |
|             | <ul style="list-style-type: none"> <li>• IEEE 802.3az EEE(Energy Efficient Ethernet)</li> <li>• IEEE 802.3x Flow Control</li> </ul>                                    |
|             | <ul style="list-style-type: none"> <li>• IEEE 802.3ad Link Aggregation Control Protocol</li> <li>• IEEE 802.1p (Class of Service Priority)</li> </ul>                  |
|             | <ul style="list-style-type: none"> <li>• IEEE 802.1D STP(Spanning Tree Protocol)</li> <li>• IEEE 802.1w RSTP(Rapid Spanning Tree Protocol)</li> </ul>                  |
|             | <ul style="list-style-type: none"> <li>• IEEE 802.1s MSTP(Multiple Spanning Tree Protocol)</li> <li>• IEEE 802.1x(Port-Based Network Access Control)</li> </ul>        |
|             | <ul style="list-style-type: none"> <li>• IEEE 802.1ad Provider Bridges(Q-in-Q)</li> <li>• IEEE 802.1Q VLAN Tagging</li> </ul>                                          |
|             | <ul style="list-style-type: none"> <li>• IEEE 802.1v VLAN Classification by Protocol &amp; Port</li> <li>• IEEE 802.1AB LLDP(Link Layer Discovery Protocol)</li> </ul> |
|             | <ul style="list-style-type: none"> <li>• IEEE 802.3af PoE</li> <li>• IEEE 802.3at PoE+</li> </ul>                                                                      |
|             |                                                                                                                                                                        |

| Standards | Description                                           |
|-----------|-------------------------------------------------------|
| RFC       | • RFC 768 UDP (User Datagram Protocol)                |
|           | • RFC 791 IP (Internet Protocol)                      |
|           | • RFC 792 ICMP (Internet Control Message Protocol)    |
|           | • RFC 793 TCP (Transmission Control Protocol)         |
|           | • RFC 826 ARP (Address Resolution Protocol)           |
|           | • RFC 854/855 Telnet and Tenet options                |
|           | • RFC 1157 SNMP                                       |
|           | • RFC 1213 MIB-II                                     |
|           | • RFC 1239 Standard MIB                               |
|           | • RFC 1918 IP Addressing                              |
|           | • RFC 2131 DHCPv4 Client                              |
|           | • RFC 2578 SMIPv2                                     |
|           | • RFC 2581 TCP Congestion Control                     |
|           | • RFC 2819 RMON MIB (groups 1,2,3 & 9)                |
|           | • RFC 2863 Interfaces Group MIB                       |
|           | • RFC 2865 RADIUS Authentication                      |
|           | • RFC 2866 RADIUS Accounting                          |
|           | • RFC 3046 DHCP Relay Agent Information Option        |
|           | • RFC 3411 SNMP Architecture                          |
|           | • RFC 3414 USM for SNMPv3                             |
|           | • RFC 3416 v2 of the Protocol Operations for the SNMP |
|           | • RFC 3418 MIB for SNMP                               |
|           | • RFC 5424 Syslog Protocol                            |
|           | • RFC 5905 NTP version 4                              |