

CS2000-8T



Specification

Hardware	Description	
Performance	• Switching Capacity: 20 Gbps	• Forwarding rate: 14.8 Mpps
Interface	• 8 port 10/100/1000 Base-T	• 2 port 1000 Base-X (SFP)
Memory	• DRAM 128 MB	• Flash 32 MB
FAN	• Fanless	
Management	• 1-port RJ-45 Console	
Power Supply	• Single Fixed Power Supply	
	• Power Consumption: 8W	• Heat Dissipation: 27.3 BTU/h
Environment	• Operating Temperature: 0°C~50°C	• Operating Humidity: 10~90% (Non-condensing)
Dimension	• 280(W) x 180(D) x 44(H) mm	

Software	Description	
Entry	• 8K MAC Table	• 4K Active VLAN
	• 9KB Jumbo frame	
VLAN	• MAC / Protocol / IP Subnet based	• QinQ
	• 802.1Q	• Private VLAN
	• Voice VLAN	• GVRP
STP / Ring Protocol and LP	• Standard STP / RSTP / MSTP	• ERPS
	• Loop Detection and Prevention	• BPDU Guard / BPDU Filter / Root Guard
Aggregation	• Static Link Aggregation	• Dynamic Link Aggregation(LACP)
Multicast	• IGMP Snooping v1/2/3	• IGMP Fast Leave
IPv6	• IPv4/IPv6 dual stack	• IPv6 Management & ACL
	• 8 Queues	• Trust COS / DSCP
QoS	• Queue Scheduling: SP / WRR / WDRR	• Classification & Marking with DSCP/802.1p
	• Per-Port Rate Limiting	• Storm Control: Broadcast, Multicast & Unknown Unicast Control

Software	Description
Security	• Port ACL
	• 802.1X Authentication
	• Port Security
	• DHCP Snooping
Management Features	• DAI (Dynamic ARP Inspection)
	• IP Source Guard
	• Per-Port MAC Address Limiting
	• Mirroring
Certification	• Ping and Traceroute
	• Console, Telnet and SSHv2
	• SNMPv1/2c/3 and RMON
	• LLDP / LLDP-MED
IEEE	• DHCP Server/Relay/Client
	• NTP
	• Flow Monitoring
	• Http / Https
IEEE	• AAA(Authentication, Authorization, Accounting)
	• Syslog
	• RADIUS / TACACS+
	• KC Electro-Magnetic Compatibility – National Radio Research Agency(NRRA)

Standards	Description
IEEE	• IEEE 802.3 10BASE-T
	• IEEE 802.3u 100BASE-T
	• IEEE 802.3ab 1000BASE-T
	• IEEE 802.3z 1000BASE-X
	• IEEE 802.3az EEE(Energy Efficient Ethernet)
	• IEEE 802.3x Flow Control
	• IEEE 802.3ad Link Aggregation Control Protocol
	• IEEE 802.1p (Class of Service Priority)
IEEE	• IEEE 802.1D STP(Spanning Tree Protocol)
	• IEEE 802.1w RSTP(Rapid Spanning Tree Protocol)
	• IEEE 802.1s MSTP(Multiple Spanning Tree Protocol)
	• IEEE 802.1x(Port-Based Network Access Control)
IEEE	• IEEE 802.1ad Provider Bridges(Q-in-Q)
	• IEEE 802.1Q VLAN Tagging
IEEE	• IEEE 802.1v VLAN Classification by Protocol & Port
	• IEEE 802.1AB LLDP(Link Layer Discovery Protocol)

Standards	Description
RFC	• RFC 768 UDP (User Datagram Protocol)
	• RFC 791 IP (Internet Protocol)
	• RFC 792 ICMP (Internet Control Message Protocol)
	• RFC 793 TCP (Transmission Control Protocol)
	• RFC 826 ARP (Address Resolution Protocol)
	• RFC 854/855 Telnet and Tenet options
	• RFC 1157 SNMP
	• RFC 1213 MIB-II
	• RFC 1239 Standard MIB
	• RFC 1918 IP Addressing
	• RFC 2131 DHCPv4 Client
	• RFC 2578 SMIPv2
	• RFC 2581 TCP Congestion Control
	• RFC 2819 RMON MIB (groups 1,2,3 & 9)
	• RFC 2863 Interfaces Group MIB
	• RFC 2865 RADIUS Authentication
	• RFC 2866 RADIUS Accounting
	• RFC 3046 DHCP Relay Agent Information Option
	• RFC 3411 SNMP Architecture
	• RFC 3414 USM for SNMPv3
	• RFC 3416 v2 of the Protocol Operations for the SNMP
	• RFC 3418 MIB for SNMP
	• RFC 5424 Syslog Protocol
	• RFC 5905 NTP version 4