

CW2000-6i



Interface Specification	
Service Port	1*10/100/1000Mbps Base-T adaptive Ethernet Port, 802.3af PoE (LAN1) 1*10/100/1000Mbps Base-T adaptive Ethernet Port (LAN2)
USB Port	1*USB 2.0
Serial Console Interface	1*RJ45 Port
Power Interface	1*12VDC (Nominal, +/-5%)
Indicators	1*Multi-Color LED (For System and Radio status)
Reset Button	1*Rest Button (Factory reset; WPS)
Environment Specification	
Working Temperature	0°C to +45°C
Working Humidity	10% to 90% non-condensing
Storage Temperature	-40°C to +70°C
Storage Humidity	5% to 95% non-condensing
IP Rating	IP41
Weight	0.53 kg
Dimension(W*D*H) mm	197mm*197mm*58mm
Hardware Specification	
Installation Mode	Ceiling Mounting
Power Supply	Adapter: DC 12V/1.5A (optional) PoE Standard: IEEE 802.3af/802.3at-compliant (compatible). When both DC and PoE power sources are available, DC power takes priority over PoE.
Power Consumption	<13W (without USB output) The maximum transmit power of the AP complies with the regulations of different countries and regions
Radio Specification	
RF Design	Dual-band design: - Radio1: 2.4GHz, 2 streams: 2*2 - Radio2: 5GHz, 2 streams: 2*2
Operating Bands (Country-specific restrictions apply)	- Radio1: 2.400-2.4835GHz - Radio2: 5.150-5.350GHz, 5.47-5.725GHz, 5.725-5.850GHz

Transmission Rate	- 802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps - 802.11a/g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps - 802.11n: 6.5Mbps-300Mbps (MCS0-MCS31, HT20-HT40), 400Mbps with 256-QAM - 802.11ac: 6.5Mbps-866Mbps (MCS0-MCS9, NSS=1-2, VHT20-VHT160) - 802.11ax (2.4GHz): 8.6Mbps-574Mbps (MCS0-MCS11, NSS=1-2, HE20-HE40) - 802.11ax (5GHz): 8.6Mbps-2,402Mbps (MCS0-MCS11, NSS = 1-2, HE20-HE160)
Antenna	Built-in Intelligent Antennas
Antenna Gain	2.4GHz: 3.6dBi 5GHz: 5.8dBi
Maximum Transmit Power	2.4GHz: +23 dBm 5GHz: +23 dBm The actual transmit power complies with the regulatory requirements for radio frequency emissions in various countries and regions
Transmit Power Adjustment	1 dBm
Modulation Mode	- 802.11b: BPSK, QPSK, CCK - 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM - 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM - 802.11ax: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
Modulation and Encoding	- Low Density Parity Check (LDPC) - Maximum Likelihood Detection (MLD)
Advanced RF Features	- TPC (Transmit Power Control) - ACS (Automatic Channel Scanning)
WIFI Specification	
WIFI Standards	IEEE 802.11a/b/g/n/ac/ax
SSID Numbers	16*SSIDs
Channelization	20, 40, 80, 160 MHz
Recommend Users	64~125
Working Mode	Fit Mode
Security Type	Open, PSK, WPA-Personal, WPA-Enterprise, WPA2-Personal, WPA2-Enterprise, WPA3-Personal, WPA3-Enterprise, Portal, 802.1X, Radius
Working Bandwidth	- 802.11ax: HE160, HE80, HE40, HE20 - 802.11ac: VHT160, VHT80, VHT40, VHT20 - 802.11n: HT40, HT20
Date Rate	- Radio1: 2.4GHz, 574Mbps - Radio2: 5GHz, 2.402Gbps
MIMO Technologies	- Multi-User Multiple Input Multiple Output (MU-MIMO) - Maximum Ratio Combining (MRC) - Space-Time Block Coding (STBC) - Cyclic Delay/Cyclic Shift Diversity (CDD/CSD) - Dynamic MIMO power saving
Energy Saving	- U-APSD - SM Power Save - Green AP mode
Advanced WIFI Features	- Orthogonal Frequency Division Multiple Access (OFDMA) - Short GI (Short Guard Interval) - DFS (Dynamic Frequency Selection) - Spectrum Navigation