

IN3100-8TG



Specification

Hardware	Description		
Performance	• Switching capacity: 20 Gbps	• Forwarding rate: 14.8 Mpps	
Interface	• 8 port 10/100/1000 Base-T	• 2 port 1000 Base-X (SFP)	
Management	• 1-port RJ-45 Console	• 2 * DIP switch	
Power	• DC	• DC 12-55V	• Additional DC power supply is required.
FAN	• Fanless		
Environment	• Operating temperature: -40°C ~ 80°C	• Operating Humidity: 10~90% (non-condensing)	
Dimension	• 90(W) x 110(D) x 46(H) mm		

Software	Description		
Entry	• 8K MAC Table	• 4K Active VLAN	• 9K Jumbo Frame
VLAN	• 802.1Q	• QinQ	• MAC / Protocol / IP Subnet based VLAN
Redundancy / Loop prevention	• STP / RSTP / MSTP	• Loopback Detection	• ERPS
Aggregation	• Static Link Aggregation	• Dynamic Link Aggregation (LACP)	
Multicast	• IGMP Snooping v1/2/3	• IGMP Proxy	
IPv6	• IPv4/IPv6 dual stack	• IPv6 management & ACL	
Security	• ACL	• IEEE 802.1x	• Port Security
	• DHCP Snooping	• Dynamic ARP Inspection	• ARP Spoofing Prevention
QoS	• Trust COS / DSCP	• SP / WRR / WDRR	• 802.1p / DSCP
Management	• Telnet / SSH	• Http / Https	• LLDP / LLDP-MED
	• Mirroring	• SNMPv1/2c/3	• RADIUS / TACACS+