

#Presenting Data: Plotting Conditional Means {#plot_means}

The idea when plotting conditional means is to show how the outcome, or variable of interest, varies as a function of predictors.

Today we'll be working with a dataset from IBM which provide a standard HR dataset, which we can use to predict attrition. (*NB this is simulated data, no employee information is being disclosed*) Attrition in this case is defined as an employee leaving without being fired or retiring. Companies generally attempt to avoid attrition, as it's very expensive to search for and hire a replacement—better in general to keep the employees you have, provided they are doing their jobs. This means that it's important to predict who might leave in a given year. This information can be used in a targeted way in order to focus resources on the employees most likely to leave.

Setup for plotting conditional means

We start with a standard set of setup commands. Today we'll be working with **tidyverse**, as usual, along with a library called **forcats** which helps us to deal with the dreaded factor variables. To handle colors, we'll need the package **RColorBrewer**.

Next we load in the data.

Loading Data

```
load("attrition.Rdata")
```

Today, our primary outcome of interest will be attrition. This is a binary variable that is currently encoded as text—“Yes” or “No.” We need to encode it as a binary variable with 1 meaning yes and 0 meaning no. After recoding, we need to make sure that the new variable looks correct.

```
## Crate a new variable named attrit and define it as 0
at<-at%>%mutate(attrit=ifelse(Attrition=="Yes",1,0))
```

```
table(at$Attrition)
```

```
##
##   No   Yes
## 1233  237
```

```
table(at$attrit)
```

```
##
##    0    1
## 1233  237
```


```
table(at$attrit,at$Attrition)
```

```
##
##           No   Yes
##    0 1233     0
##    1    0  237
```

```
##Univariate Graphics
```


Univariate graphics help us understand what individual variables look like—how are they distributed across the sample? Here's a quick rundown on some univariate graphics. Say we wanted a quick count of who was in each department. We can use `geom_bar` to get this done. By default, this will give us a count in each department.

```
gg<-ggplot(at,aes(x=Department,fill=Department))
gg<-gg+geom_bar()
gg
```




The next univariate graphic you should know is for continuous variables. The first thing you generally want is a histogram.

```
gg<-ggplot(at,aes(x=DistanceFromHome))
gg<-gg+geom_histogram(binwidth = 1)
gg
```




Density plots provide a continuous graphic of the distribution of a variable:

```
gg<-ggplot(at,aes(x=DistanceFromHome))  
gg<-gg+geom_density()  
gg
```



```
## Changing bandwidth-- not recommended, just showing you how.  
gg<-gg+geom_density(bw=10)  
gg
```



Predicting Attrition

Our first prediction will use business travel as a predictor for attrition. There are three categories here— non travel, travel infrequently, and frequent travel. We'll calculate levels of attrition at each level and then take a look at the data.

```
at_sum<-at%>%
  group_by(BusinessTravel)%>%
  summarize(attr_avg=mean(attrit))
```

```
at_sum
```

```
## # A tibble: 3 x 2
##   BusinessTravel attr_avg
##   <chr>          <dbl>
## 1 Non-Travel     0.08
## 2 Travel_Frequently 0.249
## 3 Travel_Rarely   0.150
```

Remember that the mean of a binary variable indicates the proportion of the population that has a certain characteristics. So, in our case, 0.25 of the sample that travels frequently left the company in the last year. Our first plot will be a basic bar plot, showing the average levels of attrition.

To get started, let's see what this looks like in a table.

```

at %>%
  count(BusinessTravel, attrit) %>%
  group_by(BusinessTravel) %>%
  mutate(prop = prop.table(n)) %>%
  select(-n) %>%
  spread(attrit, prop) %>% kable()

```


BusinessTravel	0	1
Non-Travel	0.9200000	0.0800000
Travel_Frequently	0.7509025	0.2490975
Travel_Rarely	0.8504314	0.1495686

Now we can plot it:

```

## Bar Plot with aesthetics: mean attrition as height, business travel as cateogry
gg<-ggplot(at_sum, aes(x=BusinessTravel, y=attr_avg))
## Use bar plot geometry, height of bars set by level observed in dataset
gg<-gg+geom_bar(stat="Identity", fill="gold", color="black")
## Print
gg

```



This is fine, but it should really be in the order of the underlying variable. We can use `fct_reorder` to do this.


Side Note

What is a factor variable? In R, factor variables are used for categorical data. These are data elements that can take on one and only one value of a mutually exclusive and exhaustive list of elements. In our case, the travel variable is a factor– employees can be in Non-Travel, Travel Frequently or Travel Rarely bins. Everyone is one bin, and the bins cover all possible options. We use factors when numbers won't work– for characteristics like race or religion or political affiliation.

```
## Same aesthetics, but now ordered by level
gg<-ggplot(at_sum,aes(x=fct_reorder(BusinessTravel,attr_avg),y=attr_avg))

gg<-gg+geom_bar(stat="identity")

## Labeling
gg<-gg+xlab("Amount of Travel")+ylab("Yearly Attrition")
##Print
gg
```



Quick Exercise: Create a bar plot showing average attrition by department instead of travel

Dot Plots

A dot plot can be a good way of displaying conditional means as well. Many times dot plots are more easily understood if they are horizontal, so we'll use `coord_flip` to make it horizontal.


```
at_sum<-at%>%
  group_by(BusinessTravel)%>%
  summarize(attr_avg=mean(attrit))
```

```
at_sum
```

```
## # A tibble: 3 x 2
##   BusinessTravel attr_avg
##   <chr>          <dbl>
## 1 Non-Travel     0.08
## 2 Travel_Frequently 0.249
## 3 Travel_Rarely  0.150
```

```
## Now a dot plot
```

```
gg<-ggplot(at_sum,aes(x=reorder(BusinessTravel,-attr_avg),y=attr_avg))
gg<-gg+geom_point(color="gold",size=5)
gg<-gg+xlab("Travel")+ylab("Average Attrition")
gg<-gg+coord_flip()
gg
```



Conditional means using two predictors

We can use graphics to display conditional means at multiple levels of predictor levels. There are a couple of ways to get this done. When using bar plots we've got two basic tools: location and color. In the first example, we're going to plot attrition by travel and gender. We'll use color to indicate gender, and location to indicate travel.

```
## Summarize attrition by travel AND gender
at_sum<-at%>%
  group_by(BusinessTravel,Gender)%>%
```



```


summarize(attr_avg=mean(attrit))

## Get the results
at_sum

## # A tibble: 6 x 3
## # Groups:   BusinessTravel [3]
##   BusinessTravel Gender attr_avg
##   <chr>         <chr>    <dbl>
## 1 Non-Travel    Female  0.0612
## 2 Non-Travel    Male   0.0891
## 3 Travel_Frequently Female  0.256
## 4 Travel_Frequently Male   0.244
## 5 Travel_Rarely Female  0.128
## 6 Travel_Rarely Male   0.164

## Plot it using a bar plot
gg<-ggplot(at_sum,aes(x=fct_reorder(BusinessTravel,attr_avg),y=attr_avg,color=Gender))
gg<-gg+geom_bar(stat="identity",aes(fill=Gender),position="dodge")
gg<-gg+ylab("Pr(Attrition)") +xlab("Frequency of Travel")
gg


```



```

## Plot it using a dot plot
gg<-ggplot(at_sum,aes(x=reorder(BusinessTravel,attr_avg),y=attr_avg),color=Gender)
gg<-gg+geom_point(aes(color=Gender),size=5)
gg<-gg+coord_flip()
gg

```



- Quick Exercise: Create either a bar plot or a dot plot showing attrition by department AND field of education *


Side Note: Colors

What if we want to change colors? This is a little tricky for most people at first. `ggplot` thinks in terms of palettes, so you need to associate a palette with a characteristics of the graphic. Below, I replace the default palette with my own ugly one.

```
## Changing Colors
mypal<-c("lightblue","orange")

gg<-gg+scale_fill_manual(values =mypal )

gg<-gg+scale_color_manual(values =mypal )
## Print
gg
```




You can also use `RColorBrewer` which has a wide variety of palettes already built. Below I use the qualitative palette creatively named “Set1”.

```
## Another way, using color brewer palettes:
gg<-gg+scale_fill_brewer(palette = "Set1")
```

```
## Scale for 'fill' is already present. Adding another scale for 'fill',
## which will replace the existing scale.
```

```
gg
```



More Variables: faceting

We can continue this logic with three variables. Now we're going to summarize by Travel, Gender and Marital status. Here we're going to use an additional tool in our arsenal: Faceting. Faceting means making multiple graphs with the same structure. In the code below, we will arrange positions based on travel, color based on gender, and then split the graphic by marital status.


```
at_sum<-at%>%
  group_by(BusinessTravel,Gender,MaritalStatus)%>%
  summarize(attr_avg=mean(attrit))%>%
  arrange(-attr_avg)

at_sum
```

```
## # A tibble: 18 x 4
## # Groups:   BusinessTravel, Gender [6]
##   BusinessTravel Gender MaritalStatus attr_avg
##   <chr>          <chr> <chr>          <dbl>
## 1 Travel_Frequently Female Single         0.388
## 2 Travel_Frequently Male Single         0.383
## 3 Travel_Rarely Male Single         0.260
## 4 Travel_Frequently Female Divorced        0.208
## 5 Travel_Frequently Male Divorced        0.205
## 6 Non-Travel Female Single         0.2
## 7 Travel_Rarely Female Single         0.185
## 8 Travel_Frequently Male Married         0.176
```

```
## 9 Non-Travel      Male   Single      0.156
## 10 Travel_Frequently Female Married 0.136
## 11 Travel_Rarely  Male   Married 0.127
## 12 Travel_Rarely  Female Married 0.122
## 13 Travel_Rarely  Male   Divorced 0.109
## 14 Non-Travel     Male   Married 0.0833
## 15 Travel_Rarely  Female Divorced 0.0488
## 16 Non-Travel     Male   Divorced 0.0303
## 17 Non-Travel     Female Divorced 0
## 18 Non-Travel     Female Married 0
```

```
gg<-ggplot(at_sum,aes(x=reorder(BusinessTravel,attr_avg),
                             y=attr_avg,
                             fill=Gender))
## Bar plot, with unstacked (dodge)
gg<-gg+geom_bar(stat="identity",position="dodge")
## Separate out by Marital Status
gg<-gg+facet_wrap(~MaritalStatus)
## Change orientation to sideways
gg<-gg+coord_flip()
## Print
gg
```



Quick Exercise: Plot predicted attrition by Education Field, Department and Gender

Multiple Predictors for Conditional Means

One solution is to use facets, or lots of little graphs, which show how the pattern varies across different groups. In this case, our groups will be defined by gender and work/life balance.

