Autoryzacja GitHub

```
Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (lab6)
$ git status
On branch lab6
Untracked files:
  (use "git add <file>..." to include in what will be committed)
        ../../LAB4/
        ../lab5_examples.zip
        ../lab5_examples/
        ../../inne/

nothing added to commit but untracked files present (use "git add" to track)

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (lab6)
$ gh auth login
? Where do you use GitHub? GitHub.com
? What is your preferred protocol for Git operations on this host? SSH
? Upload your SSH public key to your GitHub account? C:\Users\Victus\.ssh\id_ed25519.pub
? Title for your SSH key: (GitHub CLI) GitHubCLI

? Title for your SSH key: GitHubCLI
? How would you like to authenticate GitHub CLI? Login with a web browser

! First copy your one-time code: D507-B20A
Press Enter to open https://github.com/login/device in your browser...
✓ Authentication complete.
- gh config set -h github.com git_protocol ssh
✓ Configured git protocol
✓ SSH key already existed on your GitHub account: C:\Users\Victus\.ssh\id_ed25519.pub
✓ Logged in as Kupi403
! You were already logged in to this account
```

Stworzenie repozytorium

```
Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (lab6)
$ git init
Initialized empty Git repository in C:/Users/Victus/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie/.git/

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ gh repo create pawcho6 --public --source=. --remote=origin --push
`--push` enabled but no commits found in C:\Users\Victus\VSCProjects\Studia VSC\Semestr 6\Chmura\LAB5\lab5_zadanie

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ git commit -m 'add lab5'
On branch master

Initial commit

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        Dockerfile
        README.md
        index.sh
        potwierdzenie.jpg

nothing added to commit but untracked files present (use "git add" to track)

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ git add .
warning: in the working copy of 'index.sh', LF will be replaced by CRLF the next time Git touches it

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ git commit -m 'add lab5'
[master (root-commit) 7f9e1aa] add lab5
 4 files changed, 100 insertions(+)
 create mode 100644 Dockerfile
 create mode 100644 README.md
 create mode 100644 index.sh
 create mode 100644 potwierdzenie.jpg

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ gh repo create pawcho6 --public --source=. --remote=origin --push
✓ Created repository Kupi403/pawcho6 on github.com
  https://github.com/Kupi403/pawcho6
✓ Added remote git@github.com:Kupi403/pawcho6.git
Enumerating objects: 6, done.
Counting objects: 100% (6/6), done.
Delta compression using up to 12 threads
Compressing objects: 100% (6/6), done.
Writing objects: 100% (6/6), 282.57 KiB | 3.25 MiB/s, done.
Total 6 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To github.com:Kupi403/pawcho6.git
 * [new branch]      HEAD -> master
branch 'master' set up to track 'origin/master'.
✓ Pushed commits to git@github.com:Kupi403/pawcho6.git

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ 
```

Udany build

```
Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ docker build --ssh default=/.ssh/id_rsa --no-cache --build-arg VERSION=lab6 -t ghcr.io/kupi403/pawcho6:lab6 .
[+] Building 10.0s (20/20) FINISHED                                                                                    docker:desktop-linux
 => [internal] load build definition from Dockerfile                                                                                   0.0s
 => => transferring dockerfile: 1.21kB                                                                                                 0.0s
 => resolve image config for docker-image://docker.io/docker/dockerfile:1                                                             0.5s
 => CACHED docker-image://docker.io/docker/dockerfile:1@sha256:2780b5c3bab67f1f76c781860de469042999ed1a0d7992a5efdf2cffc0e3d769         0.0s
 => => resolve docker.io/docker/dockerfile:1@sha256:2780b5c3bab67f1f76c781860de469042999ed1a0d7992a5efdf2cffc0e3d769                   0.0s
 => [internal] load metadata for docker.io/library/nginx:alpine                                                                        0.5s
 => [internal] load metadata for docker.io/library/alpine:3.19                                                                         0.5s
 => [internal] load .dockerignore                                                                                                      0.0s
 => => transferring context: 2B                                                                                                        0.0s
 => CACHED [builder 1/7] FROM docker.io/library/alpine:3.19@sha256:6baf43584bcb78f2e5847d1de515f23499913ac9f12bdf834811a3145eb11ca1     0.1s
 => => resolve docker.io/library/alpine:3.19@sha256:6baf43584bcb78f2e5847d1de515f23499913ac9f12bdf834811a3145eb11ca1                   0.1s
 => CACHED [stage-2 1/4] FROM docker.io/library/nginx:alpine@sha256:582c496ccf79d8aa6f8203a79d32aaf7ffd8b13362c60a701a2f9ac64886c93d   0.1s
 => => resolve docker.io/library/nginx:alpine@sha256:582c496ccf79d8aa6f8203a79d32aaf7ffd8b13362c60a701a2f9ac64886c93d                   0.1s
 => [internal] load build context                                                                                                      0.0s
 => => transferring context: 30B                                                                                                       0.0s
 => [stage-2 2/4] RUN apk add --no-cache curl bash                                                                                     1.5s
 => [builder 2/7] RUN apk add --no-cache git openssh-client                                                                            2.3s
 => [stage-2 3/4] WORKDIR /usr/share/nginx/html                                                                                        0.1s
 => [builder 3/7] RUN mkdir -p -m 0700 ~/.ssh && ssh-keyscan github.com >> ~/.ssh/known_hosts                                         2.0s
 => [builder 4/7] WORKDIR /app                                                                                                         0.1s
 => [builder 5/7] RUN --mount=type=ssh git clone git@github.com:kupi403/pawcho6.git .                                                  2.7s
 => [builder 6/7] COPY index.sh .                                                                                                      0.1s
 => [builder 7/7] RUN chmod +x index.sh  # nadajemy prawa już tutaj                                                                    0.5s
 => [stage1 1/1] COPY --from=builder /app/index.sh /index.sh                                                                           0.0s
 => [stage-2 4/4] COPY --from=stage1 /index.sh ./index.sh                                                                              0.1s
 => exporting to image                                                                                                                 0.7s
 => => exporting layers                                                                                                                0.3s
 => => exporting manifest sha256:c344124748fcb4ae881ffd9021955cd90e4559ce92f375998119d018377fc3ef8                                    0.0s
 => => exporting config sha256:06f92455bfef515682d4f49ca75bd0044629b0a31c0bd2a874302bcce32b6831f6                                      0.0s
 => => exporting attestation manifest sha256:c1c81be6c9eb61a216a6cd9e6945d78da25271c6d1c5a158373d1c9872b9fe8b                          0.1s
 => => exporting manifest list sha256:5d671104c2c63f17a27a745337cc1cea4f6274630d0e7dc874b6c814832ab86f                                 0.0s
 => => naming to ghcr.io/kupi403/pawcho6:lab6                                                                                          0.0s
 => => unpacking to ghcr.io/kupi403/pawcho6:lab6                                                                                       0.1s

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$
```

Udana implementacja

```
Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ docker push ghcr.io/kupi403/pawcho6:lab6
The push refers to repository [ghcr.io/kupi403/pawcho6]
ff9f59a6a62e: Pushed
4f4fb700ef54: Pushed
1165b869c51a: Pushed
829d726aec87: Pushed
f03becc8ac15: Pushed
3284f3a1ac5c: Pushed
34dfdd2ef1f9: Pushed
15e759724ff6: Pushed
be9319ab5539: Pushed
589002ba0eae: Pushed
c8a2fa3a88d2: Pushed
a71873b303e8: Pushed
lab6: digest: sha256:5d671104c2c63f17a27a745337cc1cea4f6274630d0e7dc874b6c814832ab86f size: 856

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ docker run -d --name lab6_final -p 8080:80 ghcr.io/kupi403/pawcho6:lab6
4e5567a3bb69d7d907153f5ca0a74c8ad5aff5ab9a103e0009218d0adf4b21ee

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ docker ps
CONTAINER ID   IMAGE                      COMMAND                  CREATED         STATUS                          PORTS                                      NAMES
4e5567a3bb69   ghcr.io/kupi403/pawcho6:lab6   "/docker-entrypoint.…"   4 seconds ago   Up 4 seconds (health: starting)   0.0.0.0:8080->80/tcp, [::]:8080->80/tcp   lab6_final

Victus@DESKTOP-L681EK6 MINGW64 ~/VSCProjects/Studia VSC/Semestr 6/Chmura/LAB5/lab5_zadanie (master)
$ []
```

Zawartość pliku Dockerfile

```
# syntax=docker/dockerfile:1

# build
FROM alpine:3.19 AS builder

ARG VERSION=1.0
ENV APP_VERSION=$VERSION

RUN apk add --no-cache git openssh-client
RUN mkdir -p -m 0700 ~/.ssh && ssh-keyscan github.com >> ~/.ssh/known_hosts

WORKDIR /app

RUN --mount=type=ssh git clone git@github.com:Kupi403/pawcho6.git .

COPY index.sh .
RUN chmod +x index.sh  # nadajemy prawa już tutaj

# scratch
FROM scratch AS stage1
# tylko kopiujemy plik, nie robimy RUN
COPY --from=builder /app/index.sh /index.sh

# nginx
FROM nginx:alpine

ARG VERSION
ENV APP_VERSION=$VERSION

LABEL org.opencontainers.image.source="https://github.com/Kupi403/pawcho6"
LABEL org.opencontainers.image.description="Lab6 - SSH mount i ghcr.io"
LABEL org.opencontainers.image.authors="Michał Kupidura"

RUN apk add --no-cache curl bash

WORKDIR /usr/share/nginx/html

# kopiujemy skrypt z scratch
COPY --from=stage1 /index.sh ./index.sh

EXPOSE 80

# uruchamiamy skrypt dynamicznie przy starcie kontenera
CMD ["sh", "-c", "./index.sh && nginx -g 'daemon off;'"]

HEALTHCHECK --interval=30s --timeout=5s --start-period=5s \
  CMD curl -f http://localhost || exit 1
```