

1 Examples

The example below shows how to use the HyEQ solver to simulate a bouncing ball.

Example 1.2 (bouncing ball with Lite HyEQ Solver) Consider the hybrid system model for the bouncing ball with data given in Example 1.1 in the instructions file.

For this example, we consider the ball to be bouncing on a floor at zero height. The constants for the bouncing ball system are $\gamma = 9.81$ and $\lambda = 0.8$. The following procedure is used to simulate this example in the Lite HyEQ Solver:

- Inside the MATLAB script `run.m`, initial conditions, simulation horizons, a rule for jumps, ode solver options, and a step size coefficient are defined. The function `HyEQsolver.m` is called in order to run the simulation, and a script for plotting solutions is included.
- Then the MATLAB functions `f.m`, `C.m`, `g.m`, `D.m` are edited according to the data given above.
- Finally, the simulation is run by clicking the run button in `run.m` or by calling `run.m` in the MATLAB command window.




Figure 1: Solution of Example ??

Example code for each of the MATLAB files `run.m`, `f.m`, `C.m`, `g.m`, and `D.m` is given below.

```

1
2 %-----
3 % Matlab M-file Project: HyEQ Toolbox @ Hybrid Systems Laboratory (HSL),
4 % https://hybrid.soe.ucsc.edu/software
5 % http://hybridsimulator.wordpress.com/
6 % Filename: run_ex1_2a.m
7 %-----
8 % Project: Simulation of a hybrid system (bouncing ball)
9 %-----
10 %-----
11 % See also HYEQSOLVER, PLOTARC, PLOTARC3, PLOTFLows, PLOTHARC,
12 % PLOTHARCCOLOR, PLOTHARCCOLOR3D, PLOTHYBRIDARC, PLOTJUMPS.
13 % Copyright © Hybrid Systems Laboratory (HSL),

```




Figure 2: Hybrid arc corresponding to a solution of Example ??: height

```

14 % Revision: 0.0.0.3 Date: 05/20/2015 3:42:00
15
16 function run_ex1_2a
17 % initial conditions
18 x1_0 = 1;
19 x2_0 = 0;
20 x0 = [x1_0;x2_0];
21
22 % physical variables
23 global gamma lambda
24 gamma = -9.81; % gravity constant
25 lambda = 0.8; % restitution coefficient
26
27 % simulation horizon
28 TSPAN=[0 10];
29 JSPAN = [0 20];
30
31 % rule for jumps
32 % rule = 1 -> priority for jumps
33 % rule = 2 -> priority for flows
34 rule = 1;
35
36 options = odeset('RelTol',1e-6,'MaxStep',.1);
37
38 % simulate
39 [t j x] = HyEQsolver( @f_ex1_2a,@g_ex1_2a,@C_ex1_2a,@D_ex1_2a,...

```

```

40     x0,TSPAN,JSPAN,rule,options);
41
42 % plot solution
43 figure(1) % position
44 clf
45 subplot(2,1,1), plotHarc(t,j,x(:,1));
46 grid on
47 ylabel('x_1 position')
48 subplot(2,1,2), plotHarc(t,j,x(:,2));
49 grid on
50 ylabel('x_2 velocity')
51
52 % plot phase plane
53 figure(2) % position
54 clf
55 plotHarcColor(x(:,1),j,x(:,2),t);
56 xlabel('x_1')
57 ylabel('x_2')
58 grid on
59
60 % plot hybrid arc
61 figure(3)
62 plotHybridArc(t,j,x)
63 xlabel('j')
64 ylabel('t')
65 zlabel('x1')
66

```

Flow map

```

1
2 function xdot = f_ex1_2a(x)
3 %-----
4 % Matlab M-file Project: HyEQ Toolbox @ Hybrid Systems Laboratory (HSL),
5 % https://hybrid.soe.ucsc.edu/software
6 % http://hybridsimulator.wordpress.com/
7 % Filename: f_ex1_2a.m
8 %-----
9 % Project: Simulation of a hybrid system (bouncing ball)
10 % Description: Flow map
11 %-----
12 %-----
13 % See also HYEQSOLVER, PLOTARC, PLOTARC3, PLOTFLows, PLOTHARC,
14 % PLOTHARCCOLOR, PLOTHARCCOLOR3D, PLOTHYBRIDARC, PLOTJUMPS.
15 % Copyright @ Hybrid Systems Laboratory (HSL),
16 % Revision: 0.0.0.3 Date: 05/20/2015 3:42:00
17
18 % state
19 x1 = x(1);
20 x2 = x(2);
21
22 global gamma
23
24 % differential equations

```

```

25 xdot = [x2 ; gamma];
26 end

```

Flow set

```

1
2 function [value] = C_ex1_2a(x)
3 %-----
4 % Matlab M-file Project: HyEQ Toolbox @ Hybrid Systems Laboratory (HSL),
5 % https://hybrid.soe.ucsc.edu/software
6 % http://hybridsimulator.wordpress.com/
7 % Filename: C_ex1_2a.m
8 %-----
9 % Description: Flow set
10 % Return 0 if outside of C, and 1 if inside C
11 %-----
12 %-----
13 % See also HYEQSOLVER, PLOTARC, PLOTARC3, PLOTFLows, PLOTHARC,
14 % PLOTHARCCOLOR, PLOTHARCCOLOR3D, PLOTHYBRIDARC, PLOTJUMPS.
15 % Copyright @ Hybrid Systems Laboratory (HSL),
16 % Revision: 0.0.0.3 Date: 05/20/2015 3:42:00
17
18
19 x1 = x(1);
20
21 if x1 >= 0
22     value = 1;
23 else
24     value = 0;
25 end
26 end

```

Jump map

```

1
2 function xplus = g_ex1_2a(x)
3 %-----
4 % Matlab M-file Project: HyEQ Toolbox @ Hybrid Systems Laboratory (HSL),
5 % https://hybrid.soe.ucsc.edu/software
6 % http://hybridsimulator.wordpress.com/
7 % Filename: g_ex1_2a.m
8 %-----
9 % Project: Simulation of a hybrid system (bouncing ball)
10 % Description: Jump map
11 %-----
12 %-----
13 % See also HYEQSOLVER, PLOTARC, PLOTARC3, PLOTFLows, PLOTHARC,
14 % PLOTHARCCOLOR, PLOTHARCCOLOR3D, PLOTHYBRIDARC, PLOTJUMPS.
15 % Copyright @ Hybrid Systems Laboratory (HSL),
16 % Revision: 0.0.0.3 Date: 05/20/2015 3:42:00
17
18 % state
19 x1 = x(1);
20 x2 = x(2);
21

```

```

22 global lambda
23
24 xplus = [-x1 ; -lambda*x2];
25 end

```

Jump set

```



1
2 function inside = D_ex1_2a(x)
3 %-----
4 % Matlab M-file Project: HyEQ Toolbox @ Hybrid Systems Laboratory (HSL),
5 % https://hybrid.soe.ucsc.edu/software
6 % http://hybridsimulator.wordpress.com/
7 % Filename: D_ex1_2a.m
8 %-----
9 % Description: Jump set
10 % Return 0 if outside of D, and 1 if inside D
11 %-----
12 %-----
13 % See also HYEQSOLVER, PLOTARC, PLOTARC3, PLOTFLows, PLOTHARC,
14 % PLOTHARCCOLOR, PLOTHARCCOLOR3D, PLOTHYBRIDARC, PLOTJUMPS.
15 % Copyright © Hybrid Systems Laboratory (HSL),
16 % Revision: 0.0.0.3 Date: 05/20/2015 3:42:00
17
18 x1 = x(1);
19 x2 = x(2);
20 if (x1 <= 0 && x2 <= 0)
21     inside = 1;
22 else
23     inside = 0;
24 end
25 end

```



A solution to the bouncing ball system from $x(0,0) = [1,0]^\top$ and with $TSPAN = [0 \ 10]$, $JSPAN = [0 \ 20]$, $rule = 1$, is depicted in Figure ?? (height) and Figure ?? (velocity). Both the projection onto t and j are shown. Figure ?? depicts the corresponding hybrid arc for the position state.

For MATLAB files of this example, see Examples/Example_??.

□



(a) Height



(b) Velocity

Figure 3: Solution of Example ??