

# Programming Languages and Compilers (CS 421)



---

Reza Zamani

<http://www.cs.illinois.edu/class/cs421/>

Based in part on slides by Mattox Beckman, as updated by Vikram Adve and Gul Agha



# Untyped $\lambda$ -Calculus

---

- Only three kinds of expressions:
  - Variables:  $x, y, z, w, \dots$
  - Abstraction:  $\lambda x. e$   
(Function creation)
  - Application:  $e_1 e_2$



## How to Represent (Free) Data Structures (First Pass - Enumeration Types)

- Suppose  $\tau$  is a type with  $n$  constructors:  
 $C_1, \dots, C_n$  (no arguments)
- Represent each term as an abstraction:
- Let  $C_i \rightarrow \lambda x_1 \dots x_n. x_i$
- Think: you give me what to return in each case (think match statement) and I'll return the case for the  $i$ 'th constructor



# How to Represent Booleans

---

- $\text{bool} = \text{True} \mid \text{False}$
- $\text{True} \rightarrow \lambda x_1. \lambda x_2. x_1 \equiv_{\alpha} \lambda x. \lambda y. x$
- $\text{False} \rightarrow \lambda x_1. \lambda x_2. x_2 \equiv_{\alpha} \lambda x. \lambda y. y$
- Notation
  - Will write
$$\lambda x_1 \dots x_n. e \text{ for } \lambda x_1. \dots \lambda x_n. e$$
$$e_1 e_2 e_3 \dots e_n \text{ for } ((\dots((e_1 e_2) e_3) \dots) e_n)$$



# Functions over Enumeration Types

---

- Write a “match” function

- match  $e$  with  $C_1 \rightarrow x_1$

| ...

|  $C_n \rightarrow x_n$

$\rightarrow \lambda x_1 \dots x_n e. e x_1 \dots x_n$

- Think: give me what to do in each case and give me a case, and I'll apply that case



# Functions over Enumeration Types

- type  $\tau = C_1 | \dots | C_n$
- match  $e$  with  $C_1 \rightarrow x_1$   
                  |  $\dots$   
                  |  $C_n \rightarrow x_n$
- $match\tau = \lambda x_1 \dots x_n e. e\ x_1 \dots x_n$
- $e$  = expression (single constructor)  
     $x_i$  is returned if  $e = C_i$



# match for Booleans

---

- $\text{bool} = \text{True} \mid \text{False}$
- $\text{True} \rightarrow \lambda x_1 x_2. x_1 \equiv_{\alpha} \lambda x y. x$
- $\text{False} \rightarrow \lambda x_1 x_2. x_2 \equiv_{\alpha} \lambda x y. y$
- $\text{match}_{\text{bool}} = ?$



# match for Booleans

---

- $\text{bool} = \text{True} \mid \text{False}$
- $\text{True} \rightarrow \lambda x_1 x_2. x_1 \equiv_{\alpha} \lambda x y. x$
- $\text{False} \rightarrow \lambda x_1 x_2. x_2 \equiv_{\alpha} \lambda x y. y$
  
- $\text{match}_{\text{bool}} = \lambda x_1 x_2 e. e x_1 x_2$   
 $\equiv_{\alpha} \lambda x y b. b x y$





# How to Write Functions over Booleans

---

- if b then  $x_1$  else  $x_2 \rightarrow$
- if\_then\_else b  $x_1$   $x_2 = b$   $x_1$   $x_2$
- if\_then\_else  $\equiv \lambda b\ x_1\ x_2 . b\ x_1\ x_2$



# How to Write Functions over Booleans

---

- Alternately:
- $\text{if } b \text{ then } x_1 \text{ else } x_2 =$   
 $\text{match } b \text{ with True } \rightarrow x_1 \mid \text{False } \rightarrow x_2 \rightarrow$   
 $\text{match}_{\text{bool}} x_1 x_2 b =$   
 $(\lambda x_1 x_2 b . b x_1 x_2) x_1 x_2 b = b x_1 x_2$
- $\text{if\_then\_else}$   
 $\equiv \lambda b x_1 x_2 . (\text{match}_{\text{bool}} x_1 x_2 b)$   
 $= \lambda b x_1 x_2 . (\lambda x_1 x_2 b . b x_1 x_2) x_1 x_2 b$   
 $= \lambda b x_1 x_2 . b x_1 x_2$



## Example:

---

not b

= match b with True -> False | False -> True


→ (match<sub>bool</sub>) False True b

= (λ x<sub>1</sub> x<sub>2</sub> b . b x<sub>1</sub> x<sub>2</sub>) (λ x y. y) (λ x y. x) b

= b (λ x y. y)(λ x y. x)

■ not ≡ λ b. b (λ x y. y)(λ x y. x)

■ Try and, or



and

or



## How to Represent (Free) Data Structures (Second Pass - Union Types)

- Suppose  $\tau$  is a type with  $n$  constructors:  
type  $\tau = C_1 t_{11} \dots t_{1k} \mid \dots \mid C_n t_{n1} \dots t_{nm},$
- Represent each term as an abstraction:
- $C_i t_{i1} \dots t_{ij} \rightarrow \lambda x_1 \dots x_n. x_i t_{i1} \dots t_{ij},$
- $C_i \rightarrow \lambda t_{i1} \dots t_{ij}. x_1 \dots x_n. x_i t_{i1} \dots t_{ij},$
- Think: you need to give each constructor its arguments first



# How to Represent Pairs

---

- Pair has one constructor (comma) that takes two arguments
- $\text{type } (\alpha, \beta)\text{pair} = (,) \alpha \beta$
- $(a , b) \rightarrow \lambda x . x a b$
- $(\_ , \_) \rightarrow \lambda a b x . x a b$

- Write a “match” function
- match e with  $C_1 y_1 \dots y_{m1} \rightarrow f_1 y_1 \dots y_{m1}$   
 $\quad \quad \quad | \dots$   
 $\quad \quad \quad | C_n y_1 \dots y_{mn} \rightarrow f_n y_1 \dots y_{mn}$
- $match\tau \rightarrow \lambda f_1 \dots f_n e. e f_1 \dots f_n$
- Think: give me a function for each case and give me a case, and I’ll apply that case to the appropriate function with the data in that case



# Functions over Pairs

---

- $\text{match}_{\text{pair}} = \lambda f p. p f$
- $\text{fst } p = \text{match } p \text{ with } (x,y) \rightarrow x$
- $\text{fst} \rightarrow \lambda p. \text{match}_{\text{pair}} (\lambda x y. x) p$   
 $= \lambda p. (\lambda f p. p f) (\lambda x y. x) p = \lambda p. p (\lambda x y. x)$
- $\text{snd} \rightarrow \lambda p. p (\lambda x y. y)$





# How to Represent (Free) Data Structures (Third Pass - Recursive Types)

- Suppose  $\tau$  is a type with  $n$  constructors:  
$$\text{type } \tau = C_1 t_{11} \dots t_{1k} \mid \dots \mid C_n t_{n1} \dots t_{nm},$$
- Suppose  $t_{ih} : \tau$  (ie. is recursive)
- In place of a value  $t_{ih}$  have a function to compute the recursive value  $r_{ih} x_1 \dots x_n$
- $C_i t_{i1} \dots r_{ih} \dots t_{ij} \rightarrow \lambda x_1 \dots x_n . x_i t_{i1} \dots (r_{ih} x_1 \dots x_n) \dots t_{ij}$
- $C_i \rightarrow \lambda t_{i1} \dots r_{ih} \dots t_{ij} x_1 \dots x_n . x_i t_{i1} \dots (r_{ih} x_1 \dots x_n) \dots t_{ij},$



# How to Represent Natural Numbers

---

- $\text{nat} = \text{Suc nat} \mid 0$
- $\underline{\text{Suc}} = \lambda n f x. f (n f x)$
- $\underline{\text{Suc } n} = \lambda f x. f (n f x)$
- $\underline{0} = \lambda f x. x$
- Such representation called  
*Church Numerals*



# Some Church Numerals

---

- $\overline{\text{Suc}} \overline{0} = (\lambda n f x. f (n f x)) (\lambda f x. x) \rightarrow$   
 $\lambda f x. f ((\lambda f x. x) f x) \rightarrow$   
 $\lambda f x. f ((\lambda x. x) x) \rightarrow \lambda f x. f x$

Apply a function to its argument once



# Some Church Numerals

$$\begin{aligned} \blacksquare \quad \overline{\text{Suc}}(\overline{\text{Suc}} \, \overline{0}) &= (\lambda n f x. f (n f x)) (\text{Suc } 0) \rightarrow \\ &(\lambda n f x. f (n f x)) (\lambda f x. f x) \rightarrow \\ &\lambda f x. f ((\lambda f x. f x) f x) \rightarrow \\ &\lambda f x. f ((\lambda x. f x) x) \rightarrow \lambda f x. f (f x) \end{aligned}$$

Apply a function twice

In general  $\overline{n} = \lambda f x. f (\dots (f x) \dots)$  with  $n$  applications of  $f$

# Primitive Recursive Functions

- Write a “fold” function
- $\text{fold } f_1 \dots f_n \ e = \text{match } e$   
 with  $C_1 \ y_1 \dots y_{m1} \rightarrow f_1 \ y_1 \dots y_{m1}$   
 |  $\dots$   
 |  $C_i \ y_1 \dots r_{ij} \dots y_{in} \rightarrow f_i \ y_1 \dots (\text{fold } f_1 \dots f_n \ r_{ij}) \dots y_{mn}$   
 |  $\dots$   
 |  $C_n \ y_1 \dots y_{mn} \rightarrow f_n \ y_1 \dots y_{mn}$
- $\text{fold} \tau \rightarrow \lambda f_1 \dots f_n \ e. e \ f_1 \dots f_n$
- Match in non recursive case a degenerate version of fold



# Primitive Recursion over Nat

---

- $\text{fold } f \ z \ n =$
- $\text{match } n \text{ with } 0 \rightarrow z$
- $\quad \mid \text{Suc } m \rightarrow f (\text{fold } f \ z \ m)$
- $\overline{\text{fold}} \equiv \lambda f \ z \ n. n \ f \ z$
- $\overline{\text{is\_zero}} \ n = \overline{\text{fold}} (\lambda r. \text{False}) \ \text{True} \ n$
- $= (\lambda f \ x. f^n \ x) (\lambda r. \text{False}) \ \text{True}$
- $= ((\lambda r. \text{False})^n) \ \text{True}$
- $\equiv \text{if } n = 0 \text{ then True else False}$



# Adding Church Numerals

---

- $\overline{n} \equiv \lambda f x. f^n x$     and     $m \equiv \lambda f x. f^m x$
- $\overline{n + m} = \lambda f x. f^{(n+m)} x$   
 $= \lambda f x. f^n (f^m x) = \lambda f x. \overline{n} f (\overline{m} f x)$
- $\overline{+} \equiv \lambda n m f x. n f (m f x)$
- Subtraction is harder



# Multiplying Church Numerals

---

- $\overline{n} \equiv \lambda f x. f^n x$     and     $m \equiv \lambda f x. f^m x$

- $\overline{n * m} = \lambda f x. (f^{n * m}) x = \lambda f x. (f^m)^n x$   
 $= \lambda f x. \overline{n} (\overline{m} f) x$

$$\overline{*} \equiv \lambda n m f x. n (m f) x$$





# Predecessor

---

- $\text{let pred\_aux } n =$   
     $\text{match } n \text{ with } 0 \rightarrow (0,0)$   
     $| \text{ Suc } m$   
     $\rightarrow (\text{Suc}(\text{fst}(\text{pred\_aux } m)), \text{fst}(\text{pred\_aux } m))$   
     $= \text{fold } (\lambda r. (\text{Suc}(\text{fst } r), \text{fst } r)) (0,0) n$
- $\text{pred} \equiv \lambda n. \text{snd } (\text{pred\_aux } n) =$   
     $\lambda n. \text{snd } (\text{fold } (\lambda r. (\text{Suc}(\text{fst } r), \text{fst } r)) (0,0) n)$



# Recursion

---

- Want a  $\lambda$ -term  $Y$  such that for all term  $R$  we have
- $Y R = R (Y R)$
- $Y$  needs to have replication to “remember” a copy of  $R$
- $Y = \lambda y. (\lambda x. y(x x)) (\lambda x. y(x x))$
- $$\begin{aligned} Y R &= (\lambda x. R(x x)) (\lambda x. R(x x)) \\ &= R ((\lambda x. R(x x)) (\lambda x. R(x x))) \\ &= R (Y R) \end{aligned}$$
- Notice: Requires lazy evaluation



# Factorial

---

■ Let  $F = \lambda f n. \text{ if } n = 0 \text{ then } 1 \text{ else } n * f (n - 1)$

$Y F 3 = F (Y F) 3$

$= \text{if } 3 = 0 \text{ then } 1 \text{ else } 3 * ((Y F)(3 - 1))$

$= 3 * (Y F) 2 = 3 * (F(Y F) 2)$

$= 3 * (\text{if } 2 = 0 \text{ then } 1 \text{ else } 2 * (Y F)(2 - 1))$

$= 3 * (2 * (Y F)(1)) = 3 * (2 * (F(Y F) 1)) = \dots$

$= 3 * 2 * 1 * (\text{if } 0 = 0 \text{ then } 1 \text{ else } 0 * (Y F)(0 - 1))$

$= 3 * 2 * 1 * 1 = 6$



# Y in OCaml

---

```
# let rec y f = f (y f);;  
val y : ('a -> 'a) -> 'a = <fun>  
# let mk_fact =  
    fun f n -> if n = 0 then 1 else n * f(n-1);;  
val mk_fact : (int -> int) -> int -> int = <fun>  
# y mk_fact;;  
Stack overflow during evaluation (looping  
recursion?).
```



# Eager Eval Y in Ocaml

---

```
# let rec y f x = f (y f) x;;  
val y : (('a -> 'b) -> 'a -> 'b) -> 'a -> 'b  
= <fun>
```

```
# y mk_fact;;  
- : int -> int = <fun>
```

```
# y mk_fact 5;;  
- : int = 120
```

- Use recursion to get recursion



# Some Other Combinators

---

- For your general exposure
- $I = \lambda x . x$
- $K = \lambda x . \lambda y . x$
- $K_* = \lambda x . \lambda y . y$
- $S = \lambda x . \lambda y . \lambda z . x z (y z)$