

Apply filters to SQL queries

Project description

My organization is enhancing the security of its system. My responsibilities include ensuring system safety, investigating potential security issues, and updating employee computers as necessary. The following steps illustrate how I utilized SQL with filters to carry out security-related tasks.

Retrieve after hours failed login attempts

There was a potential security incident that occurred after business hours (after 18:00). All failed login attempts during this time need to be investigated.

The following code demonstrates how I created a SQL query to filter for failed login attempts that occurred after business hours:

```
MariaDB [organization]> SELECT *  
  -> FROM log_in_attempts  
  -> WHERE login_time > '18:00' AND success = FALSE;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0

The first part of the screenshot shows my query, while the second part displays a portion of the output. This query filters for failed login attempts that occurred after 18:00.

First, I selected all data from the `log_in_attempts` table. Then, I used a `WHERE` clause with an `AND` operator to refine my results, ensuring only login attempts that occurred after 18:00 and were unsuccessful are included. The first condition, `login_time > '18:00'`, filters for login attempts after 18:00. The second condition, `success = FALSE`, filters for failed login attempts.

Retrieve login attempts on specific dates

A suspicious event occurred on 2022-05-09. Any login activity that happened on 2022-05-09 or the day before needs to be investigated.

The following code demonstrates how I created a SQL query to filter for login attempts that occurred on specific dates:

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	0
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0

The first part of the screenshot shows my query, while the second part displays a portion of the output. This query returns all login attempts that occurred on 2022-05-09 or 2022-05-08.

First, I selected all data from the `log_in_attempts` table. Then, I used a `WHERE` clause with an `OR` operator to refine my results, ensuring only login attempts that occurred on either 2022-05-09 or 2022-05-08 are included. The first condition, `login_date = '2022-05-09'`, filters for logins on 2022-05-09. The second condition, `login_date = '2022-05-08'`, filters for logins on 2022-05-08.

Retrieve login attempts outside of Mexico

After investigating the organization's data on login attempts, I believe there is an issue with the login attempts that occurred outside of Mexico. These login attempts should be investigated.

The following code demonstrates how I created a SQL query to filter for login attempts that occurred outside of Mexico:

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	0
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	0

The first part of the screenshot shows my query, while the second part displays a portion of the output. This query returns all login attempts that occurred in countries other than Mexico.

First, I selected all data from the `log_in_attempts` table. Then, I used a `WHERE` clause with `NOT` to filter for countries other than Mexico. I used `LIKE` with the pattern `MEX%` because the dataset represents Mexico as both `MEX` and `MEXICO`. The percentage sign (%) represents any number of unspecified characters when used with `LIKE`.

Retrieve employees in Marketing

My team wants to update the computers for certain employees in the Marketing department. To do this, I need to gather information on which employee machines to update.

The following code demonstrates how I created a SQL query to filter for employee machines from employees in the Marketing department in the East building:

```
MariaDB [organization]> SELECT *
-> FROM employees
-> WHERE department = 'Marketing' AND office LIKE 'East%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267

The first part of the screenshot is my query, and the second part is a portion of the output. This query returns all employees in the Marketing department in the East building. First, I started by selecting all data from the `employees` table. Then, I used a `WHERE` clause with `AND` to filter for employees who work in the Marketing department and in the East building. I used `LIKE` with `East%` as the pattern to match because the data in the `office` column represents the East building with the specific office number. The first condition is the `department = 'Marketing'` portion, which filters for employees in the Marketing department. The second condition is the `office LIKE 'East%'` portion, which filters for employees in the East building.

Retrieve employees in Finance or Sales

The machines for employees in the Finance and Sales departments also need to be updated. Since a different security update is needed, I have to get information on employees only from these two departments.

The following code demonstrates how I created a SQL query to filter for employee machines from employees in the Finance or Sales departments.

```
MariaDB [organization]> SELECT *  
-> FROM employees  
-> WHERE department = 'Finance' OR department = 'Sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170

The first part of the screenshot is my query, and the second part is a portion of the output. This query returns all employees in the Finance and Sales departments. First, I started by selecting all data from the `employees` table. Then, I used a `WHERE` clause with `OR` to filter for employees who are in the Finance and Sales departments. I used the `OR` operator instead of `AND` because I want all employees who are in either department. The first condition is `department = 'Finance'`, which filters for employees from the Finance department. The second condition is `department = 'Sales'`, which filters for employees from the Sales department.

Retrieve all employees not in IT

My team needs to make one more security update on employees who are not in the Information Technology department. To make the update, I first have to get information on these employees.

The following demonstrates how I created a SQL query to filter for employee machines from employees not in the Information Technology department.

```
MariaDB [organization]> SELECT *  
-> FROM employees  
-> WHERE NOT department = 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434

The first part of the screenshot shows my query, while the second part displays a portion of the output. The query returns all employees not in the Information Technology department.

First, I selected all data from the `employees` table. Then, I used a `WHERE` clause with `NOT` to filter for employees who are not in this department.

Summary

I applied filters to SQL queries to obtain specific information on login attempts and employee machines. I utilized two different tables: `log_in_attempts` and `employees`. I employed the `AND`, `OR`, and `NOT` operators to filter for the specific information required for each task. Additionally, I used `LIKE` with the percentage sign (`%`) wildcard to filter for patterns.

- **Kushagra Gupta**