

Name: Kushal Kishor Shankhapal

Group B, Assignment 4-5: Precision, Recal, Harmonic mean (F-measure) and E-measure

Problem Statement:

Implement a program to calculate precision and recall for sample input.

(Answer set A, Query q1, Relevant documents to query q1- Rq1)

Write a program to calculate harmonic mean (F-measure) and E-measure for above example

Recall_Precision_Evaluator.cpp

```
#include <iostream>
#include <string.h>
#include <iomanip>
#include <fstream>

using namespace std;

string left(const string s, const int w)
{ // Left aligns input string in table
  stringstream ss, spaces;
  int padding = w - s.size(); // count excess room to pad
  for (int i = 0; i < padding; ++i)
    spaces << " ";
  ss << s << spaces.str() << '|'; // format with padding
  return ss.str();
}

string center(const string s, const int w)
{ // center aligns input string in table
  stringstream ss, spaces;
  int padding = w - s.size(); // count excess room to pad
  for (int i = 0; i < padding / 2; ++i)
    spaces << " ";
  ss << spaces.str() << s << spaces.str(); // format with padding
  if (padding > 0 && padding % 2 != 0) // if odd #, add 1 space
    ss << " ";
  return ss.str();
}

string prd(float x, int decDigits, int width)
{ // right aligns float values with specified no. of precision digits in a table
  stringstream ss;
  ss << fixed << right;
  ss.fill(' '); // fill space around displayed #
  ss.width(width); // set width around displayed #
  ss.precision(decDigits); // set # places after decimal
  ss << x;
  return ss.str();
}

string printDocs(string state[], int size)
{
  // prints each document at a specific iteration inside the table
  stringstream ss;
  ss << '|' << ' ';
  for (int i = 0; i < size; i++)
  { // convert the array into a string of comma separated values
    ss << state[i];
    if (state[i].compare("") != 0 and i + 1 < size and state[i + 1].compare("") != 0)
      ss << ',' << ' ';
  }
  return left(ss.str(), 98);
}
```

```

float E_value(float b, float rj, float pj)
{ // calculates E value
    return 1 - (((1 + b * b) * rj * pj) / (b * b * pj + rj));
}

int main()
{ // Hardcoded Rq and A
    string Rq[10] = {"d3", "d5", "d9", "d25", "d39", "d44", "d56", "d71", "d89", "d123"};
    string A[15] = {"d123", "d84", "d56", "d6", "d8", "d9", "d511", "d129", "d187",
"d25", "d38", "d48", "d250", "d113", "d3"};

    // Creating and opening output file
    ofstream write("Recall_Precision_Evaluation_output.txt");

    // required constants and arrays for calculations
    float modRq = sizeof(Rq) / sizeof(Rq[0]);
    string Ra[sizeof(A) / sizeof(A[0])];
    float P[sizeof(A) / sizeof(A[0])];
    float R[sizeof(A) / sizeof(A[0])];
    float modRa = 0;
    float modA = 0;
    double precision;
    double recall;

    // table header formatting and printing
    std::cout << setprecision(2) << fixed;
    write << setprecision(2) << fixed;
    std::cout << string(45 * 3 + 11, '-') << "\n";
    write << string(45 * 3 + 11, '-') << "\n";
    std::cout << '|' << center("Documents", 96) << " | "
        << center("|Ra|", 8) << " | "
        << center("|A|", 8) << " | "
        << center("Precision(%)", 5) << " | "
        << center("Recall(%)", 5) << " | " << endl;
    write << '|' << center("Documents", 96) << " | "
        << center("|Ra|", 8) << " | "
        << center("|A|", 8) << " | "
        << center("Precision(%)", 5) << " | "
        << center("Recall(%)", 5) << " | " << endl;
    std::cout << string(45 * 3 + 11, '-') << "\n";
    write << string(45 * 3 + 11, '-') << "\n";
    // Algorithm to calculate and print all the values in the output table, MAIN algo
    for (int i = 0; i < sizeof(A) / sizeof(A[0]); i++)
    {
        Ra[i] = A[i];
        modA++;
        for (int j = 0; j < modRq; j++)
        {
            if (A[i] == Rq[j])
            {
                modRa++;
                break;
            }
        }
        precision = (modRa / modA) * 100;
        P[i] = precision / 100;
        recall = (modRa / modRq) * 100;
        R[i] = recall / 100;
        // Printing documents and other values of current iteration within the table
        std::cout << printDocs(Ra, sizeof(Ra) / sizeof(Ra[0]));
        write << printDocs(Ra, sizeof(Ra) / sizeof(Ra[0]));
        std::cout << prd(modRa, 2, 10) << " | "
            << prd(modA, 2, 10) << " | "
            << prd(precision, 2, 13) << " | "
            << prd(recall, 2, 10) << " | "
            << endl;
        write << prd(modRa, 2, 10) << " | "
            << prd(modA, 2, 10) << " | "
            << prd(precision, 2, 13) << " | "
            << prd(recall, 2, 10) << " | "
            << endl;
    }
}

```

```

// closing the table
std::cout << string(45 * 3 + 11, '-') << "\n";
write << string(45 * 3 + 11, '-') << "\n";

// taking user input for calculation of Fj and Ej
int j;
do
{
    std::cout << "Harmonic mean and E-value\nEnter value of j(0 - " << (sizeof(A) /
sizeof(A[0])) - 1 << ") to find F(j)and E(j):" << endl;
    cin >> j;
} while (j > sizeof(Ra) / sizeof(Ra[0]));

// calculating Harmonic mean and printing in table
float Fj = (2 * P[j] * R[j]) / (P[j] + R[j]);
std::cout << string(15 * 2 + 3, '-') << "\n"
    << "| Harmonic mean (F" << j << ") is: |" << Fj << " |\n"
    << string(15 * 2 + 3, '-') << "\n";
write << string(15 * 2 + 3, '-') << "\n"
    << "| Harmonic mean (F" << j << ") is: |" << Fj << " |\n"
    << string(15 * 2 + 3, '-') << "\n";

// table header
std::cout << string(15 * 2 + 4, '-') << "\n"
    << "|" << center("E-Value", 32) << "|\n"
    << string(15 * 2 + 4, '-') << "\n";
write << string(15 * 2 + 4, '-') << "\n"
    << "|" << center("E-Value", 32) << "|\n"
    << string(15 * 2 + 4, '-') << "\n";

// table header (sub columns)
std::cout << "|" << center("b>1", 10) << "|"
    << center("b=0", 10) << "|"
    << center("b<1", 10) << "|\n"
    << string(15 * 2 + 4, '-') << "\n";
write << "|" << center("b>1", 10) << "|"
    << center("b=0", 10) << "|"
    << center("b<1", 10) << "|\n"
    << string(15 * 2 + 4, '-') << "\n";

// Calculating and Printing E-Values in table
std::cout << "|" << prd(E_value(1.1, R[j], P[j]), 2, 10) << "|"
    << prd(E_value(0, R[j], P[j]), 2, 10) << "|"
    << prd(E_value(0.9, R[j], P[j]), 2, 10) << "|\n";
write << "|" << prd(E_value(1.1, R[j], P[j]), 2, 10) << "|"
    << prd(E_value(0, R[j], P[j]), 2, 10) << "|"
    << prd(E_value(0.9, R[j], P[j]), 2, 10) << "|\n";
// Closing table
std::cout << string(15 * 2 + 4, '-') << "\n";
write << string(15 * 2 + 4, '-') << "\n";
write.close();
return 0;
}

```

Output:

```
it@IT-SWL-19:~$ g++ Recall_Precision_Evaluator.cpp
it@IT-SWL-19:~$ ./a.out
-----
|                                     Documents
| |Ra| | |A| | Precision(%) |Recall(%) |
|-----|
| d123
| | 1.00| | 1.00| | 100.00| | 10.00|
| d123, d84
| | 1.00| | 2.00| | 50.00| | 10.00|
| d123, d84, d56
| | 2.00| | 3.00| | 66.67| | 20.00|
| d123, d84, d56, d6
| | 2.00| | 4.00| | 50.00| | 20.00|
| d123, d84, d56, d6, d8
| | 2.00| | 5.00| | 40.00| | 20.00|
| d123, d84, d56, d6, d8, d9
| | 3.00| | 6.00| | 50.00| | 30.00|
| d123, d84, d56, d6, d8, d9, d511
| | 3.00| | 7.00| | 42.86| | 30.00|
| d123, d84, d56, d6, d8, d9, d511, d129
| | 3.00| | 8.00| | 37.50| | 30.00|
| d123, d84, d56, d6, d8, d9, d511, d129, d187
| | 3.00| | 9.00| | 33.33| | 30.00|
| d123, d84, d56, d6, d8, d9, d511, d129, d187, d25
| | 4.00| | 10.00| | 40.00| | 40.00|
| d123, d84, d56, d6, d8, d9, d511, d129, d187, d25, d38
| | 4.00| | 11.00| | 36.36| | 40.00|
| d123, d84, d56, d6, d8, d9, d511, d129, d187, d25, d38, d48
| | 4.00| | 12.00| | 33.33| | 40.00|
| d123, d84, d56, d6, d8, d9, d511, d129, d187, d25, d38, d48, d250
| | 4.00| | 13.00| | 30.77| | 40.00|
| d123, d84, d56, d6, d8, d9, d511, d129, d187, d25, d38, d48, d250, d113
| | 4.00| | 14.00| | 28.57| | 40.00|
| d123, d84, d56, d6, d8, d9, d511, d129, d187, d25, d38, d48, d250, d113, d3
| | 5.00| | 15.00| | 33.33| | 50.00|
|-----|
Harmonic mean and E-value
Enter value of j(0 - 14) to find F(j)and E(j):
7
-----
| Harmonic mean (F7) is: |0.33 |
|-----|
|                                     E-Value                                     |
|-----|
| b>1 | b=0 | b<1 |
|-----|
| 0.67| 0.62| 0.66|
|-----|
it@IT-SWL-19:~$
```