Proceedings of the 6th International Conference on IoT Based Control Networks and Intelligent Systems (ICICNIS-2025)
IEEE XPlore Part Number: CFP252B2-ART; ISBN: 979-8-3315-1520-1

2025 6th International Conference on IoT Based Control Networks and Intelligent Systems (ICICNIS) | 979-8-3315-1520-1/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICICNIS66685.2025.11315712

Autonomous Agentic AI for Clinical Workflow Orchestration: Self-Managing Healthcare Operations

Arjun Warrier
Customer Success Manager
IBM, USA
arjun.warrier.321@outlook.com

Abhilash K S
Department of Electronics and Communication Engineering
A.R.J College of Engineering and Technology
Edayarnatham, Tamil Nadu
dr.abhilashks@gmail.com

***Abstract*—Healthcare operations are inherently complex, involving dynamic coordination across emergency triage, diagnostics, surgery, and discharge processes. Traditional orchestration methods such as manual scheduling, static bed boards, and siloed communication struggle to manage this complexity, often resulting in delayed interventions, inefficiencies, and suboptimal resource utilization, especially during high-acuity surges or emergencies. Agentic Artificial Intelligence (AI) introduces a transformative paradigm by embedding autonomy, reasoning, and negotiation capabilities into intelligent digital agents that perceive, learn, and act within clinical workflows. Unlike conventional AI systems that rely on predefined rules or static predictions, agentic AI employs multi-agent reinforcement learning (MARL) to enable decentralized decision-making, adaptive resource allocation, and cooperative policy optimization across interconnected hospital systems. This study presents an autonomous agentic AI framework for clinical workflow orchestration, integrating agents for triage, bed management, laboratory, imaging, transport, and discharge operations. Using HL7 Fast Healthcare Interoperability Resources (FHIR) and DICOM standards, agents exchange real-time information while adhering to governance and safety protocols aligned with the NIST AI Risk Management Framework and the EU AI Act. The architecture further incorporates three core design elements: (i) inter-hospital communication for mutual-aid and load sharing, (ii) decentralized ambulance routing that rebalances transport in real time based on dynamic capacity and patient acuity, and (iii) distributed crisis-management protocols for maintaining operational equilibrium during mass-casualty events. Evaluation through digital-twin simulations and shadow-mode deployments demonstrated substantial operational gains, including 60% faster ambulance response, 38% shorter door-to-clinician intervals, and 22% higher operating room throughput. These results confirm that agentic AI transforms reactive, human-initiated workflows into proactive, self-governing systems, enhancing responsiveness, equity, and resilience across healthcare networks.**

Keywords*—Agentic Artificial Intelligence, Multi-Agent Reinforcement Learning, Autonomous Healthcare Systems, Digital Twins, Self-Managing Operations

I. Introduction

Healthcare delivery is a highly complex and interdependent ecosystem where thousands of coordinated actions occur simultaneously across clinical, administrative, and logistical functions. Hospitals continuously manage patient triage, diagnostic testing, imaging, operating theatres, laboratory workflows, pharmacy dispensing, and discharge coordination, all under fluctuating resource availability and unpredictable patient demand [1, 2]. Traditional orchestration mechanisms such as manual scheduling, static bed boards, and fragmented paging systems often prove inadequate in responding to real-time fluctuations in patient volume or resource constraints. As a result, healthcare institutions struggle with delayed interventions, redundant processes, and sub-optimal resource allocation, especially during high-acuity emergencies and crisis events such as pandemics or mass-casualty incidents. Fig. 1 highlights the major roles of AI agents across the healthcare ecosystem. At the core, the Healthcare AI Agent integrates data and intelligence to support functions such as diagnosis, treatment, and clinical decision-making. Surrounding applications include robot-assisted surgery, drug discovery, and patient monitoring, each benefiting from automation and predictive insights. Collectively, these AI-driven systems enhance accuracy, efficiency, and patient-centered care throughout the medical workflow.




Fig. 1. Key applications of AI agents in healthcare [6]

Recent advances in Agentic Artificial Intelligence (AI) offer a transformative opportunity to revolutionize healthcare operations through autonomous decision-making and self-managing workflows [4]. Unlike traditional rule-based or predictive systems, agentic AI embodies autonomy, reasoning, and negotiation capabilities. These agents perceive their environment, learn from experience, and coordinate actions toward shared objectives. Deployed across hospital

Authorized licensed use limited to: BMS Institute of Technology. Downloaded on June 27,2026 at 21:26:30 UTC from IEEE Xplore. Restrictions apply.

domains such as triage, bed management, imaging, laboratory, and discharge, they dynamically optimize operations through continuous communication and policy-driven negotiation, collectively minimizing waiting times, enhancing bed utilization, and improving patient safety. The basis of this transformation is MARL, which enables distributed entities to learn cooperative strategies in uncertain and partially observable environments [5]. MARL allows local decision-making while ensuring alignment with overall system goals. For instance, a triage agent pre-allocates an intensive-care bed for an incoming trauma case, while an ambulance routing agent re-optimizes patient transfers based on hospital readiness and travel time. Laboratory and imaging agents autonomously reorder task queues to prioritize critical samples, reducing turnaround delays and improving throughput. Collectively, such coordination enables autonomous orchestration of workflows previously reliant on manual oversight. Beyond efficiency, the framework emphasizes interoperability, governance, and safety. Using HL7® FHIR® standards and DICOM protocols, agents seamlessly integrate with hospital information systems [6]. A runtime assurance layer enforces compliance with institutional, clinical, and legal policies, following NIST and EU AI governance frameworks. Every decision is recorded with provenance metadata and explanation artifacts to ensure traceability and accountability.

Furthermore, digital twins virtual replicas of hospital environments enable pre-deployment simulation and stress-testing of agent policies. These models replicate patient flow, resource dynamics, and crisis conditions for continuous validation. During disruptions such as network outages, agents follow verified degraded-mode policies and later resynchronize to maintain operational continuity. Despite progress in healthcare optimization, most studies remain fragmented across scheduling, routing, or queue management. This work introduces an autonomous agentic AI architecture for clinical workflow orchestration, unifying these processes under a cohesive, adaptive, and resilient self-managing healthcare framework. The key objectives of the study are:

- To develop an autonomous agentic AI framework that orchestrates clinical workflows across hospital departments using intelligent, cooperative agents.
- To evaluate the framework's performance in improving efficiency, responsiveness, and resilience through digital-twin simulations and shadow-mode validation.
- To ensure governance, safety, and interoperability by integrating HL7® FHIR® standards and runtime assurance mechanisms within healthcare operations.

II. Related Works

In [7] investigated next-generation agentic AI in healthcare, highlighting its autonomy, adaptability, and advanced reasoning capabilities. By integrating multimodal data and iterative learning, these systems improved diagnostics, clinical decision-making, treatment planning, and healthcare administration, enhancing accuracy, reducing human error, and promoting personalized care particularly in resource-limited settings. Agentic AI applications extended to robotic-assisted surgeries, drug discovery, and administrative automation, streamlining clinical workflows and increasing efficiency. However, limitations such as the "black box" nature of decision-making, reduced transparency, interpretability challenges, data privacy concerns, algorithmic bias, and regulatory compliance hindered widespread adoption, emphasizing the need for interdisciplinary collaboration and robust governance. In [8] examined agentic AI for organ health management, focusing on custom software, diagnostic precision, and fostering a doctor-AI-patient symbiosis. These systems effectively monitored transplant patients, detecting early signs of rejection, reducing clinician workload, and providing personalized feedback. The study also highlighted the importance of multidisciplinary, context-aware AI models for diverse organ types. Nonetheless, barriers remained, including limited empirical validation, narrow model capability, regulatory challenges, and ongoing issues with system adaptability and interpretability, restricting large-scale implementation.

In [9] examined the integration of AI with wearable bioelectronics as a significant advancement in digital healthcare, enabling proactive, personalized, and data-driven medical solutions. AI-powered wearables provided real-time monitoring of physiological and biochemical parameters, enhancing early disease detection, chronic condition management, and precision therapeutics. These technologies promoted preventive care while improving accessibility and operational efficiency. However, challenges such as data interoperability, privacy risks, algorithmic bias, limited clinical validation, and regulatory and scalability constraints hindered practical implementation. Successful deployment was noted to require interdisciplinary collaboration, transparent governance, and global standardization to ensure secure, ethical, and equitable application. In [10] proposed an agentic AI framework to automate the clinical machine learning pipeline, covering data ingestion, anonymization, feature extraction, preprocessing recommendation, and model inference through modular, task-specific agents. Evaluations on geriatrics, palliative care, and colonoscopy imaging datasets demonstrated efficient handling of structured and unstructured data, interpretable outputs via SHAP, LIME, and DETR attention maps, and reduced manual intervention. Nonetheless, reliance on cloud-based infrastructure limited applicability in low-resource or constrained healthcare environments.

In [11] developed a HIPAA-compliant agentic AI framework to enhance the security and regulatory compliance of autonomous clinical workflows. The model incorporated Attribute-Based Access Control (ABAC) for context-aware data permissions, a hybrid PHI sanitization pipeline using regex and BERT models, and immutable audit trails for accountability. The hybrid approach achieved high precision, 97.6% recall, and a 98.4% F1-score, demonstrating superior accuracy in PHI redaction compared to single-method models, with a decision latency of 12.3 ms, satisfying real-time performance standards. These results validated the framework's effectiveness in protecting sensitive data and maintaining operational efficiency. Limitations included dependence on synthetic datasets and lack of large-scale real-world validation, potentially affecting applicability across diverse healthcare contexts. In [12] investigated the concept of AI scientists: agentic systems powered by large language models and generative algorithms designed to transform biomedical research through autonomous reasoning and collaboration with human experts. The method integrated AI agents with experimental platforms to facilitate hypothesis generation, workflow design, and self-assessment. These

Authorized licensed use limited to: BMS Institute of Technology. Downloaded on June 27,2026 at 21:26:30 UTC from IEEE Xplore. Restrictions apply.

agents applied structured memory and continual learning to enhance discovery processes in areas such as cell simulation, phenotype control, and therapeutic development. The method highlighted governance challenges, emphasizing the need for ethical oversight, safety protocols, and regulatory alignment. Limitations included difficulties in distinguishing causation from correlation, limited interpretability of AI reasoning, and risks of over-reliance on autonomous agents. Data bias and insufficient real-world validation further constrained the reliable and safe deployment of biomedical AI agents.

In [13] investigated the transformative role of agentic AI in computer vision, focusing on autonomous decision-making and adaptive learning in dynamic environments. The framework integrated reinforcement learning, self-supervised learning, and large-scale pre-trained vision-language models to enhance perception, reasoning, and action across applications such as autonomous vehicles, medical imaging, and surveillance. Results demonstrated improved visual data interpretation, environment assessment, and prediction of future states, enabling high-precision, real-time multi-modal analytics. Advances in convolutional neural networks and transformers further enhanced local and global feature representation, supporting deployment on edge devices for low-latency operations. Limitations included high computational demands, reliance on large datasets, challenges in interpretability, and ethical concerns regarding data privacy and accountability, which constrained widespread adoption in complex real-world scenarios. In [14] explored AI for optimizing clinical pathways in personalized healthcare, integrating multidisciplinary teams and patient-specific treatment goals. Machine learning models trained on expert-provided baseline data generated personalized pathways, leveraging clinical terminologies, ontologies, association rules, and multi-modal health data. The AI-generated pathways were largely consistent with expert recommendations, improving decision-making efficiency and supporting individualized care for patients with multiple comorbidities. Limitations included variability in patient disease trajectories, difficulty predicting transitions across complex health states, dependence on data quality, and insufficient clinical oversight, restricting fully autonomous deployment in real-world healthcare settings.

In [15] explored the application of agentic AI in autonomous decision-making across food supply chains, addressing sustainability, efficiency, and resilience challenges. The method highlighted the complexity of modern food systems, which are susceptible to disruptions from climatic events and pandemics, and emphasized the role of agentic AI in enabling agents to make autonomous, proactive, and intelligent decisions. The methodology involved analyzing data from IoT-enabled supply chains, integrating predictive and prescriptive AI models, and assessing agent interactions for reliability, ethical alignment, and operational efficiency. Results demonstrated that agentic AI enhance decision-making, improve compliance, and optimize resource allocation, while fostering shared moral responsibility among agents. Limitations included challenges in ensuring model interpretability, data quality dependency, and the need for robust ethical oversight to guide autonomous decision-making. In. [16] investigated the role of collaborative agentic AI systems in enhancing global resource management across multiple industries, including healthcare, energy, and finance. The model employed machine learning algorithms, predictive analytics, and autonomous decision-making to optimize resource distribution, reduce waste, and improve operational efficiency. The model analyzed large-scale datasets, simulated agent interactions, and implemented case studies to evaluate system performance. In healthcare, AI agents predicted patient readmission risk, enabling targeted interventions and improved resource allocation. In energy, agents optimized renewable energy integration and storage, increasing adoption and reducing carbon emissions. In finance, AI enhanced fraud detection and risk assessment, reducing losses and improving compliance. Limitations included technical complexity, ethical and security concerns, and the dependence on high-quality data for reliable decision-making and system scalability.

A. Research Gaps

Although existing studies have demonstrated the transformative potential of agentic AI in healthcare, significant gaps remain in understanding its long-term effects and broader implications. Most research has focused on short-term outcomes, such as diagnostic accuracy, clinical decision support, and immediate patient benefits, but the sustainability of AI integration in clinical workflows has received limited attention. The evolving roles of healthcare professionals, including changes in responsibilities, workflow dynamics, and patient-provider interactions, remain underexplored. Moreover, while ethical concerns such as transparency, accountability, data privacy, and bias are acknowledged, current literature lacks comprehensive, multidisciplinary frameworks that combine insights from ethicists, clinicians, and AI developers. There is also limited real-world validation of agentic AI systems across diverse healthcare settings, with most studies relying on simulated or controlled datasets. Existing studies remain limited by fragmented workflow optimization, lack of interoperability across hospital systems, and the absence of coordinated multi-agent decision-making. Furthermore, most prior works focus on isolated tasks without delivering end-to-end orchestration or real-world validation. Future research must address these gaps to ensure responsible deployment, equitable patient care, and the development of robust ethical and regulatory guidelines for long-term integration of agentic AI in healthcare.

III. METHODOLOGY

The study introduces an agentic AI framework that autonomously orchestrates hospital workflows using multi-agent reinforcement learning. Each functional unit such as triage, bed management, laboratory, imaging, transport, pharmacy, and discharge is represented as an intelligent agent capable of perceiving, reasoning, learning, and negotiating within its environment. These agents collaborate through HL7® FHIR® (Fast Healthcare Interoperability Resources) event-driven interfaces, ensuring seamless communication and interoperability across departments and hospitals.

The architecture operates over a privacy-preserving edge-to-cloud environment, where edge agents handle latency-critical, local decisions, while cloud-based controllers coordinate large-scale or inter-hospital decisions. This hybrid distribution enhances scalability, adaptability, and reliability, enabling hospitals to respond dynamically to fluctuating clinical and operational demands.

A. System Architecture

The system follows a modular and event-driven workflow, progressing systematically from data ingestion to decision execution and performance evaluation. Diverse data sources

Authorized licensed use limited to: BMS Institute of Technology. Downloaded on June 27,2026 at 21:26:30 UTC from IEEE Xplore. Restrictions apply.

including patient monitoring systems, electronic health records (EHR), diagnostic imaging, laboratory outputs, ambulance telemetry, and environmental parameters are continuously captured and standardized. This integration is implemented through the FHIR Event Bus and Communication Layer, which ensures seamless and interoperable data exchange between agents using HL7® FHIR® protocols. Fig. 2 visualizes the methodological workflow of the agentic AI-based clinical workflow orchestration framework.




Fig. 2. Methodological workflow of the agentic AI-based clinical workflow orchestration framework.

Within this framework, the MARL layer governs adaptive and decentralized decision-making. Each agent processes contextual data relevant to its operational role and cooperatively learns optimal actions through reinforcement signals. The Learning process refines these behaviors iteratively using feedback from both live operations and simulated environments, enabling agents to adapt policies dynamically as patient volumes, resource availability, and external conditions change.

A Coordinator Layer oversees higher-order orchestration among agents, managing inter-departmental dependencies, resource allocation, autonomous ambulance routing and inter-hospital coordination. To uphold institutional, ethical, and regulatory compliance, the Governance and Safety module, including Distributed Crisis Management, continuously validates agent actions against established clinical policies, ensuring transparency, traceability, risk control, and safe operation during emergencies. The system further employs a digital twin simulation environment, an exact virtual replica of hospital operations, to test and optimize agent decisions before deployment in real-world settings. Finally, outcome and impact are assessed through quantifiable metrics such as patient waiting time, bed utilization efficiency, turnaround time, and overall fairness, which collectively determine the framework's effectiveness in enhancing healthcare workflow orchestration.

B. State, Observations, and Actions

Each intelligent agent in the framework operates within a factored state space that encapsulates clinical, operational, and contextual information to enable situational awareness and informed decision-making. The clinical state includes patient acuity indicators such as the Emergency Severity Index (ESI) and National Early Warning Score (NEWS2), providing quantitative measures of urgency and stability. The operational state reflects hospital workflow parameters: queue lengths, resource availability, staff rosters, and equipment readiness allowing agents to anticipate congestion and optimize throughput. Meanwhile, the exogenous state incorporates external influences such as traffic conditions, weather variations, or regional alerts that affect ambulance routing and hospital inflow. Given the heterogeneity and incompleteness of real-world hospital data, agents operate under partial observability. To manage uncertainty, the framework employs Partially Observable Markov Decision Processes (POMDPs). Each agent maintains a belief state, a probabilistic representation of the environment, updated through Bayesian inference or learned embeddings to estimate unobserved variables. This probabilistic reasoning ensures resilient decision-making even with delayed or noisy data streams. Agent actions include task scheduling, resource reservation, ambulance routing, and inter-agent negotiation for coordinated load balancing. These actions are selected using optimized policies that maximize cumulative reward functions integrating efficiency, safety, and fairness. Collectively, the state-observation-action model forms the cognitive core of the agentic system, where real-time data are continuously perceived, interpreted, and acted upon. This module represents the conversion of raw operational signals into autonomous, context-aware actions driving coordinated healthcare orchestration.

C. Learning and Planning (MARL Framework)

The proposed system utilizes a hierarchical MARL framework to achieve distributed yet coordinated learning across diverse hospital operations. This structure enables both local adaptability and global policy alignment. At the low level, individual agents such as those managing beds, imaging, or ambulance routing learn fast, local control policies using actor-critic algorithms (e.g., A3C or DDPG). These algorithms allow agents to approximate optimal decision policies through continuous interaction with their environment, balancing exploration and exploitation. Policy regularization mechanisms are incorporated to ensure stability under fluctuating workloads and prevent overfitting to transient operational states. At the high level, a coordinator agent governs long-term and system-wide resource allocation. It employs slower learning rates to formulate higher-order policies that regulate fairness, patient flow, and cross-departmental equilibrium. This hierarchical distinction ensures that quick tactical responses from local agents remain aligned with strategic institutional objectives like equity, safety, and throughput optimization.

For rare but high-impact events such as pandemics, infrastructure failures, or multi-casualty incidents, a Model Predictive Control (MPC) layer operates over a rolling time horizon, forecasting future states and adjusting decisions dynamically. The system integrates advanced MARL optimization techniques such as value decomposition, mean-field approximation, curriculum learning, and domain randomization to scale across hospitals of varying capacities and to enhance resilience against data shifts.

D. Inter-Hospital Communication

Efficient inter-hospital communication is a core element of the agentic AI framework, enabling real-time collaboration, mutual assistance, and adaptive load balancing among healthcare facilities. Each participating hospital continuously broadcasts its current operational state through standardized capability vectors, which encode essential metrics such as the number of available beds per specialty and acuity level, staffed operating rooms, laboratory and imaging capacities, on-call personnel rosters, patient throughput, and diversion status. These vectors are transmitted through the FHIR-based communication layer, ensuring interoperability and semantic consistency across heterogeneous hospital information systems.

Authorized licensed use limited to: BMS Institute of Technology. Downloaded on June 27,2026 at 21:26:30 UTC from IEEE Xplore. Restrictions apply.

To facilitate coordinated action, agents from different institutions engage in automated negotiation protocols built on commitment contracts. Each contract formally specifies an action (e.g., patient transfer, shared imaging access), associated deadlines, expected service quality, and penalty clauses for unmet commitments. This mechanism introduces a transparent, verifiable approach to inter-hospital collaboration, replacing the traditional ad hoc coordination that often leads to communication delays and resource underutilization. All negotiation records are stored in a tamper-proof audit ledger, ensuring traceability, compliance, and accountability.

Exchange policies govern when and how inter-facility collaborations are triggered. These policies integrate regulatory guidelines, payer agreements, and institutional priorities, ensuring that every negotiation complies with local and national healthcare regulations. Data privacy is maintained through strict segregation of operational and clinical layers: only aggregated operational metrics such as capacity levels or diversion status are shared across institutions. When a patient transfer becomes necessary, it is executed through encrypted and consented HL7® FHIR® bundles, ensuring compliance with data protection laws such as HIPAA and GDPR.

This communication mechanism transforms isolated hospitals into an intelligent, cooperative healthcare network capable of mutual aid and dynamic equilibrium. By enabling near real-time awareness, equitable load distribution, and auditable collaboration, the inter-hospital communication layer enhances both the efficiency and resilience of regional healthcare systems, especially under crisis conditions where resource optimization is critical.

E. Autonomous Ambulance Routing

The Autonomous ambulance routing module represents one of the most dynamic and impactful components of the agentic AI framework, designed to minimize response time and optimize patient transport decisions under varying clinical and environmental conditions. Each ambulance agent operates as an intelligent decision-making entity that continuously evaluates the system state to determine optimal routing paths based on real-time hospital capacity, traffic flow, road conditions, and patient acuity levels. The routing process is formulated as a multi-objective optimization problem, where the agent maximizes a reward function that balances several factors minimized travel time, predicted time-to-clinical-intervention upon arrival, and penalty weights associated with delays for high-acuity patients. If the destination hospital's capacity changes (e.g., ICU occupancy increases or a key facility goes offline), the agent autonomously re-routes in-flight, leveraging learned value functions from the MARL model. These decisions integrate reinforcement learning outputs with constrained shortest-path algorithms, which dynamically adjust routes considering both geographic constraints and medical urgency. The framework also incorporates fleet-level coordination, where multiple ambulances share situational awareness. Through demand prediction models, the system anticipates future emergency clusters and proactively repositions idle ambulances to maintain optimal coverage. Exploration constraints ensure safety and stability by preventing unnecessary rerouting or risk-taking behaviors in uncertain conditions.

Importantly, all routing decisions adhere to regulatory safety constraints, ensuring that high-acuity patients are never bypassed unless an equal or better-equipped facility is reachable within the same effective intervention window. This guarantees clinical fairness and adherence to triage ethics. By integrating autonomous routing intelligence into a hospital-wide orchestration framework, this module enhances prehospital efficiency, reduces emergency response times, and ensures equitable, data-driven patient allocation across the healthcare network.

F. Distributed Crisis Management

During large-scale emergencies, such as pandemics, infrastructure failures, or mass-casualty incidents, the proposed framework activates distributed crisis management protocols to preserve healthcare system stability and continuity of care. These protocols rely on lightweight consensus mechanisms, allowing multiple hospitals to coordinate crucial actions without a central command bottleneck. Key operations include trauma center assignments, surge bed creation, temporary redistribution of staff, elective procedure de-scheduling, portable imaging deployment, and ambulance staging for optimized coverage. Each department retains local autonomy, continuing its regular workflows while complying with global surge directives issued by the coordinating agents. This decentralized structure ensures that local agents make time-critical decisions independently while remaining aligned with regional objectives. When communication networks degrade due to overload or technical failure, agents automatically transition into pre-verified degraded-mode policies, which maintain safe fallback operations until full connectivity is restored. Once communication resumes, all agents synchronize their updated states through event-driven reconciliation to restore normal functioning. A command agent continuously maintains an auditable timeline of all crisis-related decisions, including justifications and policy references, enabling detailed post-incident evaluation and improvement. This distributed, adaptive crisis management approach ensures operational resilience, equitable resource allocation, and minimal disruption to critical healthcare services during both expected and unforeseen emergencies.

G. Safety, Governance, and Assurance

A runtime assurance shell surrounds each agent, imposing hard constraints and rate limiters. Machine-readable policy knowledge encodes legal, institutional, and clinical rules, allowing the system to veto unsafe actions and escalate decisions to humans when required. Every decision is accompanied by a provenance graph, linking inputs, applied policies, model versions, and outcomes for auditing and post-hoc explanation. Real-time bias and fairness checks monitor subgroup wait times and diversion rates. Cybersecurity follows a zero-trust model, ensuring signed artifacts, encrypted communications, and least-privilege access.

H. Simulation, Data, and Evaluation Plan

The system is trained and validated using de-identified operational logs including ED arrivals, lab and imaging timestamps, bed movements, OR schedules, and transport events, all harmonized as FHIR resources. Synthetic data augmentation ensures rare scenarios are represented. A digital-twin simulator replays demand and injects shocks such as weather disruptions, road closures, and multi-casualty incidents. Performance metrics include door-to-clinician times, imaging/lab turnaround, bed turnover, ambulance response, diversion avoidance, and rule-monitor violations.

Authorized licensed use limited to: BMS Institute of Technology. Downloaded on June 27,2026 at 21:26:30 UTC from IEEE Xplore. Restrictions apply.

Statistical tests and ablation studies decouple the effects of inter-hospital negotiation, autonomous routing, and emergency protocols.

I. Outcome and Impact

Finally, the workflow evaluates operational efficiency and patient-centered outcomes, including throughput, wait times, ambulance response, diversion rates, and adherence to safety policies. These outcomes provide feedback to both the MARL agents and the digital twin simulator, enabling continuous learning and policy optimization.

To ensure clarity of agent behavior, a brief algorithmic description has been added. The MARL-based workflow follows four core steps: (1) each agent observes local clinical and operational state variables, (2) the actor–critic network computes an action such as scheduling, routing, or resource allocation, (3) the resulting environment response updates the reward function capturing efficiency and safety, and (4) policies are iteratively optimized until convergence. Ambulance routing uses a multi-objective shortest-path algorithm enhanced with MARL value functions to dynamically re-route based on traffic, hospital capacity, and patient acuity.

J. Simulation setup

The experimental setup consists of a digital twin simulation environment that replays historical ED arrivals, imaging and laboratory timestamps, ambulance telemetry, and capacity fluctuations. Agents were trained using 1,000–3,000 simulated episodes and later validated through shadow-mode deployment on live HL7® FHIR® event streams. All experiments were executed on a cloud-based environment using Python and PyTorch frameworks.

TABLE I. MARL AND SYSTEM PARAMETER SETTINGS

Parameter	Value
Learning Rate (α)	0.0003
Discount Factor (γ)	0.99
Exploration Policy	ε-greedy (ε decays from 1.0 to 0.1)
Training Episodes	1,500
Replay Buffer	50,000 transitions
Batch Size	64
MPC Horizon (crisis-mode)	6 steps
Negotiation Timeout	4 seconds

IV. RESULTS AND DISCUSSIONS

The proposed agentic AI framework for clinical workflow orchestration was evaluated in two complementary directions, capturing both operational feasibility and performance gains. The first stage involved a large-scale simulation study using digital twins of an urban hospital system, while the second stage consisted of shadow deployment, where agents processed live hospital and ambulance data but recommendations were not instantiated in patient care, allowing comparison with standard human-managed practice. Both evaluation phases aimed to quantify how inter-hospital communication, autonomous ambulance routing, and distributed crisis management affect clinical workflow efficiency, safety, and resilience.

The performance gains observed in the simulation and shadow-mode evaluation can be attributed to the agents' ability to anticipate bottlenecks, negotiate resource availability, and react to real-time state changes faster than human-managed workflows. The reduction in delays across triage, diagnostics, and transport reflects the advantage of parallel, decentralized policy execution in MARL systems, which avoids the queuing and coordination overhead present in traditional workflows.

A. Simulation-Based Evaluation

1) Emergency Response and Throughput

Simulation experiments were conducted to model baseline hospital operations using historical logs, which included emergency department arrivals, inpatient admissions, bed occupancy, time from diagnosis ordering to result reporting, and ambulance dispatch-to-arrival intervals. Upon activation of the agentic AI orchestration framework, the system demonstrated substantial improvements in throughput and responsiveness across multiple service lines. Specifically, emergency door-to-clinician time was consistently reduced, largely due to anticipatory tasking by the agents and proactive bed booking. When inter-hospital communication was enabled, tail latencies for high-acuity cases decreased because patient transfers could be scheduled before local capacity limits were reached. The introduction of autonomous ambulance routing led to an estimated 60% reduction in emergency response times. This improvement was achieved through a combination of road-based traffic optimization, destination-specific selection, and pre-arrival hospital preparedness alerts, ensuring that staff and resources were ready upon patient arrival. Table I summarizes the operational performance improvements achieved by proposed framework.

TABLE II. OPERATIONAL PERFORMANCE IMPROVEMENTS ACHIEVED BY AGENTIC AI-BASED ORCHESTRATION FRAMEWORK

Metric	Baseline	Agentic AI Activated	Improvement (%)
ED Door-to-Clinician Time (min)	35.2	21.8	38.0
Ambulance Response Time (min)	25.0	10.0	60.0
Bed Turnover Time (hours)	14.5	11.2	22.8
Imaging TAT (hours)	5.4	3.9	27.8
Laboratory TAT (hours)	4.8	3.4	29.2
OR Throughput (cases/day)	18	22	22.2

2) Resource Utilization

Beyond emergency response metrics, the agentic AI framework significantly improved hospital resource usage. Bed turnover times were reduced as discharge agents proactively triggered downstream workflows, coordinating housekeeping and admissions to minimize delays. In diagnostic services, both imaging and laboratory turnaround times decreased as available slots were dynamically adjusted based on predicted demand, which reduced idle capacity and minimized queue variability. Operating room utilization also improved; elective case scheduling was smoothed in real time, allowing higher throughput without compromising access for urgent procedures. Simulation under disaster scenarios, such as mass-casualty incidents or infrastructure failures, demonstrated the system's resilience. Surge beds were

Authorized licensed use limited to: BMS Institute of Technology. Downloaded on June 27,2026 at 21:26:30 UTC from IEEE Xplore. Restrictions apply.

efficiently added, elective cases were cancelled in a coordinated manner, and patient load was balanced across multiple facilities, highlighting the capacity of the agentic orchestration framework to maintain operational continuity under extreme conditions.

B. Shadow-Mode Deployment

To validate the simulation findings in a real-world environment, the agentic AI framework was deployed in shadow mode, where agents processed live FHIR event streams and generated real-time recommendations without directly influencing patient care. These recommendations were recorded alongside human decisions for comparison. Analysis revealed a high degree of concordance between agent suggestions and clinician decisions, particularly in areas with strong data signals, such as bed allocation and diagnostic prioritization. The runtime safety monitoring layer effectively prevented unsafe actions through vetoes, with most vetoes attributable to inconsistent or delayed data rather than flaws in the decision logic. This demonstrates that the agents operate reliably alongside human workflows while maintaining safety and system integrity. Quantitative analysis showed consistent improvements across multiple operational metrics, as presented in Table II. Emergency Department (ED) door-to-clinician time was reduced by nearly 40%, while ambulance pre-hospital time dropped by 46% due to faster routing and coordination. Similarly, ICU bed allocation conflicts were halved, and imaging queue delays decreased by over 40%, underscoring the framework's ability to optimize both patient flow and diagnostic throughput.

TABLE III. COMPARATIVE PERFORMANCE BETWEEN HUMAN-MANAGED AND AGENTIC OPERATIONS

Metric	Human-Managed	Agentic Recommendation
ED Door-to-Clinician Time (min)	36.5	22.0
Ambulance Prehospital Time (min)	28.0	15.0
ICU Bed Allocation Conflicts	4	2
Imaging Queue Delays	7	4

C. Crisis Management Performance

Both simulation and shadow-mode evaluations were used to assess the resilience of the hospital network under crisis conditions. During mass-casualty events and infrastructure failures, the system's pre-distributed crisis protocols successfully maintained operational liveness across all hospitals in the network. Surge capacity was effectively managed as elective cases were canceled in coordination with the creation of additional surge beds, preventing the ad hoc responses that typically occur under baseline conditions. Furthermore, distributed load management allowed high-acuity cases to be balanced more evenly across multiple facilities, reducing bottlenecks and ensuring equitable access to care. These findings demonstrate that the agentic crisis management framework significantly enhances hospital resilience, even under degraded communication channels and high-demand scenarios.

D. System-Wide Efficiency and Fairness

The agentic AI framework not only enhanced operational efficiency but also maintained fairness and safety across hospital networks. By leveraging predictive knowledge and decentralized negotiation, the system effectively redistributed patient and resource loads across departments and facilities, optimizing workflow without overloading individual units. Improvements were observed in operating room throughput, diagnostic turnaround times, and bed turnover, highlighting the benefits of anticipatory scheduling over traditional reactive approaches. Importantly, the framework incorporated a fairness layer, which helped reduce disparities in access and treatment across demographic and geographic catchments, although continuous monitoring remains necessary to ensure equity. These multi-dimensional considerations are captured in the Trade-off Triangle of Agentic AI in Healthcare, which illustrates the balance between efficiency, fairness, and safety & governance, demonstrating that systemic optimization was achieved without compromising compliance or equity.

E. Discussions

This study demonstrates that autonomous agentic AI can transform reactive, human-led healthcare workflows into proactive, self-governing systems. A notable outcome is a 6% reduction in emergency response time through acuity-aware ambulance routing and inter-hospital negotiation. Multi-agent orchestration optimizes patient transport and downstream clinical readiness, overcoming limitations of traditional dispatching. The framework also improves resource utilization, reducing bed turnover, shortening diagnostic cycles, and increasing operating room throughput. By combining predictive knowledge with decentralized negotiation, resources are efficiently redistributed across departments and sites, outperforming conventional scheduling and delivering system-wide benefits without central micromanagement.

A major strength of the agentic system is its distributed crisis management protocols, which proved essential during mass-casualty scenarios and in environments with degraded communication. By enabling hospitals to operate under top-down coordinated actions, the system avoided the delays associated with ad-hoc decision-making, ensuring continuity of care even under significant stress. This is particularly important in disaster response scenarios, where both clinical capacity and IT infrastructure are compromised. Despite these promising outcomes, there are notable limitations. The simulation and shadow-mode deployments revealed gaps in data quality and interoperability, with inconsistent resource states resulting from synchronization delays and heterogeneous coding practices. These issues highlight the need for stronger data governance and improved interoperability maturity for successful deployment. Additionally, fairness concerns remain, as certain demographics and regions may face prolonged wait times due to historical ambulance staging patterns or uneven distribution of facilities. Therefore, ongoing monitoring and policy safeguards are essential to prevent inequalities from exacerbating. Lastly, the adoption of agentic systems will depend heavily on trust. Clinicians, administrators, and first responders must feel confident in the system's ability to provide transparent, explainable, and accountable decisions, with clear legal and policy frameworks to govern its use.

The computational complexity of the MARL framework grows linearly with the number of agents, as each agent maintains local policies and communicates only summarized state information. The inter-hospital negotiation mechanism operates with bounded communication overhead, ensuring scalability even in multi-facility environments. This enables

Authorized licensed use limited to: BMS Institute of Technology. Downloaded on June 27,2026 at 21:26:30 UTC from IEEE Xplore. Restrictions apply.

real-time decision-making without significant increase in computational load or latency.

Table IV illustrates a clear comparative evaluation of multiple existing operational methods against the proposed agentic AI framework. The results show that agentic AI consistently achieves superior performance across all metrics, demonstrating substantial gains in responsiveness, resource optimization, and overall workflow efficiency.

TABLE IV. TABLE X. COMPARATIVE PERFORMANCE ACROSS MULTIPLE EXISTING APPROACHES

Metric	Traditional Workflow	Static Rule-Based System	ML-Based Scheduling	Agentic AI Framework
ED Door-to-Clinician Time (min)	35.2	30.5	27.4	21.8
Ambulance Response Time (min)	25.0	22.0	17.5	10.0
Bed Turnover Time (hours)	14.5	13.2	12.4	11.2
Laboratory TAT (hours)	4.8	4.4	3.9	3.4
Throughput (cases/day)	18	19	20	22

V. CONCLUSION

This study demonstrates that Agentic AI forms a transformative basis for modern healthcare operations, converting reactive, human-led workflows into proactive, self-managing orchestration systems. The developed multi-agent framework, built upon MARL and seamlessly integrated with HL7® FHIR® and DICOM standards, enables continuous coordination across emergency triage, diagnostics, operating theatres, and discharge functions. Through digital-twin simulations and shadow-mode validation, the architecture demonstrated real-time learning, negotiation, and decision-making, aligning departmental activities with institutional goals while preserving transparency, safety, and compliance with NIST and EU AI frameworks. Performance evaluations confirmed significant operational gains, including a 60% reduction in ambulance response times, 38% faster emergency door-to-clinician intervals, 29% shorter diagnostic turnaround, and a 22% increase in operating room throughput. These results arise from three key architectural pillars: inter-hospital agent communication for mutual load sharing, decentralized ambulance routing for dynamic capacity alignment, and distributed crisis-management protocols that ensure resilience under high-demand and degraded communication scenarios. Predictive reasoning, decentralized negotiation, and runtime assurance layers collectively improved efficiency while upholding fairness and governance principles, surpassing the capabilities of traditional static scheduling and centralized control systems. Beyond operational metrics, the framework establishes a scalable and ethically sound foundation for self-managing healthcare ecosystems. Each decision is accompanied by provenance and explanation artifacts, ensuring accountability and auditability crucial for clinician trust and regulatory acceptance. This work offers a clear scientific contribution by unifying MARL-based orchestration, inter-hospital coordination, and autonomous ambulance routing into a single agentic AI framework. By integrating these capabilities end-to-end, the study addresses a key research gap in achieving fully self-managing, interoperable clinical workflows.

Future research will advance this framework through federated intelligence sharing among healthcare institutions to strengthen predictive accuracy without compromising data privacy. The integration of explainable reinforcement learning will enhance interpretability for medical professionals, while equity-driven policy monitoring will ensure fairness across demographic and geographic domains. Expanding toward multi-modal data fusion and predictive digital twins will further refine anticipatory decision-making. Broad deployment across connected hospital networks is projected to yield adaptive, resilient, and ethically governed healthcare systems ushering a new era of intelligent, self-optimizing clinical operations.

REFERENCES

[1] Hirani, R., Noruzi, K., Khuram, H., Hussaini, A. S., Aifuwa, E. I., Ely, K. E., ... & Etienne, M. (2024). Artificial intelligence and healthcare: a journey through history, present innovations, and future possibilities. Life, 14(5), 557.

[2] Mullankandy, S., Kazmi, I., Islam, T., & Phia, W. J. (2024). Emerging trends in ai-driven health tech: a comprehensive review and future prospects. European Journal of Technology, 8(2), 25-40.

[3] Collaco, B. G., Haider, S. A., Prabha, S., Gomez-Cabello, C. A., Genovese, A., Wood, N. G., ... & Forte, A. J. (2025). The Role of Agentic Artificial Intelligence in Healthcare: A Systematic Review.

[4] Iancu, A., Bauer, J., May, M. S., Prokosch, H. U., Dörfler, A., Uder, M., & Kapsner, L. A. (2024). Large-scale integration of DICOM metadata into HL7-FHIR for medical research. Methods of Information in Medicine, 63(03/04), 077-084.

[5] Lin, X., Tang, Y., Lei, X., Xia, J., Zhou, Q., Wu, H., & Fan, L. (2019). MARL-based distributed cache placement for wireless networks. IEEE Access, 7, 62606-62615.

[6] Karunanayake, N. (2025). Next-generation agentic AI for transforming healthcare. Informatics and Health, 2(2), 73-83.

[7] Suura, S. R. (2025). Agentic AI Systems in Organ Health Management: Early Detection of Rejection in Transplant Patients. Journal of Neonatal Surgery, 14(4s).

[8] Huang, G., Chen, X., & Liao, C. (2025). AI-Driven Wearable Bioelectronics in Digital Healthcare. Biosensors, 15(7), 410.

[9] Shimgekar, S.R.; Vassef, S.; Goyal, A.; Kumar, N.; Saha, K. Agentic AI framework for End-to-End Medical Data Inference. arXiv preprint arXiv:2507.18115 2025.

[10] Neupane, S.; Mittal, S.; Rahimi, S. Towards a hipaa compliant agentic ai system in healthcare. arXiv preprint arXiv:2504.17669 2025.

[11] Gao, S., Fang, A., Huang, Y., Giunchiglia, V., Noori, A., Schwarz, J. R., ... & Zitnik, M. (2024). Empowering biomedical discovery with AI agents. Cell, 187(22), 6125-6151.

[12] Ogbu, D. (2023). Agentic ai in computer vision domain-recent advances and prospects. International Journal of Research Publication and Reviews, 4(12), 5102-5120.

[13] Ganti, V. K. A. T. (2023). Development of an AI-Powered Clinical Pathway Optimizer for Personalized Healthcare Treatment Planning. American Data Science Journal for Advanced Computations (ADSJAC) ISSN: 3067-4166, 1(1).

[14] Pamisetty, A. (2024). Application of agentic artificial intelligence in autonomous decision making across food supply chains. Available at SSRN 5231360.

[15] Kundu, S. (2024). Collaborative Agentic AI for Global Resource Management: Optimizing Sustainability and Efficiency Across Industries.

Authorized licensed use limited to: BMS Institute of Technology. Downloaded on June 27,2026 at 21:26:30 UTC from IEEE Xplore. Restrictions apply.