BlockVerify — Report 3

Results & Comparison

A Blockchain-Based Product Authentication System to Eliminate Counterfeit Goods Across the Supply Chain

Course — BCSE329P, Blockchain and Distributed Ledger Technology Lab
Assessment — DA-9, Report 3: Results & Comparison
Guide — Dr. Sivaranjani A
GitHub repository — https://github.com/KushalAgrawal30/BlockVerify

Roll number	Name
23BKT0030	Mayank Balmoori
23BKT0033	Kushal Agrawal
23BKT0048	Jeevesh Malhotra

---

1. Recap

Report 2 documented BlockVerify's implementation and integration: two Solidity contracts (`ProductRegistry.sol` and `OwnershipTransfer.sol`, the latter inheriting the former so a single instance is deployed), an Express API with JWT authentication and role gating over MongoDB, QR generation bound to each on-chain record, and a React interface whose verification path reads the contract directly rather than trusting the backend.

Report 2 also recorded three items as outstanding, all of them evaluation work:

1. a centralized MongoDB-only baseline, without which no comparison could be made;
2. repeatable gas and latency benchmarks reporting distributions rather than single readings;
3. tamper-rejection results from repeatable runs.

All three are complete and are the substance of this report. The centralized baseline is implemented in `backend/baseline.js`; benchmarking in `backend/bench.js`; the tamper experiment in `backend/tamper.js`. Objective 07 — demonstrating blockchain's advantage over a conventional centralized database — moves from *partial* to *complete*, and the finding is more qualified than the project proposal anticipated.

---

2. Implementation and Experimental Setup

2.1 Environment

Table 1 — Experimental environment

Parameter	Value
Blockchain platform	Ethereum (EVM, Paris target)
Network	Hardhat Network — local, chain ID 31337, automatic mining
RPC endpoint	`http://127.0.0.1:8545`
Deployed contract	`OwnershipTransfer` at `0x5FbDB2315678afecb367f032d93F642f64180aa3`
Solidity compiler	`solc` 0.8.24
Runtime	Node.js 24.13.0, npm 11.6.2
Database	MongoDB 27017 — `blockverify` (production), `blockverify-baseline` (baseline)
Services	API `:4000`, baseline API `:4001`, React/Vite `:5173`
Host	Apple silicon MacBook Air, macOS
Trials per operation	30

2.2 Technology stack

Table 2 — Tools and libraries

Layer	Technology
Smart contracts	Solidity 0.8.24
Development framework	Hardhat 2.22.x with `@nomicfoundation/hardhat-toolbox`
Blockchain client	Ethers.js 6.17.0
Backend	Node.js, Express, Mongoose, `qrcode`, `jsonwebtoken`, `bcryptjs`
Frontend	React 19 with Vite, `html5-qrcode`
Testing	Mocha + Chai via Hardhat

2.3 Wallets and key handling

Twenty externally-owned accounts are derived from Hardhat's published test mnemonic on path `m/44'/60'/0'/0/{i}` and mapped to supply-chain roles: account #0 Manufacturer, #1–5 Distributor, #6–12 Retailer, #13–19 Customer. Each is pre-funded with 10,000 test ETH. The backend signs on behalf of the authenticated user's mapped account, which removes wallet-installation friction from the demonstration at the cost of the backend holding the keys. These are publicly known development keys with no value on any network; section 8 treats this as a limitation rather than a design choice to carry forward.

2.4 Dataset

Twenty-five seed products span three batches (`BATCH-A/B/C`) across five pharmaceutical product names, with custody deliberately staggered — two with the customer, three with the retailer, five with the distributor, fifteen with the manufacturer — so every supply-chain stage is represented. Each benchmark run registers a further 30 products with unique serials. Four demonstration users represent the four roles. MongoDB holds only users, roles and sessions; no product data.

2.5 The centralized baseline


The baseline implements the same workflow — register, transfer, verify, QR generation — with MongoDB as the only source of truth and no blockchain component. It was written the way a competent team would build this without a chain: an indexed collection, a unique index on serial numbers, server-side owner authorization, and the *same* replay-based verification algorithm as the contract. The difference under measurement is therefore architectural, not a matter of one implementation being carelessly written.

---

3. Results

3.1 Functional and security tests

Figure 1 — Contract test suite: nine passing tests with gas output



All nine Hardhat/Chai tests pass. They cover registration, duplicate-serial rejection, multi-hop transfer, unauthorized-transfer rejection, transfer of an unregistered product, and all three branches of `verifyProduct` — `NOT REGISTERED`, `VERIFIED GENUINE` and `OWNERSHIP MISMATCH`.

The mismatch branch deserves a note. It is unreachable through the contract's own functions: no sequence of legitimate calls can make the transfer log disagree with `currentOwner`. It is therefore tested by forcing node storage directly with `hardhat_setStorageAt`, the same mechanism used in the tamper experiment of section 3.5. A branch that cannot be reached legitimately still has to be proven correct, because its whole purpose is to fire when something illegitimate has happened.

3.2 Transaction details

Figure 2 — A mined `transferOwnership` transaction on the local node

```
eth_chainId
eth_getTransactionCount
eth_estimateGas
eth_chainId (2)
eth_gasPrice
eth_maxPriorityFeePerGas
eth_getBlockByNumber
eth_chainId
eth_blockNumber
eth_sendRawTransaction
  Contract call:       OwnershipTransfer#transferOwnership
  Transaction:         0x0be7555b34ce0378d55897e8c4cabfbd2592f3bd959a1473fcbfeff944dbb44e
  From:                0xf39fd6e51aad88f6f4ce6ab8827279cfffb92266
  To:                  0x5fbdb2315678afecb367f032d93f642f64180aa3
  Value:               0 ETH
  Gas used:            121018 of 121018
  Block #48:           0x60a4171eb8fd1c3adf6589e1390f3f658ca01873d80caaa68406a7c7429e1d82
```

Every ownership change is a signed transaction with a hash, a gas figure and a block number. The node log distinguishes `eth_sendRawTransaction` — state changes, which are mined and consume gas — from `eth_call`, the `view` reads used by verification, which execute locally, cost nothing and appear with no gas or block number. That distinction is the economic basis of the system: writing provenance costs gas, reading it does not.

Figure 3 — Product registration: on-chain write with transaction hash, gas and generated QR code




Figure 4 — Verification: genuine status with the full chain of custody




Figure 4 is the system's central output. Product #26 returns `VERIFIED GENUINE` with its identity fields, its current owner, and all three ownership hops with on-chain timestamps — Manufacturer → Distributor → Retailer → Customer — read directly from the chain in 51 ms. Objectives 03, 04 and 05 are all evidenced in this single result.

Figure 5 — Verification of an unregistered product ID




Figure 6 — Duplicate serial registration rejected by the contract





Figure 7 — Role-based interface: the Distributor portal



3.3 Performance measurements

Figure 8 — Benchmark output: 30 trials per operation across both systems




Table 3 — Operation latency, milliseconds, 30 trials

Operation	System	Median	Mean	p95	Min	Max
Register	Blockchain	128.21	128.09	151.36	116.17	152.14
Register	Centralized	5.85	7.38	8.68	4.86	47.94
Transfer	Blockchain	118.34	118.58	138.30	100.52	140.29
Transfer	Centralized	4.74	5.09	8.59	2.81	12.23
Verify (via API)	Blockchain	45.26	45.58	49.34	39.26	52.57
Verify (direct read)	Blockchain	15.23	15.78	18.52	13.28	31.40
Verify	Centralized	3.20	3.17	4.09	1.84	5.01

Figure 9 — Median operation latency by system




Table 4 — Gas consumption

Operation	Gas	Condition
Contract deployment	1,577,877	one-time
`registerProduct`	207,988	first registration on a fresh contract
`registerProduct`	190,996	steady state (benchmark input strings)
`registerProduct`	190,888	steady state (shorter interface input strings)
`transferOwnership`	121,018	first transfer of a given product
`transferOwnership`	103,910	subsequent transfers
`getProduct`, `getTransferLog`, `verifyProduct`	0	`view` functions

Figure 10 — Gas consumption per contract operation





Figure 11 — Verification throughput



3.4 Storage

The on-chain storage layout was read directly from the node rather than inferred. Each `Product` occupies exactly six 32-byte slots — one per field, with short strings packed inline into a single slot under Solidity's short-string encoding — plus one slot for the duplicate-serial guard. Each transfer hop occupies three slots (`from`, `to`, `timestamp`), with one further slot for the array length.

Table 5 — Storage per product

System	Product record	Each transfer hop	Product with 3 hops
Blockchain	7 slots = 224 bytes	3 slots = 96 bytes	17 slots = 544 bytes
Centralized (MongoDB)	393 bytes average measured	stored inline in the document	393 bytes average measured

3.5 Tamper resistance

Figure 12 — Tamper experiment: four attacks against both systems





Figure 13 — Tamper-resistance detection matrix



Four attacks were executed against both implementations over the same dataset. Attacks 1 and 2 operate through the application interface; attacks 3 and 4 assume an attacker who has reached the storage layer directly — a database administrator, a compromised server, or a dishonest operator.

Detection rate: blockchain 4/4, centralized 2/4.

---

4. Comparison

Table 6 — BlockVerify against the centralized baseline

Parameter	BlockVerify (blockchain)	Centralized baseline (MongoDB only)
Functionality	Register, QR-bind, transfer, verify, audit history	Identical — same API surface and same verification algorithm
Register latency (median)	128.21 ms	5.85 ms — **21.9× faster**
Transfer latency (median)	118.34 ms	4.74 ms — **25.0× faster**
Verify latency (median)	15.23 ms direct, 45.26 ms via API	3.20 ms — **4.8× faster than direct**
Verification throughput	21.9 /s	1002.4 /s — **46× higher**
Transaction cost	190,996 gas register, 121,018 gas transfer	No per-operation cost
Verification cost	0 gas — `view` function	No cost
Storage per product	224 bytes on-chain, replicated on every node	393 bytes, single copy
Duplicate prevention	Contract revert, enforced by consensus	Unique index, enforced by the database
Authorization	`require(currentOwner == msg.sender)`, enforced by every validating node	Server-side check, enforced by application code
History mutability	Append-only; no code path shortens the log	Fully mutable by anyone with database access
Tamper detection	**4/4**	**2/4**
Transparency	Any party can audit with only the contract address and a public RPC endpoint	Audit requires trusting the operator's own database
Trust requirement	None for reads	Must trust the operator

---

5. Analysis and Interpretation

5.1 Why the blockchain path is roughly 20–25× slower, and why the real gap is wider

A write to the contract carries costs the database write does not: transaction construction, ECDSA signing, an `eth_estimateGas` round trip, a `staticCall` preflight, broadcast, mining, and a receipt poll. That is six or more JSON-RPC round trips where MongoDB performs one indexed document write.

The measured gap understates reality. Hardhat Network mines a block the instant a transaction arrives, so the 128 ms median contains no consensus delay whatsoever. On Ethereum mainnet a transaction waits roughly 12 seconds for a block, and several blocks for practical finality; on a Layer-2 such as Polygon, one to two seconds. The honest statement is therefore that

128 ms is a floor that only a development network can achieve

, and a production deployment would be three to four orders of magnitude slower on writes. Any claim that blockchain is competitive with a database on write latency would be false.

5.2 Why verification is the operation that actually matters

Registration and transfer happen once per product per supply-chain hop and are performed by businesses, which can absorb seconds of latency. Verification happens every time anyone scans a QR code, is performed by consumers at the point of sale, and is the only operation where latency is felt by a person waiting.

Verification is also where the architecture is most favourable. It is a `view` function: it executes locally on a node, is mined into no block, consumes zero gas, and requires no wallet. At a 15.23 ms median direct read, it is well inside the threshold at which an interaction feels instantaneous, and it would remain so on a public network, because a `view` call does not wait for consensus. The operations that blockchain makes expensive are the infrequent ones; the frequent one is free and fast. That asymmetry is what makes the design viable at all.

The 45.26 ms figure for verification through the Express API against 15.23 ms for the direct read is worth noting for a second reason. The browser uses the direct path, so the API is not merely slower — it is unnecessary, and leaving it out of the trust path is both the faster and the more trustworthy choice.

5.3 Why gas is perfectly deterministic, and what the three register figures mean

Gas showed a standard deviation of exactly zero across all 30 trials. The EVM is a deterministic state machine with a published cost per opcode; identical input over identical state costs identical gas. There is no scheduling noise to average out, which is why a single reading is sufficient for gas where it would be inadequate for latency.

The three different `registerProduct` figures across our own figures are fully accountable, and reconciling them demonstrates the cost model rather than contradicting it:

- **207,988 vs 190,888 — a difference of exactly 17,100.** The first registration on a freshly deployed contract takes `productCount` from zero to one. Writing a storage slot that currently holds zero costs 20,000 gas against 5,000 for updating a non-zero slot, a 15,000 difference, plus 2,100 for the first (cold) access to that slot under EIP-2929. 15,000 + 2,100 = 17,100.
- **190,996 vs 190,888 — a difference of exactly 108.** Calldata length. The benchmark passed 36 characters across serial, name and batch; the interface passed 27. In ABI encoding each additional character replaces a zero padding byte, costing 16 gas instead of 4 — a net 12 per character. 9 × 12 = 108.

The same effect explains `transferOwnership` at 121,018 for a product's first transfer against roughly 103,910 thereafter: the first hop initialises the transfer log's length slot from zero. The measured premium is 17,108 rather than exactly 17,100, the residual eight gas being calldata variation between recipient addresses with differing numbers of zero bytes.

5.4 Why storage is smaller on-chain and yet far more expensive

Table 5 shows the on-chain product record at 224 bytes against 393 bytes in MongoDB — the chain is *more* compact. MongoDB stores field names with every document in BSON, plus `_id` and Mongoose's `__v`; the contract stores bare 32-byte slots at computed addresses with no field names at all.

Byte count is nonetheless the wrong measure of cost. Those 224 bytes are replicated on every node in the network and are priced at 20,000 gas per fresh slot, while MongoDB's 393 bytes exist once. Storage cost here is not a function of size but of replication and permanence, which is precisely the resource being bought: the record is expensive *because* many independent parties keep it and none can quietly discard it.

5.5 Why both systems scored 2/4 on the first two attacks

The most important interpretive point in this report is that **blockchain provided no advantage on attacks 1 and 2.** A unique index rejects a duplicate serial as reliably as a contract `require`, and a server-side owner check rejects an unauthorized transfer as reliably as `require(currentOwner == msg.sender)`. Any claim that a blockchain is needed to prevent duplicate registration is simply wrong, and our own project proposal came close to implying it.

The advantage appears only against attacks 3 and 4, and only because of who the attacker is. In the centralized system the verification algorithm is identical to the contract's — it replays the custody chain and checks that it lands on the recorded owner — yet it reports `VERIFIED GENUINE` on a forged record. It does so because both the history it replays and the owner it checks against are attacker-controlled. **A consistency check is only as trustworthy as the least trustworthy party who can write to the data being checked.** The algorithm is not what provides the guarantee; the inability to rewrite the inputs is.

5.6 On attack 4 and the integrity of this experiment

Our first implementation of attack 4 erased the custody history but left `currentOwner` pointing at a forged address. That record is internally inconsistent, the replay check caught it, and the centralized system appeared to score 3/4. The attack was unrealistic: a competent insider erases the history *and* resets the owner to the manufacturer, leaving a record that is internally consistent and simply says the product never left the factory. Re-run that way, the attack goes undetected and the score is 2/4.

We record this because the weaker attack flattered our own hypothesis. An evaluation that only tests attacks the system survives measures nothing.

5.7 What the blockchain result does and does not prove

Attack 3 against the blockchain was carried out with `hardhat_setStorageAt`, which forces a storage slot directly. This is worth stating plainly: **a public Ethereum network offers no such facility.** Changing a deployed contract's storage there requires rewriting history against the network's consensus. The attack is possible here only because a development node deliberately exposes it for testing.

What the result shows is therefore narrower but still meaningful: even granting an attacker a power no real network grants, the forged record is *detected* — `verifyProduct` returns `OWNERSHIP MISMATCH` because the transfer log no longer leads to `currentOwner`. The verification algorithm fails safe rather than fails silent. Attack 4 is the stronger structural result: the transfer log is an append-only array, and no code path in the contract shortens it, so erasing a hop is not an attack the contract will perform at any privilege level.

---

6. Strengths

Verification requires no trust in us. `frontend/src/chain.js` reads the contract directly over JSON-RPC. The Express API can be shut down entirely and verification still works. Any third party with the contract address and a public

RPC endpoint can audit any product without an account, an API key or our cooperation. In the centralized baseline, an audit is a request to the operator to show their own records.

Verification is free and fast.
Zero gas, no wallet, 15.23 ms median — the operation consumers perform is the one the architecture makes cheapest.

History is append-only by construction, not by policy.
No contract function shortens the transfer log. This is a property of the code, not an access-control rule that an administrator can be persuaded to bypass.

Verification never trusts a stored flag. `verifyProduct` re-derives authenticity by replaying the custody chain, so a broken chain returns `OWNERSHIP MISMATCH` rather than a cached "genuine" boolean.

The QR carries a pointer, not a claim. Encoding only `{contractAddress, productId}` means every scan forces a fresh chain read, so forging the label gains an attacker nothing — the label is not the evidence.

Gas costs are fully accounted.
Every figure in Table 4 reconciles to the EVM cost model to the exact gas unit, rather than being reported as an observation.

Hardware-free.
Any phone camera is a verification terminal; no RFID or NFC infrastructure is required at any point in the chain.

---

7. Limitations

Write performance is 20–25× worse, and that understates it.
As section 5.1 sets out, the local network contributes no consensus delay. A production deployment would be seconds per write, not milliseconds.

Throughput is 46× lower for verification. 21.9 /s against 1002.4 /s. Our verification makes three separate JSON-RPC calls — `getProduct`, `getTransferLog`, `verifyProduct` — where one would do.

The backend holds all private keys.
Signing on behalf of users removes MetaMask friction from the demonstration, but it means a compromised backend can transact as any participant. This weakens the decentralisation argument the project makes, and is a demonstration convenience, not a design we would defend.

A local network is not a deployment.
Instant finality, no gas price, no competing transactions, no reorganisations, twenty pre-funded accounts.

The QR can be copied.
The chain proves a record's integrity; it cannot prove that the physical object carrying the label is the object the record describes. A counterfeit bottle bearing a photocopied genuine label still verifies as genuine. This is the most significant limitation in the system and no amount of cryptography addresses it.

Scan context is not checked. Report 2's design anticipated flagging a copied label by comparing `currentOwner` against the scanning party. The chain holds the data to do this, but the interface does not yet implement it, so a label copied from a genuine product returns `VERIFIED GENUINE` with the true owner's address shown rather than an explicit warning.

The chain cannot validate what was entered.
Immutability protects a record after it is written. A manufacturer who registers false batch information has written false information permanently and verifiably.

Single-machine measurement.
One host, one client, sequential requests, 30 trials. No concurrent load, no network variance, no multi-node consensus.

---

8. Proposed Improvements

Batch verification into one call. A `verifyProductFull` returning status, product and transfer log together would collapse three JSON-RPC round trips into one and should raise verification throughput materially — the clearest available performance win, and it requires no architectural change.

Replace backend-held keys with user-controlled wallets.
MetaMask or WalletConnect signing would make each participant responsible for their own transactions and remove the single point of compromise that currently undercuts the decentralisation claim.

Deploy to a public test network and re-measure.
Sepolia for Ethereum semantics, Polygon Amoy for Layer-2 costs. This would replace the floor figures in Table 3 with representative ones and let gas be converted to actual currency.

Implement scan-context mismatch detection. Comparing `currentOwner` against the scanning party's wallet would turn the copied-label case from a silent `VERIFIED GENUINE` into an explicit warning, closing the gap noted in section 7.

Strengthen physical binding.
Tamper-evident packaging, or NFC tags carrying a signed challenge-response, would address what a printed QR cannot. This is the only improvement that attacks the system's real residual weakness.

Move bulk data off-chain with on-chain hashes.
Product images or certificates belong in IPFS or similar with only a content hash anchored on-chain, keeping per-product gas flat as records grow richer.

Report concurrent-load results.
Multiple simultaneous clients, with queueing behaviour and confirmation times under contention.

Independent contract audit before any real deployment.
The contract is small, but it has not been reviewed by anyone outside the team.

---

9. Conclusion

The three evaluation gaps recorded in Report 2 are closed. A centralized MongoDB-only baseline was implemented, both systems were benchmarked over 30 trials per operation with distributions reported, and four attacks were executed against each.

The headline numbers are that the centralized system is 21.9× faster to register, 25.0× faster to transfer and sustains 46× the verification throughput, while BlockVerify detects 4 of 4 tamper attacks against the baseline's 2 of 4. The project's original framing — that blockchain is better for this problem — is not what the data supports. What it supports is narrower and more defensible:

blockchain costs roughly an order of magnitude in write latency and throughput, and buys detection of exactly the attack class a centralized system structurally cannot detect, namely tampering by whoever controls the storage.

Three findings were not anticipated when the project was proposed. First, a blockchain provides no advantage at all against duplicate registration or unauthorized transfer — a unique index and a server-side check handle both, and claiming otherwise would be wrong. Second, the verification algorithm is not what provides the guarantee; both systems run the identical replay check and the centralized one still certifies a forged record, because a consistency check is only as trustworthy as the least trustworthy party who can write to its inputs. Third, the economics are favourable in exactly the right place: the expensive operations are the infrequent business-side writes, while the operation consumers perform constantly costs no gas and completes in 15 ms.

The residual weakness is not cryptographic. A QR label can be photocopied onto a counterfeit product, and no property of the chain prevents it. BlockVerify guarantees that a product's recorded history has not been altered since it was written; it

does not guarantee that the object in a customer's hand is the object that history describes. Closing that gap requires physical measures — tamper-evident packaging or secure item-level identifiers — and is the honest boundary of what this system achieves.