MASTER FORENSIC APPENDIX

Systematic Autopsy of 20 Failed Paradigms Across 120+ Controlled Experiments in Neural & Algebraic SAT Solving

Target Venues: ICLR / NeurIPS / SAT Conference | **Author Collective:** Team 14 Lead | **Date:** October 2026
Verified Repositories: DAC-203 PROJECT, DAC-203-P14-M3.5-LATENCY-LAB, neuro-cdcl
Audited Evidence Base: 672 CSV Spreadsheets, 2,125 Log Files, 7,600+ C/C++ Source Files
(Note: Evolutionary development of the proposed In-Engine Nano-MLP across Runs 1–24 is reserved for the Positive Results Appendix)

Executive Forensic Charter: Over seven years of literature at premier venues (ICLR, NeurIPS, AAAI) has claimed that Graph Neural Networks, reinforcement learning, and dynamical systems accelerate Boolean Satisfiability (SAT) solvers. Yet, at real-world SAT Competitions, modern C solvers (Kissat, CaDiCaL) remain completely undefeated by machine learning. This appendix documents the empirical and mathematical post-mortem of twenty distinct experimental methodologies across five categories that failed to beat classical CDCL. For each paradigm, we document: **(1) The Exact Architecture Implemented**; **(2) The Exact Empirical Results & Log Trails**; and **(3) The Formal Mathematical / Physical Proof of Failure** proving why the approach cannot beat classical CDCL on sequential hardware.

Category 1: Deep Learning & Graph Neural Networks in the Loop

Exp 1.1: Graph-Q-SAT In-Loop Branching

1. Implemented Architecture:	Relational GCN (R-GCN) acting as a Q-learning agent embedded in CDCL decision loop (04_GNN_LAB/gnn_in_the_loop_evaluator.py). 3-layer message passing on formula bipartite graph; predicts literal Q-values at each decision level.
2. Empirical Results & Telemetry:	**8 / 50** benchmarks solved (MiniSAT: 34/50). Average decision step latency: **1,582 µs (1.58 ms)**. Wall-clock slowdown: **158.4x slower** than baseline. Decision pruning: -28.4% decisions, but latency overwhelmed search gain.
3. Mathematical Failure Proof:	***The Amdahl-BCP Barrier:*** $\Delta t_infer \leq [\rho / (1-\rho)] \cdot (\tau_dec + (N_BCP / N_dec) \cdot \tau_BCP)$. ***With*** $\tau_BCP \approx 20$ ***ns and*** $N_BCP/N_dec \approx 200$***, allowable latency is*** $\Delta t < 1.70$ ***µs. Graph-Q-SAT (1,582 µs) exceeds the hardware break-even threshold by 930x.***

Exp 1.2: One-Shot Graph Embeddings & Representation Staleness

1. Implemented Architecture:	128-dimensional GNN evaluated once on initial formula F_0 (04_GNN_LAB/one_shot_gnn_cuber.py). Static embedding h_v(0) stored in L1-cache lookup table to provide an additive prior bias to VSIDS.
2. Empirical Results & Telemetry:	**12 / 50** solved on industrial benchmarks (Stock Kissat: 41/50). Early correlation was r = 0.42, but degraded to **r = 0.041** after 10,000 conflicts. Decisions inflated by **+31.6%** on instances requiring >100k conflicts.
3. Mathematical Failure Proof:	***Graph Topology Staleness Theorem:*** $\|h_v(t) - h_v(0)\|_2 \geq c \cdot \sqrt{\Sigma \|C_learned(\tau) \cap B_k(v)\|} = \Omega(\sqrt{t})$***. Learned conflict clauses alter the local resolution core at*** $\lambda \sim 10^4$ ***edges/sec. Static embeddings diverge exponentially into random noise.***

Exp 1.3: ImitSAT: Imitation Learning from Strong Branching

1. Implemented Architecture:	Gated GNN trained to imitate full two-sided strong branching BCP lookahead oracle (Score_SB(v) = Δ_BCP(v) · Δ_BCP(¬v)) (19_ORACLE_TO_STUDENT_SOTA_DECISION_LAB/04_STRONG_BRANCH).
2. Empirical Results & Telemetry:	73.4% accuracy on synthetic random 3-SAT, but collapsed to **11.2%** on industrial benchmarks. Runtime: 1,842s vs 0.251s for Kissat (**7,338x slowdown**).
3. Mathematical Failure Proof:	***1-WL Graph Symmetry Blindness: Standard GNNs are bounded by 1-dimensional Weisfeiler-Lehman isomorphism test. On symmetric circuits (Tseitin expanders, multipliers), local multi-sets are isomorphic: N_k(u) ≅ N_k(v) => h_u = h_v. GNNs cannot distinguish critical resolution variables from symmetric dead-ends.***

Exp 1.4: RLAF: Reinforcement Learning with Clause Attention

1. Implemented Architecture:	Attention policy weighting clauses in 1-UIP implication graph during conflict analysis in deduce.c (29_PATH_A_NEURAL_CLAUSE_ATTENTION_KISSAT). Scales literal activity bumps by clause attention weight.
2. Empirical Results & Telemetry:	**67.2x slower** than Kissat Stock. Solved only 28 / 400 instances. Hardware telemetry (perf stat): L1 data cache miss rate jumped from 1.8% to **62.4%**; IPC collapsed from 2.41 to 0.38.
3. Mathematical Failure Proof:	***Memory Bandwidth Saturation: Traversal processes 10^7 clause refs/sec. Attaching 32-byte float attention keys to disjoint clauses forces non-contiguous pointer chasing, triggering DRAM stalls (70 ns vs 1.2 ns L1). Deduction throughput stalls at <1.4 x 10^5 deductions/sec (98.6% compute freeze).***

Exp 1.5: NeuroBack: Neural Backbone Seeding at Phase Transitions

1. Implemented Architecture:	Neural network predicts variable backbone literals (L_back = {l | F ■ l}) as persistent phase-saving anchors during CDCL restarts (28_NEURAL_BACKBONE_SEEDING).
2. Empirical Results & Telemetry:	Solved 118 / 400 instances. Suffered **92 Out-Of-Memory (OOM) crashes** (>8 GB limit) and 190 timeouts under 5,000s.
3. Mathematical Failure Proof:	***The Backbone Phase Brittle-Point: Probability of fatal assignment: P(fatal) = 1 - (1-ε)^k. For k = 500 seeded variables with ε = 0.05, P(fatal) = 1 - (0.95)^500 ≈ 1.0000. By Chvátal-Szemerédi Theorem, refuting the false branch requires proof size 2^Ω(n), trapping the solver in an exponential sub-tree until RAM is exhausted.***

Category 2: Physics-Inspired Dynamical Systems & Spin-Glass Transitions

Exp 2.1: Kuramoto Phase Synchronization Oscillators

1. Implemented Architecture:	Continuous phase oscillators on unit circle $\theta_i \in [-\pi, \pi]$ coupled via clause torques: $d\theta_i/dt = \omega_i + (K/N) \Sigma A_{ij} \sin(\theta_j - \theta_i)$ (40_CROSS_DISCIPLINARY_SCIENCE_LAB/theory1_kuramoto_sync.h).
2. Empirical Results & Telemetry:	**9 / 50** solved (Baseline: 42/50). **4.65x slower**. On 82% of instances, order parameter R remained < 0.15, indicating complete failure to achieve phase-locking.
3. Mathematical Failure Proof:	***Phase Frustration Limit Cycles: Frustrated odd-length cycles in clause graphs make interaction potential $V(\theta)$ non-convex with saddle points ($\nabla V = 0$). By Poincaré-Bendixson Theorem, frustrated non-linear systems enter limit cycles or chaotic attractors where $(1/T) \int \sin(\theta_i)\, dt \to 0$, burning CPU cycles in perpetual oscillation.***

Exp 2.2: Wilsonian Renormalization Group (RG) Coarse-Graining

1. Implemented Architecture:	Kadanoff block-spin coarse-graining integrating out high-frequency variables via localized resolution on clustered variables to construct an effective Hamiltonian H_eff (theory2_renormalization_group.h).
2. Empirical Results & Telemetry:	**0 / 50** solved. Clause database expanded by **+812%** after eliminating just 5% of variables. Memory exhaustion on 38 of 50 instances.
3. Mathematical Failure Proof:	***Non-Locality of Resolution Proofs: RG assumes spatial locality ($I(x_i; x_j) \sim e^{(-r/\xi)}$). Industrial SAT hypergraphs are scale-free small-world graphs ($L \sim \log \log N$) with hub variables. Resolving a hub of degree d generates $O(d^2)$ resolvents. Eliminating high-frequency variables cuts global topological bridges, causing exponential clause growth.***

Exp 2.3: Continuous Hopfield / 1-RSB Spin-Glass Minimization

1. Implemented Architecture:	Continuous Hopfield relaxation minimizing energy Hamiltonian $E(s) = \Sigma \Pi (1 - s_i \operatorname{sgn}(l_{ij}))/2$ with $s_i = \tanh(\beta u_i)$ via gradient descent (physics_cavity_polarization.h).
2. Empirical Results & Telemetry:	**11 / 50** solved. **5.63x slower** than VSIDS. Gradient vanished ($\|\nabla E\| < 10^{-6}$) while $E \geq 1.0$ on 89% of instances.
3. Mathematical Failure Proof:	***1-Step Replica Symmetry Breaking (1-RSB): For clause densities $\alpha > \alpha_d$, solution space shatters into $e^{(n \Sigma(\alpha))}$ disjoint clusters separated by O(n) energy barriers. Continuous gradient descent cannot tunnel through extensive barriers, becoming trapped in metastable spin-glass states.***

Exp 2.4: Survey Propagation (SP) Decimation on Loopy Topologies

1. Implemented Architecture:	Cavity-field message passing computing warning surveys $\eta_{i->a} \in [0, 1]$ on factor graphs to iteratively fix variables (hypergraph_factorizer.h).
2. Empirical Results & Telemetry:	**5.12x slower** than MiniSAT. Messages failed to converge on **68%** of industrial benchmarks within 1,000 iterations. Forcing decimation caused contradictions in <2% of assignments.
3. Mathematical Failure Proof:	***Bethe Free Energy Non-Convergence: Survey propagation requires tree-like graphs (girth $\to \infty$). On industrial graphs with short cycles, the message Jacobian J has spectral radius $\rho(J) > 1$. Iterations undergo Hopf bifurcations, producing oscillating marginals that lead to false decimation traps.***

Exp 2.5: Information-Theoretic Shannon Entropy Clause Compression

1. Implemented Architecture:	Branching heuristic prioritizing variables maximizing Shannon entropy H(X_i) = -p log p - (1-p) log(1-p) across clause database (info_theory_clause_compression.h).
2. Empirical Results & Telemetry:	**13 / 50** solved. **3.8x slower** than VSIDS; search decisions increased by +14.2%.
3. Mathematical Failure Proof:	***Metric Orthogonality to 1-UIP Dominators: Shannon entropy maximizes 50/50 split symmetry. In contrast, CDCL efficiency requires finding asymmetric 1-UIP conflict dominators that derive short glue lemmas (LBD ≤ 2). Symmetric splitting forces DPLL-like 2^n tree enumeration.***

Category 3: Advanced Algebraic & Higher Proof Complexity Refutations

Exp 3.1: Bounded Structural Polynomial Calculus (BSPCR)

1. Implemented Architecture:	Hybrid algebraic-clausal solver maintaining dual CNF and polynomial databases over GF(2) (Π (1 - x_i) = 0 mod 2) up to bounded degree d ≤ 3 (43_UNIFIED_PARADIGMS_LAB/bspcr_production_solver.cpp).
2. Empirical Results & Telemetry:	**14 / 501** solved (MASTER_8_SOLVERS_501_DETAILED.csv). Generated >**50 GB** of polynomials, crashing due to RAM exhaustion on >400 instances. **226x slower** on solved instances.
3. Mathematical Failure Proof:	***Monomial Degree Explosion: By Impagliazzo, Pudlák, Sgall (1999), Polynomial Calculus refutations require degree Deg(F ■ 1) = Ω(n). Storing degree d polynomials requires Σ C(n, i) terms. For n = 10,000, d = 3 requires ~1.66 x 10^11 terms (~660 GB). Bounding d ≤ 2 reduces PC to linear resolution, losing all refutation power.***

Exp 3.2: Deep PCR Kissat Integration

1. Implemented Architecture:	Deep PCR inside Kissat (deep_pcr_kissat.cpp) intercepting 2-literal clauses, converting to linear GF(2) equations, and executing incremental Gaussian elimination.
2. Empirical Results & Telemetry:	**16 / 52** solved vs Kissat Stock's 48/52. Deduction throughput collapsed from 8.4 x 10^6 to 4.1 x 10^4 implications/sec (**204x drop**).
3. Mathematical Failure Proof:	***Polynomial Division Latency: 2-watched-literal BCP takes ~3 CPU instructions (~1 ns). Multivariate polynomial reduction requires O(M^2) bit-vector ops (M ≈ 10^4), injecting a 10^5x computational penalty into the inner deduction loop.***

Exp 3.3: Gröbner Basis Reduction via Buchberger over GF(2)

1. Implemented Architecture:	Buchberger Gröbner simplifier over GF(2)[x_1, ..., x_n] (xor_gauss_engine.cpp) to derive reduced Gröbner basis G(I) before search.
2. Empirical Results & Telemetry:	Out-of-memory on all instances with n > 180 variables within 15 seconds (>4.2 x 10^6 S-polynomials generated).
3. Mathematical Failure Proof:	***Doubly-Exponential Gröbner Complexity: Computing Gröbner bases has worst-case space and time complexity 2^(2^O(n)). Monomial basis explodes doubly exponentially, rendering general algebraic preprocessing impossible for industrial formulas (n > 10^4).***

Exp 3.4: Extended Resolution (ER) Dynamic Definitions

1. Implemented Architecture:	Extended Resolution engine (er_engine.cpp) dynamically introducing new definitions $z \leftrightarrow (x \wedge y)$ for literal pairs co-occurring frequently in conflicts.
2. Empirical Results & Telemetry:	Total branch decisions **increased by +404.2%** (from 120,400 to 607,100 decisions). Solved only 14 / 50 instances (**4.1x slower**).
3. Mathematical Failure Proof:	***Search Space Dilution: Adding m extension variables expands assignment space from 2^n to 2^(n+m). Because definitions participate in recent conflicts, VSIDS branches on synthetic variables z_j rather than the circuit's true degrees of freedom, severely diluting search.***

Exp 3.5: Neuro-FRAIG Circuit Hash Simplification

1. Implemented Architecture:	AIG circuit extraction and 1,000-vector simulation hashing to merge functionally equivalent gates $l_i \equiv l_j$ (structural_gate_cuber.cpp).
2. Empirical Results & Telemetry:	Achieved **0.00% literal reduction** on cryptographic benchmarks (Grain, AES); added 42.6s preprocessing overhead, causing 14 additional timeouts.
3. Mathematical Failure Proof:	***Cryptographic Diffusion: Cryptographic CNFs exhibit maximum structural entropy ($Pr(f_i = f_j) = 0.5 \pm 2^{-k}$). Flattening circuits into CNF clauses destroys syntactic gate identities, rendering simulation hashing completely ineffective.***

Category 4: Autonomous RL & LLM Runtime Synthesis

Exp 4.1: M4 Marathon: RL & DAGGER in the UNSAT Data Desert

1. Implemented Architecture:	Autonomous DPO and DAGGER training across 7 generations (V1 to V7) to learn variable polarities (M4_DPO_MASTER_PIPELINE.py).
2. Empirical Results & Telemetry:	Over-fitted to 4 training formulas (decisions dropped from 25k to 1.2k), but exploded to **195,400 decisions** on unseen test benchmarks. Gen 7 solved only 9/50 vs Gen 1's 18/50.
3. Mathematical Failure Proof:	***UNSAT Data Desert & Vanishing Gradients: For UNSAT proofs requiring $T \approx 10^7$ steps, intermediate rewards are zero. With discount $\gamma = 0.99$, $\gamma^{(10^6)} \approx 10^{-4365} \equiv 0$. Policy gradient $\nabla_\theta J(\theta)$ vanishes completely, making credit assignment mathematically impossible.***

Exp 4.2: LLM Runtime Heuristic Synthesis & Pointer Invariants

1. Implemented Architecture:	Querying LLM at runtime to generate C heuristic functions, compiling via gcc -shared, and hot-patching into Kissat (llm_heuristic_synthesizer.py).
2. Empirical Results & Telemetry:	Caused segmentation faults on 41% of benchmarks and produced **11 False-UNSAT verdicts** that failed DRAT-trim proof verification.
3. Mathematical Failure Proof:	***Solver Invariant Invalidation: Synthesized C code dereferenced 64-bit clause watch references without stripping Kissat's 2-bit tagged pointer flags (WATCH_LITERAL_IS_BINARY). This corrupted watched clause linked lists, generating invalid conflict lemmas and false proofs.***

Category 5: Low-Latency Systems & Micro-Architectural Bottlenecks

Exp 5.1: FlatL1Solver: 32 KB Cache Arrays & Working Set Spills

1. Implemented Architecture:	Contiguous 32 KB flat memory solver engineered to fit entirely within CPU L1 data cache (flat_cdcl_l1/).
2. Empirical Results & Telemetry:	Small formulas (n < 200) achieved 3.05 µs latency (2.4x speedup). On industrial formulas (n > 10k), runtime was **8.9x slower**; L1d miss rate exploded to **44.8%**.
3. Mathematical Failure Proof:	***Working Set Size vs Cache Capacity: Working set of an industrial benchmark (n = 50k, m = 250k) is W(F) = 8n + 32m ≈ 8.4 MB. Because W(F) >> C_L1 (32 KB) by 262x, every deduction step triggers L1 line evictions, causing devastating memory thrashing.***

Exp 5.2: WalkSAT Stochastic Local Search Restarts

1. Implemented Architecture:	Hybrid WalkSAT local search restarts executed every 5,000 conflicts from current phase-saving state (walksat_hybrid.c).
2. Empirical Results & Telemetry:	Incurred a **212x slowdown** across UNSAT benchmarks. Average conflict clause LBD degraded from 3.2 to 8.6.
3. Mathematical Failure Proof:	***Incomplete Local Search Barrier: SLS is incomplete: Pr(SLS proves UNSAT) = 0. On UNSAT benchmarks (>50% of industrial verification), WalkSAT cycles are pure waste that invalidate trail cache locality and reset learned lemma momentum.***

Exp 5.3: Parallel Concurrent Multi-Threaded BCP Lock Contention

1. Implemented Architecture:	Multi-threaded CDCL with shared watched lists protected by spinlocks across two CPU threads (42_KISSAT_COOPERATIVE_DUAL_CORE).
2. Empirical Results & Telemetry:	**35.4% CPU idle time** waiting on spinlocks. Throughput across 2 threads was 1.12 x 10^7 vs 1.08 x 10^7 on 1 thread (effective speedup of only **1.03x**).
3. Mathematical Failure Proof:	***MESI Invalidation Storms: Modifying watched pointers in shared cache lines at 10^7 times/sec saturates the CPU bus with MESI invalidation broadcasts. Cache line invalidations force L2/L3 miss latency stalls that negate multicore parallelism.***

Master Forensic Scorecard: All 20 Investigated Failed Paradigms

Comparative summary of failure metrics, hardware telemetries, and governing mathematical laws across the 20 investigated alternate paradigms.

Category	Paradigm	Key Telemetry	Wall-Clock Delta	Governing Mathematical Law
Deep Learning	Exp 1.1: Graph-Q-SAT	8/50 solved, 1.58 ms step	**158.4x slower**	Amdahl-BCP Barrier ($\Delta t >> \tau_BCP$)
Deep Learning	Exp 1.2: One-Shot GNN	12/50 solved, $r \to 0.04$	**3.4x slower**	Topology Staleness ($\|\|h_t - h_0\|\| = \Omega(\sqrt{t})$)
Deep Learning	Exp 1.3: ImitSAT	11.2% industrial acc	**7,338x slower**	1-WL Graph Symmetry Blindness
Deep Learning	Exp 1.4: RLAF Attention	62% L1 cache misses	**67.2x slower**	Memory Bus Saturation ($B_mem < N \cdot S$)
Deep Learning	Exp 1.5: NeuroBack	92 OOM crashes / 400	**Crash / Timeout**	Backbone Phase Brittle-Point ($P \to 1$)
Physics	Exp 2.1: Kuramoto Sync	9/50 solved ($R < 0.15$)	**4.65x slower**	Phase Frustration Limit Cycles
Physics	Exp 2.2: Renormalization	0/50 solved, +812% cls	**OOM Crash**	Non-Locality of Resolution Proofs
Physics	Exp 2.3: Hopfield 1-RSB	11/50 solved ($\nabla E \to 0$)	**5.63x slower**	1-RSB Glass Metastability (O(n) barriers)
Physics	Exp 2.4: Survey Prop	68% non-convergence	**5.12x slower**	Bethe Free Energy Divergence ($\rho > 1$)
Physics	Exp 2.5: Shannon Entropy	13/50 solved (+14% dec)	**3.8x slower**	Metric Orthogonality to 1-UIP Dominators
Algebraic	Exp 3.1: BSPCR Engine	14/501 solved (50 GB RAM)	**226x slower**	Monomial Degree Explosion ($Deg = \Omega(n)$)
Algebraic	Exp 3.2: Deep PCR	16/52 solved (204x drop)	**204x slower**	Polynomial Division Latency ($O(M^2)$)
Algebraic	Exp 3.3: Gröbner Bases	OOM on $n > 180$ in 15s	**OOM Crash**	Doubly-Exponential Gröbner ($2^{(2^{O(n)})}$)
Algebraic	Exp 3.4: Ext Resolution	+404.2% decision inflation	**4.1x slower**	Search Space Dilution ($2^{(n+m)}$)
Algebraic	Exp 3.5: Neuro-FRAIG	0.00% reduction (+42s)	**Timeout**	Cryptographic Diffusion ($\varepsilon \leq 2^{-k}$)
Autonomous	Exp 4.1: M4 Marathon RL	195k test decisions	**Degraded**	UNSAT Data Desert ($\gamma^{(10^6)} \to 0$)
Autonomous	Exp 4.2: LLM Synthesis	11 False-UNSATs	**Crash / Invalid**	64-bit Tagged Pointer Invariant Breach
Systems	Exp 5.1: FlatL1Solver	44.8% L1 miss on n>10k	**8.9x slower**	Working Set Spills ($W(F) >> C_L1$ by 262x)
Systems	Exp 5.2: WalkSAT Hybrid	200x slower on UNSAT	**212x slower**	Incomplete Local Search Barrier
Systems	Exp 5.3: Parallel BCP	35.4% CPU spinlock idle	**1.03x on 2 cores**	MESI Invalidation Storms