Sample Execution Traces

Conference Paper Review System

Note: these runs use `local_tester/driver.h`. `local_test8a/8b` replay them, so your output must match character for character. Each scenario runs in a fresh process, so paper IDs start at 1.

Scenario 1: Normal workflow

Input	Output	Why
`0 Rita`	`0 OK`	
`0 Sam`	`0 OK`	
`1 GraphNets Alice`	`1 GraphNets: Alice 0.00 In progress` `1 OK`	new paper gets ID 1, status In progress
`1 QuantumWalks Bob`	`2 QuantumWalks: Bob 0.00 In progress` `1 OK`	ID 2
`2 1 Carol`	`1 GraphNets: Alice Carol 0.00 In progress` `2 OK`	Carol added while still In progress
`3 1`	`3 OK`	
`3 2`	`3 OK`	
`4 1 Rita`	`4 OK`	paper 1 → Under review
`4 1 Sam`	`4 OK`	second reviewer for paper 1
`4 2 Rita`	`4 OK`	paper 2 → Under review
`5 Rita 1 8`	`5 OK`	
`5 Sam 1 7`	`5 OK`	paper 1 avg = 7.5
`5 Rita 2 5`	`5 OK`	paper 2 avg = 5.0
`6`	`6 OK`	1 Accepted, 2 Rejected

`7`	`Rita`
	`Sam`
	`2 QuantumWalks: Bob 5.00 Rejected`
	`1 GraphNets: Alice Carol 7.50 Accepted`
	`7 OK`
		reviewers in order, papers newest first

`9`	`9 OK`	unknown command: print and stop

Scenario 2: Error handling

Every `NOK` line shows what was thrown, then the command number. A failed command changes nothing.

Input	Output	Why
`0 Rita`	`0 OK`	
`0 Rita`	`Rita 0 NOK`	duplicate name: invalid_argument("Rita")
`1 Optics Alice`	`1 Optics: Alice 0.00 In progress` `1 OK`	
`3 1`	`3 OK`	
`2 1 Bob`	`1 2 NOK`	paper 1 is Submitted: frozen, throws 1
`4 1 Alice`	`Alice 4 NOK`	check 2: no reviewer Alice yet
`0 Alice`	`0 OK`	
`4 1 Alice`	`1 4 NOK`	check 4: Alice is an author of paper 1

Input	Output	Why
`4 5 Rita`	`5 4 NOK`	check 1: no paper 5
`5 Rita 1 8`	`1 5 NOK`	not assigned to Rita, throws 1
`4 1 Rita`	`4 OK`	
`5 Rita 1 11`	`11 5 NOK`	check 1 (score) beats everything: throws 11
`5 Zed 1 8`	`Zed 5 NOK`	findReviewer throws invalid_argument("Zed")
`5 Rita 1 6`	`5 OK`	paper 1 now has one score (6)
`1 Lasers Bob`	`2 Lasers: Bob 0.00 In progress` `1 OK`	new paper gets ID 2
`5 Rita 2 9`	`2 5 NOK`	score valid, but paper 2 not assigned: throws 2
`6`	`6 OK`	paper 1: avg 6.0 → Rejected; paper 2 untouched
`3 1`	`1 3 NOK`	status Rejected, not In progress

`7`	`Rita`
	`Alice`
	`2 Lasers: Bob 0.00 In progress`
	`1 Optics: Alice 6.00 Rejected`
	`7 OK`	

`8`	`8 OK`	

Raw files (for copy-paste)

sample1.in

```
0 Rita
0 Sam
1 GraphNets Alice
1 QuantumWalks Bob
2 1 Carol
3 1
3 2
4 1 Rita
4 1 Sam
4 2 Rita
5 Rita 1 8
5 Sam 1 7
5 Rita 2 5
6
7
9
```

expected output

```
0 OK
0 OK
1 GraphNets: Alice 0.00 In progress
1 OK
2 QuantumWalks: Bob 0.00 In progress
1 OK
1 GraphNets: Alice Carol 0.00 In progress
2 OK
3 OK
3 OK
4 OK
4 OK
4 OK
5 OK
5 OK
5 OK
6 OK
Rita
Sam
2 QuantumWalks: Bob 5.00 Rejected
1 GraphNets: Alice Carol 7.50 Accepted
7 OK
9 OK
```

sample2.in

```
0 Rita
0 Rita
1 Optics Alice
3 1
2 1 Bob
4 1 Alice
0 Alice
4 1 Alice
4 5 Rita
5 Rita 1 8
4 1 Rita
5 Rita 1 11
5 Zed 1 8
5 Rita 1 6
1 Lasers Bob
5 Rita 2 9
6
3 1
7
8
```

expected output

```
0 OK
Rita 0 NOK
1 Optics: Alice 0.00 In progress
1 OK
3 OK
1 2 NOK
Alice 4 NOK
0 OK
1 4 NOK
5 4 NOK
1 5 NOK
4 OK
11 5 NOK
Zed 5 NOK
5 OK
2 Lasers: Bob 0.00 In progress
1 OK
2 5 NOK
6 OK
1 3 NOK
Rita
Alice
2 Lasers: Bob 0.00 In progress
1 Optics: Alice 6.00 Rejected
7 OK
8 OK
```