

# Exploring the Energy Consumption of Highly Parallel Software on Windows

Mads Hjuler Kusk\*, Jeppe Jon Holt\*  
and Jamie Baldwin Pedersen\*

Department of Computer Science, Aalborg University, Denmark  
\*{mkusk18, jholt18, jjbp18}@student.aau.dk

April 14, 2023

## Abstract

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

- RQ2: What are the advantages and drawbacks of the different types of measuring instruments in terms of accuracy, ease of use, and cost?
- RQ3: What effect does parallelism have on the energy consumption of the test cases?
- RQ4: What effect do P- and E-cores have on the parallel execution of a process, compared to a traditional desktop CPU?

To answer these research questions a command line framework is created to assist with running a series of different experiments.

## 1 Introduction

In recent years there has been rapid growth in Information and Communications Technology (ICT) which has led to an increase in energy consumption. Furthermore, it is expected that the rapid growth of ICT will continue in the future. [jones2018stop, andrae2015global] As the use of ICT rises the demand for computational power rises as well, therefore energy efficiency has or perhaps should become more of a concern for companies and software developers alike.

In this paper, we investigate energy consumption of various C++ test cases using different measuring instruments on Windows 11, comparing the efficiency and tradeoffs between sequential and parallel execution. Our experiments involve two Device Under Tests (DUTs): an Intel Coffee Lake CPU with a traditional P-core setup and an Intel Raptor Lake CPU with P- and E-cores. We analyze the impact of Asymmetric Multicore Processors (AMPs) on parallel execution compared to traditional Symmetric MultiCore Processors.

- RQ1: How does the compiler used to compile the test cases impact the energy consumption?

In Section 2 the related work which lay the foundation for our work is covered, including our previous work. This is followed by Section 3 which includes the necessary background information about e.g. CPUs and schedulers. Thereafter in Section 4 our experimental setup is presented. In Section 6 the results are presented whereafter they are discussed in Section 7 and finally a conclusion is made in Section 8.

## 2 Related Work

This section provides an overview of related work in energy consumption, parallel software, compilers, and asymmetric multicore processors. It also builds upon our previous work in comparing measuring instruments.

### 2.1 Previous Work

In our previous work “A Comparison Study of Measuring Instruments” [biksbois] where different measuring instruments were compared to explore whether a viable software-based measuring instrument was available for Windows. It was found that Intel Power Gadget (IPG) and Libre Hardware Monitor (LHM) on Windows have similar correlation to hardware-based

measuring instruments as Intel's Running Average Power Limit (RAPL) has on Linux. The remainder of this chapter builds upon the related work chapter in [biksbois] and as such will not be repeated, however, it will be expanded upon.

## 2.2 Parallel Software

Amdahl's law describes the maximum potential speedup that can be achieved through the parallelization of an algorithm based on the proportion of the algorithm that can be parallelized and the number of cores used.[amdahl1967validity] In [woo2008extending] Amdahl's law, was extended to also estimate the energy consumption. Then three different many-core designs were compared with different amounts of cores using the extended Amdahl's law. The comparison showed that a CPU can lose its energy efficiency as the number of cores increases and it was argued that knowing how parallelizable a program is before execution allows for calculating the optimal number of active cores for maximizing performance and energy consumption. However, the comparison was based on an analytical model and not real measurements.[woo2008extending]

[prinslow2011overview] presented a program that solves Laplace equations and compares the observed speedup for computing the Laplace equations with one, two, and four cores, with estimates given by Amdahl's law and Gustafson's law. Gustafson's law evaluates the speedup of a parallel program based on the size of the problem and the number of cores. Unlike Amdahl's law which assumes a fixed problem size and a fixed proportion of the program that can be parallelized, Gustafson's law takes into account that larger problems can be solved when more cores are available and that the parallelization of a program can scale with the problem size. Comparing the observed speedup and the estimates it was clear that Gustafson's law is more optimistic than Amdahl's law, however, both estimate smaller speedups than the observed speedup on two and four cores.[prinslow2011overview]

In [Pinto2014], three different thread management constructs from Java were explored and analyzed regarding energy consumption. It was found that as the number of threads increased, energy consumption would do the same. However, this was only up to a certain point, after which energy consumption would start to decrease as the number of threads approached the number of cores in the CPU. The peak of this energy consumption was application-dependent. The study also found that in eight out of nine benchmarks, there was a decrease in execution time when transitioning from sequential execution on one thread to using multiple threads. It should be noted, though, that four of their benchmarks were embarrassingly

parallel, while only one was embarrassingly serial. Moreover, decreased execution time does not necessarily imply decreased energy consumption, because in six out of nine benchmarks, the lowest energy consumption was found in the sequential version using one thread. Furthermore, the study investigated the energy-performance trade-off using the Energy-Delay-Product (EDP), which is the product of energy consumption and execution time. Using EDP, the study generally found parallel execution to be more favorable; however, depending on the benchmark, increasing the number of threads might not result in an improvement in EDP.[Pinto2014]

In [abdelhafez2019], the energy consumption for sequential and parallel genetic algorithms was explored, where one research question aimed to explore the impact on energy consumption when using different numbers of cores. It found that a larger number of cores in the execution pool results in a lower running time and energy consumption, and conclude that parallelism can help reduce energy consumption. Parallelism's ability to reduce energy consumption was argued to be due to the large number of cores working to solve the problem simultaneously, where the combination of more cores, and more parallel operations per time unit will require less energy. When considering parallel software, it also found asynchronous implementations to use less energy, because there are no idle cores waiting for data in asynchronous implementations, while in synchronous implementations cores can be blocked during runtime, while waiting for responses from other cores.

In [Lindholt2022], the behavior of parallel applications and the relationship between execution time and energy consumption are explored. It tests four different language constructs which can be used to implement parallelism in C#. Furthermore, it uses varying amounts of threads and a sample of micro- and macro-benchmarks. It found that workload size has a large influence on running time and energy efficiency and that a certain limit must be reached before improvements can be observed when changing a sequential program into a parallel one. Additionally, it was found that execution time and energy consumption of parallel benchmarks do not always correlate. Comparing micro- and macro-benchmarks the findings remain consistent, although the impact becomes low for the macrobenchmarks due to an overall larger energy consumption. Furthermore, it has included some recommendations, which should be considered:[Lindholt2022]

- Shield cores: Avoid unintended threads running on the cores used in the benchmarking
- PowerUp: Can be used to ensure that benchmark is not optimized away during compilation

- Static clock: Make the clock rate of the CPU as static as possible
- Interrupt request: Avoid interrupt requests being sent to cores used in the benchmarking
- Turn off CPU turbo boost
- Turn off hyperthreading

## 2.3 Compilers

In [hassan2017], the C++ language and different compilers were explored and compared to determine the impact of using various coding styles and compilers, with the goal of finding a balance between performance and energy efficiency. The different coding styles introduced examined the impact of splitting CPU and IO operations and interrupting CPU-intensive instructions with sleep statements. The C++ compilers used in [hassan2017] included MinGW GCC, Cygwin GCC, Borland C++, and Visual C++, and the energy measurements were performed using Windows Performance Analyzer (WPA). All compilers were used with default settings, and no optimizations were chosen. This decision was based on works like [lima2013], where it was found that mainstream compilers apply multiple optimizations to the final code, which in the worst case may result in worse performance and increased energy consumption. The issue of optimizations being highly machine-dependent was also demonstrated in [cooper2004], where analysis and optimizations were conducted on a Texas Instruments C6200 DSP CPU. In [cooper2004], it was discovered that a significant portion of the energy was used by fetching instructions, which was addressed by introducing a fetch packet mechanism. The study also found loop-unrolling to reduce energy consumption. While these optimizations decreased energy consumption for the Texas Instruments C6200 DSP CPU, the authors noted that varying results were expected for other CPUs. A similar conclusion was also reached in [hassan2017], where it was found that when choosing a compiler and coding style, energy reduction depends on the nature of the target machine and application. Based on the test case used, which involved an election sort algorithm, the best performance was achieved with the Borland compiler, and the lowest energy consumption was observed with the Visual C++ compiler. When considering the coding styles, the study found that both separating IO and CPU operations and interrupting CPU-intensive instructions with sleep statements also decreased energy consumption.

## 2.4 Asymmetric Multicore Processors

AMPs are CPUs in which not all cores are treated equally. One example of this is the combination of performance cores and efficiency cores, as seen in

Intel's Alder Lake and Raptor Lake. Intel's Thread Director (ITD) was introduced alongside Intel's Alder Lake. The purpose of ITD is to assist the operating system in deciding on which cores to run a thread. In [saez2022evaluation], support for utilizing ITD in Linux was developed, although official support for ITD has since been released. Additionally, some SPEC benchmarks were conducted to analyze the estimated Speedup Factor (SF) from the ITD compared to the observed SF. SF is the relative benefit a thread receives from running on a P-core. The study examined which classes were assigned to different threads in the benchmark and found that 99.9% of class readings were class 0 or 1. Class 0 is for threads that perform similarly on P- and E-cores, while Class 1 is for threads where P-cores are preferred. [Intel202?whitepaper] Furthermore, class 3, which is for threads that are preferred to be on an E-core, was not used. The experiment indicated that the ITD overestimated the SF of using the P-cores for many threads but also underestimated it for some threads. Overall, it was found that the estimated SF had a low correlation coefficient ( $< 0.1$ ) with the observed values. Furthermore, a performance monitoring counter (PMC) based prediction model was trained. The model outperformed ITD, but it still produced some errors. However, the correlation coefficient was higher at ( $> 0.8$ ). The study then implemented support for the IDT in different Linux scheduling algorithms and compared the results from using the IDT and the PMC-based model. It found that the PMC-based model provided superior SF predictions compared to ITD. [saez2022evaluation]

# 3 Background

## 3.1 CPU States

This section provides an overview of CPU-states. The concept of CPU-states is concerned with how a system manages its energy consumption during different operational conditions. The C-states are a crucial aspect of CPU-states, as they dictate the extent to which a system shuts down various components of the CPU to conserve energy. The C0 state represents the normal operation of a computer under load. [Intel, CHard] As the system moves from C0 to C10 [biksbois], progressively more components of the CPU are shut down until, in C10, the CPU is almost inactive. It is important to note that the number of C-states supported may vary depending on the CPU and motherboard in use, in [biksbois] the workstation used supported from C0 to C10 states.

In our work the C-states can have a large impact on the energy consumption of the test cases, especially the idle case as was found in [biksbois].

### 3.2 Performance and Efficiency cores

For the CPU architecture x86, the core layout has comprised of identical cores. However, the ARM architecture introduced the big.LITTLE layout in 2011[ARM2011origin]. It is an architecture that utilizes two types of cores, a set for maximum energy efficiency and a set for maximum computer performance.[ARMWhatIsIt]. Intel introduced a hybrid architecture in 2021[Intel2021Alder] codenamed Alder lake, which is similar to ARM's big.LITTLE architecture. Alder lake also has two types of cores: performance cores (P-cores) and efficiency cores (E-cores). These types of cores are optimized for different tasks, where P-cores are standard CPU cores focusing on maximizing performance. In contrast, the E-cores are designed to maximize performance per watt and are intended to handle smaller non-time critical jobs, such as background services[rotem2022intel].

### 3.3 CPU Affinity

Affinity is a feature in operating systems(OSs) that enables processes to be bound to specific cores in a multi-core processor. In OSs, jobs and threads are constantly rescheduled for optimal system performance, which means that the same process can be assigned to different cores of the CPU. Processor affinity allows applications to bind or unbind a process to a specific set of cores or range of cores/CPU(s). When a process is pinned to a core, the OS ensures it only executes on the assigned core(s) or CPU(s) each time it is scheduled.[affinity]

```
1 void ExecuteWithAffinity(string path)
2 {
3     var process = new Process();
4     process.StartInfo.FileName = path
5     process.Start();
6
7     // Set affinity for the process
8     process.ProcessorAffinity =
9         new IntPtr(0b0000_0011)
10 }
```

**Listing 1:** An example of how to set affinity for a process in C#

Processor affinity is particularly useful for scaling performance on multi-core processor architectures that share the same global memory and have local caches referred to as the Uniform memory access architecture. Processor affinity is also useful for out-of-the-box study, as this allows the framework to assign a single thread or a set of cores and threads to a process.[affinity]

When setting the affinity for a process in C#, it is done through a bitmask, where each bit represents a CPU core. An example of how it is done in C# can be seen in Listing 1, where the process is allowed to execute on core #0 and #1.

### 3.4 Scheduling Priority

Scheduling threads on Windows, is done based on each thread's scheduling priority level and the priority class of the process. For the priority the value can be either IDLE, BELOW NORMAL, NORMAL, ABOVE NORMAL, HIGH or REALTIME, where the default is NORMAL. It is noted that HIGH priority should be used with care, as other threads in the system will not get any processor time while that process is running. If a process needs HIGH priority, it is recommended to raise the priority class temporarily. The REALTIME priority class should only be used for applications that "talk" to hardware directly, as this class will interrupt threads managing mouse input, keyboard inputs, etc.[priority]

For the priority level, the levels can be either IDLE, LOWEST, BELOW NORMAL, NORMAL, ABOVE NORMAL, HIGHEST and TIME CRITICAL, where the default is NORMAL. A typical strategy is to increase the level of the input threads for applications to ensure they are responsive, and to decrease the level for background processes, meaning they can be interrupted as needed.[priority]

The scheduling priority is assigned to each thread as a value from zero to 31, where this value is called the base priority. The base priority is decided using both the thread priority level and the priority class, where a table showing the scheduling priority given these two parameter can be found in [priority]. When assigning a base priority where both the priority class and thread priority are the default values, e.i.NORMAL, the base priority is 8.[priority]

The idea of having different priorities is to treat threads with the same priority equally, by assigning time slices to each thread in a round-robin fashion, starting with the highest priority. In the case of none of the highest priority threads being ready to run, the lower priority threads will be assigned time slices. The lower-priority threads will then execute until a higher-priority thread is available, in which case the system will assign a full time slice to the thread, and stop executing the lower-priority threads, without time to finish using its time slice.[priority]

```
void ExecuteWithPriority(string path)
{
    var process = new Process();
    process.StartInfo.FileName = path
    process.Start();

    // Set priority class for process
    process.PriorityClass =
        ProcessPriorityClass.High;

    // Set priority level for threads
    foreach (var t in process.Threads)
    {
        thread.PriorityLevel =
            ThreadPriorityLevel.Highest;
    }
}
```

```

16 }
17 }

```

**Listing 2:** An example of how to set priorities for a process in C#

Note when setting priority class and priority level for a process through C#, the priority class is supported for both Windows and Linux, while the priority level is only supported for Windows. An example of how both the priority class and priority level can be set for a process and its threads can be seen in Listing 2.

### 3.5 OpenMP

OpenMP (Open Multi-Processing) is a parallel programming API consisting of a set of compiler directives and runtime library routines, with support for multiple platforms like Linux, macOS, and Windows as well as multiple compilers like GCC, LLVM/Clan, and Intel's OpenApi. OpenMP allows programmers to write parallel code for multi-core CPUs and GPUs.[[openmp](#)]

The directives provide a way to specify parallelism among multiple threads of execution within a single program, while the library provides mechanisms for managing threads and data synchronization. When using OpenMP programmers can write parallel codes and take advantage of multiple processors without having to deal with low-level details.[[openmp](#)]

When executing using OpenMP, the parallel mode used is called the Fork-Join Execution Model. This model works by first executing the program with a single thread, called the master thread. This thread is executed serially until parallel regions are encountered, in which case a thread group is created, consisting of the master thread, and additional worker threads. This process is called a fork. After splitting up, each thread will execute until an implicit barrier at the end of the parallel region. When all threads have reached this barrier, only the master thread continues.[[openmp](#)]

```

1 #pragma omp directive-name [
2     clause[ [,] clause]...
3 ]

```

**Listing 3:** The basic format of OpenMP directive in C/C++

When using OpenMP, the parallel regions are identified using a series of directives and clauses, where the basic format can be seen in Listing 3. By default, the parallel regions are executed using the number of present threads in the system, but this can also be specified using `num_threads(x)`, where `x` represents the number of threads.[[openmp](#)]

## 4 Experimental Setup

### 4.1 Measuring Instruments

This section present the different measuring instruments utilized in our work. The measuring instruments utilized in our previous work will only be briefly introduced, however more detail can be found in [[biksbois](#)]. In this paper, four software-based measuring instruments and two hardware-based measuring instrument were used, one of the latter was used as our ground truth.

**Intel's Running Average Power Limit (RAPL):** is in the literature a commonly used software-based measuring instrument.[[biksbois](#)] It uses model-specific registers (MSRs) and Hardware performance counters to calculate how much energy the processor uses. The MSRs RAPL uses include `MSR_PKG_ENERGY_STATUS`, `MSR_DRAM_ENERGY_STATUS`, `MSR_PP0_ENERGY_STATUS` and `MSR_PP1_ENERGY_STATUS`. Which corresponds to the power domains, PKG, DRAM, PP0, and PP1 which are explained in [[biksbois](#)]. RAPL has previously only been directly accessible on Linux and Mac. In [[biksbois](#)] we found that RAPL had a high correlation of 0.81 with our ground truth on Linux.[[biksbois](#)]

**Intel Power Gadget (IPG):** is a software tool created by Intel, which can estimate the power of Intel processors. It contains a command line version called Powerlog which allows accessing the energy consumption using callable APIs. It uses the same hardware counters and MSRs as RAPL[[FireFox](#)], therefore it is expected to observe similar measurements to that of RAPL. Which is also shown in [[biksbois](#)] where we found that IPG had a high correlation of 0.78 with our ground truth on Windows. We also found that IPG had a high correlation of 0.83 with RAPL, although the measurements is on different operating systems.[[biksbois](#)]

**Libre Hardware Monitor (LHM):** is a fork of Open Hardware Monitor, where the difference is that LHM does not have a UI.[[LHM](#)] Both projects are open source. LHM can use the same hardware counters and MSRs as RAPL and IPG and as such can measure the power domains PKG, DRAM, PP0, and PP1. Since it uses the methods to read energy consumption, a similar measurement is expected between LHM and IPG. We found that LHM correlated 0.76 with our ground truth on Windows. LHM was also found to have a high correlation of 0.85 with IPG.[[biksbois](#)]

**MN60 AC Current Clamp (Clamp):** Serves as our ground truth measurement. It is a setup comprised of an MN60 AC clamp that is connected to the phase of

the wire that goes into the PSU. It is also connected to an Analog Discovery 2 which is used as an oscilloscope which in turn is then connected to a Raspberry Pi 4. This setup allows us to continuously measure and log our data. The accuracy is reported to be 2% For more detail see [biksbois].

**CloudFree EU smart Plug (Plug):** is used, as a lower-priced hardware-based measuring instrument, which also has greater ease of use than the AC Current Clamp setup. We have not found any information about the accuracy or sampling rate of the plug.[CloudFreeEUSmartPlug]

**Scaphandre (SCAP):** is described as a monitoring agent that can measure energy consumption.[scaphandre] It is designed for Linux where it can use Powercap RAPL, a Linux kernel subsystem that reads data from RAPL. Additionally, SCAP can measure the energy consumption of some virtual machines, specifically Qemu and KVM hypervisors. A driver also exists for installing RAPL on Windows[RAPL·Windows]. This enables SCAP to be used on a Windows computer, where the sensor is RAPL, which utilizes the MSRs to update its counters.

The Windows version of SCAP has some limitations but can report the energy consumption of the power domain PKG using the MSR *MSR\_PKG\_ENERGY\_STATUS*. Moreover, it can estimate the energy consumption for individual processes. SCAP accomplishes this by storing CPU usage statistics alongside the energy counter values. It then calculates the ratio of CPU time for each Process ID (PID). Using the calculated ratio, SCAP determines the subset of energy consumption estimated to belong to a specific PID.

## 4.2 Dynamic Energy Consumption (DEC)

Dynamic Energy Consumption (DEC) was utilized in [fahad2019comparative, biksbois] to enable comparison between the software-based measuring instruments and the hardware-based measuring instruments, where the former measures energy consumption of the CPU only and the latter the entire DUT. DEC was also used in our work. A brief explanation of DEC based on [fahad2019comparative] is given:

$$E_D = E_T - (P_S * T_E) \quad (1)$$

In Equation (1)  $E_D$  is the DEC,  $E_T$  is the total energy consumption of the system,  $P_S$  is the energy consumption when the system is idle and  $T_E$  is the duration of the program execution. With this equation the energy consumption of the test case is isolated. Using DEC requires also measuring the energy consumption on an idle case. [fahad2019comparative]

## 4.3 Statistical Methods

In this sections the statistical method used to analyze our results are presented. This section is based on what was found in [biksbois] and can be referred to for further detail.

**Shapiro-Wilk Test:** was used to examine if the data followed a normal distribution, which is an important assumption for some statistical methods. Prior research suggested that our data won't be normally distributed [biksbois], therefore we expected our data to not be normally distributed, this was tested using the Shapiro-Wilk test. Understanding the distribution of the data helped choose subsequent statistical methods.[razali2011power]

**Mann-Whitney U Test:** To evaluate if there is a statistical significant difference between samples the Mann-Whitney U Test was used, because it is a non-parametric test that does not assume normality in the data.[mann1947test]

**Kendall's Tau Correlation Coefficient:** to assess the correlation between our measurements, Kendall's Tau correlation coefficient was used. This non-parametric measure of association was chosen because it can evaluate the strength and direction of relationships between ordinal variables, even when the underlying data does not adhere to a normal distribution.[han1987non] The correlation can be evaluated using the Guilford scale [guilford1950fundamental] as can be seen in Table 1.

Values	Label
< .20	Slight; almost negligible relationship
.20 – .40	Low correlation; definite but small relationship
.40 – .70	Moderate correlation; substantial relationship
.70 – .90	High Correlation; marked relationship
.90 – 1	Very high correlation; very dependable relationship

**Table 1:** The values for the scale presented by Guilford in [guilford1950fundamental]

**Cochran's Formula:** To determine an appropriate sample size for our measurements, Cochran's formula was used. With this formula a required sample size to achieve a desired level of statistical power can be calculated.[Cochran]

In summary, the selection of the Shapiro-Wilk test, Mann-Whitney U test, Kendall's Tau correlation coefficient, and Cochran's formula allowed us to effectively analyze our data, taking into account its non-normal distribution and ordinal nature while determining statistically significant differences, correlations, and an appropriate sample size for our measurements.



#### 4.4 Device Under Tests

Two workstations were used as DUTs in the experiments. These were chosen to enable comparison between CPUs with and without P- and E-cores. When the two DUTs were set up, they were updated to have the same version of Windows and Linux. In Tables 2 and 3 the specifications of the two workstations can be seen. They will be referred to as DUT 1 and DUT 2.

Workstation 1 (DUT 1)	
Processor:	Intel i9-9900K
Memory:	DDR4 16GB
Disk:	Samsung MZVLB512HAJQ
Motherboard:	ROG STRIX Z390 -F GAMING
PSU:	Corsair TX850M 80+ Gold
Ubuntu:	22.04.2 LTS
Linux kernel:	5.19.0-35-generic
Windows 11:	10.0.22621 Build 2262

**Table 2:** The specifications for DUT 1

Workstation 2 (DUT 2)	
Processor:	Intel i5-13400
Memory:	DDR4 32GB
Disk:	Kingston SNV2S2000G
Motherboard:	ASRock H610M-HVS
PSU:	Cougar GEX 80+ Gold
Ubuntu:	22.04.2 LTS
Linux kernel:	5.19.0-35-generic
Windows 11:	10.0.22621 Build 22621

**Table 3:** The specifications for DUT 2

When running the experiments, the recommendations presented in [Lindholt2022] were followed. These included that the WiFi, CPU turbo boost and hyperthreading was disabled. Lastly, the CPU was set to static, which was achieved by disabling the C-states in the bios.

#### 4.5 Compilers

This section introduces the various C++ compilers that were used in our study. Some of the chosen compilers were based on [hassan2017], which found that applications compiled by Microsoft Visual C++ and MinGW exhibited the lowest energy consumption. Additionally, the Intel OneAPI C++ compiler and Clang were included as both can be found on lists of the most popular C++ compilers[mycplus, educba, softwaretestinghelp].

<sup>1</sup><https://benchmarksgame-team.pages.debian.net/>

Microbenchmarks	
Name	Version
Clang	15.0.0
MinGW	12.2.0
Intel OneAPI C++	2023.0.0.20221201
MSVC	19.34.31942

**Table 4:** C++ Compilers

**Clang:** is an open source compiler that builds on the LLVM optimizer and code generator. It is available for both Windows and Linux[clang]

**Minimalist GNU for Windows (MinGW):** is an open-source project which provides tools for compiling code using the GCC toolchain on Windows. It includes a port of GCC. Additionally, MinGW can be cross-hosted on Linux.[mingw]

**Intel’s oneAPI C++ (oneAPI):** is a suite of libraries and tools aimed at simplifying development across different hardware. One of these tools is the C++ compiler, which implements SYCL, this being an evolution of C++ for heterogeneous computing. It is available for both Windows and Linux.[oneapi]

**Microsoft Visual C++ (MSVC):** comprises a set of libraries and tools designed to assist developers in building high-performance code. One of the included tools is a C++ compiler, which is only available for Windows[msvc].

#### 4.6 Test cases

Our work employed microbenchmarks and macrobenchmarks to assess the measuring instruments. This section outlines the selected test cases and the rationale behind their selection.

**Microbenchmarks:** are small, focused benchmarks that test a specific operation, algorithm or piece of code. They are useful for measuring the performance of some particular code precisely while minimizing the impact of other factors. However microbenchmarks may not provide an accurate representation of overall performance.[MicroVSMacro]

The first couple of experiments utilized microbenchmarks from the Computer Language Benchmark Game (CLBG)<sup>1</sup> as test cases. The selected test cases encompassed both single- and multi-threaded microbenchmarks. A challenge in choosing test cases involved ensuring compatibility with the chosen compilers, as well as with both Windows and Linux. Certain libraries, such as <sched.h>, were used in many implementations and was not available on Windows, which [benchmarksgame/index.html](https://benchmarksgame/index.html)

limited the pool of compatible microbenchmarks. The microbenchmarks were executed using the highest parameters specified in the CLBG as input for each test case. The chosen microbenchmark test cases and their abbreviation are presented in Table 5. During compilation, the only parameter given is `-openmp` for the multi-core test cases, ensuring optimization for all cores of the DUT.

Microbenchmarks		
Name	Parameter	Focus
NBody (NB)	$50 * 10^6$	single core
Spectra-Norm (SN)	5.500	single core
Mandelbrot (MB)	16.000	multi core
Fannkuch-Redux (FR)	12	multi core

Table 5: Microbenchmarks

**Macrobenchmarks:** are large-scale benchmarks that test the performance of an entire application or system. They provide a more comprehensive overview of how the system performs in real-world scenarios. Macrobenchmarks are more suitable for understanding the overall performance of an application or system rather than focusing on specific operations. [MicroVSMacro] Application-level benchmarks are benchmarks in a real-world application, which provides a more realistic test case. TBC

## 4.7 Background Processes

To limit background processes on Windows, a few steps were taken. When the DUTs were set up, all startup processes in the Task Manager on Windows were also disabled, in addition to non-Microsoft background services found in System Configuration. Exceptions were however made to processes related to Intel.

During runtime, different background processes were also stopped. These processes were found by looking at the running processes using command `Get-Process`. A list of processes was found which are killed using the `Stop-Process` command before running the experiments. The list can be found in Table 6.

Background Processes
Name
searchapp
runtimebroker
phoneexperiencehost
TextInputHost
SystemSettings
SkypeBackgroundHost
SkypeApp
Microsoft.Photos
GitHubDesktop
OneDrive
msedge
AsusDownloadLicense
AsusUpdateCheck

Table 6: Background Processes

## 5 Experiments

In the following section, the conducted experiments are described. All experiments carried out in this section will utilize the framework detailed in Appendix A, with the results stored in the database introduced in Appendix B. During the experiments, the `ProcessPriorityClass` for the measuring instrument, framework, and test cases was set to High, unless specified otherwise by the particular experiment.

### 5.1 Experiment One

The first experiment investigated RQ 1. This experiment employed both multi-core test cases presented in Section 4.6, and the measurements were performed using IPG. IPG was chosen based on its performance in [biksbois], where it was found to produce similar measurements to LHM. Since the objective of this experiment was to identify the most energy-efficient compiler, the expectation was that a similar conclusion would be made if multiple measuring instruments were used. This experiment was conducted on DUT 1.

**Initial Measurements:** As was presented in Section 4.3, Cochran’s formula was used to ensure confidence in the measurements made. The initial measurements were taken to gain insight into the number of measurements required before making additional measurements if required. The number chosen for the initial measurements was 30, as the central limit theorem suggests that a sample size of at least 30 is usually sufficient to ensure that the sampling distribution of the sample mean approximates normality, regardless of the underlying distribution of the population [central-limit-theorem]. In this experiment, the process’ priority class for the framework,




the test case, and the measuring instrument were set to HIGH.

After 30 measurements, the results from Cochran's formula can be seen in Table 7, where it was evident that the required samples varied between compilers and test cases. When the test cases were analyzed it was found that MB deviates less than FR, with MB requiring as little as 3 samples with MinGW, while FR requires up to 62,086 samples with Clang. Given these results, more measurements were necessary. When the compilers were analyzed interestingly oneAPI had the lowest energy consumption for FR, but the highest for MB. oneAPI also displayed the lowest energy consumption. As a result, 550 additional measurements were conducted for the next step.

Initial Measurements		
Name	Fannkuch Redux	Mandelbrot
Clang	61.086	40
MinGW	1.644	3
oneAPI	550	222
MSVC	2.994	10

**Table 7:** The required samples to gain confidence in the measurements made by IPG on Windows

**Results:** After 550 measurements were obtained, the reported values by Cochran's formula still indicated that MSVC, MinGW, and Clang needed more measurements. Between the different compilers, Clang stands out where 61.086 measurements are required. Because this number is so much higher than other compilers, additional measurements were taken using this compiler. After 10.000 measurements, Cochran's formula now indicated that 1.289 measurements were required, which is more in line with other compilers.




**Figure 1:** CPU measurements by IPG on DUT 1 for test case(s) FR

When looking at the results for FR in Figures 1 and 2, and for MB in Appendix C, oneAPI had the lowest DEC and total energy consumption for both test cases. Clang deviated the most in Figure 2.

In the first experiment, it was concluded that the different compilers have a huge impact on the energy consumption but also how many measurements were required to be confident in the results. In the end, oneAPI had the lowest energy consumption and was used in the remaining experiments, unless otherwise specified.

The dynamic energy consumption of the CPU



**Figure 2:** CPU measurements by IPG on DUT 1 for test case(s) FR


## 5.2 Experiment Two

The second experiment investigated RQ 2, in order to identify our preferred measuring instrument on Windows. The measuring instrument was chosen based on a combination of different factors, including its correlation with our ground truth, ease of use and cost.

A couple of changes were made in the experimental setup for experiment two. Firstly, due to some issues with SCAP, where its sampling rate significantly decreased when the DUT was under full load, the process priority class of the test case was set to Normal. Secondly, due to an execution time of less than a second for MB when compiled with Intel's oneAPI, MB's input parameter was changed from 16.000 to 64.000 which increased the duration of the test case execution time to ~ 14 seconds. This avoided a scenario where the Plug only had a single data point per measurement. For this experiment, FR was executed 550 times, while MB was executed 222 times, based on Table 7.


**Initial Measurements:** When analyzing how many measurements is required when applying Cochran's to the results can be seen in Appendix E. The Clamp requires significantly more measurements in this case compared to other measuring instruments, which is why a more in depth analysis was conducted. In Figure 3 boxplots showing the evolution measurements can be seen when executing 100 – 1000 measurements. The median decreased by 3.38% from 100 measurements to 1000 measurements, and by 1.03% between 900 and 1000 measurements. A pattern can be observed, where the median decreased as more measure-

ments are made. Another pattern that can be observed is how the whisker increase in width as more measurement are taken. It can also be observed that the data is left skewed. However as more measurements are conducted the distribution evolves towards a more symmetric distribution. Due to the excessive time required to run the experiments, we have capped the maximum amount of measurement at 1000.




**Figure 3:** A visual representation of how the energy measurements evolve as more measurements are made by clamp WIN on DUT 2 for test case MB

**Results:** When analyzing the results, it will be done for DUT 1 using barcharts as the deviation in the results is limited, where boxplots for boths dut's can be found in Appendix D.



When applying statistical methods from Section 4.3, it was discovered that some of the data did not follow a normal distribution and were significantly different from eachother, previous studies

[biksbois, Koedijk2022diff] have had simliar results. Thus, Kendalls Tau Correlation Coefficient was used, and the results for the two test cases can be seen in Figure 4 and Appendix E.



**Figure 4:** Heatmap showing the correlation ceofficient between all of the measurement instrument on windows for the fannkuch-redux testcase

All DUTs showed moderate to high correlation with the ground truth (Clamp) when assessed with the Guildford Scale. The measuring instruments varied in their correlation performance, with SCAPI being the best but with very few data points logged, this is also the case with SCAP. LHM and IPG being essentially equal in performance for both test cases which Slight diviations. Since usability is also a factor, IPG was chosen as the best measuring instrument and will be used for future experiments on Windows.

### 5.3 Experiment Three

The third experiment investigated RQs 3 and 4, by taking a look at the per-core performance. In this experiment only IPG and the Clamp was used to conduct measurements. The test case was executed on one core at a time using the single-core test cases introduced in Section 4.6. This allowed a comparison between the energy consumption of the P- and E-cores on DUT 2 and the P-cores on DUT 1.

**Per-Core Initial Measurements:** An initial 250 measurements were made for each test case on each core. Then Cochran's formula was calculated to determine if more measurements were required as shown in Appendix G. However the limit of 1000 measurements set in experiment two was still used.

MB measurements on DUT 2			
Metric	E-core	P-core	Difference
Duration	58.96 s	13.96 s	−76.32%
Energy	336.88 j	99.53 j	−70.45%
DEC	253.85 j	16.26 j	−93.59%
DEC per second	0.53 w	1.88 w	+254.71%

**Table 8:** The performance difference between E and P cores on DUT 2, MB

**Per-Core Results:** The results, presented here are based on DUT 2, where the results will be shown in graphs, given the low deviation in the results. Box-plots for both DUTs can be found in Appendix F. The run time was on average 76.26% lower on the P-cores compared to the E-cores and The total DEC was on average 70.44% lower on P cores, however the E cores had a 72.88% lower energy consumption per second. The largest difference between two cores of the same type was found on DUT 1 with test case NB, where the performance was 11.61% worse on core 1 than core 6. The smallest difference was found on DUT 2, test case NB on a E core, where the energy consumption was 1.17% higher on core 6 than core 9.

## 6 Results

## 7 Discussion

## 8 Conclusion

## Acknowledgements

## 9 Future Works

**References**

## A The Framework

The framework used in this work is an extension to [biksbois], where one key difference is it a command line tool, supporting all languages. The framework is called Biks Diagnostics Energy (BDE) and can be executed in two ways, as seen in Listing 4, where one is with a configuration, and one is with a path to an executable file.

```
1 .\BDEnergyFramework --config path/to/config.json
2
3 .\BDEnergyFramework --path path/to/file.exe --parameter parameter
```

**Listing 4:** An example of how BDE can be started

When using `--config`, the user specifies a path to a valid json file of the format seen in Listing 5. Through Listing 5, it is possible to specify paths to executable files and assign each executable file with a parameter in `TestCasePaths` and `TestCaseParameter` respectively. Information like the compiler, language, etc can also be specified about the test case in the configuration. It is also possible to specify the affinity of the test case through `AllocatedCores`, where an empty list represents the use of all cores and the list `1,2` specifies how the test case can only execute on core one and two. When multiple affinities are specified, each test case will be run on both. Limits for the temperature the test cases should be executed within can also be specified, and lastly, `AdditionalMetadata` can be used to specify relevant aspects about the experiment, which cannot already be specified through the configuration.

```
1 [
2   {
3     "MeasurementInstruments": [ 2 ],
4     "RequiredMeasurements": 30,
5     "TestCasePaths": [
6       "path/to/one.exe", "path/to/two.exe"
7     ],
8     "AllocatedCores": [
9       [], [1,2]
10    ],
11    "TestCaseParameters": [
12      "one_parameter", "two_parameter",
13    ],
14    "UploadToDatabase": true,
15    "BurnInPeriod": 0,
16    "MinimumTemperature": 0,
17    "MaximumTemperature": 100,
18    "DisableWifi": false,
19    "ExperimentNumber": 0,
20    "ExperimentName": "testing-phase",
21    "ConcurrencyLimit": "multi-thread",
22    "TestCaseType": "microbenchmarks",
23    "Compiler": "clang",
24    "Optimizations": "openmp",
25    "Language": "c++",
26    "StopBackgroundProcesses": false,
27    "AdditionalMetadata": {}
28  }
29 ]
```

**Listing 5:** An example of a valid configuration for BDE

When using the parameters `--path`, the `--parameter` is an optional way to provide the executable with parameters. When using BDE this way, a default configuration is set up, containing all fields in the configuration, except `TestCasePath` and `TestCaseParameter`.

```

1 public interface IDutService
2 {
3     public void DisableWifi();
4     public void EnableWifi();
5     public List<EMeasuringInstrument> GetMeasuringInstruments();
6     public string GetOperatingSystem();
7     public double GetTemperature();
8     public bool IsAdmin();
9     public void StopBackgroundProcesses();
10 }

```

**Listing 6:** The DUT interface which allows BDE to work on multiple OSs

Both Windows and Linux is supported on BDE. This is supported through the IDutService seen in Listing 6, where all OS dependent operations are located. This includes the ability to enable and disable the WiFi, stop background processes, ect. The IDutService has a Windows and Linux implementation on BDE where depending on the OS of the machine BDE is executed on, one of these will be initialized and used.

```

1 public class MeasuringInstrument
2 {
3
4     public (TimeSeries, Measurement) GetMeasurement()
5     {
6         var path = GetPath(_measuringInstrument, fileCreatingTime);
7         return ParseData(path);
8     }
9
10    public void Start(DateTime fileCreatingTime)
11    {
12        var path = GetPath(_measuringInstrument, fileCreatingTime);
13
14        StartMeasuringInstruments(path);
15
16        StartTimer();
17    }
18
19    public void Stop(DateTime date)
20    {
21        StopTimer();
22        StopMeasuringInstrument();
23    }
24
25    internal virtual int GetMillisecondsBetweenSamples()
26    {
27        return 100;
28    }
29
30    internal virtual (TimeSeries, Measurement) ParseData(string path) { }
31
32    internal virtual void StopMeasuringInstrument() { }
33
34    internal virtual void StartMeasuringInstruments(string path) { }
35
36    internal virtual void PerformMeasuring() { }
37 }

```

**Listing 7:** The implementation of the different measuring instruments on BDE

BDE also supports multiple measuring instruments, through a parent class MeasuringInstrument in Listing 7 the measuring instruments can inherit from. MeasuringInstrument implements a start (line 10) and stop (line 19) method, and a method to get the data measured between the start and stop in line 4. In terms of the virtual methods, each measuring instrument needs to override, these are measuring instruments specific. This includes a start (line 34) and stop (line 32) method, a method to parse the measurement data in line 30 and a method in line 36 which performs a measurement by default every 100ms by default. The method in line 36 is made for measuring instruments line RAPL, where an action is required to read the energy consumption.

```

1 public void PerformMeasurement(MeasurementConfiguration config)
2 {

```

```

3      var measurements = new List<MeasurementContext>();
4      var burninApplied = SetIsBurninApplies(config);
5
6      if (burninApplied)
7          measurements = InitializeMeasurements(config, _machineName);
8
9      do
10     {
11         if (CpuTooHotOrCold(config))
12             Cooldown(config);
13
14         if (config.DisableWifi)
15             _dutService.DisableWifi();
16
17         PerformMeasurementsForAllConfigs(config, measurements);
18
19         if (burninApplied && config.UploadToDatabase)
20             UploadMeasurementsToDatabase(config, measurements);
21
22         if (!burninApplied && IsBurnInCountAchieved(measurements, config))
23         {
24             measurements = InitializeMeasurements(config, _machineName);
25             burninApplied = true;
26         }
27     } while (!EnoughMeasurements(measurements));
28
29 }

```

**Listing 8:** An example of how BDE performs measurements

Listing 8 shows how BDE performs measurements given the configuration. In the configuration, the burn-in period can be set to any positive integer, where if this value is one, the boolean `burninApplied` will be set to `true`, and the measurements will be initialized in line 7. This initialization will, if the results should be uploaded to the database, mean BDE will fetch existing results from the database, where the configuration is the same, and continue where it was left off. Otherwise, an empty list will be returned. If `burninApplied` is set to `false`, the amount of burn-in specified in the configuration will be performed before initializing the measurements.

Next, a do-while loop is entered in line 9, which will execute until the condition `EnoughMeasurements` from line 28 is met. Inside the do-while loop, a cooldown will occur in line 12, until the DUT is below and above the temperature limits specified in the configuration. Once this is achieved, the WiFi/Ethernet is disabled, and `PerformMeasurementsForAllConfigs` will then iterate over all measuring instruments and test cases specified, and perform one measurement for all permutations. Afterward, a few checks are made. If the burn-in period is over, and the configuration states that the results should be uploaded to the database, `UploadMeasurementsToDatabase` is called. If the burn-in period is not over yet, but `IsBurnInCountAchieved` is true, the measurements are initialized similarly to line 7, and the boolean `burninIsApplied` is set to `true`, indicating that the burn-in period is over, and the measurements are about to be taken.

## B The Database


In [biksbois], a MySQL database was used to store the measurements made by the different measuring instruments. In this work, a similar database will be used, but with some modifications to accommodate the different focus compared to [biksbois]. The design of the database can be seen in Figure 5, where the `MeasurementCollection` table defines under which circumstances the measurements were made. This includes which measuring instrument was used, which test case was running, which DUT the measurements were made on, whether or not there was a burn-in period, etc. Compared to [biksbois], a few extra columns have been added to `TestCase`, this includes metadata like compiler, optimizations, and parameters used.

In the `MeasurementCollection`, the columns `CollectionNumber` and `Name` represents which experiment the measurement is from, and the name of the experiment respectively. A column found in both `MeasurementCollection`, `Measurement` and `Sample` is `AdditionalMetadata`. This column can be used to set values unique for specific rows, where an example could be how some metrics are only measured by one measuring instrument.

The `Measurement` contains values for the energy consumption during the entire execution time of one test case, while the `Sample` represents samples taken during the execution of the test case. This means for one row in the `MeasurementCollection` table, there can exist one to many rows in `Measurement`. Each row in




Measurement is associated with multiple rows in the Sample table, where the samples will be a time-series illustrating the energy consumption over time.




**Figure 5:** An UML diagram representing the tables in the SQL database

## C Experiment One


Measurements made on test case Mandelbrot for the first experiment, found in Section 5.1.




**Figure 6:** Runtime measurements by IPG on DUT 1 for test case(s) FR



**Figure 7:** CPU measurements by IPG on DUT 1 for test case(s) MB




**Figure 8:** CPU measurements by IPG on DUT 1 for test case(s) MB




**Figure 9:** Runtime measurements by IPG on DUT 1 for test case(s) MB

## D Experiment Two


Measurements made on for the second experiment, aiming to find the best measuring instrument, found in Section 5.2.




**Figure 10:** CPU measurements on DUT 1 for test case(s) FR compiled on oneAPI




**Figure 11:** CPU measurements on DUT 1 for test case(s) FR compiled on oneAPI




**Figure 12:** Runtime measurements on DUT 1 for test case(s) FR compiled on oneAPI




**Figure 13:** CPU measurements on DUT 1 for test case(s) MB compiled on oneAPI




**Figure 14:** CPU measurements on DUT 1 for test case(s) MB compiled on oneAPI




**Figure 15:** Runtime measurements on DUT 1 for test case(s) MB compiled on oneAPI




**Figure 16:** CPU measurements on DUT 2 for test case(s) FR compiled on oneAPI




**Figure 17:** CPU measurements on DUT 2 for test case(s) FR compiled on oneAPI




**Figure 18:** Runtime measurements on DUT 2 for test case(s) FR compiled on oneAPI



**Figure 19:** CPU measurements on DUT 2 for test case(s) MB compiled on oneAPI



**Figure 20:** CPU measurements on DUT 2 for test case(s) MB compiled on oneAPI



**Figure 21:** Runtime measurements on DUT 2 for test case(s) MB compiled on oneAPI

## E Initial Measurements in Experiment Two

This section illustrates how many measurements are required from the different measuring instruments in order to gain confidence in them, and are used in Section 5.2.

Initial Measurements		
Name	Fannkuch Redux	Mandelbrot
Plug (W)	2.474	1.790
Plug (L)	5	4818
Clamp (W)	16.908	2855
Clamp (L)	???	???
RAPL	52	53
SCAP	459	74
SCAPI	453	153
IPG	714	216
LHM	604	45

**Table 9:** The required samples to gain confidence in the measurements made by the different measuring instruments, on both OSs for DUT 1


Initial Measurements		
Name	Fannkuch Redux	Mandelbrot
Plug (W)	916	1.088
Plug (L)	738	1056
Clamp (W)	36.558	44.106
Clamp (L)	???	???
RAPL	1298	4.340
SCAP	416	1.478
SCAPI	840	3.095
IPG	379	88
LHM	379	31

**Table 10:** The required samples to gain confidence in the measurements made by the different measuring instruments, on both OSs for DUT 2

## Correlation from Experiment Two

This section shows the correlation heatmap from Section 5.2.







**Figure 22:** Heatmap showing the correlation coefficient between all of the measurement instruments on windows for the Mandelbrot test case.

## F Experiment Three


This section includes the results from the third experiment, as can be found in Section 5.3




**Figure 23:** CPU measurements by IPG on DUT 1 for test case(s) NB compiled on oneAPI




**Figure 24:** CPU measurements by IPG on DUT 1 for test case(s) NB compiled on oneAPI




**Figure 25:** Runtime measurements by IPG on DUT 1 for test case(s) NB compiled on oneAPI




**Figure 26:** CPU measurements by IPG on DUT 1 for test case(s) SN compiled on oneAPI




**Figure 27:** CPU measurements by IPG on DUT 1 for test case(s) SN compiled on oneAPI




**Figure 28:** Runtime measurements by IPG on DUT 1 for test case(s) SN compiled on oneAPI




**Figure 29:** CPU measurements by IPG on DUT 2 for test case(s) NB compiled on oneAPI




**Figure 30:** CPU measurements by IPG on DUT 2 for test case(s) NB compiled on oneAPI




**Figure 31:** Runtime measurements by IPG on DUT 2 for test case(s) NB compiled on oneAPI



**Figure 32:** CPU measurements by IPG on DUT 2 for test case(s) SN compiled on oneAPI



**Figure 33:** CPU measurements by IPG on DUT 2 for test case(s) SN compiled on oneAPI



**Figure 34:** Runtime measurements by IPG on DUT 2 for test case(s) SN compiled on oneAPI

## G Initial Measurements in Experiment Three

This section illustrates how many measurements are required from IPG when measuring the energy consumption on different cores in order to gain confidence in them, and are used in Section 5.3.

Initial Measurements		
Name	NBody	Spectral-Norm
Core 0	5.162	1.991
Core 1	11.771	1.999
Core 2	5.119	2.047
Core 3	4.678	2.039
Core 4	4.597	1.979
Core 5	5.005	2.082
Core 6	4.622	1.852
Core 7	4.996	1.945

**Table 11:** The required samples to gain confidence in the measurements made by IPG in different cores for DUT 1

Initial Measurements		
Name	NBody	Spectral-Norm
Core 0	4	36
Core 1	7	33
Core 2	1	35
Core 3	1	28
Core 4	3	33
Core 5	2	30
Core 6	17	115
Core 7	22	99
Core 8	18	121
Core 9	39	92

**Table 12:** The required samples to gain confidence in the measurements made by IPG in different cores for DUT 2