

Contents

1	Introduction	2
1.1	A Short Overview of Programming Languages	2
1.1.1	C, Strengths and Weaknesses	3
1.2	Shell Basics on Linux	4
2	Fundamentals of C Language	8
2.1	Writing a Simple Program, <code>Hello, McMaster!</code>	8
2.1.1	A General Form of a Program	8
2.1.2	Compiling and Executing the Program	10
2.2	Variables	12
2.3	Statements	12
2.3.1	Comparison: <code>if</code> and <code>switch</code>	12
2.3.2	Loops and Iterations: <code>while</code>	12
2.3.3	Loops and Iterations: <code>do</code>	12
2.3.4	Loops and Iterations: <code>for</code>	12
2.3.5	Loops and Iterations: Exiting from a Loop	12
3	Intermediate Topics in C	12
4	Advanced Topics in C	13
5	A Short Overview of ANN	13

1 Introduction

1.1 A Short Overview of Programming Languages

Programming languages can be categorized based on their level of abstraction, which refers to how closely they resemble the underlying hardware operations of a computer. At the lowest level, we have **machine code**, which consists of binary instructions that are directly executed by the computer's hardware. Above machine code, we have **assembly language**, which uses **human-readable** characters to represent the low-level instructions. However, assembly language is specific to each CPU architecture, so it can differ between different types of processors.

Moving up the hierarchy, we encounter **C**, which was created in around 1970 as a by-product of UNIX based operating systems. **C** is considered a slightly higher-level language compared to **assembly language**. It provides a set of abstract statements and constructs that are closer to human-readable text. **C** code can be compiled using a program called **compiler**, which translates the **C** code into **machine code** that can be executed on any CPU. This portability is one of the reasons why **C** is often referred to as "**portable assembly**." **C** allows programmers to efficiently write code with a relatively low level of abstraction.

Above **C**, we find **C++**, which was created around 1985. **C++** is an extension of **C** and introduces **object-oriented programming** concepts. It includes the ability to define **classes**, which encapsulate data and behavior into reusable structures. However, for the purpose of this course, we won't delve into the specifics of object-oriented programming.

Moving further up the ladder, we have **Java** and **C#**, which are considered **mid-level** languages. These languages restrict certain low-level operations available in **C** and **C++**, for example, managing memory environments. Instead of allowing direct memory allocation, **Java** and **C#** handle memory management themselves, offering automatic memory allocation and garbage collection. This trade-off provides programmers with increased security and simplifies memory management, but it also limits some of the flexibility and control offered by lower-level languages.

At the **highest level**, we have interpreted languages like **Python** and **JavaScript**. These languages are considered highly abstracted and provide significant levels of convenience and ease of use for developers. Interpreted languages do not require a separate compilation step; instead, they use an **interpreter** to execute the source code directly. The interpreter reads the code **line-by-line**, executing each instruction as it encounters it. This line-by-line execution allows for more dynamic and interactive programming experiences but can result in slower performance compared to compiled languages.

1.1.1 C, Strengths and Weaknesses

Weaknesses

While C has many strengths, it also has a few weaknesses that developers should be aware of:

- 1. Error-prone:** Due to its flexibility, C programs can be prone to errors that may not be easily detectable by the compiler. For example, missing a semicolon or adding an extra one can lead to unexpected behavior, such as infinite loops! It means you are waiting for hours to get the result, then you figure out it shouldn't take that much time! Don't worry there are some ways to avoid it!
- 2. Difficulty in Understanding:** C can be more difficult to understand compared to higher-level languages. It requires a solid understanding of low-level concepts, such as memory management and pointers. The syntax and usage of certain features, like pointers and complex memory operations, may be unfamiliar to beginners or programmers coming from higher-level languages. This learning curve can make it more challenging for individuals new to programming to grasp and write code in C effectively.
- 3. Limited Modularity:** C lacks built-in features for modular programming, making it harder to divide large programs into smaller, more manageable pieces. Other languages often provide mechanisms like namespaces, modules, or classes that facilitate the organization and separation of code into logical components. Without these features, developers must rely on manual techniques, such as using header files and carefully organizing code structure, to achieve modularity in C programs. This can lead to codebases that are harder to maintain and modify as the project grows in complexity.

Strength

C programming language possesses several strengths that have contributed to its enduring popularity and wide-ranging applicability:

- 1. Efficiency:** C is renowned for its efficiency, allowing programs written in C to execute quickly and consume minimal memory resources. It provides low-level access to memory and hardware, enabling developers to optimize their code for performance-critical applications.
- 2. Power:** C offers a rich set of data types and a flexible syntax, enabling developers to express complex algorithms and manipulate data efficiently. Its extensive standard library provides numerous functions for tasks such as file I/O, memory management, and string manipulation, allowing programmers to accomplish a lot with concise and readable code.
- 3. Flexibility:** The versatility of C is evident in its widespread use across different domains and industries. C has been employed in diverse applications, including embedded systems, oper-

ating systems, game development, scientific research, commercial data processing, and more. Its flexibility makes it a suitable choice for a broad range of programming tasks.

4. Portability: C is highly portable, meaning that programs written in C can be compiled and run on a wide range of computer systems, from personal computers to supercomputers. The C language itself is platform-independent, and compilers are available for various operating systems and architectures.

5. UNIX Integration: C has deep integration with the UNIX operating system, which includes Linux. This integration allows C programs to interact seamlessly with the underlying system, making it a favored language for system-level programming and development on UNIX-based platforms.

1.2 Shell Basics on Linux

To create a new folder (directory) in Linux using the terminal, you can use the `mkdir` command. Here's how you can do it:

Open your terminal application. This can vary depending on the Linux distribution you're using. You can typically find the terminal in Applications menu or by pressing `Ctrl+Alt+T`. Navigate to the location where you want to create the new folder. You can use the `cd` command to change directories. For example, if you want to create the folder in your home directory, you can use `cd ~` to navigate there. Once you're in the desired location, use the `mkdir` command followed by the name you want to give to the new folder. For example, to create a folder called "COMPSCI1XC3," you would type `mkdir COMPSCI1XC3`. Press `Enter` to execute the command.

In the world of Linux commands hold the power to shape the digital landscape. Let's do start with some basic commands:

1. Current directory: To know your current directory, use the command `pwd`. It will display the path of the directory you are currently in. To view all the files and folders in the current directory, use the command `ls`. This will provide a list of all the files and folders. Look for a folder named `COMPSCI1XC3` in the list of files and folders (if you have did the previous step successfully!). Once you find it, you'll use the following steps to navigate and work within that folder. To open the `COMPSCI1XC3` folder in the file manager, use the command `open COMPSCI1XC3`.

2. Moving back and forth in directories: To change your current directory to the `COMPSCI1XC3` folder, use the command `cd COMPSCI1XC3` in the terminal. This command allows you to move into the specified folder (use `pwd` to double check!) If you want to go back to the initial directory, simply use the command `cd` without any arguments. This will take you back to the `/home/username` directory, where `username` is what you picked during installation of Linux. To go back one folder,

use the command `cd ..`. This will navigate you up one level in the directory structure.

3. Making a file: Now, go back to `COMPSCI1XC3` directory. If you want to create a text file named "AnneMarie", use the command `nano AnneMarie.txt`. This will open the file editor where you can write and edit text. To open the `AnneMarie.txt` file in the Nano text editor, use the command `nano AnneMarie.txt` again. This allows you to make changes to the file. If you wish to save your changes, press `Ctrl+O` and then press `Enter`. This will save the file. Alternatively, if you want to save and exit the Nano text editor, press `Ctrl+X` and then press `Enter`. This will save the changes and return you to the terminal.

To reopen the `AnneMarie.txt` file in the terminal using the Nano text editor, use the command `nano AnneMarie.txt`. If you prefer to open the `AnneMarie.txt` file in the Windows environment, use the command open `AnneMarie.txt` after saving the file. This will open the file using the default application associated with `.txt` files.

4. Copy and Paste: To copy the `AnneMarie.txt` file and paste it into another directory, you can use the `cp` command, like:

```
cp AnneMarie.txt /path/to/destination/directory/
```

Replace `/path/to/destination/directory/` with the actual path of the directory where you want to paste the file.

5. View a file: The `cat` command is used to display the contents of a file in the terminal. It can be helpful when you want to quickly view the contents of files. Here's an `.txt` file example: `cat AnneMarie.txt`. Running this command will print the contents of `AnneMarie.txt` in the terminal window. Easier way just double click on the file!

6. Finding a folder of file: To find a file or folder using the `locate` command or similar commands, you need to have the appropriate indexing database set up on your system. The `locate` command searches this database for file and folder names. For example, `locate AnneMarie.txt`, will search the indexing database for any files or folders with the name `AnneMarie.txt` and display their paths if found. In this case, nothing is shown in terminal. Since we just made this file, the database including directories is not updated to include this file. To update the directory database in all memory, we have to use the command `updatedb`, and you will probably get the following message:

```
/var/lib/plocate/: Permission denied
```

indicating that you do not have the necessary permissions to access the directory. To solve the issue and update the directories index successfully, use the `sudo updatedb` which prompts you to a password which you picked. Enter the password, it might not be shown when you are entering the password, then press `Enter`. By this command, you are running the `updatedb` with superuser

(root) privileges. `sudo` stands for "Super User Do" and is a command that allows regular users to execute commands with the security privileges of the superuser. Now you can use command `locate`, but this time it shows the directory that the file is saved.

Alternatively, you can use:

```
find /path/to/search/directory -name AnneMarie.txt
```

Replace `/path/to/search/directory` with the directory where you want to start the search.

Tips! Debugging is an essential aspect of programming. No programmer possesses complete knowledge or can remember every command, especially when working with multiple programming languages. However, it is crucial to know where to find the answers. Here are two approaches to tackle a specific issue:

1. Use internet. For instance, search for "permission denied on Linux." Take a quick look at the top search results, paying particular attention to reputable sources such as [Stack Overflow](#). Spend a few minutes scrolling through the search results.
2. Engage with ChatGPT by asking a specific question related to the problem you encountered. For example, you could ask, "I tried `updatedb` on Linux terminal, and it gives me Permission denied. How can I solve it?"

7. Remove: The `rm` command is used to remove (delete) files and directories. It's important to exercise caution when using this command, as deleted files cannot be easily recovered. Here's an example to remove the `AnneMarie.txt` file: `rm AnneMarie.txt`. This command will permanently delete the `AnneMarie.txt` file. Be sure to double-check the file name and verify that you want to delete it.

The `rmdir` command is used to remove (delete) empty directories. It cannot remove directories that have any files or subdirectories within them. Here's an example: `rmdir empty_directory`. Replace `empty_directory` with the name of the directory you want to remove. This command will only work if the directory is empty. If there are any files or subdirectories inside it, you'll need to delete them first or use the `rm` command with appropriate options to remove them recursively.

8. Let's checkout some OS characteristics.

Linux distribution: distThe `lsb_release -a` command provides comprehensive information about your Linux distribution, including the release version, codename, distributor ID, and other relevant details. The `-a` option is a command-line option or flag that stands for "all." When used with the `lsb_release` command, it instructs the command to display all available information about the Linux distribution. It is a convenient way to quickly check the specifics of your Linux

distribution from the command line. My Linux distribution is:

```
Distributor ID: Ubuntu
Description: Ubuntu 22.04.2 LTS
Release: 22.04
Codename: jammy
```

CPU: The `lscpu` command is used to gather and display information about the CPU (Central Processing Unit) and its architecture on a Linux system. It provides detailed information about the processor, including its model, architecture, number of cores, clock speed, cache sizes, and other relevant details. **Some** of details for my system:

```
Architecture:          x86_64
CPU op-mode(s):        32-bit, 64-bit
Address sizes:          39 bits physical, 48 bits virtual
Byte Order:             Little Endian
CPU(s):                 8
On-line CPU(s) list:   0-7
Vendor ID:              GenuineIntel
Model name:              Intel(R) Core(TM) i7-7700HQ CPU @ 2.80GHz
CPU family:              6
Model:                  158
Thread(s) per core:     2
```

Disk space available: The `df -h` command is used to display information about the disk space usage on your Linux system. In this command, `df` stands for **disk free**, and `-h` is a command-line option or flag that stands for **human-readable**. The

Filesystem	Size	Used	Avail	Use%	Mounted on
/dev/sda2	228G	113G	104G	53%	/

`/dev/sda2` is a partition identifier that represents the second partition on the first SATA (or SCSI) disk (sda). It typically contains the main file system of your Linux system. The actual partition identifiers may differ depending on your system's configuration and the number of disks or partitions present.

Information about the RAM: In the command `free -h`, `free` represents the command used to display memory usage statistics, and `-h` is a command-line option that stands for **human-readable**.

	total	used	free	shared	buff/cache	available
Mem:	15Gi	4.4Gi	3.3Gi	637Mi	7.8Gi	10Gi

Swap:	2.0Gi	0B	2.0Gi
-------	-------	----	-------

The **Swap** space is a portion of the hard drive that is used as virtual memory by the operating system. It acts as an extension to the physical memory (RAM) and allows the system to temporarily store data that doesn't fit into the RAM.

9. Short keys in terminal: `Ctrl+L` to remove the history of terminal. Pressing up key takes you to previous commands. To copy from terminal you have to press `Cntrl + Shift + C` and to paste a command press `Ctrl + shift + V`.

2 Fundamentals of C Language

This section is designed to provide an introduction to fundamental concepts in C, including data types, variables, and control flow statements such as if and loops. Some of students with prior knowledge of programming might already know these concepts, but we will delve into each topic extensively and provide detailed explanations. Our goal is to ensure that everyone, regardless of their programming background, can grasp these essential concepts effectively. We will illustrate each concept with practical examples and problem-solving exercises to enhance understanding, as these concepts form the backbone of C programming.

2.1 Writing a Simple Program, Hello, McMaster!

2.1.1 A General Form of a Program

Let's make a new file using `nano Hello.c` where the `.c` extension represent a C file. Before closing the the opened file in terminal copy and paste the following code in the file and save it. To paste the the copied section you have to use `Ctrl + shift + V`. Press `Ctrl + X` then `y` and press Enter to save before exit.

```
// this code is written by Pedram
#include <stdio.h>

// the main function
int main(void) {
    /* calling "printf" function
    the "defination" is included in "stdio" library */
    printf("Hello, McMaster!\n");
}
```


Open the file by `open Hello.c`. This is a more user friendly environment to edit the code. Maybe the main difference is I can click different parts of the code and edit the code. During you lab lectures this week, you TAs will discuss Visual Studio Code IDE (Integrated Development Environment) which support many programming languages, including C, as well as many useful tools such as automatic code formatting. I strongly suggest to install it and set it up for C format for the next lectures. If I want to modify the code in terms of extra spaces in the code using `open Hello.c` it will take me some time. But if you have Visual Studio Code installed, in the terminal enter `code Hello.c` to open the same code in Visual Studio Code (VSC). Right click on the code and choose **Format Document** which automatically modifies the code in C format.

Tips! Get your hands dirty! I promise you that by only reading these notes you will NOT be able to learn programming. You have to write, modify, and change every code in these notes. Play with them like you play video games!

Anything starts with two slashes, `//`, until the end of the line is a comment and it will not be executed. To make multiple lines as comments, you can place them between `/*` and `*/`. The following lines in the code are all comments:

```
// this code is written by Pedram

// the main function

/* calling "printf" function
the "defination" is included in "stdio" library */
```

Based on the IDE that you are using the colour of the comments might be different. I have said earlier that understanding C codes especially written by someone else might be difficult. Comments are supposed to be helpful to remember or tell others what is the purpose of each part of the code or even how it works.

So the first line which is really executed is `include <stdio.h>`. Usually at the beginning of a code, we include libraries used in the code. `include <stdio.h>` tells C to read **header file** named `stdio` with extension `.h` which stands for **header file**. In this library the definition of function `printf` is mentioned. Any time you forget what library a function is in, you can ask your best friend **Google** or **ChatGPT** by simply asking "what library in C printf is in."

The second line that will be executed is `int main(void)` as a function. In C, defining a function starts with the type of value the function returns, which in this case it is `int`. The `int` means **integer** and the function `main` will automatically return the value `0` if there is no error in the code.

The `main` is the name of function. This function must be included in all C programs, and you have to write your code inside this function.

Between the parentheses, `void` what inputs your program needs and requires the user to give the input(s) every time the code is going to be executed. In this case, we don't have any input so it is `void`, or we can define `int main()` instead of `int main(void)`. Both means the program requires no input(s).

Anything between `{`, right after `int main(void)`, and `}`, at the end of the code, is called **compound statement** or **code block**, which belongs to `main` function. So the following statement is the general format that we have to include in all C programs:

```
Including Library

int main(){

    your statements

}
```

In this code, `printf("Hello, McMaster!\n")` is the only statement we have and `printf` function is used to print a text. Between `(` and `)` the arguments for the function `printf` is given, which is a string or text to be printed!

A string is sequence of characters enclosed within quotation marks. `"Hello, McMaster!\n"` is the string that will be printed. The backslash `\` before `n` tells C to go to (`n`)ext line after printing `Hello, McMaster!`. Try to compile and run the code two times with `\n` and two times without `\n` and see the difference in the terminal! At the end of this line there is `;` indicating the command for this line has ended.

A reminder, the closing bracket `}` at the end, means the end of function `main`!

2.1.2 Compiling and Executing the Program

Now we have to convert the program, the file `Hello.c`, to a format that machine can understand and execute. It usually involves, **Pre-processing**, **Compiling**, and **Linking**. During **Pre-processing** some modification will be done automatically to the code, before making the executable **object** code in **Compiling** step. These two steps are done at the same time and automatically, so won't need to be worried about it! In the Linking step, the library included will be linked to the executable file. Since this code is using a standard library, `<stdio.h>`, it happens automatically. Again, you don't need to be worried!!!

To compile the program in UNIX based OS, usually `cc` is used. Open a terminal in the directory where `Hello.c` file is located (please refer to the section Shell Basics on Linux). Type `cc Hello.c`. Check out the directory. A new executable **object** file named `a.out` by default will be created.

If you see the following error after executing `cc Hello.c`, it means you are not in the same directory where `Hello.c` is located. A reminder, use `pwd` to check your current directory.

```
cc1: fatal error: Hello.c: No such file or directory
compilation terminated.
```

Visual Studio Code! You may open the code in Visual Studio Code (VSCode) by running `code Hello.c` in the terminal. Again make sure current directory is where `Hello.c` is located, otherwise you will see an error indicating the is no such a file in this directory. At the top of VSCode opened, press **View** and click **Terminal**. A window will be opened at the bottom, named **TERMINAL**. There is no difference between this Terminal and terminal you open using `Ctrl + Alt + T`. Make sure the directory of this Terminal in VSCode is the where `Hello.c` is located to avoid the error I have mention before running `cc Hello.c` in the terminal.

After `cc Hello.c` if there is no problem, you should be able to see a new executable **object** file named `a.out` by default in the directory.

At this stage the code is compiled, the **object** `a.out` readable by machine is created. This means the program is translated to a language that machine can understand and it saved in the **object** file `a.out`. Now it is time to tell the machine to run the translated code and show us the result. Run `./a.out` in the terminal. Again, make sure you are in the directory where `a.out` is located. It is done! you should be able to see the result!

Hello, McMaster!

I have mentioned the name `a.out` is given to the **object** file by default. I can define any name I want. Lets remove the previous object file by `rm a.out` and make a new one with the name "Brad" by using `cc -o Brad Hello.c`. The compiler `cc` has many options, and `-o` means translate the program `Hello.c` to the machine language with an (**o**)bject file named `Brad`. Now you must be able to see an **object** file named `Brad` in the same directory. If you run the command line `./Brad` in the same directory, you should be able to see the output.

GCC compiler Another popular compiler in C is GCC (GNU Compiler Collection) compiler supported by Unix OS. It is known for its robustness, efficiency, and compatibility with multiple platforms. GCC supports various optimizations and provides comprehensive error checking, making it a reliable choice for compiling C code.

One notable feature of GCC is its similarity to the "cc" compiler command. This similarity stems from the fact that on many Unix-like systems, the "cc" command is often a symbolic link or an alias for GCC. Therefore, using "cc" to compile your code essentially invokes the GCC compiler with its default settings. GCC offers numerous options to control various aspects of the compilation process, such as optimization levels, debugging symbols, and specific target architectures.

You can compile the same program using GCC instead of `cc` by executing `gcc -o Brad Hello.c` in the terminal.

The **object** file `./Brad` is executable in any Unix based OS. It is software of application you developed!

2.2 Variables

2.3 Statements

2.3.1 Comparison: `if` and `switch`

including boolean and switch

2.3.2 Loops and Iterations: `while`

2.3.3 Loops and Iterations: `do`

2.3.4 Loops and Iterations: `for`

2.3.5 Loops and Iterations: Exiting from a Loop

including break, continue, goto

3 Intermediate Topics in C

including:

debugging

floating point

type conversion

pointers

Dynamic memory allocation

4 Advanced Topics in C

including:

structs and typedefs

input and output reading a file or output a file

parallel computing

further topics

5 A Short Overview of ANN