Supplementary Material

Thresholds and Learning in Adaptive Intrusion Detection: A Two-Capture Case Study

Oleksandr Kuznetsov Emanuele Pio De Bernardis

1 November 2026 — second-review revision

This supplement preserves the historical campaign, its development record, and full diagnostics. All five-seed summaries describe algorithmic randomization conditional on the same recorded stream. Historical measurements and later reconstructions are separate evidence stages. The main article gives the current interpretation; the archived negative and unfavorable results remain available here.

S1 Historical protocol and implementation

S1.1 Dataset, feature availability, and chronological partitions

The source network archive contains 22,339,021 rows. The preprocessing manifest records 869 invalid rows and 22,338,152 retained rows. The retained input vector contains eight numerical fields in this order: `duration`, `src_bytes`, `dst_bytes`, `missed_bytes`, `src_pkts`, `src_ip_bytes`, `dst_pkts`, and `dst_ip_bytes`. Binary labels distinguish normal traffic from attacks. The eight-feature contract was inherited from the project's compact-detector experiments: it uses flow-level numerical aggregates without IP identifiers, ports, application strings, or categorical encodings. Holding it fixed makes the adaptation intervention comparable, but is not a feature-optimality claim. The chronological evaluation stream retains its observed prevalence.

Records are ordered by their complete-feature availability time,

$$t_{\text{ready}} = t_{\text{start}} + \text{duration}. \tag{1}$$

This is an offline flow-completion replay. It does not assume that duration or byte totals are known at the first packet. The retained data cover ten UTC calendar days in April 2019, with no retained interval from 5 to 22 April. Table S1 defines the four chronological partitions. A estimates the initial transformation and model; B selects the initial threshold; C supports development; and D is reserved for the final predictive campaign.

Attack composition changes across these intervals. A contains scanning attacks; B contains scanning and denial of service. C contains distributed denial of service, denial of service, injection, and password attacks. D contains backdoor, man-in-the-middle, password, ransomware, and cross-site scripting records. These changes provide temporal heterogeneity, but the experiment does not

Table S1: Chronological data partitions. Counts refer to retained rows; normal and attack counts sum to each partition total. The separate overlap strata are described in Section S1.5.

Partition	UTC dates, April 2019	Total	Normal	Attack
A: initial fit	2–4, 23	3,956,308	223,199	3,733,109
B: initial threshold	24	5,681,198	89,323	5,591,875
C: development	25–26	9,150,673	173,316	8,977,357
D: final evaluation	27–29	3,549,973	309,673	3,240,300

identify a causal type of drift. Backdoor, man-in-the-middle, ransomware, and cross-site scripting are absent from A/B/C; password also occurs in C. The extension reports per-family attack recall.

Before the final campaign, D had been read for structural checks and feature-vector overlap analysis. Its predictive evaluation was run only after the protocol and code were fixed. Accordingly, D is a later evaluation interval, not a completely unseen resource in the broader research process. The five initial models and their B thresholds are prepared before the final runner loads D. C is used in that runner to construct the prior-vector inventory; the C adaptive state is not carried into D.

S1.2 Initial model and restricted adaptation

Each raw input is transformed by $\log(1 + \max(x, 0))$ and standardized using means and standard deviations estimated from A. A zero standard deviation is replaced by one. The transformation remains fixed. Each transformed feature is then mapped to its range observed in A and clipped to $[0, 1 - 10^{-9}]$ for spline evaluation. Values outside the observed range therefore saturate at a boundary rather than extrapolating the spline.

For input j, the model contains eight cubic B-spline basis functions B_{jr} with an open knot vector based on six equally spaced positions between zero and one. The initial function is

$$f_j(x_j) = \sum_{r=1}^{8} \theta_{jr} B_{jr}(u_j(x_j)), \qquad s(x; g, b) = b + \sum_{j=1}^{8} g_j f_j(x_j). \tag{2}$$

The 64 spline coefficients and initial intercept are fitted by logistic regression on a uniform, seeded 400,000-row sample of A. The implementation uses scikit-learn with `C=1.0` and `max_iter=1000` [1]. The initial gains are $g_j = 1$. Subsequent adaptation leaves the transformation, knots, and all θ_{jr} fixed, and refits only the eight gains and intercept on the current fitting memory. Each refit solves a new logistic-regression problem with L2 shrinkage of the eight weights toward zero and an unpenalized intercept. It neither starts from nor penalizes distance to the previous head. The fixed spline functions retain information from A, while the head is newly fitted to the current memory. The extension explicitly tests a penalty centred at the previous head.

The empirical object is a logistic generalized additive model with an adaptive linear combination of fixed spline functions. Head refitting can reweight these functions, but cannot learn a new spline shape or an interaction between inputs.

S1.3 Threshold objective and four paired traces

The implementation predicts attack when $s(x) > \tau$ and normal otherwise. For labeled set $\mathcal{L}$, the threshold objective is

$$\tau^*(\mathcal{L}, s) \in \arg\max_{\tau \in \mathcal{T}} \frac{1}{2} \left[\frac{\mathrm{TP}(\tau)}{P} + \frac{\mathrm{TN}(\tau)}{N} \right], \tag{3}$$

where P and N are the attack and normal counts in $\mathcal{L}$. Candidates comprise the distinct observed scores and a floating-point value strictly below the minimum; together with the maximum observed score, this covers the all-attack and all-normal decisions. Scores and objective values use float64. Maximizers are selected by exact equality, without a tolerance, and ties are resolved by the lower median of the sorted maximizing candidates, at zero-based index $\lfloor (m-1)/2 \rfloor$. This is a deterministic convention, not a demonstrated threshold-stability property.

The B threshold is selected separately for each initial model using all of B, then kept fixed in the corresponding B traces. Table S2 defines the four traces. Both frozen traces use identical initial scores; both FIT192 traces use an identical adapted score trajectory. Consequently, a threshold-only contrast cannot change AUROC. All traces share the same label requests and update eligibility decisions within a seed.

Table S2: Four paired traces. B denotes the initial fixed threshold; CAL64 denotes recent threshold selection. The primary contrast is the last row minus the second row.

Trace	Score function	Decision threshold
Frozen / B	Initial A model	Fixed, selected on B
Frozen / CAL64	Initial A model	Selected on recent CAL64 labels
FIT192 / B	Head refitted on FIT192	Fixed, selected on B
FIT192 / CAL64	Same refitted head as FIT192 / B	Selected on recent CAL64 labels




Figure S1: Causal protocol. A label requested in block k cannot affect predictions before block $k+2$. Fitting and threshold selection use separate memories; all state changes are committed together only after the eligibility checks succeed.

S1.4 Label budget, delay, and memory separation

D is divided into 354 blocks of 10,000 records and a final block of 9,973 records, indexed from 0 to 354. Predictions for a block are emitted before any labels from that block enter the controller. A uniform sample without replacement requests $\lfloor 0.01 n_k \rfloor$ labels from block k: 100 from a full block and 99 from the last block. Requested labels arrive at the end of block $k+1$ and can first influence predictions in block $k+2$ (Figure S1). Thus 35,499 labels are requested, of which the final 99 remain pending when the observed stream ends. Full labels are available only to the offline evaluation code; the online update receives the delayed requested subset.

Both memories start empty at the beginning of D. FIT192 holds at most 192 labeled examples, with target quotas of 96 normal and 96 attack examples. CAL64 holds at most 64 examples, with target quotas of 32 per class. Either class can borrow unused capacity. On overflow, the oldest example from a class above quota is removed. The quotas alter the stored fitting and threshold-selection samples, not the evaluation stream or the requested-label budget.

A fixed salted SHA-256 rule assigns each raw eight-feature vector permanently to one role: digest modulo four equal to zero selects CAL, and other values select FIT. This prevents an identical vector from appearing in both fitting and calibration memories, even if it recurs later in the stream. It does not deduplicate either memory internally. Role serialization uses canonical float64 bytes; exact overlap between chronological partitions is measured separately using the stored float32 vectors. Appendix S3 specifies these encodings.

FIT192 requires both binary classes. CAL64 contributes only entries observed at most 50 blocks earlier and requires at least five normal and five attack labels. FIT192 has no corresponding age cutoff. If these conditions hold, the implementation fits a candidate head, scores the eligible CAL64 examples with both the frozen and candidate heads, and computes two thresholds using Equation 3. A valid candidate head and both thresholds replace the prior state atomically for the next block. A failed eligibility or numerical check leaves all prior state unchanged and records the reason.

This common schedule isolates the effect of enabling head fitting within the fixed controller, while keeping threshold data and update eligibility matched. It does not estimate a benefit per additional label: FIT192/CAL64 can use FIT-role labels that Frozen/CAL64 leaves unused. The extension therefore adds independently eligible CAL64 and a frozen CAL256 control that can use every acquired label. The 256-example capacity also excludes the delayed-label queue, model state, feature transformations, Python object overhead, temporary solver arrays, and full input arrays used by the offline runner. It must not be interpreted as a total memory bound for an embedded implementation.

S1.5 Overlap-aware reporting

The chronological partitions have disjoint row identities, but their eight-feature vectors overlap. An exact SHA-256 inventory of A/B/C marks each D vector as previously observed or unobserved. In D, 37.23% of rows and 58.03% of normal rows match a prior vector. The unobserved-vector mask retains 2,228,436 rows: 129,982 normal and 2,098,454 attack observations. The complementary seen stratum contains 179,691 normal and 1,141,846 attack observations.

This mask is applied only when aggregating predictions. It changes neither the prediction sequence nor the adaptive state. Requested labels from all of D can still enter the controller, and repetitions within D remain. The supplementary result therefore measures performance on vectors absent from A/B/C during the same adaptive replay. It is not a separately trained no-overlap experiment, an unseen-attack-family test, or a guarantee that a vector has never previously affected the state within D. A matching eight-feature vector is also not proof that two original network events are duplicates.

S1.6 Metrics, paired seeds, and decision criterion

We report global false negatives (FN), false positives (FP), attack recall TP/P, false-positive rate FP/N, and balanced accuracy

$$\mathrm{BA} = \tfrac{1}{2}\left(\mathrm{recall} + 1 - \mathrm{FPR}\right). \tag{4}$$

These rates are computed from the confusion matrix aggregated over the selected scope. Ranking is summarized by the unweighted mean of AUROC over blocks containing both classes:

$$\overline{\mathrm{AUC}}_{\mathrm{block}} = \frac{1}{|\mathcal{V}|}\sum_{k\in\mathcal{V}} \mathrm{AUC}_k. \tag{5}$$

Undefined AUROCs remain missing. Valid denominators are 352 of 355 blocks for all D and 350 of 355 for the A/B/C-unseen subset. This statistic is not the AUROC obtained by pooling every score across the stream; it does not require scores from different adaptive states to be directly comparable.

Seeds 42–46 determine the initial A subsample and block-level label sampling. The original sampler initializes each block with seed+k; different seed/block pairs can therefore reuse the same relative query positions. The extension replaces this with a tuple-keyed SeedSequence while retaining common requests across methods. Each seed shares all observations and requests across its four traces. Values are means and sample standard deviations ($n-1$ denominator) over the

five seeds. Differences are computed within seed before aggregation. These deviations describe stochastic variation conditional on one recorded stream; they are neither confidence intervals nor variation across five independent datasets.

The versioned protocol fixed the primary comparison as FIT192 / CAL64 minus Frozen / CAL64. Its decision criterion required $\Delta\mathrm{FN} \leq 0$ and $\Delta\mathrm{FP} \leq 0$, with at least one strict inequality, in at least four of five seeds. This is a pre-specified empirical acceptance rule, not a statistical significance test or an externally registered trial. The full-stream and supplementary outcomes are reported whether or not the criterion succeeds. We do not select a new operating threshold using final D outcomes.

S2 Historical TON evidence and development record

S2.1 Development evidence motivating the final comparison

Development on C proceeded through four recorded stages. These stages answer different questions and are not a single ranking of competing algorithms. In the initial adaptation study, selecting updates using evidence of score inversion outperformed a random schedule with the same number of updates in mean block AUROC by 0.0217, 0.0559, and 0.0719 for logistic regression, an MLP, and the additive spline model, respectively, against the mean of 20 random schedules. For the additive spline model, none of these update policies exceeded the frozen mean block AUROC of 0.8911: evidence-driven, continuous, and random updates attained 0.8341, 0.8073, and 0.7621. The fitted-memory inversion diagnostic was in sample, and out-of-sample evidence from requested block labels was often unavailable or weak after the required delay. Improved ranking did not consistently improve both error counts.

The next stage changed the memory policy while retaining a 256-example capacity. For the continuously updated spline model, class-aware memory increased mean block AUROC by about 0.084 compared with global FIFO, while attack recall fell by 56.66 percentage points at the fixed historical threshold. Subsequent threshold experiments showed why score and decision changes had to be separated. Re-selecting only the frozen spline threshold improved recall on C by 17.73 percentage points and increased FPR by 1.48 percentage points, with exactly unchanged AUROC. Recalibration using the entire B archive was also explored during development, but that configuration required the additional historical archive and is not presented as satisfying the final 256-example online-memory contract.

The final development configuration separated FIT192 and CAL64. For seed 42 on C, FIT192 / CAL64 reduced FPR by 16.08 percentage points relative to Frozen / CAL64, but reduced recall by 2.60 percentage points and mean block AUROC by about 0.109. This mixed outcome motivated preserving the four traces and reporting FN and FP separately in the final evaluation. The C findings are development evidence, not an additional independent confirmation of the final D result.

S2.2 Absolute outcomes on the final interval

Tables S3 and S4 report all four traces, including the controls that retain the B threshold. With frozen weights, recent threshold selection raises mean attack recall on all D from 21.11% to 89.09%, while FPR rises from 12.64% to 46.74%. Mean block AUROC remains 0.8536 because the scores are identical. Thus, a large recovery in recall can arise entirely from moving the decision threshold.

The FIT192/B diagnostic displays the expected risk of retaining a threshold after changing the fitted sample and score scale. FIT192 / B reaches mean block AUROC 0.9359, yet attack recall is only 8.81% and FPR is 0.88%. The ranking improves on average, but the inherited threshold misses most attacks. Refitting with approximately balanced class quotas differs from fitting A, where about 94% of observations are attacks. Under pure prior shift, the log-odds correction would

Table S3: Final rates: mean ± sample SD over five paired seeds. Recall, FPR, and BA are percentages calculated globally. AUROC is the unweighted mean over valid blocks (352/355 for all D; 350/355 for A/B/C-unseen vectors), then averaged over seeds.

Trace	Recall (%)	FPR (%)	BA (%)	Mean block AUROC
All D				
Frozen / B	21.11 ± 0.72	12.64 ± 0.13	54.24 ± 0.33	0.8536 ± 0.0122
Frozen / CAL64	89.09 ± 1.64	46.74 ± 2.04	71.18 ± 1.73	0.8536 ± 0.0122
FIT192 / B	8.81 ± 5.89	0.88 ± 1.00	53.96 ± 3.23	0.9359 ± 0.0034
FIT192 / CAL64	89.38 ± 1.53	20.47 ± 2.11	84.46 ± 1.15	0.9359 ± 0.0034
Vectors not observed in A/B/C (same replay)				
Frozen / B	3.12 ± 1.11	5.30 ± 0.20	48.91 ± 0.52	0.7934 ± 0.0229
Frozen / CAL64	87.83 ± 3.05	33.99 ± 3.25	76.92 ± 2.82	0.7934 ± 0.0229
FIT192 / B	1.47 ± 0.27	0.71 ± 0.18	50.38 ± 0.19	0.9051 ± 0.0049
FIT192 / CAL64	91.20 ± 1.83	31.94 ± 1.11	79.63 ± 1.01	0.9051 ± 0.0049

Table S4: Absolute final error counts: mean ± sample SD over five seeds. Noninteger means result from averaging integer counts. The paired differences in Table S5 retain the seed correspondence.

Trace	False negatives	False positives
All D		
Frozen / B	$2{,}556{,}210.8 \pm 23{,}236.3$	$39{,}136.2 \pm 413.1$
Frozen / CAL64	$353{,}454.0 \pm 53{,}161.4$	$144{,}730.2 \pm 6{,}318.6$
FIT192 / B	$2{,}954{,}958.6 \pm 190{,}791.8$	$2{,}737.2 \pm 3{,}083.7$
FIT192 / CAL64	$344{,}198.8 \pm 49{,}694.1$	$63{,}374.8 \pm 6{,}542.7$
Vectors not observed in A/B/C (same replay)		
Frozen / B	$2{,}032{,}985.0 \pm 23{,}235.3$	$6{,}887.2 \pm 260.8$
Frozen / CAL64	$255{,}423.0 \pm 63{,}982.9$	$44{,}176.4 \pm 4{,}223.8$
FIT192 / B	$2{,}067{,}609.4 \pm 5{,}672.1$	917.6 ± 228.5
FIT192 / CAL64	$184{,}594.4 \pm 38{,}339.5$	$41{,}521.2 \pm 1{,}447.6$

be an intercept shift; here reweighted slopes and changing class-conditional traffic also contribute. Thus this control illustrates score–threshold mismatch rather than a newly discovered property of logistic models. With the same adapted scores and a recent threshold, FIT192 / CAL64 reaches recall 89.38% and FPR 20.47%. Relative to FIT192 / B, this threshold change removes 2,610,759.8 mean false negatives at the cost of 60,637.6 additional false positives. Figure S2 shows the resulting operating-point changes.

S2.3 Primary paired comparison and the joint-error criterion

The primary contrast compares FIT192 / CAL64 with Frozen / CAL64. On all D, mean balanced accuracy improves by 13.28 ± 2.26 percentage points and mean block AUROC by 0.0823 ± 0.0155. Mean FP decreases by $81{,}355.4 \pm 6{,}051.6$. Mean FN decreases by $9{,}255.2 \pm 97{,}413.0$, corresponding to a recall difference of 0.29 ± 3.01 percentage points. Hence the average balanced-accuracy gain is predominantly associated with lower false-positive rates, while the missed-attack outcome is variable.

The per-seed counts in Table S5 and Figure S3 show the limitation directly. All five seeds reduce FP on the full stream, but seeds 42 and 44 increase FN. Seeds 43, 45, and 46 improve both counts. The pre-specified four-of-five criterion is therefore not met. The sign of the mean FN change does not overturn that result, and the sample SD should not be read as a confidence bound supporting superiority.




Figure S2: Operating points on the same final replay. Points are seed means; bars show sample SD. Lines connect traces with identical score functions and different threshold policies, not a continuously optimized ROC curve. The large threshold effects coexist with a narrower primary comparison between the two CAL64 traces.

Table S5: Primary paired differences, FIT192 / CAL64 minus Frozen / CAL64. Negative values indicate fewer errors. Seeds 43, 45, and 46 jointly improve FN and FP in both reporting scopes; seed 44 worsens both on A/B/C-unseen vectors.

	All D		A/B/C-unseen vectors	
Seed	ΔFN	ΔFP	ΔFN	ΔFP
42	+54,175	−84,858	+4,271	−3,659
43	−115,380	−89,311	−165,016	−6,888
44	+125,148	−73,762	+59,443	+3,547
45	−40,935	−77,720	−129,600	−4,684
46	−69,284	−81,126	−123,241	−1,592

S2.4 Previously unobserved vectors and concentration of the FP gain

For D vectors absent from A/B/C, FIT192 / CAL64 reaches 91.20% attack recall but an FPR of 31.94%. The corresponding Frozen / CAL64 rates are 87.83% and 33.99%. The paired BA gain is 2.71 ± 3.63 percentage points, substantially smaller than the full-stream gain. Mean FN decreases by $70{,}828.6 \pm 97{,}060.6$ and mean FP by $2{,}655.2 \pm 3{,}957.2$. Again, only three of five seeds jointly improve both counts.

The complementary seen stratum exposes the trade-off (Table S6). Head adaptation lowers recall from 91.41% to 86.02%, while FPR falls from 55.96% to 12.16%. It adds 61,573.4 mean FN while removing 78,700.2 FP. In the unseen stratum it removes 70,828.6 FN and 2,655.2 FP. Thus the small full-stream mean FN reduction combines effects with opposite signs. The seen

Table S6: Complementary overlap strata in the original campaign: mean ± seed SD. Rates are percentages. The same adaptive trajectory supplies both strata.

Stratum	Trace	Recall	FPR	BA
Seen	Frozen / CAL64	91.41 ± 2.00	55.96 ± 2.11	67.73 ± 1.22
Seen	FIT192 / CAL64	86.02 ± 2.30	12.16 ± 3.72	86.93 ± 2.49
Unseen	Frozen / CAL64	87.83 ± 3.05	33.99 ± 3.25	76.92 ± 2.82
Unseen	FIT192 / CAL64	91.20 ± 1.83	31.94 ± 1.11	79.63 ± 1.01




Figure S3: Primary paired differences by seed. Both axes show thousands of errors. Joint improvement requires a point in the lower-left quadrant (including a non-deteriorating boundary). The horizontal scales differ to make the much smaller unseen-vector FP changes visible.

stratum contributes 96.7% of the total FP reduction, but that percentage describes the location of FP savings rather than the fraction of all benefit caused by overlap. The strata differ in traffic composition and share one adaptive state.

The factorial BA interaction is positive in every original full-stream seed: 10.76–17.65 percentage points, with mean 13.55. On unseen vectors it ranges from −4.43 to +4.89 points, with mean 1.24. The gain from jointly changing the head and threshold therefore depends on the reporting population. The four-trace interaction and the complementary-stratum decomposition reveal information concealed by a single average BA gain.

S2.5 When limited labels prevent adaptation

Label availability creates a distinct temporal failure mode in the C development replay. There are 440 skipped update decisions, all associated with insufficient recent normal examples for calibration. The longest consecutive sequence spans decision blocks 241–663 and affects predictions in blocks 242–664: 423 blocks. Figure S4 shows the eligible normal-label count and the corresponding decision rates.

Stratifying predictions by the preceding update decision yields opposite FN patterns. Across 474 blocks following applied updates, FIT192 / CAL64 has 29,697 fewer FN and 26,528 fewer FP than Frozen / CAL64. Across 440 blocks following skips, it has 263,032 more FN and 1,342 fewer FP. In the longest skipped segment alone, both counts worsen: FN increases by 219,608 and FP by 807. These are post hoc associations conditioned on the realized stream. The segments have different class composition and cannot establish that skipping caused the deterioration.

The final D replay behaves differently. Of 354 recorded update opportunities per seed, 337, 351, 347, 341, and 350 are accepted for seeds 42–46, respectively. Their 17, 3, 7, 13, and 4 skips all occur before the first valid update. There is no recurrence of the long post-update starvation interval observed on C. The historical D record shows a different eligibility pattern from development C.

S2.6 Measured computation and its boundary

Table S7 gives recorded computational costs on the original evaluation machine: Windows 11, Python 3.13.2, NumPy 2.3.4, scikit-learn 1.7.2, an Intel processor reported as Family 6 Model 186 Stepping 3, 12 visible CPU threads, and 16,067.4 MiB of system RAM. These are elapsed times




Figure S4: Development interval C, seed 42. Shading marks prediction blocks 242–664, following 423 consecutive skipped update decisions. The upper panel shows the recorded number of recent normal examples in CAL64, with the minimum of five indicated. Recall and FPR are per-block values; undefined class-specific rates remain gaps. The display is descriptive and does not randomize the occurrence of skips.

from one execution environment, not cross-device benchmarks.

The five-seed command takes 1,234.388 seconds within its recorded timer boundary. This includes D hashing and loading, initial A fitting and B preparation, the five D replays, and writing the five per-seed reports. It excludes the earlier A/B/C hash calculation and final summary serialization. Within each replay, accumulated head-fitting time is 9.630–10.672 seconds; each of the two accumulated threshold-selection components is below 0.11 seconds. These observations support only the relative cost of these implementation components in this run. They do not establish an energy advantage, a device-level latency guarantee, or an embedded memory footprint.

Table S7: Recorded final-run costs in seconds. Fits and threshold-selection times are components included within replay time, not extra times to add to it. The final recorded update has no subsequent evaluated block.

Seed	Updates	Skips	Head fit	Frozen threshold	Adapted threshold	D replay
42	337	17	10.672	0.103	0.059	59.837
43	351	3	10.224	0.090	0.052	52.683
44	347	7	9.630	0.083	0.050	49.032
45	341	13	9.632	0.094	0.055	48.622
46	350	4	10.378	0.090	0.057	53.348

S3 Implementation details and reproducibility map

S3.1 Immutable roles and retained examples

The role hash is SHA-256 over the ASCII salt `ADAPT04-C-seed42-v1`, a zero byte, and the eight raw feature values encoded as little-endian float64. Both signs of zero are normalized to positive zero; NaNs are canonicalized. The digest is interpreted as a big-endian integer and assigned to CAL if its remainder modulo four is zero, otherwise to FIT. The salt's historical seed label is literal: the same salt is used for every final seed. Each requested observation retains its assigned role. Stored model inputs are transformed only when its label arrives; the role digest continues to identify the raw vector.

For chronological overlap, the separately defined fingerprint is SHA-256 over the 32 bytes of the eight stored float32 inputs in little-endian order. This predicate checks equality at the stored feature precision. It is not an event-identity test. The two hashing procedures have different purposes and must not be substituted for one another in reproduction.

Calibration age is measured from the observation block, not from the arrival block. Repeated vectors can occupy multiple positions in a role memory; the five-per-class minimum counts observations, not unique vectors. Class quotas determine eviction when capacity is exceeded; an age filter determines which retained CAL64 entries are eligible for threshold selection. FIT192 has no age filter. Pending requests are maintained separately from both memories.

S3.2 Ordering and end-of-stream accounting

For each block, the runner (i) transforms and scores records using the incoming state, (ii) records the four decision outcomes for the evaluator, (iii) requests labels without using their values, (iv) receives the previous block's requested labels, (v) updates memories, and (vi) attempts an atomic transaction for the next block. Labels from a predicted block do not affect any predictions within that block.

There are 355 prediction blocks but 354 update opportunities because no requested labels arrive at the end of block zero. A decision at the end of the final block is recorded and timed, although its resulting state has no subsequent evaluated block. The last 99 requested labels remain pending. This boundary explains why counts of decisions and counts of affected prediction blocks differ. Likewise, the C temporal stratification excludes the two initial prediction blocks without a preceding delayed-label decision.

S3.3 Artifact entry points

The following paths are relative to `adattamento-drift/ton_temporal/` in the repository snapshot. They provide a direct map from the manuscript to implementation and evidence:

- `replay.py`: fixed transformation, additive spline model, logistic head refitting, sampling, and class-aware memory.
- `soglia_bilanciata.py`: strict-threshold convention, candidate construction, exact comparison, and lower-median tie rule.
- `calibrazione_recente.py`: immutable roles, recent-label eligibility, and atomic transaction.
- `replay_validazione_finale.py`: five-seed final replay, paired traces, overlap mask, and aggregate metric definitions.
- `split_manifest.json` and `sovrapposizioni_abcd.json`: chronology, counts, historical exposure, and cross-partition vector checks.
- `articolo_02/protocollo_validazione_finale.md`: protocol fixed before the final predictive campaign.

- `articolo_02/validazione_finale_D/analisi_finale.json`: absolute metrics, paired differences, temporal summaries, and measured costs.
- `adapt04_calibrazione_recente/replay_completo/confronto_per_blocco.csv`: C per-block evidence used in Figure S4.

The manuscript package retains these original summaries and the initial Methods/Results draft. The accompanying extension package adds the complete reports and model artifacts described in Section S5. Rebuilding figures is separate from reconstructing raw data and rerunning the predictive campaign.

S4 Second-review diagnostic design and complete summaries

The diagnostic protocol is fixed in commit `67239e4`, after all first-extension outcomes were known. It defines 120 predictive cells: 80 spline cells (eight settings, two captures, five seeds), ten LR main cells, and 30 forest cells (three conditions, two captures, five seeds). Thirty main cells repeat previous trajectories to check the new runner. They are not additional independent evidence. The first diagnostic attempt was invalidated after a uint8 overflow was found in the guard that determines whether AP is defined. The retained AP diagnostics use the widened integer-count fix and are checked against AUC class-validity coverage, with a dedicated regression test. This affected the new AP diagnostic only; the historical and first-extension reports remain unchanged. The excluded attempt is identified in the provenance log.

S4.1 Operating-point comparisons

Retrospective interpolation uses observed FPR/recall points within each seed's support. It uses no extrapolation. FPR ties retain the larger recall for a matched-FPR description; recall ties retain the smaller FPR for a matched-recall description. The result is a piecewise-linear description of recorded policies, not an estimated deployment frontier. The CSV includes missing comparisons when a target is outside either controller's observed support. Averaging paired interpolations differs from interpolating seed means because the operating-point locations vary across seeds. The

Table S8: Descriptive matched-FPR comparison of the original five cost points on TON D. The paired columns interpolate within each seed, then summarize the supported pairs. Mean-curve columns interpolate curves of seed means. Values are recall percentages; the difference is in percentage points. No comparison extrapolates.

FPR	Pairs	Paired frozen	Paired head	Paired difference	Mean-curve frozen	Mean-curve head
10	4	70.47 ± 10.93	84.23 ± 2.95	13.76 ± 10.45	69.69	84.87
13	5	83.86 ± 2.99	86.27 ± 1.26	2.41 ± 3.11	85.88	86.27
20	5	87.83 ± 1.48	89.86 ± 1.55	2.03 ± 1.72	87.83	89.68

mean-curve and paired-seed summaries describe different operations. At 13% FPR, the paired head-minus-frozen difference is 2.41 ± 3.11 percentage points on this stream, whereas the mean curves nearly coincide. These descriptive calculations do not establish equivalence or superiority in a new stream. The low-FPR comparison has incomplete common support. The denser nine-weight audit is retained as additional operating points, without selecting a weight from D for deployment. With the denser nine-weight grid, the paired head-minus-frozen recall difference at 13% FPR is 1.49 ± 3.66 percentage points (5 supported pairs). This remains a retrospective interpolation within each seed, rather than a threshold selected for a new stream.

S4.2 Model audit and threshold transfer

Model audits verify that label one denotes an attack and higher scores denote greater attack confidence. LR coefficients, decision-function output, and the attack-probability column are checked directly. Cached D scores are checked on 5,000 fixed sampled observations against direct model predictions. Full A/B/D fixed-score metrics and class-specific score quantiles are retained. A metrics describe the training population, not generalization. Chronological ARF initial fitting and its shuffled control use exactly the same sampled row set; only their order changes.

The fixed LR class ordering is $[0, 1]$. Coefficient scores and the attack-probability column agree numerically with the cached score; the full audit records the maximum discrepancies and solver iteration counts. On TON the inversion is already visible on B, before D. This supports poor temporal transfer within the compact feature contract, rather than an implementation that systematically reverses the attack label.

For frozen spline thresholds, the following summaries weight each calibration/next-block pair by the next block's normal count and exclude the initial period before valid calibration. TON, $\lambda = 1$: calibration FPR 42.67%, next-block FPR 48.30%; median distinct normal scores 55. TON, $\lambda = 2$: calibration FPR 8.26%, next-block FPR 13.20%; median distinct normal scores 55. UNSW, $\lambda = 1$: calibration FPR 2.67%, next-block FPR 5.64%; median distinct normal scores 110. UNSW, $\lambda = 2$: calibration FPR 2.36%, next-block FPR 5.16%; median distinct normal scores 110. The calibration and future populations differ; these are descriptive transfer diagnostics, not estimates of independent calibration-sample uncertainty. Distinct scores can be much fewer than retained normal observations.

S4.3 Conditional ranking and precision–recall summaries

AP is noninterpolated average precision. AP is recorded for the main, shuffled, and FIT-only conditions; the seven spline sensitivity conditions retain AUC and confusion counts. Blocks containing only one class are excluded from within-block AUC/AP summaries; their counts and class coverage are explicit in the CSV. Macro AP is not pooled AP, and weighting block AP by class counts does not turn it into pooled AP. Precision at each operating policy is computed from globally summed confusion counts. Comparisons across captures must account for their different prevalence.

Table S9: Ranking summaries, mean ± seed SD conditional on each capture. NW and AW denote normal-count and attack-count weighting of valid blocks. Adaptive rows use the chronological initialization and default controller.

Stream	Model	Score	AUC macro	AUC NW	AP macro	AP NW	AP AW
TON	SPLINE	Frozen	0.850 ± 0.017	0.557 ± 0.004	0.940 ± 0.001	0.466 ± 0.001	0.981 ± 0.001
TON	SPLINE	Adaptive	0.937 ± 0.004	0.715 ± 0.011	0.955 ± 0.001	0.562 ± 0.006	0.989 ± 0.001
TON	LR	Frozen	0.432 ± 0.005	0.566 ± 0.002	0.927 ± 0.001	0.527 ± 0.001	0.961 ± 0.001
TON	LR	Adaptive	0.874 ± 0.009	0.704 ± 0.012	0.954 ± 0.001	0.576 ± 0.008	0.987 ± 0.000
TON	ARF	Frozen	0.540 ± 0.073	0.532 ± 0.032	0.931 ± 0.005	0.477 ± 0.017	0.970 ± 0.004
TON	ARF	Adaptive	0.957 ± 0.005	0.732 ± 0.014	0.959 ± 0.001	0.588 ± 0.010	0.991 ± 0.001
UNSW	SPLINE	Frozen	0.977 ± 0.000	0.977 ± 0.001	0.840 ± 0.006	0.825 ± 0.006	0.894 ± 0.003
UNSW	SPLINE	Adaptive	0.970 ± 0.003	0.969 ± 0.003	0.822 ± 0.008	0.805 ± 0.008	0.888 ± 0.009
UNSW	LR	Frozen	0.921 ± 0.080	0.924 ± 0.072	0.688 ± 0.136	0.670 ± 0.125	0.754 ± 0.175
UNSW	LR	Adaptive	0.944 ± 0.005	0.942 ± 0.005	0.725 ± 0.007	0.701 ± 0.008	0.815 ± 0.005
UNSW	ARF	Frozen	0.505 ± 0.220	0.519 ± 0.215	0.366 ± 0.150	0.364 ± 0.157	0.374 ± 0.128
UNSW	ARF	Adaptive	0.978 ± 0.004	0.977 ± 0.004	0.889 ± 0.008	0.874 ± 0.009	0.943 ± 0.005

Table S10: Forest label and state ledger, mean ± SD conditional on each capture. Learned labels count D arrivals used once for learning, excluding initial A fitting. Final serialized model size excludes external controller memory and is not peak RAM.

Stream	Condition	Acquired labels	Learned labels	Final model MiB
TON	main	35499 ± 0	35400 ± 0	0.53 ± 0.22
TON	shuffled	35499 ± 0	35400 ± 0	0.42 ± 0.18
TON	fit_only	35499 ± 0	26104 ± 58	0.57 ± 0.15
UNSW	main	10160 ± 0	10100 ± 0	3.84 ± 0.67
UNSW	shuffled	10160 ± 0	10100 ± 0	4.63 ± 0.44
UNSW	fit_only	10160 ± 0	7851 ± 42	4.50 ± 0.96

S4.4 Forest feedback and persistent state

Standard and shuffled forests reuse CAL-role labels for learning. The FIT-only condition excludes those labels throughout D, while retaining the same chronological initial state. The acquired budget remains shared even though fewer labels enter learning. Per-seed timings are retained in the CSV; runs execute concurrently, so those timings are audit records rather than a controlled hardware benchmark.

S4.5 Memory, age, eligibility, and role-salt sensitivity

One factor changes at a time. The default is FIT192/CAL64, age 50, minimum five CAL observations per class, and salt `ADAPT04-C-seed42-v1`. Labels continue to arrive after prediction, and all configurations use the same query sequence for each dataset/seed. The age factor also applies to the independent all-label CAL256 control. FIT entries have no age filter. Capacity variants preserve the nominal 3:1 FIT/CAL allocation but change the total retained examples to 128 or 512. Alternative salts are literal `review2-salt-1` and `review2-salt-2`; the same alternative is used for all five seeds. No setting is chosen as a new primary configuration from D results.

Table S11: Spline head/CAL sensitivity. Rates are percentages, mean ± sample SD conditional on each stream. Updates are mean valid transactions. Main denotes the default.

Stream	Changed setting	Recall	FPR	BA	Updates
TON	main	89.46 ± 0.89	19.78 ± 0.77	84.84 ± 0.79	347.8
TON	mem96_32	89.95 ± 0.53	26.98 ± 3.31	81.49 ± 1.89	347.8
TON	mem384_128	89.81 ± 1.14	15.82 ± 1.79	86.99 ± 0.51	347.8
TON	age10	90.33 ± 1.04	22.90 ± 2.04	83.71 ± 1.41	160.4
TON	age100	89.73 ± 0.78	19.67 ± 0.83	85.03 ± 0.79	347.8
TON	min10	87.23 ± 1.11	19.14 ± 0.71	84.04 ± 0.40	327.2
TON	salt1	89.24 ± 2.62	21.34 ± 2.16	83.95 ± 1.50	345.8
TON	salt2	91.53 ± 0.64	13.59 ± 2.51	88.97 ± 1.41	349.0
UNSW	main	96.79 ± 0.14	10.36 ± 0.50	93.22 ± 0.22	100.2
UNSW	mem96_32	96.51 ± 0.50	14.22 ± 1.14	91.14 ± 0.37	100.2
UNSW	mem384_128	96.78 ± 0.20	8.99 ± 0.40	93.89 ± 0.21	100.2
UNSW	age10	96.70 ± 0.18	10.26 ± 0.56	93.22 ± 0.21	100.2
UNSW	age100	96.79 ± 0.14	10.36 ± 0.50	93.22 ± 0.22	100.2
UNSW	min10	96.78 ± 0.17	10.31 ± 0.51	93.24 ± 0.27	97.4
UNSW	salt1	96.47 ± 0.27	11.60 ± 0.94	92.44 ± 0.40	101.0
UNSW	salt2	97.63 ± 0.32	18.38 ± 1.42	89.63 ± 0.73	98.6

S4.6 Complete first-extension default comparisons

The following tables retain all displayed default model comparisons from the first extension. Each seed describes the same captured stream. Frozen LR and chronological ARF quality must be interpreted using the audits in the main paper; the macro AUROC column is accompanied by normal-weighted and pooled summaries elsewhere in this Supplement.

Table S12: TON first-extension defaults. Rates are percentages, mean ± SD conditional on one stream; AUROC is the macro mean over valid prediction blocks.

Controller	Recall	FPR	BA	AUROC
Spline: Frozen / B	20.93 ± 0.37	12.59 ± 0.14	54.17 ± 0.18	0.850 ± 0.017
Spline: Frozen / CAL64	91.37 ± 2.24	47.93 ± 4.68	71.72 ± 1.73	0.850 ± 0.017
Spline: Frozen / CAL256	92.38 ± 1.32	48.14 ± 4.67	72.12 ± 2.42	0.850 ± 0.017
Spline: FIT192 / CAL64	89.46 ± 0.89	19.78 ± 0.77	84.84 ± 0.79	0.937 ± 0.004
LR: Frozen / B	27.00 ± 1.22	76.01 ± 1.45	25.50 ± 0.21	0.432 ± 0.005
LR: Frozen / CAL256	87.20 ± 2.72	43.10 ± 12.33	72.05 ± 5.83	0.432 ± 0.005
LR: FIT192 / CAL64	88.96 ± 1.49	19.36 ± 2.42	84.80 ± 1.84	0.874 ± 0.009
ARF: Frozen / B	16.46 ± 7.19	34.40 ± 17.63	41.03 ± 8.76	0.540 ± 0.073
ARF: Frozen / CAL256	76.32 ± 15.88	40.57 ± 8.27	67.87 ± 8.19	0.540 ± 0.073
ARF: threshold 0.5	97.98 ± 0.15	19.03 ± 2.94	89.47 ± 1.47	0.957 ± 0.005
ARF: threshold B	61.38 ± 30.60	0.31 ± 0.14	80.54 ± 15.25	0.957 ± 0.005
ARF: CAL64	95.95 ± 1.11	20.92 ± 3.05	87.52 ± 1.59	0.957 ± 0.005
ARF: CAL256	96.41 ± 0.64	15.62 ± 1.94	90.39 ± 0.97	0.957 ± 0.005

Table S13: UNSW first-extension defaults, with the same conditional reporting convention.

Controller	Recall	FPR	BA	AUROC
Spline: Frozen / B	94.53 ± 0.11	1.95 ± 0.02	96.29 ± 0.05	0.977 ± 0.000
Spline: Frozen / CAL64	96.63 ± 0.25	9.12 ± 0.72	93.75 ± 0.34	0.977 ± 0.000
Spline: Frozen / CAL256	96.37 ± 0.07	5.53 ± 0.12	95.42 ± 0.06	0.977 ± 0.000
Spline: FIT192 / CAL64	96.79 ± 0.14	10.36 ± 0.50	93.22 ± 0.22	0.970 ± 0.003
LR: Frozen / B	90.16 ± 4.91	6.33 ± 8.87	91.92 ± 2.00	0.921 ± 0.080
LR: Frozen / CAL256	93.82 ± 2.82	10.09 ± 7.18	91.86 ± 2.20	0.921 ± 0.080
LR: FIT192 / CAL64	94.97 ± 0.48	12.20 ± 0.64	91.39 ± 0.49	0.944 ± 0.005
ARF: Frozen / B	47.21 ± 48.03	25.48 ± 42.53	60.87 ± 15.86	0.505 ± 0.220
ARF: Frozen / CAL256	47.57 ± 47.74	26.09 ± 42.15	60.74 ± 15.90	0.505 ± 0.220
ARF: threshold 0.5	86.91 ± 1.65	2.09 ± 0.42	92.41 ± 0.65	0.978 ± 0.004
ARF: threshold B	98.98 ± 0.93	97.73 ± 1.86	50.63 ± 0.65	0.978 ± 0.004
ARF: CAL64	97.21 ± 0.92	8.53 ± 1.62	94.34 ± 0.86	0.978 ± 0.004
ARF: CAL256	96.48 ± 1.03	4.77 ± 0.76	95.86 ± 0.38	0.978 ± 0.004




Figure S5: Spline head/CAL64 minus Frozen/CAL256 at $\lambda = 1$ in the first extension, by representation-recurrence stratum. Points are paired seed means and bars are sample SD on the same stream. Positive recall and negative FPR changes favor the head; concurrent reductions describe fewer false alarms at the expense of recall.

S4.7 Additional first-extension controls

Table S14: Independent CAL64, offset-only and prior-centred spline controls. Mean ± SD describes five randomizations on one stream.

Dataset	Controller	Recall	FPR	BA
TON	Independent CAL64	91.37 ± 2.24	47.93 ± 4.68	71.72 ± 1.73
TON	Offset / B	11.51 ± 7.70	1.70 ± 1.19	54.91 ± 3.49
TON	Offset / CAL64	91.37 ± 2.24	47.93 ± 4.68	71.72 ± 1.73
TON	Prior-centred / CAL64	89.59 ± 1.18	20.74 ± 1.98	84.42 ± 1.13
UNSW	Independent CAL64	96.63 ± 0.25	9.12 ± 0.72	93.75 ± 0.34
UNSW	Offset / B	97.23 ± 0.14	20.42 ± 0.10	88.41 ± 0.04
UNSW	Offset / CAL64	96.63 ± 0.25	9.12 ± 0.72	93.75 ± 0.34
UNSW	Prior-centred / CAL64	96.88 ± 0.15	9.43 ± 0.64	93.72 ± 0.34

Independent CAL64 produces the same outcomes as the matched CAL64 schedule in these main runs. Offset/CAL64 produces the same decisions as frozen/CAL64, as expected from $s + c > \tau + c$ being equivalent to $s > \tau$. The prior-centred refit minimizes summed logistic loss plus $\frac{1}{2}\|w - w_{\text{previous}}\|^2$, with an unpenalized intercept. Its BA is 84.42% on TON and 93.72% on UNSW, compared with 84.84% and 93.22% for the default head. It supplies no uniform remedy across the two captures.

Table S15: First-extension TON delay and budget sensitivity, conditional on the same stream. Default budget is 1%; only the final pair uses 0.1%. Updates include the final transaction without a subsequent evaluated block.

Condition	Controller	Recall	FPR	BA	Updates
Delay 0	Frozen/CAL256	92.69 ± 1.33	46.24 ± 4.93	73.23 ± 2.52	353.2 ± 0.4
Delay 0	FIT192/CAL64	89.62 ± 0.95	17.82 ± 1.02	85.90 ± 0.89	348.8 ± 2.6
Delay 1	Frozen/CAL256	92.38 ± 1.32	48.14 ± 4.67	72.12 ± 2.42	352.2 ± 0.4
Delay 1	FIT192/CAL64	89.46 ± 0.89	19.78 ± 0.77	84.84 ± 0.79	347.8 ± 2.6
Delay 5	Frozen/CAL256	91.22 ± 1.30	46.72 ± 7.96	72.25 ± 4.07	348.2 ± 0.4
Delay 5	FIT192/CAL64	87.96 ± 0.79	22.22 ± 4.11	82.87 ± 1.78	343.8 ± 2.6
Delay 20	Frozen/CAL256	87.07 ± 1.25	37.49 ± 6.06	74.79 ± 3.32	333.2 ± 0.4
Delay 20	FIT192/CAL64	83.32 ± 0.89	23.18 ± 6.65	80.07 ± 3.09	322.4 ± 7.7
Budget 0.1%	Frozen/CAL256	86.22 ± 4.35	27.25 ± 4.71	79.48 ± 4.02	292.4 ± 34.6
Budget 0.1%	FIT192/CAL64	32.13 ± 24.30	17.14 ± 9.81	57.49 ± 7.35	85.6 ± 7.0

S5 Supplementary experimental summaries

Table S16: Extension resource ledger, mean ± seed SD. Times are seconds. Initial artifact size includes the transform; final base-model size excludes it and all external controller state. Neither size is peak RAM. Offline cached replay is not deployment latency.

Dataset	Model	Initial fit	B scoring	D cache	Replay	Initial KiB	Final base KiB
TON	ARF	179.4 ± 7.5	42.5 ± 3.2	160.0 ± 23.0	231.6 ± 8.6	938.7 ± 328.8	543.8 ± 223.9
TON	LR	0.3 ± 0.1	0.7 ± 0.1	1.3 ± 0.1	16.3 ± 1.6	1.0 ± 0.0	0.7 ± 0.0
TON	SPLINE	4.4 ± 0.4	16.4 ± 1.5	11.7 ± 0.7	25.6 ± 1.4	2.1 ± 0.0	1.9 ± 0.0
UNSW	ARF	124.6 ± 8.6	17.2 ± 1.6	29.2 ± 1.8	63.9 ± 4.5	340.5 ± 100.7	$3{,}935.9 \pm 689.1$
UNSW	LR	0.3 ± 0.0	0.1 ± 0.0	0.3 ± 0.0	4.2 ± 0.3	1.0 ± 0.0	0.7 ± 0.0
UNSW	SPLINE	3.1 ± 0.2	1.4 ± 0.1	3.0 ± 0.3	6.7 ± 0.4	2.1 ± 0.0	1.9 ± 0.0

Table S17: Fixed-score ranking summaries in the extension, mean ± seed SD. Pooled AUROC compares all fixed scores; macro block AUROC weights valid blocks equally; normal-weighted AUROC weights them by normal observations. The full CSV includes valid-block counts and all overlap strata.

Dataset	Initial model	Pooled AUROC	Macro block	Normal-weighted block
TON	SPLINE	0.821 ± 0.020	0.850 ± 0.017	0.557 ± 0.004
TON	LR	0.318 ± 0.007	0.432 ± 0.005	0.566 ± 0.002
TON	ARF	0.425 ± 0.023	0.540 ± 0.073	0.532 ± 0.032
UNSW	SPLINE	0.973 ± 0.000	0.977 ± 0.000	0.977 ± 0.001
UNSW	LR	0.922 ± 0.066	0.921 ± 0.080	0.924 ± 0.072
UNSW	ARF	0.439 ± 0.278	0.505 ± 0.220	0.519 ± 0.215

For the resampling lengths in Table S19, the full-stream FN range crosses zero while the FP range remains negative. On unseen vectors the FP and BA ranges cross zero. This reinforces the distinction between an aggregate FP saving and stable joint improvement, but the ranges are conditional summaries of the recorded trajectories. A valid inference about retrained policies under a new process would require a sampling design for that process and rerunning the adaptive state transitions.

S5.1 Numerical bridge and archive contents

The legacy-sampler reruns use exactly the original requested row identities in every block. Their mean FIT192/CAL64 outcomes are close to the original aggregates (the FN difference is -563.0 and the FP difference is -7.4), but individual seeds and some other traces differ materially.

Table S18: Attack-family recall (percent) for the spline detector in the extension. Counts are evaluated attacks, shared by every trace and seed. Means and sample SDs refer to five seeds. The machine-readable supplement includes LR and ARF, each seed, and every operating-cost policy.

Dataset	Attack family	Count	Frozen/B	Frozen/CAL256	FIT192/CAL64
TON	backdoor	508,116	99.96 ± 0.00	99.97 ± 0.00	98.78 ± 1.16
TON	mitm	1,052	4.81 ± 0.33	12.79 ± 1.93	4.77 ± 1.60
TON	password	549,383	19.81 ± 0.01	86.08 ± 3.38	74.39 ± 4.04
TON	ransomware	72,805	9.29 ± 0.00	72.33 ± 14.59	54.56 ± 2.97
TON	xss	2,108,944	2.60 ± 0.57	92.92 ± 1.49	92.38 ± 1.06
UNSW	Analysis	1,459	93.83 ± 0.44	94.37 ± 0.46	93.78 ± 1.24
UNSW	Backdoor	1,390	86.37 ± 0.38	90.04 ± 0.29	92.75 ± 0.41
UNSW	DoS	10,262	86.91 ± 0.39	91.23 ± 0.23	93.83 ± 0.35
UNSW	Exploits	26,423	82.72 ± 0.48	89.05 ± 0.31	90.12 ± 0.61
UNSW	Fuzzers	13,334	76.22 ± 0.47	82.85 ± 0.57	85.01 ± 1.11
UNSW	Generic	149,998	99.45 ± 0.02	99.63 ± 0.01	99.65 ± 0.02
UNSW	Reconnaissance	8,426	87.56 ± 1.51	92.54 ± 0.78	92.36 ± 0.94
UNSW	Shellcode	886	60.93 ± 0.57	77.09 ± 1.15	77.22 ± 1.56
UNSW	Worms	104	72.88 ± 1.43	85.00 ± 2.11	83.65 ± 4.30

Table S19: Descriptive moving-block sensitivity of the original paired FIT192/CAL64 minus Frozen/CAL64 errors. Brackets are 2.5th–97.5th resampling percentiles, not confidence intervals for a refitted adaptive process. Each analysis resamples contiguous blocks of the recorded error trajectories, sharing block selections across seeds and policies.

Scope	Block length	ΔFN (thousands)	ΔFP (thousands)	ΔBA (pp)
All D	5	[-52.96, 35.87]	[-138.85, -32.64]	[8.77, 16.88]
All D	20	[-73.68, 58.34]	[-190.30, -9.77]	[4.97, 17.72]
All D	50	[-94.44, 85.35]	[-217.51, -8.33]	[5.19, 16.47]
Unseen	5	[-94.51, -47.32]	[-19.38, 13.64]	[-3.49, 8.42]
Unseen	20	[-104.59, -36.07]	[-19.62, 19.53]	[-4.19, 10.15]
Unseen	50	[-116.03, -19.18]	[-18.79, 17.03]	[-3.07, 11.29]

For example, the FIT192/B FN difference ranges from −9,617 to +335,381. Accordingly, the original per-seed observations and the newly fitted observations are separate evidence stages. The file `analysis/legacy_replication_bridge.csv` gives every difference; no rerun is presented as bitwise replication.

The original A parser and the extension A parser produce identical arrays and an identical NPZ file in the present environment. The extension also records array-level digests to distinguish data identity from archive-container bytes. Repeating the initial seed-42 fit with NumPy 2.3.4 and SciPy 1.16.3 in Linux gives the same fitted head as the new environment, so library version labels alone do not identify the source of the Windows/Linux difference. An exact causal attribution would require the original arrays and fitted model state. This residual reproducibility boundary is retained rather than explained speculatively.

The revision archive includes all 55 extension reports, the original five full reports, compact fitted initial-model artifacts, input manifests, and a validation summary. `analysis/per_seed_metrics.csv` contains every controller, seed, condition, and overlap stratum; `analysis/paired_differences.csv` preserves paired comparisons. `analysis/attack_family_recall.csv`, `analysis/resources_and_labels.csv`, and `analysis/time_partitions.json` document attack counts, computational components, feedback timing, and chronology. All paper figures and generated tables can be rebuilt from these artifacts without downloading the raw CSVs.

S6 Dataset attributions

The TON provider requests acknowledgement of the network, telemetry, operating-system, architecture, and related botnet publications [2–9]. The UNSW-NB15 provider's associated papers are also retained [10–14]. Their algorithms are not imported as experimental observations. The input manifests distinguish publisher descriptions from hash-identified public mirrors.

References

[1] Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake Vanderplas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, and Édouard Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011. URL https://jmlr.org/papers/v12/pedregosa11a.html.

[2] Nour Moustafa. A new distributed architecture for evaluating AI-based security systems at the edge: Network TON_IoT datasets. *Sustainable Cities and Society*, 72:102994, 2021. doi: 10.1016/j.scs.2021.102994. URL https://doi.org/10.1016/j.scs.2021.102994.

[3] Tim M. Booij, Irina Chiscop, Erik Meeuwissen, Nour Moustafa, and Frank T. H. den Hartog. ToN_IoT: The role of heterogeneity and the need for standardization of features and attack types in IoT network intrusion data sets. *IEEE Internet of Things Journal*, 9(1):485–496, 2022. doi: 10.1109/JIOT.2021.3085194. URL https://doi.org/10.1109/JIOT.2021.3085194.

[4] Abdullah Alsaedi, Nour Moustafa, Zahir Tari, Abdun Mahmood, and Adnan Anwar. TON_IoT telemetry dataset: A new generation dataset of IoT and IIoT for data-driven intrusion detection systems. *IEEE Access*, 8:165130–165150, 2020. doi: 10.1109/ACCESS.2020.3022862. URL https://doi.org/10.1109/ACCESS.2020.3022862.

[5] Nour Moustafa, Marwa Keshk, Essam Debie, and Helge Janicke. Federated TON_IoT Windows datasets for evaluating AI-based security applications. In *IEEE 19th International Conference on Trust, Security and Privacy in Computing and Communications (TrustCom)*, pages 848–855, 2020. doi: 10.1109/TrustCom50675.2020.00114. URL https://doi.org/10.1109/TrustCom50675.2020.00114.

[6] Nour Moustafa, Mohiuddin Ahmed, and Sherif Ahmed. Data analytics-enabled intrusion detection: Evaluations of ToN_IoT Linux datasets. In *IEEE 19th International Conference on Trust, Security and Privacy in Computing and Communications (TrustCom)*, pages 727–735, 2020. doi: 10.1109/TrustCom50675.2020.00100. URL https://doi.org/10.1109/TrustCom50675.2020.00100.

[7] Nour Moustafa. New generations of Internet of Things datasets for cybersecurity applications based machine learning: TON_IoT datasets. In *eResearch Australasia Conference*, Brisbane, Australia, 2019. URL https://research.unsw.edu.au/projects/toniot-datasets.

[8] Nour Moustafa. A systemic IoT-Fog-Cloud architecture for big-data analytics and cyber security systems: A review of fog computing. arXiv:1906.01055, 2019. URL https://arxiv.org/abs/1906.01055.

[9] Javed Ashraf, Marwa Keshk, Nour Moustafa, Mohamed Abdel-Basset, Hasnat Khurshid, Asim D. Bakhshi, and Reham R. Mostafa. IoTBoT-IDS: A novel statistical learning-enabled botnet detection framework for protecting networks of smart cities. *Sustainable Cities and Society*, page 103041, 2021. doi: 10.1016/j.scs.2021.103041. URL https://doi.org/10.1016/j.scs.2021.103041.

[10] Nour Moustafa and Jill Slay. Unsw-nb15: a comprehensive data set for network intrusion detection systems (unsw-nb15 network data set). In *2015 Military Communications and Information Systems Conference (MilCIS)*, page 1–6. IEEE, November 2015. doi: 10.1109/milcis.2015.7348942. URL http://dx.doi.org/10.1109/MilCIS.2015.7348942.

[11] Nour Moustafa and Jill Slay. The evaluation of network anomaly detection systems: Statistical analysis of the unsw-nb15 data set and the comparison with the kdd99 data set. *Information Security Journal: A Global Perspective*, 25(1-3):18–31, January 2016. ISSN 1939-3547. doi: 10.1080/19393555.2015.1125974. URL http://dx.doi.org/10.1080/19393555.2015.1125974.

[12] Nour Moustafa, Jill Slay, and Gideon Creech. Novel geometric area analysis technique for anomaly detection using trapezoidal area estimation on large-scale networks. *IEEE Transactions on Big Data*, 5 (4):481–494, December 2019. ISSN 2372-2096. doi: 10.1109/tbdata.2017.2715166. URL http://dx.doi.org/10.1109/TBDATA.2017.2715166.

[13] Nour Moustafa, Gideon Creech, and Jill Slay. *Big Data Analytics for Intrusion Detection System: Statistical Decision-Making Using Finite Dirichlet Mixture Models*, page 127–156. Springer International Publishing, 2017. ISBN 9783319594392. doi: 10.1007/978-3-319-59439-2_5. URL http://dx.doi.org/10.1007/978-3-319-59439-2_5.

[14] Mohanad Sarhan, Siamak Layeghy, Nour Moustafa, and Marius Portmann. *NetFlow Datasets for Machine Learning-Based Network Intrusion Detection Systems*, page 117–135. Springer International Publishing, 2021. ISBN 9783030728021. doi: 10.1007/978-3-030-72802-1_9. URL http://dx.doi.org/10.1007/978-3-030-72802-1_9.