# m o o i



# Random Light

Designed by Bertjan Pot and introduced in the Moooi collection in 2002, the Random Light has become a best seller right from the beginning. It transmit a feeling of simplicity, softness and a touch of magic in contemporary style.

DesignerBertjan PotYear of design2001

Material fibreglass soaked in epoxy resin, chromed steel pendant

www.moooi.com

Updated: 30 Jul, 2013

# moooi

# detailing



The Random light has a small opening to help with replacing the light bulb.

#### colours



White



Black

# technical (Incandescent version)



E27 x I
60 W MAX type G
Cable length 4M (black)
I 0M cable available on request
Plastic white canopy (white shade)
Plastic black canopy (black shade)



E26 x I
60 W MAX type G
Cable length 4M (black)
10M cable available on request
Chrome canopy

# m o o i

### technical (LED version)



#### small Random LED (CE)

Power consumption 10,3W (30lm/W)
Colour temperature (degrees Kelvin, K) 2600K
(warm white)
Luminous flux ( Lumen, lm) 300lm

#### medium Random LED(CE)

Power consumption 11,7W (41.5lm/W)
Colour temperature (degrees Kelvin, K) 2600K (warm white)
Luminous flux ( Lumen, lm) 485lm

#### general Random LED(CE)

Input voltage of 240V ~ 50Hz/ 60 Hz AC Power supply included in canopy Cable length 4M (black) I 0M cable available on request Plastic white canopy (white shade) Plastic black canopy (black shade)

The average service life of Random light LED is 50,000 hours, while maintaining +70% of the light output.

#### compatible Dimmers (CE):

**SIEMENS** 

manufacturer	type
BERKER	286710
BUSCH JAEGER	6513U-102
ELARI	ATD 315
ELARI	ATD 600R
EPV	PAB 315
INSTA	51190
INSTA	51040
JUNG	225TDE
LUTRON	LPRPM-4A
LUTRON	GRAFIK INTEGRAL XGI
OPUS	852395
PEHA	433HAB
SCHNEIDER	ATD 315
SCHNEIDER	600R

Or similar specifications. Lowest dimming position will be approx. 20% -25% depening on dimmer/ lamp combinations.

Please note when using other dimmers (other types and/or manufacturers) than recommended the dimming curve may not be as fluent, in certain positions flickering or other inconsistencies could occur.

5 TC8 284

www.moooi.com Updated: 30 Jul, 2013





#### medium & small random LED (cULus)

Power consumption 11.3W (42.9lm/W)
Colour temperature (degrees Kelvin, K) 2600K (warm white)
Luminous flux ( Lumen, lm) 485lm

Input voltage of 120V ~ 60Hz AC Power supply included in canopy Cable length 4M (black) 10M cable available on request

Metal matt white canopy (white shade) Metal matt black canopy (black shade)

The average service life of Random light LED is 50,000 hours, while maintaining +70% of the light output.

#### compatible dimmers LED (cULus):

manufacturer	type
LUTRON	SKYLARK SF-12P-277
LUTRON	DVF-103P-277
LUTRON	SKYLARK SF-10P
LUTRON	SKYLARK S-600P
LUTRON	SKYLARK DVF-103P
LEVITON	ILLUMATECH TM Cat.No.IP106
LEVITON	SURESLIDE TM Cat.No.6633-P
LEVITON	SURESLIDE TM Cat. NO.6615-P
JUNG	Licht-Management 225 TDE
JUNG	Licht-Management 225 NV DE
BERKER	Tronic-Drehdimmer 286710
Bodo Ehmann LICHTREGLER	T39.01
CLIPSAL	32E450UDM
CLIPSAL	NO 32E450TM

Or similar specifications. Lowest dimming position will be approx. 20% -25% depening on dimmer/ lamp combinations.

Please note when using other dimmers (other types and/or manufacturers) than recommended the dimming curve may not be as fluent, in certain positions flickering or other inconsistencies could occur.



### packaging

random light small & random light medium & âandom light large random light LED small random light LED medium H II0 cm | 43.3" H 53 cm | 20.9" H 88 cm | 34.6" W II0 cm | 43.3" W 51 cm | 20.1" W 87 cm | 34.3" D 110 cm | 43.3" D 51 cm | 20.1" D 87 cm | 34.3" Colli I/I Colli I/I Colli I/I Product weight: Product weight: Product weight: 2,5 KG | 5,5 lb 1,2 KG | 2,6 lb 1,8 KG | 4 lb With packaging: With packaging: With packaging: 13 KG | 28,7 lb 2,7 KG | 6 lb 6,2 KG | 13,7 lb

# cleaning instructions

Due to the intricacy of the Random light it is advised to regularly use a feather duster to remove dust particles.

www.moooi.com

Updated: 30 Jul, 2013

# m o o i

### dimensions

