

UNIVERSITY OF OSLO

CONTROL OF MOBILE ROBOTS

UNIK4490

---

# **An Unnecessarily Extra Long Convoluted Academic Title That Makes Little Sense**

---

*Authors*

Daniel SANDER ISAKSEN, Eirik  
KVALHEIM and Torgrim R. NÆSS

*Supervisors*

Dr. Kim MATHIASSEN and  
Magnus BAKSAAS

November 21, 2017

## Some Heading



Figure 1: 4 by 4 Rover

The main task of the project was to make the robot move to a desired pose, and this was divided into four subtasks/stages as listed below the following summary:

*A significant portion of the project time was spent on reverse engineering the robot to better understand the system before we could begin implementing our own solutions. We decided to keep the original PID motor control code and write code for odometric localization and posture regulation. Most of the work was done in collaboration with the other group, as we were working on the same robot while trying to get the system up and running. (Note! One important subtask that is not mentioned in the list was to create a system of ROS nodes, for which we had to learn about ROS.)*

1. Implement motor control for each wheel

We started our project by running and reverse engineering the mobile robot together with the other group. As we were not familiar with the system and there were no README or comments the challenges here was: login, run robot, understand the controller and deduce the reason behind the constants in the controller. The implementation of motor control for each wheel was already available in the robots source.

2. Implement odometric localization

3. Implement posture regulation motion control

In general the posture regulation controller takes in the configuration variables,  $q = [x, y, \theta]^T$ , and outputs  $v$  and  $\omega$ . It is assumed that the desired variables are  $q_d = [0, 0, 0]^T$  and the error from  $q_d$  is represented by following variables:

$$\rho = \sqrt{x^2 + y^2}$$

$$\gamma = \text{Atan2}(y, x) - \theta + \pi$$

$$\delta = \gamma + \theta$$

Where  $\rho = ||\vec{e}_p||$  is the distance between current point  $(x, y)$  and desired point  $(0, 0)$ ,  $\gamma$  is the angle between  $\vec{e}_p$  and the sagittal axis of the vehicle and  $\delta$  is the axis between  $\vec{e}_p$  and the x-axis.  $v$  and  $\omega$  are found by:

$$v = k_1 \rho \cos(\gamma) \tag{1}$$

$$\omega = k_2 \gamma + k_1 \frac{\sin(\gamma) \cos(\gamma)}{\gamma} (\gamma + k_3 \delta) \tag{2}$$

In our implementation of the controller we get  $\vec{q}$  from the odometric module and output  $\omega_R$  and  $\omega_L$  to the motor controller. Equations for  $\omega_R$  and  $\omega_L$  expressed by error variables  $\rho$ ,  $\gamma$  and  $\delta$ , by setting the following equations (3) and (4) equal to equations (1) and (2) respectively,

$$v = \frac{r(\omega_R + \omega_L)}{2} \quad (3)$$

$$\omega = \frac{r(\omega_R - \omega_L)}{d} \quad (4)$$

and then solve for  $\omega_R$  and  $\omega_L$  by the inserting method. This yields:

$$\omega_R = \frac{2k_1\rho\cos(\gamma)}{2r} + \frac{dk_2\gamma}{2r} + \frac{d\sin(\gamma)\cos(\gamma)(\gamma + k_3\delta)}{2r\gamma} \quad (5)$$

$$\omega_L = \frac{2k_1\rho\cos(\gamma)}{2r} - \frac{dk_2\gamma}{2r} - \frac{d\sin(\gamma)\cos(\gamma)(\gamma + k_3\delta)}{2r\gamma} \quad (6)$$

4. Move the robot to a pose