

Contents

1	Setting	1
1.1	Header	1
1.2	vimrc	1
1.3	Sublime text	1
2	String	1
2.1	KMP	1
2.2	Aho Chorasick	1
2.3	Suffix array	2
2.4	Manacher’s algorithm	3
2.5	Z algorithm	3
3	Graph & Flow	3
3.1	BCC	3
3.2	Maximum Clique	4
3.3	Hopcroft Karp	4
3.4	Dinic	5
3.5	MCMF	5
3.6	Stoer Wagner	6
3.7	Arborescence	7
3.8	Dominator Tree	7
3.9	Vizing’s Algorithm	8
3.10	LR-flow	8
4	Query	9
4.1	Splay Tree	9
4.2	Link Cut Tree	10
4.3	Mo Hilbert Order	11
4.4	Parallel binary search	11
4.5	Lazy Propagation 1	12
5	Geometry	13
6	Math	13
6.1	FFT	13
6.2	Kirchhoff Theorem	13
6.3	Simplex	13
6.4	Gaussian Elimination	14
6.5	Prime Algorithms	15
7	Miscellaneous	15
7.1	Hungarian	15
7.2	LiChao Tree	17
7.3	Persistence Segment Tree	18

7.4	XOR FFT	18
7.5	NTT	19
7.6	2D FFT	19
7.7	Order Statistic Tree	21
7.8	BITSET	21

1 Setting

1.1 Header

```
#include<bits/stdc++.h>

using namespace std;
typedef long long ll;
typedef unsigned long long ull;
typedef pair<int,int> Pi;
typedef pair<ll,ll> Pll;

#define Fi first
#define Se second
#define pb(x) push_back(x)
#define sz(x) (int)x.size()
#define rep(i, n) for(int i=0;i<n;i++)
#define repp(i, n) for(int i=1;i<=n;i++)
#define all(x) x.begin(), x.end()

#define INF 987654321
#define IINF 654321987654321LL
```

1.2 vimrc

```
syntax on
set nu ai ci si nobk et ar ru nocp hls
set bs=2 ts=4 sw=4 sts=4
set cb=unnamed
set mouse=an
command PS vsp %:r.in|sp %:r.out|vert res 30|wa
command RIO wall|!g++ -O2 -std=c++14 -Wall -lm %:r.cpp && ./a.out < %:r.in > %:r.out
command RI wall|!g++ -O2 -std=c++14 -Wall -lm %:r.cpp && ./a.out < %:r.in
```

1.3 Sublime text

```
{
    "shell_cmd": "g++ -O2 -std=c++11 \"${file}\" -o \"${file_path}/${file_base_name}\" && \"${file_path}/${file_base_name}\" < input.txt",
    "working_dir": "${file_path}",
    "selector": "source.c++",
}
```

## 2 String

### 2.1 KMP

```
vector<int> preprocess(string p){
    int m = p.size();
    vector<int> fail(m);
    fail[0] = 0; int j = 0;
    for(int i=1;i<m;i++){
        while(j>0&&p[i]!=p[j]) j = fail[j-1];
        if( p[i] == p[j] ){
            fail[i] = j+1; j++;
        }else{
            fail[i] = 0;
        }
    }
    return fail;
}

vector<int> kmp(string s, string p){
    auto fail = preprocess(p);
    vector<int> ans; int n = s.size(), m = p.size();
    int j = 0;
    for(int i=0;i<n;i++){
        while(j>0 && s[i]!=p[j]) j = fail[j-1];
        if( s[i] == p[j] ){
            if( j == m-1 ){
                ans.pb(i-m+1); j = fail[j];
            }else{
                j++;
            }
        }
    }
    return ans;
}
```

### 2.2 Aho Chorasick

```
struct AhoCorasick{
    struct Node{
        int fail;
        vector<int> output;
        int children[26];

        Node(){
            for(int i=0;i<26;i++) children[i] = -1;
            fail = -1;
        }
    };

    vector<Node> trie;
    int new_node(){
        Node x;
        trie.push_back(x);
    }
};
```

```
        return (int)trie.size()-1;
    }

    void add(int node, string &s, int idx, int string_num){
        //cout << node << " " << idx << endl;
        if( idx == s.size() ){
            trie[node].output.push_back(string_num);
            return;
        }
        int c = s[idx] - 'a';
        if( trie[node].children[c] == -1 ){
            int next = new_node();
            trie[node].children[c] = next;
        }

        add(trie[node].children[c], s, idx+1, string_num);
    }

    void build(vector<string> v){
        int root = new_node();
        for(int i=0;i<v.size();i++){
            add(root,v[i],0,i);
        }

        queue<int> q;
        q.push(root); trie[root].fail = root;
        while( !q.empty() ){
            int cur = q.front(); q.pop();
            for(int i=0;i<26;i++){
                int next = trie[cur].children[i];
                if( next == -1 ) continue;

                // build fail
                if( cur == root ){
                    trie[next].fail = root;
                }
                else{
                    int x = trie[cur].fail;
                    while( x != root && trie[x].children[i] == -1 ) x = trie[x].fail;
                    if( trie[x].children[i] != -1 ) x = trie[x].children[i];
                    trie[next].fail = x;
                }
                // build output
                int f = trie[next].fail;
                for(auto e : trie[f].output) trie[next].output.push_back(e);
                q.push(next);
            }
        }
    }

    vector<Pi> find(string s){
        int n = (int) s.size();
        int cur = 0, root = 0;
        vector<Pi> ans;
        for(int i=0;i<n;i++){
```

```

        int c = s[i]-'a';
        while( cur != root && trie[cur].children[c] == -1 ) cur = trie[cur].
            fail;
        if( trie[cur].children[c] != -1 ) cur = trie[cur].children[c];

        for(auto e : trie[cur].output){
            ans.push_back({e,i});
        }
    }
    return ans;
};

```

## 2.3 Suffix array

```

// Make sure to add !, #, $, %, & at the end of input string
class SuffixArray{
public:
    int n;
    string s;
    vector<int> rank, temprank, sa, tempsa, c;
    vector<int> lcp;
    SuffixArray(string _s){
        n = _s.size(); s = _s;
        rank.resize(n); temprank.resize(n); sa.resize(n); tempsa.resize(n);
        lcp.resize(n);
        constructSA();
        constructLCP();
    }

    void countingSort(int k){
        int sum = 0, maxi = max(270, n); //ASCII 256
        c.clear(); c.resize(maxi+10);
        for(auto& e : c) e = 0;
        for(int i=0; i<n; i++){
            c[ i+k<n ? rank[i+k] : 0 ] ++;
        }
        for(int i=0; i<maxi; i++){
            int t = c[i]; c[i] = sum; sum += t;
        }
        for(int i=0; i<n; i++) tempsa[ c[ sa[i]+k < n ? rank[sa[i]+k] : 0 ] ++ ]
            = sa[i];
        for(int i=0; i<n; i++) sa[i] = tempsa[i];
    }

    void constructSA(){
        for(int i=0; i<n; i++) rank[i] = s[i];
        for(int i=0; i<n; i++) sa[i] = i;
        for(int k=1; k<n; k<=<1){
            countingSort(k);
            countingSort(0);
            int r = 0;
            temprank[sa[0]] = 0;
            for(int i=1; i<n; i++){
                temprank[sa[i]] = (rank[sa[i]] == rank[sa[i-1]] && rank[sa[i]+k]

```

```

                == rank[sa[i-1]+k] ) ? r : ++r;
            }
            for(int i=0; i<n; i++) rank[i] = temprank[i];
            if( rank[sa[n-1]] == n-1 ) break;
        }
    }

    // lcp Implementation from
    // http://m.blog.naver.com/dark__nebula/220419358547
    void constructLCP(){
        int h = 0;
        for(int i=0; i<n; i++){
            if( rank[i] ){
                int j = sa[rank[i]-1];
                while( s[i+h] == s[j+h] ) h++;
                lcp[rank[i]] = h;
            }
            if( h > 0 ) h--;
        }
    }
};

```

## 2.4 Manacher's algorithm

```

// finds radius of longest palindrome centered at s[i]
// If you also want to find even-length paindromes, use dummy characters
// baab -> #b#a#a#b#
vector<int> ManacherAlgorithm(string s){
    int n = (int) s.size();
    int p = -1, r = -1;
    vector<int> A(n);
    for(int i=0; i<n; i++){
        if( r < i ){
            A[i] = 0;
            int j = 0;
            while( i + A[i] < n && i - A[i] >= 0 && s[ i+A[i] ] == s[ i-A[i] ] )
                A[i]++;
            A[i]--;
        }
        else{
            A[i] = min( A[2*p - i] , r-i );
            while( i + A[i] < n && i - A[i] >= 0 && s[ i+A[i] ] == s[ i-A[i] ] )
                A[i]++;
            A[i]--;
        }

        // update r
        if( r < i + A[i] ){
            r = i + A[i];
            p = i;
        }
    }
}

```

```
    return A;
}
```

## 2.5 Z algorithm

```
// Calculates LCP[i] for all 0 ≤ i < n
vector<int> Zalgorithm(string s){
    int l=0, r=0;
    int n = (int) s.size();
    vector<int> Z(n);
    Z[0] = n;
    for(int i=1; i<n; i++){
        // reset and calculate again
        if( i > r ){
            l = r = i;
            while( r<n && s[r] == s[r-l] ) r++;
            r--;
            Z[i] = r-l+1;
        }

        // extend [l,r]
        else{
            int k = i-l;
            // not enough matching at position k
            if( Z[k] < r-i+1 ) Z[i] = Z[k];
            // enough matching. extend [l,r]
            else{
                l = i;
                while( r<n && s[r] == s[r-l] ) r++;
                r--;
                Z[i] = r-l+1;
            }
        }
    }
    return Z;
};
```

## 3 Graph & Flow

### 3.1 BCC

```
int N,M;
int timer = 0;
vector<int> E[300500];
int vis[300500], low[300500];

// dfs1 is to fill vis(discover time) and low array
int dfs1(int x, int pa){
    vis[x] = ++timer;
    low[x] = vis[x];
    for(auto e : E[x]){
        if( vis[e] ){
```

```
            low[x] = min(low[x], vis[e]);
        }
        else{
            dfs1(e,x);
            low[x] = min(low[x], low[e]);
        }
    }
    return low[x] ;
}

int color = 0;
vector<int> colors[300500], E2[300500];
int vis2[300500];

// dfs2 is to color every nodes
// Store node's colors into colors array
// Store new edges into E2
void dfs2(int x, int pa, int c){
    colors[x].pb(c);
    vis2[x] = 1;
    for(auto e : E[x]){
        if(!vis2[e]){
            // x-e is an articulation edge
            if( low[e] > vis[x] ){
                ++color;
                colors[x].pb(color);
                E2[c].pb(color); E2[color].pb(c);
                dfs2(e,x,color);
            }
            // x-e is not an articulation edge
            else dfs2(e,x,c);
        }
    }
}

int main(){
    geti(N,M);
    repp(i,M){
        int a, b; geti(a,b);
        E[a].pb(b); E[b].pb(a);
    }
    // fill vis & low
    dfs1(1,-1);
    // find out articulation edge and color of nodes
    color = 1;
    dfs2(1,-1,color);
}
```

### 3.2 Maximum Clique

```
ll G[40]; // 0-index
void get_clique(int R = 0, ll P = (1ll<<N)-1, ll X = 0){
    if((P|X) == 0){
        cur = max(cur, R);
        return;
    }
```

```

int u = __builtin_ctzll(P|X);
ll c = P&~G[u];
while(c){
    int v = __builtin_ctzll(c);
    get_clique(R + 1, P&G[v], X&G[v]);
    P ^= 1ll << v;
    X |= 1ll << v;
    c ^= 1ll << v;
}
}

```

### 3.3 Hopcroft Karp

```

namespace Matching{
//matching [1...n] <-> [1...m]
const int MX = 40040, MY = 40040;
vector<int> E[MX];
int xy[MX], yx[MY];
int n, m;

void addE(int x, int y) { E[x].pb(y); }
void setnm(int sn, int sm) { n = sn; m = sm; }

int tdis[MX], que[MX], *dis = tdis + 1;
int bfs() {
    int *fr = que, *re = que;
    for(int i=1;i<=n;i++) {
        if(xy[i] == -1) *fr++ = i, dis[i] = 0;
        else dis[i] = -1;
    }
    dis[-1] = -1;
    while(fr != re) {
        int t = *re++;
        if(t == -1) return 1;
        for(int e : E[t]) {
            if(dis[yx[e]] == -1) dis[yx[e]] = dis[t] + 1, *fr++ = yx[e];
        }
    }
    return 0;
}

int dfs(int x) {
    for(int e : E[x]) {
        if(yx[e] == -1 || (dis[yx[e]] == dis[x] + 1 && dfs(yx[e]))) {
            xy[x] = e;
            yx[e] = x;
            return 1;
        }
    }
    dis[x] = -1;
    return 0;
}

int Do() {
    memset(xy, -1, sizeof xy);

```

```

memset(yx, -1, sizeof yx);

int ans = 0;
while(bfs()) {
    for(int i=1;i<=n;i++) if(xy[i] == -1 && dfs(i)) ++ans;
}
return ans;
}
}

```

```

void solve(){
    int n, m;
    scanf("%d%d", &n, &m);
    Matching::setnm(n, m);
    for(int i=1;i<=n;i++) {
        int x; scanf("%d", &x);
        while(x--) {
            int y; scanf("%d", &y);
            Matching::addE(i, y);
        }
    }
    printf("%d\n", Matching::Do());
}

```

### 3.4 Dinic

```

struct MaxFlowDinic{
    struct Edge{
        // next, inv, residual
        int to, inv; ll res;
    };

    int n;
    vector<vector<Edge>> graph;

    vector<int> lev, work;

    void init(int x){
        n = x+10;
        graph.resize(x+10);
        lev.resize(n); work.resize(n);
    }

    void make_edge(int s, int e, ll cap, ll caprev = 0){
        Edge forward = {e, (int)graph[e].size(), cap};
        Edge backward = {s, (int)graph[s].size(), caprev};
        graph[s].push_back(forward);
        graph[e].push_back(backward);
    }

    bool bfs(int source, int sink){
        queue<int> q;
        for(auto& e : lev) e = -1;
        lev[source] = 0; q.push(source);
    }

```

```

        while(!q.empty()){
            int cur = q.front(); q.pop();
            for(auto e : graph[cur]){
                if(lev[e.to]==-1 && e.res > 0){
                    lev[e.to] = lev[cur]+1;
                    q.push(e.to);
                }
            }
        }
        return lev[sink] != -1;
    }

    ll dfs(int cur, int sink, ll flow){
        if( cur == sink ) return flow;
        for(int &i = work[cur]; i < (int)graph[cur].size(); i++){
            Edge &e = graph[cur][i];
            if( e.res == 0 || lev[e.to] != lev[cur]+1 ) continue;
            ll df = dfs(e.to, sink, min(flow, e.res) );
            if( df > 0 ){
                e.res -= df;
                graph[e.to][e.inv].res += df;
                return df;
            }
        }
        return 0;
    }

    ll solve( int source, int sink ){
        ll ans = 0;
        while( bfs(source, sink) ){
            for(auto& e : work) e = 0;
            while( true ){
                ll flow = dfs(source,sink,54321987654321LL);
                if( flow == 0 ) break;
                ans += flow;
            }
        }
        return ans;
    }
};

```

### 3.5 MCMF

```

struct MCMF{
    struct edge{
        int to, inv, cap, flow, cost;
        int res(){
            return cap - flow;
        }
    };
    vector<vector<edge>> graph;
    vector<int> pv, pe;

```

```

    vector<int> dist, inq;

    void init(int x){
        graph.resize(x+10);
        for(auto& e : graph) e.resize(x+10);
        pv.resize(x+10); pe.resize(x+10);
        dist.resize(x+10);
        inq.resize(x+10);
    }

    void make_edge(int from, int to, int cap, int cost){
        //printf("%d -> %d | cost = %d\n",from,to,cost);
        edge forward = {to, (int)graph[to].size(), cap, 0, cost};
        edge backward = {from, (int)graph[from].size(), 0, 0, -cost};
        graph[from].push_back(forward);
        graph[to].push_back(backward);
    }

    int solve(int source, int sink){
        int ans = 0;
        int totalflow = 0;
        while(true){
            for(auto& e : dist) e = INF;
            for(auto& e : inq) e = 0;
            queue<int> q;
            q.push(source); inq[source] = 1;
            dist[source] = 0;

            while(!q.empty()){
                int cur = q.front(); q.pop();
                inq[cur] = 0;
                for(int i=0;i<(int)graph[cur].size();i++){
                    auto& e = graph[cur][i];
                    if( e.res() > 0 && dist[e.to] > dist[cur] + e.cost ){
                        dist[e.to] = dist[cur] + e.cost;
                        pv[e.to] = cur; pe[e.to] = i;
                        if( inq[e.to] == 0 ){
                            q.push(e.to); inq[e.to] = 1;
                        }
                    }
                }
            }

            if( dist[sink] == INF ) break;

            // add this limit when we don't require maxflow
            //if( dist[sink] > 0 ) break;

            int mnflow = INF;
            for( int v = sink; v != source; v = pv[v] ){
                mnflow = min( mnflow, graph[pv[v]][pe[v]].res() );
            }

            for( int v = sink; v != source; v = pv[v] ){
                int tmp = graph[pv[v]][pe[v]].inv;
                graph[pv[v]][pe[v]].flow += mnflow;

```

```

        graph[v][tmp].flow -= mnflow;
    }
    totalflow += mnflow;
    ans += dist[sink] * mnflow;
}
return ans;
}
};

```

### 3.6 Stoer Wagner

```

// Stoer-Wagner algorithm
struct mincut {
    int n;
    vector<vector<int>> graph;

    void init(int nn) {
        n = nn;
        graph.resize(n, vector<int>(n, 0));
    }

    void addEdge(int u, int v, int w) {
        graph[u][v] += w;
        graph[v][u] += w;
    }

    pair<int, vector<int>> findMincut() {
        vector<vector<int>> weight = graph;
        vector<bool> used(n, 0);
        vector<int> best_cut;
        int best_weight = -1;

        vector<vector<int>> group(n);
        for(int i = 0; i < n; i++)
            group[i].push_back(i);

        for(int phase = n-1; phase >= 0; phase--) {
            int start = 0;
            vector<int> w = weight[start];
            vector<bool> inSet = used;
            inSet[start] = true;
            int prev, last = start;

            for(int i = 0; i < phase; i++) {
                prev = last;
                last = -1;
                for(int j = 0; j < n; j++)
                    if(!inSet[j] && (last == -1 || w[j] > w[last])) last = j;

                if(i < phase-1) {
                    inSet[last] = true;
                    for(int j = 0; j < n; j++)
                        w[j] += weight[last][j];
                }
            }
        }
    }
};

```

```

    } else { // last step - merge two nodes: prev & last
        for(int j = 0; j < n; j++) {
            weight[prev][j] += weight[last][j];
            weight[j][prev] = weight[prev][j];
        }
        used[last] = true;
        group[prev].insert(group[prev].end(), group[last].begin(),
            group[last].end());
        if(best_weight == -1 || w[last] < best_weight) {
            best_weight = w[last];
            best_cut = group[last];
        }
    }
}
return make_pair(best_weight, best_cut);
};

```

### 3.7 Arborescence

```

namespace Arborescence{
    const int MX = 510, INF = 1e9;
    int e[MX][MX], lst[MX][MX];
    vector<int> v[MX], rev[MX], order;
    int was[MX], vst[MX], ans[MX], p[MX];
    vector<pii> G[MX];

    int find(int x){ return p[x] == x? x : p[x] = find(p[x]); }
    void set_graph(int ee[MX][MX]){ memcpy(e, ee, sizeof e); }

    void go(int x) {
        if(vst[x]) return;
        vst[x] = 1;
        for (int to : v[x]) go(to);
        order.pb(x);
    }

    void col(int x, int o) {
        if (was[x]) return;
        was[x] = o;
        for (int to : rev[x]) col(to, o);
    }

    int run(int n, int root) {
        int ret = 0, done = 0;
        for(int i = 1; i <= n; i++) p[i] = i;
        memset(lst, 0, sizeof lst);
        for(int tt = 1; tt <= n; tt++) {
            memset(was, 0, sizeof was);
            memset(vst, 0, sizeof vst);
            for (int i = 1; i <= n; i++) {
                v[i].clear();
                rev[i].clear();
            }
        }
    }
};

```

```

order.clear();

int mn[MX] = {};
for(int i = 1; i <= n; i++) mn[i] = INF;
for (int i = 1; i <= n; i++) if (find(i) != find(root))
    for (int j = 1; j <= n; j++) if(find(i) != find(j))
        mn[find(i)] = min(mn[find(i)], e[j][i]);
for (int i = 1; i <= n; i++) if (find(i) != find(root)) {
    if(find(i) == i) ret += mn[i];
    for (int j = 1; j <= n; j++) if(find(i) != find(j)) e[j][i] -= mn[find(i)];
}
for (int i = 1; i <= n; i++) for (int j = 1; j <= n; j++){
    int a = find(i), b = find(j);
    if (a != b && e[i][j] == 0) {
        lst[i][j] = tt;
        v[a].pb(b);
        rev[b].pb(a);
    }
}
if (done) break;
for (int i = 1; i <= n; i++) if (!vst[i]) go(i);
reverse(order.begin(), order.end());
for(int u : order) if (!was[u]) col(u, u);
done = 1;
for(int i = 1; i <= n; i++) if(was[i] != i) done = 0, p[i] = was[i];
}
priority_queue<t3, vector<t3>, greater<t3>> Q;

memset(ans, -1, sizeof ans);
ans[root] = 0;
for(int i = 1; i <= n; i++) for(int j = 1; j <= n; j++)
    if(e[i][j] == 0) G[i].emplace_back(lst[i][j], j);
for(pii c : G[root]) Q.emplace(c.first, root, c.second);
while(Q.size()){
    int a, b; tie(ignore, a, b) = Q.top(); Q.pop();
    if(ans[b] != -1) continue;
    ans[b] = a;
    for(pii c : G[b]) Q.emplace(c.first, b, c.second);
}
return ret;
}
};
;

```

### 3.8 Dominator Tree

```

#include<vector>
using namespace std;
#define pb(x) push_back(x)
namespace dtree{
const int MAXN = 100010;
vector <int> E[MAXN];
vector <int> RE[MAXN], rdom[MAXN];

```

```

int S[MAXN], RS[MAXN], cs;
int par[MAXN], val[MAXN];
int sdom[MAXN], rp[MAXN];
int dom[MAXN];

int Find(int x, int c = 0) {
    if(par[x] == x) return c ? -1 : x;
    int p = Find(par[x], 1);
    if(p == -1) return c ? par[x] : val[x];
    if(sdom[val[x]] > sdom[val[par[x]]]) val[x] = val[par[x]];
    par[x] = p;
    return c ? p : val[x];
}

void Union(int x, int y) {
    par[x] = y;
}

void dfs(int x) {
    RS[ S[x] = ++cs ] = x;
    par[cs] = sdom[cs] = val[cs] = cs;
    for(int e : E[x]) {
        if(S[e] == 0) dfs(e), rp[S[e]] = S[x];
        RE[S[e]].pb(S[x]);
    }
}

int Do(int s, int *up) {
    dfs(s);
    for(int i=cs;i--){
        for(int e : RE[i]) sdom[i] = min(sdom[i], sdom[Find(e)]);
        if(i > 1) rdom[sdom[i]].pb(i);
        for(int e : rdom[i]) {
            int p = Find(e);
            if(sdom[p] == i) dom[e] = i;
            else dom[e] = p;
        }
        if(i > 1) Union(i, rp[i]);
    }
    for(int i=2;i<=cs;i++) if(sdom[i] != dom[i]) dom[i] = dom[dom[i]];
    for(int i=2;i<=cs;i++) {
        up[RS[i]] = RS[dom[i]];
    }
    return cs;
}

void addE(int x, int y) { E[x].pb(y); }
}

```

### 3.9 Vizing's Algorithm

```

// Color every edge in G with (max degree)+1 colors.
// Edges with shared vertex must have distinct colors.

```

```

typedef pair<int,int> pii;

```



```

const int MX = 2505;
int C[MX][MX] = {}, G[MX][MX] = {};

void solve(vector<pii> &E, int N, int M){
    int X[MX] = {}, a, b;

    auto update = [&](int u){ for(X[u] = 1; C[u][X[u]]; X[u]++); };
    auto color = [&](int u, int v, int c){
        int p = G[u][v];
        G[u][v] = G[v][u] = c;
        C[u][c] = v; C[v][c] = u;
        C[u][p] = C[v][p] = 0;
        if( p ) X[u] = X[v] = p;
        else update(u), update(v);
        return p; };
    auto flip = [&](int u, int c1, int c2){
        int p = C[u][c1], q = C[u][c2];
        swap(C[u][c1], C[u][c2]);
        if( p ) G[u][p] = G[p][u] = c2;
        if( !C[u][c1] ) X[u] = c1;
        if( !C[u][c2] ) X[u] = c2;
        return p; };

    for(int i = 1; i <= N; i++) X[i] = 1;
    for(int t = 0; t < E.size(); t++){
        int u = E[t].first, v0 = E[t].second, v = v0, c0 = X[u], c = c0, d;
        vector<pii> L;
        int vst[MX] = {};
        while(!G[u][v0]){
            L.emplace_back(v, d = X[v]);
            if(!C[v][c]) for(a = (int)L.size()-1; a >= 0; a--) c = color(u, L[a].first, c);
            else if(!C[u][d])for(a=(int)L.size()-1;a>=0;a--)color(u,L[a].first,L[a].second);
            else if( vst[d] ) break;
            else vst[d] = 1, v = C[u][d];
        }
        if( !G[u][v0] ){
            for(;v; v = flip(v, c, d), swap(c, d));
            if(C[u][c0]){
                for(a = (int)L.size()-2; a >= 0 && L[a].second != c; a--);
                for(; a >= 0; a--) color(u, L[a].first, L[a].second);
            } else t--;
        }
    }
}

```

### 3.10 LR-flow

G has a feasible (s,t)-flow iff G' has a saturating (s',t')-flow  
in G' total capacity out of s' and into t' are both D (sum of demands)  
saturating flow : flow with value exactly D.

1. Make new source, new sink (s', t')

2. for every v:  
 $c'(s' \rightarrow v) = \sum \{ d(u \rightarrow v) \}$  (give demands into v)  
 $c'(v \rightarrow t') = \sum \{ d(v \rightarrow w) \}$  (take demands out of v)

3. for every u->v:  
 $c'(u \rightarrow v) = c(u \rightarrow v) - d(u \rightarrow v)$  (difference of cap, demand)

3. make t->s cap:INF

## 4 Query

### 4.1 Splay Tree

```

const int N_ = 2e5;
const int inf = ~0u>>1;

```

```

struct node{
    inline void pushdown()
    {
        if( rev ){
            if( link[0] ) link[0]->rev ^= 1;
            if( link[1] ) link[1]->rev ^= 1;
            swap( link[0], link[1] );
            rev = 0;
        }
        if( add ){
            if( link[0] ) link[0]->add += add, link[0]->mn += add, link[0]->val += add;
            if( link[1] ) link[1]->add += add, link[1]->mn += add, link[1]->val += add;
            add = 0;
        }
    }

    inline void pushup()
    {
        cnt = (link[0]? link[0]->cnt:0) + (link[1]? link[1]->cnt:0) + 1;
        mn = min( val, min(link[0]?link[0]->mn:inf, link[1]?link[1]->mn:inf));
    }

    int cnt, add, mn, val; //cnt: number of nodes
    bool rev;
    node *link[2], *par;
};

```

```

struct splaytree{
    node N[ N_ ];
    node* root;
    int sz;

    node* operator[](int idx){ return N + idx; }

    void clear(int s){
        sz = 0;
    }
}

```

```

    for(int i=0;i<=s+2;i++){
        N[i].link[0] = N[i].link[1] = N[i].par = 0, N[i].cnt = 1;
        N[i].rev = false;
    }
// dummy nodes can remove many null-pointer exceptions
    root = N+s+1; root->cnt = 2;
    N[s+2].par = N+s+1; N[s+1].link[1] = N+s+2;
}

inline int dir(node *x){ return x->par->link[0] != x; }
inline int cnt(node* p){ return p? p->cnt: 0; }

void rotate(node *n) // To
{
    n->par->pushdown(); n->pushdown();
    node *p = n->par;
    int d = dir(n);
    p->link[d] = n->link[!d]; if( n->link[!d] ) n->link[!d]->par = p;
    n->par = p->par; if( p->par ) p->par->link[ dir(p) ] = n;
    n->link[!d] = p; p->par = n;
    p->pushup(); n->pushup();
}

void splay(node *x, node *f){
    if( x == f ) return;
    while(x->par != f){
        x->par->pushdown();
        if( x->par->par == f );
        else if(dir(x) == dir(x->par)) rotate(x->par);
        else rotate(x);
        rotate(x);
    }
    x->pushdown();
    if( f == NULL ) root = x;
}
// 1-index if dummy node exists
node* kth_splay(int k,node* f)
{
    node *x = root;
    x->pushdown();
    while( cnt( x->link[0] ) != k ){
        if( cnt( x->link[0] ) < k ){
            if( !x->link[1] ) return x;
            k -= cnt(x->link[0]) + 1, x = x->link[1];
        }
        else x = x->link[0];
        x->pushdown();
    }
    splay( x, f );
    return x;
}
// 1-index if dummy nodes exist
// recommend: 'dont copy & paste code below.
// be careful if dummy nodes 'dont exist (ex. null-pointer exception)
void insert(int wi, node *n)
{

```

```

    if( !root ){
        root = n;
        return;
    }
    kth_splay(wi-1, 0);
    kth_splay(wi, root);
    root->link[1]->link[0] = n; n->par = root->link[1];
    root->link[1]->pushup(); root->pushup();
}

void Delete(int x){
    kth_splay(x-1,0);
    kth_splay(x+1,root);
    root->link[1]->link[0] = NULL;
    root->link[1]->pushup(); root->pushup();
}

void Reverse(int x,int y){
    if( x > y ) return;
    kth_splay(x-1,0);
    kth_splay(y+1,root);
    root->link[1]->link[0]->rev ^= 1;
}

void revolve(int x,int y,int T){ // rotate x~y T times
    if( x >= y ) return;
    int l = (y-x+1);
    T = (T%l+l) % l;
    Reverse(x,y-T);
    Reverse(y-T+1,y);
    Reverse(x,y);
}

int node_address(int wi)
{
    node *p = N+wi;
    splay(p, 0);
    return cnt( p->link[0] );
}

int min(int x,int y){
    kth_splay(x-1,0);
    kth_splay(y+1,root);
    return root->link[0]->link[1]->mn;
}
} pre, post;

```

## 4.2 Link Cut Tree

```

#define _CRT_SECURE_NO_WARNINGS
#include<algorithm>
#include<stdio.h>

using namespace std;
const int N_ = 2e5;

```

```

struct node{
    void pushup(){
        cnt = (link[0]? link[0]->cnt:0) + (link[1]? link[1]->cnt:0) + 1;
        mx = max( max( link[0]? link[0]->mx:0, link[1]? link[1]->mx:0 ), val);
    }

    int cnt, val, mx; //cnt: number of nodes
    node *link[2], *par, *path_parent;
};

struct linkcuttree{
    node N[ N_ ];

    void clear(int s){
        for(int i=0;i<=s;i++){
            N[i].link[0] = N[i].link[1] = N[i].par = N[i].path_parent = 0, N[i].cnt = 1;
        }

        inline int dir(node *x){ return x->par->link[0] != x; }
        inline int cnt(node *x){ return x?x->cnt:0; }
        inline int mx(node *x){ return x?x->mx:0; }

        void rotate(node *n) // To
        {
            if( !n->par ) return;
            node *p = n->par;
            int d = dir(n);
            n->path_parent = p->path_parent; p->path_parent = NULL;
            p->link[d] = n->link[!d]; if( n->link[!d] ) n->link[!d]->par = p;
            n->par = p->par; if( p->par ) p->par->link[ dir(p) ] = n;
            n->link[!d] = p; p->par = n;
            p->pushup(); n->pushup();
        }

        void splay(node *x){
            while( x->par ){
                if( !x->par->par );
                else if(dir(x) == dir(x->par)) rotate(x->par);
                else rotate(x);
                rotate(x);
            }
        }

        void access(node* x)
        {
            splay(x);
            if( x->link[1] ) x->link[1]->path_parent = x, x->link[1]->par = NULL;
            x->link[1] = NULL; x->pushup();
            while( x->path_parent ){
                node *pp = x->path_parent, *r;
                splay(pp);
                r = pp->link[1];
                if( r ) r->par = NULL, r->path_parent = pp;
                pp->link[1] = x; pp->pushup(); x->par = pp;
            }
        }
    }

```

```

        x->path_parent = NULL;
        splay(x);
    }
}

void cut(int u)
{
    access(N+u);
    if( N[u].link[0] ) N[u].link[0]->par = NULL;
    N[u].link[0] = NULL; N[u].pushup();
}

void link(int u, int v) // u must be root.
{
    if( u == v ) return;
    access(N+u);
    access(N+v);
    //assert(!N[u].link[0]);
    N[u].link[0] = N+v; N[v].par = N+u; N[u].pushup();
}

// recommend: 'dont copy & paste code below.
int read(int u)
{
    access( N+u );
    return N[u].cnt;
}

int root(int u)
{
    access( N+u );
    node* ans = N+u;
    while( ans->link[0] ) ans = ans->link[0];
    splay(ans);
    return ans - N;
}

int mx(int u)
{
    access( N+u );
    return N[u].mx;
}

bool chk()
{
    for(int i=0;i<N_;i++){
        if( N[i].cnt == 0 ) return true;
        if( N[i].cnt != cnt(N[i].link[0]) + cnt(N[i].link[1]) + 1 ) return false;
        if( N[i].mx != max( max( mx(N[i].link[0]), mx(N[i].link[1]) ), N[i].val ) )
            return false;
        if( N[i].par && N+i != N[i].par->link[dir(N+i)] ) return false;
        if( N[i].link[0] && N+i != N[i].link[0]->par ) return false;
        if( N[i].link[1] && N+i != N[i].link[1]->par ) return false;
    }
    return true;
}

```

```
}LCT;
```

### 4.3 Mo Hilbert Order

```
inline int64_t gilbertOrder(int x, int y, int pow, int rotate) {
    if (pow == 0) {
        return 0;
    }
    int hpow = 1 << (pow-1);
    int seg = (x < hpow) ? (
        (y < hpow) ? 0 : 3
    ) : (
        (y < hpow) ? 1 : 2
    );
    seg = (seg + rotate) & 3;
    const int rotateDelta[4] = {3, 0, 0, 1};
    int nx = x & (x ^ hpow), ny = y & (y ^ hpow);
    int nrot = (rotate + rotateDelta[seg]) & 3;
    int64_t subSquareSize = int64_t(1) << (2*pow - 2);
    int64_t ans = seg * subSquareSize;
    int64_t add = gilbertOrder(nx, ny, pow-1, nrot);
    ans += (seg == 1 || seg == 2) ? add : (subSquareSize - add - 1);
    return ans;
}

struct Query {
    int l, r, idx;
    int64_t ord;

    inline void calcOrder() {
        ord = gilbertOrder(l, r, 21, 0);
    }
};

inline bool operator<(const Query &a, const Query &b) {
    return a.ord < b.ord;
}
```

### 4.4 Parallel binary search

```
int N,M,K,Q;

vector<Pi> edge[1000500];
int pa[MAXN]; int sz[MAXN];

// each query's answer
Pi ans[MAXN];
// each query's possible answer range for binary search
int low[MAXN], high[MAXN];
// focus[x] : list of query # where it's mid value is x
vector<int> focus[1000500];

int find(int x){
    if( x == pa[x] ) return x;
```

```
    return pa[x] = find(pa[x]);
}
int x[MAXN], y[MAXN];

void uni(int a, int b){
    a = find(a); b = find(b);
    if( a == b ) return;
    pa[a] = b;
    sz[b] += sz[a];
}

int main(void){
    //ios::sync_with_stdio(false);
    geti(N,M);
    int C = -1;
    repp(i,M){
        int a,b,c; geti(a,b,c);
        edge[c].push_back({a,b});
        C = max(C, c);
    }

    geti(Q);
    repp(i,Q){
        int a,b;
        geti(a,b); x[i] = a; y[i] = b;
        ans[i] = {INF,-1};
        // Initially, every query has answer in [0,C] range
        low[i] = 0; high[i] = C;
    }

    bool changed = true;
    while( changed ){
        changed = false;

        // Clear variables
        rep(i,C+1) focus[i].clear();
        repp(i,N) pa[i] = i, sz[i] = 1;

        // Put each query into corresponding focus group
        repp(i,Q){
            if( low[i] > high[i] ) continue;
            focus[ (low[i] + high[i])/2 ].push_back(i);
        }

        // for every time 0~C
        for(int k=0;k<=C;k++){
            // perform action of that time
            for(auto e : edge[k]) uni(e.Fi,e.Se);

            // for each focus group
            // determine it's answer & next position
            for(auto e : focus[k]){
                changed = true;
                int a = x[e]; int b = y[e];
                if( find(a) == find(b) ){
                    ans[e].Fi = min(ans[e].Fi, k);
                }
            }
        }
    }
}
```

```

        ans[e].Se = sz[find(a)];
        high[e] = k-1;
    }
    else{
        low[e] = k+1;
    }
}
}

repp(i,Q){
    if( ans[i].Fi == INF ) printf("%d\n",-1);
    else printf("%d %d\n",ans[i].Fi, ans[i].Se);
}
}

```

## 4.5 Lazy Propagation 1

```

struct segTree{
    struct Node{
        ll d, lazy;
    };
    vector<Node> data;
    int n;
    void init(int x){
        n = 1; while( n < x ) n *= 2;
        data.resize(n*2+10);
    }
    void propagate(int node, int nodeL, int nodeR){
        if( data[node].lazy == 0 ) return;
        ll len = nodeR - nodeL + 1;
        data[node].d += len*data[node].lazy;
        if( len > 1 ){
            data[node*2].lazy += data[node].lazy;
            data[node*2+1].lazy += data[node].lazy;
        }
        data[node].lazy = 0;
    }

    void update(int l, int r, ll val, int node, int nodeL, int nodeR){
        propagate(node, nodeL, nodeR);
        if( l > nodeR || r < nodeL ) return;
        if( l <= nodeL && nodeR <= r ){
            data[node].lazy += val;
            propagate(node,nodeL,nodeR);
            return;
        }
        update(l,r,val,node*2,nodeL,(nodeL+nodeR)/2);
        update(l,r,val,node*2+1,(nodeL+nodeR)/2+1,nodeR);
        data[node].d = data[node*2].d + data[node*2+1].d;
    }

    ll query(int l, int r, int node, int nodeL, int nodeR){
        propagate(node, nodeL, nodeR);

```

```

        if( l > nodeR || r < nodeL ) return 0;
        if( l <= nodeL && nodeR <= r ){
            return data[node].d;
        }
        ll sum = 0;
        sum += query(l,r,node*2,nodeL,(nodeL+nodeR)/2);
        sum += query(l,r,node*2+1,(nodeL+nodeR)/2+1,nodeR);
        return sum;
    }
};

```

## 5 Geometry

## 6 Math

### 6.1 FFT

```

#include <cmath>
#include <complex>
using namespace std;
typedef pair<int,int> pii;
typedef complex<double> base;

void fft(vector<base> &a, bool invert){
    int n = a.size();
    for(int i=1,j=0;i<n;i++){
        int bit = n >> 1;
        for (;j=bit;bit>>=1)j -= bit;
        j += bit;
        if (i < j) swap(a[i], a[j]);
    }
    for(int len=2;len<=n;len<=1){
        double ang = 2*acos(-1)/len*(invert?-1:1);
        base wlen(cos(ang),sin(ang));
        for(int i=0;i<n;i+=len){
            base w(1);
            for(int j=0;j<len/2;j++){
                base u = a[i+j], v = a[i+j+len/2]*w;
                a[i+j] = u+v;
                a[i+j+len/2] = u-v;
                w *= wlen;
            }
        }
    }
    if (invert) {
        for(int i=0;i<n;i++) a[i] /= n;
    }
}

void multiply(const vector<int> &a, const vector<int> &b, vector<int> &res){
    vector<base> fa(a.begin(), a.end()), fb(b.begin(),b.end());

```

```

int n = 1;
while(n < max(a.size(), b.size())) n <= 1;
n <= 1;
fa.resize(n); fb.resize(n);
fft(fa,false);fft(fb,false);
for(int i=0;i<n;i++) fa[i] *= fb[i];
fft(fa,true);
res.resize(n);
for(int i=0;i<n;i++) res[i] = int(fa[i].real() + (fa[i].real() > 0 ? 0.5 :
-0.5));
}

```

## 6.2 Kirchhoff Theorem

Find number of MST in given graph G.

$m[i][j] := -(\text{number of } i \leftrightarrow j \text{ edges}) \ (i \neq j)$

$m[i][i] := \text{degree of vertex } i$

$(\text{ans}) = (\det \text{ of } (n-1) \times (n-1) \text{ matrix obtained from } m \text{ with first row \& col deleted})$

(의 m 첫번째행과 첫번째열을 없앤  $(n-1)$  by  $(n-1)$  의 matrix 행렬식)

## 6.3 Simplex

```

/*
LP Duality
tableau 를 대각선으로 뒤집고 음수 부호를 붙인 답 = -(원문제의 답)
ex) n = 2, m = 3, a = [[0.5, 2, 1], [1, 2, 4]], b = [24, 60], c = [6, 14, 13]
<=> n = 3, m = 2, a = [[-0.5, -1], [-2, -2], [-1, -4]], b = [-6, -14, -13], c =
[-24, -60]

```

```

n := number of variables
m := number of constraints
a[1~m][1~n] := constraints
b[1~m] := constraints value (b[i] can be negative)
c[1~n] := maximum coefficient
v := results
sol[i] := 등호조건, i 번째 변수의 값
ex) Maximize p = 6x + 14y + 13z
Constraints: 0.5x + 2y + z ≤ 24
             x + 2y + 4z ≤ 60
             n = 2, m = 3, a = [[0.5, 2, 1], [1, 2, 4]], b = [24, 60], c = [6, 14, 13]
*/

```

```

namespace simplex {
using T = long double;
const int N = 410, M = 30010;
const T eps = 1e-7;
int n, m;
int Left[M], Down[N];
T a[M][N], b[M], c[N], v, sol[N];

bool eq(T a, T b) { return fabs(a - b) < eps; }
bool ls(T a, T b) { return a < b && !eq(a, b); }

```

```

void init(int p, int q) {
n = p; m = q; v = 0;
for(int i = 1; i <= m; i++){
for(int j = 1; j <= n; j++) a[i][j]=0;
}
for(int i = 1; i <= m; i++) b[i]=0;
for(int i = 1; i <= n; i++) c[i]=sol[i]=0;
}

```

```

void pivot(int x,int y) {
swap(Left[x], Down[y]);
T k = a[x][y]; a[x][y] = 1;
vector<int> nz;
for(int i = 1; i <= n; i++){
a[x][i] /= k;
if(!eq(a[x][i], 0)) nz.push_back(i);
}
b[x] /= k;

for(int i = 1; i <= m; i++){
if(i == x || eq(a[i][y], 0)) continue;
k = a[i][y]; a[i][y] = 0;
b[i] -= k*b[x];
for(int j : nz) a[i][j] -= k*a[x][j];
}
if(eq(c[y], 0)) return;
k = c[y]; c[y] = 0;
v += k*b[x];
for(int i : nz) c[i] -= k*a[x][i];
}

```

// 0: found solution, 1: no feasible solution, 2: unbounded

```

int solve() {
for(int i = 1; i <= n; i++) Down[i] = i;
for(int i = 1; i <= m; i++) Left[i] = n+i;
while(1) { // Eliminating negative b[i]
int x = 0, y = 0;
for(int i = 1; i <= m; i++) if (ls(b[i], 0) && (x == 0 || b[i] < b[x])) x = i;
if(x == 0) break;
for(int i = 1; i <= n; i++) if (ls(a[x][i], 0) && (y == 0 || a[x][i] < a[x][y])) y = i;
if(y == 0) return 1;
pivot(x, y);
}
while(1) {
int x = 0, y = 0;
for(int i = 1; i <= n; i++)
if (ls(0, c[i]) && (!y || c[i] > c[y])) y = i;
if(y == 0) break;
for(int i = 1; i <= m; i++)
if (ls(0, a[i][y]) && (!x || b[i]/a[i][y] < b[x]/a[x][y])) x = i;
if(x == 0) return 2;
pivot(x, y);
}
for(int i = 1; i <= m; i++) if(Left[i] <= n) sol[Left[i]] = b[i];
}

```

```

    return 0;
}
}

```

## 6.4 Gaussian Elimination

```

#define MAX_N 300 // adjust this value as needed
struct AugmentedMatrix { double mat[MAX_N][MAX_N + MAX_N + 10]; };
struct ColumnVector { double vec[MAX_N]; };

// 0 indexed row and column
AugmentedMatrix GaussianElimination(int N, AugmentedMatrix Aug) {
    // input: N X 2N matrix [A I], output: [I invA]

    // forward eliminataion phase
    for(int i=0;i<N;i++){
        int l = i;
        // which row has largest column value
        for(int j=i+1;j<N;j++){
            if( fabs(Aug.mat[j][i]) > fabs(Aug.mat[l][i]) )
                l = j;
        }
        // swap this pivot row to minimize error
        for(int k=i;k<2*N;k++){
            swap(Aug.mat[i][k],Aug.mat[l][k]);
        }
        // calculate forward elimination
        for(int j=i+1;j<N;j++){
            for(int k=2*N-1;k>=i;k--){
                Aug.mat[j][k] -= Aug.mat[i][k] * Aug.mat[j][i] / Aug.mat[i][i];
            }
        }

        // normalize pivots
        for(int i=0;i<N;i++){
            for(int j=2*N-1;j>=i;j--){
                Aug.mat[i][j] /= Aug.mat[i][i];
            }
        }

        // backward elimination
        for(int i=N-1;i>0;i--){
            for(int j=i-1;j>=0;j--){
                for(int k=2*N-1;k>=i;k--){
                    Aug.mat[j][k] -= Aug.mat[i][k] * Aug.mat[j][i] / Aug.mat[i][i];
                }
            }
        }

        return Aug;
    }
}

int main() {
    AugmentedMatrix Aug;
    int N; geti(N);
    rep(i,N) rep(j,N) scanf("%lf",&Aug.mat[i][j]);
    for(int i=N;i<2*N;i++) Aug.mat[i-N][i] = 1;

    AugmentedMatrix res = GaussianElimination(N, Aug);

    // Print inversion of A

```

```

    for(int i=0;i<N;i++){
        for(int j=N;j<2*N;j++) printf("%f ",res.mat[i][j]);
        printf("\n");
    }

```

```

    return 0;
}

```

## 6.5 Prime Algorithms

```

typedef long long ll;
using namespace std;

ll gcd(ll a, ll b) {
    if (b == 0)
        return a;
    return gcd(b, a%b);
}

namespace miller_rabin {
    ll mul(ll x, ll y, ll mod) { return (__int128)x * y % mod; }
    //ll mul(ll x, ll y, ll mod) { return x * y % mod; }
    ll ipow(ll x, ll y, ll p) {
        ll ret = 1, piv = x % p;
        while (y) {
            if (y & 1) ret = mul(ret, piv, p);
            piv = mul(piv, piv, p);
            y >>= 1;
        }
        return ret;
    }
    bool miller_rabin(ll x, ll a) {
        if (x % a == 0) return 0;
        ll d = x - 1;
        while (1) {
            ll tmp = ipow(a, d, x);
            if (d & 1) return (tmp != 1 && tmp != x - 1);
            else if (tmp == x - 1) return 0;
            d >>= 1;
        }
    }
    bool isprime(ll x) {
        for (auto &i : { 2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37 }) {
            if (x == i) return 1;
            if (x > 40 && miller_rabin(x, i)) return 0;
        }
        if (x <= 40) return 0;
        return 1;
    }
}

namespace pollard_rho {
    ll f(ll x, ll n, ll c) {
        return (c + miller_rabin::mul(x, x, n)) % n;
    }
}

```

```

void rec(ll n, vector<ll> &v) {
    if (n == 1) return;
    if (n % 2 == 0) {
        v.push_back(2);
        rec(n / 2, v);
        return;
    }
    if (miller_rabin::isprime(n)) {
        v.push_back(n);
        return;
    }
    ll a, b, c;
    while (1) {
        a = rand() % (n - 2) + 2;
        b = a;
        c = rand() % 20 + 1;
        do {
            a = f(a, n, c);
            b = f(f(b, n, c), n, c);
        } while (gcd(abs(a - b), n) == 1);
        if (a != b) break;
    }
    ll x = gcd(abs(a - b), n);
    rec(x, v);
    rec(n / x, v);
}
vector<ll> factorize(ll n) {
    vector<ll> ret;
    rec(n, ret);
    sort(ret.begin(), ret.end());
    return ret;
}
};

int main() {
    vector<ll> res;
    ll num;
    scanf("%lld", &num);
    res = pollard_rho::factorize(num);
    for (int i = 0; i < res.size(); ++i)
        printf("%lld\n", res[i]);
}

```

## 7 Miscellaneous

### 7.1 Hungarian

/\*  
Tests  
<http://www.spoj.com/problems/GREED/>  
<https://www.acmicpc.net/problem/8992>  
SRM 506 mid

Time complexity  $O(n^3)$

Usage  
MinWeightBipartiteMatch matcher(n);  
for (int i = 0; i < n; i++) for (int j = 0; j < n; j++) matcher.weights[i][j] = SOMETHING;  
cost\_t total = matcher.solve();

See matcher.match(row -> col) and matcher.matched(col -> row) for actual match \*/

```

struct MinWeightBipartiteMatch
{
    typedef long long cost_t;

    cost_t max_cost() const { return numeric_limits<cost_t>::max(); }

    // input
    int n;
    vector<vector<cost_t>> weights;
    // output
    vector<int> match, matched;

    MinWeightBipartiteMatch(int n) :
        n(n), match(n), matched(n), weights(n, vector<cost_t>(n))
    {
    }

    void resize(int n) {
        this->n = n;
        match.resize(n);
        matched.resize(n);
        weights.resize(n);
        for (int i = 0; i < n; i++) {
            weights[i].resize(n);
        }
    }

    /* for solve() */
    vector<cost_t> slack;
    vector<cost_t> potential_row, potential_col;
    vector<int> reach_row, reach_col;
    int rcnt;
    vector<int> from;
    void found_match(int r, int c) {
        do {
            int old_match = match[r];
            match[r] = c;
            matched[c] = r;
            tie(r, c) = make_pair(from[r], old_match);
        } while (r >= 0 && c >= 0);
    }

    void augment(int row_to_match) {
        slack.resize(n);
        for (int c = 0; c < n; c++) {

```



```

    slack[c] = weights[row_to_match][c] - potential_row[row_to_match] -
        potential_col[c];
}
++rcnt;
vector<int> q; q.reserve(n);
int h = 0;
q.push_back(row_to_match);
reach_row[row_to_match] = rcnt;
from[row_to_match] = -1;
for (;;) {
    while (h < q.size()) {
        int r = q[h++];
        for (int c = 0; c < n; c++) {
            cost_t gap = weights[r][c] - potential_row[r] - potential_col[c];
            slack[c] = min(slack[c], gap);
            if (gap != cost_t()) continue;
            int next = matched[c];
            if (next < 0) {
                found_match(r, c);
                return;
            }
            reach_col[c] = rcnt;
            if (reach_row[next] == rcnt) continue;
            q.push_back(next);
            reach_row[next] = rcnt;
            from[next] = r;
        }
    }
    cost_t delta = max_cost();
    for (int c = 0; c < n; c++) {
        if (reach_col[c] == rcnt) continue; // non-covered -> continue
        delta = min(delta, slack[c]);
    }
    for (int r = 0; r < n; r++) {
        if (reach_row[r] == rcnt) continue;
        potential_row[r] -= delta;
    }
    for (int c = 0; c < n; c++) {
        if (reach_col[c] == rcnt) continue;
        potential_col[c] += delta;
        slack[c] -= delta;
    }
    int lastsize = q.size();
    for (int c = 0; c < n; c++) {
        if (reach_col[c] == rcnt) continue;
        if (slack[c] != cost_t()) continue;
        int next = matched[c];
        if (next >= 0 && reach_row[next] == rcnt) continue;
        for (int qi = 0; qi < lastsize; qi++) {
            int r = q[qi];
            cost_t gap = weights[r][c] - potential_row[r] - potential_col[c];
            if (gap != cost_t()) continue;
            if (next < 0) {
                found_match(r, c);
                return;
            }
        }
    }
}

```

```

        reach_col[c] = rcnt;
        q.push_back(next);
        reach_row[next] = rcnt;
        from[next] = r;
        break;
    }
}
}

void initialize() {
    potential_row.assign(n, cost_t());
    potential_col.assign(n, cost_t());
    match.assign(n, -1);
    matched.assign(n, -1);
    reach_row.assign(n, 0);
    reach_col.assign(n, 0);
    from.resize(n);
    rcnt = 1;
    for (int i = 0; i < n; i++) {
        cost_t row_min_weight = *min_element(weights[i].begin(), weights[i].end());
        ;
        potential_row[i] = row_min_weight;
    }
    for (int i = 0; i < n; i++) {
        cost_t col_min_weight = weights[0][i] - potential_row[0];
        for (int j = 1; j < n; j++) col_min_weight = min(col_min_weight, weights[j][i] - potential_row[j]);
        potential_col[i] = col_min_weight;
    }
}

cost_t solve() {
    initialize();
    for (int row_to_match = 0; row_to_match < n; row_to_match++) {
        augment(row_to_match);
    }
    cost_t ans = cost_t();
    for (auto v : potential_row) ans += v;
    for (auto v : potential_col) ans += v;
    return ans;
}
};

```

## 7.2 LiChao Tree

```

// LiChaoTree for dynamic CHT trick
// This example maintains CHT for finding MAXIMUM of corresponding x
// op=1 : add ax + b into CHT
// op=2 : find max value of position x
// https://cp-algorithms.com/geometry/convex_hull_trick.html
ll f(Pl1 line, ll x){
    return line.Fi*x + line.Se;
}

```

```

vector<ll> xlist;
struct LiChaoTree{
    int n; vector<Pll> d;
    void init(int x){
        n = 1; while (n < x) n *= 2;
        d.resize(n*2+10);
        for(auto& e : d){
            e = {0, -3*(1e18)};
        }
    }

    void insert(int node, int nL, int nR, Pll newline){
        if( nL == nR ){
            if( f(d[node], xlist[nL]) < f(newline, xlist[nL]) ) d[node] =
                newline;
            return;
        }
        bool left = f(d[node], xlist[nL]) < f(newline, xlist[nL]);
        bool right = f(d[node], xlist[nR]) < f(newline, xlist[nR]);

        // take upper, lower line based on leftmost point of the segment
        Pll upper = d[node], lower = newline;
        if( left ) swap(upper, lower);

        // one line totally cover another line
        if( left == right ){
            d[node] = upper; return;
        }

        int m = (nL+nR)/2;
        // intersection in left half segment
        if( f(upper, xlist[m]) <= f(lower, xlist[m]) ){
            d[node] = lower;
            insert(node*2, nL, m, upper);
        }
        // intersection in right half segment
        else{
            d[node] = upper;
            insert(node*2+1, m+1, nR, lower);
        }
    }

    ll query(int node, int nL, int nR, int pos){
        if( nL == nR ) return f(d[node], xlist[pos]);

        int m = (nL+nR)/2;
        ll nval = -3*(1e18);
        if( pos <= m ) nval = query(node*2, nL, m, pos);
        else nval = query(node*2+1, m+1, nR, pos);

        return max(nval, f(d[node], xlist[pos]) );
    }
};

int main(){

```

```

    int Q; scanf("%d",&Q);
    vector<pair<int,Pll>> qlist;
    repp(q,Q){
        int op; scanf("%d",&op);
        if( op == 1 ){
            ll a,b; scanf("%lld%lld",&a,&b);
            qlist.push_back({1,{a,b}});
        }
        else{
            ll x; scanf("%lld",&x);
            xlist.push_back(x);
            qlist.push_back({2,{x,x}});
        }
    }

    xlist.push_back(-2*(1e12) - 10);
    sort(all(xlist));
    xlist.erase(unique(all(xlist)), xlist.end());
    LiChaoTree tree;
    tree.init( sz(xlist)+1 );

    // careful to put padding into xlist
    // so that it fits to tree size
    while( sz(xlist) < tree.n+5 ) xlist.push_back(2*(1e12));

    for(auto q : qlist){
        if( q.Fi == 1 ){
            tree.insert(1,1,tree.n,q.Se);
        }
        if( q.Fi == 2 ){
            int pos = lower_bound(all(xlist), q.Se.Fi) - xlist.begin();
            printf("%lld\n",tree.query(1,1,tree.n,pos));
        }
    }
}

```

### 7.3 Persistence Segment Tree

```

int n, cnt;
int root[MAXN];

struct node {
    int sum, left, right;
} tree[3 * MAXN * LOGN];

int build(int l = 0, int r = n) {
    int idx = ++cnt;
    if(r - l <= 1) {
        tree[idx] = {0, 0, 0};
        return idx;
    }
    int mid = (l + r) >> 1;
    tree[idx] = {0, build(l, mid), build(mid, r)};
    return idx;
}

```

```

}

int update(int x, int prev, int l = 0, int r = n) {
    if(x < l || r <= x) return prev;
    int idx = ++cnt;
    if(r - l <= 1) {
        tree[idx] = {l, 0, 0};
        return idx;
    }

    int mid = (l + r) >> 1;
    int L = update(x, tree[prev].left, l, mid);
    int R = update(x, tree[prev].right, mid, r);
    tree[idx] = {tree[L].sum + tree[R].sum, L, R};
    return idx;
}

int query(int x, int y, int k, int l = 0, int r = n) {
    if(r - l <= 1) return l;
    int mid = (l + r) >> 1;
    int leftSum = tree[tree[y].left].sum - tree[tree[x].left].sum;
    if(leftSum >= k)
        return query(tree[x].left, tree[y].left, k, l, mid);
    else
        return query(tree[x].right, tree[y].right, k - leftSum, mid, r);
}

int a[MAXN], rev[MAXN];
map<int, int> M;

int main() {
    int q;
    geti(n, q);
    for(int i = 1; i <= n; i++) {
        geti(a[i]);
        rev[i-1] = a[i];
    }
    sort(rev, rev + n);
    for(int i = 0; i < n; i++)
        M[rev[i]] = i;
    for(int i = 1; i <= n; i++)
        a[i] = M[a[i]];

    root[0] = build();
    for(int i = 1; i <= n; i++)
        root[i] = update(a[i], root[i-1]);

    while(q--) {
        int i, j, k;
        geti(i, j, k);
        printf("%d\n", rev[query(root[i-1], root[j], k)]);
    }
}

```

## 7.4 XOR FFT

```

#include <cstdio>
#include <complex>

const int SZ = 20, N = 1 << SZ;

using namespace std;

int Rev(int x) {
    int i, r = 0;
    for (i = 0; i < SZ; i++) {
        r = r << 1 | x & 1;
        x >>= 1;
    }
    return r;
}

void FFT(int *a, bool f) {
    int i, j, k, z;
    for (i = 0; i < N; i++) {
        j = Rev(i);
        if (i < j) {
            z = a[i];
            a[i] = a[j];
            a[j] = z;
        }
    }
    for (i = 1; i < N; i <= 1) for (j = 0; j < N; j += i << 1) for (k = 0; k <
        i; k++) {
        z = a[i + j + k];
        a[i + j + k] = a[j + k] - z;
        a[j + k] += z;
    }
    if (f) for (i = 0; i < N; i++) a[i] /= N;
}

int X[N];

int main() {
    int i, n;
    scanf("%d", &n);
    for (i = 0; i < 1 << n; i++) scanf("%d", &X[i]);
    FFT(X, false);
    for (i = 0; i < N; i++) X[i] *= X[i];
    FFT(X, true);
    for (i = 0; i < 1 << n; i++) printf("%d ", X[i]);
}

```

## 7.5 NTT

```

#include <cstdio>

const int A = 7, B = 26, P = A << B | 1, R = 3;
const int SZ = 20, N = 1 << SZ;

```

```

int Pow(int x, int y) {
    int r = 1;
    while (y) {
        if (y & 1) r = (long long)r * x % P;
        x = (long long)x * x % P;
        y >>= 1;
    }
    return r;
}

void FFT(int *a, bool f) {
    int i, j, k, x, y, z;
    j = 0;
    for (i = 1; i < N; i++) {
        for (k = N >> 1; j >= k; k >>= 1) j -= k;
        j += k;
        if (i < j) {
            k = a[i];
            a[i] = a[j];
            a[j] = k;
        }
    }
    for (i = 1; i < N; i <= 1) {
        x = Pow(f ? Pow(R, P - 2) : R, P / i >> 1);
        for (j = 0; j < N; j += i << 1) {
            y = 1;
            for (k = 0; k < i; k++) {
                z = (long long)a[i | j | k] * y % P;
                a[i | j | k] = a[j | k] - z;
                if (a[i | j | k] < 0) a[i | j | k] += P;
                a[j | k] += z;
                if (a[j | k] >= P) a[j | k] -= P;
                y = (long long)y * x % P;
            }
        }
    }
    if (f) {
        j = Pow(N, P - 2);
        for (i = 0; i < N; i++) a[i] = (long long)a[i] * j % P;
    }
}

int X[N];

int main() {
    int i, n;
    scanf("%d", &n);
    for (i = 0; i <= n; i++) scanf("%d", &X[i]);
    FFT(X, false);
    for (i = 0; i < N; i++) X[i] = (long long)X[i] * X[i] % P;
    FFT(X, true);
    for (i = 0; i <= n + n; i++) printf("%d ", X[i]);
}

```

## 7.6 2D FFT

```

const double EPS = 0.00001;

typedef complex<double> base;

void fft(vector<base> &a, bool invert){
    int n = a.size();
    for(int i=1,j=0;i<n;i++){
        int bit = n >> 1;
        for (;j>=bit;bit>>=1)j -= bit;
        j += bit;
        if (i < j) swap(a[i], a[j]);
    }
    for(int len=2;len<=n;len<=1){
        double ang = 2*acos(-1)/len*(invert?-1:1);
        base wlen(cos(ang),sin(ang));
        for(int i=0;i<n;i+=len){
            base w(1);
            for(int j=0;j<len/2;j++){
                base u = a[i+j], v = a[i+j+len/2]*w;
                a[i+j] = u+v;
                a[i+j+len/2] = u-v;
                w *= wlen;
            }
        }
    }
    if (invert) {
        for(int i=0;i<n;i++) a[i] /= n;
    }
}

void multiply(const vector<int> &a, const vector<int> &b, vector<int> &res){
    vector<base> fa(a.begin(), a.end()), fb(b.begin(),b.end());
    int n = 1;
    while(n < max(a.size(), b.size())) n <= 1;
    n <= 1;
    fa.resize(n); fb.resize(n);
    fft(fa,false);fft(fb,false);
    for(int i=0;i<n;i++) fa[i] *= fb[i];
    fft(fa,true);
    res.resize(n);
    for(int i=0;i<n;i++) res[i] = int(fa[i].real() + (fa[i].real() > 0 ? 0.5 :
        -0.5));
}

void multiply_complex(const vector<base> &a, const vector<base> &b, vector<base>
    &res){
    vector<base> fa(a.begin(), a.end()), fb(b.begin(),b.end());
    int n = 1;
    while(n < max(a.size(), b.size())) n <= 1;
    n <= 1;
    fa.resize(n); fb.resize(n);
    fft(fa,false);fft(fb,false);
    for(int i=0;i<n;i++) fa[i] *= fb[i];
    fft(fa,true);
}

```

```

    res.resize(n);
    for(int i=0;i<n;i++) res[i] = fa[i];
}

const int MAXN = 405;
const int LOGN = 19;

string S[MAXN], T[MAXN];

int main() {
    int n, m;
    geti(n, m);
    for(int i = 0; i < n; i++)
        cin >> S[i];
    int r, c;
    geti(r, c);
    for(int i = 0; i < r; i++)
        cin >> T[i];

    int p = 1, q = 1;
    while(q < m+c) q <= 1;
    while(p < n+r) p <= 1;

    vector<vector<base>> a(p, vector<base>(q)), b(p, vector<base>(q));
    for(int i = 0; i < p; i++) {
        for(int j = 0; j < q; j++) {
            int t = S[i%n][j%m] - 'a';
            double ang = 2*acos(-1)*t/26;
            a[i][j] = base(cos(ang), sin(ang));
        }
    }
    int cnt = 0;
    for(int i = 0; i < r; i++) {
        for(int j = 0; j < c; j++) {
            if(T[i][j] != '?') {
                cnt++;
                int t = T[i][j] - 'a';
                double ang = 2*acos(-1)*t/26;
                b[(r-1)-i][(c-1)-j] = base(cos(-ang), sin(-ang));
            }
        }
    }

    vector<vector<base>> fa, fb, res;
    for(int i = 0; i < p; i++) {
        vector<base> ta(a[i].begin(), a[i].end()), tb(b[i].begin(), b[i].end());
        fft(ta, false);
        fft(tb, false);
        fa.push_back(ta);
        fb.push_back(tb);
    }

    for(int j = 0; j < q; j++) {
        vector<base> ta(p), tb(p), tmp;
        for(int i = 0; i < p; i++) {

```

```

            ta[i] = fa[i][j];
            tb[i] = fb[i][j];
        }
        multiply_complex(ta, tb, tmp);
        if(j == 0)
            res.resize(tmp.size(), vector<base>(q));

        for(int i = 0; i < res.size(); i++)
            res[i][j] = tmp[i];
    }

    for(int i = 0; i < res.size(); i++)
        fft(res[i], true);

    for(int i = 0; i < n; i++) {
        for(int j = 0; j < m; j++) {
            if(abs(res[i+r-1][j+c-1].real() - cnt) < EPS && abs(res[i+r-1][j+c-1].imag()) < EPS) printf("1");
            else printf("0");
        }
        printf("\n");
    }
}

```

## 7.7 Order Statistic Tree

```

#include <ext/pb_ds/assoc_container.hpp> // Common file
#include <ext/pb_ds/tree_policy.hpp> // Including
tree_order_statistics_node_update

```

```

// Need this
// We can run this code on codeforces
// http://codeforces.com/blog/entry/11080
using namespace __gnu_pbds;

```

```

typedef tree<
int,
null_type,
less<int>,
rb_tree_tag,
tree_order_statistics_node_update>
ordered_set;

```

```

int main(){
    ordered_set X;
    X.insert(1);
    X.insert(2);
    X.insert(4);
    X.insert(8);
    X.insert(16);

    cout<<*X.find_by_order(1)<<endl; // 2
    cout<<*X.find_by_order(2)<<endl; // 4
    cout<<*X.find_by_order(4)<<endl; // 16
    cout<<(end(X)==X.find_by_order(6))<<endl; // true
}

```

```

    cout<<X.order_of_key(-5)<<endl; // 0
    cout<<X.order_of_key(1)<<endl; // 0
    cout<<X.order_of_key(3)<<endl; // 2
    cout<<X.order_of_key(4)<<endl; // 2
    cout<<X.order_of_key(400)<<endl; // 5
}

```

## 7.8 BITSET

```

#define M 32
int main()
{
    // default constructor initializes with all bits 0
    bitset<M> bset1;

    // bset2 is initialized with bits of 20
    bitset<M> bset2(20);

    // bset3 is initialized with bits of specified binary string
    bitset<M> bset3(string("1100"));

    // cout prints exact bits representation of bitset
    cout << bset1 << endl; // 00000000000000000000000000000000
    cout << bset2 << endl; // 0000000000000000000000000000010100
    cout << bset3 << endl; // 000000000000000000000000000001100
    cout << endl;

    // declaring set8 with capacity of 8 bits

    bitset<8> set8; // 00000000

    // setting first bit (or 6th index)
    set8[1] = 1; // 00000010
    set8[4] = set8[1]; // 00010010
    cout << set8 << endl;

    // count function returns number of set bits in bitset
    int numberOf1 = set8.count();

    // size function returns total number of bits in bitset
    // so there difference will give us number of unset(0)
    // bits in bitset
    int numberOf0 = set8.size() - numberOf1;
    cout << set8 << " has " << numberOf1 << " ones and "
        << numberOf0 << " zeros\n";

    // test function return 1 if bit is set else returns 0
    cout << "bool representation of " << set8 << " : ";
    for (int i = 0; i < set8.size(); i++)
        cout << set8.test(i) << " ";

    cout << endl;
}

```

```

// any function returns true, if atleast 1 bit
// is set
if (!set8.any())
    cout << "set8 has no bit set.\n";

if (!bset1.any())
    cout << "bset1 has no bit set.\n";

// none function returns true, if none of the bit
// is set
if (!bset1.none())
    cout << "bset1 has all bit set\n";

// bset.set() sets all bits
cout << set8.set() << endl;

// bset.set(pos, b) makes bset[pos] = b
cout << set8.set(4, 0) << endl;

// bset.set(pos) makes bset[pos] = 1 i.e. default
// is 1
cout << set8.set(4) << endl;

// reset function makes all bits 0
cout << set8.reset(2) << endl;
cout << set8.reset() << endl;

// flip function flips all bits i.e. 1 <-> 0
// and 0 <-> 1
cout << set8.flip(2) << endl;
cout << set8.flip() << endl;

// Converting decimal number to binary by using bitset
int num = 100;
cout << "\nDecimal number: " << num
    << " Binary equivalent: " << bitset<8>(num);

return 0;
}

int main()
{
    bitset<4> bset1(9); // bset1 contains 1001
    bitset<4> bset2(3); // bset2 contains 0011

    // comparison operator
    cout << (bset1 == bset2) << endl; // false 0
    cout << (bset1 != bset2) << endl; // true 1

    // bitwise operation and assignment
    cout << (bset1 ^= bset2) << endl; // 1010
    cout << (bset1 &= bset2) << endl; // 0010
    cout << (bset1 |= bset2) << endl; // 0011

    // left and right shifting
    cout << (bset1 <<= 2) << endl; // 1100
}

```

```
    cout << (bset1 >>= 1) << endl;    // 0110

    // not operator
    cout << (~bset2) << endl;         // 1100

    // bitwise operator
    cout << (bset1 & bset2) << endl;    // 0010
    cout << (bset1 | bset2) << endl;    // 0111
    cout << (bset1 ^ bset2) << endl;    // 0101
}
```











