



[Synchroteam API v3](#)

- [Introduction](#)
- [Endpoint URL](#)
- [Data Format](#)
- [HTTP VERBS](#)

[Authentication](#)

[Pagination](#)

- [Query Parameters](#)
- [Response Properties](#)

[Rate Limits and Quotas](#)

- [Rate Limits](#)
- [Daily Request Quota](#)

[Errors](#)

[Changelogs](#)

- [V62.1](#)

[Resources](#)

[Activities](#)

- [The activity object](#)
- [Retrieve an activity](#)
- [Create/Update an activity](#)
- [Delete an activity](#)
- [List activities](#)

[Activity types](#)

- [The activity_type object](#)
- [List activity types](#)

[Custom fields](#)

[Custom field values](#)

[Customers](#)

[Sites](#)

- [The site object](#)
- [Retrieve a site](#)
- [Create/Update a site](#)
- [Delete a site](#)
- [Undelete a site](#)
- [List sites](#)

- [Activate a site](#)
- [Deactivate a site](#)
- [Transfer a site](#)

[Equipment](#)

- [The equipment object](#)
- [Retrieve equipment](#)
- [Create/Update equipment](#)
- [Delete equipment](#)
- [Undelete equipment](#)
- [List equipment](#)
- [Activate an equipment](#)
- [Deactivate an equipment](#)
- [Transfer an equipment](#)

[Jobs](#)

- [The job object](#)
- [Retrieve a job](#)
- [Create/Update a job](#)
- [Delete a job](#)
- [List jobs](#)
- [Schedule a job](#)
- [Unschedule a job](#)
- [Cancel a job](#)
- [Validate a job](#)
- [Start a job](#)
- [Pause a job](#)
- [Confirm a job](#)
- [Complete a job](#)
- [Retrieve job photos](#)
- [Send job parts](#)

[Job Scheduling Preferences](#)

- [The job scheduling preferences object](#)

[Job Scheduling Windows](#)

- [The job scheduling window object](#)
- [List job scheduling windows](#)

[Contracts](#)

- [The contract object](#)
- [Retrieve a contract](#)
- [Create/Update a contract](#)
- [List contracts](#)

[Job Types](#)

- [The job type object](#)
- [Retrieve a job type](#)

- [List Job Types](#)
- [Send job type](#)

[Job Reports](#)

- [The job report object](#)
- [Retrieve a job report](#)

[Report Templates](#)

- [The report template object](#)
- [Retrieve a report template](#)
- [List job report templates](#)

[Blocks](#)

- [The block object](#)
- [The item object](#)
- [Retrieve a block](#)
- [List shared blocks](#)

[Projects](#)

- [The project object](#)
- [Retrieve a project](#)
- [Create/Update a project](#)
- [Link jobs to a project](#)
- [List projects](#)
- [Delete a project](#)

[Recurrences](#)

- [The Recurrence object](#)
- [Retrieve a Recurrence](#)
- [Delete a Recurrence](#)
- [Close a Recurrence](#)
- [List Recurrences](#)
- [Create/Update a recurrence](#)

[Recurrence Scheduling Preferences](#)

- [The recurrence scheduling_preferences object](#)

[Positions](#)

- [DESCRIPTION](#)
- [METHODS](#)

[Users](#)

- [The user object](#)
- [Retrieve a user](#)
- [Create/Update a user](#)
- [Delete a user](#)
- [List users](#)

[Teams](#)

- [The team object](#)
- [List teams](#)

[Tax Rates](#)

- [The tax object](#)
- [List taxes](#)

[Attachments](#)

- [The attachment object](#)
- [Retrieve an attachment](#)
- [Create an attachment](#)
- [Delete an attachment](#)
- [List attachments](#)

[Parts and Services](#)

- [The part object](#)
- [Retrieve a part](#)
- [List parts](#)
- [Create/Update a part](#)
- [Delete a part](#)
- [Bulk part price update](#)

[Invoices](#)

- [The invoice object](#)
- [Retrieve an invoice](#)
- [Create/Update an invoice](#)
- [Duplicate an invoice](#)
- [Cancel an invoice](#)
- [List invoices](#)

[Quotations](#)

- [The quotation object](#)
- [Retrieve a quotation](#)
- [Create/Update a quotation](#)
- [Cancel a quotation](#)
- [Duplicate a quotation](#)
- [List quotations](#)

[Credit Notes](#)

- [The Credit Note object](#)
- [Retrieve a Credit Note](#)
- [List Credit Notes](#)

[Inventory Management](#)

[Part Movements](#)

- [Move parts](#)

[Part Requests](#)

- [The parts request object](#)
- [Retrieve a part request](#)
- [Create/Update a part request](#)
- [List part requests](#)
- [Fulfill a parts request](#)

[Stock Depots](#)

- [The stock depot object](#)
- [Retrieve a depot](#)
- [List depots](#)
- [Initialize depot quantities](#)

[Stock Parts](#)

[Messages](#)

- [The Message object](#)
- [Send a Message](#)

[Timeline](#)

- [The Timeline object](#)
- [List Timeline items](#)
- [Create a Timeline item](#)

[Tasks](#)

- [The Task object](#)
- [List Tasks](#)
- [Create a Task](#)

Synchroteam API v3

Introduction

Welcome to the Synchroteam API!

Synchroteam's data is not locked in. We understand that there exists a wide variety of situations where you will want to read data kept within synchroteam.com, or push data into it. We are happy to provide you with a complete REST API that will allow you to integrate Synchroteam.com with other systems.

If you use other solutions to manage your customer information (CRM, Invoicing systems, etc.), you will not want to duplicate data between them and Synchroteam.com. By leveraging the data transparency provided by the REST API, you can exchange data between Synchroteam.com and other applications.

Endpoint URL

i For security reasons all HTTP request should implement HTTPS overs TLS 1.2+ protocol

Type	Description
Endpoint	https://ws.synchroteam.com
Protocol	HTTPS (TLS 1.2+)

Data Format

By Default, JSON is returned by all API responses, including errors.

i Our API supports **JSON** for your data payloads. All the examples provided within this documentation show **JSON** payloads.

For the data format to be visible in your API calls, you can manipulate the HTTP request headers to explicitly tell the Synchroteam API you are using **JSON** :

JSON (DEFAULT)

To exchange data in **JSON** you need to add the following HTTP headers:

Header	Value
Content-Type	<code>application/json</code> OR <code>text/json</code>
Accept	<code>application/json</code> OR <code>text/json</code>

HTTP VERBS

The Synchroteam API used standard HTTP verbs to support CRUD (Create, Read, Update, Delete) operations:

Verb	Operation
<code>POST</code>	creating OR updating records
<code>GET</code>	reading
<code>PUT</code>	updating object properties
<code>DELETE</code>	delete

i

Authentication

To authorize, use this code:

```
curl --request GET \
  --url https://ws.synchroteam.com/Api/v3/api_endpoint_here \
  --header 'authorization: Basic bXljYzIwYW55OjZmZmOGU1YjYzLTBlNzQtNDUwMi1iYTgzLWw4Mj1hY2ZiNThmMw==' \
  --header 'cache-control: no-cache'
```

The Synchroteam API is implemented over authenticated HTTP using Basic Authentication.

To connect using basic HTTP authentication, you will need both your **personalized domain identifier** and your **API key**.

Synchroteam expects for the API key to be included in all API requests to the server. A basic HTTP authentication header looks like the following:

Authorization: Basic a2VlcG9uOjczNmYxMDFmLTE0ZTAtNDgzZC1iNzBlLWY4YjNjZjBmOGFmMQ==

This encoded portion is the **base64 encoded** representation of:

```
domain:api-key
```

Parameter	Example	Description
domain	mycompany	This is your domain identifier if your domain is https://mycompany.synchroteam.com
api-key	ff8e5b63-0e74-4102-ba93-c829acfb58f3	Find this key under <i>Configuration, Authentication Key</i>

API testing tools like Postman will do this for you.

Pagination

The Synchroteam API uses pagination for all endpoints that support bulk fetches via **list** API methods.

Query Parameters

Sample Request

```
GET https://ws.synchroteam.com/v3/job/list?page=3&pageSize=25
```

Pagination is controlled via `page` and `pageSize` query parameters applied to resources that support bulk fetches. If unspecified, the default values below are used:

Parameter	Default	Description
<code>page</code>	1	The page number (pagination starts at 1)
<code>pageSize</code>	25	Maximum allowed pageSize is 100

Response Properties

Sample API response with pagination

```
{
  "request": "list",
  "object": "job",
  "page": 3,
  "pageSize": 25,
  "records": 25,
  "recordsTotal": 452,
  "data": [
    {<job object>},
    {<job object>},
    ...
    {<job object>}
  ]
}
```

These methods will return `page`, `pageSize`, `records`, `recordsTotal`

Parameter	Description
<code>page</code>	page number returned
<code>pageSize</code>	page size requested
<code>records</code>	number of records returned
<code>recordsTotal</code>	total number or records available

Rate Limits and Quotas

The Synchroteam API applies Rate Limiting (per minute) and a Request Quota (per day). Usage rates are tracked per API Access Token.

Rate Limits

Sample HTTP Headers Returned

```
X-RateLimit-Limit: 1000
X-RateLimit-Remaining: 554
X-RateLimit-Reset: 1530199810
X-Quota-Limit: 15000
X-Quota-Remaining: 9452
```

Request are throttled at a maximum rate of 1000 requests every minute.

Your current rate limit information is provided in the response headers of every request.

Header	Description
X-RateLimit-Limit	Maximum number of requests allowed in the current window
X-RateLimit-Remaining	Number of requests remaining in the current window
X-RateLimit-Reset	A UTC Unix timestamp detailing when the rate limit will reset

Daily Request Quota

Each API key has a daily request quota. You current daily quota information is provided in the response headers of every request.

Header	Description
X-Quota-Limit	Number of requests allowed in the current day
X-Quota-Remaining	Number of requests remaining in the current day (resets at UTC midnight)

If you encounter issues or wish to make arrangements for a higher rate limit or daily quota, please contact our support team.

Errors

Sample error reponse format

```
REQUEST:
GET https://ws.synchroteam.com/v3/job/list?page=3&pageSize=25

RESPONSE:
HTTP/1.0 429 Too Many Requests
(...)
Content-Type: application/json; charset=utf-8
X-RateLimit-Limit: 120
X-RateLimit-Remaining: 120
X-RateLimit-Reset: 1530199810
X-Quota-Limit: 10000
X-Quota-Remaining: 0

RESPONSE BODY:
{
  "error": "Too Many Requests",
  "message": "You have gone above your daily quota"
}
```

When errors are encountered, the Synchroteam API uses and standard HTTP response code along with a standard error response format

HTTP status code summary:

Error Code	Meaning
400	Bad Request -- You have an error in your request
401	Unauthorized -- Your API key is wrong
403	Forbidden -- The resource you are trying to access is Forbidden
404	Not Found -- The requested resource does not exist
405	Method Not Allowed -- You tried to access an object with an invalid method
406	Not Acceptable -- You requested a format that isn't JSON
429	Too Many Requests -- You've hit our API rate limits
500	Internal Server Error -- We had a problem with our server. Try again later.
503	Service Unavailable -- We're temporarily offline for maintenance. Please try again later.

Reponse Body Properties:

Property	Meaning
error	Short error description
message	Detailed error message

Changelogs

V62.1

API — DEFAULT CREATOR FOR JOBS

Fixed the API job creation process to automatically assign the oldest active administrator of the account as the creator, instead of leaving the creator as NULL.

Resources

Activities

The activity object

JSON Representation

```
{
  "id":5697,
  "activityType":{
    "id":596,
    "name":"Standard Travel",
    "category":"travel",
    "payable":true
  },
  "note":"Hey this is a sample note!",
  "dateStart":"2018-01-01 14:22",
  "dateEnd":"2018-01-01 14:50",
  "distance":{
    "km":10.50,
    "mi":6.52
  },
  "user": {
    "id":54022,
    "login":"login_user",
    "firstName":"John",
    "lastName":"Doe"
  },
  "team": null
}
```

Activities are data elements in Synchroteam that can be used to declare:

- Unavailabilities (e.g. Holidays, Vacation, Sick Days) - `category code: "unavail"`
- Work related activities (e.g. Lunch Break, Training) - `category code: "atwork"`
- Travel (e.g. Travel from home or Travel to/from Job site) - `category code: "travel"`
- Technician Clock IN and Clock OUT times. - `category code: "clock"`

An activity is represented by the following fields

Field	Type	Description
id	integer	Activity id (read only)
activityType	object	Simplified Activity Type object, containing, the id, name, category and payable flag.
note	string	Note for the activity
dateStart	dateTime	Activity start date and time (Local time, ISO 8601 Representation : YYYY-MM-DD hh:mm)
dateEnd	dateTime	Activity end date and time (Local time, ISO 8601 Representation : YYYY-MM-DD hh:mm)
distance	object	Distance object provinding distance data in kilometers (km) and miles (mi). Used for travel activities.
user	object	Simplified user object, containing the id, login, firstName and lastName of the user
team	object	Simplified team object, containing the id and name of the team - used only for unavailabilities.

Retrieve an activity

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/activity/details?id=5697' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response (Here, an unavailability assigned to an entire team)

```
{
  "id":5697,
  "activityType":{
    "id":596,
    "name":"Parties",
    "category":"unavail",
    "payable":false
  },
  "note":"Everyone can attend!",
  "dateStart":"2018-01-01 14:00",
  "dateEnd":"2018-01-01 17:00",
  "distance": null
  "user": null
  "team": {
    "id": 476,
    "name": "East Team"
  }
}
```

HTTP REQUEST

```
GET /api/v3/activity/details?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code>
{paramValue}	string	<code>id</code> of the activity

REQUEST BODY

none

RESPONSE BODY

Returns the activity if found.

If the activity is not found a 404 Error is returned.

Create/Update an activity

Synchroteam provides a single endpoint to handle creating or updating activities. The API determines if the activity record already exists by checking the value provided for `id`.

POST Body

```
{
  "activityType":{
    "id":596
  },
  "note":"Hey this is a sample note!",
  "dateStart":"2018-01-01 14:22",
  "dateEnd":"2018-01-01 14:50",
  "distance":{
    "km":10.50,
    "mi":6.52
  },
  "user": {
    "id":54022
  },
  "team": null
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/activity/send \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUTQzhEMjg4NzhBQTthB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{\r\n  "activityType":{"id":596},\r\n  "note": "Hey, this is a sample note!" (...)'
```

JSON Returned

```
{
  "id":5697,
  "activityType":{
    "id":596,
```

```

    "name": "Standard Travel",
    "category": "travel",
    "payable": true
  },
  "note": "Hey this is a sample note!",
  "dateStart": "2018-01-01 14:22",
  "dateEnd": "2018-01-01 14:50",
  "distance": {
    "km": 10.50,
    "mi": 6.52
  },
  "user": {
    "id": 54022,
    "login": "login_user",
    "firstName": "John",
    "lastName": "Doe"
  },
  "team": null
}

```

HTTP REQUEST

POST /api/v3/activity/send

REQUEST BODY

Activity information in JSON format, if the `id` exists, the activity will be updated, if not the activity will be created.

When updating an activity, if you provide a partial payload, only the fields provided will be updated. Fields not provided *will not be deleted*.

Required Fields For Creation

- activityType -> id
- dateStart
- dateEnd
- user -> id and/or login at minimum (If specifying a user)
- team -> id (If specifying a team)

RESPONSE BODY

The response contains the updated activity record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.

❗ Special Case: Unavailabilities

Unavailabilities can be created for all users by setting **user** and **team** to `null`.

Unavailabilities can also be created for all single team by setting **user** to `null`, and specifying the **team**.

NB: All other types require a **user** to be specified, and will ignore the **team** specification.

Delete an activity

```

curl --request DELETE \
  --url 'https://ws.synchroteam.com/api/v3/activity/delete?id=8976' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0EUEtQzhEMjg4NzhBQThB' \

```

```
--header 'cache-control: no-cache' \  
--header 'content-type: application/json'
```

JSON Returned

```
[  
  {  
    "id":8976  
    "deleted":true  
  }  
]
```

HTTP REQUEST

```
DELETE /api/v3/activity/delete
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code>
{paramValue}	string	<code>id</code> of the activity

REQUEST BODY

none

RESPONSE BODY

Returns a list containing a single object with a deleted parameter set to true on success, and the activity ID. If no activity is found, a 404 error is returned.

List activities

```
curl --request GET \  
--url https://ws.synchroteam.com/api/v3/activity/list?team_id=476 \  
--header 'accept: text/json' \  
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \  
--header 'cache-control: no-cache' \  
--header 'content-type: application/json'
```

Example Response

```
{  
  "page":1,  
  "pageSize":25,  
  "records":6,  
  "recordsTotal":6,  
  "data":[  
    {<activity object>},  
    {<activity object>},  
    ...  
    {<activity object>}  
  ]  
}
```

```
}
}
```

HTTP REQUEST

GET /api/v3/activity/list

QUERY PARAMETERS

Parameter	Type	Description
startDate	dateTime	Activity start date and time (yyyy-mm-dd hh:mm) (requires endDate)
endDate	dateTime	Activity end date and time (yyyy-mm-dd hh:mm) (requires startDate)
activityType_name	string	Performs an exact name search
activityType_category	string	one of "unavailability", "atwork", "travel" or "clock"
user_id	integer	return activities belonging to a user by user id
user_login	integer	return activities belonging to a user by user login
team_id	integer	return activities belonging to a team by team id
sort	string	sort order, takes one of four values: startDate, endDate, activityType_name and user_login (Optional. Default is startDate)
sortOrder	string	takes one of two values: ascending or descending (Optional. Default is ascending)

Add pagination parameters if needed.

 When providing startDate and endDate, we return any activities that **intersect** this range

RESPONSE BODY

A list of activities found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Activity types

The activity type object

```
{
  "id":596,
  "name":"Standard Travel",
  "category":"travel",
  "color":"DDEEDD"
```

```
"payable":true
}
```

Activity types are set and controlled via the Synchroteam Web based back office, and can fall in one of four categories:

- Unavailabilities (e.g. Holidays, Vacation, Sick Days) - `category code: "unavail"`
- Work related activities (e.g. Lunch Break, Training) - `category code: "atwork"`
- Travel (e.g. Travel from home or Travel to/from Job site) - `category code: "travel"`
- Technician Clock IN and Clock OUT times. - `category code: "clock"`

Do note that certain types ("travel" and "clock") only apply when the Time Tracking option is activated on your account.

An activity type is represented by the following fields

Field	Type	Description
id	integer	ID of the activity type
name	string	Name of the activity type
category	string	One of "unavail", "atwork", "travel" or "clock"
color	string	Color of the activity type (RGB, Hexadecimal format)
payable	boolean	indicated whether or not time logged for this activity type is payable to the technician

List activity types

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/activityType/list?category=unavail \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":6,
  "recordsTotal":6,
  "data":[
    {<activity type object>},
    {<activity type object>},
    ...
    {<activity type object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/activityType/list
```

QUERY PARAMETERS

Parameter	Type	Description
{category}	string	One of "unavail", "atwork", "travel" or "clock"
{name}	string	Will find all activity types containing <code>{name}</code>
{sort}	string	sort order, takes one of two values: <code>{name}</code> or <code>{category}</code> (Optional. Default is <i>name</i>)
{sortOrder}	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

RESPONSE BODY

A list of activity types found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Custom fields

The custom field object

JSON Representation

```
{
  "id": "2",
  "label": "Equipment Serial Number",
  "type": "text",
  "private": false,
  "mandatory": true,
  "order": 1
}
```

There can be any number of custom fields values associated with jobs, users, customers, sites, equipment. Custom fields consist of the following fields :

Field	Type	Description
id	integer	ID of the custom field (read only)
label	string	Name of the custom field.
type	string	Custom field type (<code>text</code> , <code>select</code> , <code>date</code> , <code>number</code> , <code>checkbox</code> , <code>autocomplete</code> , <code>email</code> or <code>phone</code>)
private	boolean	Specifies whether or not the custom field is visible to customers
mandatory	boolean	set to <code>true</code> if the current custom field is mandatory
order	int	display order

Custom fields are configured via the web based back office.

Types are as follows:

- **text**: Text field
- **select**: list of predefined options
- **date**: Date field
- **number**: any numeric entry
- **checkbox**: a single checkbox is presented
- **autocomplete**: Text field. Will suggest any value previously entered for the same field.
- **email**: Validates a correct email format
- **phone**: telephone number

Send Custom Fields

Synchroteam provides a single endpoint to handle adding Custom Fields on a Job. The Job is identified by its `id`, `num` or `myId`.

POST Body

```
{
  "Job": {
    "num": "24789"
  },
  "CustomFieldValues": [
    {
      "id": 6420,
      "label": "text",
      "value": "test"
    },
    {
      "id": 6418,
      "label": "case à cocher",
      "value": "0"
    }
  ]
}
```

Sample Code

```
curl --location --request POST 'https://ws.synchroteam.com/api/v3/customfield/send' \
--header 'Authorization: Basic ZGVtbzo1Y2MyODM4MS01ZTM0LTQ0YWUtYjk1MC05MWI1MDQxMTA3ZTE=' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--data-raw '{"Job": { "num": "24789" }, "CustomFieldValues": [...]}'
```

JSON Returned

```
{
  "CustomFieldValues": [
    {
      "id": 6419,
      "label": "email",
      "value": "test@gmail.com"
    },
    {
      "id": 6420,
      "label": "text",
      "value": "test"
    }
  ]
}
```

```
{
  {
    "id": 6418,
    "label": "case à cocher",
    "value": "0"
  }
}
```

HTTP REQUEST

POST /api/v3/customfield/send

REQUEST BODY

- The Job identified by its `id`, `num` or `myId`.
- `CustomFieldValues`: custom field values list. For each custom field value specify the custom field `id`, `label` and `value`.

List Custom Fields

List Custom Fields by object `type` (Job, Customer, Site, Equipment or User)

Sample Code

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/customfield/list?type=customer \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0EUTQzhEMjg4NzhBQTbB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":4,
  "recordsTotal":4,
  "data":[
    {<customfield object>},
    {<customfield object>},
    ...
    {<customfield object>}
  ]
}
```

HTTP REQUEST

GET /api/v3/customfield/list

QUERY PARAMETERS

Parameter	Type	Description
type	string	object type for which the custom field definition is returned, one of: <code>job</code> , <code>customer</code> , <code>site</code> , <code>equipment</code> Or <code>user</code> (mandatory)
sort	string	sort order, takes one of two values: <code>label</code> and <code>order</code> (Optional. Default is <code>label</code>)

Parameter	Type	Description
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of Custom Fields found.

If none are found, an empty list is returned.

Custom field values

THE CUSTOM FIELD VALUE OBJECT

There can be any number of different custom field values associated with jobs, users, customers, sites, equipment. A representation of a custom field value has the following fields :

Field	Type	Description
id	integer	ID of the custom field (read only)
label	string	Name of the custom field.
value	string	Value of the custom field for the associated object.

```
{
  "id": "2",
  "label": "Equipment Serial Number",
  "value": "125FTD47842"
}
```

Customers

The customer object

JSON Representation

```
{
  "id": 35604,
  "myId": "sCustomer08",
  "name": "Sample Customer",
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "United States",
  "addressCity": "Falls Church",
  "addressCountry": "United States",
  "addressProvince": "Virginia",
```

```

    "addressStreet": "6605 Fisher Avenue",
    "addressZIP": "22046",
    "contactEmail": "customer@synchroteam.com",
    "contactFirstName": "John",
    "contactFax": "(719) 388-1967",
    "contactPhone": "(719) 388-1966",
    "contactLastName": "Doe",
    "vatNumber": "34567-87695-345867",
    "publicLink": "https://yourdomain.synchroteam.com/Customer/...",
    "customFieldValues": [
      {
        "id": 4658
        "label": "Zone",
        "value": "B4"
      },
      {
        "id": 94057
        "label": "Status"
        "value": "Silver",
      }
    ],
    "position": {
      "longitude": "74.0060"
      "latitude": "40.7128"
    },
    "tags" : ["plumber", "restaurant", "test"],
    "active": true
  }
}
```

The customer object is represented by the following fields

Field	Type	Description
id	integer	Customer id (read only system ID)
name	string	Customer name
myId	string	Custom customer ID (e.g. can reference your internal customer ID)
address	string	Complete Address
addressStreet	string	Street address of the customer
addressComplement	string	Complementary street address information
addressZIP	string	Address zip code
addressCity	string	Address city
addressProvince	string	Address province/state
addressCountry	string	Address country
contactLastName	string	Contact last name
contactFirstName	string	Contact first name
contactPhone	string	Contact phone number

Field	Type	Description
contactMobile	string	Contact mobile number
contactEmail	string	Contact email address
contactFax	string	Contact fax number
vatNumber	string	VAT (or other service tax) number
publicLink	string	Link you can share with your customer create/access jobs, invoices, etc. (read only)
customFieldValues	list	List of custom field values for this customer. (optional)
position	position	Position object associated with the customer. (optional)
tags	list(string)	List of tags for the customer.
active	boolean	Whether or not the customer is activated

Retrieve a customer

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/customer/details?id=35604' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "id": 35604,
  "myId": "sCustomer08",
  "name": "Sample Customer",
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "United States",
  "addressCity": "Falls Church",
  "addressCountry": "United States",
  "addressProvince": "Virginia",
  "addressStreet": "6605 Fisher Avenue",
  "addressZIP": "22046",
  "contactEmail": "customer@synchroteam.com",
  "contactFirstName": "John",
  "contactFax": "(719) 388-1967",
  "contactPhone": "(719) 388-1966",
  "contactLastName": "Doe",
  "vatNumber": "34567-87695-345867",
  "publicLink": "https://yourdomain.synchroteam.com/Customer/...",
  "customFieldValues": [customFieldValue1,...],
  "position": {Position},
  "tags" : ["plumber", "restaurant", "test"]
}
```

HTTP REQUEST

GET /api/v3/customer/details?{paramType}={paramValue}

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> , <code>id</code> , <code>myId</code> or <code>email</code>
{paramValue}	string	The <code>name</code> , <code>id</code> , <code>myId</code> or <code>email</code> for the customer

REQUEST BODY

none

RESPONSE BODY

Returns the customer if found.

If the customer is not found a 404 Error is returned.

Create/Update a customer

Synchroteam provides a single endpoint to handle creating or updating customer. The API determines if the customer record already exists by checking values provide for `id` and/or `myid`.

POST Body

```
{
  "myId": "sCustomer08",
  "name": "Sample Customer",
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "Unit B",
  "contactEmail": "customer@synchroteam.com",
  "contactFirstName": "John",
  "contactFax": "(719) 388-2222",
  "contactPhone": "(719) 388-3333",
  "contactLastName": "Doe",
  "customFieldValues": [customfieldvalue1,...],
  "position": {Position},
  (...)
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/customer/send \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE00EUTQzhEMjg4NzhBQTthB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{\n  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",\n  "addressComplement": "Unit B", (...)}'
```

JSON Returned

```
{
  "id": 35604,
```

```
{
  "myId": "sCustomer08",
  "name": "Sample Customer",
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "Unit B",
  "addressCity": "Falls Church",
  "addressCountry": "United States",
  "addressProvince": "Virginia",
  "addressStreet": "6605 Fisher Avenue",
  "addressZIP": "22046",
  "contactEmail": "customer@synchroteam.com",
  "contactFirstName": "John",
  "contactFax": "(719) 388-2222",
  "contactPhone": "(719) 388-3333",
  "contactLastName": "Doe",
  "vatNumber": "34567-87695-34567",
  "publicLink": "https://yourdomain.synchroteam.com/Customer/...",
  "customFieldValues": [
    {
      "id": 4658,
      "label": "Zone",
      "value": "B4"
    },
    {
      "id": 94057,
      "label": "Status",
      "value": "Silver",
    }
  ],
  "position": {
    "longitude": "74.0060",
    "latitude": "40.7128"
  },
  "tags": ["plumber", "restaurant", "test"],
  "dateModified": "2023-09-05 19:03",
  "dateCreated": "2023-07-28 20:01",
  "active": true
}
```

HTTP REQUEST

POST /api/v3/customer/send

PARAMETERS

None

REQUEST BODY

Customer information in JSON format, if the `id` or `myId` exist, the customer will be updated, if not the customer will be created. (If the provided `id` does not exist, the request will fail with an error)

When updating a customer, if you provide a partial payload, only the fields provided will be updated. Fields not provided *will not be deleted*.

RESPONSE BODY

The response contains the updated customer record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.

For creation, * At minimum, you must provide a **customer name** and an **address** (`address` or `addressCity` fields). All other fields are not required

- * Cannot edit **tags**
- * The **active** parameter id **read-only**

Delete a customer

```
curl --request DELETE \
--url 'https://ws.synchroteam.com/api/v3/customer/delete?name=HAMILTON%20ASSET%20MANAGEMENT' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
```

JSON Returned

```
[
  {
    "id":40946
    "deleted":true
  },
  (...)
]
```

HTTP REQUEST

```
DELETE /api/v3/customer/delete?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> , <code>id</code> , <code>myId</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> of the customer

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a deleted parameter set to true on success, and the customer ID. If no customers are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform a deletion of customers with a given name and there is more than one customer using this name, every customer whose name is given as a parameter will be deleted.

Undelete a customer

```
curl --request POST \
--url 'https://ws.synchroteam.com/api/v3/customer/undelete?name=HAMILTON%20ASSET%20MANAGEMENT' \
```

```
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE00EUTQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
```

JSON Returned

```
{
  "customersDeleted": [
    {
      "id": 2711750,
      "isDeleted": true
    }
  ]
}
```

HTTP REQUEST

```
POST /api/v3/customer/undelele?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> , <code>id</code> , <code>myId</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> of the customer

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a undeleted parameter set to true on success, and the customer ID. If no customers are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform a deletion of customers with a given name and there is more than one customer using this name, every customer whose name is given as a parameter will be undeleted.

List customers

List all customers. Search parameters can be provided.

If no parameters are given, will return all active customers.

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/customer/list?changedFrom=2016-11-02+16:32:00' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE00EUTQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
```

Example Response

```
{
  "page": 3,
  "pageSize": 25,
  "records": 25,
  "recordsTotal": 589,
  "data": [
    {<customer object>},
    {<customer object>},
    ...
    {<customer object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/customer/list
```

QUERY PARAMETERS

Parameter	Type	Description
changedSince	dateTime	return customers modified after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
name	string	search by name - a wildcard search is performed
email	string	search by contactEmail. An exact search is performed
active	boolean	search by active customers (Default is <i>true</i>)
sort	string	sort order, takes one of three values: <code>name</code> , <code>dateModified</code> , <code>dateCreated</code> and <code>myId</code> (Optional. Default is <i>name</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of customers found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Activate a customer

```
curl --request POST \
  --url 'https://ws.synchroteam.com/api/v3/customer/activate?name=HAMILTON%20ASSET%20MANAGEMENT' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
```

JSON Returned

```
{
  "customersActivated": [
    {
      "id": 2711750,
      "isActivated": true
    }
  ]
}
```

HTTP REQUEST

POST /api/v3/customer/activate?{paramType}={paramValue}

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> , <code>id</code> , <code>myId</code> or <code>email</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> or <code>email</code> of the customer

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a activated parameter set to true on success, and the customer ID. If no customers are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform an activation of customers with a given name and there is more than one customer using this name, every customer whose name is given as a parameter will be activated.

Deactivate a customer

```
curl --request POST \
--url 'https://ws.synchroteam.com/api/v3/customer/deactivate?name=HAMILTON%20ASSET%20MANAGEMENT' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C0NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
```

JSON Returned

```
{
  "customersDesactivated": [
    {
      "id": 2711750,
      "isDesactivated": true
    }
  ]
}
```

HTTP REQUEST

POST /api/v3/customer/deactivate?{paramType}={paramValue}

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> , <code>id</code> , <code>myId</code> or <code>email</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> or <code>email</code> of the customer

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a deactivated parameter set to true on success, and the customer ID. If no customers are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform a deactivation of customers with a given name and there is more than one customer using this name, every customer whose name is given as a parameter will be deactivated.

Sites

The site object

JSON Representation

```
{
  "id":2811,
  "myId": "ref-2511",
  "name":"Sample Site",
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "Unit 2",
  "addressCity": "Falls Church",
  "addressCountry": "United States",
  "addressProvince": "Virginia",
  "addressStreet": "6605 Fisher Avenue",
  "addressZIP": "22046",
  "contactEmail":"paul@hamilton.com",
  "contactFax":"(719) 388-1967",
  "contactMobile":"(719) 388-1969",
  "contactName":"Mr Paul",
  "contactPhone":"(877) 413-5903",
  "publiclink":"https://yourdomain.synchroteam.com/Site/...",
  "customer": {
    "id":35604,
    "myId":"sCustomer08",
    "name":"Sample Customer"
  },
  "customFieldValues": [
    {
      "id":4411
      "label": "Service Area",
      "value": "East"
    },
    {
      "id": 95261
      "label": "Status"
      "value": "Silver",
    }
  ]
}
```

```
    }
  ],
  "position":{
    "longitude": "74.0060"
    "latitude": "40.7128"
  },
  "tags" : ["plumber","restaurant","test"]
}
```

A site is represented by the following fields

Field	Type	Description
id	integer	Site id (read only)
myId	string	Your custom reference number for this site
name	string	Name of the site
address	string	Complete Address
addressStreet	string	Street address of the site
addressComplement	string	Complementary street address information
addressZIP	string	Address zip code
addressCity	string	Address city
addressProvince	string	Address province/state
addressCountry	string	Address country
contactLastName	string	Last name of your contact
contactFirstName	string	First name of your contact.
contactPhone	string	Phone number of your contact.
contactMobile	string	Mobile number of your contact.
contactEmail	string	Email of your contact.
contactFax	string	Fax number of your contact.
publicLink	string	Link you can share with your customer to create/access the site's jobs, invoices, etc. (read only)
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields (id or myId required when creating a site)
customFieldValues	list	List of custom field values for your site. (optional)
position	position	position associated with the site. (optional)
tags	list(string)	List of tags for this site.
active	boolean	Whether or not the site is activated

Retrieve a site

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/site/details?id=345' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "id":2811,
  "myId": "ref-2511",
  "name":"Sample Site",
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "Unit 2",
  "addressCity": "Falls Church",
  "addressCountry": "United States",
  "addressProvince": "Virginia",
  "addressStreet": "6605 Fisher Avenue",
  "addressZIP": "22046",
  "contactEmail":"paul@hamilton.com",
  "contactFax":"(719) 388-1967",
  "contactMobile":"(719) 388-1969",
  "contactName":"Mr Paul",
  "contactPhone":"(877) 413-5903",
  "publicLink":"https://yourdomain.synchroteam.com/Site/....",
  "customer": {
    "id":35604,
    "myId":"sCustomer08",
    "name":"Sample Customer"
  },
  "customFieldValues":[customfieldvalue1,...],
  "position":{"Position"},
  "tags" : ["plumber","restaurant","test"]
}
```

HTTP REQUEST

```
GET /api/v3/site/details?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>name</code> , the <code>id</code> or <code>myId</code> of the site

REQUEST BODY

none

RESPONSE BODY

Returns the site if found.

If the site is not found a 404 Error is returned.

Create/Update a site

Synchroteam provides a single endpoint to handle creating or updating sites. The API determines if the site record already exists by checking values provided for `id` and/or `myid`.

POST Body

```
{
  "id":2811,
  "myId": "ref-2541",
  "name":"Sample Site 2",
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "Unit 3",
  "contactEmail":"paul@hamilton.com",
  "contactFax":"(719) 388-1967",
  "contactMobile":"(719) 388-1969",
  "contactName":"Mr Paul",
  "contactPhone":"(877) 413-5903",
  "customer": {
    "id":35604
  },
  "customFieldValues":[customfieldvalue1,...],
  "position":{"Position"}
  (...)
}
```

Sample Code

```
curl --request POST \
  --url https://ws.synchroteam.com/api/v3/site/send \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{\r\n  "id":1454,\r\n  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States" (...)}'
```

JSON Returned

```
{
  "id":2811,
  "myId": "ref-2541",
  "name":"Sample Site 2",
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "Unit 3",
  "addressCity": "Falls Church",
  "addressCountry": "United States",
  "addressProvince": "Virginia",
  "addressStreet": "6605 Fisher Avenue",
  "addressZIP": "22046",
  "contactEmail":"paul@hamilton.com",
  "contactFax":"(719) 388-1967",
  "contactMobile":"(719) 388-1969",
  "contactName":"Mr Paul",
  "contactPhone":"(877) 413-5903",
  "publicLink":"https://yourdomain.synchroteam.com/Site/....",
  "customer": {
    "id":35604,
    "myId":"sCustomer08",
    "name":"Sample Customer"
  },
}
```

```
"customFieldValues": [
  {
    "id": 4411
    "label": "Service Area",
    "value": "West"
  },
  {
    "id": 95261
    "label": "Status"
    "value": "Bronze",
  }
],
"position": {
  "longitude": "74.0060"
  "latitude": "40.7128"
},
"tags" : [],
"dateModified": "2023-09-05 19:03",
"dateCreated": "2023-07-28 20:01",
"active": true
}
```

HTTP REQUEST

POST /api/v3/site/send

REQUEST BODY

Site information in JSON format, if the `id` or `myId` exist, the site will be updated, if not the site will be created. (If the provided `id` does not exist, the request will fail with an error)

When creating, if the referring customer has tags defined, these are inherited by the site.

When updating a site, if you provide a partial payload, only the fields provided will be updated. Fields not provided *will not be deleted*.

RESPONSE BODY

The response contains the updated site record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.

- * At minimum, you must provide a site **name**, an **address** (`address` or `addressCity` fields) and a **customer id or customer myId**. All other fields are not required
- * Cannot edit **tags**
- * The **active** parameter is **read-only**

Delete a site

```
curl --request DELETE \
  --url 'https://ws.synchroteam.com/api/v3/site/delete?id=2541542' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
```

```
--header 'cache-control: no-cache' \  
--header 'content-type: application/json'
```

JSON Returned

```
[  
  {  
    "id":2541542  
    "deleted":true  
  },  
  (...)  
]
```

HTTP REQUEST

```
DELETE /api/v3/site/delete
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> of the site

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a deleted parameter set to true on success, and the site ID. If no sites are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform a deletion of sites with a given name and there is more than one site using this name, every site whose name is given as a parameter will be deleted.

Undelete a site

```
curl --request POST \  
--url 'https://ws.synchroteam.com/api/v3/site/undelete?id=2541542' \  
--header 'accept: text/json' \  
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \  
--header 'cache-control: no-cache' \  
--header 'content-type: application/json'
```

JSON Returned

```
{  
  "SitesUnDeleted": [  
    {  
      "id": 1579434,  
      "isUnDeleted": true  
    }  
  ]  
}
```

```
    ]
  }
```

HTTP REQUEST

POST /api/v3/site/undelete

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> of the site

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a undeleted parameter set to true on success, and the site ID. If no sites are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform a deletion of sites with a given name and there is more than one site using this name, every site whose name is given as a parameter will be undeleted.

List sites

List all sites. Search parameters can be provided.

If no parameters are given, will return all active sites.

```
curl --request GET \
  --url https://ws.synchroteam.com/api/v3/site/list?customer_id=35604 \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C0NDQzLUE0OEutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":4,
  "recordsTotal":4,
  "data":[
    {<site object>},
    {<site object>},
    ...
    {<site object>}
  ]
}
```

HTTP REQUEST

GET /api/v3/site/list

QUERY PARAMETERS

Parameter	Type	Description
changedSince	dateTime	return sites modified after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
name	string	search by name - a wildcard search is performed
customer_id	integer	return sites belonging to a customer by customer id
customer_myId	string	return sites belonging to a customer by customer myId
active	boolean	search by active sites (Default is <i>true</i>)
sort	string	sort order, takes one of four values: <code>name</code> , <code>dateModified</code> , <code>dateCreated</code> and <code>myId</code> (Optional. Default is <i>name</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of sites found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Activate a site

```
curl --request POST \
  --url 'https://ws.synchroteam.com/api/v3/site/activate?id=2541542' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

JSON Returned

```
{
  "SitesActivated": [
    {
      "id": 1579434,
      "isActivated": true
    }
  ]
}
```

HTTP REQUEST

```
POST /api/v3/site/activate
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> of the site

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a activated parameter set to true on success, and the site ID. If no sites are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform an activation of sites with a given name and there is more than one site using this name, every site whose name is given as a parameter will be activated.

Desactivate a site

```
curl --request POST \
  --url 'https://ws.synchroteam.com/api/v3/site/desactivate?id=2541542' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

JSON Returned

```
{
  "SitesDesactivated": [
    {
      "id": 1579434,
      "isDesactivated": true
    }
  ]
}
```

HTTP REQUEST

POST /api/v3/site/desactivate

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> of the site

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a desactivated parameter set to true on success, and the site ID. If no sites are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform a desactivation of sites with a given name and there is more than one site using this name, every site whose name is given as a parameter will be desactivated.

Transfer a site

POST Body

```
{
  "site":{
    "id": 9075619,
    "myid": "147856",
    "name": "TestSite"
  },
  "toCustomer":{
    "id": 9280343,
    "myid": "1141",
    "name": "TestCustomer"
  }
}
```

```
curl --request POST \
--url 'https://ws.synchroteam.com/api/v3/site/tranfert' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{\r\n "site": {\r\n "id": 9075619,\n "myid": "147856",\n "name": "TestSite"} ...}'
```

JSON Returned

```
{
  "newCustomer": 9280343,
  "site": 9075619,
}
```

HTTP REQUEST

POST /api/v3/site/transfer

REQUEST BODY

Field	Type	Description
site	object	The site which is transferred. Specify <code>id</code> or <code>myid</code> or <code>name</code> .
toCustomer	object	Destination customer to which Site is transferred to. Specify <code>id</code> or <code>myid</code> or <code>name</code> .

RESPONSE BODY

If successful, the response contains the following data:

Field	Type	Description
newCustomer	integer	Id of the customer to which the site is transferred.

Field	Type	Description
site	integer	Id of site which was transferred.

ERRORS

If an error is encountered a 400 Error is returned, e.g.:

- *Client not found*
- *Site not found*

Equipment

The equipment object

JSON Representation

```
{
  "id":93971,
  "myId": "ref-2541",
  "name":"Heater 2345",
  "publicLink":"https://yourdomain.synchroteam.com/Equipment/...",
  "customer": {
    "id":35604,
    "myId":"sCustomer08",
    "name":"Sample Customer"
  },
  "site": {
    "id":2811,
    "myId":"ref-2511",
    "name":"Sample Site"
  },
  "customFieldValues": [
    {
      "id":4411
      "label": "Service Area",
      "value": "East"
    },
    {
      "id": 95261
      "label": "Status"
      "value": "Silver",
    }
  ],
  "tags" : ["plumber","restaurant","test"]
}
```

A piece of equipment is represented by the following fields

Field	Type	Description
id	integer	Equipment id (read only)
myId	string	Your custom reference number for this piece of equipment

Field	Type	Description
name	string	Name of the piece of equipment
publicLink	string	Link you can share with your customer to create/access the piece of equipment's jobs, invoices, etc. (read only)
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields (id or myId of a customer or site are required when creating a new piece of equipment)
site	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> site fields (id or myId of a customer or site are required when creating a new piece of equipment)
customFieldValues	list	List of custom field values for your site. (optional)
tags	list(string)	List of tags for this piece of equipment.
active	boolean	Whether or not the equipment is activated

Retrieve equipment

```
curl --request GET \  
--url 'https://ws.synchroteam.com/api/v3/equipment/details?id=93971' \  
--header 'accept: text/json' \  
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \  
--header 'cache-control: no-cache' \  
--header 'content-type: application/json'
```

JSON Returned

```
{  
  "id":93971,  
  "myId": "ref-2541",  
  "name":"Heater 2345",  
  "publicLink":"https://yourdomain.synchroteam.com/Equipment/...",  
  "customer": {  
    "id":35604,  
    "myId":"sCustomer08",  
    "name":"Sample Customer"  
  },  
  "site": {  
    "id":2811,  
    "myId":"ref-2511",  
    "name":"Sample Site"  
  },  
  "customFieldValues":[customfieldvalue1,...],  
  "tags" : ["plumber","restaurant","test"]  
}
```

HTTP REQUEST

```
GET /api/v3/equipment/details
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>name</code> , the <code>id</code> or <code>myId</code> of the piece of equipment

REQUEST BODY

none

RESPONSE BODY

Returns the piece of equipment if found.

If it is not found a 404 Error is returned.

Create/Update equipment

Synchroteam provides a single endpoint to handle creating or updating pieces of equipment. The API determines if the record already exists by checking values provide for `id` and/or `myid`.

POST Body (Create with site association)

```
{
  "myId": "ref-2541",
  "name": "Heater 2345",
  "site": {
    "id": 2811,
    "myId": "ref-2511",
    "name": "Sample Site"
  },
  "customFieldValues": [customfieldvalue1,...]
}
```

OR (Create with customer association)

```
{
  "myId": "ref-2541",
  "name": "Heater 2345",
  "customer": {
    "id": 35604,
    "myId": "sCustomer08",
    "name": "Sample Customer"
  },
  "customFieldValues": [customfieldvalue1,...],
}
```

OR (Update - site/customer not required unless you want them updated)

```
{
  "id":
  "myId": "ref-2541",
  "name": "New Heater 2345 Name",
  "customFieldValues": [customfieldvalue1,...],
}
```

Sample Code

```
curl --request POST \
  --url https://ws.synchroteam.com/api/v3/equipment/send \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0EUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
  --data '{\r\n  "myId":"ref-2542",\r\n  "name":"Heater 2345", (...)}'
```

JSON Returned

```
{
  "id":93971,
  "myId": "ref-2541",
  "name":"Heater 2345",
  "publicLink":"https://yourdomain.synchroteam.com/Equipment/...",
  "customer": {
    "id":35604,
    "myId":"sCustomer08",
    "name":"Sample Customer"
  },
  "site": {
    "id":2811,
    "myId":"ref-2511",
    "name":"Sample Site"
  },
  "customFieldValues": [
    {
      "id":4411
      "label": "Service Area",
      "value": "East"
    },
    {
      "id": 95261
      "label": "Status"
      "value": "Silver",
    }
  ],
  "tags" : ["plumber", "restaurant", "test"],
  "dateModified": "2023-09-05 19:03",
  "dateCreated": "2023-07-28 20:01",
  "active": true
}
```

HTTP REQUEST

POST /api/v3/equipment/send

REQUEST BODY

Data for a piece of equipment in JSON format. If the `id` or `myId` exist, the piece of equipment will be updated, if not the piece of equipment will be created. (If the provided `id` does not exist, the request will fail with an error)

When creating, if the referring site or customer has tags defined, these are inherited by the piece of equipment.

When updating, if you provide a partial payload, only the fields provided will be updated. Fields not provided *will not be deleted*.

RESPONSE BODY

The response contains the updated equipment record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.

!

* At minimum, you must provide an **equipment name** and either: a **customer** (using ``id`` or ``myId``), or a **site** (using ``id`` or ``myId``). If both are provided, only the site will be taken into account. All other fields are not required

* Cannot edit **tags**

* The **active** parameter id **read-only**

Delete equipment

```
curl --request DELETE \
--url 'https://ws.synchroteam.com/api/v2/equipment/delete?id=939721' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUTQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

JSON Returned

```
[
  {
    "id":939721
    "deleted":true
  },
  (...)
]
```

HTTP REQUEST

DELETE /api/v3/equipment/delete

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> of the site

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a deleted parameter set to true on success, and the equipment ID. If no pieces of equipment are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform a deletion of pieces of equipment with a given name and there is more than one using this name, every equipment record that matches the name given as a parameter will be deleted.

Undelete equipment

```
curl --request POST \
--url 'https://ws.synchroteam.com/api/v2/equipment/undelete?id=939721' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C00NDQzLUE0E0EutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

JSON Returned

```
{
  "EquipmentsUnDeleted": [
    {
      "id": 939721,
      "isUnDeleted": true
    }
  ]
}
```

HTTP REQUEST

```
POST /api/v3/equipment/undelete
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> of the site

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a undeleted parameter set to true on success, and the equipment ID. If no pieces of equipment are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform a undeletion of pieces of equipment with a given name and there is more than one using this name, every equipment record that matches the name given as a parameter will be undeleted.

List equipment

List all equipments. Search parameters can be provided.

If no parameters are given, will return all active equipments.

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/equipment/list?site_id=2811 \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C00NDQzLUE0E0EutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "page": 1,
  "pageSize": 25,
  "records": 6,
  "recordsTotal": 6,
  "data": [
    {<equipment object>},
    {<equipment object>},
    ...
    {<equipment object>}
  ]
}
```

HTTP REQUEST

GET /api/v3/equipment/list

QUERY PARAMETERS

Parameter	Type	Description
changedSince	dateTime	return pieces of equipment modified after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
name	string	search by name - a wildcard search is performed
customer_id	integer	return equipment belonging to a customer by customer id
customer_myId	string	return equipment belonging to a customer by customer myId
site_id	integer	return equipment belonging to a site by site id
site_myId	string	return equipment belonging to a site by site myId
active	boolean	search by active equipments (Default is <i>true</i>)
sort	string	sort order, takes one of three values: <code>name</code> , <code>dateModified</code> , <code>dateCreated</code> and <code>myId</code> (Optional. Default is <i>name</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of equipment found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Activate an equipment

```
curl --request POST \
  --url 'https://ws.synchroteam.com/api/v2/equipment/activate?id=939721' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0EUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

JSON Returned

```
{
  "EquipmentsActivated": [
    {
      "id": 1579434,
      "isActivated": true
    }
  ]
}
```

HTTP REQUEST

```
POST /api/v3/equipment/activate
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> of the site

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a activated parameter set to true on success, and the equipment ID. If no pieces of equipment are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform an activation of pieces of equipment with a given name and there is more than one using this name, every equipment record that matches the name given as a parameter will be activated.

Deactivate an equipment

```
curl --request POST \
  --url 'https://ws.synchroteam.com/api/v2/equipment/deactivate?id=939721' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0EUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

JSON Returned

```
{
  "EquipmentsDesactivated": [
```

```
{
  "id": 1579434,
  "isDesactivated": true
}
```

HTTP REQUEST

POST /api/v3/equipment/desactivate

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>name</code> , <code>id</code> or <code>myId</code> of the site

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a desactivated parameter set to true on success, and the equipment ID. If no pieces of equipment are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform a desactivation of pieces of equipment with a given name and there is more than one using this name, every equipment record that matches the name given as a parameter will be desactivated.

Transfer an equipment

POST Body

```
{
  "equipment":{
    "id": 6347394,
    "myid": "",
    "name": "TestEquipment"
  },
  "toSite":{
    "id": 9075619,
    "myid": "147856",
    "name": "TestSite"
  },
  "toCustomer":{
    "id": 9280343,
    "myid": "1141",
    "name": "TestCustomer"
  }
}
```

```
curl --request POST \
--url 'https://ws.synchroteam.com/api/v3/equipment/tranfert' \
--header 'accept: text/json' \
```

```
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{\r\n  "equipment": {\r\n    "id": 6347394,\r\n    "myid": "",\r\n    "name": "TestSite"} ...}'
```

JSON Returned

```
{
  "newCustomer": 9280343,
  "newSite": 9075619,
  "equipment": 6347394
}
```

HTTP REQUEST

POST /api/v3/equipment/transfer

REQUEST BODY

Field	Type	Description
equipment	object	The equipment which is transferred. Specify <code>id</code> or <code>myid</code> or <code>name</code> .
toSite	object	Destination site to which Equipment is transferred to. Specify <code>id</code> or <code>myid</code> or <code>name</code> . (Optional)
toCustomer	object	Destination customer to which Equipment is transferred to. Specify <code>id</code> or <code>myid</code> or <code>name</code> .

RESPONSE BODY

If successful, the response contains the following data:

Field	Type	Description
newCustomer	integer	Id of the customer to which the equipment is transferred.
newSite	integer	Id of the site to which the equipment is transferred.
equipment	integer	Id of equipment which was transferred.

When transferring an equipment, if you provide only the Customer, the equipment will no longer be attached to a Site.

ERRORS

If an error is encountered a 400 Error is returned, e.g.:

- *Client not found*
- *Site not found*
- *Equipment not found*

Jobs

The job object

JSON Representation

```
{
  "id": "265_160719144323649",
  "myId": "ref-job05014",
  "num": 154872,
  "description": "This is the job description",
  "priority": "low",
  "customer": {
    "id": 35604,
    "myId": "sCustomer08",
    "name": "Sample Customer",
  },
  "site": {
    "id": 2811,
    "myId": "ref-2511",
    "name": "Sample Site",
  },
  "equipment": {
    "id": 93971,
    "myId": "ref-2541",
    "name": "Heater 2345",
  },
  "type": {
    "id": 629,
    "name": "Standard Job"
  },
  "reportTemplate": {
    "id": 781,
    "name": "Maintenance Report"
  },
  "technician": {
    "id": 1551,
    "name": "John Doe",
    "login": "johndoe"
  },
  "otherTechnicians": [
    {
      "id": 1552,
      "name": "Jim Doe",
      "login": "jimdoe"
    },
    {
      "id": 1553,
      "name": "Jane Doe",
      "login": "janedoe"
    }
  ],
  "createdBy": {
    "id": 265,
    "name": "Bill Williams",
    "login": "billw"
  },
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "Unit 2",
  "addressCity": "Falls Church",
  "addressCountry": "United States",
  "addressProvince": "Virginia",
  "addressStreet": "6605 Fisher Avenue",
  "addressZIP": "22046",
  "position": {
    "latitude": "43.9695148",
    "longitude": "-99.90181310000"
  },
  "contactFirstName": "Paul",
  "contactLastName": "Hamilton",
  "contactEmail": "paul@hamilton.com",
}
```

```

"contactMobile": "(719) 388-1969",
"contactPhone": "(877) 413-5903",
"scheduledStart": "19/07/2016 14:43:00",
"scheduledEnd": "19/07/2016 16:43:00",
"actualStart": "19/07/2016 14:50:00",
"actualEnd": "19/07/2016 16:16:00",
"createdByCustomer": false,
"duration": 86,
"status": "completed",
"publicLink": "https://yourdomain.synchroteam.com/Jobs/PublicJob/afb5853-3ec6-46ea-bc9c-db4e75a63bc2",
"timeEntries": [
  {
    "user": {
      "id": 1551,
      "name": "John Doe",
      "login": "johndoe"
    },
    "start": "19/07/2016 14:50:00",
    "stop": "19/07/2016 14:56:00"
  },
  {
    "user": {
      "id": 1551,
      "name": "John Doe",
      "login": "johndoe"
    },
    "start": "19/07/2016 15:05:00",
    "stop": "19/07/2016 15:46:00"
  },
  {
    "user": {
      "id": 1551,
      "name": "John Doe",
      "login": "johndoe"
    },
    "login": "techtest",
    "start": "19/07/2016 15:58:00",
    "stop": "19/07/2016 16:16:00"
  }
],
"parts": [
  {
    "id": 34454,
    "quantity": 2,
    "reference": "ACCROCHE FIX CF62033",
    "serialNumbers": ["1234r5twy3y", "45yue596ksmg5"]
  },
  {
    "id": 35947,
    "quantity": 10,
    "reference": "111-a",
    "serialNumbers": null
  }
],
"report": <job report object>,
"customFieldValues": [
  {
    "label": "sector",
    "value": "",
    "id": 182
  },
  {
    "label": "city",
    "value": "",
    "id": 185
  }
],
"dateCreated": "15/07/2017 13:28:00",

```

```
"dateModified": "19/07/2017 11:11:00",
"preferences": {
  "date": "2019-03-10",
  "dateTime": null,
  "isDraft": true,
  "isPool": false,
  "schedulingWindow": {
    "id": 1,
    "name": "Morning"
  },
},
"team": {
  "id": 4512,
  "name": "California"
},
"user": {
  "id": 72300,
  "name": "Andrew Smith",
  "login": "asmith"
}
},
"skills":["Plumber","Electrician"],
"tags":["East"],
"validateBy": {
  "id": 57246,
  "login": "johndoe",
  "name": "John Doe",
  "date": "2021-02-01 15:37"
}
}
```

A job is represented by the following fields.

Field	Type	Description
id	string	ID of the job (read only)
myId	string	Your custom reference number for this job
num	integer	Number of the job
priority	string	Job priority: <code>low</code> , <code>medium</code> or <code>high</code> . Default is <code>medium</code> .
description	string	Job Description
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields (id or myId required when creating a job)
site	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> site fields (id or myId of a customer or site are required when creating a new job)
equipment	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> equipment fields (optional)
type	object	Object containing <code>id</code> and <code>name</code> for the job type.
reportTemplate	object	Object containing <code>id</code> and <code>name</code> for the job report template
technician	object	Object containing <code>id</code> , <code>name</code> and <code>login</code> for the user assigned to the job

Field	Type	Description
createdBy	object	Object containing <code>id</code> , <code>login</code> or <code>name</code> for the user that created the job
address	string	Complete Address
addressStreet	string	Street address for the job
addressComplement	string	Complementary street address information
addressZIP	string	Address zip code
addressCity	string	Address city
addressProvince	string	Address province/state
addressCountry	string	Address country
position	position associated with the job. (optional)	
contactFirstName	string	Contact First Name
contactLastName	string	Contact Last Name
contactMobile	string	Contact Mobile Number
contactPhone	string	Contact Phone Number
contactEmail	string	Contact Email Address
scheduledStart	date time	Scheduled Start Date
scheduledEnd	date time	Scheduled End Date
actualStart	date time	Actual Start Date
actualEnd	date time	Actual End Date
createdByCustomer	boolean	Whether or not the job has been created by a Customer
duration	integer	Time spent working on the job, given in minutes
status	string	Job Status, one of: <code>created</code> , <code>scheduled</code> , <code>synchronized</code> , <code>started</code> , <code>paused</code> , <code>completed</code> , <code>validated</code> or <code>cancelled</code>
publicLink	string	Public link for the job
otherTechnicians	list of objects	Other technicians associated with this job. List of user objects containing <code>id</code> , <code>name</code> and <code>login</code> .
timeEntries	list of objects	Each object contains a simplified user object, <code>start</code> (datetime) and <code>stop</code> (datetime)
parts	list	List of parts consumed for the job

Field	Type	Description
report	report	Job Detail : Report details, as filled by the technician Job Creation : list of Item containing <code>nmCategory</code> , <code>nmItem</code> , <code>value</code> , and <code>iteration</code>
customFieldValues	list	List of custom field values for your job
tags	list(string)	List of tags for this job (read-only)
skills	list(string)	List of required skills for this job
dateCreated	datetime	creation date
dateModified	datetime	last modification date
preferences	object	Job Scheduling Preferences for the job
validateBy	object	Object containing <code>id</code> , <code>login</code> , <code>name</code> and <code>date</code> for the user that validated the job and when
geocoding	boolean	Whether or not the geocoding is activated (true by default)
dateDeleted	datetime	Deletion date

Retrieve a job

```
curl --request GET \  
--url 'https://ws.synchroteam.com/api/v3/job/details?id=265_160719144323649' \  
--header 'accept: text/json' \  
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQTbB' \  
--header 'cache-control: no-cache' \  
--header 'content-type: application/json' \  

```

JSON Returned

```
{  
  "id": "265_160719144323649",  
  "myId": "ref-job05014",  
  "num": 154872,  
  "description": "This is the job description",  
  "priority": "low",  
  "customer": {  
    "id": 35604,  
    "myId": "sCustomer08",  
    "name": "Sample Customer",  
  },  
  "site": {  
    "id": 2811,  
    "myId": "ref-2511",  
    "name": "Sample Site",  
  },  
  "equipment": {  
    "id": 93971,  
    "myId": "ref-2541",  
    "name": "Heater 2345",  
  },  
}
```

```

    },
    "type": {
      "id": 629,
      "name": "Standard Job"
    },
    "reportTemplate": {
      "id": 781,
      "name": "Maintenance Report"
    },
    "technician": {
      "id": 1551,
      "name": "John Doe",
      "login": "johndoe"
    },
    "otherTechnicians": [
      {
        "id": 1552,
        "name": "Jim Doe",
        "login": "jimdoe"
      },
      {
        "id": 1553,
        "name": "Jane Doe",
        "login": "janedoe"
      }
    ],
    "createdBy": {
      "id": 265,
      "name": "Bill Williams",
      "login": "billw"
    },
    "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
    "addressComplement": "Unit 2",
    "addressCity": "Falls Church",
    "addressCountry": "United States",
    "addressProvince": "Virginia",
    "addressStreet": "6605 Fisher Avenue",
    "addressZIP": "22046",
    "position": {
      "latitude": "43.9695148",
      "longitude": "-99.90181310000"
    },
    "contactFirstName": "Paul",
    "contactLastName": "Hamilton",
    "contactEmail": "paul@hamilton.com",
    "contactMobile": "(719) 388-1969",
    "contactPhone": "(877) 413-5903",
    "scheduledStart": "19/07/2016 14:43:00",
    "scheduledEnd": "19/07/2016 16:43:00",
    "actualStart": "19/07/2016 14:50:00",
    "actualEnd": "19/07/2016 16:16:00",
    "createdByCustomer": false,
    "duration": 86,
    "status": "completed",
    "publicLink": "https://yourdomain.synchroteam.com/Jobs/PublicJob/afb5853-3ec6-46ea-bc9c-db4e75a63bc2",
    "timeEntries": [
      {
        "user": {
          "id": 1551,
          "name": "John Doe",
          "login": "johndoe"
        },
        "start": "19/07/2016 14:50:00",
        "stop": "19/07/2016 14:56:00"
      },
      {
        "user": {
          "id": 1551,

```

```
      "name": "John Doe",
      "login": "johndoe"
    },
    "start": "19/07/2016 15:05:00",
    "stop": "19/07/2016 15:46:00"
  },
  {
    "user": {
      "id": 1551,
      "name": "John Doe",
      "login": "johndoe"
    },
    "login": "techtest",
    "start": "19/07/2016 15:58:00",
    "stop": "19/07/2016 16:16:00"
  }
],
"parts": [
  {
    "id": 34454,
    "quantity": 2,
    "reference": "ACCROCHE FIX CF62033",
    "serialNumbers": ["1234r5twy3y", "45yue596ksmg5"]
  },
  {
    "id": 35947,
    "quantity": 10,
    "reference": "111-a",
    "serialNumbers": null
  }
],
"report": <job report object>,
"customFieldValues": [
  {
    "label": "sector",
    "value": "",
    "id": 182
  },
  {
    "label": "city",
    "value": "",
    "id": 185
  }
],
"dateCreated": "17/07/2017 13:28:00",
"dateModified": "19/07/2017 11:11:00",
"validateBy": {
  "id": 57246,
  "login": "johndoe",
  "name": "John Doe",
  "date": "2021-02-01 15:37"
}
```

HTTP REQUEST

GET /api/v3/job/details?paramType=paramValue

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>num</code> or <code>id</code> or <code>myId</code>

Parameter	Type	Description
{paramValue}	string	The <code>num</code> or <code>id</code> or <code>myId</code> for the job

REQUEST BODY

none

RESPONSE BODY

Job information in JSON format

Create/Update a job

Synchroteam provides a single endpoint to handle creating or updating jobs. The API determines if the job record already exists by checking values provided for `id` and/or `myid` and/or `num`.

POST Body

```
{
  "myId": "ref-job05014",
  "description": "This is the job description",
  "priority": "low",
  "customer": {
    "id": 35604
  },
  "site": {
    "myId": "ref-2511"
  },
  "equipment": {
    "myId": "ref-2541"
  },
  "type": {
    "id": 629
  },
  "reportTemplate": {
    "id": 781
  },
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "Unit 2",
  "contactFirstName": "Paul",
  "contactLastName": "Hamilton",
  "contactEmail": "paul@hamilton.com",
  "contactMobile": "(719) 388-1969",
  "contactPhone": "(877) 413-5903",
  "scheduledStart": "19/07/2016 14:43:00",
  "scheduledEnd": "19/07/2016 16:43:00",
  "status": "scheduled",
  "report": [<only for Job creation>
    {
      "idCategory": 123,
      "nmCategory": "Customer section",
      "id": 78941,
      "nmItem": "Did the Customer approve the quote?",
      "value": "Yes",
      "iteration": 0
    }, <...>,
  ],
  "customFieldValues": [
    {
```

```
    "label": "sector",
    "value": "",
    "id": 182
  },
  {
    "label": "city",
    "value": "",
    "id": 185
  }
],
"skills":["Plumber"]
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/job/send \
--header 'accept: text/json' \
--header 'content-type: application/json' \
--data '{\r\n  "myId": "ref-job05014",\r\n  "description": "This is the job description" (...)}'
```

JSON Returned

```
{
  "id": "265_160719144323649",
  "myId": "ref-job05014",
  "num": 154872,
  "description": "This is the job description",
  "priority": "low",
  "customer": {
    "id": 35604,
    "myId": "sCustomer08",
    "name": "Sample Customer",
  },
  "site": {
    "id": 2811,
    "myId": "ref-2511",
    "name": "Sample Site",
  },
  "equipment": {
    "id": 93971,
    "myId": "ref-2541",
    "name": "Heater 2345",
  },
  "type": {
    "id": 629,
    "name": "Standard Job"
  },
  "reportTemplate": {
    "id": 781,
    "name": "Maintenance Report"
  },
  "technician": null,
  "otherTechnicians": [],
  "createdBy": {
    "id": 265,
    "name": "Bill Williams",
    "login": "billw"
  },
  "address": "6605 Fisher Avenue, Falls Church, VA 22046, United States",
  "addressComplement": "Unit 2",
}
```

```

"addressCity": "Falls Church",
"addressCountry": "United States",
"addressProvince": "Virginia",
"addressStreet": "6605 Fisher Avenue",
"addressZIP": "22046",
"position": {
  "latitude": "43.9695148",
  "longitude": "-99.90181310000"
},
"contactFirstName": "Paul",
"contactLastName": "Hamilton",
"contactEmail": "paul@hamilton.com",
"contactMobile": "(719) 388-1969",
"contactPhone": "(877) 413-5903",
"scheduledStart": "19/07/2016 14:43:00",
"scheduledEnd": "19/07/2016 16:43:00",
"actualStart": null,
"actualEnd": null,
"duration": 86,
"status": "scheduled",
"publicLink": "https://yourdomain.synchroteam.com/Jobs/PublicJob/afb5853-3ec6-46ea-bc9c-db4e75a63bc2",
"timeEntries": [],
"report": <job report object>,
"customFieldValues": [
  {
    "label": "sector",
    "value": "",
    "id": 182
  },
  {
    "label": "city",
    "value": "",
    "id": 185
  }
],
"dateCreated": "17/07/2017 13:28:00",
"dateModified": "19/07/2017 11:11:00",
}

```

HTTP REQUEST

POST /api/v3/job/send

REQUEST BODY

Job information in JSON format, if `idJob` or `myId` or `num` exist, the job will be updated, if not the job will be created.

When updating a job, if you provide a partial payload, only the fields provided will be updated. Fields not provided *will not be deleted*.

RESPONSE BODY

The response contains the updated job record, with the `id` field and `num` specified.

If an error occurred, a standard error payload will be returned.

- * At minimum: you must provide a **customer object with id, name or myId**. All other fields are not required
- * Cannot edit a started job
- * Cannot edit the `parts` or the `report`

REMARK

Only when creating a Job (not updating) you can initialize Report Values using a `Simplified Report` which consists on an Array of `Simplified Items`. See sample on right panel.

Delete a job

```
curl --request DELETE \
  --url 'https://ws.synchroteam.com/api/v3/job/delete?id=265_160719144323649' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C00NDQzLUE00EutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

JSON Returned

```
[
  {
    "id":265_160719144323649
    "deleted":true
  },
  (...)
]
```

HTTP REQUEST

```
DELETE /api/v3/job/delete
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>num</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	The <code>num</code> , <code>id</code> or <code>myId</code> of the job

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a deleted parameter set to true on success, and the job ID. If no jobs are found, a 404 error is returned.

The list will generally only contain a single response object.

List jobs

Sample Code

```
curl --request GET \
  --url https://ws.synchroteam.com/api/v3/job/list?customer_id=35604&dateFrom=2018-12-01+00:00:00 \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C00NDQzLUE00EutQzhEMjg4NzhBQThB' \
```

```
--header 'cache-control: no-cache' \  
--header 'content-type: application/json'
```

JSON Returned

```
{  
  "page":1,  
  "pageSize":25,  
  "records":25,  
  "recordsTotal":32,  
  "data":[  
    {<job object>},  
    {<job object>},  
    ...  
    {<job object>}  
  ]  
}
```

HTTP REQUEST

```
GET /api/v3/job/list
```

QUERY PARAMETERS

Parameter	Type	Description
myId	string	Filter by job myId
status	string	Filter by current job status (<code>created</code> , <code>scheduled</code> , <code>synchronized</code> , <code>started</code> , <code>paused</code> , <code>completed</code> , <code>validated</code> or <code>cancelled</code>), one or more status separated by commas are allowed.
dateFrom	date time (yyyy-mm-dd hh:mm:ss)	Get jobs planned, ongoing or completed on or after <code>dateFrom</code>
dateTo	date time (yyyy-mm-dd hh:mm:ss)	Get jobs planned, ongoing or completed on or before <code>dateTo</code>
createdSince	date time (yyyy-mm-dd hh:mm:ss)	Get jobs created, planned, ongoing or completed on or after <code>createdSince</code>
changedSince	date time (yyyy-mm-dd hh:mm:ss)	Get jobs planned, ongoing or completed, the older modification checked on or after <code>change dSince</code>
reportChangedSince	date time (yyyy-mm-dd hh:mm:ss)	Get jobs planned, ongoing or completed, the older modification checked in his report on or after <code>reportChangedSince</code>
validatedSince	date time (yyyy-mm-dd hh:mm:ss)	Get jobs validated on or after <code>validatedSince</code>
user_login	string	Get jobs assigned to a technician, by user <code>login</code>

Parameter	Type	Description
user_id	integer	Get jobs assigned to a technician, by user <code>id</code>
team_id	integer	Get jobs assigned to a technician of the Team, by Team <code>id</code>
team_id_pref	integer	Get jobs with the Team in the Scheduling Preferences, by Team <code>id</code>
customer_id	integer	return jobs belonging to a customer by customer <code>id</code>
customer_myId	string	return jobs belonging to a customer by customer <code>myId</code>
site_id	integer	return jobs belonging to a site by site <code>id</code>
site_myId	string	return jobs belonging to a site by site <code>myId</code>
equipment_id	integer	return jobs belonging to a piece of equipment by equipment <code>id</code>
equipment_myId	string	return jobs belonging to a piece of equipment by equipment <code>myId</code>
type_id	integer	Get jobs using a specific Job Type, by jobtype <code>id</code>
type_name	string	Get jobs using a specific Job Type, by jobtype <code>name</code>
reportTemplate_id	integer	Get jobs using a specific Job Report Template, by report <code>id</code>
reportTemplate_name	string	Get jobs using a specific Job Report Template, by report <code>name</code>
project_id	string	Get jobs using a specific Project, by project <code>id</code>
project_myId	string	Get jobs using a specific Project, by project <code>myId</code>
project_num	string	Get jobs using a specific Project, by project <code>num</code>
hasPhotos	boolean	whether or not the Job has pictures
otherTechnicians	boolean	whether or not the field otherTechnicians (<code>id</code> , <code>name</code> , <code>login</code>) is shown in the results of the request
sort	string	sort order, takes one of the following values: <code>num</code> , <code>scheduledstart</code> , <code>scheduledend</code> , <code>actualstart</code> , <code>actualend</code> or <code>datemodified</code> (Optional. Default is <i>num</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)
show	string	accepts one of three values: <code>active</code> , <code>deleted</code> or <code>all</code> (default: <code>active</code>)

Add pagination parameters if needed.

RESPONSE BODY

A list of **simplified** jobs found. A `Simplified Job` is a job object without Report nor Parts nor Scheduling Preferences nor Other Technicians list nor Time Entries.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Schedule a job

Schedule a job using `id`, `myId` or `num`. Provide the desired schedule, and technician assigned.

Example POST Body

```
{
  "id": "265_160719144323649",
  "scheduledStart": "2018-12-12 15:00:00",
  "scheduledEnd": "2018-12-12 17:00:00",
  "technician": {
    "id": 1551
  },
  "otherTechnicians": [
    {
      "login": "alainpp"
    }
  ]
}
```

Sample Code

```
curl --request POST \
  --url https://ws.synchroteam.com/api/v3/job/schedule\
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0EUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{"id":"265_160719144323649","scheduledStart":"2018-12-12 15:00:00","scheduledEnd":"2018-12-12 17:00:00","technician":{"id":1551}}'
```

JSON Returned

```
[
  {
    "id": "265_160719144323649",
    "status": "scheduled",
    "scheduledStart": "2018-12-12 15:00:00",
    "scheduledEnd": "2018-12-12 17:00:00",
    "technician": {
      "id": 1551,
      "name": "John Doe",
      "login": "johndoe"
    },
    "otherTechnicians": [
      {
        "id": 59728,
        "name": "alain pp",
        "login": "alainpp"
      }
    ]
  }
]
```

HTTP REQUEST

POST /v3/job/schedule

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	string	ID of the job
myId	string	Your custom reference number for this job
num	integer	Number of the job
scheduledStart	date time (yyyy-mm-dd hh:mm:ss)	Start date and time
scheduledEnd	date time (yyyy-mm-dd hh:mm:ss)	End date and time
technician	object	Object containing <code>id</code> , <code>name</code> and <code>login</code> for the user assigned to the job
otherTechnicians	list of objects	Other technicians associated with this job. List of user objects containing <code>id</code> , <code>name</code> and <code>login</code> .

NB: You can re-schedule the suspended job to another technician.

RESPONSE BODY

The response contains a list of scheduled jobs, job id, status, schedule and technician assigned.

* At minimum: you must provide a **job id, myId or num** a **scheduledStart** a **scheduledEnd** and a **user object with id, name or login**

Unschedule a job

Unschedule a job using `id`, `myId` or `num`.

Example POST Body

```
{
  "id": "265_160719144323649",
}
```

Sample Code

```
curl --request POST \
  --url https://ws.synchroteam.com/api/v3/job/unschedule\
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{"id":"265_160719144323649"}'
```

JSON Returned

```
[
  {
    "id": "265_160719144323649",
    "status": "scheduled",
    "scheduledStart": null,
    "scheduledEnd": null,
    "technician": null
  }
]
```

HTTP REQUEST

POST /v3/job/unschedule

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	string	ID of the job
myId	string	Your custom reference number for this job
num	integer	Number of the job

RESPONSE BODY

The response contains a list of unscheduled jobs, job id and status with schedule and technician set to null.

Cancel a job

Cancel a job using `id`, `myId` or `num`.

Example POST Body

```
{
  "id": "265_160719144323649",
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/job/cancel\
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{"id":"265_160719144323649"}'
```

JSON Returned

```
[
  {

```

```
    "id": "265_160719144323649",
    "status": "cancelled",
  }
]
```

HTTP REQUEST

POST /v3/job/cancel

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	string	ID of the job
myId	string	Your custom reference number for this job
num	integer	Number of the job

RESPONSE BODY

The response contains a list of cancelled jobs, job id and status specified.

Validate a job

Validate a job using `id`, `myId` or `num`

Example POST Body

```
{
  "id": "265_160719144323649",
  "validateBy": {
    "id": 57246,
    "login": "johndoe"
  }
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/job/validate \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUTQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{"id": "265_160719144323649","validateBy": {"id": 57246,"login": "johndoe"}}'
```

JSON Returned

```
[
  {
    "id": "265_160719144323649",
    "status": "validated"
  }
]
```

```
}
]
```

HTTP REQUEST

POST /v3/job/validate

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	string	ID of the job
myId	string	Your custom reference number for this job
num	integer	Number of the job
validateBy	object	Object containing <code>id</code> or <code>login</code> of the user who validates the job

RESPONSE BODY

The response contains a list of validated jobs, showing the job id and status.

Start a job

Start a job using `id`, `myId` or `num` and `actualStartv` (default value = Date Time Now)

Example POST Body

```
{
  "id": "f9d0cb7b-ef8e-4f36-807f-21bcd47d53b7",
  "actualStart": "2023-08-19 13:20"
}
```

Sample Code

```
curl --request POST \
  --url https://ws.synchroteam.com/api/v3/job/start \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{"id":"265_160719144323649"}'
```

JSON Returned

```
[
  {
    "job": {
      "id": "f9d0cb7b-ef8e-4f36-807f-21bcd47d53b7",
      "myId": null,
      "num": 2966
    },
    "startDate": "2023-08-19 13:20"
  }
]
```

```
  "status": "started"
]
```

HTTP REQUEST

POST /v3/job/start

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	string	ID of the job
myId	string	Your custom reference number for this job
num	integer	Number of the job

RESPONSE BODY

The response contains a started job, showing the job, startDate and status.

NB: If the job technician already has another started job, the latter is paused.

Pause a job

Pause a job using `id`, `myId` or `num`

Example POST Body

```
{
  "id": "f9d0cb7b-ef8e-4f36-807f-21bcd47d53b7"
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/job/pause \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQTthB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{"id":"265_160719144323649"}'
```

JSON Returned

```
[
  {
    "job": {
      "id": "f9d0cb7b-ef8e-4f36-807f-21bcd47d53b7",
      "myId": null,
      "num": 2966
    },
    "status": "paused",
  }
]
```

```
    "pauseDate": "2025-11-24 14:08"
  ]
}
```

HTTP REQUEST

POST /v3/job/pause

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	string	ID of the job
myId	string	Your custom reference number for this job
num	integer	Number of the job

RESPONSE BODY

The response contains a paused job, showing the job, pauseDate and status.

Confirm a job

Confirm the Scheduling of a job currently in Draft status, using `id`, `myId` or `num`

Example POST Body

```
{
  "id": "265_160719144323649"
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/job/confirm \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{"id":"265_160719144323649"}'
```

JSON Returned

```
[
  {
    "id": "265_160719144323649",
    "status": "confirmed"
  }
]
```

HTTP REQUEST

POST /v3/job/confirm

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	string	ID of the job
myId	string	Your custom reference number for this job
num	integer	Number of the job

RESPONSE BODY

The response contains a list of confirmed jobs, showing the job id and status.

Complete a job

Complete a job using `id` (or `myId` or `num`), and both `actualStart` and `endStart`

Example POST Body

```
{
  "id": "265_160719144323649",
  "actualStart": "2019-11-06 13:13",
  "actualEnd": "2019-11-06 14:28"
}
```

Sample Code

```
curl --request POST \
  --url https://ws.synchroteam.com/api/v3/job/complete \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQTthB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{"id":"265_160719144323649","actualStart":"2019-11-06 13:13","actualEnd":"2019-11-06 14:28"}'
```

JSON Returned

```
[
  {
    "id": "265_160719144323649",
    "status": "completed"
  }
]
```

HTTP REQUEST

POST /v3/job/complete

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	string	ID of the job
myId	string	Your custom reference number for this job
num	integer	Number of the job
actualStart	datetime	Real Start Date & Time
actualEnd	datetime	Real End Date & Time

RESPONSE BODY

The response contains a list of completed jobs, showing the job id and status.

Retrieve job photos

Returns a list of photos for a given job. Get job photos by job `id`, `num` or `myId`

DESCRIPTION

NB: photos are represented using the following fields :

Field	Type	Description
url	string	url to download photo
fileName	string	Name of the file, including the extension (.png, .jpg, etc.)
iteration	integer	defaults to 0. If the photo is within a repeatable report block, will show which block iteration the photo came from.
comment	string	Comment associated to the photo
imageData	String	Image data encoded as a Base64String (optional)

Sample Code

```
curl --request GET \
  --url 'https://ws.synchroteam.com/api/v3/job/photos?myId=ref-25415&getImageData=true&getImageData=true' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE00EUTQzhEMjg4NzhBQTlhB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

JSON Returned

```
{
  "job": {
    "id": "265_160719144323649",
    "myId": "ref-25415",
    "num": 13473
  },
}
```

```
"photos":[
  {
    "url":"https://url.to/image.png",
    "fileName": "image.png",
    "iteration": 0,
    "comment":"a Comment",
    "imageData":[Base64String]
  },
  {
    "url":"https://url.to/image1.png",
    "fileName": "image1.png",
    "iteration": 0,
    "comment":"photo1",
    "imageData":[Base64String]
  },
  {
    "url":"https://url.to/image2.png",
    "fileName": "image2.png",
    "iteration": 1,
    "comment":"photo2",
    "imageData":[Base64String]
  }
]
```

HTTP REQUEST

```
GET /v3/job/photos?{paramType}={paramValue}&getImageData={true|false}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>num</code> or <code>id</code> or <code>myId</code>
{paramValue}	string	<code>num</code> or <code>id</code> or <code>myId</code> for the job
getImageData	boolean	if set to true, image data will be provided in base64 format. If set to false imageData will be set to null (default: false)

REQUEST BODY

none

RESPONSE BODY

A simplified job object and the list of photos for the job.

Send job parts

Synchroteam provides a single endpoint to handle adding Parts on a Job. The Job is identified by its `id`, `num` or `myId`.

POST Body

```
{
  "id": null,
  "myId": "GFrance2020-APIv3_2035",
  "num": 0,
  "parts": [
```

```
{
  "id": null,
  "quantity": 2,
  "reference": "1002",
  "serialNumbers": ["123", "7"]
},
{
  "id": null,
  "quantity": 50,
  "reference": "REF_API_002",
  "serialNumbers": null
},
{
  "id": null,
  "quantity": 35,
  "reference": "REF_API_020",
  "serialNumbers": null
}
]
```

Sample Code

```
curl --location --request POST 'https://ws.synchroteam.com/api/v3/job/parts/send' \
--header 'Authorization: Basic ZGVtbzo1Y2MyODM4MS01ZTM0LTQ0YWUyYjk1MC05MWI1MDQxMTA3ZTE=' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--data-raw '{"id": null,"myId": "GFrance2020-APIv3_2035","num": 0,"parts": [...]}'
```

JSON Returned

```
{
  "id": "c1736b28-49ca-4bd7-b2e6-fb8c4a5b34fe",
  "parts": [
    {
      "id": null,
      "quantity": 2,
      "reference": "1002",
      "serialNumbers": ["123", "7"]
    },
    {
      "id": null,
      "quantity": 50,
      "reference": "REF_API_002",
      "serialNumbers": null
    },
    {
      "id": null,
      "quantity": 35,
      "reference": "REF_API_020",
      "serialNumbers": null
    }
  ]
}
```

HTTP REQUEST

POST /api/v3/job/parts/send

REQUEST BODY

- The Job identified by its `id`, `num` or `myId`.

Job Scheduling Preferences

The job scheduling preferences object

```
{
  "date": "2019-03-10",
  "dateTime": null,
  "isDraft": true,
  "isPool": false,
  "schedulingWindow": {
    "id": 1,
    "name": "Morning"
  },
  "team": {
    "id": 4512,
    "name": "California"
  },
  "user": {
    "id": 72300,
    "name": "Andrew Smith",
    "login": "asmith"
  },
  "freeNote": "Free note text"
}
```

Job Scheduling Preferences are represented by the following fields

Field	Type	Description
date	date (yyyy-mm-dd)	Prefered Date
dateTime	date (yyyy-mm-dd hh:mm:ss)	Meeting Date & Time
isDraft	bool	Specify if the Job will be scheduled as Draft (not synced on technician devices)
isPool	bool	Specify if the Job belongs to Job Pool list
schedulingWindow	object	Object containing <code>id</code> and <code>name</code> job scheduling window fields
team	object	Object containing <code>id</code> and <code>name</code> team fields
user	object	Object containing <code>id</code> , <code>name</code> and <code>login</code> technician fields (<code>name</code> is read-only)
freeNote	string	Scheduling preference note

Job Scheduling Windows

The job scheduling window object

```
{
  "id":476,
  "name":"Morning",
  "startTime":"08:00",
  "endTime":"12:00",
}
```

Job Scheduling Windows are set and controlled via the Synchroteam Web based back office.

A job scheduling window is represented by the following fields

Field	Type	Description
id	integer	ID of the job scheduling window
name	string	Name of the job scheduling window
startTime	time (hh:mm)	Start time (24h time format)
endTime	time (hh:mm)	End time (24h time format)

List job scheduling windows

```
curl --request GET \
  --url https://ws.synchroteam.com/api/v3/jobschedulingwindow/list \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE00EUTQzhEMjg4NzhBQTthB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":10,
  "recordsTotal":10,
  "data":[
    {<job scheduling window object>},
    {<job scheduling window object>},
    ...
    {<job scheduling window object>}
  ]
}
```

HTTP REQUEST

GET /api/v3/jobschedulingwindow/list

QUERY PARAMETERS

Parameter	Type	Description
sort	string	sort order, takes one value: <code>name</code> (Optional. Default is <i>name</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of job scheduling windows found.

If none are found, an empty list is returned.

Contracts

The contract object

JSON Representation

```
{
  "id": "5612a930-fad8-4367-bcc2-eb1df5b4e3f6",
  "num": 63,
  "name": "contract XYZ",
  "note": null,
  "customer": {
    "id": 4211049,
    "myId": "myidCust",
    "name": "nameCust"
  },
  "site": {
    "id": 3651230,
    "myId": "myidSite",
    "name": "nameSite"
  },
  "equipment": [
    {
      "id": 2558212,
      "myId": "myidEquip",
      "name": "nameEquip"
    }
  ],
  "jobTypes": [
    {
      "id": 45,
      "name": "test1",
      "sla": null
    },
    {
      "id": 57,
      "name": "test2",
      "sla": "sla normal"
    }
  ],
  "start": "2022-02-01",
  "end": "2024-03-31",
  "hours": "3:00",
}
```

```

    "hoursUsed": "1:15",
    "sla": [
      {
        "name": "sla normal",
        "tto": 60,
        "tts": 120,
        "ttr": 180,
      },
      {
        "name": "sla urgence",
        "tto": 30,
        "tts": 60,
        "ttr": 165,
      },
      {
        "name": "sla time",
        "tto": 120,
        "tts": 240,
        "ttr": 480,
      }
    ]
  }
}
```

A contract is represented by the following fields.

Field	Type	Description
id	string	ID of the contract (read only)
num	integer	Number of the contract (read only)
name	string	The name of the contract
note	string	Contract note
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields(id or myId required when creating a contract)
site	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> site fields
equipments	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> equipment fields
jobTypes	object	Object containing <code>id</code> and <code>name</code> job types fields and <code>name</code> of the sla linked to the jobType
start	date	Start Date
end	date	End Date
hours	time (hh:mm)	Total number of hours and minutes included in the contract
hoursUsed	time (hh:mm)	Total number of hours and minutes already used in the contract (read only)
sla	object	Object containing <code>tto</code> , <code>tts</code> , <code>ttr</code> (these integer are time in minutes), <code>name</code>
active	boolean	If the contract is active or not (default: true)

Retrieve a contract

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/contract/details?id=5612a930-fad8-4367-bcc2-eb1df5b4e3f6' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
```

JSON Returned

```
{
  "id": "5612a930-fad8-4367-bcc2-eb1df5b4e3f6",
  "num": 63,
  "name": "contract XYZ",
  "note": null,
  "customer": {
    "id": 4211049,
    "myId": "myidCust",
    "name": "nameCust"
  },
  "site": {
    "id": 3651230,
    "myId": "myidSite",
    "name": "nameSite"
  },
  "equipment": [
    {
      "id": 2558212,
      "myId": "myidEquip",
      "name": "nameEquip"
    }
  ],
  "jobTypes": [
    {
      "id": 45,
      "name": "test1",
      "sla": null
    },
    {
      "id": 57,
      "name": "test2",
      "sla": "sla normal"
    }
  ],
  "start": "2022-02-01",
  "end": "2024-03-31",
  "hours": "04:00",
  "hoursUsed": "01:00",
  "sla": [
    {
      "name": "sla normal",
      "tto": 60,
      "tts": 120,
      "ttr": 180,
    },
    {
      "name": "sla urgency",
      "tto": 30,
      "tts": 60,
      "ttr": 165,
    },
    {
      "name": "sla time",
      "tto": 120,
      "tts": 240,
      "ttr": 480,
    }
  ]
}
```

```
    }
  ]
}
```

HTTP REQUEST

```
GET /api/v3/contract/details?paramType=paramValue
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code> or <code>num</code>
{paramValue}	string	The <code>num</code> or <code>id</code> for the contract

REQUEST BODY

none

RESPONSE BODY

Contract information in JSON format

Create/Update a contract

Synchroteam provides a single endpoint to handle creating or updating contracts. The API determines if the contract record already exists by checking values provided for `id` and/or `num`.

POST Body

```
{
  <id or num contract only for update>
  "name": "Contract Name",
  "note": "This is the note of the contract",
  "customer": {
    <One of id or myId>
    "id": 4211049,
    "myId": "myidBK"
  },
  "site": {
    <One of id or myId>
    "id": 3651230,
    "myId": "myidsite"
  },
  "equipment": [
    {
      <One of id or myId>
      "id": 2558212,
      "myID": 78,
      "action": <add or remove>
    },
    {
      <One of id or myId>
      "id": 6179073,
      "myID": 123456789,
      "action": <add or remove>
    },
    <...>,
  ],
}
```

```

"jobTypes":[
  {
    <One of id or name>
    "id": 87,
    "name": "jobtypetest",
    "sla": null,
    "action":<add or remove>
  },
  {
    <One of id or name>
    "id": 12,
    "name": "defaultJT",
    "sla": "sla name",
    "action":<add or remove>
  }
],
"start": "2024-10-01",
"end": "2024-11-05",
"hours": "04:00",
"sla": [
  {
    "name": "sla name",
    "tto": 60,
    "tts": 120,
    "ttr": 180,
  },
  {
    "name": "name test sla",
    "tto": 120,
    "tts": 240,
    "ttr": 480,
  }, <...>,
]
}

```

Sample Code

```

curl --request POST \
  --url https://ws.synchroteam.com/api/v3/contract/send \
  --header 'accept: text/json' \
  --header 'content-type: application/json' \
  --data '{\r\n  "name": "Contract Name",\r\n  "note": "This is the note of the contract" (...)}'

```

JSON Returned

```

{
  "id": "5612a930-fad8-4367-bcc2-eb1df6b4e3f6",
  "num": 64,
  "name": "Contract Name",
  "note": "This is the note of the contract",
  "customer": {
    "id": 4211049,
    "myId": "myidBK"
  },
  "site": {
    "id": 3651230,
    "myId": "myidsite"
  },
  "equipment":[
    {
      "id":2558212,
      "myID":78,
    },
    {

```

```

    "id": 6179073,
    "myID": 123456789,
  },
],
"jobTypes": [
  {
    "id": 87,
    "name": "jobtypetest",
    "sla": null,
  },
  {
    "id": 12,
    "name": "defaultJT",
    "sla": "sla name",
  }
],
"start": "2024-10-01",
"end": "2024-11-05",
"hours": "04:00",
"sla": [
  {
    "name": "sla name",
    "tto": 60,
    "tts": 120,
    "ttr": 180,
  },
  {
    "name": "name test sla",
    "tto": 120,
    "tts": 240,
    "ttr": 480,
  }
]
}

```

HTTP REQUEST

POST /api/v3/contract/send

REQUEST BODY

Contract information in JSON format, if `id` or `num` exist, the contract will be updated, if not the contract will be created.

When updating a contract, if you provide a partial payload, only the fields provided will be updated. Fields not provided *will not be deleted*.

RESPONSE BODY

The response contains the updated contract record, with the `id` field and `num` specified.

If an error occurred, a standard error payload will be returned.

- * At minimum: you must provide a **name**, a **start**, an **end** and **customer object with id or num** or **site object with id or num**. All other fields are not required
- * tto, tta and ttr are time in minutes
- * Cannot add an sla with the same name as an other sla
- * Cannot add hoursUsed
- * action is by default add
- * jobTypes sla is by default null"

List contracts

Sample Code

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/contract/list?customer_id=4211049&start=2024-04-21 \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

JSON Returned

```
{
  "page":1,
  "pageSize":25,
  "records":25,
  "recordsTotal":16,
  "data":[
    {<contract object>},
    {<contract object>},
    ...
    {<contract object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/contract/list
```

QUERY PARAMETERS

Parameter	Type	Description
name	string	Filter by contract name
customer_id	integer	Return contract belonging to a customer by customer <code>id</code> .
customer_myId	string	Return contract belonging to a customer by customer <code>myId</code> .
site_id	integer	Return contract belonging to a site by site <code>id</code> .
site_myId	string	Return contract belonging to a site by site <code>myId</code> .
start	date (yyyy-mm-dd)	Get contract planned, ongoing or completed on or after <code>start</code>
end	date (yyyy-mm-dd)	Get contract planned, ongoing or completed on or before <code>end</code>
active	boolean	If the contract is active or not (default: true)
sort	string	sort order, takes one of the following values: <code>num</code> , <code>start</code> , <code>end</code> or <code>datemodified</code> (Optional. Default is <i>num</i>)

Parameter	Type	Description
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of **simplified** contracts found. A `Simplified Contract` is a contract object without equipment nor hourUsed nor sla.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Job Types

The job type object

```
{
  "id": 7464,
  "name": "Repair",
  "duration": "01:00:00",
  "isDefault": false,
  "priority": "medium",
  "customHeader": null,
  "customLogoUrl": null,
  "defaultJobReport": {
    "id": 7880,
    "name": "Maintenance"
  },
  "skills":["Plumber","Electrician"]
}
```

Job Types are set and controlled via the Synchroteam Web based back office.

A job type is represented by the following fields

Field	Type	Description
id	integer	ID of the job type
name	string	Name of the job type
duration	time (as string)	The default duration (hh:mm:ss)
isDefault	boolean	Whether or not this is the default job type
priority	string	priority level : <code>low</code> , <code>medium</code> , <code>high</code>
customHeader	string	Custom Address used in Header of Reports for this job type
customLogoUrl	string	URL of the Custom Logo used in Header of Reports for this job type

Field	Type	Description
defaultJobReport	object	Object containing <code>id</code> and <code>name</code> report template fields
skills	list(string)	List of skills for the job type

Retrieve a job type

```
curl --request GET \
  --url 'https://ws.synchroteam.com/api/v3/jobtype/details?id=345' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
{
  "id": 7464,
  "name": "Repair",
  "duration": "01:00:00",
  "isDefault": false,
  "priority": "medium",
  "customHeader": null,
  "customLogoUrl": null,
  "defaultJobReport": {
    "id": 7880,
    "name": "Maintenance"
  },
  "skills": ["Plumber", "Electrician"]
}
```

HTTP REQUEST

```
GET /api/v3/jobtype/details?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>name</code> or <code>id</code>
{paramValue}	string	The <code>name</code> , the <code>id</code> of the job type

REQUEST BODY

none

RESPONSE BODY

Returns the job type if found.

If the job type is not found a 404 Error is returned.

List Job Types

```
curl --request GET \
  --url https://ws.synchroteam.com/api/v3/jobtype/list?name=repair \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0E0EutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":10,
  "recordsTotal":10,
  "data":[
    {<job type object>},
    {<job type object>},
    ...
    {<job type object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/jobtype/list
```

QUERY PARAMETERS

Parameter	Type	Description
name	string	Will find all job types containing <code>name</code>
sort	string	sort order, takes one value: <code>name</code> (Optional. Default is <i>name</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of job types found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Send job type

Synchroteam provides a single endpoint to handle adding a Job Type. The Job Type is identified by its `id` or `name`.

POST Body

```
{
  "id": 7464,
  "name": "Repair",
  "duration": "01:00:00",
  "isDefault": false,
  "priority": "medium",
  "customHeader": null,
  "customLogoUrl": null,
  "defaultJobReport": {
    "id": 7880,
    "name": "Maintenance"
  },
  "skills": ["Plumber", "Electrician"]
}
```

Sample Code

```
curl --location --request POST 'https://ws.synchroteam.com/api/v3/jobtype/send' \
--header 'Authorization: Basic ZGVtbzo1Y2MyODM4MS01ZTM0LTQ0YWUtYjk1MC05MmWI1MDQxMTA3ZTE=' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--data-raw '{\"id\": 7464, \"name\": \"Repair\", \"duration\": \"01:00:00\", ...}'
```

JSON Returned

```
{
  "id": 7464,
  "name": "Repair",
  "duration": "01:00:00",
  "isDefault": false,
  "priority": "medium",
  "customHeader": null,
  "customLogoUrl": null,
  "defaultJobReport": {
    "id": 7880,
    "name": "Maintenance"
  },
  "skills": ["Plumber", "Electrician"]
}
```

HTTP REQUEST

POST /api/v3/jobtype/send

REQUEST BODY

- The Job Type identified by its `id` or `name`.

Job Reports

The job report object

JSON Representation

```
[
  {
    "id": 3275,
    "name": "Sample Block 1",
    "isShared": false,
    "iteration": 0,
    "isMandatory": true,
    "position": 0,
    "items": [
      {
        "id": 10363,
        "type": "text",
        "name": "Item name 1",
        "isMandatory": false,
        "isPrivate": false,
        "conditionByItem": 0,
        "conditionValue": "",
        "position": 1,
        "value": "sample value",
        "comment": "hey, this is a comment!",
        "issue": "Issue Reported"
      },
      {
        "id": 10364,
        "type": "list",
        "name": "Item name 2",
        "isMandatory": true,
        "isPrivate": false,
        "conditionByItem": 0,
        "conditionValue": "",
        "position": 2,
        "value": "In the street",
        "comment": "",
        "issue": "Resolved"
      }
    ]
  },
  {
    "id": 3276,
    "blockName": "Sample Block 2",
    "isShared": false,
    "iteration": 0,
    "isMandatory": true,
    "position": 2,
    "items": [
      {
        "id": 10365,
        "type": "list",
        "name": "Do we need to intervene?",
        "isMandatory": false,
        "isPrivate": false,
        "conditionByItem": 0,
        "conditionValue": "",
        "position": 1,
        "value": "yes",
        "comment": "",
        "issue": "-"
      },
      {
        "id": 10366,
        "type": "date",
        "name": "Date for next visit",
        "isMandatory": false,
        "isPrivate": false,
        "conditionByItem": 10365,
        "conditionValue": "yes",
        "position": 2,

```

```
        "value": "",
        "comment": "",
        "issue": ""
      }
    ]
  }
}
```

A Job Report is represented by the following fields

Field	Type	Description
id	int	Job Report Type id
name	string	Job Report Type name
isPublished	boolean	Whether or not the block is published
isDefault	boolean	Whether or not the block is shared
blocks	list of blocks each containing a list of items.	

NB: Note the following changes on items inside blocks:

- for items of type `list`, the `listValues` property is not shown.
- the `issue` field is shown. It can hold 4 possible values: `-`, `None`, `Issue Reported` and `Resolved`.

Retrieve a job report

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/jobReport/details?id=265_160719144323649' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
[
  {
    "id": 3275,
    "name": "Sample Block 1",
    "isShared": false,
    "iteration": 0,
    "isMandatory": true,
    "position": 0,
    "items": [
      {
        "id": 10363,
        "type": "text",
        "name": "Item name 1",
        "isMandatory": false,
        "isPrivate": false,
        "conditionByItem": 0,
        "conditionValue": "",
        "position": 1,

```

```
      "value": "sample value",
      "comment": "hey, this is a comment!",
      "issue": "Issue Reported"
    },
    {
      "id": 10364,
      "type": "list",
      "name": "Item name 2",
      "isMandatory": true,
      "isPrivate": false,
      "conditionByItem": 0,
      "conditionValue": "",
      "position": 2,
      "value": "In the street",
      "comment": "",
      "issue": "Resolved"
    }
  ]
},
{
  "id": 3276,
  "blockName": "Sample Block 2",
  "isShared": false,
  "iteration": 0,
  "isMandatory": true,
  "position": 2,
  "items": [
    {
      "id": 10365,
      "type": "list",
      "name": "Do we need to intervene?",
      "isMandatory": false,
      "isPrivate": false,
      "conditionByItem": 0,
      "conditionValue": "",
      "position": 1,
      "value": "yes",
      "comment": "",
      "issue": "-"
    },
    {
      "id": 10366,
      "type": "date",
      "name": "Date for next visit",
      "isMandatory": false,
      "isPrivate": false,
      "conditionByItem": 10365,
      "conditionValue": "yes",
      "position": 2,
      "value": "",
      "comment": "",
      "issue": "-"
    }
  ]
}
]
```

HTTP REQUEST

GET /api/v3/jobReport/details?{paramType}={paramValue}

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code> or <code>num</code> or <code>myId</code>

Parameter	Type	Description
{paramValue}	string	The <code>num</code> or <code>id</code> or <code>myId</code> for the job

REQUEST BODY

none

RESPONSE BODY

Returns the job report if found.

If the block is not found a 404 Error is returned.

Report Templates

Synchroteam supports different report templates each with customizable sections and items. The Job Report Templates API allows you to consult which templates are available along with their internal structure (blocks and items in each block).

The report template object

JSON Representation

```
{
  "id":45690,
  "name":"Sample Job Report Template",
  "isPublished":true,
  "isDefault":false,
  "blocks":[
    {
      "id":4986
      "name":"Satisfaction Survey",
      "isShared":false,
      "position":0,
      "min":1,
      "max":1,
      "items":[
        {
          "id":3421,
          "type":"list",
          "name": "Pick a value",
          "isMandatory": false,
          "isPrivate": false,
          "conditionByItem": null,
          "conditionValue": null,
          "position": 0,
          "listValues": [
            "not very",
            "somewhat",
            "very"
          ]
        },
        {
          "id":3422,
```

```
      "type": "numeric",
      "name": "How many?",
      "isMandatory": true,
      "isPrivate": false,
      "conditionByItem": null,
      "conditionValue": null,
      "position": 1,
      "listValues": null
    }
  ]
},
{
  "id": 4992
  "name": "window",
  "isShared": true,
  "position": 1,
  "min": 0,
  "max": 0,
  "items": [
    <item object>,
    <item object>,
    (...),
    <item object>
  ]
}
]
```

REPORT TEMPLATE OBJECT

Field	Type	Description
id	int	Job Report Template id
name	string	Job Report Template name
isPublished	boolean	Whether or not the template is published
isDefault	boolean	Whether or not the template is the default template
blocks	list of blocks each containing a list of items.	

NB: Blocks defined inside a Job Report Template contain three additional fields: `min`, `max` and `isMandatory`

- `min` is the minimum number of times a block needs to a in a report. 0 means it's not required.
- `max` is the maximum number of repetitions of a block in a report. 0 means it can be repeated as many times as needed.
- `isMandatory` (boolean) indicates whether or not the block must be completed.

NB2: Blocks defined inside a Job Report Template do not contain the field: `isPublished`. This field only has a meaning for shared blocks. If a shared block is inside a job report template, it has to be in a published state.

Retrieve a report template

```
curl --request GET \
  --url 'https://ws.synchroteam.com/api/v3/jobReportTemplate/details?id=45690' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0EUTQzhEMjg4NzhBQThB' \
```

```
--header 'cache-control: no-cache' \  
--header 'content-type: application/json'
```

Example Response

```
{  
  "id":45690,  
  "name":"Sample Job Report Template",  
  "isPublished":true,  
  "isDefault":false,  
  "blocks":[  
    {  
      "id":4986  
      "name":"Satisfaction Survey",  
      "isShared":false,  
      "isMandatory":true,  
      "position":0,  
      "min":1,  
      "max":1,  
      "items":[  
        <item object>,  
        <item object>,  
        (...),  
        <item object>  
      ]  
    },  
    {  
      "id":4992,  
      "name":"Window",  
      "isShared":true,  
      "isMandatory":false,  
      "position":1,  
      "min":0,  
      "max":0,  
      "items":[  
        <item object>,  
        <item object>,  
        (...),  
        <item object>  
      ]  
    }  
  ]  
}
```

HTTP REQUEST

```
GET /api/v3/jobReportTemplate/details?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code> (Job Report Template id)
{paramValue}	string	<code>id</code>

REQUEST BODY

none

RESPONSE BODY

Returns the report template if found.

If the report template is not found a 404 Error is returned.

List job report templates

Sample Code

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/jobReportTemplate/list \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":8,
  "recordsTotal":8,
  "data":[
    {<job report template object without blocks>},
    {<job report template object without blocks>},
    ...
    {<job report template object without blocks>}
  ]
}
```

You can list available job report templates via the API.

HTTP REQUEST

```
GET /api/v3/jobReportTemplate/list
```

QUERY PARAMETERS

Parameter	Type	Description
name	string	search by name - a wildcard search is performed
isPublished	boolean	get published or unpublished job report templates
sort	string	sort order, takes one value: <code>name</code> (Optional. Default is <i>name</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

REQUEST BODY

None

RESPONSE BODY

The list of job report templates. Each template will not show the blocks. An additional property called `numBlocks` is provided to show the number of blocks in each job report template.

If none are found, an empty list is returned.

Blocks

The block object

JSON Representation

```
{
  "id":4986
  "name":"Satisfaction Survey",
  "isShared":false,
  "isPublished":true,
  "items":[
    {
      "id":3421,
      "type":"list",
      "name": "Pick a value",
      "isMandatory": false,
      "isPrivate": false,
      "conditionByItem": null,
      "conditionValue": null,
      "position": 0
    },
    {
      "id":3422,
      "type":"numeric",
      "name": "Number of doors",
      "isMandatory": true,
      "isPrivate": false,
      "conditionByItem": null,
      "conditionValue": null,
      "position": 1,
    },
    (...)
  ]
}
```

A block is represented by the following fields

Field	Type	Description
id	int	ID of the block
name	string	Name of the block
isPublished	int	Defines if the block is published (1) or not (0).
isShared	int	Defines if the block is shared (1) or not (0).
items	list of items in the block, ordered by position.	

The item object

JSON Representation

```
{
  "id":3423,
  "type":"list",
  "name": "How happy are you?",
  "isMandatory": true,
  "isPrivate": false,
  "conditionByItem": 3549,
  "conditionValue": "1",
  "position": 1,
  "listValues": [
    "not very",
    "somewhat",
    "very"
  ]
}
```

An item is represented by the following fields

Report Design Fields

Field	Type	Description
id	int	item id
name	string	Name of the item
type	string	one of: compliance, list, text, date, time, numeric, signature, picture
isMandatory	boolean	Indicates if the item is mandatory.
isPrivate	boolean	Indicates if the item is mandatory.
conditionByItem	int	<code>id</code> of the item the current item depends on. 0 if there are no dependencies
conditionValue	string	Value held in <code>conditionByItem</code> for the current item to be shown
position	int	item position inside parent block. Starts at 0.
listValues	string array	List of every possible value if the item is of type <i>list</i> . (defaults to <code>null</code>)

Stored Values

When viewing a job report inside a job (versus a template), these fields are added to the output

Field	Type	Description
value	string	value stored for the report item
comment	string	comment stored for the report item
issue	string	One of: <code>Issue Reported</code> , <code>Resolved</code> , <code>None</code> or <code>-</code> (meaning <i>unspecified</i>)

Retrieve a block

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/block/details?id=45690' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "id":4986
  "name":"Satisfaction Survey",
  "isShared":false,
  "isPublished":true,
  "items":[
    <item object>,
    <item object>,
    (...),
    <item object>
  ]
}
```

HTTP REQUEST

```
GET /api/v3/block/details?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code>
{paramValue}	string	<code>id</code>

REQUEST BODY

none

RESPONSE BODY

Returns the block if found.

If the block is not found a 404 Error is returned.

List shared blocks

Sample Code

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/block/list \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
```

```
--header 'cache-control: no-cache' \  
--header 'content-type: application/json' \
```

Example Response

```
{  
  "page":1,  
  "pageSize":25,  
  "records":4,  
  "recordsTotal":4,  
  "data":[  
    {<block object without items>},  
    {<block object without items>},  
    ...  
    {<block object without items>}  
  ]  
}
```

Job Report Templates contain blocks that are uniquely tied to that particular report template.

However, shared blocks are also available and can be added to a Job Report Type, or a Job Report. Shared blocks also have the option of being repeatable (e.g. A maintenance job may require recording information for more than one window or door).

You can only list available shared blocks via the API.

HTTP REQUEST

```
GET /api/v3/block/list
```

QUERY PARAMETERS

Add pagination parameters if needed.

REQUEST BODY

None

RESPONSE BODY

The list of shared blocks. Each shared block will not show the items. An additional property called `numItems` is provided to show the number of items in each shared block.

If none are found, an empty list is returned.

Projects

The project object

JSON Representation

```
{  
  "id": 184831,  
  "myId": null,  
  "num": 87,  
  "customer": {
```

```
    "id": 9280343,
    "name": "sCustomer08",
    "myId": "1141"
  },
  "site": {
    "id": 2811,
    "myId": "ref-2511",
    "name": "Sample Site",
  },
  "equipment": {
    "id": 93971,
    "myId": "ref-2541",
    "name": "Heater 2345",
  },
  "type": {
    "id": 629,
    "name": "Standart Type"
  },
  "description": "This is the project description",
  "tags": [
    "tagstest1",
    "tagstest2",
    "tagstest3",
    "tagstest4",
    "tagstest5"
  ],
  "progression": 0,
  "jobs": [
    {
      "id": "d33a56fb-d205-45aa-959f-7a0a4d51b45f",
      "num": "14578",
      "status": "created",
      "type": {
        "id": 629,
        "name": "Standard Job"
      }
    }
  ]
}
```

A project is represented by the following fields.

Field	Type	Description
id	string	ID of the project (read only)
myId	string	Your custom reference number for this project
num	integer	Number of the project
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields(id or myId required when creating a project)
site	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> site fields (optional)
equipments	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> equipment fields (optional)
type	object	Object containing <code>id</code> and <code>name</code> for the project type
description	string	Project description
tags	list(string)	List of tags for the project

Field	Type	Description
progression	integer	Progression of the project (read only)
job	object	Object containing <code>id</code> , <code>num</code> , <code>status</code> and type Jobs fields

Retrieve a project

```
curl --request GET \
  --url 'https://ws.synchroteam.com/api/v3/project/details?id=184831' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
```

JSON Returned

```
{
  "id": 184831,
  "myId": null,
  "num": 87,
  "customer": {
    "id": 9280343,
    "name": "sCustomer08",
    "myId": "1141"
  },
  "site": {
    "id": 2811,
    "myId": "ref-2511",
    "name": "Sample Site",
  },
  "equipment": {
    "id": 93971,
    "myId": "ref-2541",
    "name": "Heater 2345",
  },
  "type": {
    "id": 629,
    "name": "Standart Type"
  },
  "description": "This is the project description",
  "tags": [
    "tag 1",
    "tag 2",
  ],
  "progression": 50,
  "jobs": [
    {
      "id": "d33a56fb-d205-45aa-959f-7a0a4d51b45f",
      "num": "56853",
      "status": "validated",
      "type": {
        "id": 629,
        "name": "Standard Job"
      }
    },
    {
      "id": "d33q76fb-dg85-84ea-784d-7a0a4d54r45f",

```

```
    "num": "56856",
    "status": "completed",
    "type": {
      "id": 629,
      "name": "Job Stdrt"
    }
  },
]
```

HTTP REQUEST

GET /api/v3/project/details?paramType=paramValue

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code> , <code>num</code> or <code>myID</code>
{paramValue}	string	The <code>num</code> or <code>id</code> or <code>myID</code> for the project

REQUEST BODY

none

RESPONSE BODY

Project information in JSON format

Create/Update a project

Synchroteam provides a single endpoint to handle creating or updating projects. The API determines if the project record already exists by checking values provided for `id` and/or `num` and/or `myId`.

POST Body

```
{
  <id or num project only for update>
  "myId": null,
  "customer": {
    <One of id or myId>
    "id": 9280343,
    "myId": "1141"
  },
  "site":{
    <One of id or myId>
    "id":2811,
    "myId": "ref-2511",
  },
  "equipment":{
    <One of id or myId>
    "id":93971,
    "myId": "ref-2541",
  },
  "type": {
    "id": 629,
    "name": "Standart Type"
  },
}
```

```
{
  "description": "This is the project description",
  "tags": [
    "tag one",
    "tag two",
  ]
}
```

Sample Code

```
curl --request POST \
  --url https://ws.synchroteam.com/api/v3/project/send \
  --header 'accept: text/json' \
  --header 'content-type: application/json' \
  --data '{\r\n  "myID": "MyProject",\r\n  "customer":{"id":9280343} (...)}'
```

JSON Returned

```
{
  "id": 184913,
  "myId": "myIDProject-45",
  "num": 93,
  "customer": {
    "id": 9280343,
    "name": "TestCust",
    "myId": "1141"
  },
  "site": {
    "id": 2811,
    "name": "TestSite",
    "myId": "ref-2511"
  },
  "equipment": {
    "id": 93971,
    "name": "TestEq",
    "myId": "ref-2541"
  },
  "type": [
    "restaurant"
  ],
  "description": "Job desc",
  "progression": 0,
  "jobs": []
}
```

HTTP REQUEST

POST /api/v3/project/send

REQUEST BODY

Project information in JSON format, if `id`, `num` or `myId` exist, the project will be updated, if not the project will be created.

When updating a project, if you provide a partial payload, only the fields provided will be updated. Fields not provided *will not be deleted*.

RESPONSE BODY

The response contains the updated project record, with the `id` field, `num` and `myId` specified.

If an error occurred, a standard error payload will be returned.

- * At minimum: you must provide a **customer object with id, name or myId**
- * Cannot edit `progression` and `jobs`

Link jobs to a project

POST Body

```
{
  <One of id, num or myId>
  "id":7847859,
  "jobs": [
    {
      "id": "805d4cf7-d8e1-4a9b-b0c1-228b3fe01d6d"
    }
  ]
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/project/linkjobs \
--header 'accept: text/json' \
--header 'content-type: application/json' \
--data '{\r\n  "id": 78459,\r\n  "jobs": {\\"id\\":805d4cf7-d8e1-4a9b-b0c1-228b3fe01d6d} (...)}'
```

JSON Returned

```
{
  "project": {
    "id": "7847859",
    "num": "94",
    "myId": "myIDProject-7894"
  },
  "jobs": [
    {
      "id": "805d4cf7-d8e1-4a9b-b0c1-228b3fe01d6d",
      "num": "57385"
    }
  ]
}
```

HTTP REQUEST

POST /api/v3/project/linkjobs

REQUEST BODY

Field	Type	Description
id	string	ID of the contract

Field	Type	Description
num	string	Number of the contract
myid	string	Your custom reference number of the project
jobs	object	Object containing id or num

RESPONSE BODY

The response contains the project, showing all the jobs linked to it.

If an error occured, a standard error payload will be returned.

List projects

Sample Code

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/project/list?customer_id=24334 \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

JSON Returned

```
{
  "page":1,
  "pageSize":25,
  "records":25,
  "recordsTotal":32,
  "data":[
    {<project object>},
    {<project object>},
    ...
    {<project object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/project/list
```

QUERY PARAMETERS

Parameter	Type	Description
customer_id	integer	return projects belonging to a customer by customer <code>id</code>
customer_myId	string	return projects belonging to a customer by customer <code>myId</code>
site_id	integer	return projects belonging to a site by site <code>id</code>

Parameter	Type	Description
site_myId	string	return projects belonging to a site by site <code>myId</code>
equipment_id	integer	return projects belonging to a piece of equipment by equipment <code>id</code>
equipment_myId	string	return projects belonging to a piece of equipment by equipment <code>myId</code>
type_id	integer	Get projects using a specific Project Type, by projecttype <code>id</code>
type_name	string	Get projects using a specific Project Type, by projecttype <code>name</code>
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Delete a project

```
curl --request DELETE \
  --url 'https://ws.synchroteam.com/api/v3/project/delete?id=182710' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

JSON Returned

```
{
  "id": 182710,
  "isDeleted": true
}
```

HTTP REQUEST

```
DELETE /api/v3/project/delete
```

QUERY PARAMETERS

Parameter	Type	Description
id	integer	ID of the project

REQUEST BODY

none

RESPONSE BODY

Returns project id with a `isDeleted` parameter set to true on success. If no project found, a 404 error is returned.

Recurrences

The Recurrence object

JSON Representation

```
{
  "id": 123456,
  "myId": null,
  "num": 669,
  "description": "Annual Maintenance",
  "priority": "medium",
  "customer": {
    "id": 981232,
    "name": "ST Corp",
    "myId": null
  },
  "site": {
    "id": 98123,
    "name": "Main Office",
    "myId": null
  },
  "equipment": {
    "id": 1654952,
    "name": "Heat Pump #129349",
    "myId": null
  },
  "type": {
    "id": 26565,
    "name": "Maintenance Air conditioning"
  },
  "reportTemplate": {
    "id": 4488,
    "name": "modèle par défaut"
  },
  "createdBy": {
    "id": 48984,
    "name": "William DELANO",
    "login": "william"
  },
  "address": "360 NW 27th St, Miami, FL 33127, États-Unis",
  "addressStreet": "360 Northwest 27th Street",
  "addressComplement": null,
  "addressCity": "Miami",
  "addressProvince": "Florida",
  "addressZIP": "33127",
  "addressCountry": "United States",
  "position": {
    "latitude": "25.8019892",
    "longitude": "-80.20158099999"
  },
  "contactFirstName": "John",
  "contactLastName": "Smith",
  "contactMobile": "+33623456789",
  "contactPhone": "+33123456789",
  "contactEmail": "jsmith@stcorp.com",
  "dateStart": "2022-03-01 00:00",
}
```

```
"dateEnd": null,
"frequency": 1,
"frequencyLevel": "year",
"days": "2",
"duration": "01:00:00",
"customFields": [
  {
    "id": 6542123,
    "label": "Installation Date",
    "value": "2019-04-17"
  }
],
"preferences": {
  "schedulingWindow": {
    "id": 786786,
    "name": "Afternoon"
  },
  "team": {
    "id": 2455,
    "name": "Maintenance"
  },
  "user": {
    "id": 1551,
    "name": "John Doe",
    "login": "jdoe"
  },
  "otherTechnicians": [
    {
      "id": 1552,
      "name": "Jim Doe",
      "login": "jimdoe"
    },
    {
      "id": 1553,
      "name": "Jane Doe",
      "login": "janedoe"
    }
  ],
  "autoScheduleDays": 14,
  "flAutoSchedule": true
},
"isClosed": false,
"idContract": null,
"dateDeleted": null
}
```

A Recurrence is represented by the following fields

Field	Type	Description
id	integer	recurrence's ID (read only system ID)
myId	string	Custom recurrence ID (e.g. can reference your internal recurrence ID)
num	integer	Number of the recurrence
description	string	Recurrence Description
priority	string	Recurrence priority: <code>low</code> , <code>medium</code> or <code>high</code> . Default is <code>medium</code> .
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields (id or myId required when creating a Recurrence)

Field	Type	Description
site	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> site fields (id or myId of a customer or site are required when creating a new Recurrence)
equipment	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> equipment fields (optional)
type	object	Object containing <code>id</code> and <code>name</code> for the job type.
reportTemplate	object	Object containing <code>id</code> and <code>name</code> for the job report template
createdBy	object	Object containing <code>id</code> , <code>login</code> or <code>name</code> for the user that created the recurrence
address	string	Complete Address
addressStreet	string	Street address
addressComplement	string	Complementary street address information
addressZIP	string	Address zip code
addressCity	string	Address city
addressProvince	string	Address province/state
addressCountry	string	Address country
position	position associated with the jobs. (optional)	
contactFirstName	string	Contact First Name
contactLastName	string	Contact Last Name
contactMobile	string	Contact Mobile Number
contactPhone	string	Contact Phone Number
contactEmail	string	Contact Email Address
dateStart	date	Start Date for the Recurrence Contract
dateEnd	date	End Date for the Recurrence Contract (optional)
frequencyLevel	string	Recurrence frequency : <code>day</code> , <code>week</code> , <code>month</code> or <code>year</code>
frequency	integer	Frequency for Job Creation : A job need to be scheduled every <code>frequency</code> <code>frequencyLevel</code> (e.g "every 2 years")
days	list of int	Days in the Week to schedule the Job. <code>1</code> for Monday, <code>2</code> for Tuesday,... (e.g "2,5" means Tuesday AND Friday)
duration	string	Duration for each Job (Read-only - inherited from Job Type duration)
customFields	list	List of custom field values for Jobs

Field	Type	Description
preferences	object	Recurrence job scheduling preferences
isClosed	boolean	whether or not the recurrence has been closed (read only)
dateDeleted	datetime	Deletion date
idContract	integer	linked contract id

Retrieve a Recurrence

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/recurrence/details?id=123456' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "id": 123456,
  "myId": null,
  "num": 669,
  "description": "Annual Maintenance",
  "priority": "medium",
  "customer": {
    "id": 981232,
    "name": "ST Corp",
    "myId": ""
  },
  "site": {
    "id": 98123,
    "name": "Main Office",
    "myId": ""
  },
  "equipment": {
    "id": 1654952,
    "name": "Heat Pump #129349",
    "myId": ""
  },
  "type": {
    "id": 26565,
    "name": "Maintenance Air conditioning"
  },
  "reportTemplate": {
    "id": 4488,
    "name": "modèle par défaut"
  },
  "createdBy": {
    "id": 48984,
    "name": "William DELANO",
    "login": "william"
  },
  "address": "360 NW 27th St, Miami, FL 33127, États-Unis",
  "addressStreet": "360 Northwest 27th Street",
  "addressComplement": null,
```

```
    "addressCity": "Miami",
    "addressProvince": "Florida",
    "addressZIP": "33127",
    "addressCountry": "United States",
    "position": {
      "latitude": "25.8019892",
      "longitude": "-80.20158099999"
    },
    "contactFirstName": "John",
    "contactLastName": "Smith",
    "contactMobile": "+33623456789",
    "contactPhone": "+33123456789",
    "contactEmail": "jsmith@stcorp.com",
    "dateStart": "2022-03-01 00:00",
    "dateEnd": null,
    "frequency": 1,
    "frequencyLevel": "year",
    "days": "2",
    "duration": "01:00:00",
    "customFields": [customfieldvalue1,...],
    "preferences": {
      "schedulingWindow": {
        "id": 786786,
        "name": "Afternoon"
      },
      "team": {
        "id": 2455,
        "name": "Maintenance"
      },
      "autoScheduleDays": 14,
      "flAutoSchedule": true
    },
    "isClosed": false,
    "idContract": null,
    "dateDeleted": null
  }
}
```

HTTP REQUEST

GET /api/v3/recurrence/details?{paramType}={paramValue}

REQUEST PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code>
{paramValue}	string	The <code>id</code> of the recurrence

REQUEST BODY

none

RESPONSE BODY

Returns the Recurrence if the `id` is found.

If the recurrence is not found a 404 Error is returned.

Delete a Recurrence

```
curl --request DELETE \
--url 'https://ws.synchroteam.com/api/v3/recurrence/delete?id=4494' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

JSON Returned

```
{
  "id": 4494,
  "isDeleted": true
}
```

HTTP REQUEST

```
DELETE /api/v3/recurrence/delete
```

QUERY PARAMETERS

Parameter	Type	Description
id	integer	ID of the recurrence

REQUEST BODY

none

RESPONSE BODY

Returns recurrence id with a `isDeleted` parameter set to true on success. If no recurrence found, a 404 error is returned.

Close a Recurrence

```
curl --request PUT \
--url 'https://ws.synchroteam.com/api/v3/recurrence/close?id=4494' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

JSON Returned

```
{
  "id": 4494,
  "isClosed": true
}
```

HTTP REQUEST

```
PUT /api/v3/recurrence/close
```

QUERY PARAMETERS

Parameter	Type	Description
id	integer	ID of the recurrence

REQUEST BODY

none

RESPONSE BODY

Returns recurrence id with a `isClosed` parameter set to true on success. If no recurrence found, a 404 error is returned.

List Recurrences

List all recurrences. Search parameters can be provided.

If no parameters are given, will return all active recurrences.

Sample Code

```
curl --request GET \
  --url 'https://ws.synchroteam.com/api/v3/recurrence/list?dateFrom=2022-01-01&show=ongoing' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":16,
  "recordsTotal":16,
  "data":[
    {<recurrence object>},
    {<recurrence object>},
    ...
    {<recurrence object>}
  ]
}
```

HTTP REQUEST

`GET /api/v3/recurrence/list`

REQUEST PARAMETERS

Parameter	Type	Description
dateFrom	date	return recurrences that start after <i>dateFrom</i>
dateTo	date	return recurrences that end before <i>dateTo</i>
show	string	accepts one of both values: <code>ongoing</code> , or <code>closed</code> (default: <code>ongoing</code>)

Parameter	Type	Description
customer_id	integer	return recurrences belonging to a customer by customer <code>id</code>
customer_myId	string	return recurrences belonging to a customer by customer <code>myId</code>
site_id	integer	return recurrences belonging to a site by site <code>id</code>
site_myId	string	return recurrences belonging to a site by site <code>myId</code>
equipment_id	integer	return recurrences belonging to a piece of equipment by equipment <code>id</code>
equipment_myId	string	return recurrences belonging to a piece of equipment by equipment <code>myId</code>
type_id	integer	Get recurrences using a specific Job Type, by jobtype <code>id</code>
type_name	string	Get recurrences using a specific Job Type, by jobtype <code>name</code>
reportTemplate_id	integer	Get recurrences using a specific Job Report Template, by report <code>id</code>
reportTemplate_name	string	Get recurrences using a specific Job Report Template, by report <code>name</code>

Add pagination parameters if needed.

RESPONSE BODY

A list of recurrences found.

If none are found, an empty list is returned.

Create/Update a recurrence

Synchroteam provides a single endpoint to handle creating or updating recurrences. The API determines if the recurrence record already exists by checking values provide for `id` and/or `num`.

Example Request (POST Body)

```
{
  "description": "Visit twice a month",
  "priority": "high",
  "customer": {
    "name": "ST Corp"
  },
  "type": {
    "name": "Medical assistance"
  },
  "address": "360 NW 27th St, Miami, FL 33127, États-Unis",
  "dateStart": "2022-03-01 00:00",
  "dateEnd": "2022-04-28 00:00",
  "frequency": 2,
  "frequencyLevel": "week",
  "days": "1,5"
}
```

Sample Code

```
curl --request POST \
--url 'https://ws.synchroteam.com/api/v3/recurrence/send' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{"description":"Visit twice a month","priority":"high",...}'
```

Example Response

```
{
  "id": 9846542,
  "myId": null,
  "num": 672,
  "description": "Visit twice a month",
  "priority": "high",
  "customer": {
    "id": 4545816,
    "name": "ST Corp",
    "myId": ""
  },
  "site": {
    "id": null,
    "myId": ""
  },
  "equipment": {
    "id": null,
    "myId": ""
  },
  "type": {
    "id": 456456,
    "name": "Medical assistance"
  },
  "reportTemplate": {
    "id": 33878,
    "name": "Medical report"
  },
  "address": "360 NW 27th St, Miami, FL 33127, États-Unis",
  "addressStreet": "360 Northwest 27th Street",
  "addressComplement": null,
  "addressCity": "Miami",
  "addressProvince": "Miami-Dade County Florida",
  "addressZIP": "33127",
  "addressCountry": "United States",
  "position": {
    "latitude": "25.8019892",
    "longitude": "-80.20158099999"
  },
  "contactFirstName": null,
  "contactLastName": null,
  "contactMobile": null,
  "contactPhone": null,
  "contactEmail": null,
  "dateStart": "2022-03-01 00:00",
  "dateEnd": "2022-04-28 00:00",
  "frequency": 2,
  "frequencyLevel": "week",
  "days": "1,5",
  "duration": "02:00:00",
  "customFields": [],
  "preferences": {
    "user": {
      "id": 1551,
      "name": "John Doe",
      "login": "jdoe"
    }
  }
}
```

```
    },
    "otherTechnicians": [
      {
        "id": 1552,
        "name": "Jim Doe",
        "login": "jimdoe"
      },
      {
        "id": 1553,
        "name": "Jane Doe",
        "login": "janedoe"
      }
    ],
    "autoScheduleDays": 1,
    "flAutoSchedule": false
  },
  "flClosed": false,
  "idContract": null,
  "contactFax": null,
  "dateDeleted": null
}
```

HTTP REQUEST

POST /api/v3/recurrence/send

REQUEST BODY

Recurrence information in JSON format, if `id`, `myId` or `num` exists, the recurrence will be updated, if not the recurrence will be created.

RESPONSE BODY

The response contains the updated recurrence record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.

- ❗ For creation, at minimum: you must provide **description**, **customer**, **address**, **dateStart**, **frequency**, and **frequencyLevel**. All other fields are not required

Recurrence Scheduling Preferences

The recurrence scheduling preferences object

```
{
  "schedulingWindow": {
    "id": 1,
    "name": "Morning"
  },
  "team": {
    "id": 4512,
    "name": "California"
  },
  "user": {
    "id": 1551,
    "name": "John Doe",
    "login": "jdoe"
  }
}
```

```
    },
    "otherTechnicians":[
      {
        "id": 1552,
        "name": "Jim Doe",
        "login":"jimdoe"
      },
      {
        "id": 1553,
        "name": "Jane Doe",
        "login":"janedoe"
      }
    ],
    "autoScheduleDays": 14,
    "flAutoSchedule": true
  }
}
```

Recurrence Scheduling Preferences are represented by the following fields

Field	Type	Description
schedulingWindow	object	Object containing <code>id</code> and <code>name</code> recurrence scheduling window fields
team	object	Object containing <code>id</code> and <code>name</code> team fields
user	object	Object containing <code>id</code> , <code>name</code> and <code>login</code> for the user assigned to the recurrence
otherTechnicians	list of objects	Other technicians associated with this recurrence. List of user objects containing <code>id</code> , <code>name</code> and <code>login</code> .
autoScheduleDays	int	Number of days before a recurrence occurrence creates a job
flAutoSchedule	boolean	Whether jobs created by the recurrence will have the <code>scheduled</code> status

Positions

Description of positions objects. Position objects are GPS coordinates, they are associated with jobs, customers and sites.

DESCRIPTION

There can be only one position for each job, customer or site. The values can only be accessed with the associated object.

When an object associated with a position is created if no GPS position is provided, a position is associated with it according to its address field, if it is possible.

When an object associated with a position is changed an a new address is provided, and no position is provided, a new position is calculated; if it is possible.

A representation of a position has the following fields :

Field	Type	Description
latitude	decimal	The latitude of the position, the value is greater than -90 and smaller than 90

Field	Type	Description
longitude	decimal	The longitude of the position, the value is greater than -90 and smaller than 90.

METHODS

The are no methods directly associated to positions. They can be accessed, created, deleted, altered via the associated data.

```
{
  "latitude": "42.479",
  "longitude": "-0.4586"
}
```

Users

The user object

JSON Representation

```
{
  "id": 54022,
  "firstName": "John",
  "lastName": "Doe",
  "login": "login_user",
  "phone": "(719) 388-1966",
  "profile": "technician",
  "email": "djohn@gmail.com",
  "language": "EN",
  "password": "123456abc",
  "startLocation": {
    "fullAddress": "411 Pearl St, New York, NY 10038, USA",
    "latitude": "40.7115539",
    "longitude": "-74.0035686"
  },
  "lastLocation": {
    "latitude": "40.726539",
    "longitude": "-73.859565",
    "datetime": "2019-04-02 16:28:45"
  },
  "customFieldValues": [
    {
      "id": 85,
      "label": "Sector",
      "value": "OD 89874 sector"
    },
    {
      "id": 88,
      "label": "Contract Number",
      "value": "1547-TRH-402937",
    }
  ],
  "teams": ["team5", "team87"],
  "skilledTrades": [
    "plumber", "electrician"
  ],
  "deleted": null,
}
```

```
    "lastConnection": "2020-10-14 12:53",
    "timezone": "Romance Standard Time",
    "isSubcontractor": true
  }
```

An user is represented by the following fields

Field	Type	Description
id	integer	user's ID (read only system ID)
firstName	string	First name
lastName	string	Last name
login	string	Login name
password	string	Password of the user account (<i>Write only</i> - required when creating or updating)
language	string	Language code for the user (possible value: EN,FR,ES,RO,CZ)
email	string	Email address
phone	string	Phone number
profile	string	User level : <code>technician</code> , <code>administrator</code> , <code>manager</code>
customFieldValues	list	List of custom field values for this user (optional)
skilledTrades	list(string)	List of skilled for this user (optional)
teams	list(string)	List of teams memberships for this user
startLocation	object	User location information, containing these properties: <code>fullAddress</code> and <code>latitude</code> and <code>longitude</code>
lastLocation	object	User last location based on GPS Tracking, containing these properties: <code>latitude</code> , <code>longitude</code> and <code>datetime</code>
deleted	date	Deletion date. set to <code>null</code> if user record is active
lastConnection	date	The last Date & Time connection (read-only)
timezone	string	The Time Zone of the User - by default the Time zone of the Account
isSubcontractor	boolean	The user is subcontractor or not (default <code>false</code>)

Retrieve a user

```
curl --request GET \
  --url 'https://ws.synchroteam.com/api/v3/user/details?id=54022' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \
```

```
--header 'cache-control: no-cache' \  
--header 'content-type: application/json'
```

Example Response

```
{  
  "id": 54022,  
  "firstName": "John",  
  "lastName": "Doe",  
  "login": "login_user",  
  "phone": "(719) 388-1966",  
  "profile": "technician",  
  "email": "djohn@gmail.com",  
  "language": "EN",  
  "teams": [  
    "team1",  
    "team5"  
  ],  
  "skilledTrades": [  
    "plumber",  
    "electrician"  
  ],  
  "startLocation": {  
    "fullAddress": "411 Pearl St, New York, NY 10038, USA",  
    "latitude": "40.7115539",  
    "longitude": "-74.0035686"  
  },  
  "lastLocation": {  
    "latitude": "40.726539",  
    "longitude": "-73.859565",  
    "datetime": "2019-04-02 16:28:45"  
  },  
  "customFieldValues": [customFieldValue1,...],  
  "deleted": null,,  
  "lastConnection": "2020-10-14 12:53",  
  "lastSynchronization": "2023-07-02 16:20",  
  "timezone": "Romance Standard Time",  
  "isSubcontractor": true  
}
```

HTTP REQUEST

```
GET /api/v3/user/details?{paramType}={paramValue}
```

REQUEST PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts login or id
{paramValue}	string	The login or the id of the user
{sort}	string	sort order, takes one of three values: login, dateModified (Optional. Default is login)
{sortOrder}	string	takes one of two values: ascending or descending (Optional. Default is ascending)
{phoneFormat}	string	takes one of two values: local or intl (Optional. Default is local)

REQUEST BODY

none

RESPONSE BODY

Returns the user if the `id` or `login` is found.

If the user is not found a 404 Error is returned.

Create/Update a user

Synchroteam provides a single endpoint to handle creating or updating users. The API determines if the user record already exists by checking values provide for `id` and/or `login`.

Example Request (POST Body)

```
{
  "firstName": "John",
  "lastName": "Doe",
  "login": "login_user",
  "phone": "(719) 388-1966",
  "profile": "technician",
  "email": "djohn@gmail.com",
  "language": "EN",
  "password": "123456abc",
  "startLocation": {
    "fullAddress": "411 Pearl St, New York, NY 10038, USA"
  },
  "customFieldValues": [
    {
      "id": 85,
      "label": "Sector",
      "value": "0D 89874 sector"
    },
    {
      "id": 88,
      "label": "Contract Number",
      "value": "1547-TRH-402937"
    }
  ],
  "teams": ["team5", "team87"],
  "skilledTrades": ["plumber", "electrician"],
  "timezone": "Romance Standard Time",
  "isSubcontractor": true
}
```

Sample Code

```
curl --request POST \
  --url 'https://ws.synchroteam.com/api/v3/user/send' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3R1YW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{"id":54022, "firstName":"John","lastName":"Doe", (...) }'
```

Example Response

```
{
  "id": 54022,
  "firstName": "John",
  "lastName": "Doe",
  "login": "login_user",
  "phone": "(719) 388-1966",
  "profile": "technician",
  "email": "djohn@gmail.com",
  "language": "EN",
  "startLocation": {
    "fullAddress": "411 Pearl St, New York, NY 10038, USA",
    "latitude": "40.7115539",
    "longitude": "-74.0035686"
  },
  "lastLocation": {
    "latitude": "40.726539",
    "longitude": "-73.859565",
    "datetime": "2019-04-02 16:28:45"
  },
  "customFieldValues": [
    {
      "id": 85,
      "label": "Sector",
      "value": "OD 89874 sector"
    },
    {
      "id": 88,
      "label": "Contract Number",
      "value": "1547-TRH-402937"
    }
  ],
  "teams": ["team5", "team87"],
  "skilledTrades": ["plumber", "electrician"],
  "deleted": null,
  "lastConnection": "2020-10-14 12:53",
  "timezone": "Romance Standard Time",
  "isSubcontractor": true
}
```

HTTP REQUEST

POST /api/v3/user/send

REQUEST BODY

user information in JSON format, if `id` or `login` exist, the user will be updated, if not the user will be created.

When creating a user, leave the `id` field out of the payload, or set to an null value.

When updating a user, if you provide a partial payload, only the fields provided will be updated. Fields not provided *will not be deleted*.

RESPONSE BODY

The response contains the updated user record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.

! For creation, at minimum: you must provide **login**, **lastName** and **password**. All other fields are not required

Delete a user

```
curl --request DELETE \
--url 'https://ws.synchroteam.com/api/v3/user/delete?login=dave' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
```

JSON Returned

```
[
  {
    "id":50998
    "deleted":true
  }
]
```

HTTP REQUEST

```
DELETE /api/v3/user/delete?{paramType}={paramValue}
```

REQUEST PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code> or <code>login</code>
{paramValue}	string	The <code>id</code> or the <code>login</code> of the user

RESPONSE BODY

Returns a list containing a single object with a deleted parameter set to true on success, and the user ID. If no user is found, a 404 error is returned.

 Admin and Manager level accounts cannot be deleted using the API. In such an instance, a 403 Forbidden error is returned

List users

List all users. Search parameters can be provided.

If no parameters are given, will return all active users.

Sample Code

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/user/list?teamId=23&skilledTrade=Electrician&show=all' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
```

```
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":16,
  "recordsTotal":16,
  "data":[
    {<user object>},
    {<user object>},
    ...
    {<user object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/user/list
```

REQUEST PARAMETERS

Parameter	Type	Description
teamId	int	return users in the team with <i>team ID</i>
teamName	string	return users in <i>team name</i>
skilledTrade	string	return users having the skilled trade specified
show	string	accepts one of three values: <code>active</code> , <code>deleted</code> or <code>all</code> (default: <code>active</code>)

Add pagination parameters if needed.

RESPONSE BODY

A list of users found.

If none are found, an empty list is returned.

Teams

The team object

```
{
  "id":476,
  "name":"East Team",
  "description":"Team that works from the east end office",
  "numTechs":6,
  "numManagers":1,
  "tags":["maintenance","hvac"],
}
```

```
"deleted":null
}
```

Teams are set and controlled via the Synchroteam Web based back office.

A team is represented by the following fields

Field	Type	Description
id	integer	ID of the team
name	string	Name of the team
description	string	Description given for the team
numTechs	int	Number of currently active technicians in the team
numManagers	int	Number of currently active managers in the team
tags	list(string)	List of tags for the team.
deleted	date	Deletion date. set to <code>null</code> if team record is active

List teams

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/team/list?name=east \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":10,
  "recordsTotal":10,
  "data":[
    {<team object>},
    {<team object>},
    ...
    {<team object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/team/list
```

QUERY PARAMETERS

Parameter	Type	Description
name	string	Will find all teams containing <code>name</code>
show	string	accepts one of three values: <code>active</code> , <code>deleted</code> or <code>all</code> (default: <code>active</code>)
sort	string	sort order, takes one value: <code>name</code> (Optional. Default is <i>name</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of teams found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Tax Rates

The tax object

```
{
  "id":476,
  "name": "VAT",
  "rate": "19.50",
  "default":false,
  "deleted":false
}
```

Tax Rates are set and controlled via the Synchroteam Web based back office.

A tax is represented by the following fields

Field	Type	Description
id	integer	ID of the tax
name	string	Name of the tax
rate	decimal (as string)	The tax rate (Use a "." as the decimal separator)
default	boolean	Whether or not this is the default tax rate

List taxes

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/tax/list?name=vat \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":10,
  "recordsTotal":10,
  "data":[
    {<tax object>},
    {<tax object>},
    ...
    {<tax object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/tax/list
```

QUERY PARAMETERS

Parameter	Type	Description
name	string	Will find all taxes containing <code>name</code>
default	boolean	Will find all taxes with the specified value for <code>default</code>
show	string	accepts one of three values: <code>active</code> , <code>deleted</code> or <code>all</code> (default: <code>active</code>)
sort	string	sort order, takes one value: <code>name</code> (Optional. Default is <i>name</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of taxes found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Attachments

Attachments can be added to Jobs, Customers, Sites, Equipments or Contracts.

You can also create general attachments, not associated with any other object.

The attachment object

JSON Representation (attached to a job)

```
{
  "id":3547,
  "name":"Excel data file",
  "url":"https://yourdomainname.synchroteam.com/app/Attachment/Download/61370f0b-af50-4123-a066-a7565b57ad54",
  "isPrivate":false,
  "isExternalLink":false,
  "job":{
    "id":"265_160627143211768",
    "myId":"jb-4567-89",
    "num" : "587"
  },
  "customer":null,
  "site":null,
  "equipment":null,
  "contract":null
}
```

JSON Representation (external link attached to a site)

```
{
  "id":3547,
  "name":"Sample External Link",
  "url":"https://externalsite.com",
  "isPrivate":false,
  "isExternalLink":true,
  "job":null,
  "customer":null,
  "site":{
    "id":2811,
    "name":"Sample Site"
    "myId":"ref-2511",
  },
  "equipment":null,
  "contract":null
}
```

An attachment is represented by the following fields

Field	Type	Description
id	integer	Attachment id (read only)
name	string	Attachment name (or label)
url	string	Url to access the attachment
isPrivate	boolean	Whether or not the attachment is private (visible to your team only)
isExternalLink	boolean	Whether or not the attachment is an external web link (versus being a file)
job	object	Nullable partial job object containing <code>id</code> , <code>myId</code> and <code>num</code> fields
customer	object	Nullable partial customer object containing <code>id</code> , <code>name</code> and <code>myId</code> fields.

Field	Type	Description
site	object	Nullable partial site object containing <code>id</code> , <code>name</code> and <code>myId</code> fields
equipment	object	Nullable partial equipment object containing <code>id</code> , <code>name</code> and <code>myId</code> fields
contract	object	Nullable partial contract object containing <code>id</code> and <code>num</code> fields

Retrieve an attachment

```
curl --request GET \
  --url 'https://ws.synchroteam.com/api/v3/attachment/details?id=15494' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
{
  "id": 15494,
  "name": "Test.pdf",
  "url": "https://yourdomain.synchroteam.com/app/Attachment/Download/...",
  "isPrivate": false,
  "isExternalLink": false,
  "job": {
    "id": "272_15091513250044",
    "myId": null,
    "num": 1717
  },
  "customer": null,
  "site": null,
  "equipment": null,
  "contract": null,
  "fileData": [Base64String]
}
```

HTTP REQUEST

```
GET /api/v3/attachment/details?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code>
{paramValue}	string	The <code>id</code> of the attachment

REQUEST BODY

none

RESPONSE BODY

Returns the attachment if found.

If the attachment is not found a 404 Error is returned.

Create an attachment

POST Body (creating file attachment)

```
{
  "name": "Sample attachment name",
  "isPrivate": true,
  "isExternalLink": false,
  "equipment": {
    "id": 93971,
    "myId": "ref-2541",
  },
  "fileName": "data5.csv",
  "fileData": [Base64String]
}
```

POST Body (creating external link)

```
{
  "name": "Sample attachment name",
  "isPrivate": false,
  "isExternalLink": true,
  "equipment": {
    "id": 93971,
    "myId": "ref-2541",
  },
  "url": "https://externalsite.com"
}
```

Sample Code

```
curl --request POST \
  --url https://ws.synchroteam.com/api/v3/attachment/create \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{\r\n  "name": "Sample Attachment Name",\r\n  "isPrivate": true (...)}'
```

JSON Returned

```
{
  "id": 3547,
  "name": "Sample attachment name",
  "url": "https://yourdomainname.synchroteam.com/app/Attachment/Download/61370f0b-af50-4123-a066-a7565b57ad54",
  "isPrivate": true,
  "isExternalLink": false,
  "job": null,
  "customer": null,
  "site": null,
  "equipment": {
    "id": 93971,
```

```
    "myId": "ref-2541",
    "name": "Sample Piece of Equipment"
  },
  "contract": null
}
```

HTTP REQUEST

POST /api/v3/attachment/create

REQUEST BODY

attachment information in JSON format. See table below:

Field	Type	Description
name	string	Label for the attachment. For file attachments, will default to <code>fileName</code> if not provided. Required when <code>isExternalLink:true</code>
url	string	The url for an external link. Required when <code>isExternalLink:true</code>
isPrivate	boolean	Whether or not the attachment is private (visible to your team only)
isExternalLink	boolean	Whether or not the attachment is an external web link (versus being a file)
job	object	<code>id</code> or <code>myId</code> or <code>num</code> of the job (optional)
customer	object	<code>id</code> or <code>myId</code> of the customer (optional)
site	object	<code>id</code> or <code>myId</code> of the site (optional)
equipment	object	<code>id</code> or <code>myId</code> of the equipment (optional)
contract	object	<code>id</code> or <code>num</code> of the contract (optional)
fileName	string	Name of the attachment. Required when <code>isExternalLink:false</code>
fileData	string	File data encoded as a Base64String. Required when <code>isExternalLink:false</code>

NB: if no job, customer, site, equipment or contract objects are specified, you will be creating a general (global) attachment.

RESPONSE BODY

The response contains the attachment record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.



* Attachment size is limited to 3MB.

* Only the following file extensions are allowed:
.pdf, .xls, .xlsx, .csv, .txt, .doc, .docx, .rtf, .gif, .jpeg, .jpg, .png and .bmp

Delete an attachment

```
curl --request DELETE \
--url 'https://ws.synchroteam.com/api/v3/attachment/delete?id=3547' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

JSON Returned

```
[
  {
    "id":3547
    "deleted":true
  }
]
```

HTTP REQUEST

DELETE /api/v3/attachment/delete

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code>
{paramValue}	string	The <code>id</code> of the attachment

REQUEST BODY

none

RESPONSE BODY

Returns a list containing a single object with a deleted parameter set to true on success, and the attachment ID. If no attachment is found, a 404 error is returned.

List attachments

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/attachment/list?customer_id=35604 \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
```

```
"records":4,
"recordsTotal":4,
"data":[
  {<attachment object>},
  {<attachment object>},
  ...
  {<attachment object>}
]
}
```

HTTP REQUEST

GET /api/v3/attachment/list

QUERY PARAMETERS

Parameter	Type	Description
name	string	search by name - a wildcard search is performed
job_id	integer	return attachments belonging to a job by job id
job_myId	string	return attachments belonging to a job by job myId
job_num	integer	return attachments belonging to a job by job number (exact match)
customer_id	integer	return attachments belonging to a customer by customer id
customer_myId	string	return attachments belonging to a customer by customer myId
site_id	integer	return attachments belonging to a site by site id
site_myId	string	return attachments belonging to a site by site myId
equipment_id	integer	return attachments belonging to a equipment by equipment id
equipment_myId	string	return attachments belonging to a equipment by equipment myId
contract_id	string	return attachments belonging to a contract by contract id
contract_num	integer	return attachments belonging to a contract by contract myId
sort	string	sort order, one of three values: <code>id</code> or <code>name</code> (Optional. Default is <i>id</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of attachments found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Parts and Services

Parts and/or Services are represented using a **part** object.

The part object

JSON Representation

```
{
  "id": 35918,
  "name": "5mm Bearing",
  "reference": "p458",
  "description": "This is the Description \n on 2 lines",
  "price": "10.00",
  "minQuantity": 5,
  "quantity": 10,
  "isTracked": false,
  "isSerializable": true,
  "category": {
    "id": 1532,
    "name": "Bearings"
  },
  "tax": {
    "id": 37,
    "name": "VAT",
    "rate": "14.00"
  },
  "status": "active",
  "type": "part",
  "dateModified": "2022-03-11 11:49"
}
```

A Part is represented by the following fields

Field	Type	Description
id	integer	ID of the part (read only)
name	string	Part Name
reference	string	Part reference number or code
description	string	Description for the Part. Use <code>\n</code> for line break
price	decimal number	The part unit price (before taxes)
minQuantity	integer	The minimum stock quantity for this part (optional. meaningful is <code>isTracked=true</code>)
quantity	integer	The actual stock quantity for this part
isTracked	boolean	Whether or not the part's quantity is tracked (optional, default <code>false</code>)

Field	Type	Description
isSerializable	boolean	The part is serializable or not (optional, default <code>false</code>)
tax	object	object containing the tax <code>id</code> , <code>name</code> and <code>rate</code> (optional)
category	integer	object containing the part's category <code>id</code> and <code>name</code> and <code>rate</code> (optional)
status	string	Part Status, one of: <code>active</code> (default), <code>inactive</code> (optional)
type	string	Part Type, one of: <code>part</code> (default), <code>service</code> , <code>travel</code> , <code>other</code> (optional)
dateModified	datetime	last modification date

Retrieve a part

```
curl --request GET \
  --url 'https://ws.synchroteam.com/api/v3/part/details?id=35918' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
{
  "id": 35918,
  "name": "5mm Bearing",
  "reference": "p458",
  "description": "This is the Description \n on 2 lines",
  "price": "10.00",
  "minQuantity": 5,
  "quantity": 10,
  "isTracked": false,
  "isSerializable": true,
  "category": {
    "id": 1532,
    "name": "Bearings"
  },
  "tax": {
    "id": 37,
    "name": "VAT",
    "rate": "14.00"
  },
  "status": "active",
  "type": "part"
}
```

HTTP REQUEST

GET /api/v3/part/details?{paramType}={paramValue}

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code> or <code>reference</code>
{paramValue}	string	The <code>id</code> or the <code>reference</code> of the part

REQUEST BODY

none

RESPONSE BODY

Returns the part if found.

If the part is not found a 404 Error is returned.

List parts

```
curl --request GET \
  --url 'https://ws.synchroteam.com/api/v3/part/list' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":6,
  "recordsTotal":6,
  "data":[
    {<part object>},
    {<part object>},
    ...
    {<part object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/part/list?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
category_id	integer	return Parts from a specific category, by category id
category_name	string	return Parts from a specific category, by category id
changedSince	dateTime	return Parts modified after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
isTracked	boolean	Whether or not the parts are tracked in inventory management

Parameter	Type	Description
isSerializable	boolean	Whether or not the parts are serializable
status	string	Filter by Part status (<code>active</code> , <code>inactive</code>)
type	string	Filter by Part type (<code>part</code> , <code>service</code> , <code>travel</code> , <code>other</code>)
sort	string	sort order, takes one of four values: <code>name</code> (default), <code>reference</code> , <code>category</code> (name)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

REQUEST BODY

none

RESPONSE BODY

Returns a list of parts.

Create/Update a part

Synchroteam provides a single endpoint to handle creating or updating parts. The API determines if the part record already exists by checking values provided for `id` and/or `reference`.

POST Body (use existing part category and tax)

```
{
  "name": "5mm Bearing",
  "reference": "p458",
  "description": "This is the Description \n on 2 lines",
  "price": "10.00",
  "minQuantity": 5,
  "isTracked": false,
  "isSerializable": true,
  "category": {
    "id": 1532
  },
  "tax": {
    "id": 37
  },
  "status": "active",
  "type": "part"
}
```

POST Body (Update part and create new part category, no tax)

```
{
  "id": 35918
  "name": "5mm Bearing",
  "reference": "p458",
  "description": "This is the Description \n on 2 lines",
  "price": "10.00",
  "minQuantity": 5,
  "isTracked": false,
  "isSerializable": true,
  "category": {
```

```
{
  "name": "Roller Bearings"
},
"tax": null
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/part/send \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{"name": "5mm Bearing", "reference": "p458" (...)}'
```

JSON Returned

```
{
  "id": 35918,
  "name": "5mm Bearing",
  "reference": "p458",
  "description": "This is the Description \n on 2 lines",
  "price": "10.00",
  "minQuantity": 5,
  "isTracked": false,
  "isSerializable": true,
  "category": {
    "id": 1532,
    "name": "Bearings"
  },
  "tax": {
    "id": 37,
    "name": "VAT",
    "rate": "14.00"
  },
  "status": "active",
  "type": "part"
}
```

HTTP REQUEST

```
POST /api/v3/part/send
```

REQUEST BODY

part information in JSON format, if the `id` or `reference` exist, the part will be updated, if not the part will be created.

When updating a part, if you provide a partial payload, only the fields provided will be updated. Fields not provided *will not be deleted*.

NB:

- If you only provide a category name, if the category name exists, the part will be mapped to that category. Otherwise, the category will be created
- Tax is specified by `id` only and is optional. If the tax is not found it will be ignored.

RESPONSE BODY

The response contains the created/updated part record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.



* At minimum, you must provide a part **name**, a **reference** and a **price**. All other fields are not required

Delete a part

```
curl --request DELETE \
  --url 'https://ws.synchroteam.com/api/v3/part/delete?id=35918' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3R1YW06MTUzODc0REItMUM0OC00NDQzLUE00EUTQzhEMjg4NzhBQTlh' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

JSON Returned

```
{
  "PartsDeleted": [
    {
      "id": 3168094,
      "isDeleted": true
    },
    (...)
  ]
}
```

HTTP REQUEST

DELETE /api/v3/part/delete

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code> or <code>reference</code>
{paramValue}	string	The <code>id</code> or <code>reference</code> of the part

REQUEST BODY

none

RESPONSE BODY

Returns a list of objects with a deleted parameter set to true on success, and the part ID. If no parts are found, a 404 error is returned.

The list will generally only contain a single response object. However, if you perform a deletion of parts with a given reference and there is more than one part using this reference, every part whose reference is given as a parameter will be deleted.

Bulk part price update

POST Body

```
[
  {
    "reference": "p11",
    "price": "10,25"
  },
  {
    "id": 35959,
    "price": "70,25"
  },
  {
    "id": 35919,
    "price": "-100,25"
  },
  {
    "id": 359112519,
    "price": "540,25"
  }
]
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/part/prices \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '[{"reference": "p11","price": "10,25"} (...)]'
```

JSON Returned

```
[
  {
    "reference": "p11",
    "price": "10,25",
    "error": null
  },
  {
    "id": 35959,
    "price": "70,25",
    "error": null
  },
  {
    "id": 35919,
    "price": "-100,25",
    "error": "Part id not found"
  },
  {
    "id": 359112519,
    "price": "540,25",
    "error": null
  }
]
```

HTTP REQUEST

POST /api/v3/part/prices

REQUEST BODY

Set of `id` or `reference` paired with the new price, in JSON format.

RESPONSE BODY

If the request is entirely or partially successful, the response will contain the request content with an `error` field added to each part (set to `null` if there was no error, otherwise error description is shown).

If another type of error occurred, a standard error payload will be returned.

Invoices

The invoice object

JSON Representation

```
{
  "id":456,
  "num":132,
  "reference":"132_Invoice_12_6_2022",
  "type":"invoice",
  "status":"draft",
  "description":"Boiler Installation Invoice",
  "paymentDate":"2018-05-02",
  "customer":{
    "id":35604,
    "myId":"sCustomer08",
    "name": "Sample Customer",
  },
  "site":{
    "id":2811,
    "myId": "ref-2511",
    "name":"Sample Site",
  },
  "job":{
    "id": "265_160719144323649",
    "myId": "ref-job05014",
    "num": 154872
  },
  "dateCreated": "2018-04-06 10:19",
  "dateChanged": "2018-04-06 10:23",
  "lines":[
    {
      "description":"Hybrid Valve",
      "partProductCode":"HV-11",
      "quantity":"10",
      "unitPrice":"19.95",
      "discountPercent":"0",
      "subTotal":"199.50",
      "taxRate":"10.00",
      "taxAmt":"19.95",
      "total":"219.45"
    },
    {
      "description":"Valve Gasket (Special Order)",
      "partProductCode":"",
      "quantity":"10",
      "unitPrice":"2.00",
      "discountPercent":"50.00",
      "subTotal":"10.00",
      "taxRate":"10.00",
      "taxAmt":"1.00",
    }
  ]
}
```

```
    "total": "11.00"
  },
  ],
  "subtotal": 209.50,
  "taxAmt": 20.95,
  "total": 230.45,
  "customFieldValues": [
    {
      "id": 6543,
      "label": "Contact",
      "value": "Marketing"
    },
    {
      "id": 6544,
      "label": "Date",
      "value": "2022-12-22"
    },
    {
      "id": 6545,
      "label": "Reference",
      "value": "ref_132"
    }
  ]
}
```

Invoices are represented by the following fields

Field	Type	Description
id	integer	Invoice id (read only)
num	integer	Invoice number
reference	string	Invoice reference
type	string	type : <code>invoice</code>
status	string	Status of the invoice, one of <code>draft</code> , <code>new</code> , <code>sent</code> , <code>late</code> , <code>paid</code> or <code>cancelled</code>
description	string	Description of the Invoice
paymentDate	datetime	Invoice payment date
dateCreated	datetime	Invoice creation date
dateChanged	datetime	Invoice update date
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields (required when creating an invoice)
site	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> site fields (optional - not required when creating an invoice)
job	object	Object containing <code>id</code> , <code>num</code> and <code>myId</code> job fields (optional - not required when creating an invoice)
lines	list	List of line items (see below)
subtotal	decimal	Sub-total (before taxes)
taxAmt	decimal	Total taxes applied

Field	Type	Description
total	decimal	Total amount
customFieldValues	list	List of custom field values for your invoice

A representation of an Invoice's or a Quotation's or a Credit Note's **line** has the following fields :

Field	Type	Description
description	string	Line description (or Part description if the line refers to a part)
partProductCode	string	Part product code
quantity	string	Number or items/parts for the line
unitPrice	string	Price for one part/item
discountPercent	string	percent discount applied. defaults to 0.
subTotal	string	sub total for the line with the discount (if any) applied
taxRate	string	The tax rate applied
taxAmt	string	The tax amount calculated (based on <code>subTotal</code>)
total	string	Calculated total, inclusive of tax

Retrieve an invoice

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/invoice/details?num=132' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "id":456,
  "num":132,
  "reference":"132_Invoice_12_6_2022",
  "type":"invoice",
  "status":"draft",
  "description":"Boiler Installation Invoice",
  "paymentDate":"2018-05-02",
  "customer":{
    "id":35604,
    "myId":"sCustomer08",
    "name": "Sample Customer",
  },
  "site":{
    "id":2811,
```

```

    "myId": "ref-2511",
    "name": "Sample Site",
  },
  "job": {
    "id": "265_160719144323649",
    "myId": "ref-job05014",
    "num": 154872
  },
  "dateCreated": "2018-04-06 10:19",
  "dateChanged": "2018-04-06 10:23",
  "lines": [
    {
      "description": "Hybrid Valve",
      "partProductCode": "HV-11",
      "quantity": "10",
      "unitPrice": "19.95",
      "discountPercent": "0",
      "subTotal": "199.50",
      "taxRate": "10.00",
      "taxAmt": "19.95",
      "total": "219.45"
    },
    {
      "description": "Valve Gasket (Special Order)",
      "partProductCode": "",
      "quantity": "10",
      "unitPrice": "2.00",
      "discountPercent": "50.00",
      "subTotal": "10.00",
      "taxRate": "10.00",
      "taxAmt": "1.00",
      "total": "11.00"
    }
  ],
  "subtotal": 209.50,
  "taxAmt": 20.95,
  "total": 230.45,
  "customFieldValues": [
    {
      "id": 6543,
      "label": "Contact",
      "value": "Marketing"
    },
    {
      "id": 6544,
      "label": "Date",
      "value": "2022-12-22"
    },
    {
      "id": 6545,
      "label": "Reference",
      "value": "ref_132"
    }
  ]
}
```

HTTP REQUEST

```
GET /api/v3/invoice/details?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code> , <code>reference</code> or <code>num</code>

Parameter	Type	Description
{paramValue}	string	The <code>id</code> , <code>reference</code> or <code>num</code> of the invoice

REQUEST BODY

none

RESPONSE BODY

Returns the invoice if found.

If the invoice/quotation is not found a 404 Error is returned.

Create/Update an invoice

POST Body (creating)

```
{
  "num":132,
  "reference":"132_Invoice_12_6_2022",
  "type":"invoice",
  "status":"draft",
  "description":"Boiler Installation Invoice",
  "action":"add",
  "customer":{
    "id":35604,
  },
  "site":{
    "myId": "ref-2511",
  },
  "job":{
    "num": 154872
  },
  "lines":[
    {
      "description":"Hybrid Valve",
      "partProductCode":"HV-11",
      "quantity":"10",
      "unitPrice":"19.95",
      "discountPercent":"0",
      "subTotal":"199.50",
      "taxRate":"10.00",
      "taxAmt":"19.95",
      "total":"219.45"
    },
    {
      "description":"Valve Gasket (Special Order)",
      "partProductCode":"",
      "quantity":"10",
      "unitPrice":"2.00",
      "discountPercent":"50.00",
      "subTotal":"10.00",
      "taxRate":"10.00",
      "taxAmt":"1.00",
      "total":"11.00"
    }
  ],
  "customFieldValues": [
    {
```

```

    "id": 6543,
    "label": "Contact",
    "value": "Marketing"
  },
  {
    "id": 6544,
    "label": "Date",
    "value": "2022-12-22"
  },
  {
    "id": 6545,
    "label": "Reference",
    "value": "ref_132"
  }
]
}

```

POST Body (updating invoice lines)

```

{
  "num":132,
  "reference":"132_Invoice_12_6_2022",
  "type":"invoice",
  "status":"draft",
  "description":"Boiler Installation Invoice",
  "action":"replace",
  "lines":[
    {
      "description":"Hybrid Valve",
      "partProductCode":"HV-11",
      "quantity":"10",
      "unitPrice":"19.95",
      "discountPercent":"0",
      "subTotal":"199.50",
      "taxRate":"10.00",
      "taxAmt":"19.95",
      "total":"219.45"
    },
    {
      "description":"Valve Gasket (Special Order)",
      "partProductCode":"",
      "quantity":"10",
      "unitPrice":"2.00",
      "discountPercent":"50.00",
      "subTotal":"10.00",
      "taxRate":"10.00",
      "taxAmt":"1.00",
      "total":"11.00"
    }
  ]
}

```

POST Body (changing status)

```

{
  "num":132,
  "status":"sent",
  "action":"add",
  "lines":[]
}

```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/invoice/send \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{\r\n  "num":132,\r\n  "type": "invoice" (...)'
```

JSON Returned

```
{
  "id":456,
  "num":132,
  "reference":"132_Invoice_12_6_2022",
  "type":"invoice",
  "status":"draft",
  "description":"Boiler Installation Invoice",
  "paymentDate":"2018-05-02",
  "customer":{
    "id":35604,
    "myId":"sCustomer08",
    "name": "Sample Customer",
  },
  "site":{
    "id":2811,
    "myId": "ref-2511",
    "name":"Sample Site",
  },
  "job":{
    "id": "265_160719144323649",
    "myId": "ref-job05014",
    "num": 154872
  },
  "dateCreated": "2018-04-06 10:19",
  "dateChanged": "2018-04-06 10:23",
  "lines":[
    {
      "description":"Hybrid Valve",
      "partProductCode":"HV-11",
      "quantity":"10",
      "unitPrice":"19.95",
      "discountPercent":"0",
      "subTotal":"199.50",
      "taxRate":"10.00",
      "taxAmt":"19.95",
      "total":"219.45"
    },
    {
      "description":"Valve Gasket (Special Order)",
      "partProductCode":"",
      "quantity":"10",
      "unitPrice":"2.00",
      "discountPercent":"50.00",
      "subTotal":"10.00",
      "taxRate":"10.00",
      "taxAmt":"1.00",
      "total":"11.00"
    }
  ],
  "subtotal": 209.50,
  "taxAmt": 20.95,
  "total": 230.45,
  "customFieldValues": [
    {
      "id": 6543,
```

```
    "label": "Contact",
    "value": "Marketing"
  },
  {
    "id": 6544,
    "label": "Date",
    "value": "2022-12-22"
  },
  {
    "id": 6545,
    "label": "Reference",
    "value": "ref_132"
  }
]
```

Synchroteam provides a single endpoint to handle creating or updating invoices. The API determines if the invoice record already exists by checking values provided for `id` and/or `num` and/or `reference`:

- if one or both are provided and the invoice is found, the corresponding invoice will be updated
- if neither are provided, a new invoice will be created and a number assigned automatically
- if `id` and/or `num` and/or `reference` is/are provided and not found, an error will be returned.

HTTP REQUEST

POST /api/v3/invoice/send

REQUEST BODY

Invoice information in JSON format, if the `id`, `num` or `reference` exist, the invoice will be updated, if not the invoice will be created.

Special Parameters

Field	Type	Description
action	string	<code>add</code> (lines specified are added to the invoice) or <code>replace</code> (lines specified replace all the existing invoice lines)
customer	object	Object containing all or any of <code>id</code> , <code>name</code> and <code>myId</code> customer fields (required when creating a quotation/invoice)
site	object	Object containing all or any of <code>id</code> , <code>name</code> and <code>myId</code> site fields (optional - not required when creating a quotation/invoice)
job	object	Object containing all or any of <code>id</code> , <code>num</code> and <code>myId</code> job fields (optional - not required when creating a quotation/invoice)

Do note, if you just want to change an invoice status, use `"action": "add"` and send no lines (`"lines": []`).

RESPONSE BODY

The response contains the updated invoice record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.



* No need to provide `subtotal`, `total` and `taxAmt` for the invoice. These are recalculated.

Duplicate an invoice

```
curl --request POST \
  --url 'https://ws.synchroteam.com/api/v3/invoice/duplicate' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0E0EutQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{"id": 98654}'
```

JSON Returned if cancel = true

```
{
  "id": 456,
  "idCreditnote": 457,
  "idDraft": 458
}
```

JSON Returned if cancel = false

```
{
  "id":456,
  "num":0,
  "reference":null,
  "type":"invoice",
  "status":"draft",
  "description":"Boiler Installation Quote",
  "paymendDate":null,
  "customer":{
    "id":35604,
    "myId":"sCustomer08",
    "name": "Sample Customer",
  },
  "site":{
    "id":2811,
    "myId": "ref-2511",
    "name":"Sample Site",
  },
  "job":{
    "id": "265_160719144323649",
    "myId": "ref-job05014",
    "num": 154872
  },
  "dateCreated": "2018-04-06 10:19",
  "lines":[
    {
      "description":"Hybrid Valve",
      "partProductCode":"HV-11",
      "quantity":"10",
      "unitPrice":"19.95",
      "discountPercent":"0",
      "subTotal":"199.50",
      "taxRate":"10.00",
      "taxAmt":"19.95",
      "total":"219.45"
    },
    {
      "description":"Valve Gasket (Special Order)",
      "partProductCode":"",
      "quantity":"10",
      "unitPrice":"2.00",
    }
  ]
}
```

```
{
  "discountPercent": "50.00",
  "subTotal": "10.00",
  "taxRate": "10.00",
  "taxAmt": "1.00",
  "total": "11.00"
},
{
  "subtotal": 209.50,
  "taxAmt": 20.95,
  "total": 230.45,
  "customFieldValues": [
    {
      "id": 6543,
      "label": "Contact",
      "value": "Marketing"
    },
    {
      "id": 6544,
      "label": "Date",
      "value": "2022-12-22"
    },
    {
      "id": 6545,
      "label": "Reference",
      "value": "ref_132"
    }
  ]
}
```

HTTP REQUEST

POST /api/v3/invoice/duplicate

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	integer	ID of the invoice
num	integer	Number of the invoice
reference	string	Reference of the invoice

Special Parameter

Field	Type	Description
cancel	boolean	If set to true, a credit note will be generated + the invoice will be canceled + the invoice will be duplicated in draft. If set to false, the invoice will be duplicated in draft (default: false)

RESPONSE BODY

If `cancel` = true: The response contains `id` of current invoice, `idCreditnote` and `idDraft`.

If `cancel` = false: The response contains the generated invoice record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.

Cancel an invoice

```
curl --request POST \
--url 'https://ws.synchroteam.com/api/v3/invoice/cancel' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{\r\n  "num":132,\r\n  "id": 98654, \r\n  "reference":"98654_Invoice_12_6_2022"}'
```

JSON Returned if credit note has been created

```
{
  "id": 98654,
  "status": "canceled",
  "idCreditnote": 98655
}
```

JSON Returned if credit note hasn't been created

```
{
  "id": 98654,
  "status": "canceled"
}
```

HTTP REQUEST

DELETE /api/v3/invoice/cancel

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	integer	ID of the invoice
num	integer	Number of the invoice
reference	string	Reference of the invoice

Special Parameter

Field	Type	Description
createCreditnote	boolean	Whether or not create a credit note (default: false)

RESPONSE BODY

Returns a Json object with the status `canceled`, the invoice id and the credit note id (if it was created). If no invoice found, a 404 error is returned.



* If the **Strict Invoicing** option is activated, the **createCreditnote** parameter is forced to true

List invoices

```
curl --request GET \
  --url https://ws.synchroteam.com/api/v3/invoice/list?customer_id=35604 \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3R1YW06MTUzODc0REItMUM0OC00NDQzLUE00EUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":4,
  "recordsTotal":4,
  "data":[
    {<invoice object>},
    {<invoice object>},
    ...
    {<invoice object>}
  ]
}
```

HTTP REQUEST

GET /api/v3/invoice/list

QUERY PARAMETERS

Parameter	Type	Description
changedSince	dateTime	return invoices modified after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
createdSince	dateTime	return invoices created after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
paidSince	dateTime	return invoices paid after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
status	string	<code>draft</code> , <code>new</code> , <code>sent</code> , <code>late</code> , <code>paid</code> or <code>cancelled</code>
customer_id	integer	return invoices belonging to a customer by customer <code>id</code>
customer_myId	string	return invoices belonging to a customer by customer <code>myId</code>
site_id	integer	return invoices belonging to a site by site <code>id</code>
site_myId	string	return invoices belonging to a site by site <code>myId</code>
job_id	integer	return invoices belonging to a job by job <code>id</code>
job_myId	string	return invoices belonging to a job by job <code>myId</code>

Parameter	Type	Description
job_num	integer	return invoices belonging to a job by job <code>num</code>
sort	string	sort order, takes one of four values: <code>changedSince</code> , <code>paidSince</code> , <code>status</code> and <code>num</code> (Optional. Default is <i>num</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>descending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of invoices found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Quotations

The quotation object

JSON Representation

```
{
  "id":456,
  "num":132,
  "reference":"132_Quotation_12_6_2022",
  "type":"quotation",
  "status":"draft",
  "description":"Boiler Installation Quote",
  "paymendDate":null,
  "customer":{
    "id":35604,
    "myId":"sCustomer08",
    "name": "Sample Customer",
  },
  "site":{
    "id":2811,
    "myId": "ref-2511",
    "name":"Sample Site",
  },
  "job":{
    "id": "265_160719144323649",
    "myId": "ref-job05014",
    "num": 154872
  },
  "dateCreated": "2018-04-06 10:19",
  "dateChanged": "2018-08-09 16:02",
  "lines":[
    {
      "description":"Hybrid Valve",
      "partProductCode":"HV-11",
      "quantity":"10",
      "unitPrice":"19.95",
      "discountPercent":"0",
      "subTotal":"199.50",
    }
  ]
}
```

```
    "taxRate": "10.00",
    "taxAmt": "19.95",
    "total": "219.45"
  },
  {
    "description": "Valve Gasket (Special Order)",
    "partProductCode": "",
    "quantity": "10",
    "unitPrice": "2.00",
    "discountPercent": "50.00",
    "subTotal": "10.00",
    "taxRate": "10.00",
    "taxAmt": "1.00",
    "total": "11.00"
  }
],
"subtotal": 209.50,
"taxAmt": 20.95,
"total": 230.45,
"customFieldValues": [
  {
    "id": 6543,
    "label": "Contact",
    "value": "Marketing"
  },
  {
    "id": 6544,
    "label": "Date",
    "value": "2022-12-22"
  },
  {
    "id": 6545,
    "label": "Reference",
    "value": "ref_132"
  }
]
}
```

Quotations are the same as invoices, with minor differences:

- `paymentDate` is returned but always null
- `status` only accepts the values: `draft`, `new`, `sent` and `accepted`

Quotations are represented by the following fields

Field	Type	Description
id	integer	Quotation id (read only)
num	integer	Quotation number
reference	string	Quotation reference
type	string	type : <code>quotation</code>
status	string	Status of the quotation, one of <code>draft</code> , <code>new</code> , <code>sent</code> or <code>accepted</code>
description	string	Description of the Quotation
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields (required when creating a quotation)
site	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> site fields (optional - not required when creating a quotation)

Field	Type	Description
job	object	Object containing <code>id</code> , <code>num</code> and <code>myId</code> job fields (optional - not required when creating a quotation)
lines	list	List of line items (see below)
subtotal	decimal	Sub-total (before taxes)
taxAmt	decimal	Total taxes applied
total	decimal	Total amount
customFieldValues	list	List of custom field values for your quotation

A representation of an Invoice's or a Quotation's **line** has the following fields :

Field	Type	Description
description	string	Line description (or Part description if the line refers to a part)
partProductCode	string	Part product code
quantity	string	Number or items/parts for the line
unitPrice	string	Price for one part/item
discountPercent	string	percent discount applied. defaults to 0.
subTotal	string	sub total for the line with the discount (if any) applied
taxRate	string	The tax rate applied
taxAmt	string	The tax amount calculated (based on <code>subTotal</code>)
total	string	Calculated total, inclusive of tax

Retrieve a quotation

HTTP REQUEST

`GET /api/v3/quotation/details`

Uses the same endpoint definition as invoices: See Retrieve an invoice

Create/Update a quotation

HTTP REQUEST

`POST /api/v3/quotation/send`

Uses the same endpoint as invoices: See Create/Update an invoice

Cancel a quotation

```
curl --request POST \
  --url 'https://ws.synchroteam.com/api/v3/quotation/cancel' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{\r\n  "num":132,\r\n  "id": 98654}'
```

JSON Returned

```
[
  {
    "id":984561,
    "status":"canceled"
  }
]
```

HTTP REQUEST

DELETE /api/v3/quotation/cancel

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	integer	ID of the quotation
num	integer	Number of the quotation
reference	string	Reference of the quotation

RESPONSE BODY

Returns a Json object with the status `canceled`, and the quotation ID. If no quotations are found, a 404 error is returned.

Duplicate a quotation

```
curl --request POST \
  --url 'https://ws.synchroteam.com/api/v3/quotation/duplicate' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{"id": 98654}'
```

JSON Returned

```

{
  "id":456,
  "num":0,
  "reference":null,
  "type":"quotation",
  "status":"draft",
  "description":"Boiler Installation Quote",
  "paymendDate":null,
  "customer":{
    "id":35604,
    "myId":"sCustomer08",
    "name": "Sample Customer",
  },
  "site":{
    "id":2811,
    "myId": "ref-2511",
    "name":"Sample Site",
  },
  "job":{
    "id": "265_160719144323649",
    "myId": "ref-job05014",
    "num": 154872
  },
  "dateCreated": "2018-04-06 10:19",
  "dateChanged": "2018-04-06 10:19",
  "lines":[
    {
      "description":"Hybrid Valve",
      "partProductCode":"HV-11",
      "quantity":"10",
      "unitPrice":"19.95",
      "discountPercent":"0",
      "subTotal":"199.50",
      "taxRate":"10.00",
      "taxAmt":"19.95",
      "total":"219.45"
    },
    {
      "description":"Valve Gasket (Special Order)",
      "partProductCode":"",
      "quantity":"10",
      "unitPrice":"2.00",
      "discountPercent":"50.00",
      "subTotal":"10.00",
      "taxRate":"10.00",
      "taxAmt":"1.00",
      "total":"11.00"
    }
  ],
  "subtotal": 209.50,
  "taxAmt": 20.95,
  "total": 230.45,
  "customFieldValues": [
    {
      "id": 6543,
      "label": "Contact",
      "value": "Marketing"
    },
    {
      "id": 6544,
      "label": "Date",
      "value": "2022-12-22"
    },
    {
      "id": 6545,
      "label": "Reference",
      "value": "ref_132"
    }
  ]
}

```

```
    }
  ]
}
```

HTTP REQUEST

```
POST /api/v3/quotation/duplicate
```

REQUEST BODY

provide one or more of the following parameters in the JSON POST payload:

Parameter	Type	Description
id	integer	ID of the quotation
num	integer	Number of the quotation
reference	string	Reference of the quotation

RESPONSE BODY

The response contains the generated quotation record, with the `id` field specified.

If an error occured, a standard error payload will be returned.

NB: The generated quotation will be in draft.

List quotations

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/quotation/list?customer_id=35604 \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":4,
  "recordsTotal":4,
  "data":[
    {<quotation object>},
    {<quotation object>},
    ...
    {<quotation object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/quotation/list
```

QUERY PARAMETERS

Parameter	Type	Description
changedSince	dateTime	return quotations modified after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
createdSince	dateTime	return quotations created after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
status	string	<code>draft</code> , <code>new</code> , <code>sent</code> Or <code>accepted</code>
customer_id	integer	return quotations belonging to a customer by customer <code>id</code>
customer_myId	string	return quotations belonging to a customer by customer <code>myId</code>
site_id	integer	return quotations belonging to a site by site <code>id</code>
site_myId	string	return quotations belonging to a site by site <code>myId</code>
job_id	integer	return quotations belonging to a job by job <code>id</code>
job_myId	string	return quotations belonging to a job by job <code>myId</code>
job_num	integer	return quotations belonging to a job by job <code>num</code>
sort	string	sort order, takes one of four values: <code>changedSince</code> , <code>paidSince</code> , <code>status</code> and <code>num</code> (Optional. Default is <i>changedSince</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>descending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of quotations found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Credit Notes

The Credit Note object

JSON Representation

```
{
  "id":456,
  "num":132,
  "reference": null,
  "job":{
    "id": "265_160719144323649",
    "myId": "ref-job05014",
    "num": 154872
  },
}
```

```
"customer":{
  "id":35604,
  "myId":"sCustomer08",
  "name": "Sample Customer",
},
"description":"","
"type":"creditnote",
"status":"draft",
"site":{
  "id":2811,
  "myId": "ref-2511",
  "name":"Sample Site",
},
"paymendDate":null,
"dateCreated": "2018-04-06 10:19",
"dateChanged": "2018-06-08 08:47",
"lines":[
  {
    "description":"Hybrid Valve",
    "partProductCode":"HV-11",
    "quantity":"10",
    "unitPrice":"19.95",
    "discountPercent":"0",
    "subTotal":"199.50",
    "taxRate":"10.00",
    "taxAmt":"19.95",
    "total":"219.45"
  },
  {
    "description":"Valve Gasket (Special Order)",
    "partProductCode":"","
    "quantity":"10",
    "unitPrice":"2.00",
    "discountPercent":"50.00",
    "subTotal":"10.00",
    "taxRate":"10.00",
    "taxAmt":"1.00",
    "total":"11.00"
  }
],
"subtotal": 209.50,
"taxAmt": 20.95,
"total": 230.45,
"customFieldValues": [],
"linkedInvoice": {
  "id": 9787539,
  "num": 12233,
  "reference": "INV_2050-47-94-012233"
}
}
```

Credit Notes are represented by the following fields

Field	Type	Description
id	integer	Creditnote id (read only)
num	integer	Creditnote number
type	string	type : <code>creditnote</code>
status	string	Status of the Credit Note, one of <code>draft</code> , <code>new</code> , <code>sent</code> or <code>accepted</code>
description	string	Description of the Credit Note

Field	Type	Description
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields
site	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> site fields
job	object	Object containing <code>id</code> , <code>num</code> and <code>myId</code> job fields
lines	list	List of line items (see below)
subtotal	decimal	Sub-total (before taxes)
taxAmt	decimal	Total taxes applied
total	decimal	Total amount
customFieldValues	list	List of custom field values for your credit node
linkedInvoice	object	Object containing <code>id</code> , <code>num</code> and <code>reference</code> invoice fields

A representation of an Invoice's or a Quotation's **line** has the following fields :

Field	Type	Description
description	string	Line description (or Part description if the line refers to a part)
partProductCode	string	Part product code
quantity	string	Number or items/parts for the line
unitPrice	string	Price for one part/item
discountPercent	string	percent discount applied. defaults to 0.
subTotal	string	sub total for the line with the discount (if any) applied
taxRate	string	The tax rate applied
taxAmt	string	The tax amount calculated (based on <code>subTotal</code>)
total	string	Calculated total, inclusive of tax

Retrieve a Credit Note

```
curl --request GET \
  --url 'https://ws.synchroteam.com/api/v3/creditnote/details?num=132' \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUTQzhEMjg4NzhBQTthB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```

{
  "id": 9806938,
  "num": 12239,
  "reference": "CN_2026- 000012239",
  "job": null,
  "customer": {
    "id": 2710618,
    "name": "AC CONFORT",
    "myId": "zzz2026"
  },
  "vat": "1111111111111111",
  "name": "AC CONFORT",
  "address": "109 rue de la gare BAGNOLET, 93170 \nBagnolet, Seine-Saint-Denis île-de-France 93170 \nFrance",
  "description": null,
  "site": null,
  "type": "creditnote",
  "status": "draft",
  "paymentDate": null,
  "dateCreated": "2026-04-16 18:12",
  "dateChanged": "2026-04-16 18:12",
  "dueDate": null,
  "subTotal": -2660.0000,
  "taxAmt": -146.3100,
  "total": -2806.3100,
  "lines": [
    {
      "description": "Qualified workforce",
      "partProductCode": "MO_T2",
      "taxRate": "0,00000",
      "discountPercent": "0,0000",
      "discountAmount": "0",
      "quantity": "1,00",
      "unitPrice": "-735,0000",
      "subTotal": "-735,0000",
      "taxAmt": "0,0000",
      "total": "-735,0000"
    },
    {
      "description": "Screw",
      "partProductCode": "VIS_50*5",
      "taxRate": "0,00000",
      "discountPercent": "0,0000",
      "discountAmount": "0",
      "quantity": "1,00",
      "unitPrice": "-665,0000",
      "subTotal": "-665,0000",
      "taxAmt": "0,0000",
      "total": "-665,0000"
    },
    {
      "description": "Voirie",
      "partProductCode": "TDV",
      "taxRate": "0,00000",
      "discountPercent": "0,0000",
      "discountAmount": "0",
      "quantity": "1,00",
      "unitPrice": "-630,0000",
      "subTotal": "-630,0000",
      "taxAmt": "0,0000",
      "total": "-630,0000"
    },
    {
      "description": "Blue",
      "partProductCode": "BL",
      "taxRate": "0,00000",
      "discountPercent": "0,0000",
      "discountAmount": "0",

```

```
    "quantity": "1,00",
    "unitPrice": "-630,0000",
    "subTotal": "-630,0000",
    "taxAmt": "0,0000",
    "total": "-630,0000"
  }
],
"customFieldValues": [],
"linkedInvoice": {
  "id": 489489,
  "num": 7815,
  "reference": "INV_2026-04-14-012233"
}
}
```

HTTP REQUEST

```
GET /api/v3/invocreditnoteice/details?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code> , <code>reference</code> or <code>num</code>
{paramValue}	string	The <code>id</code> , <code>reference</code> or <code>num</code> of the creditnote

REQUEST BODY

none

RESPONSE BODY

Returns the creditnote if found.

If the creditnote is not found an 404 Error is returned.

List Credit Notes

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/creditnote/list?customer_id=35604 \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE00EUTQzhEMjg4NzhBQThtB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":4,
  "recordsTotal":4,
  "data":[
    {<Credit Note object>},
    {<Credit Note object>},
```

```
...
  {<Credit Note object>}
}
```

HTTP REQUEST

GET /api/v3/creditnote/list

QUERY PARAMETERS

Parameter	Type	Description
changedSince	dateTime	return Credit Notes modified after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
createdSince	dateTime	return Credit Notes created after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
status	string	<code>draft</code> , <code>new</code> , <code>sent</code> or <code>accepted</code>
customer_id	integer	return Credit Notes belonging to a customer by customer <code>id</code>
customer_myId	string	return Credit Notes belonging to a customer by customer <code>myId</code>
site_id	integer	return Credit Notes belonging to a site by site <code>id</code>
site_myId	string	return Credit Notes belonging to a site by site <code>myId</code>
job_id	integer	return Credit Notes belonging to a job by job <code>id</code>
job_myId	string	return Credit Notes belonging to a job by job <code>myId</code>
job_num	integer	return Credit Notes belonging to a job by job <code>num</code>
sort	string	sort order, takes one of four values: <code>changedSince</code> , <code>paidSince</code> , <code>status</code> and <code>num</code> (Optional. Default is <i>changedSince</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>descending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of Credit Notes found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Inventory Management

In Synchroteam Inventory Management is an extension of the Parts and Services catalogue. It allows you to manage Stock Depots and either request or move parts between them.

Part Movements

Move parts

The parts and quantities specified are moved from the source depot to the destination depot.

POST Body (serialized part)

```
{
  "source":{
    "id":"18af2bf1-0973-4958-a66e-c5fe974ec129"
  },
  "destination":{
    "name":"Test stock depot"
  },
  "part":{
    "id": "p666",
    "serials":["bb11","bb22"]
  }
}
```

POST Body (unserialized part)

```
{
  "source":{
    "id":"18af2bf1-0973-4958-a66e-c5fe974ec129"
  },
  "destination":{
    "name":"Test stock depot"
  },
  "part":{
    "reference": "MO_T23",
    "quantity":2
  }
}
```

Sample Code

```
curl --request POST \
  --url https://ws.synchroteam.com/api/v3/partmovement/do \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThtB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json' \
  --data '{\r\n  "quantity":2,\r\n  "serials":["bb11","bb22"]\r\n}'
```

JSON Returned

```
{
  "quantityMoved":2,
  "serialsMoved":["bb11","bb22"]
}
```

HTTP REQUEST

POST /api/v3/partmovement/do

REQUEST BODY

Field	Type	Description
source	object	Source depot for movement. Specify <code>id</code> or <code>name</code> .
destination	object	Destination depot for movement. Specify <code>id</code> or <code>name</code> .
part	part	Specify the part <code>reference</code> (or <code>id</code>) and <code>quantity</code> . For serialized parts, provide a list of serial numbers and omit the quantity (<code>serials</code> : list of strings).

RESPONSE BODY

If successful, the response contains the following data:

Field	Type	Description
quantityMoved	integer	Number of parts moved
serialsMoved	list(string)	List of part serial numbers moved (empty list if the part was not serialized)

ERRORS

If an error is encountered a 400 Error is returned, e.g.:

- *Not enough parts at source*
- *Serial number `serial_number` not found*

Part Requests

The parts request object

JSON Representation

```
{
  "id": "22aa76ac-03c8-4fdb-baee-dca2d33cdd23",
  "source": {
    "idStock": "18af2bf1-0973-4958-a66e-c5fe974ec129",
    "nmStock": "stock4"
  },
  "destination": {
    "idStock": "d6a71643-0ad2-4de8-abcb-34f54c4ca12e",
    "nmStock": "stock"
  },
  "user": {
    "id": 54022,
    "name": "John Doe",
    "login": "login_user",
  },
  "part": {
    "id": 35947,
    "reference": "p6666",
    "name": "p6666",
  }
}
```

```
    "unitPrice": "12.50"
    "isSerializable":true
  },
  "quantity": 2,
  "isDeleted": false,
  "isComplete": true,
  "isUrgent": false,
  "dateCreated": "2019-01-01 14:10:00"
}
```

A part request is represented by the following fields

Field	Type	Description
id	string	part movement request ID (read-only)
source	object	Source depot for movement (<code>id</code> and <code>name</code>).
destination	object	Destination depot for movement (<code>id</code> or <code>name</code>).
user	object	Object containing <code>id</code> , <code>name</code> and <code>login</code> for the user that made the request
part	object	Object containing <code>id</code> , <code>reference</code> , <code>name</code> , <code>isSerializable</code> and <code>unitPrice</code> for the part
quantity	integer	Number of parts in the request
isDeleted	boolean	whether or not the request has been deleted
isComplete	boolean	whether or not the request has been completed
isUrgent	boolean	whether or not the request is urgent
dateCreated	datetime (yyyy-mm-dd HH:mm)	Date the request was created

Retrieve a part request

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/partrequest/details?id=22aa76ac-03c8-4fdb-baee-dca2d33cdd23' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0C0NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "id": "22aa76ac-03c8-4fdb-baee-dca2d33cdd23",
  "source": {
    "idStock": "18af2bf1-0973-4958-a66e-c5fe974ec129",
    "nmStock": "stock4"
  },
  "destination": {
    "idStock": "d6a71643-0ad2-4de8-abcb-34f54c4ca12e",
```

```
    "nmStock": "stock"
  },
  "user": {
    "id": 54022,
    "name": "John Doe",
    "login": "login_user",
  }
  "part": {
    "id": 35947,
    "reference": "p6666",
    "name": "p6666",
    "unitPrice": "12.50"
    "isSerializable": true
  },
  "quantity": 2,
  "isDeleted": false,
  "isComplete": true,
  "isUrgent": false,
  "dateCreated": "2019-01-01 14:10:00"
}
```

HTTP REQUEST

GET /api/v3/partrequest/details?{paramType}={paramValue}

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code>
{paramValue}	string	The <code>id</code> of the partrequest

REQUEST BODY

none

RESPONSE BODY

Returns the part request if found.

If the part request is not found a 404 Error is returned.

Create/Update a part request

Creates a request for the movement of parts from the source depot to the destination depot.

POST Body (serialized part)

```
{
  "source": {
    "idStock": "18af2bf1-0973-4958-a66e-c5fe974ec129"
  },
  "destination": {
    "nmStock": "stock"
  },
  "user": {
    "id": 54022,
  }
  "part": {
```

```
    "id": 35947
  },
  "quantity": 2,
  "isUrgent": false
},
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/partrequest/send \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{"source":{"idStock":"18af2bf1-0973-4958-a66e-c5fe974ec129"} (...)}'
```

JSON Returned

```
{
  "id": "22aa76ac-03c8-4fdb-baee-dca2d33cdd23",
  "source": {
    "idStock": "18af2bf1-0973-4958-a66e-c5fe974ec129",
    "nmStock": "stock4"
  },
  "destination": {
    "idStock": "d6a71643-0ad2-4de8-abc3-34f54c4ca12e",
    "nmStock": "stock"
  },
  "user": {
    "id":54022,
    "name": "John Doe",
    "login": "login_user",
  }
  "part": {
    "id": 35947,
    "reference": "p6666",
    "name": "p6666",
    "unitPrice": "12.50"
    "isSerializable":true
  },
  "quantity": 2,
  "isDeleted": false,
  "isComplete": true,
  "isUrgent": false,
  "dateCreated": "2019-01-01 14:10:00"
}
```

HTTP REQUEST

POST /api/v3/partrequest/send

REQUEST BODY

Field	Type	Description
id	string	part movement request ID (read-only - optional: specify to perform an update)
source	object	Source depot for movement. Specify <code>id</code> and/or <code>name</code> .
destination	object	Destination depot for movement. Specify <code>id</code> and/or <code>name</code> .

Field	Type	Description
user	object	Object containing <code>id</code> and/or <code>login</code> for the user that makes the request
part	object	Object containing <code>id</code> and/or <code>reference</code> for the part
quantity	integer	Number of parts moved (optional if you provide a list of serial numbers)
isDeleted	boolean	whether or not the request has been deleted (optional - default <code>false</code>)
isUrgent	boolean	whether or not the request is urgent (optional - default <code>false</code>)

RESPONSE BODY

The response contains the updated part request record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.

List part requests

```
curl --request GET \
--url https://ws.synchroteam.com/api/v3/partrequest/list?isUrgent=true \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE00EUTQzhEMjg4NzhBQTthB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":8,
  "recordsTotal":8,
  "data":[
    {<part request object>},
    {<part request object>},
    ...
    {<part request object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/partrequest/list
```

QUERY PARAMETERS

Parameter	Type	Description
isUrgent	boolean	Is the request urgent (true/false)?
isDeleted	boolean	Is the request deleted (true/false)?

Parameter	Type	Description
isSent	boolean	Is the request sent (true/false)?
isComplete	boolean	Has the request been completed (true/false)?
changedSince	date time (yyyy-mm-dd HH:mm)	Get requests modified after <code>changedSince</code>
createdSince	date time (yyyy-mm-dd HH:mm)	Get requests created after <code>createdSince</code>
sort	string	sort order, takes one of three values: <code>dateCreated</code> , <code>isUrgent</code> and <code>isSent</code> (Optional. Default is <code>dateCreated</code>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <code>ascending</code>)

Add pagination parameters if needed.

RESPONSE BODY

A list of part requests found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Fulfill a parts request

POST Body (for a serialized part)

```
{
  "quantity":2,
  "requestId":"1C9035A3-CE56-4E13-B9D0-DFFB9C02E782",
  "serials":["bb11","bb22"]
}
```

POST Body (for an unserialized part)

```
{
  "quantity":2,
  "requestId":"1C9035A3-CE56-4E13-B9D0-DFFB9C02E782",
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/partrequest/fulfill \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
```

```
--header 'content-type: application/json' \
--data '{"quantity":2,"requestId":"1C9035A3-CE56-4E13-B9D0-DFFB9C02E782","requestId":["bb11","bb22"]}'
```

JSON Returned

```
{
  "id": "22aa76ac-03c8-4fdb-baee-dca2d33cdd23",
  "source": {
    "idStock": "18af2bf1-0973-4958-a66e-c5fe974ec129",
    "nmStock": "stock4"
  },
  "destination": {
    "idStock": "d6a71643-0ad2-4de8-abcb-34f54c4ca12e",
    "nmStock": "stock"
  },
  "user": {
    "id": 54022,
    "name": "John Doe",
    "login": "login_user",
  }
  "part": {
    "id": 35947,
    "reference": "p6666",
    "name": "p6666",
    "unitPrice": "12.50"
    "isSerializable":true
  },
  "quantity": 2,
  "isDeleted": false,
  "isComplete": true,
  "isUrgent": false,
  "dateCreated":"2019-01-01 14:10:00"
}
```

HTTP REQUEST

```
POST /api/v3/partrequest/fulfill
```

REQUEST BODY

Field	Type	Description
id	string	ID of the part movement request
isPartial	boolean	if <code>true</code> the request will not be marked as completed (default <code>false</code>)
quantity	integer	Number of parts (only required when the request relates to an unserialized part)

RESPONSE BODY

The response contains the updated part request.

If an error occurred, a standard error payload will be returned.

Stock Depots

Within Sychroteam's Stock Management. You can have one or more stock depots, and each of your technicians' vehicles can be tracked as stock depots as well, allowing you to follow part movements across your infrastructure.

The stock depot object

JSON Representation

```
{
  "id": "1C9035A3-CE56-4E13-B9D0-DFFB9C02E782",
  "name": "Main Depot",
  "isDefault": true,
  "isProvider": true,
  "owners": [{
    "id": 123456,
    "name": "John Doe",
    "login": "jdoe"
  },
  {
    "id": 987654,
    "name": "Jane Doe",
    "login": "janedoe"
  }
],
  "parts": [{
    "id": 245684,
    "name": "10mm Bearing",
    "reference": "refHi001",
    "quantity": 4,
    "serials": ["3000", "3103", "3020", "3057"]
  }, {
    "id": 685946,
    "name": "Titanium Hinges Ti48",
    "reference": "KAAQ3104A",
    "quantity": 20,
    "serials": []
  }
]
```

A stock depot is represented by the following fields

Field	Type	Description
id	int	Stock Depot ID
name	string	Stock Depot Name
isDefault	boolean	Sets this stock depot as the default (true) or not (false).
isProvider	boolean	Sets this stock depot as a provider (true) or not (false).*
owners	list of object	List of all users who owns the depot, with <code>id</code> , <code>name</code> and <code>login</code> .
parts	list of objects	List of all parts in the depot, with <code>id</code> , <code>name</code> , <code>reference</code> and <code>quantity</code> (and serial numbers for serialized parts).

(*) A provider depot is one that generally sources parts to mobile depots, such as a technician's vehicle

Retrieve a depot

```
curl --request GET \
--url 'https://ws.synchroteam.com/api/v3/depot/details?id=1C9035A3-CE56-4E13-B9D0-DFFB9C02E782' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json'
```

Example Response

```
{
  "id": "1C9035A3-CE56-4E13-B9D0-DFFB9C02E782",
  "name": "Main Depot",
  "isDefault": true,
  "isProvider": true,
  "owners": [
    {
      "id": 123456,
      "name": "John Doe",
      "login": "jdoe"
    },
    {
      "id": 987654,
      "name": "Jane Doe",
      "login": "janedoe"
    }
  ],
  "parts": [
    {
      "id": 245684,
      "name": "10mm Bearing",
      "reference": "refHi001",
      "quantity": 4,
      "serials": ["3000", "3103", "3020", "3057"]
    },
    {
      "id": 685946,
      "name": "Titanium Hinges Ti48",
      "reference": "KAAQ3104A",
      "quantity": 20,
      "serials": []
    }
  ]
}
```

HTTP REQUEST

```
GET /api/v3/depot/details?{paramType}={paramValue}
```

QUERY PARAMETERS

Parameter	Type	Description
{paramType}	string	Parameter name. Accepts <code>id</code>
{paramValue}	string	The <code>id</code> of the depot

REQUEST BODY

none

RESPONSE BODY

Returns the stock depot if found.

If the depot is not found a 404 Error is returned.

List depots

```
curl --request GET \
  --url https://ws.synchroteam.com/api/v3/depot/list?isProvider=true \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQTthB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
{
  "page":1,
  "pageSize":25,
  "records":4,
  "recordsTotal":4,
  "data":[
    {<stock depot object>},
    {<stock depot object>},
    ...
    {<stock depot object>}
  ]
}
```

HTTP REQUEST

```
GET /api/v3/depot/list
```

QUERY PARAMETERS

Parameter	Type	Description
isProvider	boolean	true/false (optional)
isDefault	boolean	true/false (optional)
name	string	search by name - a wildcard search is performed
sort	string	sort order, takes one of two values: <code>name</code> or <code>isProvider</code> (Optional. Default is <i>name</i>)
sortOrder	string	takes one of two values: <code>ascending</code> or <code>descending</code> (Optional. Default is <i>ascending</i>)

Add pagination parameters if needed.

RESPONSE BODY

A list of depots found (NB: In this mode, the part list for each depot **is not** provided. Retrieve a specific depot to see the parts list)

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Initialize depot quantities

POST Body

```
[
  {
    "depot": {
      "name": "stock4"
    },
    "parts": [
      {
        "productCode": "KAAQ3104A",
        "quantity": 210
      },
      {
        "productCode": "refHi001",
        "serials": ["771000", "771010", "771020", "771050", "771045", "771045"]
      }
    ]
  },
  {
    "depot": {
      "id": "1C9035A3-CE56-4E13-B9D0-DFFB9C02E782",
    },
    "parts": [
      {
        "productCode": "refHi001",
        "quantity": null,
        "serials": ["3000", "3103", "3020", "3057"]
      },
      {
        "productCode": "KAAQ3104A",
        "quantity": 20,
        "serials": []
      }
    ]
  }
]
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/depot/quantities \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '[{"\r\n  {\r\n    "depot":{"name":"stock4"},",\r\n    "parts":[{"\r\n  (...}]'
```

JSON Returned

```
[
  {
    "id": "1D9035A4-AA56-4E13-C9D0-DFFB9C02E784",
    "name": "stock4",
    "partsLoaded": 2,
    "error": [
      null,
      null
    ]
  },
  {
    "id": "1C9035A3-CE56-4E13-B9D0-DFFB9C02E782",
    "name": "stock3",
    "partsLoaded": 1,
```

```
{
  "error": [
    "Depot part Id not found",
    null
  ]
}
```

HTTP REQUEST

POST /api/v3/depot/quantities

QUERY PARAMETERS

None

REQUEST BODY

A list of objects containing:

- `depot`: simplified depot object. Provide `name` and/or `id`.
- `parts`: parts list. For each part specify the part `productCode` and `quantity`. For serialized parts, provide a list of serial numbers and omit the quantity (`serials`: list of strings).

RESPONSE BODY

A list of objects containing:

- `id`: depot id
- `name`: depot name
- `partsLoaded`: number of parts loaded
- `errors`: list of strings. any errors encountered are listed.

Stock Parts

See the Parts and Services documentation.

Messages

The Message object

JSON Representation

```
{
  "title": "Training Info",
  "message": "Hi - The Synchroteam Training is scheduled for Monday at 2pm",
  "priority": "high",
  "users": [
    {
      "id": 123654
    },
    {
      "login": "john"
    }
  ]
}
```

```
}
]
}
```

A Message is represented by the following fields

Field	Type	Description
title	string	Title of the message
message	string	The message to send
priority	string	Priority : <code>null</code> , <code>medium</code> , <code>high</code>
users	list(User)	Users recipients, defined by <code>id</code> or <code>login</code>

Send a Message

Synchroteam provides a single endpoint to send a Message to a Technician. These are Messages that the Technician can find inside the Mobile App

Sample Code

```
curl --request POST \
--url 'https://ws.synchroteam.com/api/v3/message/send' \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEutQzhEMjg4NzhBQThB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{"title":"Training Info","priority" : "high", (...) }'
```

Example Response

```
{
  "message": "Hi - The Synchroteam Training is scheduled for Monday at 2pm",
  "priority": "high",
  "title": "Training Info",
  "users": [
    {
      "id": 123654,
      "login": "william"
    },
    {
      "id": 13579,
      "login": "john"
    }
  ]
}
```

Timeline

The Timeline object

JSON Representation

```
{
  "id": 7,
  "type": "meeting",
  "title": "Test Note",
  "content": "Note Content",
  "isPinned": true,
  "isPublic": false,
  "dateCreated": "2023-04-29 22:45",
  "event": null,
  "source": "timeline",
  "customer": {
    "id": 24306,
    "name": " Philippe The Originals",
    "myId": "ref Philippe "
  },
  "site": {
    "id": 267681,
    "name": "Philippe The Originals -- Site1",
    "myId": "ref Site1"
  },
  "equipment": {
    "id": 260484,
    "name": "Philippe The Originals -- Site1 -- Equip1",
    "myId": "ref Equip1"
  },
  "job": {
    "id": "91e79fa9-c307-4570-9946-73d5b409a8de",
    "num": "2861",
    "myId": "ref job 2861"
  },
  "user": {
    "id": 272,
    "name": "ADIL ROUAY",
    "login": "arouay"
  }
}
```

Timeline items are represented by the following fields

Field	Type	Description
id	integer	Timeline item id (read only)
type	string	Timeline item type: <code>note</code> , <code>call</code> , <code>email</code> , <code>meeting</code> , <code>sms</code>
title	string	Timeline item title
content	string	Timeline item note
isPinned	boolean	Whether or not the Timeline item is pinned

Field	Type	Description
isPublic	boolean	Whether or not the Timeline item is public
dateCreated	datetime	Timeline item creation date
event	string	Timeline item event: <code>unscheduled</code> , <code>created</code> , <code>scheduled</code> , <code>synchronized</code> , <code>started</code> , <code>paused</code> , <code>completed</code> , <code>validated</code> , <code>cancelled</code> , <code>deleted</code> Or <code>null</code>
source	string	Timeline item source: <code>timeline</code> , <code>notification</code>
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields
site	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> site fields
equipment	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> equipment fields
job	object	Object containing <code>id</code> , <code>num</code> and <code>myId</code> job fields
user	object	Object containing <code>id</code> , <code>name</code> and <code>login</code> user fields

List Timeline items

```
curl --request GET \
  --url https://ws.synchroteam.com/api/v3/timeline/list \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0OEUtQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
[
  {<timeline object>},
  {<timeline object>},
  ...
  {<timeline object>}
]
```

HTTP REQUEST

```
GET /api/v3/timeline/list
```

QUERY PARAMETERS

Parameter	Type	Description
changedSince	dateTime	return Timeline items modified after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
createdSince	dateTime	return Timeline items created after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)

Parameter	Type	Description
isPinned	boolean	return pinned Timeline items
isPublic	boolean	return public Timeline items
customer_id	integer	return Timeline items belonging to a customer by customer <code>id</code>
customer_myId	string	return Timeline items belonging to a customer by customer <code>myId</code>
site_id	integer	return Timeline items belonging to a site by site <code>id</code>
site_myId	string	return Timeline items belonging to a site by site <code>myId</code>
equipment_id	integer	return Timeline items belonging to a equipment by equipment <code>id</code>
equipment_myId	string	return Timeline items belonging to a equipment by equipment <code>myId</code>
job_id	integer	return Timeline items belonging to a job by job <code>id</code>
job_myId	string	return Timeline items belonging to a job by job <code>myId</code>
job_num	integer	return Timeline items belonging to a job by job <code>num</code>
user_id	integer	return Timeline items belonging to a user by user <code>id</code>
user_login	string	return Timeline items belonging to a user by user <code>login</code>
type	string	<code>note</code> , <code>call</code> , <code>email</code> , <code>meeting</code> , <code>sms</code>
event	string	<code>unscheduled</code> , <code>created</code> , <code>scheduled</code> , <code>synchronized</code> , <code>started</code> , <code>paused</code> , <code>completed</code> , <code>validated</code> , <code>cancelled</code> , <code>deleted</code> Or <code>null</code>
source	string	<code>timeline</code> , <code>notification</code>

 * A minimum filter on a Customer or Site or Equipment or Job is required.

RESPONSE BODY

A list of timeline found.

If none are found, an empty list is returned.

The returned list contains notes + notifications.

NB: Multiple filters are cumulative.

Create a Timeline item

POST Body

Sample Code

JSON Returned

180/185

```
}  
}
```

HTTP REQUEST

POST /api/v3/timeline/send

REQUEST BODY

Timeline information in JSON format, only creation is allowed no updates.

RESPONSE BODY

The response contains the updated timeline record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.

 * Content and Customer or Site or Equipment or Job are required.

Tasks

The Task object

JSON Representation

```
{  
  "id": 27,  
  "content": "test 22",  
  "dateDue": "2023-05-26 00:00",  
  "dateDone": null,  
  "dateCreated": "2023-05-06 20:22",  
  "customer": {  
    "id": 24126,  
    "name": " Philippe The Originals",  
    "myId": "ref Philippe "  
  },  
  "site": {  
    "id": 267981,  
    "name": "Philippe The Originals -- Site1",  
    "myId": "ref Site1"  
  },  
  "equipment": {  
    "id": 261484,  
    "name": "Equip 01",  
    "myId": "ref Equip 01"  
  },  
  "job": {  
    "id": "91e79f09-c307-4570-9946-73d5b4a9a8de",  
    "num": "2801",  
    "myId": "ref job 2801"  
  },  
  "user": {  
    "id": 272,  
    "name": "ADIL ROUAY",  
    "login": "arouay"  
  },  
  "userDone": {
```

```
    "id": 271,
    "name": "Tech Mobile",
    "login": "techm"
  },
  "category": "meeting"
}
```

Tasks are represented by the following fields

Field	Type	Description
id	integer	Task id (read only)
content	string	Task note
dateDue	datetime	Task due date
dateDone	datetime	Task done date
dateCreated	datetime	Task creation date
customer	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> customer fields
site	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> site fields
equipment	object	Object containing <code>id</code> , <code>name</code> and <code>myId</code> equipment fields
job	object	Object containing <code>id</code> , <code>num</code> and <code>myId</code> job fields
user	object	Object containing <code>id</code> , <code>name</code> and <code>login</code> user fields
userDone	object	Object containing <code>id</code> , <code>name</code> and <code>login</code> user fields
category	string	Task category <code>rappe1</code> , <code>email</code> , <code>followup</code> , <code>meeting</code> ...

List Tasks

```
curl --request GET \
  --url https://ws.synchroteam.com/api/v3/tasks/list \
  --header 'accept: text/json' \
  --header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE00EUTQzhEMjg4NzhBQThB' \
  --header 'cache-control: no-cache' \
  --header 'content-type: application/json'
```

Example Response

```
[
  {<task object>},
  {<task object>},
  ...
  {<task object>}
]
```

HTTP REQUEST

GET /api/v3/tasks/list

QUERY PARAMETERS

Parameter	Type	Description
changedSince	dateTime	return Tasks modified after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
createdSince	dateTime	return Tasks created after the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
from	dateTime	return Tasks due after UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
to	dateTime	return Tasks due befor the UTC date+time specified (dateTime format: yyyy-mm-dd HH:mm:ss)
customer_id	integer	return Tasks belonging to a customer by customer <code>id</code>
customer_myId	string	return Tasks belonging to a customer by customer <code>myId</code>
site_id	integer	return Tasks belonging to a site by site <code>id</code>
site_myId	string	return Tasks belonging to a site by site <code>myId</code>
equipment_id	integer	return Tasks belonging to a equipment by equipment <code>id</code>
equipment_myId	string	return Tasks belonging to a equipment by equipment <code>myId</code>
job_id	integer	return Tasks belonging to a job by job <code>id</code>
job_myId	string	return Tasks belonging to a job by job <code>myId</code>
job_num	integer	return Tasks belonging to a job by job <code>num</code>
user_id	integer	return Tasks belonging to a user by user <code>id</code>
user_login	string	return Tasks belonging to a user by user <code>login</code>
userDone_id	integer	return Tasks done to a user by user <code>id</code>
userDone_login	string	return Tasks done to a user by user <code>login</code>
category	string	<code>rappel</code> , <code>email</code> , <code>followup</code> , <code>meeting</code> ...

 * A minimum filter on a Customer or Site or Equipment or Job is required.

RESPONSE BODY

A list of tasks found.

If none are found, an empty list is returned.

NB: Multiple filters are cumulative.

Create a Task

POST Body

```
{
  "content": "test task",
  "dateDue": "2023-05-26 00:00",
  "customer": {
    "id": 24306,
    "name": "Philippe The Originals",
    "myId": "ref Philippe "
  },
  "site": {
    "id": 217681,
    "name": "Philippe The Originals -- Site1",
    "myId": "ref Site1"
  },
  "equipment": {
    "id": 260404,
    "name": "Equip 01",
    "myId": "ref Equip 01"
  },
  "job": {
    "id": "91e79fa9-c307-4506-9946-73d5b4a9a8de",
    "num": "2061",
    "myId": "ref job 2061"
  },
  "user": {
    "id": 272,
    "name": "ADIL ROUAY",
    "login": "arouay"
  },
  "category": "followup"
}
```

Sample Code

```
curl --request POST \
--url https://ws.synchroteam.com/api/v3/tasks/send \
--header 'accept: text/json' \
--header 'authorization: Basic c3luY2hyb3RlYW06MTUzODc0REItMUM0OC00NDQzLUE0E0UtQzhEmjg4NzhBQThtB' \
--header 'cache-control: no-cache' \
--header 'content-type: application/json' \
--data '{"content": "test task", "dateDue": "2023-05-26 00:00" (...)}'
```

JSON Returned

```
{
  "id": 27,
  "content": "test 22",
  "dateDue": "2023-05-26 00:00",
  "dateDone": null,
  "dateCreated": "2023-05-06 20:22",
  "customer": {
    "id": 24306,
    "name": " Philippe The Originals",
    "myId": "ref Philippe "
  },
  "site": {
    "id": 217681,
    "name": "Philippe The Originals -- Site1"
```

```
{
  "myId": "ref Site1"
},
"equipment": {
  "id": 260404,
  "name": "Equip 01",
  "myId": "ref Equip 01"
},
"job": {
  "id": "91e79fa9-c307-4506-9946-73d5b4a9a8de",
  "num": "2061",
  "myId": "ref job 2061"
},
"user": {
  "id": 272,
  "name": "ADIL ROUAY",
  "login": "arouay"
},
"userDone": null,
"category": "followup"
}
```

HTTP REQUEST

POST /api/v3/tasks/send

REQUEST BODY

Tasks information in JSON format, only creation is allowed no updates.

RESPONSE BODY

The response contains the updated Tasks record, with the `id` field specified.

If an error occurred, a standard error payload will be returned.

 * Description, Due Date, User and Customer or Site or Equipment or Job are required.

API v62