
LayerSkip Llama2-7B + AMD-Llama-135M | Adopted PS optimization | P1 hit | UID 514_t0 | steps 7-8

Runtime matches ver1.2 9390e21 | RTX4090 | B1 BF16 T0.7 | exit20 K1/K2 6/3 M1/M2 12/8 C3 | frontier

Red dashed line = next target request starts (observed deadline reference). Green circle = PS cache ready; triangle = draft ready to receive.

Both target steps and their DS/PS work share one time axis. Only the following request boundary is used for the second deadline.

In this measurement: no observed proxy computation / target graph_post overlap. Send enqueue does not measure transfer completion.



ALL ELIGIBLE STEPS FOR THIS SETTING (not the two example steps above); Overall is step-weighted.


Current outcome	Steps	Rate (%)	AL (tokens/step)	Profile TPS (tokens/s)
P1 hit	813	34.003	3.399	170.993
P2 hit	1245	52.070	2.010	102.241
Miss	333	13.927	1.937	92.621
Overall	**2391**	**86.073**	**2.472**	**124.175**

Rate = source / all steps; Overall rate = total hit (P1 + P2) / all. AL includes recovery/bonus. Profile TPS = emitted tokens / summed step seconds.

Current outcome	Steps	Step (ms)	DS total (ms)	DS spare* (ms)	DS graph/K1 (ms)	PS total (ms)	PS spare (ms)	PS graph/K2 (ms)
P1 hit	813	19.875	7.715	+1.529	1.137	4.914	+1.482	0.953
P2 hit	1245	19.656	7.567	+1.925	1.109	4.943	+1.391	0.953
Miss	333	20.913	6.604	+3.478	0.952	4.905	+1.638	0.947
Overall	**2391**	**19.905**	**7.483**	**+2.007**	**1.097**	**4.928**	**+1.456**	**0.952**

Step = current target request start -> next request start. *DS spare = proxy send-ready - DS end; PS spare = next request start - draft receive-ready.

Positive spare = early; negative = late. Graph/K includes sampling/selection, not isolated transformer latency. These are profiled-subset TPS, not full evaluation TPS.



Hatched gaps = unprofiled elapsed intervals, NOT proven GPU idle. Nested spans are not additive. White graph dividers show counts, NOT per-forward measurements.

Raw intervals retained, no 0.02 ms visibility floor. Cross-device margins inherit CUDA-to-host clock alignment uncertainty; exact raw events and source hashes accompany this figure.


LayerSkip Llama2-7B + AMD-Llama-135M | Adopted PS optimization | P2 hit | UID 397_t0 | steps 15-16

Runtime matches ver1.2 9390e21 | RTX4090 | B1 BF16 T0.7 | exit20 K1/K2 6/3 M1/M2 12/8 C3 | frontier

Red dashed line = next target request starts (observed deadline reference). Green circle = PS cache ready; triangle = draft ready to receive.

Both target steps and their DS/PS work share one time axis. Only the following request boundary is used for the second deadline.

In this measurement: no observed proxy computation / target graph_post overlap. Send enqueue does not measure transfer completion.



ALL ELIGIBLE STEPS FOR THIS SETTING (not the two example steps above); Overall is step-weighted.

Current outcome	Steps	Rate (%)	AL (tokens/step)	Profile TPS (tokens/s)
P1 hit	813	34.003	3.399	170.993
P2 hit	1245	52.070	2.010	102.241
Miss	333	13.927	1.937	92.621
Overall	**2391**	**86.073**	**2.472**	**124.175**

Rate = source / all steps; Overall rate = total hit (P1 + P2) / all. AL includes recovery/bonus. Profile TPS = emitted tokens / summed step seconds.

Current outcome	Steps	Step (ms)	DS total (ms)	DS spare* (ms)	DS graph/K1 (ms)	PS total (ms)	PS spare (ms)	PS graph/K2 (ms)
P1 hit	813	19.875	7.715	+1.529	1.137	4.914	+1.482	0.953
P2 hit	1245	19.656	7.567	+1.925	1.109	4.943	+1.391	0.953
Miss	333	20.913	6.604	+3.478	0.952	4.905	+1.638	0.947
Overall	**2391**	**19.905**	**7.483**	**+2.007**	**1.097**	**4.928**	**+1.456**	**0.952**

Step = current target request start -> next request start. *DS spare = proxy send-ready - DS end; PS spare = next request start - draft receive-ready.

Positive spare = early; negative = late. Graph/K includes sampling/selection, not isolated transformer latency. These are profiled-subset TPS, not full evaluation TPS.

Command-to-request gap (unprofiled)
PS dispatch gap (unprofiled)
PS prepare A: roots / visibility
PS prepare B: graph input buffers
Post-PS gap (unprofiled)
draft_recv_cmd
draft_recv_request
draft_response_pack
draft_send_fused
draft_send_parent_q_p1
draft_send_parent_q_p2
draft_send_response
exit_logits
exit_proxy_launch
exit_proxy_side
final_logits
glue
graph_post
graph_pre
hit_cache_respond_hit_k1
hit_cache_respond_hit_k2
merge_cache
p1_graph_replay
p1_prepare
p1_root_build
p1_slot_prepare
p2_cache_merge
p2_graph_replay
p2_output_convert
phase2_build
proxy_send_enqueue
proxy_wait
target_postprocess
target_recv_fused
target_recv_parent_q_p1
target_recv_parent_q_p2
target_recv_response_wait
target_response_meta_read
target_response_received
target_send_request
target_spec_wait
tree_accept_walk
tree_hit_pack_served_p1
tree_hit_pack_served_p2
tree_hit_parent_q_gather_p1
tree_hit_parent_q_gather_p2
tree_hit_rerank_p1
tree_hit_rerank_p2
tree_kv_commit
tree_kv_restore
tree_parent_q_select
tree_prep
tree_proxy_graph_replay
tree_proxy_topology_prepare
tree_replay
tree_verify_attention_buffers
tree_verify_mask_prepare
tree_verify_meta_cpu
tree_wire_parse_validate
verify_accept_prep
verify_sample_accept
verify_setup

Hatched gaps = unprofiled elapsed intervals, NOT proven GPU idle. Nested spans are not additive. White graph dividers show counts, NOT per-forward measurements.

Raw intervals retained, no 0.02 ms visibility floor. Cross-device margins inherit CUDA-to-host clock alignment uncertainty; exact raw events and source hashes accompany this figure.


LayerSkip Llama2-7B + AMD-Llama-135M | Adopted PS optimization | Miss | UID 234_t0 | steps 39-40

Runtime matches ver1.2 9390e21 | RTX4090 | B1 BF16 T0.7 | exit20 K1/K2 6/3 M1/M2 12/8 C3 | frontier

Red dashed line = next target request starts (observed deadline reference). Green circle = PS cache ready; triangle = draft ready to receive.

Both target steps and their DS/PS work share one time axis. Only the following request boundary is used for the second deadline.

In this measurement: no observed proxy computation / target graph_post overlap. Send enqueue does not measure transfer completion.



ALL ELIGIBLE STEPS FOR THIS SETTING (not the two example steps above); Overall is step-weighted.


Current outcome	Steps	Rate (%)	AL (tokens/step)	Profile TPS (tokens/s)
P1 hit	813	34.003	3.399	170.993
P2 hit	1245	52.070	2.010	102.241
Miss	333	13.927	1.937	92.621
Overall	**2391**	**86.073**	**2.472**	**124.175**

Rate = source / all steps; Overall rate = total hit (P1 + P2) / all. AL includes recovery/bonus. Profile TPS = emitted tokens / summed step seconds.

Current outcome	Steps	Step (ms)	DS total (ms)	DS spare* (ms)	DS graph/K1 (ms)	PS total (ms)	PS spare (ms)	PS graph/K2 (ms)
P1 hit	813	19.875	7.715	+1.529	1.137	4.914	+1.482	0.953
P2 hit	1245	19.656	7.567	+1.925	1.109	4.943	+1.391	0.953
Miss	333	20.913	6.604	+3.478	0.952	4.905	+1.638	0.947
Overall	**2391**	**19.905**	**7.483**	**+2.007**	**1.097**	**4.928**	**+1.456**	**0.952**

Step = current target request start -> next request start. *DS spare = proxy send-ready - DS end; PS spare = next request start - draft receive-ready.

Positive spare = early; negative = late. Graph/K includes sampling/selection, not isolated transformer latency. These are profiled-subset TPS, not full evaluation TPS.



Hatched gaps = unprofiled elapsed intervals, NOT proven GPU idle. Nested spans are not additive. White graph dividers show counts, NOT per-forward measurements.

Raw intervals retained, no 0.02 ms visibility floor. Cross-device margins inherit CUDA-to-host clock alignment uncertainty; exact raw events and source hashes accompany this figure.