

✖

Try again once you are ready.

Required to pass: 80% or higher

You can retake this quiz up to 3 times every 8 hours.

Back to Week 1

Retake



1 / 1  
points

1. Which of the following are absolutely necessary for creating a functioning shiny app? (Check all that apply)

☐ A server.R file that sets configuration options for hosting the App

Un-selected is correct

☐ A shiny.R file containing calls to shinyServer() and shinyUI()

Un-selected is correct

☒ A server.R file containing a call to shinyServer()

Correct

☐ A ui.R file that contains information about the CSS and styling of the App

Un-selected is correct

☒ A ui.R file containing a call to shinyUI()

Correct



1 / 1  
points

2. What is incorrect about the following syntax in ui.R?

```
1 library(shiny)
2 shinyUI(pageWithSidebar(
3   headerPanel("Data science FTW!"),
4   sidebarPanel(
5     h2("Big text")
6     h3("Sidebar")
7   ),
8   mainPanel(
9     h3("Main Panel text")
10  )
11 ))
```

☐ Missing comma after the h3 command

☐ The h2 command does not take text arguments

☒ Missing a comma in the sidebar panel

Correct

☐ The h3 command should be an h2 command



1 / 1  
points

3. Consider the following in ui.R

```
1 shinyUI(pageWithSidebar(
2   headerPanel("Example plot"),
3   sidebarPanel(
4     sliderInput('mu', 'Guess at the mu', value = 70, min = 60, max = 80, step =
5       0.05, ) ),
6   mainPanel(
7     plotOutput('newHist')
8   ))
```

And the following in server.R

```
1 library(UsingR)
2 data(galton)
3
4 shinyServer({
5   function(input, output) {
6     output$myHist <- renderPlot({
7       hist(galton$child, xlab="child height", col="lightblue", main
8         ="Histogram")
9       mu <- input$mu
10      lines(c(mu, mu), c(0, 200), col="red", lwd=5)
11      mse <- mean((galton$child - mu)^2)
12      text(63, 150, paste("mu = ", mu))
13      text(63, 140, paste("MSE = ", round(mse, 2)))
14    })
15  }
```

Why isn't it doing what we want? (Check all that apply.)

☐ The limits of the slider are set incorrectly and giving an error.

☒ The server.R output name isn't the same as the plotOutput command used in ui.R.

Correct

☐ It should be

```
1 mu <- input$mean
```

in server.R

☐ The phrase "Guess at the mu value" should say "mean" instead of "mu"

0.80 / 1  
points

4. What are the main differences between creating a Shiny Gadget and creating a regular Shiny App? (Check all that apply)

☒ Shiny Gadgets are designed to have small user interfaces that fit on one page.

Correct

☒ Shiny Gadgets can be run on a user's personal computer, unlike a regular Shiny App which needs to be hosted online.

This should not be selected

☐ Shiny Gadgets are smaller programs and therefore run faster than Shiny Apps.

Un-selected is correct

☒ Shiny Gadgets are designed to be used by R users in the middle of a data analysis.

Correct

☐ Shiny Gadgets are specially designed for use on mobile phones and tablet computers.

Un-selected is correct



0 / 1  
points

5. Consider the following R script:

```
1 library(shiny)
2 library(miniUI)
3
4 pickXY <- function() {
5   ui <- miniPage(
6     gadgetTitleBar("Select Points by Dragging your Mouse"),
7     miniContentPanel(
8       plotOutput("plot", height = "100%", brush = "brush")
9     )
10  )
11
12  server <- function(input, output, session) {
13    output$plot <- renderPlot({
14      plot(data_frame$X, data_frame$Y, main = "Plot of Y versus X",
15        xlab = "X", ylab = "Y")
16    })
17    observeEvent(input$done, {
18      stopApp(brushedPoints(data_frame, input$brush,
19        xvar = "X", yvar = "Y"))
20    })
21  }
22
23  runGadget(ui, server)
24 }
25
26 my_data <- data.frame(X = rnorm(100), Y = rnorm(100))
27
28 pickXY(my_data)
```

Why isn't it doing what we want?

☐ No arguments are defined for pickXY()

☐ The call to plot() references the column names of the data frame in the wrong order.

☒ The input data is defined in such a way that it is not compatible with pickXY()

This should not be selected

☐ The wrong column names are passed to brushedPoints()