



CHANGE OVERVIEW

IVI VERSION 2.0

CONTENT

Version	4
Introduction	4
General information	4
POWERTRAINGROUP	4
LEVELS OF REGISTRATION	4
COMBINING FIELDS TEST RESULTS (N)OVC AND OTHER VEHICLE	4
LANGUAGES IN IVI	5
MANUFACTURER INFORMATION AND MULTISTAGE	5
Data structure changes	6
NAMESPACE	6
IVIREFERENCEID	6
CHANGED DEFINITION FOR NON NUMERIC FIELDS	6
INTEGER DEFINITION	6
MORE MANDATORY FIELDS IN IVI 2.0	7
USAGE OF TAGNAMES “RANGE VALUES AND MINIMUM/MAXIMUM VALUES”	7
DIMENSIONS MASS GROUP	8
Enumerations	9
GENERALCODEEcoINNOVATION	9
MECHANICALCOUPLINGCLASSCANBEFITTEDCODE	9
VIENNA COUNTRY CODE	10
ENERGYSOURCE	10
CHANGED THE ENUMERATION FROM COUNTRY CODES TO LANGUAGE CODES.	11
SPEEDCATEGORYSYMBOLCODE	11
TYPEAPPROVALTRANSPORTDANGEROUSGOODSCLASS	12
EUCOUNTRYCODE	12
Field information	13
ELECTRONICBRAKINGSYSTEM	13
MECHANICALCOUPLINGTECHNICALLYPERMISSIBLETOWABLEMASS	13
MECHANICALCOUPLINGVALUEDC	13
DESIGNATEDTYPEAPPROVALCOUNTRY	13
TYPE/VARIANT/VERSION	13
TYPEAPPROVALISSUEDATE	13
LOCATIONSTATUTORYPLATESCODE AND LOCATIONVIN	13
REPRESENTATIVE INFORMATION	14
CONFIGURATION OF DOORS	14
POSITIONOFSEATS	15
RIMSIZEINCLUDINGOFFSET	15
WORKINGPRINCIPLECODE AND ENGINECYCLECODE	16
TESTFAMILYIDENTIFIERSTABLE	16
MAXIMUMSPEED/DECLAREDMAXIMUMSPEED	16
VECTOGROUP	17
PUREELECTRICVEHICLEINDICATOR	17
TYREFITTEDPRODUCTIONINDICATOR / TYRECO2DETERMINATIONINDICATOR	18
EXHAUSTEMISSIONLEVEL AND EXHAUSTEMISSIONLATESTREGULATIONNUMBER	18
INTERCONNECTIONWITHPOWEREDAXLES	18
MAXIMUMAUTHORISEDDIMENSIONSDEROGATIONINDICATOR	19
VEHICLESUBGROUPCODE	19
CONSOLIDATEDMAXIMUMNETPOWERELECTRICENGINE	19
NUMBEROFDOORSREAR	19

AXLEGROUPMEMBERTABLE	19
TYRETYPE INFORMATION	19
ERRORS IN TAGNAMES	20
PERMISSIBLE HEIGHT	20
Trailer masses.....	21
MechanicalCoupling	22
MECHANICALCOUPLINGPARTSTABLE.....	22
MECHANICALCOUPLINGCANBEFITTEDTABLE	22
TECHNICALLYPERMISSIBLEMAXIMUMSTATICVERTICALMASSCOUPLINGPOINT	23
Euro 7 changes	24
47. EXHAUSTEMISSIONLEVEL	24
48.3 OBM TESTFAMILY.....	24
48.3 IMPLEMENTING ACTS	24
IVI Contentcheck Module (ICM)	25
Signing (minimum) requirements - conclusion	25

VERSION

Versionnumber	Date	Remark
1.0	2026-01-18	First consolidated version.

INTRODUCTION

With effect from 5th July 2026 the eCoC (IVI 2.0) will become mandatory for the framework directive (EU) 2018/858 vehicle categories. It's important to note that the new IVI version and guideline related to the IVI 2.0 also apply to the framework directives (EU)167/2013 and 168/2013 vehicle categories.

This document contains the changes that have been discussed within the Ereg Topic Group XII. Other documents containing additional information can be found on the eCoC website:

<https://ecoc.eucaris.net/> under the Documentation menu item.

The document relates to the IVI version 2.0 of December 18, 2025.

```
<xs:annotation>
  <xs:documentation>Message: Initial Vehicle Information</xs:documentation>
  <xs:documentation>Version: 2.0</xs:documentation>
  <xs:documentation>Generated: 2025-12-18 12:00</xs:documentation>
</xs:annotation>
```

GENERAL INFORMATION

POWERTRAINGROUP

The powertrain level, which was added in a previous draft version, has been removed. Consolidated power fields have moved to the CoC DataGroup. No vehicles with several powertrains exist.

LEVELS OF REGISTRATION

Registration of groups on different levels has to be avoided as the handling of the information and checking against the type approvals will make implementation too complex and almost impossible. Er is tijdens de overleggen binnen de topic Group discussie geweest over het vastleggen van bijvoorbeeld emissietest gegevens op zowel voertuig motor als brandstofniveau.

However, after discussion, this turned out to be too complex and not really necessary. Agreements have been made about specifying values in the case of different types of vehicles, such as hybrid, plug-in hybrid, fully electric, etc. These agreements are laid down in the document: eCoC2IVI manual.docx. See the eCoC website under Documentation.

COMBINING FIELDS TEST RESULTS (N)OVC AND OTHER VEHICLE

Some fields are either for (N)OVC or other vehicles in the IVI message. For instance charge sustaining only for plug-in hybrid (OVC) or Co2combined only for NOVC vehicles. Field will not be combined to one tag. Main reason is that if these fields should be combined the definition is only clear when using other information in the IVI message. The tag itself does not define the content anymore.

Having the fields separated is also in line with the legislation. If necessary the ICM can check the correct usage of the fields.

LANGUAGES IN IVI

Only the general remarks fields will be defined as multi lingual. Other free text fields will be defined without an language option. In general the CoC, according to the regulation, has to be published in one of the EU languages. Only for the fields mentioned below more than one language is optional:

- ✓ Remarks
- ✓ AdditionalInformation
- ✓ Exemptions
- ✓ Comments

MANUFACTURER INFORMATION AND MULTISTAGE

Removed from the RoleTable and RoleGroup, multistage information has been simplified. This implies that ManufacturerStageNumber is a mandatory field also for non-multistage vehicles.

ManufacturerTable			
ManufacturerGroup			
ManufacturerStageNumber	1	2	3
ManufacturerName	First stage manufacturer name	Second stage manufacturer name	Third stage manufacturer name
ManufacturerAdressLine1	First stage address information	Second stage address information	Third stage address information
ManufacturerAdressLine2	First stage address information	Second stage address information	Third stage address information
ManufacturerAdressLine3	First stage address information	Second stage address information	Third stage address information
ManufacturerPlaceOfResidence	First stage address information place	Second stage address information place	Third stage address information place
ManufacturerCountryOfResidence	First stage address information country	Second stage address information country	Third stage address information country
PreviousStageTypeApprovalNumber		Type approval number previous stage	Type approval number previous stage
PreviousStageType		Type previous stage	Type previous stage
PreviousStageVariant		Variant previous stage	Variant previous stage
PreviousStageVersion		Version previous stage	Version previous stage

DATA STRUCTURE CHANGES

NAMESPACE

A namespace has been added to de XSD scheme.

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:sig="http://www.w3.org/2000/09/xmldsig#"
xmlns="http://eu.ereg.initialvehicleinformation.v2" targetNamespace="http://eu.ereg.initialvehicleinformation.v2" elementFormDefault="qualified">
```

IVIREFERENCEID

Additional check on the IVIReferenceId to make sure that a GUID UUID version 4 is being used. The min/maxlength has been removed, as this is covered by the new pattern check:

```
<xs:simpleType name="IviReferenceId">
  <xs:restriction base="xs:string">
    <xs:pattern value="[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-4[0-9a-fA-F]{3}-[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}" />
  </xs:restriction>
</xs:simpleType>
```

CHANGED DEFINITION FOR NON NUMERIC FIELDS

Some fields have been changed from numeric (NonnegativeInteger of PositiveInteger) to string field. As these fields are not used as numeric. This has no functional effect on the eCoC xml files.

<xs:simpleType name="EnergySourceCode"> <xs:restriction base="xs:nonNegativeInteger"> <xs:totalDigits value="2"/> </xs:restriction> </xs:simpleType>	<xs:simpleType name="EnergySourceCode"> <xs:restriction base="xs:string"> <xs:maxLength value="2"/> </xs:restriction> </xs:simpleType>
<xs:restriction base="xs:nonNegativeInteger"> <xs:totalDigits value="3"/> <xs:minInclusive value="0"/> <xs:maxInclusive value="279"/> </xs:restriction>	<xs:simpleType name="LoadCapacityIndex"> <xs:restriction base="xs:int"> <xs:minInclusive value="0"/> <xs:maxInclusive value="279"/> </xs:restriction> </xs:simpleType>
s:simpleType name="TyrePlyRatingNumber"> <xs:restriction base="xs:nonNegativeInteger"> </xs:restriction> </s:simpleType>	<xs:simpleType name="TyrePlyRatingNumber"> <xs:restriction base="xs:string"> <xs:maxLength value="2"/> </xs:restriction> </xs:simpleType>
<xs:simpleType name="ColourCode"> <xs:restriction base="xs:positiveInteger"> </xs:restriction> </xs:simpleType>	<xs:simpleType name="ColourCode"> <xs:restriction base="xs:string"> <xs:totalDigits value="2"/> </xs:restriction> </xs:simpleType>

INTEGER DEFINITION

Due to remarks to be able to use generic tools to be able to use the XSD scheme in software generation tooling the integer definition has been changed. This has no functional effect on the eCoC xml files.

<xs:simpleType name="Integer2"> <xs:restriction base="xs:nonNegativeInteger"> <xs:totalDigits value="2"/> </xs:restriction> </xs:simpleType>	<xs:simpleType name="Integer2"> <xs:restriction base="xs:short"> <xs:minInclusive value="0"/> <xs:maxInclusive value="99"/> </xs:restriction> </xs:simpleType>
<xs:simpleType name="Integer3"> <xs:restriction base="xs:nonNegativeInteger"> <xs:totalDigits value="3"/> </xs:restriction> </xs:simpleType>	<xs:simpleType name="Integer3"> <xs:restriction base="xs:short"> <xs:minInclusive value="0"/> <xs:maxInclusive value="999"/> </xs:restriction> </xs:simpleType>

	</xs:simpleType>
<xs:simpleType name="Integer3"> <xs:restriction base="xs:nonNegativeInteger"> <xs:totalDigits value="4"/> </xs:restriction> </xs:simpleType>	<xs:simpleType name="Integer4"> <xs:restriction base="xs:short"> <xs:minInclusive value="0"/> <xs:maxInclusive value="9999"/> </xs:restriction> </xs:simpleType>
<xs:simpleType name="Integer3"> <xs:restriction base="xs:nonNegativeInteger"> <xs:totalDigits value="5"/> </xs:restriction> </xs:simpleType>	<xs:simpleType name="Integer5"> <xs:restriction base="xs:int"> <xs:minInclusive value="0"/> <xs:maxInclusive value="99999"/> </xs:restriction> </xs:simpleType>
<xs:simpleType name="Integer3"> <xs:restriction base="xs:nonNegativeInteger"> <xs:totalDigits value="6"/> </xs:restriction> </xs:simpleType>	<xs:simpleType name="Integer6"> <xs:restriction base="xs:int"> <xs:minInclusive value="0"/> <xs:maxInclusive value="999999"/> </xs:restriction> </xs:simpleType>

MORE MANDATORY FIELDS IN IVI 2.0

More fields have become mandatory in this version. The required fields can be recognized by the absence of minOccurs="0" in the XSD. In addition, it is important to indicate that the fields that are required within a group are in principle only mandatory if the group is actually present.

USAGE OF TAGNAMES "RANGE VALUES AND MINIMUM/MAXIMUM VALUES"

Added to Guideline document version 0.6

Example:

AxleSpacing

AxleSpacingAdjustableMin

AxleSpacingAdjustableMax

For the range values for masses Adjustable is not the correct naming, this has been changed to :
"Variable" -> example: MassInRunningOrderVariableMin

DIMENSIONS MASS GROUP

Has been divided into a DimensionGroup and MassGroup.

```
<xs:complexType name="DimensionGroup">
  <xs:all>
    <xs:element name="Wheelbase" minOccurs="0" type="Integer5"/>
    <xs:element name="WheelbaseAdjustableMin" minOccurs="0" type="Integer5"/>
    <xs:element name="WheelbaseAdjustableMax" minOccurs="0" type="Integer5"/>
    <xs:element name="WheelbaseSideCar" minOccurs="0" type="Integer5"/>
    <xs:element name="WheelBaseGroundRatio" minOccurs="0" type="Decimal32"/>
    <xs:element name="Length" minOccurs="0" type="Integer5"/>
    <xs:element name="LengthAdjustableMin" minOccurs="0" type="Integer5"/>
    <xs:element name="LengthAdjustableMax" minOccurs="0" type="Integer5"/>
    <xs:element name="Width" minOccurs="0" type="Integer4"/>
    <xs:element name="WidthAdjustableMin" minOccurs="0" type="Integer4"/>
    <xs:element name="WidthAdjustableMax" minOccurs="0" type="Integer4"/>
    <xs:element name="Height" minOccurs="0" type="Integer4"/>
    <xs:element name="HeightAdjustableMin" minOccurs="0" type="Integer4"/>
    <xs:element name="HeightAdjustableMax" minOccurs="0" type="Integer4"/>
    <xs:element name="SeatingHeight" minOccurs="0" type="Integer4"/>
    <xs:element name="RearOverhang" minOccurs="0" type="Integer4"/>
    <xs:element name="RearOverhangAdjustableMin" minOccurs="0" type="Integer4"/>
    <xs:element name="RearOverhangAdjustableMax" minOccurs="0" type="Integer4"/>
    <xs:element name="MaximumPermissibleRearOverhang" minOccurs="0" type="Integer4"/>
    <xs:element name="MaximumPermissibleLength" minOccurs="0" type="Integer5"/>
    <xs:element name="MaximumPermissibleLengthMin" minOccurs="0" type="Integer5"/>
    <xs:element name="MaximumPermissibleLengthMax" minOccurs="0" type="Integer5"/>
    <xs:element name="MaximumPermissibleWidth" minOccurs="0" type="Integer4"/>
    <xs:element name="MaximumPermissibleWidthMin" minOccurs="0" type="Integer4"/>
    <xs:element name="MaximumPermissibleWidthMax" minOccurs="0" type="Integer4"/>
    <xs:element name="MaximumPermissibleHeight" minOccurs="0" type="Integer4"/>
    <xs:element name="MaximumPermissibleHeightMin" minOccurs="0" type="Integer4"/>
    <xs:element name="MaximumPermissibleHeightMax" minOccurs="0" type="Integer4"/>
    <xs:element name="LengthLoadingArea" minOccurs="0" type="Integer5"/>
    <xs:element name="LengthLoadingAreaAdjustableMin" minOccurs="0" type="Integer5"/>
    <xs:element name="LengthLoadingAreaAdjustableMax" minOccurs="0" type="Integer5"/>
    <xs:element name="ElongatedCabIndicator" minOccurs="0" type="Indicator"/>
    <xs:element name="AerodynamicDeviceEquipped" minOccurs="0" type="AerodynamicDeviceEquippedCode"/>
    <xs:element name="MaximumAuthorisedDimensionsDerogationIndicator" minOccurs="0" type="Indicator"/>
  </xs:all>
</xs:complexType>
<xs:complexType name="MassGroup">
  <xs:all>
    <xs:element name="MassInRunningOrder" minOccurs="0" type="Integer6"/>
    <xs:element name="MassInRunningOrderVariableMin" minOccurs="0" type="Integer6"/>
    <xs:element name="MassInRunningOrderVariableMax" minOccurs="0" type="Integer6"/>
    <xs:element name="ActualMass" minOccurs="0" type="Integer6"/>
    <xs:element name="MassInRunningOrderIncomplete" minOccurs="0" type="Integer6"/>
    <xs:element name="TechnicallyPermissibleMaximumLadenMass" minOccurs="0" type="Integer6"/>
    <xs:element name="TechnicallyPermissibleMaximumLadenMassVariableMin" minOccurs="0" type="Integer6"/>
    <xs:element name="TechnicallyPermissibleMaximumLadenMassVariableMax" minOccurs="0" type="Integer6"/>
    <xs:element name="MinimumMassCompleted" minOccurs="0" type="Integer6"/>
    <xs:element name="AdditionalMassAlternativePropulsion" minOccurs="0" type="Integer5"/>
    <xs:element name="AdditionalMassDueToBatteries" minOccurs="0" type="Integer4"/>
    <xs:element name="BallastMassTotal" minOccurs="0" type="Integer6"/>
    <xs:element name="ThreePointLiftingMechanismMaximumTowableMass" minOccurs="0" type="Integer6"/>
    <xs:element name="MaximumStaticVerticalMassCouplingPointTable" minOccurs="0" type="MaximumStaticVerticalMassCouplingPointTable"/>
  </xs:all>
</xs:complexType>
```

ENUMERATIONS

GENERALCODEECOINNOVATION

Enumeration added: 28 / 29 / 32 / 33 / 35 / 37 / 38

List of eco-innovations approved under WLTP					
Passenger cars					
Eco-innovation code	Commission Implementing Decision (link)	Technology	Amendments	Powertrains (other than ICEV)	Fuels (other than diesel and gasoline)
28 ¹	CID (EU) 2019/1119	LED lights	CID (EU) 2020/1714	NOVC- HEV	Alternative fuels
37	CID (EU) 2020/174	Alternator	CID (EU) 2021/136	-	Alternative fuels
29	CID (EU) 2020/1167	48V motor generator with DC/DC converter	CID (EU) 2021/488	NOVC- HEV	Alternative fuels
32	CID (EU) 2020/1232	12V motor generator	CID (EU) 2022/252	NOVC- HEV	Alternative fuels
33	CID (EU) 2022/716	Smart diesel fuel heater	-	NOVC-HEV	Only diesel
Light Commercial Vehicles					
Eco-innovation code	Commission Implementing Decision (link)	Technology	Amendments	Powertrains (other than ICEV)	Fuels (other than diesel and gasoline)
29	CID (EU) 2020/174	Alternator	CID (EU) 2021/488	-	Alternative fuels
32	CID (EU) 2020/1167	48V motor generator with DC/DC converter	CID (EU) 2021/488	NOVC- HEV	Alternative fuels
33	CID (EU) 2020/1232	12V motor generator	CID (EU) 2022/252	NOVC- HEV	Alternative fuels
35	CID (EU) 2020/1339	LED lights	CID (EU) 2020/1714	NOVC- HEV	Alternative fuels
38	CID (EU) 2022/716	Smart diesel fuel heater	CID (EU) 2021/136	NOVC-HEV	Only diesel

MECHANICALCOUPLINGCLASSCANBEFITTEDCODE

Enumeration added:

A

A50-1	C50-7	J	S
A50-2	C50-X	K	T
A50-3	D	K1	W
A50-4	D50-A	K2	
A50-5	D50-B	K3	
A50-X	D50-C	K4	
B	D50-D	KA1	
B50-X	D50-X	KA2	
C	E	KA3	
C50-1	F	L	
C50-2	G	L1	
C50-3	G50	L2	
C50-4	G50-X	L3	
C50-5	H	L4	
C50-6	H50-X	L5	

VIENNACOUNTRYCODE

Enumeration restricted to official Vienna codes:

A	CR	GCA	LT	PL	SK	WL
AL	CV	GE	LV	PNG	SLO	WS
AND	CY	GH	M	PS	SME	WV
AM	CZ	GR	MA	PY	SN	YV
AUS	D	GUY	MAL	RA	SRB	Z
AZ	DK	H	MC	RC	SY	ZA
B	DOM	HK	MD	RCA	SYR	ZW
BD	DZ	HKJ	MEX	RCB	T	
BDS	E	HR	MGL	RCH	TG	
BG	EAK	I	MNE	RH	TJ	
BH	EAT	IL	MS	RI	TM	
BIH	EAU	IND	MW	RL	TN	
BR	EC	IR	MYA	RM	TR	
BRN	EG	IRL	N	RMM	TT	
BRU	EST	IRQ	NA	RN	UA	
BS	F	IS	NAM	RO	UAE	
BW	FIN	J	NIC	ROK	UK	
BY	FJI	JA	NL	ROU	USA	
C	FL	KH	NZ	RP	UZ	
CDN	FO	KG	OM	RSM	V	
CGO	GBA	KWT	P	RUS	VN	
CH	GBG	KZ	PA	RWA	WAG	
CI	GBJ	L	PK	S	WAL	
CL	GBM	LAO	PAL	SD	WAN	
CO	GBZ	LS	PE	SGP	WG	

ENERGYSOURCE

Limit the number of EnergySources to the list as mention below:

- 10 Petrol
- 11 Petrol E5
- 12 Petrol E10
- 15 Ethanol
- 16 Ethanol E85
- 19 Mixture
- 20 Diesel
- 21 Biodiesel
- 22 ED95
- 30 LPG
- 40 CNG
- 44 Biomethane
- 50 Hydrogen

55 H2NG

60 LNG

90 Other

91 Compressed air

95 Electricity

Add 95 Electricity as an energy source. Keep the numbering of existing FuelCodes in line with the current numbering.

CHANGED THE ENUMERATION FROM COUNTRY CODES TO LANGUAGE CODES.

Restricted to the official EU languages:

[Languages, multilingualism, language rules | European Union \(europa.eu\)](#) using the ISO-639-1 codes:

639-1	639-2	639-3	EU Languages
bg	bul	bul	Bulgarian
cs	cze/ces	ces	Czech
da	dan	dan	Danish
de	ger/deu	deu	German
el	gre/ell	ell	Greek
en	eng	eng	English
es	spa	spa	Spanish
et	est	est	Estonian
fi	fin	fin	Finnish
fr	fre/fra	fra	French
ga	gle	gle	Irish
hr	scr/hrv	hrv	Croatian
hu	hun	hun	Hungarian
it	ita	ita	Italian
lt	lit	lit	Lithuanian
lv	lav	lav	Latvian
mt	mlt	mlt	Maltese
nl	dut/nld	nld	Dutch
pl	pol	pol	Polish
pt	por	por	Portuguese
ro	rum/ron	ron	Romanian
sk	slo/slk	slk	Slovak
sl	slv	slv	Slovenian
sv	swe	swe	Swedish

SPEEDCATEGORYSYMBOLCODE

Added enumeration:

A1	D	N	Z
A2	E	P	
A3	F	Q	
A4	G	R	
A5	H	S	
A6	I	T	
A7	J	U	
A8	K	V	
B	L	W	
C	M	Y	

TYPEAPPROVALTRANSPORTDANGEROUSGOODSCLASS

Add enumeration for this field: TypeApprovalTransportDangerousGoodsClassCode

Text-10

EX/II

EX/III

AT

FL

MEMU

The enumeration value "OX" has been removed.

EU COUNTRY CODE

Norway, Switzerland, United Kingdom and Iceland added:

CH Switzerland

NO Norway

IS Iceland

UK United Kingdom

LI Liechtenstein

FIELD INFORMATION

ELECTRONICBRAKINGSYSTEM

Moved to the CoCDataGroup:

```
<xs:element name="ElectronicBrakingSystem" minOccurs="0"
type="ElectronicBrakingSystemCode"/>
```

MECHANICALCOUPLINGTECHNICALLYPERMISSIBLETOWABLEMASS

According to 2015/504 the field has to be stated in Tonnes (T).
Change type from Integer 6 to Decimal 5.2.

MECHANICALCOUPLINGVALUEDC

Has been added after receiving comments from DAF.

DESIGNATEDTYPEAPPROVALCOUNTRY

A new field has been added to the header and set to mandatory in order to be able to redirect eCoC's to the relevant Type approval authority easily. Without having to use the first part before the * of the TypeApprovalNumber. If this changes in future no change is needed in the software.

TYPE/VARIANT/VERSION

No pattern check will be added to limit the usage of other characters than A-Z and 0-9.
The field Type will be limited to 15 positions. No check on case sensitive check for Variant of Version.

TYPEAPPROVALISSUEDATE

Remove "RevisionDateVersion". The TypeApprovalIssueDate will be used to indicate the issue date of the document. This date doesn't change in case of revisions or corrections. It only changes in case of extensions. First set at extension 00 and subsequently at extensions 01 etc.

LOCATIONSTATUTORYPLATESCODE AND LOCATIONVIN

The fields will be replaced by a new Table.

LocationMarkingsTable

LocationMarkingsGroup

LocationMarkingsSubject

LocationMarkingsVehiclePart

LocationMarkingsVehiclePartSide

LocationMarkingsVehiclePartSideSection

LocationOfMarkingsSubjectCode

VIN = LocationVIN

STAT = LocationStatutoryPlatesCode

LocationOfMarkingsVehiclePartCode

ENGCT = Engine compartment

PASCT = Passenger compartment

LUGCT = Luggage compartment

INSPL = Instrument panel

DRAWB = Drawbar

CHASS = Chassis

APILR = A-pillar

BPILR = B-pillar

CPILR = C-pillar

DPILR = D-pillar

LocationOfMarkingsVehiclePartSideCode

FRONTSIDE = Frontside

LEFTSIDE = Leftside

RIGHT = Rightside

BACK = Backside

LocationOfMarkingsVehiclePartSideSectionCode

LEFT = Left

MIDDLE = Middle

RIGHT = Right

FRONT = Front

BACK = Back

LocationStatutoryPlates23Wheel and LocationVin23Wheel will not be added to this table in accordance with the definition in the 168/2013. The new table can be used for 2018/858 and 167/2013.

REPRESENTATIVE INFORMATION

Removed from the RoleTable and RoleGroup and stated in separate Group. Not added in a Table, as in all cases there's only one EU representative. If a representative is mentioned the EURepresentativeName, EURepresentativeAdressLine1, EURepresentativePlaceOfResidence and EURepresentativeCountryOfResidence are mandatory.

EURepresentativeGroup

EURepresentativeName

EURepresentativeAdressLine1

EURepresentativeAdressLine2

EURepresentativeAdressLine2

EURepresentativePlaceOfResidence

EURepresentativeCountryOfResidence

CONFIGURATION OF DOORS

Replace Text-40 field by a new definition.

ConfigurationOfDoorsGroup

NumberOfDoorsFront

NumberOfDoorsLeft

NumberOfDoorsRight

NumberOfDoorsBack

Example:

	NumberOfDoorsFront	2
--	--------------------	---

	NumberOfDoorsLeft	4
	NumberOfDoorsRight	3
	NumberOfDoorsBack	1

Please note: as the attribute “Number of doors” is still part of the CoC this will also be in the IVI file as NumberOfDoors in the GeneralConstructionGroup.

POSITIONOFSEATS

For the CoC data this element only applies to the 168/2013 vehicle categories. The proposal is not in line with the regulation. The proposed setup will be added to the regulation changes as proposed to the TCMV.

Until the regulation has been changed no changes will be made for this field.

Regulation 901/2014

Bodywork

6.20.2.1. Door configuration and number of doors^(3g) (i) (j):

6.16.1. Number of seating positions:

6.16.1.1. Location and arrangement^{(3g)(k)}:

^(k) Indicate the position by the following codes:

- rx: row number
- R: right side of the vehicle
- C: centre of the vehicle
- L: left side of the vehicle

Example for a vehicle with a first row with 2 front seating positions, 1 right, 1 left and a second row with 1 rear seating positions, 1 centre:

r1: 1R,1L r2: 1C

RIMSIZEINCLUDINGOFFSET

RimSize

The size designation of wheels and rims shown by numbers and letters in following order as marked on the wheel: Nominal rim diameter, Rim type (optional), Nominal rim width, Rim profile, Flange height (optional)

String-20

RimOffset

Offset, inset or outset as marked on the wheel, using the codes of ISO 3911:2021

Decimal value, can be a negative value.

Decimal 6.3 (-999.999)

WORKINGPRINCIPLECODE AND ENGINECYCLECODE

Change working principle codes to a combination of workingprinciple and enginecycle instead of repeating the engine cycle within the working principle.

WorkingPrincipleCode

Change enumeration to:

CA	Compressed air
ECI	External compression ignition
ECP	External positive ignition
ICI	Internal compression ignition
IPI	Internal positive ignition
TB	Turbine

WorkingPrincipleCode	WorkingPrinciple	CombustionCycle	FuelType
C2 compression ignition, two stroke	ICI	internal compression ignition	2ST
C4 compression ignition, four stroke	ICI	internal compression ignition	4ST
CA compressed air	CA	compressed air	
CI compression ignition	ICI	internal compression ignition	
DF dualfuel			
E2 positive ignition, two stroke	IPI	internal positive ignition	2ST
E4 positive ignition, four stroke	IPI	internal positive ignition	4ST
EC external combustion engine compression ignition	ECI	external compression ignition	
EE electric engine			
EF external combustion engine			
EP external combustion engine positive ignition	ECP	external positive ignition	
ER positive ignition, rotary	IPI	internal positive ignition	ROT
IC internal combustion engine compression ignition	ICI	internal compression ignition	
IE internal combustion engine positive ignition	IPI	internal positive ignition	
PI positive ignition	IPI	internal positive ignition	
TB turbine	TB	turbine	
CombustionCycle			
2ST = Two stroke			
4ST = Four stroke			
ROT = Rotary			
OTH = Other			

TESTFAMILYIDENTIFIERSTABLE

The TestFamilyIdentifiersTable has been moved to

CoCDataGroup/EnergyConvertorTable/EnergyConvertorGroup/EnergySourceTable

Mainly because ATCT Family can occur on an EnergySource level. In case of multiple fuels the FamilyIdentifiers information has to be duplicated.

MAXIMUMSPEED/DECLAREDMAXIMUMSPEED

Have moved to CoCDataGroup.

VECTOGROUP

Keep the Vecto related fields together in one VectoGroup:

CoCDataGroup

VectoGroup

CryptographicHashManufacturerRecord

ZeroEmissionHeavyDutyIndicator

VocationalVehicleIndicator

CryptographicHashCustomerInformationFile

AveragePayload

AverageOccupancy

VehicleGroup

VehicleSubgroup

SpecificCo2EmissionsMass

SpecificCo2EmissionsPerson

CryptographicHashVehicleFile

CargoVolume

VolumeOrientationIndicator

EfficiencyRatioKilometer

EfficiencyRatioTonKilometer

EfficiencyRatioM3Kilometer

Note: While fuel type (e.g., diesel, LNG, electricity) influences the engine map and fuel properties used in the simulation, VECTO does not calculate CO₂ emissions per fuel type in isolation.

Also the O category vehicles (trailers) are included in the VECTO (Vehicle Energy Consumption Calculation Tool) framework under EU regulations.

This is why it has been decided to move the Co2 Vecto fields from EnergySource to VectoGroup:

SpecificCo2EmissionsMass

SpecificCo2EmissionsPerson

PUREELECTRICVEHICLEINDICATOR

1. Question is if the field PureElectricVehicleIndicator according to point 23 is only applicable for hybrid vehicles that might or might not have a pure electric mode, see below for reference:

After re-evaluating the facts regarding the completion of field 23 in the CoC, I would like to inform you today about the changed procedure in relation to the type records and the IVI-CoC data.

Until now, the fields for the "pure electric drive" could also be filled with Yes (type data) or Y (IVI-CoC) in the case of **avehicle that is exclusively electrically driven** . According to a new perspective, this is not correct: "A pure electric vehicle does not have a selectable mode, it always drives purely electrically."

The points mentioned in the subject only refer to hybrid vehicles, so they are not to be used for electric vehicles!

- Use for **pure electric vehicles and combustion engines**:
Leave the field blank in the type data - in the IVI-CoC, the "PureElectricVehIndicator" element is omitted.
- Use for **hybrid vehicles** (where it is always to be used): Type data CoC Pt. 23 – Description sheet Pt.3.4.3.1.1:
Type data:
Yes - switchable to purely electric
No - not switchable, can't drive purely electrically

IVI-CoC: „PureElectricVehIndicator“
Y - switchable to purely electric
N - not switchable, cannot drive purely electrically

2. Or does this field apply to fully electric vehicles only. So Yes only applies to vehicles with EnergySourceCode 95 for Electricity only.

Decision of the Forum is that the field has to be defined as the second option. If a switch mode (HybridElectricOperatingModeSwitchIndicator) is relevant information, a new field has to be added to the legislation and the IVI message.

TYREFITTEDPRODUCTIONINDICATOR / TYRECO2DETERMINATIONINDICATOR

Relates to Item 35. This only states information on the fitted tyre/wheel combination which is used for Co2 determination. If TyreFittedProductionIndicator = Y this also indicates that it has been used for CO2Determination. The TyreCo2DeterminationIndicator has been removed.

EXHAUSTEMISSIONLEVEL AND EXHAUSTEMISSIONLATESTREGULATIONNUMBER

Have been moved to the CoCDataGroup. Value not different on fuel/energysource level.

INTERCONNECTIONWITHPOWEREDAXLES

In the current version this is a text field. Suggestion is to change the free text to a standardized list of codes (enumeration).

Current version 1.x

InterconnectionWithPoweredAxleTable

InterconnectionWithPoweredAxleGroup

InterconnectionWithPoweredAxleNumber

InterconnectionPoweredAxles

New version 2.0

InterconnectionWithPoweredAxleTable

InterconnectionWithPoweredAxleGroup

InterconnectionWithPoweredAxleNumber

InterconnectionWithPoweredAxleConnection type

= "InterconnectionWithPoweredAxleCode"

Possible values InterconnectionWithPoweredAxleCode:

TRA	Transfer box
ELE	Electronic
SHA	Shaft

MAXIMUMAUTHORISEDDIMENSIONSDEROGATIONINDICATOR

This field was removed from the previous version of IVI 2.0 but has been re-instated:

In accordance with the second subparagraph of Article 6(5) of Regulation (EU) 2018/858, an EU type-approval may be granted for vehicles exceeding the maximum authorised dimensions set out in point 1.1 of Sections C, D and E of Part 2 of Annex XIII to this Regulation, in which case the remark 'maximum authorised dimensions derogation' shall be included in point 52 of the type-approval certificate and the certificate of conformity.

VEHICLESUBGROUPCODE

The enumeration has been extended according to the recent regulation.

CONSOLIDATEDMAXIMUMNETPOWERELECTRICENGINE

De tag has been renamed to make it more consistent with ConsolidatedMaximum30MinutesPower
<xs:element name="ConsolidatedMaximumNetPowerElectric" minOccurs="0" type="Decimal62"/>

NUMBEROFDOORSREAR

De tag NumberOfDoorsRear has been renamed to NumberOfDoorsBack.

AXLEGROUPMEMBERTABLE

Corrected : not mandatory anymore.

TYRETYPE INFORMATION

In the previous IVI version 2.0 the TyreType information contains combinations of TyreTypes as separate codes.

For instance XLATMS being a combination of:

XL = Extra Load – The tire is reinforced to carry more weight than a standard tire of the same size.

AT = All Terrain

M+S = Mud and Snow – Indicates basic suitability for muddy and snowy conditions

A new table is added to be able to combine different TyreTypes without having to add enumerations for different combinations to the list.

```
<xs:complexType name="TyreTypeTable">
  <xs:sequence>
    <xs:element name="TyreTypeGroup" maxOccurs="unbounded" type="TyreTypeGroup"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="TyreTypeGroup">
  <xs:all>
    <xs:element name="TyreType" minOccurs="0" type="TyreTypeCode"/>
  </xs:all>
</xs:complexType>
```

With the following enumerations mentioned:

```
<xs:simpleType name="TyreTypeCode">
  <xs:restriction base="xs:string">
    <xs:maxLength value="7"/>
    <xs:enumeration value="AT"/>
    <xs:enumeration value="AL"/>
    <xs:enumeration value="AS"/>
    <xs:enumeration value="HLC"/>
    <xs:enumeration value="MC"/>
    <xs:enumeration value="MS"/>
    <xs:enumeration value="RF"/>
    <xs:enumeration value="S"/>
    <xs:enumeration value="XL"/>
    <xs:enumeration value="MST"/>
    <xs:enumeration value="3PMSF"/>
    <xs:enumeration value="TGS"/>
    <xs:enumeration value="FAX"/>
  </xs:restriction>
</xs:simpleType>
```

Also new code has been added: HLC = High load capacity

ERRORS IN TAGNAMES

Name:	Changed to:
ElongatedCabineIndicator	ElongatedCabIndicator
AerisollIndicator	AerosollIndicator
ProtectionPenetratingObjectsForestryIndicator	ProtectionPenetratingObjectsForestryIndicator
ProtectionPenetratingObjectsNonForestryIndicator	ProtectionPenetratingObjectsNonForestryIndicator
FallingObjectProtectectiveStructureForestryIndicator	FallingObjectsProtectiveStructureForestryIndicator
FallingObjectProtectiveStructureNonForestryIndicator	FallingObjectProtectiveStructureNonForestryIndicator
AerodynamicDeviceEquiped	AerodynamicDeviceEquipped
AerodynamicDeviceEquipedCode	AerodynamicDeviceEquippedCode
MechanicalCouplingNumberOfTrackTrainCouplingPoint	MechanicalCouplingNumberOfTrackTrainCouplingPoint
CabineCategoryCode	CabCategoryCode
SoundLevelDriverPerceivedOpenCabine	SoundLevelDriverPerceivedOpenCab
SoundLevelDriverPerceivedClosedCabine	SoundLevelDriverPerceivedClosedCab
WhscHc	WhscThc
WhtcHc	WhtcThc

PERMISSIBLE HEIGHT

For agricultural vehicles a range for height of incomplete vehicles has been added:

MaximumPermissibleHeightMin

MaximumPermissibleHeightMax

TRAILER MASSES

Usage of the table structure for all vehicle categories, avoiding duplication of information.

The key-items are braking-system, bodywork type of the trailer and the maximum masses.

Benefits

- for all vehicle categories one way to handle this mass information and setup for the eCoC;
- for all vehicle categories one way of using the information for the registration processes;
- can be easily extended by extending the braking type code without having to add new fields

Disadvantages

- more complex to initially setup for the M,N and O categories

Example:

Masses

13. Mass in running order/13.2 Actual mass of the vehicle : 2175 / 2184 kg

16. Technically permissible maximum masses

16.1 Technically permissible maximum laden mass : 2640 kg

16.2 Technically permissible mass on each axle: No.1/No.2/No.3 : 1380 / 1470 / NA kg

16.4 Technically permissible maximum mass of the combination : 3390 kg

18. Technically permissible maximum towable mass in case of

18.1 Drawbar trailer	18.3 Centre-axle trailer	18.4 Unbraked trailer
750 kg	750 kg	750 kg

19. Technically permissible maximum static vertical mass at the coupling point : 75 kg

18.1 Drawbar trailer

```
<TowingBrakedTypeTrailTable>
  <TowingBrakedTypeTrailGroup>
    <BrakedTypeTrail>BRK</BrakedTypeTrail>
    <BodyworkTypeTable>
      <BodyworkTypeGroup>
        <BodyworkTypeTrailer>DB</BodyworkTypeTrailer>
        <TechnicallyPermissibleMaximumTowableMass>750</TechnicallyPermissibleMaximumTowableMass>
      </BodyworkTypeGroup>
    </BodyworkTypeTable>
  </TowingBrakedTypeTrailGroup>
</TowingBrakedTypeTrailTable>
```

18.3 Centre-axle trailer

```
<TowingBrakedTypeTrailGroup>
  <BrakedTypeTrail>BRK</BrakedTypeTrail>
  <BodyworkTypeTable>
    <BodyworkTypeGroup>
      <BodyworkTypeTrailer>DC</BodyworkTypeTrailer>
      <TechnicallyPermissibleMaximumTowableMass>750</TechnicallyPermissibleMaximumTowableMass>
    </BodyworkTypeGroup>
  </BodyworkTypeTable>
</TowingBrakedTypeTrailGroup>
```

18.4 Unbraked trailer

```
<TowingBrakedTypeTrailGroup>
  <BrakedTypeTrail>UNB</BrakedTypeTrail>
  <BodyworkTypeTable>
    <BodyworkTypeGroup>
      <TechnicallyPermissibleMaximumTowableMass>750</TechnicallyPermissibleMaximumTowableMass>
    </BodyworkTypeGroup>
  </BodyworkTypeTable>
</TowingBrakedTypeTrailGroup>
```

16.4 Technically permissible maximum mass of the combination

```
<TowingBrakedTypeTrailGroup>
  <BodyworkTypeTable>
    <BodyworkTypeGroup>
      <TechnicallyPermissibleMaximumCombinationMass>3390</TechnicallyPermissibleMaximumCombinationMass>
    </BodyworkTypeGroup>
  </BodyworkTypeTable>
</TowingBrakedTypeTrailGroup>
```

```
<MaximumStaticVerticalMassCouplingPointTable>
  <MaximumStaticVerticalMassCouplingPointGroup>
    <TechnicallyPermissibleMaximumStaticVerticalMassCouplingPoint>75</TechnicallyPermissibleMaximumStaticVerticalMassCouplingPoint>
  </MaximumStaticVerticalMassCouplingPointGroup>
</MaximumStaticVerticalMassCouplingPointTable>
```

BodyworkTypeTrailer - BodyworkTypeTrailerCode:

UND has been removed from enumeration. For agricultural vehicles a value is always applicable.
Also DF and DG have been removed, as these are not applicable here.

BrakedTypeTrail-BrakedTypeTrailCode :

UND has been removed from enumeration. For agricultural vehicles a value is always applicable.
Also CSB , PNH, IPD have been removed, as these are not applicable here.

MECHANICALCOUPLING

MECHANICALCOUPLINGPARTSTABLE

A mechanical coupling consists of several parts, where the different parts of the coupling can also have their own data. This can apply to the vehicle categories: M2, M3, N, O, T, C, R and S.



As requested the option to add information on parts of a mechanical coupling has been added tot the IVI structure:

```
<xs:complexType name="MechanicalCouplingPartsTable">
  <xs:sequence>
    <xs:element name="MechanicalCouplingPartsGroup" maxOccurs="unbounded" type="MechanicalCouplingPartsGroup"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="MechanicalCouplingPartsGroup">
  <xs:all>
    <xs:element name="MechanicalCouplingPartsTypeAccordingAppendixEU" minOccurs="0" type="Text120"/>
    <xs:element name="MechanicalCouplingPartsMake" minOccurs="0" type="Text52"/>
    <xs:element name="MechanicalCouplingPartsManufacturersTypeDesignation" minOccurs="0" type="Text40"/>
    <xs:element name="MechanicalCouplingPartsApprovalMark" minOccurs="0" type="Text80"/>
    <xs:element name="MechanicalCouplingPartsApprovalNumber" minOccurs="0" type="Text50"/>
    <xs:element name="MechanicalCouplingPartsValueD" minOccurs="0" type="Decimal62"/>
    <xs:element name="MechanicalCouplingPartsValueDc" minOccurs="0" type="Decimal62"/>
    <xs:element name="MechanicalCouplingPartsValueV" minOccurs="0" type="Decimal62"/>
    <xs:element name="MechanicalCouplingPartsValueS" minOccurs="0" type="Integer6"/>
    <xs:element name="MechanicalCouplingPartsValueU" minOccurs="0" type="Decimal62"/>
  </xs:all>
</xs:complexType>
```

MECHANICALCOUPLINGCANBEFITTEDTABLE

To make it possible to specify multiple couplings that can possibly be attached to a vehicle for incomplete vehicles with their own data, a table has been added and the fields
“MechanicalCouplingCanBeFittedType” en “MechanicalCouplingCanBeFittedClass” have been moved to “MechanicalCouplingCanBeFittedTable”.

```

<xs:complexType name="MechanicalCouplingCanBeFittedGroup">
  <xs:all>
    <xs:element name="MechanicalCouplingCanBeFittedType" minOccurs="0" type="Text80"/>
    <xs:element name="MechanicalCouplingCanBeFittedClass" minOccurs="0" type="MechanicalCouplingCanBeFittedClassCode"/>
    <xs:element name="MechanicalCouplingCanBeFittedValueD" minOccurs="0" type="Decimal62"/>
    <xs:element name="MechanicalCouplingCanBeFittedValueDc" minOccurs="0" type="Decimal62"/>
    <xs:element name="MechanicalCouplingCanBeFittedValueV" minOccurs="0" type="Decimal62"/>
    <xs:element name="MechanicalCouplingCanBeFittedValueS" minOccurs="0" type="Integer6"/>
    <xs:element name="MechanicalCouplingCanBeFittedValueU" minOccurs="0" type="Decimal62"/>
  </xs:all>
</xs:complexType>

```

TECHNICALLYPERMISSIBLEMAXIMUMSTATICVERTICALMASSCOUPLINGPOINT

The location of the vertical maximum static mass has been moved from the mechanical coupling table to its own table. As a result, the maximum static vertical mass can be defined as follows:

1. At vehicle level, when no coupling is installed, but towing maximum masses are available. For example, a passenger car that is delivered without a coupling device. The tag MechanicalCouplingNumberVerticalMass (which refers to specific MechanicalCouplingNumber) can be omitted.
2. At coupling level, by means of the MechanicalCouplingNumber as the identifier, which is also included in the mechanical coupling table. This allows the maximum static vertical mass to be linked to multiple attachment points on the vehicle. For example, when a vehicle has two coupling device options, such as a 50 mm ball coupling (75 kg) and a drawbar coupling (1,000 kg). The tag MechanicalCouplingNumberVerticalMass (which refers to specific MechanicalCouplingNumber) has to have a reference to a MechanicalCouplingNumber in the MechanicalCouplingTable.

The S-value of the coupling device itself remains in the MechanicalCouplingTable.

Article 2

Scope

This Regulation applies to motor vehicles of categories M₁, M₂, M₃, N₁, N₂ and N₃, as well as trailers of categories O₃ and O₄ as specified in Article 4 of Regulation (EU) 2018/858, including those designed and constructed in one or more stages, and to systems, components and separate technical units intended for such vehicles, and C₁, C₂ and C₃ class tyres, as specified in UN Regulation No 117 ⁽²³⁾, with the exception of ice grip tyres.

47. EXHAUST EMISSION LEVEL

The following enumerations have been added:

Euro 7 FL

Euro 7 FE

Euro 7 GL

Euro 7 GE

Euro 7 GS

Euro 7 GT

Euro 7 HL

Euro 7 HE

Euro 7 HS

Euro 7 HT

Euro 7 TL

Euro 7 TE

Euro 7 TS

Euro 7 TT

48.3 OBM TEST FAMILY

The OBM testfamily will be registered in TestFamilyIdentifiers table. Other testfamilies will be added as well for Euro 7 in future. This could also be the case for batteries and brakes (to be determined).

The paper format of the CoC also contains the OBM family identifier in entry 48.3. and might contain more identifiers that are not an approval number.

Extend enumeration for TestFamilyIdentifierCode with: OM

48.3 IMPLEMENTING ACTS

A new table has been added for registration of the implementing acts related to Euro 7. For instance, the main implementing act (MIA) can be added here, with a possibility to add other subject approvals as well.

```

<xs:complexType name="SubjectApprovalTable">
  <xs:sequence>
    <xs:element name="SubjectApprovalGroup" maxOccurs="unbounded" type="SubjectApprovalGroup"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="SubjectApprovalGroup">
  <xs:all>
    <xs:element name="SubjectApprovalCertificateNumber" type="Text80"/>
  </xs:all>
</xs:complexType>

```

IVI CONTENTCHECK MODULE (ICM)

The new version of the ICM will check if fields are relevant for a specific vehicle category. If not applicable the ICM will reject the IVI file.

For instance if a Colour is stated for the VehicleCategory M2, the file will be rejected.

Also if an indicator field is relevant for the VehicleCategory it has to be present with a Y or N.

For instance for M1 PureElectricVehicleIndicator is mentioned on the CoC, for Petrol vehicles the tag has to be present with value "N".

More information about the ICM and the checks can be found on the eCoC website under the menu item documentation.

SIGNING (MINIMUM) REQUIREMENTS - CONCLUSION

Manufacturers, in minimum, have to apply an **advanced electronic seal** to the IVI messages which can be made with a **non-qualified certificate**. Article 36 of regulation 910/2014 states the requirements for such a seal.

Manufacturers **can** (but are not required to) apply a **qualified electronic seal** which can be made with a **qualified certificate**.

This seal must be applied as of 5 July 2026

Having a valid code signing certificate issued by **trusted CA** and applying xmldsig will suffice to meet these requirements for submission of IVI messages.

X-ADES can be applied, as best practice; however this is not mandatory.