

```
In [3]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import warnings
warnings.filterwarnings("ignore")
```

```
In [4]: data=pd.read_csv("/home/placement/Downloads/Advertising.csv")
```

```
In [5]: data.head()
```

```
Out[5]:
```

	Unnamed: 0	TV	radio	newspaper	sales
0	1	230.1	37.8	69.2	22.1
1	2	44.5	39.3	45.1	10.4
2	3	17.2	45.9	69.3	9.3
3	4	151.5	41.3	58.5	18.5
4	5	180.8	10.8	58.4	12.9

```
In [7]: data.describe()
```

```
Out[7]:
```

	Unnamed: 0	TV	radio	newspaper	sales
count	200.000000	200.000000	200.000000	200.000000	200.000000
mean	100.500000	147.042500	23.264000	30.554000	14.022500
std	57.879185	85.854236	14.846809	21.778621	5.217457
min	1.000000	0.700000	0.000000	0.300000	1.600000
25%	50.750000	74.375000	9.975000	12.750000	10.375000
50%	100.500000	149.750000	22.900000	25.750000	12.900000
75%	150.250000	218.825000	36.525000	45.100000	17.400000
max	200.000000	296.400000	49.600000	114.000000	27.000000

In [8]: data.info()

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 200 entries, 0 to 199
Data columns (total 5 columns):
#   Column      Non-Null Count  Dtype
---  -
0   Unnamed: 0   200 non-null   int64
1   TV           200 non-null   float64
2   radio        200 non-null   float64
3   newspaper    200 non-null   float64
4   sales        200 non-null   float64
dtypes: float64(4), int64(1)
memory usage: 7.9 KB
```

In [9]: list(data)

Out[9]: ['Unnamed: 0', 'TV', 'radio', 'newspaper', 'sales']

In [10]: data1=data.drop(['Unnamed: 0'],axis=1)

```
In [11]: data1
```

```
Out[11]:
```

	TV	radio	newspaper	sales
0	230.1	37.8	69.2	22.1
1	44.5	39.3	45.1	10.4
2	17.2	45.9	69.3	9.3
3	151.5	41.3	58.5	18.5
4	180.8	10.8	58.4	12.9
...
195	38.2	3.7	13.8	7.6
196	94.2	4.9	8.1	9.7
197	177.0	9.3	6.4	12.8
198	283.6	42.0	66.2	25.5
199	232.1	8.6	8.7	13.4

200 rows × 4 columns

```
In [13]: y=data1['sales']  
x=data1.drop('sales',axis=1)
```

```
In [14]: list(x)
```

```
Out[14]: ['TV', 'radio', 'newspaper']
```

```
In [15]: from sklearn.model_selection import train_test_split  
x_train,x_test,y_train,y_test=train_test_split(x,y,test_size=0.33,random_state=42)
```

```
In [16]: x_test.head()
```

```
Out[16]:
```

	TV	radio	newspaper
95	163.3	31.6	52.9
15	195.4	47.7	52.9
30	292.9	28.3	43.2
158	11.7	36.9	45.2
128	220.3	49.0	3.2

```
In [17]: y_test.head()
```

```
Out[17]:
```

95	16.9
15	22.4
30	21.4
158	7.3
128	24.7

Name: sales, dtype: float64

```
In [20]: from sklearn.linear_model import Lasso
from sklearn.model_selection import GridSearchCV
lasso=Lasso()
parameters={'alpha': [1e-15,1e-10,1e-8,1e-4,1e-3,1e-2,1,5,10,20]}
lasso_regressor=GridSearchCV(lasso,parameters)
lasso_regressor.fit(x_train,y_train)
```

```
Out[20]: GridSearchCV(estimator=Lasso(),
                        param_grid={'alpha': [1e-15, 1e-10, 1e-08, 0.0001, 0.001, 0.01, 1,
                                                5, 10, 20]}))
```

In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.
On GitHub, the HTML representation is unable to render, please try loading this page with nbviewer.org.

```
In [22]: lasso_regressor.best_params_
```

```
Out[22]: {'alpha': 1}
```

```
In [25]: lasso=Lasso(alpha=1)
lasso.fit(x_train,y_train)
y_pred_lasso=lasso.predict(x_test)
```

```
In [26]: from sklearn.metrics import mean_squared_error
Lasso_Error=mean_squared_error(y_pred_lasso,y_test)
Lasso_Error
```

```
Out[26]: 3.641439660278575
```

```
In [27]: from sklearn.metrics import r2_score
r2_score(y_test,y_pred_lasso)
```

```
Out[27]: 0.8589079527148957
```

```
In [ ]:
```