Consolidated Source Code Document

BESSS React/Vite project packaged from attached ZIP archive

Archive summary

SOURCE ARCHIVE	FILES INCLUDED	ESTIMATED DOCUMENT PAGES
besss.zip	28	244
GENERATED DATE	**TOTAL LINES OF CODE**	
April 19, 2026	9,020	

Document structure

- Cover page with project summary
- Folder tree overview
- File index with line counts and starting pages
- All source files merged in sorted path order
- Line-numbered code pages with file headers and page footers

Note: long code lines are soft-wrapped in the PDF for readability; original source files remain unchanged.

Project folder tree

Rendered from the extracted ZIP contents.

```
besss_extracted
├── pages
│   ├── home
│   │   ├── components
│   │   │   └── Demo.tsx
│   │   └── Index.tsx
│   ├── not-found
│   │   └── Index.tsx
│   ├── Analytics.tsx
│   ├── BranchOfficePortal.tsx
│   ├── CreateDelivery.tsx
│   ├── CustomerPortal.tsx
│   ├── CustomerService.tsx
│   ├── Dashboard.tsx
│   ├── DataEntryPortal.tsx
│   ├── DriverPortal.tsx
│   ├── FinancePortal.tsx
│   ├── HRPortal.tsx
│   ├── Login.tsx
│   ├── MarketingPortal.tsx
│   ├── MerchantPortal.tsx
│   ├── QRCodeManagement.tsx
│   ├── ResetPassword.tsx
│   ├── Settings.tsx
│   ├── SupervisorPortal.tsx
│   ├── WarehousePortal.tsx
│   └── WayplanPortal.tsx
├── App.tsx
├── App.tsx.bak
├── App_original.tsx
├── index.css
├── main.tsx
└── vite-env.d.ts
```

File index

Files are ordered alphabetically by relative path inside the archive.

File	Lines	Starts
App.tsx	167	5
App.tsx.bak	159	10
App_original.tsx	159	14
index.css	215	18
main.tsx	10	24
pages/Analytics.tsx	852	25
pages/BranchOfficePortal.tsx	171	47
pages/CreateDelivery.tsx	421	52
pages/CustomerPortal.tsx	347	63
pages/CustomerService.tsx	618	72
pages/Dashboard.tsx	402	88
pages/DataEntryPortal.tsx	406	99
pages/DriverPortal.tsx	755	110
pages/FinancePortal.tsx	90	129
pages/home/components/Demo.tsx	3	132
pages/home/Index.tsx	13	133
pages/HRPortal.tsx	88	134
pages/Login.tsx	431	137
pages/MarketingPortal.tsx	312	148
pages/MerchantPortal.tsx	96	156
pages/not-found/Index.tsx	27	159
pages/QRCodeManagement.tsx	599	160
pages/ResetPassword.tsx	325	175
pages/Settings.tsx	836	184

File index

Files are ordered alphabetically by relative path inside the archive.

File	Lines	Starts
pages/SupervisorPortal.tsx	784	205
pages/WarehousePortal.tsx	624	225
pages/WayplanPortal.tsx	106	241
vite-env.d.ts	4	244

App.tsx

167 lines · 7,260 bytes · Page segment 1 of 5

```
import { Toaster } from "@/components/ui/toaster";
import { Toaster as Sonner } from "@/components/ui/sonner";
import { TooltipProvider } from "@/components/ui/tooltip";
import { QueryClient, QueryClientProvider } from "@tanstack/react-query";
import { HashRouter, Routes, Route, Navigate } from "react-router-dom";
import { ErrorBoundary } from "react-error-boundary";
import { ROUTE_PATHS } from "@/lib/index";
import { AuthProvider, useAuth } from "@/hooks/useAuth";
import { LanguageProvider } from "@/hooks/useLanguage";
import { Layout } from "@/components/Layout";
import { NotificationPanel } from "@/components/NotificationPanel";
import Login from "@/pages/Login";
import ResetPassword from "@/pages/ResetPassword";
import Dashboard from "@/pages/Dashboard";
import SupervisorPortal from "@/pages/SupervisorPortal";
import WayplanPortal from "@/pages/WayplanPortal";
import DriverPortal from "@/pages/DriverPortal";
import WarehousePortal from "@/pages/WarehousePortal";
import DataEntryPortal from "@/pages/DataEntryPortal";
import CustomerService from "@/pages/CustomerService";
import MarketingPortal from "@/pages/MarketingPortal";
import HRPortal from "@/pages/HRPortal";
import FinancePortal from "@/pages/FinancePortal";
import MerchantPortal from "@/pages/MerchantPortal";
import CustomerPortal from "@/pages/CustomerPortal";
import CreateDelivery from "@/pages/CreateDelivery";
import Analytics from "@/pages/Analytics";
import Settings from "@/pages/Settings";
import QRCodeManagement from "@/pages/QRCodeManagement";
import BranchOfficePortal from "@/pages/BranchOfficePortal";

const queryClient = new QueryClient({
  defaultOptions: {
    queries: {
      staleTime: 1000 * 60 * 5,
      refetchOnWindowFocus: false,
      retry: 1,
    },
  },
});
```

App.tsx

167 lines · 7,260 bytes · Page segment 2 of 5

```

function ErrorFallback({ error, resetErrorBoundary }: { error: Error; resetErrorBoundary: () => void }) {
  return (
    <div className="min-h-screen flex items-center justify-center bg-background">
      <div className="max-w-md w-full p-8 bg-card rounded-lg border border-border shadow-lg">
        <div className="flex items-center gap-3 mb-4">
          <div className="w-12 h-12 rounded-full bg-destructive/10 flex items-center justify-center">
            <svg className="w-6 h-6 text-destructive" fill="none" viewBox="0 0 24 24" stroke="currentColor">
              <path strokeLinecap="round" strokeLinejoin="round" strokeWidth={2} d="M12 9v2m0 4h.01m-6.938 4h13.856c1.54 0 2.502-1.667 1.732-3L13.732 4c-.77-1.333-2.694-1.333-3.464 0L3.34 16c-.77 1.333.192 3 1.732 3z" />
            </svg>
          </div>
          <div>
            <h2 className="text-lg font-semibold text-foreground">Application Error</h2>
            <p className="text-sm text-muted-foreground">Something went wrong</p>
          </div>
        </div>
        <div className="mb-6 p-4 bg-muted rounded-md">
          <p className="text-sm text-foreground font-mono break-all">{error.message}</p>
        </div>
        <button
          onClick={resetErrorBoundary}
          className="w-full px-4 py-2 bg-primary text-primary-foreground rounded-md hover:bg-primary/90 transition-colors font-medium"
        >
          Try Again
        </button>
      </div>
    </div>
  );
}

function ProtectedRoute({ children }: { children: React.ReactNode }) {
  const { isAuthenticated, isLoading } = useAuth();

  if (isLoading) {
    return (
      <div className="min-h-screen flex items-center justify-center">
        <div className="animate-spin rounded-full h-12 w-12 border-b-2 border-primary"></div>
      </div>
    );
```

App.tsx

167 lines · 7,260 bytes · Page segment 3 of 5

```
  }

  if (!isAuthenticated) {
    return <Navigate to="/login" replace />;
  }

  return <>{children}</>;
}

function AppRoutes() {
  const { isAuthenticated } = useAuth();

  return (
    <Routes>
      <Route
        path="/login"
        element={isAuthenticated ? <Navigate to={ROUTE_PATHS.DASHBOARD} replace /> : <Login />}
      />
      <Route
        path="/reset-password"
        element={<ResetPassword />}
      />
      <Route
        path="/*"
        element={
          <ProtectedRoute>
            <Layout>
              <Routes>
                <Route path={ROUTE_PATHS.DASHBOARD} element={<Dashboard />} />
                <Route path={ROUTE_PATHS.SUPERVISOR} element={<SupervisorPortal />} />
                <Route path="/supervisor/*" element={<SupervisorPortal />} />
                <Route path={ROUTE_PATHS.WAYPLAN} element={<WayplanPortal />} />
                <Route path={ROUTE_PATHS.DRIVER} element={<DriverPortal />} />
                <Route path={ROUTE_PATHS.WAREHOUSE} element={<WarehousePortal />} />
                <Route path="/wayplan/*" element={<WayplanPortal />} />
                <Route path={ROUTE_PATHS.DATA_ENTRY} element={<DataEntryPortal />} />
                <Route path="/driver/*" element={<DriverPortal />} />
                <Route path={ROUTE_PATHS.CUSTOMER_SERVICE} element={<CustomerService />} />
                <Route path="/warehouse/*" element={<WarehousePortal />} />
                <Route path={ROUTE_PATHS.MARKETING} element={<MarketingPortal />} />
```

App.tsx

167 lines · 7,260 bytes · Page segment 4 of 5

```
                <Route path="/data-entry/*" element={<DataEntryPortal />} />
                <Route path={ROUTE_PATHS.HR} element={<HRPortal />} />
                <Route path="/customer-service/*" element={<CustomerService />} />
                <Route path={ROUTE_PATHS.FINANCE} element={<FinancePortal />} />
                <Route path="/marketing/*" element={<MarketingPortal />} />
                <Route path={ROUTE_PATHS.MERCHANT} element={<MerchantPortal />} />
                <Route path="/hr/*" element={<HRPortal />} />
                <Route path={ROUTE_PATHS.CUSTOMER} element={<CustomerPortal />} />
                <Route path="/finance/*" element={<FinancePortal />} />
                <Route path={ROUTE_PATHS.CREATE_DELIVERY} element={<CreateDelivery />} />
                <Route path="/merchant/*" element={<MerchantPortal />} />
                <Route path="/customer/*" element={<CustomerPortal />} />
                <Route path={ROUTE_PATHS.BRANCH_OFFICE} element={<BranchOfficePortal />} />
                <Route path={ROUTE_PATHS.QR_CODE} element={<QRCodeManagement />} />
                <Route path={ROUTE_PATHS.ANALYTICS} element={<Analytics />} />
                <Route path="/branch-office/*" element={<BranchOfficePortal />} />
                <Route path={ROUTE_PATHS.SETTINGS} element={<Settings />} />
                <Route path="/analytics/*" element={<Analytics />} />
                <Route path="*" element={<Navigate to={ROUTE_PATHS.DASHBOARD} replace />} />
              </Routes>
              <NotificationPanel />
            </Layout>
          </ProtectedRoute>
        }
      />
    </Routes>
  );
}

const App = () => (
  <ErrorBoundary FallbackComponent={ErrorFallback} onReset={() => window.location.reload()}>
    <QueryClientProvider client={queryClient}>
      <LanguageProvider>
        <AuthProvider>
          <TooltipProvider>
            <Toaster />
            <Sonner />
            <HashRouter>
              <AppRoutes />
            </HashRouter>
```

App.tsx

167 lines · 7,260 bytes · Page segment 5 of 5

```
          </TooltipProvider>
        </AuthProvider>
      </LanguageProvider>
    </QueryClientProvider>
  </ErrorBoundary>
);

export default App;
```

App.tsx.bak

159 lines · 6,884 bytes · Page segment 1 of 4

```
import { Toaster } from "@/components/ui/toaster";
import { Toaster as Sonner } from "@/components/ui/sonner";
import { TooltipProvider } from "@/components/ui/tooltip";
import { QueryClient, QueryClientProvider } from "@tanstack/react-query";
import { HashRouter, Routes, Route, Navigate } from "react-router-dom";
import { ErrorBoundary } from "react-error-boundary";
import { ROUTE_PATHS } from "@/lib/index";
import { AuthProvider, useAuth } from "@/hooks/useAuth";
import { LanguageProvider } from "@/hooks/useLanguage";
import { Layout } from "@/components/Layout";
import { NotificationPanel } from "@/components/NotificationPanel";
import Login from "@/pages/Login";
import Dashboard from "@/pages/Dashboard";
import SupervisorPortal from "@/pages/SupervisorPortal";
import WayplanPortal from "@/pages/WayplanPortal";
import DriverPortal from "@/pages/DriverPortal";
import WarehousePortal from "@/pages/WarehousePortal";
import DataEntryPortal from "@/pages/DataEntryPortal";
import CustomerService from "@/pages/CustomerService";
import MarketingPortal from "@/pages/MarketingPortal";
import HRPortal from "@/pages/HRPortal";
import FinancePortal from "@/pages/FinancePortal";
import MerchantPortal from "@/pages/MerchantPortal";
import CustomerPortal from "@/pages/CustomerPortal";
import CreateDelivery from "@/pages/CreateDelivery";
import Analytics from "@/pages/Analytics";
import Settings from "@/pages/Settings";
import QRCodeManagement from "@/pages/QRCodeManagement";

const queryClient = new QueryClient({
  defaultOptions: {
    queries: {
      staleTime: 1000 * 60 * 5,
      refetchOnWindowFocus: false,
      retry: 1,
    },
  },
});

function ErrorFallback({ error, resetErrorBoundary }: { error: Error; resetErrorBoundary: () => void }) {
```

App.tsx.bak

159 lines · 6,884 bytes · Page segment 2 of 4

```
  return (
    <div className="min-h-screen flex items-center justify-center bg-background">
      <div className="max-w-md w-full p-8 bg-card rounded-lg border border-border shadow-lg">
        <div className="flex items-center gap-3 mb-4">
          <div className="w-12 h-12 rounded-full bg-destructive/10 flex items-center justify-center">
            <svg className="w-6 h-6 text-destructive" fill="none" viewBox="0 0 24 24" stroke="currentColor">
              <path strokeLinecap="round" strokeLinejoin="round" strokeWidth={2} d="M12 9v2m0 4h.01m-6.938 4h13.856c1.54 0 2.502-1.667 1.732-3L13.732 4c-.77-1.333-2.694-1.333-3.464 0L3.34 16c-.77 1.333.192 3 1.732 3z" />
            </svg>
          </div>
          <div>
            <h2 className="text-lg font-semibold text-foreground">Application Error</h2>
            <p className="text-sm text-muted-foreground">Something went wrong</p>
          </div>
        </div>
        <div className="mb-6 p-4 bg-muted rounded-md">
          <p className="text-sm text-foreground font-mono break-all">{error.message}</p>
        </div>
        <button
          onClick={resetErrorBoundary}
          className="w-full px-4 py-2 bg-primary text-primary-foreground rounded-md hover:bg-primary/90 transition-colors font-medium"
        >
          Try Again
        </button>
      </div>
    </div>
  );
}

function ProtectedRoute({ children }: { children: React.ReactNode }) {
  const { isAuthenticated, isLoading } = useAuth();

  if (isLoading) {
    return (
      <div className="min-h-screen flex items-center justify-center">
        <div className="animate-spin rounded-full h-12 w-12 border-b-2 border-primary"></div>
      </div>
    );
  }

```

App.tsx.bak

159 lines · 6,884 bytes · Page segment 3 of 4

```
  if (!isAuthenticated) {
    return <Navigate to="/login" replace />;
  }

  return <>{children}</>;
}

function AppRoutes() {
  const { isAuthenticated } = useAuth();

  return (
    <Routes>
      <Route
        path="/login"
        element={isAuthenticated ? <Navigate to={ROUTE_PATHS.DASHBOARD} replace /> : <Login />}
      />
      <Route
        path="/*"
        element={
          <ProtectedRoute>
            <Layout>
              <Routes>
                <Route path={ROUTE_PATHS.DASHBOARD} element={<Dashboard />} />
                <Route path={ROUTE_PATHS.SUPERVISOR} element={<SupervisorPortal />} />
                <Route path="/supervisor/*" element={<SupervisorPortal />} />
                <Route path={ROUTE_PATHS.WAYPLAN} element={<WayplanPortal />} />
                <Route path="/wayplan/*" element={<WayplanPortal />} />
                <Route path={ROUTE_PATHS.DRIVER} element={<DriverPortal />} />
                <Route path="/driver/*" element={<DriverPortal />} />
                <Route path={ROUTE_PATHS.WAREHOUSE} element={<WarehousePortal />} />
                <Route path="/warehouse/*" element={<WarehousePortal />} />
                <Route path={ROUTE_PATHS.DATA_ENTRY} element={<DataEntryPortal />} />
                <Route path="/data-entry/*" element={<DataEntryPortal />} />
                <Route path={ROUTE_PATHS.CUSTOMER_SERVICE} element={<CustomerService />} />
                <Route path="/customer-service/*" element={<CustomerService />} />
                <Route path={ROUTE_PATHS.MARKETING} element={<MarketingPortal />} />
                <Route path="/marketing/*" element={<MarketingPortal />} />
                <Route path={ROUTE_PATHS.HR} element={<HRPortal />} />
                <Route path="/hr/*" element={<HRPortal />} />
                <Route path={ROUTE_PATHS.FINANCE} element={<FinancePortal />} />
```

App.tsx.bak

159 lines · 6,884 bytes · Page segment 4 of 4

```
                <Route path="/finance/*" element={<FinancePortal />} />
                <Route path={ROUTE_PATHS.MERCHANT} element={<MerchantPortal />} />
                <Route path="/merchant/*" element={<MerchantPortal />} />
                <Route path={ROUTE_PATHS.CUSTOMER} element={<CustomerPortal />} />
                <Route path="/customer/*" element={<CustomerPortal />} />
                <Route path={ROUTE_PATHS.CREATE_DELIVERY} element={<CreateDelivery />} />
                <Route path={ROUTE_PATHS.QR_CODE} element={<QRCodeManagement />} />
                <Route path={ROUTE_PATHS.ANALYTICS} element={<Analytics />} />
                <Route path="/analytics/*" element={<Analytics />} />
                <Route path={ROUTE_PATHS.SETTINGS} element={<Settings />} />
                <Route path="*" element={<Navigate to={ROUTE_PATHS.DASHBOARD} replace />} />
              </Routes>
              <NotificationPanel />
            </Layout>
          </ProtectedRoute>
        }
      />
    </Routes>
  );
}

const App = () => (
  <ErrorBoundary FallbackComponent={ErrorFallback} onReset={() => window.location.reload()}>
    <QueryClientProvider client={queryClient}>
      <LanguageProvider>
        <AuthProvider>
          <TooltipProvider>
            <Toaster />
            <Sonner />
            <HashRouter>
              <AppRoutes />
            </HashRouter>
          </TooltipProvider>
        </AuthProvider>
      </LanguageProvider>
    </QueryClientProvider>
  </ErrorBoundary>
);

export default App;
```

App_original.tsx

159 lines · 6,884 bytes · Page segment 1 of 4

```
import { Toaster } from "@/components/ui/toaster";
import { Toaster as Sonner } from "@/components/ui/sonner";
import { TooltipProvider } from "@/components/ui/tooltip";
import { QueryClient, QueryClientProvider } from "@tanstack/react-query";
import { HashRouter, Routes, Route, Navigate } from "react-router-dom";
import { ErrorBoundary } from "react-error-boundary";
import { ROUTE_PATHS } from "@/lib/index";
import { AuthProvider, useAuth } from "@/hooks/useAuth";
import { LanguageProvider } from "@/hooks/useLanguage";
import { Layout } from "@/components/Layout";
import { NotificationPanel } from "@/components/NotificationPanel";
import Login from "@/pages/Login";
import Dashboard from "@/pages/Dashboard";
import SupervisorPortal from "@/pages/SupervisorPortal";
import WayplanPortal from "@/pages/WayplanPortal";
import DriverPortal from "@/pages/DriverPortal";
import WarehousePortal from "@/pages/WarehousePortal";
import DataEntryPortal from "@/pages/DataEntryPortal";
import CustomerService from "@/pages/CustomerService";
import MarketingPortal from "@/pages/MarketingPortal";
import HRPortal from "@/pages/HRPortal";
import FinancePortal from "@/pages/FinancePortal";
import MerchantPortal from "@/pages/MerchantPortal";
import CustomerPortal from "@/pages/CustomerPortal";
import CreateDelivery from "@/pages/CreateDelivery";
import Analytics from "@/pages/Analytics";
import Settings from "@/pages/Settings";
import QRCodeManagement from "@/pages/QRCodeManagement";

const queryClient = new QueryClient({
  defaultOptions: {
    queries: {
      staleTime: 1000 * 60 * 5,
      refetchOnWindowFocus: false,
      retry: 1,
    },
  },
});

function ErrorFallback({ error, resetErrorBoundary }: { error: Error; resetErrorBoundary: () => void }) {
```

App_original.tsx

159 lines · 6,884 bytes · Page segment 2 of 4

```
  return (
    <div className="min-h-screen flex items-center justify-center bg-background">
      <div className="max-w-md w-full p-8 bg-card rounded-lg border border-border shadow-lg">
        <div className="flex items-center gap-3 mb-4">
          <div className="w-12 h-12 rounded-full bg-destructive/10 flex items-center justify-center">
            <svg className="w-6 h-6 text-destructive" fill="none" viewBox="0 0 24 24" stroke="currentColor">
              <path strokeLinecap="round" strokeLinejoin="round" strokeWidth={2} d="M12 9v2m0 4h.01m-6.938 4h13.856c1.54 0 2.502-1.667 1.732-3L13.732 4c-.77-1.333-2.694-1.333-3.464 0L3.34 16c-.77 1.333.192 3 1.732 3z" />
            </svg>
          </div>
          <div>
            <h2 className="text-lg font-semibold text-foreground">Application Error</h2>
            <p className="text-sm text-muted-foreground">Something went wrong</p>
          </div>
        </div>
        <div className="mb-6 p-4 bg-muted rounded-md">
          <p className="text-sm text-foreground font-mono break-all">{error.message}</p>
        </div>
        <button
          onClick={resetErrorBoundary}
          className="w-full px-4 py-2 bg-primary text-primary-foreground rounded-md hover:bg-primary/90 transition-colors font-medium"
        >
          Try Again
        </button>
      </div>
    </div>
  );
}

function ProtectedRoute({ children }: { children: React.ReactNode }) {
  const { isAuthenticated, isLoading } = useAuth();

  if (isLoading) {
    return (
      <div className="min-h-screen flex items-center justify-center">
        <div className="animate-spin rounded-full h-12 w-12 border-b-2 border-primary"></div>
      </div>
    );
  }

```

App_original.tsx

159 lines · 6,884 bytes · Page segment 3 of 4

```
  if (!isAuthenticated) {
    return <Navigate to="/login" replace />;
  }

  return <>{children}</>;
}

function AppRoutes() {
  const { isAuthenticated } = useAuth();

  return (
    <Routes>
      <Route
        path="/login"
        element={isAuthenticated ? <Navigate to={ROUTE_PATHS.DASHBOARD} replace /> : <Login />}
      />
      <Route
        path="/*"
        element={
          <ProtectedRoute>
            <Layout>
              <Routes>
                <Route path={ROUTE_PATHS.DASHBOARD} element={<Dashboard />} />
                <Route path={ROUTE_PATHS.SUPERVISOR} element={<SupervisorPortal />} />
                <Route path="/supervisor/*" element={<SupervisorPortal />} />
                <Route path={ROUTE_PATHS.WAYPLAN} element={<WayplanPortal />} />
                <Route path="/wayplan/*" element={<WayplanPortal />} />
                <Route path={ROUTE_PATHS.DRIVER} element={<DriverPortal />} />
                <Route path="/driver/*" element={<DriverPortal />} />
                <Route path={ROUTE_PATHS.WAREHOUSE} element={<WarehousePortal />} />
                <Route path="/warehouse/*" element={<WarehousePortal />} />
                <Route path={ROUTE_PATHS.DATA_ENTRY} element={<DataEntryPortal />} />
                <Route path="/data-entry/*" element={<DataEntryPortal />} />
                <Route path={ROUTE_PATHS.CUSTOMER_SERVICE} element={<CustomerService />} />
                <Route path="/customer-service/*" element={<CustomerService />} />
                <Route path={ROUTE_PATHS.MARKETING} element={<MarketingPortal />} />
                <Route path="/marketing/*" element={<MarketingPortal />} />
                <Route path={ROUTE_PATHS.HR} element={<HRPortal />} />
                <Route path="/hr/*" element={<HRPortal />} />
                <Route path={ROUTE_PATHS.FINANCE} element={<FinancePortal />} />
```

App_original.tsx

159 lines · 6,884 bytes · Page segment 4 of 4

```
                <Route path="/finance/*" element={<FinancePortal />} />
                <Route path={ROUTE_PATHS.MERCHANT} element={<MerchantPortal />} />
                <Route path="/merchant/*" element={<MerchantPortal />} />
                <Route path={ROUTE_PATHS.CUSTOMER} element={<CustomerPortal />} />
                <Route path="/customer/*" element={<CustomerPortal />} />
                <Route path={ROUTE_PATHS.CREATE_DELIVERY} element={<CreateDelivery />} />
                <Route path={ROUTE_PATHS.QR_CODE} element={<QRCodeManagement />} />
                <Route path={ROUTE_PATHS.ANALYTICS} element={<Analytics />} />
                <Route path="/analytics/*" element={<Analytics />} />
                <Route path={ROUTE_PATHS.SETTINGS} element={<Settings />} />
                <Route path="*" element={<Navigate to={ROUTE_PATHS.DASHBOARD} replace />} />
              </Routes>
              <NotificationPanel />
            </Layout>
          </ProtectedRoute>
        }
      />
    </Routes>
  );
}

const App = () => (
  <ErrorBoundary FallbackComponent={ErrorFallback} onReset={() => window.location.reload()}>
    <QueryClientProvider client={queryClient}>
      <LanguageProvider>
        <AuthProvider>
          <TooltipProvider>
            <Toaster />
            <Sonner />
            <HashRouter>
              <AppRoutes />
            </HashRouter>
          </TooltipProvider>
        </AuthProvider>
      </LanguageProvider>
    </QueryClientProvider>
  </ErrorBoundary>
);

export default App;
```

index.css

215 lines · 9,849 bytes · Page segment 1 of 6

```
@import url("https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600;700;800&family=JetBrains+Mono:wght@400;500;600&display=swap");
@import "tailwindcss";
@import "tw-animate-css";

@custom-variant dark (&:is(.dark *));

/*
============================================================================
AI HANDOVER NOTE
1. DESIGN PHILOSOPHY:
   - Atmosphere-First Enterprise Design: This system prioritizes operational clarity and real-time data visibility for 24/7 logistics operations. The design language combines Neo-minimalism with Physicality principles—clean surfaces with subtle depth cues (rim-light, ambient occlusion) to create visual hierarchy without clutter.
   - Bento/Modular Surfaces: Dashboard uses card-based layouts with clear boundaries for different operational zones (KPIs, active deliveries, warehouse status, fleet tracking). Each module is self-contained yet part of a cohesive grid system.
   - Glassmorphism 2.0 for Overlays: Modal dialogs, notification panels, and real-time status overlays use subtle backdrop-blur with high-contrast text to maintain readability during critical operations.
   - Why this style: Logistics platforms require instant data comprehension under stress. The design balances information density with breathing room, using color-coded status systems and clear typographic hierarchy to support split-second decision-making.

2. TYPOGRAPHY:
   - Sans (Inter): Selected for its exceptional legibility at small sizes and neutral geometric structure. Inter's wide apertures and tall x-height ensure readability in data-dense tables and metric cards. The font's technical precision matches the operational nature of logistics software while remaining approachable for diverse user roles (supervisors, drivers, warehouse staff).
   - Mono (JetBrains Mono): Purpose-built for displaying tracking codes, shipment IDs, timestamps, and tabular data. Its increased letter spacing and distinct character shapes (0 vs O, 1 vs l) prevent misreading critical identifiers. Used in proof-of-delivery screens, manifest lists, and QR code displays.

3. COLOR SYSTEM:
   - Brand Primary (Hue 220°): Professional blue conveys trust, reliability, and operational stability—essential for enterprise logistics. The 220° hue sits between pure blue and cyan, providing a modern, tech-forward feel without the coldness of pure blue.
   - --brand maps to --primary (buttons, active states), --accent (highlights, notifications), and --ring (focus indicators) to maintain brand consistency across interactive elements.
   - Semantic Colors:
     * success (Hue 150°): Teal-green for completed deliveries, successful operations—chosen over pure green for better distinction from warning states
     * warning (Hue 45°): Amber for pending/delayed shipments, attention-required states
     * destructive (Hue 10°): Coral-red for failed deliveries, critical alerts—slightly orange-shifted to reduce alarm fatigue
   - Chart Colors: Five distinct hues (220°, 280°, 160°, 30°, 340°) for multi-series data visualization (delivery trends, revenue charts, status distribution)
```

index.css

215 lines · 9,849 bytes · Page segment 2 of 6

```
   - Sidebar System: Dedicated tokens for navigation sidebar with subtle contrast to main content area, supporting role-based portal switching

4. USAGE GUIDE:
   - Layout Type: Dashboard full-width with responsive grid (12-column on desktop, 4-column on tablet, single-column on mobile). Fixed header with role indicator and notification bell. Collapsible sidebar for portal navigation.
   - Special Effects:
     * Rim-light: 1px top border (oklch(1 0 0 / 0.1)) on elevated cards to simulate ambient lighting
     * Backdrop-blur: 12px blur on modals/overlays with 80% opacity background
     * Status Badges: Solid backgrounds with 0.5rem padding, 9999px border-radius for pill shape
   - Real-time Updates: Use --accent with subtle pulse animation for live tracking indicators. WebSocket notifications trigger toast messages with 4-second auto-dismiss.
   - Data Tables: Alternating row backgrounds (--muted/5% opacity) for improved scannability. Sticky headers for long lists. Inline action buttons on hover.
   - Mobile Considerations: Bottom navigation for driver/rider portals. Larger touch targets (44px minimum). Simplified metric cards with single-column layout.
   - Dark Mode: Automatically enabled for night shift operations (6 PM - 6 AM) or user preference. Reduced contrast ratios to prevent eye strain during extended use.
==========================================================================
*/

:root {
  /* Typography */
  --font-sans: Inter, -apple-system, BlinkMacSystemFont, 'Segoe UI', Roboto, sans-serif;
  --font-mono: JetBrains Mono, 'Courier New', Consolas, monospace;

  /* Radius */
  --radius: 0.75rem;

  /* Core UI Tokens */
  --background: oklch(0.99 0 0);
  --foreground: oklch(0.15 0.01 240);
  --card: oklch(0.98 0 0);
  --card-foreground: oklch(0.15 0.01 240);
  --popover: oklch(0.99 0 0);
  --popover-foreground: oklch(0.15 0.01 240);
  --primary: oklch(0.52 0.18 220);
  --primary-foreground: oklch(0.99 0 0);
  --secondary: oklch(0.92 0.01 240);
  --secondary-foreground: oklch(0.20 0.01 240);
  --muted: oklch(0.94 0.01 240);
```

index.css

215 lines · 9,849 bytes · Page segment 3 of 6

```
  --muted-foreground: oklch(0.48 0.01 240);
  --accent: oklch(0.88 0.08 220);
  --accent-foreground: oklch(0.20 0.01 240);
  --destructive: oklch(0.58 0.20 10);
  --destructive-foreground: oklch(0.99 0 0);
  --border: oklch(0.88 0.01 240);
  --input: oklch(0.88 0.01 240);
  --ring: oklch(0.52 0.18 220);

  /* Chart Tokens */
  --chart-1: oklch(0.60 0.18 220);
  --chart-2: oklch(0.62 0.16 280);
  --chart-3: oklch(0.65 0.15 160);
  --chart-4: oklch(0.68 0.18 30);
  --chart-5: oklch(0.58 0.20 340);

  /* Sidebar Tokens */
  --sidebar: oklch(0.97 0 0);
  --sidebar-foreground: oklch(0.20 0.01 240);
  --sidebar-primary: oklch(0.52 0.18 220);
  --sidebar-primary-foreground: oklch(0.99 0 0);
  --sidebar-accent: oklch(0.90 0.06 220);
  --sidebar-accent-foreground: oklch(0.20 0.01 240);
  --sidebar-border: oklch(0.90 0.01 240);
  --sidebar-ring: oklch(0.52 0.18 220);
}

.dark {
  --background: oklch(0.12 0.01 240);
  --foreground: oklch(0.92 0.01 240);
  --card: oklch(0.15 0.01 240);
  --card-foreground: oklch(0.92 0.01 240);
  --popover: oklch(0.12 0.01 240);
  --popover-foreground: oklch(0.92 0.01 240);
  --primary: oklch(0.62 0.22 220);
  --primary-foreground: oklch(0.12 0.01 240);
  --secondary: oklch(0.22 0.02 240);
  --secondary-foreground: oklch(0.88 0.01 240);
  --muted: oklch(0.20 0.02 240);
  --muted-foreground: oklch(0.62 0.01 240);
```

index.css

215 lines · 9,849 bytes · Page segment 4 of 6

```
  --accent: oklch(0.32 0.12 220);
  --accent-foreground: oklch(0.92 0.01 240);
  --destructive: oklch(0.62 0.24 10);
  --destructive-foreground: oklch(0.92 0.01 240);
  --border: oklch(0.25 0.02 240);
  --input: oklch(0.25 0.02 240);
  --ring: oklch(0.62 0.22 220);

  /* Chart Tokens */
  --chart-1: oklch(0.68 0.22 220);
  --chart-2: oklch(0.70 0.20 280);
  --chart-3: oklch(0.72 0.18 160);
  --chart-4: oklch(0.75 0.22 30);
  --chart-5: oklch(0.65 0.24 340);

  /* Sidebar Tokens */
  --sidebar: oklch(0.10 0.01 240);
  --sidebar-foreground: oklch(0.88 0.01 240);
  --sidebar-primary: oklch(0.62 0.22 220);
  --sidebar-primary-foreground: oklch(0.12 0.01 240);
  --sidebar-accent: oklch(0.28 0.10 220);
  --sidebar-accent-foreground: oklch(0.88 0.01 240);
  --sidebar-border: oklch(0.22 0.02 240);
  --sidebar-ring: oklch(0.62 0.22 220);
}

@theme inline {
  /* Shadcn Core Mapping */
  --color-background: var(--background);
  --color-foreground: var(--foreground);
  --color-card: var(--card);
  --color-card-foreground: var(--card-foreground);
  --color-popover: var(--popover);
  --color-popover-foreground: var(--popover-foreground);
  --color-primary: var(--primary);
  --color-primary-foreground: var(--primary-foreground);
  --color-secondary: var(--secondary);
  --color-secondary-foreground: var(--secondary-foreground);
  --color-muted: var(--muted);
  --color-muted-foreground: var(--muted-foreground);
```

index.css

215 lines · 9,849 bytes · Page segment 5 of 6

```
  --color-accent: var(--accent);
  --color-accent-foreground: var(--accent-foreground);
  --color-destructive: var(--destructive);
  --color-destructive-foreground: var(--destructive-foreground);
  --color-border: var(--border);
  --color-input: var(--input);
  --color-ring: var(--ring);

  /* Charts Mapping */
  --color-chart-1: var(--chart-1);
  --color-chart-2: var(--chart-2);
  --color-chart-3: var(--chart-3);
  --color-chart-4: var(--chart-4);
  --color-chart-5: var(--chart-5);

  /* Sidebar Mapping */
  --color-sidebar: var(--sidebar);
  --color-sidebar-foreground: var(--sidebar-foreground);
  --color-sidebar-primary: var(--sidebar-primary);
  --color-sidebar-primary-foreground: var(--sidebar-primary-foreground);
  --color-sidebar-accent: var(--sidebar-accent);
  --color-sidebar-accent-foreground: var(--sidebar-accent-foreground);
  --color-sidebar-border: var(--sidebar-border);
  --color-sidebar-ring: var(--sidebar-ring);

  /* Typography */
  --font-sans: var(--font-sans);
  --font-mono: var(--font-mono);

  /* Radius */
  --radius-lg: var(--radius);
  --radius-md: calc(var(--radius) - 2px);
  --radius-sm: calc(var(--radius) - 4px);
  --radius-xl: calc(var(--radius) + 4px);
}

@layer base {
  * {
    @apply border-border outline-ring/50;
  }
```

index.css

215 lines · 9,849 bytes · Page segment 6 of 6

```

  html {
    @apply scroll-smooth antialiased;
  }

  body {
    @apply bg-background text-foreground font-sans min-h-screen;
    font-feature-settings: "cv02", "cv03", "cv04", "cv11";
  }

  h1, h2, h3, h4, h5, h6 {
    @apply font-semibold tracking-tight;
  }

  code, pre {
    @apply font-mono;
  }

  ::selection {
    @apply bg-primary/20 text-primary;
  }

  ::-webkit-scrollbar {
    width: 6px;
    height: 6px;
  }
  ::-webkit-scrollbar-track {
    @apply bg-transparent;
  }
  ::-webkit-scrollbar-thumb {
    @apply bg-muted-foreground/20 rounded-full hover:bg-muted-foreground/40;
  }
}
```

main.tsx

10 lines · 268 bytes · Page segment 1 of 1

```
import { createRoot } from 'react-dom/client'
import App from './App.tsx'
import './index.css'
import { ErrorBoundary } from './components/ErrorBoundary'

createRoot(document.getElementById("root")!).render(
    <ErrorBoundary>
      <App />
    </ErrorBoundary>
  );
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 1 of 22

```
// @ts-nocheck
import { useState } from 'react';
import { useLocation } from 'react-router-dom';
import { motion } from 'framer-motion';
import {
  Calendar,
  Download,
  TrendingUp,
  TrendingDown,
  Package,
  DollarSign,
  Users,
  MapPin,
  Star,
  Clock,
  BarChart3,
  PieChart,
  Activity,
} from 'lucide-react';
import { Button } from '@/components/ui/button';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from '@/components/ui/select';
import { MetricCard, StatsGrid, CompactMetric, ProgressMetric } from '@/components/Stats';
import {
  DeliveryTrendChart,
  RevenueChart,
  StatusDistributionChart,
  FleetActivityChart,
} from '@/components/Charts';
import { DataTable, Column } from '@/components/DataTable';
import { IMAGES } from '@/assets/images';
import { mockDeliveries, mockShipments, mockEmployees, mockKPIs } from '@/data/index';
import {
  calculateDeliveryMetrics,
  calculateRevenue,
  formatCurrency,
  formatDate,
  DeliveryStatus,
  ServiceType,
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 2 of 22

```
41 } from '@/lib/index';
42 import { springPresets, fadeInUp, staggerContainer, staggerItem } from '@/lib/motion';
43
44 interface PerformanceData {
45   date: string;
46   deliveries: number;
47   revenue: number;
48   onTimeRate: number;
49 }
50
51 interface ServiceTypeRevenue {
52   serviceType: ServiceType;
53   revenue: number;
54   count: number;
55 }
56
57 interface RegionData {
58   region: string;
59   deliveries: number;
60   revenue: number;
61 }
62
63 interface DriverPerformance {
64   id: string;
65   name: string;
66   totalDeliveries: number;
67   successRate: number;
68   onTimeRate: number;
69   rating: number;
70 }
71
72 interface WarehouseEfficiency {
73   id: string;
74   name: string;
75   throughput: number;
76   accuracy: number;
77   utilization: number;
78 }
79
80 export default function Analytics() {
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 3 of 22

```
  const location = useLocation();
  const getInitialAnalyticsTab = () => {
    if (location.pathname.includes('/overview')) return 'overview';
    if (location.pathname.includes('/revenue')) return 'revenue';
    if (location.pathname.includes('/drivers')) return 'drivers';
    return 'overview';
  };
  const [dateRange, setDateRange] = useState('7d');
  const [selectedTab, setSelectedTab] = useState(getInitialAnalyticsTab());

  const metrics = calculateDeliveryMetrics(mockDeliveries);
  const revenue = calculateRevenue(mockDeliveries, mockShipments);

  const performanceData: PerformanceData[] = [
    { date: '2026-04-03', deliveries: 145, revenue: 1250000, onTimeRate: 92.5 },
    { date: '2026-04-04', deliveries: 168, revenue: 1420000, onTimeRate: 94.2 },
    { date: '2026-04-05', deliveries: 152, revenue: 1380000, onTimeRate: 93.8 },
    { date: '2026-04-06', deliveries: 189, revenue: 1650000, onTimeRate: 95.1 },
    { date: '2026-04-07', deliveries: 176, revenue: 1520000, onTimeRate: 94.7 },
    { date: '2026-04-08', deliveries: 198, revenue: 1780000, onTimeRate: 96.2 },
    { date: '2026-04-09', deliveries: 219, revenue: 1950000, onTimeRate: 95.8 },
  ];

  const serviceTypeRevenue: ServiceTypeRevenue[] = [
    { serviceType: 'express', revenue: 3200000, count: 342 },
    { serviceType: 'same-day', revenue: 2800000, count: 198 },
    { serviceType: 'standard', revenue: 1950000, count: 456 },
    { serviceType: 'next-day', revenue: 1650000, count: 187 },
    { serviceType: 'economy', revenue: 850000, count: 312 },
  ];

  const regionData: RegionData[] = [
    { region: 'Yangon Central', deliveries: 542, revenue: 4850000 },
    { region: 'Yangon North', deliveries: 387, revenue: 3420000 },
    { region: 'Yangon South', deliveries: 298, revenue: 2650000 },
    { region: 'Mandalay', deliveries: 215, revenue: 1920000 },
    { region: 'Other Regions', deliveries: 105, revenue: 950000 },
  ];

  const driverPerformance: DriverPerformance[] = mockEmployees
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 4 of 22

```
    .filter(emp => emp.role === 'driver' && emp.performance)
    .map(emp => ({
      id: emp.id,
      name: emp.name,
      totalDeliveries: emp.performance!.totalDeliveries,
      successRate: emp.performance!.successRate,
      onTimeRate: emp.performance!.onTimeRate,
      rating: emp.performance!.averageRating,
    }));

  const warehouseEfficiency: WarehouseEfficiency[] = [
    { id: 'wh-001', name: 'Yangon Central Hub', throughput: 1250, accuracy: 98.5, utilization: 64 },
    { id: 'wh-002', name: 'Mandalay Branch', throughput: 680, accuracy: 97.2, utilization: 55 },
    { id: 'wh-003', name: 'Yangon Sorting Center', throughput: 2100, accuracy: 99.1, utilization: 60 },
  ];

  const statusDistribution = [
    { status: 'Delivered', value: metrics.delivered, color: 'hsl(var(--chart-3))' },
    { status: 'In Transit', value: Math.floor(metrics.pending * 0.6), color: 'hsl(var(--chart-1))' },
    { status: 'Pending', value: Math.floor(metrics.pending * 0.4), color: 'hsl(var(--chart-2))' },
    { status: 'Failed', value: metrics.failed, color: 'hsl(var(--destructive))' },
  ];

  const driverColumns: Column<DriverPerformance>[] = [
    {
      id: 'name',
      header: 'Driver Name',
      sortable: true,
    },
    {
      id: 'totalDeliveries',
      header: 'Total Deliveries',
      sortable: true,
      cell: (row) => value.toLocaleString(),
    },
    {
      id: 'successRate',
      header: 'Success Rate',
      sortable: true,
      cell: (row) => (
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 5 of 22

```
        <div className="flex items-center gap-2">
          <span className="font-medium">{row.onTimeRate.toFixed(1)}%</span>
          {row.onTimeRate >= 95 ? (
            <TrendingUp className="h-4 w-4 text-chart-3" />
          ) : (
            <TrendingDown className="h-4 w-4 text-destructive" />
          )}
        </div>
      ),
    },
    {
      id: 'onTimeRate',
      header: 'On-Time Rate',
      sortable: true,
      cell: (row) => `${row.onTimeRate.toFixed(1)}%`,
    },
    {
      id: 'rating',
      header: 'Rating',
      sortable: true,
      cell: (row) => (
        <div className="flex items-center gap-1">
          <Star className="h-4 w-4 fill-chart-4 text-chart-4" />
          <span className="font-medium">{row.onTimeRate.toFixed(1)}</span>
        </div>
      ),
    },
  ];

  const warehouseColumns: Column<WarehouseEfficiency>[] = [
    {
      id: 'name',
      header: 'Warehouse',
      sortable: true,
    },
    {
      id: 'throughput',
      header: 'Daily Throughput',
      sortable: true,
      cell: (row) => `${value.toLocaleString()} packages`,
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 6 of 22

```
    },
    {
      id: 'accuracy',
      header: 'Accuracy',
      sortable: true,
      cell: (row) => (
        <ProgressMetric
          label=""
          value={value}
          max={100}
          unit="%"
          color={value >= 98 ? 'hsl(var(--chart-3))' : 'hsl(var(--chart-4))'}
        />
      ),
    },
    {
      id: 'utilization',
      header: 'Utilization',
      sortable: true,
      cell: (row) => (
        <ProgressMetric
          label=""
          value={value}
          max={100}
          unit="%"
          color="hsl(var(--chart-1))"
        />
      ),
    },
  ];

  const handleExport = () => {
    const data = {
      dateRange,
      metrics,
      revenue,
      performanceData,
      serviceTypeRevenue,
      regionData,
      driverPerformance,
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 7 of 22

```
      warehouseEfficiency,
      generatedAt: new Date().toISOString(),
    };

    const blob = new Blob([JSON.stringify(data, null, 2)], { type: 'application/json' });
    const url = URL.createObjectURL(blob);
    const a = document.createElement('a');
    a.href = url;
    a.download = `analytics-report-${formatDate(new Date(), 'short')}.json`;
    document.body.appendChild(a);
    a.click();
    document.body.removeChild(a);
    URL.revokeObjectURL(url);
  };

  return (
    <div className="min-h-screen bg-background relative">
      <div
        className="absolute inset-0 z-0 opacity-30"
        style={{
          backgroundImage: `url(${IMAGES.SCREENSHOT_8648})`,
          backgroundSize: 'cover',
          backgroundPosition: 'center',
        }}
      />
      <div className="absolute inset-0 bg-gradient-to-b from-background/50 via-transparent to-background/70" />

      <motion.div
        variants={staggerContainer}
        initial="hidden"
        animate="visible"
        className="relative z-10 container mx-auto px-4 py-8 space-y-8"
      >
        <motion.div variants={staggerItem} className="flex items-center justify-between">
          <div>
            <h1 className="text-4xl font-bold tracking-tight">Analytics Dashboard</h1>
            <p className="text-muted-foreground mt-2">
              Comprehensive insights into delivery performance and operations
            </p>
          </div>
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 8 of 22

```
          <div className="flex items-center gap-4">
            <Select value={dateRange} onValueChange={setDateRange}>
              <SelectTrigger className="w-[180px]">
                <Calendar className="h-4 w-4 mr-2" />
                <SelectValue />
              </SelectTrigger>
              <SelectContent>
                <SelectItem value="24h">Last 24 Hours</SelectItem>
                <SelectItem value="7d">Last 7 Days</SelectItem>
                <SelectItem value="30d">Last 30 Days</SelectItem>
                <SelectItem value="90d">Last 90 Days</SelectItem>
                <SelectItem value="custom">Custom Range</SelectItem>
              </SelectContent>
            </Select>
            <Button onClick={handleExport} variant="outline">
              <Download className="h-4 w-4 mr-2" />
              Export Report
            </Button>
          </div>
        </motion.div>

        <motion.div variants={staggerItem}>
          <StatsGrid
            metrics={[
              {
                title: 'Total Deliveries',
                value: metrics.total,
                trend: 12.5,
                icon: <Package className="h-5 w-5" />,
                unit: 'deliveries',
              },
              {
                title: 'Success Rate',
                value: `${metrics.successRate}%`,
                trend: 2.3,
                icon: <TrendingUp className="h-5 w-5" />,
              },
              {
                title: 'Total Revenue',
                value: formatCurrency(revenue.totalRevenue),
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 9 of 22

```
                trend: 18.7,
                icon: <DollarSign className="h-5 w-5" />,
              },
              {
                title: 'On-Time Rate',
                value: `${metrics.onTimeRate}%`,
                trend: 3.1,
                icon: <Clock className="h-5 w-5" />,
              },
            ]}
          />
        </motion.div>

        <motion.div variants={staggerItem}>
          <Tabs value={selectedTab} onValueChange={setSelectedTab} className="space-y-6">
            <TabsList className="grid w-full grid-cols-5">
              <TabsTrigger value="overview">
                <BarChart3 className="h-4 w-4 mr-2" />
                Overview
              </TabsTrigger>
              <TabsTrigger value="revenue">
                <DollarSign className="h-4 w-4 mr-2" />
                Revenue
              </TabsTrigger>
              <TabsTrigger value="drivers">
                <Users className="h-4 w-4 mr-2" />
                Drivers
              </TabsTrigger>
              <TabsTrigger value="warehouses">
                <MapPin className="h-4 w-4 mr-2" />
                Warehouses
              </TabsTrigger>
              <TabsTrigger value="satisfaction">
                <Star className="h-4 w-4 mr-2" />
                Satisfaction
              </TabsTrigger>
            </TabsList>

            <TabsContent value="overview" className="space-y-6">
              <div className="grid grid-cols-1 lg:grid-cols-2 gap-6">
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 10 of 22

```
                <Card>
                  <CardHeader>
                    <CardTitle>Delivery Performance Trend</CardTitle>
                    <CardDescription>Daily delivery volume over time</CardDescription>
                  </CardHeader>
                  <CardContent>
                    <DeliveryTrendChart
                      data={performanceData.map(d => ({
                        date: formatDate(d.date, 'short'),
                        deliveries: d.deliveries,
                      }))}
                      height={300}
                    />
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle>Status Distribution</CardTitle>
                    <CardDescription>Current delivery status breakdown</CardDescription>
                  </CardHeader>
                  <CardContent>
                    <StatusDistributionChart data={statusDistribution} height={300} />
                  </CardContent>
                </Card>
              </div>

              <Card>
                <CardHeader>
                  <CardTitle>Fleet Activity</CardTitle>
                  <CardDescription>Real-time fleet utilization and activity</CardDescription>
                </CardHeader>
                <CardContent>
                  <FleetActivityChart
                    data={performanceData.map(d => ({
                      date: formatDate(d.date, 'short'),
                      active: Math.floor(d.deliveries * 0.15),
                      idle: Math.floor(d.deliveries * 0.05),
                    }))}
                    height={300}
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 11 of 22

```
                    />
                  </CardContent>
                </Card>

                <div className="grid grid-cols-1 md:grid-cols-3 gap-6">
                  <Card>
                    <CardHeader>
                      <CardTitle className="text-base">Average Delivery Time</CardTitle>
                    </CardHeader>
                    <CardContent>
                      <div className="space-y-2">
                        <div className="text-3xl font-bold">{metrics.averageDeliveryTime.toFixed(1)}h</div>
                        <div className="flex items-center gap-2 text-sm text-muted-foreground">
                          <Activity className="h-4 w-4" />
                          <span>Within SLA targets</span>
                        </div>
                      </div>
                    </CardContent>
                  </Card>

                  <Card>
                    <CardHeader>
                      <CardTitle className="text-base">COD Collection</CardTitle>
                    </CardHeader>
                    <CardContent>
                      <div className="space-y-2">
                        <div className="text-3xl font-bold">{formatCurrency(revenue.codCollected)}</div>
                        <div className="flex items-center gap-2 text-sm text-chart-3">
                          <TrendingUp className="h-4 w-4" />
                          <span>+15.2% from last period</span>
                        </div>
                      </div>
                    </CardContent>
                  </Card>

                  <Card>
                    <CardHeader>
                      <CardTitle className="text-base">Failed Deliveries</CardTitle>
                    </CardHeader>
                    <CardContent>
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 12 of 22

```
                    <div className="space-y-2">
                      <div className="text-3xl font-bold">{metrics.failed}</div>
                      <div className="flex items-center gap-2 text-sm text-chart-3">
                        <TrendingDown className="h-4 w-4" />
                        <span>-12.1% from last period</span>
                      </div>
                    </div>
                  </CardContent>
                </Card>
              </div>
            </TabsContent>

            <TabsContent value="revenue" className="space-y-6">
              <div className="grid grid-cols-1 lg:grid-cols-2 gap-6">
                <Card>
                  <CardHeader>
                    <CardTitle>Revenue by Service Type</CardTitle>
                    <CardDescription>Revenue breakdown across service categories</CardDescription>
                  </CardHeader>
                  <CardContent>
                    <RevenueChart
                      data={serviceTypeRevenue.map(s => ({
                        name: s.serviceType.charAt(0).toUpperCase() + s.serviceType.slice(1),
                        revenue: s.revenue,
                      }))}
                      height={300}
                    />
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle>Revenue by Region</CardTitle>
                    <CardDescription>Geographic revenue distribution</CardDescription>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-4">
                      {regionData.map((region, index) => (
                        <div key={index} className="space-y-2">
                          <div className="flex items-center justify-between text-sm">
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 13 of 22

```
                            <span className="font-medium">{region.region}</span>
                            <span className="text-muted-foreground">{formatCurrency(region.revenue)}</span>
                          </div>
                          <ProgressMetric
                            label=""
                            value={region.revenue}
                            max={Math.max(...regionData.map(r => r.revenue))}
                            color="hsl(var(--chart-1))"
                          />
                        </div>
                      ))}
                    </div>
                  </CardContent>
                </Card>
              </div>

              <div className="grid grid-cols-1 md:grid-cols-4 gap-6">
                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Total Revenue</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <CompactMetric
                      label=""
                      value={formatCurrency(revenue.totalRevenue)}
                      icon={<DollarSign className="h-5 w-5" />}
                      color="hsl(var(--chart-1))"
                    />
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">COD Collected</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <CompactMetric
                      label=""
                      value={formatCurrency(revenue.codCollected)}
                      icon={<DollarSign className="h-5 w-5" />}
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 14 of 22

```
                      color="hsl(var(--chart-3))"
                    />
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Prepaid Revenue</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <CompactMetric
                      label=""
                      value={formatCurrency(revenue.prepaidRevenue)}
                      icon={<DollarSign className="h-5 w-5" />}
                      color="hsl(var(--chart-2))"
                    />
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Pending COD</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <CompactMetric
                      label=""
                      value={formatCurrency(revenue.pendingCod)}
                      icon={<DollarSign className="h-5 w-5" />}
                      color="hsl(var(--chart-4))"
                    />
                  </CardContent>
                </Card>
              </div>
            </TabsContent>

            <TabsContent value="drivers" className="space-y-6">
              <Card>
                <CardHeader>
                  <CardTitle>Driver Performance Metrics</CardTitle>
                  <CardDescription>
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 15 of 22

```
                    Individual driver statistics and performance indicators
                  </CardDescription>
                </CardHeader>
                <CardContent>
                  <DataTable
                    columns={driverColumns}
                    data={driverPerformance}
                    searchable
                    filterable
                    exportable
                  />
                </CardContent>
              </Card>

              <div className="grid grid-cols-1 md:grid-cols-3 gap-6">
                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Top Performer</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-2">
                      <div className="text-2xl font-bold">{driverPerformance[0]?.name}</div>
                      <div className="flex items-center gap-2 text-sm text-muted-foreground">
                        <Star className="h-4 w-4 fill-chart-4 text-chart-4" />
                        <span>{driverPerformance[0]?.rating.toFixed(1)} rating</span>
                      </div>
                    </div>
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Average Success Rate</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-2">
                      <div className="text-2xl font-bold">
                        {(
                          driverPerformance.reduce((sum, d) => sum + d.successRate, 0) /
                          driverPerformance.length
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 16 of 22

```
                        ).toFixed(1)}
                        %
                      </div>
                      <div className="flex items-center gap-2 text-sm text-chart-3">
                        <TrendingUp className="h-4 w-4" />
                        <span>Above target</span>
                      </div>
                    </div>
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Total Deliveries</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-2">
                      <div className="text-2xl font-bold">
                        {driverPerformance
                          .reduce((sum, d) => sum + d.totalDeliveries, 0)
                          .toLocaleString()}
                      </div>
                      <div className="flex items-center gap-2 text-sm text-muted-foreground">
                        <Package className="h-4 w-4" />
                        <span>All drivers combined</span>
                      </div>
                    </div>
                  </CardContent>
                </Card>
              </div>
            </TabsContent>

            <TabsContent value="warehouses" className="space-y-6">
              <Card>
                <CardHeader>
                  <CardTitle>Warehouse Efficiency Metrics</CardTitle>
                  <CardDescription>
                    Operational efficiency and utilization across facilities
                  </CardDescription>
                </CardHeader>
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 17 of 22

```
                <CardContent>
                  <DataTable
                    columns={warehouseColumns}
                    data={warehouseEfficiency}
                    searchable
                    exportable
                  />
                </CardContent>
              </Card>

              <div className="grid grid-cols-1 md:grid-cols-3 gap-6">
                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Total Throughput</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-2">
                      <div className="text-2xl font-bold">
                        {warehouseEfficiency
                          .reduce((sum, w) => sum + w.throughput, 0)
                          .toLocaleString()}
                      </div>
                      <div className="flex items-center gap-2 text-sm text-muted-foreground">
                        <Package className="h-4 w-4" />
                        <span>Packages per day</span>
                      </div>
                    </div>
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Average Accuracy</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-2">
                      <div className="text-2xl font-bold">
                        {(
                          warehouseEfficiency.reduce((sum, w) => sum + w.accuracy, 0) /
                          warehouseEfficiency.length
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 18 of 22

```
                        ).toFixed(1)}
                        %
                      </div>
                      <div className="flex items-center gap-2 text-sm text-chart-3">
                        <TrendingUp className="h-4 w-4" />
                        <span>Excellent performance</span>
                      </div>
                    </div>
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Average Utilization</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-2">
                      <div className="text-2xl font-bold">
                        {(
                          warehouseEfficiency.reduce((sum, w) => sum + w.utilization, 0) /
                          warehouseEfficiency.length
                        ).toFixed(0)}
                        %
                      </div>
                      <div className="flex items-center gap-2 text-sm text-muted-foreground">
                        <Activity className="h-4 w-4" />
                        <span>Capacity usage</span>
                      </div>
                    </div>
                  </CardContent>
                </Card>
              </div>
            </TabsContent>

            <TabsContent value="satisfaction" className="space-y-6">
              <div className="grid grid-cols-1 lg:grid-cols-2 gap-6">
                <Card>
                  <CardHeader>
                    <CardTitle>Customer Satisfaction Score</CardTitle>
                    <CardDescription>Overall customer feedback and ratings</CardDescription>
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 19 of 22

```
                    </CardHeader>
                    <CardContent>
                      <div className="space-y-6">
                        <div className="text-center">
                          <div className="text-6xl font-bold">4.7</div>
                          <div className="flex items-center justify-center gap-1 mt-2">
                            {[1, 2, 3, 4, 5].map(i => (
                              <Star
                                key={i}
                                className={`h-6 w-6 ${
                                  i <= 4 ? 'fill-chart-4 text-chart-4' : 'text-muted'
                                }`}
                              />
                            ))}
                          </div>
                          <p className="text-muted-foreground mt-2">Based on 1,247 reviews</p>
                        </div>

                        <div className="space-y-3">
                          {[
                            { stars: 5, count: 892, percentage: 71.5 },
                            { stars: 4, count: 245, percentage: 19.6 },
                            { stars: 3, count: 78, percentage: 6.3 },
                            { stars: 2, count: 22, percentage: 1.8 },
                            { stars: 1, count: 10, percentage: 0.8 },
                          ].map(rating => (
                            <div key={rating.stars} className="flex items-center gap-3">
                              <div className="flex items-center gap-1 w-20">
                                <span className="text-sm font-medium">{rating.stars}</span>
                                <Star className="h-3 w-3 fill-chart-4 text-chart-4" />
                              </div>
                              <ProgressMetric
                                label=""
                                value={rating.percentage}
                                max={100}
                                color="hsl(var(--chart-4))"
                              />
                              <span className="text-sm text-muted-foreground w-16 text-right">
                                {rating.count}
                              </span>
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 20 of 22

```
                        </div>
                      ))}
                    </div>
                  </div>
                </CardContent>
              </Card>

              <Card>
                <CardHeader>
                  <CardTitle>Satisfaction Trends</CardTitle>
                  <CardDescription>Customer satisfaction over time</CardDescription>
                </CardHeader>
                <CardContent>
                  <DeliveryTrendChart
                    data={performanceData.map(d => ({
                      date: formatDate(d.date, 'short'),
                      deliveries: 4.5 + Math.random() * 0.5,
                    }))}
                    height={300}
                  />
                </CardContent>
              </Card>
            </div>

            <div className="grid grid-cols-1 md:grid-cols-4 gap-6">
              <Card>
                <CardHeader>
                  <CardTitle className="text-base">Delivery Experience</CardTitle>
                </CardHeader>
                <CardContent>
                  <div className="space-y-2">
                    <div className="text-2xl font-bold">4.8/5.0</div>
                    <div className="flex items-center gap-2 text-sm text-chart-3">
                      <TrendingUp className="h-4 w-4" />
                      <span>+0.2 from last month</span>
                    </div>
                  </div>
                </CardContent>
              </Card>

```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 21 of 22

```
                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Driver Courtesy</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-2">
                      <div className="text-2xl font-bold">4.9/5.0</div>
                      <div className="flex items-center gap-2 text-sm text-chart-3">
                        <TrendingUp className="h-4 w-4" />
                        <span>Excellent feedback</span>
                      </div>
                    </div>
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Package Condition</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-2">
                      <div className="text-2xl font-bold">4.6/5.0</div>
                      <div className="flex items-center gap-2 text-sm text-muted-foreground">
                        <Activity className="h-4 w-4" />
                        <span>Good performance</span>
                      </div>
                    </div>
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Communication</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-2">
                      <div className="text-2xl font-bold">4.7/5.0</div>
                      <div className="flex items-center gap-2 text-sm text-chart-3">
                        <TrendingUp className="h-4 w-4" />
                        <span>Above average</span>
```

pages/Analytics.tsx

852 lines · 32,381 bytes · Page segment 22 of 22

```
                        </div>
                      </div>
                    </CardContent>
                  </Card>
                </div>
              </TabsContent>
            </Tabs>
          </motion.div>
        </motion.div>
      </div>
    );
  }
```

pages/BranchOfficePortal.tsx

171 lines · 10,517 bytes · Page segment 1 of 5

```
// @ts-nocheck
import { useState, useMemo } from 'react';
import { useLocation } from 'react-router-dom';
import { motion } from 'framer-motion';
import { Building2, Package, Truck, Users, BarChart3, DollarSign, TrendingUp, Activity, FileText } from 'lucide-react';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Badge } from '@/components/ui/badge';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { Input } from '@/components/ui/input';
import { mockShipments, mockEmployees, mockManifests, mockDeliveries } from '@/data/index';
import { formatDate, formatCurrency, formatWeight, calculateDeliveryMetrics } from '@/lib/index';
import { MetricCard, StatusBadge } from '@/components/Stats';
import { DataTable } from '@/components/DataTable';


export default function BranchOfficePortal() {
  const location = useLocation();
  const getInitialTab = () => {
    if (location.pathname.includes('/shipments')) return 'shipments';
    if (location.pathname.includes('/team')) return 'team';
    if (location.pathname.includes('/finance')) return 'finance';
    return 'overview';
  };
  const [activeTab, setActiveTab] = useState(getInitialTab());
  const [searchQuery, setSearchQuery] = useState('');

  const metrics = useMemo(() => calculateDeliveryMetrics(mockDeliveries), []);

  const branchShipments = useMemo(() => mockShipments.filter(s => s.branchId === 'br-001' || true), []);
  const branchEmployees = useMemo(() => mockEmployees.filter(e => e.branchId === 'br-001' || true), []);
  const branchDrivers = useMemo(() => branchEmployees.filter(e => e.role === 'driver' || e.role === 'rider'), [branchEmployees]);
  const todayShipments = useMemo(() => branchShipments.filter(s => {
    const today = new Date().toDateString();
    return new Date(s.createdAt).toDateString() === today;
  }), [branchShipments]);

  const filteredShipments = useMemo(() => {
    if (!searchQuery) return branchShipments;
    const q2 = searchQuery.toLowerCase();
```

pages/BranchOfficePortal.tsx

171 lines · 10,517 bytes · Page segment 2 of 5

```
    return branchShipments.filter(s => s.awb.toLowerCase().includes(q2) || s.recipient?.name?.toLowerCase().includes(q2) || s.status.toLowerCase().includes(q2));
  }, [branchShipments, searchQuery]);

  const shipmentColumns = [
    { id: 'awb', header: 'AWB', cell: (row) => <span className='font-mono text-sm font-medium'>{row.awb}</span> },
    { id: 'recipient', header: 'Recipient', cell: (row) => (
      <div><div className='font-medium'>{row.recipient?.name}</div><div className='text-sm text-muted-foreground'>{row.recipient?.address?.city}</div></div>
    ) },
    { id: 'serviceType', header: 'Service', cell: (row) => <Badge variant='secondary'>{row.serviceType?.replace('-', ' ')}</Badge> },
    { id: 'status', header: 'Status', cell: (row) => <StatusBadge status={row.status} size='sm' /> },
    { id: 'createdAt', header: 'Date', sortable: true, cell: (row) => formatDate(row.createdAt, 'date') },
  ];

  const teamColumns = [
    { id: 'name', header: 'Employee', cell: (row) => (
      <div><div className='font-medium'>{row.name}</div><div className='text-sm text-muted-foreground'>{row.employeeNumber}</div></div>
    ) },
    { id: 'role', header: 'Role', cell: (row) => <Badge variant='outline'>{row.role?.replace('-', ' ')}</Badge> },
    { id: 'status', header: 'Status', cell: (row) => (
      <Badge variant={row.is_active !== false && row.status !== 'inactive' ? 'default' : 'secondary'}>{row.status || (row.is_active ? 'active' : 'inactive')}</Badge>
    ) },
    { id: 'deliveries', header: 'Deliveries', cell: (row) => row.performance?.totalDeliveries ?? 0 },
    { id: 'successRate', header: 'Success Rate', cell: (row) => <span>{((row.performance?.successRate) ?? 0).toFixed(1)}%</span> },
  ];

  const recentActivities = [
    { id: 1, type: 'delivery', message: 'Shipment delivered successfully', time: '5 mins ago', status: 'success' },
    { id: 2, type: 'pickup', message: 'New pickup request from Merchant', time: '12 mins ago', status: 'pending' },
    { id: 3, type: 'route', message: 'Route optimization completed for Zone A', time: '25 mins ago', status: 'success' },
    { id: 4, type: 'issue', message: 'Delivery delay reported', time: '1 hour ago', status: 'warning' },
    { id: 5, type: 'cod', message: 'COD collection of MMK 125,000 recorded', time: '2 hours ago', status: 'success' },
  ];

  return (
    <div className='space-y-6'>
      <div className='flex items-center justify-between'>
        <div>
```

pages/BranchOfficePortal.tsx

171 lines · 10,517 bytes · Page segment 3 of 5

```
          <h1 className='text-3xl font-bold flex items-center gap-3'>
            <Building2 className='w-8 h-8 text-primary' />Branch Office Portal
          </h1>
          <p className='text-muted-foreground mt-1'>Complete branch operations</p>
        </div>
      </div>
      <Tabs value={activeTab} onValueChange={setActiveTab}>
        <TabsList className='grid w-full grid-cols-4'>
          <TabsTrigger value='overview'>Overview</TabsTrigger>
          <TabsTrigger value='shipments'>Shipments</TabsTrigger>
          <TabsTrigger value='team'>Team</TabsTrigger>
          <TabsTrigger value='finance'>Finance</TabsTrigger>
        </TabsList>
        <TabsContent value='overview' className='space-y-4'>
          <div className='grid gap-4 md:grid-cols-4'>
            <MetricCard title='Deliveries Today' value={branchShipments.filter(s=>s.status===='delivered').length} icon={<Package className='w-5 h-5' />} />
            <MetricCard title='Active Drivers' value={branchDrivers.length} icon={<Truck className='w-5 h-5' />} />
            <MetricCard title='Success Rate' value={metrics.successRate.toFixed(1)+'%'} icon={<TrendingUp className='w-5 h-5' />} />
            <MetricCard title='Total Shipments' value={branchShipments.length} icon={<Activity className='w-5 h-5' />} />
          </div>
          <div className='grid gap-4 md:grid-cols-2'>
            <Card>
              <CardHeader><CardTitle>Recent Activity</CardTitle></CardHeader>
              <CardContent className='space-y-3'>
                {recentActivities.map(act => (
                  <div key={act.id} className='flex items-start gap-3 p-3 border rounded-lg'>
                    <div className={['w-2 h-2 rounded-full mt-2',act.status===='success'?'bg-green-500':'bg-yellow-500'].join(' ')} />
                    <div><p className='text-sm font-medium'>{act.message}</p><p className='text-xs text-muted-foreground'>{act.time}</p></div>
                  </div>
                ))}
              </CardContent>
            </Card>
            <Card>
              <CardHeader><CardTitle>Status Breakdown</CardTitle></CardHeader>
              <CardContent className='space-y-3'>
                {['delivered','in-transit','pending','failed'].map(st => {
                  const cnt = branchShipments.filter(s=>s.status===st).length;
                  const pct = branchShipments.length>0?Math.round(cnt/branchShipments.length*100):0;
                  return (<div key={st}><div className='flex justify-between text-sm mb-1'><span className='capitalize'>{st.replace('-',' ')}</s
```

pages/BranchOfficePortal.tsx

171 lines · 10,517 bytes · Page segment 4 of 5

```
pan><span>{cnt} ({pct}%)</span></div><div className='w-full bg-muted rounded-full h-2'><div className='bg-primary h-2 rounded-full' style={{widt
h:pct+'%'}} /></div></div>);
                })}
              </CardContent>
            </Card>
          </div>
        </TabsContent>
        <TabsContent value='shipments' className='space-y-4'>
          <Card>
            <CardHeader>
              <div className='flex items-center justify-between'>
                <CardTitle>All Shipments</CardTitle>
                <Input placeholder='Search by AWB or recipient...' value={searchQuery} onChange={e=>setSearchQuery(e.target.value)} className='w
-64' />
              </div>
            </CardHeader>
            <CardContent>
              <DataTable data={filteredShipments} columns={shipmentColumns} searchable={false} />
            </CardContent>
          </Card>
        </TabsContent>

        <TabsContent value='team' className='space-y-4'>
          <div className='grid gap-4 md:grid-cols-3 mb-4'>
            <MetricCard title='Total Staff' value={branchEmployees.length} icon={<Users className='w-5 h-5' />} />
            <MetricCard title='Active Drivers' value={branchDrivers.length} icon={<Truck className='w-5 h-5' />} />
            <MetricCard title='On Duty' value={branchDrivers.filter(d=>d.status!=='inactive').length} icon={<Activity className='w-5 h-5' />} />
          </div>
          <Card>
            <CardHeader><CardTitle>Team Members</CardTitle><CardDescription>All branch staff and performance</CardDescription></CardHeader>
            <CardContent>
              <DataTable data={branchEmployees} columns={teamColumns} />
            </CardContent>
          </Card>
        </TabsContent>

        <TabsContent value='finance' className='space-y-4'>
          <div className='grid gap-4 md:grid-cols-3'>
            <Card><CardHeader><CardTitle className='text-base'>COD Collections</CardTitle></CardHeader><CardContent><div className='text-3xl fon
t-bold'>MMK 45,230</div><p className='text-sm text-muted-foreground mt-2'>Today total</p></CardContent></Card>
```

pages/BranchOfficePortal.tsx

171 lines · 10,517 bytes · Page segment 5 of 5

```
            <Card><CardHeader><CardTitle className='text-base'>Pending Payments</CardTitle></CardHeader><CardContent><div className='text-3xl fo
nt-bold'>MMK 8,450</div><p className='text-sm text-muted-foreground mt-2'>23 transactions</p></CardContent></Card>
            <Card><CardHeader><CardTitle className='text-base'>Monthly Revenue</CardTitle></CardHeader><CardContent><div className='text-3xl fon
t-bold'>MMK 1.2M</div><p className='text-sm text-green-600 mt-2'>+22% from last month</p></CardContent></Card>
          </div>
          <Card>
            <CardHeader><CardTitle>Payment Breakdown</CardTitle></CardHeader>
            <CardContent className='space-y-4'>
              {[{type:'COD',amount:'MMK 12,500',count:23},{type:'Prepaid',amount:'MMK 32,730',count:89},{type:'Credit',amount:'MMK 5,200',count:
12}].map(p=>(
                <div key={p.type} className='flex items-center justify-between p-3 border rounded-lg'>
                  <div><p className='font-medium'>{p.type}</p><p className='text-sm text-muted-foreground'>{p.count} shipments</p></div>
                  <span className='text-lg font-bold'>{p.amount}</span>
                </div>
              ))}
            </CardContent>
          </Card>
        </TabsContent>
      </Tabs>
    </div>
  );
}
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 1 of 11

```
import { useState } from 'react';
import { useNavigate } from 'react-router-dom';
import { motion } from 'framer-motion';
import { Package, Upload, CheckCircle, ArrowRight, ArrowLeft } from 'lucide-react';
import { Button } from '@/components/ui/button';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { DeliveryForm } from '@/components/Forms';
import { MetricCard, CompactMetric } from '@/components/Stats';
import { ROUTE_PATHS, generateAWB, type Shipment } from '@/lib/index';
import { springPresets, fadeInUp, staggerContainer, staggerItem } from '@/lib/motion';
import { IMAGES } from '@/assets/images';

type FormStep = 'details' | 'review' | 'success';

export default function CreateDelivery() {
  const navigate = useNavigate();
  const [currentStep, setCurrentStep] = useState<FormStep>('details');
  const [formData, setFormData] = useState<Partial<Shipment> | null>(null);
  const [awbNumber, setAwbNumber] = useState<string>('');

  const handleFormSubmit = (data: any) => {
    setFormData(data);
    setCurrentStep('review');
  };

  const handleConfirmDelivery = () => {
    const newAwb = generateAWB();
    setAwbNumber(newAwb);
    setCurrentStep('success');

    setTimeout(() => {
      navigate(ROUTE_PATHS.DASHBOARD);
    }, 3000);
  };

  const handleBackToForm = () => {
    setCurrentStep('details');
  };

  const handleCreateAnother = () => {
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 2 of 11

```
    setCurrentStep('details');
    setFormData(null);
    setAwbNumber('');
  };

  const steps = [
    { id: 'details', label: 'Delivery Details', icon: Package },
    { id: 'review', label: 'Review & Confirm', icon: CheckCircle },
  ];

  const currentStepIndex = steps.findIndex(s => s.id === currentStep);

  return (
    <div className="min-h-screen bg-background">
      {/* Hero Section */}
      <div className="relative bg-gradient-to-br from-primary/10 via-background to-accent/5 border-b border-border">
        <div className="absolute inset-0 opacity-30">
          <img
            src={IMAGES.SCREENSHOT_1487_2}
            alt="Delivery Background"
            className="w-full h-full object-cover"
          />
        </div>
        <div className="absolute inset-0 bg-gradient-to-b from-background/50 via-transparent to-background/70" />

        <div className="relative max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-12">
          <motion.div
            initial={{ opacity: 0, y: 24 }}
            animate={{ opacity: 1, y: 0 }}
            transition={springPresets.gentle}
          >
            <h1 className="text-4xl font-bold text-foreground mb-3">
              Create New Delivery
            </h1>
            <p className="text-lg text-muted-foreground max-w-2xl">
              Fill in the delivery details below to create a new shipment. You can also upload bulk deliveries via CSV.
            </p>
          </motion.div>

          {/* Quick Stats */}
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 3 of 11

```
          <motion.div
            variants={staggerContainer}
            initial="hidden"
            animate="visible"
            className="grid grid-cols-1 md:grid-cols-3 gap-4 mt-8"
          >
            <motion.div variants={staggerItem}>
              <CompactMetric
                label="Today's Deliveries"
                value={47}
                icon={<Package className="w-4 h-4" />}
                color="text-primary"
              />
            </motion.div>
            <motion.div variants={staggerItem}>
              <CompactMetric
                label="Pending Pickup"
                value={12}
                icon={<Package className="w-4 h-4" />}
                color="text-chart-4"
              />
            </motion.div>
            <motion.div variants={staggerItem}>
              <CompactMetric
                label="In Transit"
                value={35}
                icon={<Package className="w-4 h-4" />}
                color="text-accent"
              />
            </motion.div>
          </motion.div>
        </div>
      </div>

      {/* Main Content */}
      <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-8">
        {currentStep !== 'success' && (
          <motion.div
            initial={{ opacity: 0, y: 12 }}
            animate={{ opacity: 1, y: 0 }}
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 4 of 11

```
            transition={springPresets.gentle}
            className="mb-8"
          >
            {/* Step Indicator */}
            <div className="flex items-center justify-center space-x-4">
              {steps.map((step, index) => {
                const StepIcon = step.icon;
                const isActive = index === currentStepIndex;
                const isCompleted = index < currentStepIndex;

                return (
                  <div key={step.id} className="flex items-center">
                    <div
                      className={`flex items-center space-x-3 px-4 py-2 rounded-lg transition-all ${
                        isActive
                          ? 'bg-primary text-primary-foreground'
                          : isCompleted
                          ? 'bg-chart-3 text-white'
                          : 'bg-muted text-muted-foreground'
                      }`}
                    >
                      <StepIcon className="w-5 h-5" />
                      <span className="font-medium">{step.label}</span>
                    </div>
                    {index < steps.length - 1 && (
                      <ArrowRight className="w-5 h-5 mx-2 text-muted-foreground" />
                    )}
                  </div>
                );
              })}
            </div>
          </motion.div>
        )}

        {/* Form Step */}
        {currentStep === 'details' && (
          <motion.div
            variants={fadeInUp}
            initial="initial"
            animate="animate"
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 5 of 11

```
            transition={springPresets.gentle}
          >
            <Card className="shadow-lg">
              <CardHeader>
                <CardTitle>Delivery Information</CardTitle>
                <CardDescription>
                  Enter sender and recipient details, package information, and service preferences
                </CardDescription>
              </CardHeader>
              <CardContent>
                <DeliveryForm onSubmit={handleFormSubmit} defaultValues={formData} />
              </CardContent>
            </Card>

            {/* Bulk Upload Option */}
            <motion.div
              initial={{ opacity: 0, y: 12 }}
              animate={{ opacity: 1, y: 0 }}
              transition={{ ...springPresets.gentle, delay: 0.2 }}
              className="mt-6"
            >
              <Card className="border-dashed border-2 hover:border-primary transition-colors">
                <CardContent className="flex items-center justify-between p-6">
                  <div className="flex items-center space-x-4">
                    <div className="p-3 bg-accent rounded-lg">
                      <Upload className="w-6 h-6 text-accent-foreground" />
                    </div>
                    <div>
                      <h3 className="font-semibold text-foreground">Bulk Upload</h3>
                      <p className="text-sm text-muted-foreground">
                        Upload multiple deliveries at once using CSV file
                      </p>
                    </div>
                  </div>
                  <Button variant="outline" size="lg">
                    <Upload className="w-4 h-4 mr-2" />
                    Upload CSV
                  </Button>
                </CardContent>
              </Card>
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 6 of 11

```
            </motion.div>
          </motion.div>
        )}

        {/* Review Step */}
        {currentStep === 'review' && formData && (
          <motion.div
            variants={fadeInUp}
            initial="initial"
            animate="animate"
            transition={springPresets.gentle}
          >
            <Card className="shadow-lg">
              <CardHeader>
                <CardTitle>Review Delivery Details</CardTitle>
                <CardDescription>
                  Please review the information below before confirming the delivery
                </CardDescription>
              </CardHeader>
              <CardContent className="space-y-6">
                {/* Sender Information */}
                <div>
                  <h3 className="text-lg font-semibold text-foreground mb-3">Sender Information</h3>
                  <div className="grid grid-cols-1 md:grid-cols-2 gap-4 p-4 bg-muted/50 rounded-lg">
                    <div>
                      <p className="text-sm text-muted-foreground">Name</p>
                      <p className="font-medium text-foreground">{formData.sender?.name}</p>
                    </div>
                    <div>
                      <p className="text-sm text-muted-foreground">Phone</p>
                      <p className="font-medium text-foreground">{formData.sender?.phone}</p>
                    </div>
                    <div className="md:col-span-2">
                      <p className="text-sm text-muted-foreground">Address</p>
                      <p className="font-medium text-foreground">
                        {formData.sender?.address.street}, {formData.sender?.address.city},{' '}
                        {formData.sender?.address.state} {formData.sender?.address.postalCode}
                      </p>
                    </div>
                  </div>
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 7 of 11

```
                </div>

                {/* Recipient Information */}
                <div>
                  <h3 className="text-lg font-semibold text-foreground mb-3">Recipient Information</h3>
                  <div className="grid grid-cols-1 md:grid-cols-2 gap-4 p-4 bg-muted/50 rounded-lg">
                    <div>
                      <p className="text-sm text-muted-foreground">Name</p>
                      <p className="font-medium text-foreground">{formData.recipient?.name}</p>
                    </div>
                    <div>
                      <p className="text-sm text-muted-foreground">Phone</p>
                      <p className="font-medium text-foreground">{formData.recipient?.phone}</p>
                    </div>
                    <div className="md:col-span-2">
                      <p className="text-sm text-muted-foreground">Address</p>
                      <p className="font-medium text-foreground">
                        {formData.recipient?.address.street}, {formData.recipient?.address.city},{' '}
                        {formData.recipient?.address.state} {formData.recipient?.address.postalCode}
                      </p>
                    </div>
                  </div>
                </div>

                {/* Package Details */}
                <div>
                  <h3 className="text-lg font-semibold text-foreground mb-3">Package Details</h3>
                  <div className="grid grid-cols-1 md:grid-cols-3 gap-4 p-4 bg-muted/50 rounded-lg">
                    <div>
                      <p className="text-sm text-muted-foreground">Weight</p>
                      <p className="font-medium text-foreground">{formData.packageDetails?.weight} kg</p>
                    </div>
                    <div>
                      <p className="text-sm text-muted-foreground">Dimensions</p>
                      <p className="font-medium text-foreground">
                        {formData.packageDetails?.dimensions.length} x{' '}
                        {formData.packageDetails?.dimensions.width} x{' '}
                        {formData.packageDetails?.dimensions.height} cm
                      </p>
                    </div>
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 8 of 11

```
                    <div>
                      <p className="text-sm text-muted-foreground">Value</p>
                      <p className="font-medium text-foreground">MMK {formData.packageDetails?.value?.toLocaleString()}</p>
                    </div>
                    <div className="md:col-span-3">
                      <p className="text-sm text-muted-foreground">Description</p>
                      <p className="font-medium text-foreground">{formData.packageDetails?.description}</p>
                    </div>
                  </div>
                </div>

                {/* Service Details */}
                <div>
                  <h3 className="text-lg font-semibold text-foreground mb-3">Service Details</h3>
                  <div className="grid grid-cols-1 md:grid-cols-3 gap-4 p-4 bg-muted/50 rounded-lg">
                    <div>
                      <p className="text-sm text-muted-foreground">Service Type</p>
                      <p className="font-medium text-foreground capitalize">
                        {formData.serviceType?.replace('-', ' ')}
                      </p>
                    </div>
                    <div>
                      <p className="text-sm text-muted-foreground">Payment Method</p>
                      <p className="font-medium text-foreground uppercase">{formData.paymentMethod}</p>
                    </div>
                    {formData.codAmount && (
                      <div>
                        <p className="text-sm text-muted-foreground">COD Amount</p>
                        <p className="font-medium text-foreground">MMK {formData.codAmount.toLocaleString()}</p>
                      </div>
                    )}
                  </div>
                </div>

                {formData.specialInstructions && (
                  <div>
                    <h3 className="text-lg font-semibold text-foreground mb-3">Special Instructions</h3>
                    <div className="p-4 bg-muted/50 rounded-lg">
                      <p className="text-foreground">{formData.specialInstructions}</p>
                    </div>
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 9 of 11

```
                  </div>
                )}

                {/* Action Buttons */}
                <div className="flex items-center justify-between pt-6 border-t border-border">
                  <Button
                    variant="outline"
                    size="lg"
                    onClick={handleBackToForm}
                  >
                    <ArrowLeft className="w-4 h-4 mr-2" />
                    Back to Edit
                  </Button>
                  <Button
                    size="lg"
                    onClick={handleConfirmDelivery}
                  >
                    Confirm & Create Delivery
                    <ArrowRight className="w-4 h-4 ml-2" />
                  </Button>
                </div>
              </CardContent>
            </Card>
          </motion.div>
        )}

        {/* Success Step */}
        {currentStep === 'success' && (
          <motion.div
            initial={{ opacity: 0, scale: 0.95 }}
            animate={{ opacity: 1, scale: 1 }}
            transition={springPresets.bouncy}
            className="flex items-center justify-center min-h-[60vh]"
          >
            <Card className="max-w-2xl w-full shadow-2xl">
              <CardContent className="p-12 text-center">
                <motion.div
                  initial={{ scale: 0 }}
                  animate={{ scale: 1 }}
                  transition={{ ...springPresets.bouncy, delay: 0.2 }}
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 10 of 11

```
                  className="inline-flex items-center justify-center w-24 h-24 bg-chart-3 rounded-full mb-6"
                >
                  <CheckCircle className="w-12 h-12 text-white" />
                </motion.div>

                <motion.h2
                  initial={{ opacity: 0, y: 12 }}
                  animate={{ opacity: 1, y: 0 }}
                  transition={{ ...springPresets.gentle, delay: 0.3 }}
                  className="text-3xl font-bold text-foreground mb-3"
                >
                  Delivery Created Successfully!
                </motion.h2>

                <motion.p
                  initial={{ opacity: 0, y: 12 }}
                  animate={{ opacity: 1, y: 0 }}
                  transition={{ ...springPresets.gentle, delay: 0.4 }}
                  className="text-lg text-muted-foreground mb-8"
                >
                  Your delivery has been created and is ready for processing.
                </motion.p>

                <motion.div
                  initial={{ opacity: 0, y: 12 }}
                  animate={{ opacity: 1, y: 0 }}
                  transition={{ ...springPresets.gentle, delay: 0.5 }}
                  className="p-6 bg-muted/50 rounded-lg mb-8"
                >
                  <p className="text-sm text-muted-foreground mb-2">AWB Number</p>
                  <p className="text-2xl font-bold text-primary">{awbNumber}</p>
                </motion.div>

                <motion.div
                  initial={{ opacity: 0, y: 12 }}
                  animate={{ opacity: 1, y: 0 }}
                  transition={{ ...springPresets.gentle, delay: 0.6 }}
                  className="flex items-center justify-center space-x-4"
                >
                  <Button
```

pages/CreateDelivery.tsx

421 lines · 17,495 bytes · Page segment 11 of 11

```
                      variant="outline"
                      size="lg"
                      onClick={handleCreateAnother}
                    >
                      Create Another
                    </Button>
                    <Button
                      size="lg"
                      onClick={() => navigate(ROUTE_PATHS.DASHBOARD)}
                    >
                      Go to Dashboard
                    </Button>
                  </motion.div>
                </CardContent>
              </Card>
            </motion.div>
          )}
        </div>
      </div>
    );
  }
```

pages/CustomerPortal.tsx

347 lines · 16,786 bytes · Page segment 1 of 9

```
import { useState } from 'react';
import { useLocation } from 'react-router-dom';
import { motion } from 'framer-motion';
import {
  ShoppingBag, Package, MapPin, Headphones, Search,
  RefreshCw, CheckCircle, Clock, AlertTriangle, Eye, Star
} from 'lucide-react';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { shipmentsAPI, complaintsAPI } from '@/api/supabase';
import { useQuery } from '@/hooks/useSupabaseQuery';
import { useAuth } from '@/hooks/useAuth';
import { formatDate } from '@/lib/index';
import { useToast } from '@/hooks/use-toast';

export default function CustomerPortal() {
  const location = useLocation();
  const getInitialCustTab = () => {
    if (location.pathname.includes('/track')) return 'tracking';
    if (location.pathname.includes('/orders')) return 'history';
    if (location.pathname.includes('/support')) return 'support';
    return 'tracking';
  };
  const [activeTab, setActiveTab] = useState(getInitialCustTab());
  const [trackingAWB, setTrackingAWB] = useState('');
  const [trackedShipment, setTrackedShipment] = useState<any>(null);
  const [isTracking, setIsTracking] = useState(false);
  const { user } = useAuth();
  const { toast } = useToast();

  // Customer sees their own shipments (as sender or recipient by phone/email)
  const { data: shipmentData, isLoading, refetch } = useQuery(() =>
    shipmentsAPI.getAll()
  );
  const { data: complaintData } = useQuery(() =>
    complaintsAPI.getAll()
  );

```

pages/CustomerPortal.tsx

347 lines · 16,786 bytes · Page segment 2 of 9

```
41  const shipments = (shipmentData as any[]) || [];
42  const complaints = (complaintData as any[]) || [];
43
44  const delivered = shipments.filter((s: any) => s.status === 'delivered').length;
45  const inTransit = shipments.filter((s: any) => s.status?.includes('transit')).length;
46  const pending = shipments.filter((s: any) => s.status === 'pending').length;
47
48  const handleTrack = async () => {
49    if (!trackingAWB.trim()) return;
50    setIsTracking(true);
51    try {
52      const s = await shipmentsAPI.getByAWB(trackingAWB.trim());
53      setTrackedShipment(s);
54    } catch {
55      toast({
56        title: 'Shipment not found',
57        description: `No shipment found with AWB: ${trackingAWB}`,
58        variant: 'destructive',
59      });
60      setTrackedShipment(null);
61    } finally {
62      setIsTracking(false);
63    }
64  };
65
66  const statusSteps = [
67    { label: 'Order Placed', icon: <ShoppingBag className="w-5 h-5" />, statuses: ['pending', 'processing'] },
68    { label: 'Picked Up', icon: <Package className="w-5 h-5" />, statuses: ['picked_up', 'in_warehouse'] },
69    { label: 'In Transit', icon: <Clock className="w-5 h-5" />, statuses: ['in_transit', 'out_for_delivery'] },
70    { label: 'Delivered', icon: <CheckCircle className="w-5 h-5" />, statuses: ['delivered'] },
71  ];
72
73  const getStepIndex = (status: string) => {
74    if (!status) return 0;
75    for (let i = 0; i < statusSteps.length; i++) {
76      if (statusSteps[i].statuses.some((s) => status.includes(s.replace('_', '')))) return i;
77    }
78    return 0;
79  };
80
```

pages/CustomerPortal.tsx

347 lines · 16,786 bytes · Page segment 3 of 9

```
  return (
    <div className="min-h-screen bg-background">
      {/* Header */}
      <div className="bg-gradient-to-br from-primary/10 via-background to-accent/10 border-b px-6 py-8">
        <div className="flex items-center justify-between">
          <div>
            <h1 className="text-3xl font-bold flex items-center gap-2">
              <ShoppingBag className="w-8 h-8 text-primary" />
              Customer Portal
            </h1>
            <p className="text-muted-foreground mt-1">
              Welcome, {user?.name || user?.email} — Track your deliveries and get support
            </p>
          </div>
          <Button variant="outline" onClick={refetch}>
            <RefreshCw className="w-4 h-4 mr-2" />
            Refresh
          </Button>
        </div>
      </div>

      <div className="p-6 space-y-6">
        {/* Quick Stats */}
        <div className="grid grid-cols-3 gap-4">
          {[
            { label: 'Delivered', value: delivered, icon: <CheckCircle className="w-4 h-4" />, color: 'text-green-600' },
            { label: 'In Transit', value: inTransit, icon: <Clock className="w-4 h-4" />, color: 'text-blue-600' },
            { label: 'Pending', value: pending, icon: <AlertTriangle className="w-4 h-4" />, color: 'text-yellow-600' },
          ].map((kpi, i) => (
            <motion.div key={i} whileHover={{ scale: 1.02 }}>
              <Card>
                <CardContent className="p-4">
                  <div className={`flex items-center gap-2 mb-1 ${kpi.color}`}>
                    {kpi.icon}
                    <span className="text-xs text-muted-foreground">{kpi.label}</span>
                  </div>
                  <div class="text-2xl font-bold">{kpi.value}</div>
                </CardContent>
              </Card>
            </motion.div>
```

pages/CustomerPortal.tsx

347 lines · 16,786 bytes · Page segment 4 of 9

```
          ))}
        </div>

        <Tabs value={activeTab} onValueChange={setActiveTab}>
          <TabsList>
            <TabsTrigger value="tracking">
              <MapPin className="w-4 h-4 mr-2" />
              Track Shipment
            </TabsTrigger>
            <TabsTrigger value="history">
              <Package className="w-4 h-4 mr-2" />
              Shipment History
            </TabsTrigger>
            <TabsTrigger value="support">
              <Headphones className="w-4 h-4 mr-2" />
              Support
            </TabsTrigger>
          </TabsList>

          {/* Tracking Tab */}
          <TabsContent value="tracking" className="mt-4">
            <Card>
              <CardHeader>
                <CardTitle>Track Your Shipment</CardTitle>
                <CardDescription>Enter your AWB or tracking number to see real-time status</CardDescription>
              </CardHeader>
              <CardContent>
                <div className="flex gap-2 mb-6">
                  <Input
                    placeholder="Enter AWB number (e.g. BX-2026-00001)"
                    className="flex-1 text-lg"
                    value={trackingAWB}
                    onChange={(e) => setTrackingAWB(e.target.value)}
                    onKeyDown={(e) => e.key === 'Enter' && handleTrack()}
                  />
                  <Button size="lg" onClick={handleTrack} disabled={isTracking}>
                    <Search className="w-4 h-4 mr-2" />
                    {isTracking ? 'Searching...' : 'Track'}
                  </Button>
                </div>
```

pages/CustomerPortal.tsx

347 lines · 16,786 bytes · Page segment 5 of 9

```

                  {trackedShipment ? (
                    <div className="space-y-6">
                      {/* Status Progress */}
                      <div className="p-6 bg-primary/5 border border-primary/20 rounded-xl">
                        <div className="flex items-center justify-between mb-6">
                          <div>
                            <p className="font-mono font-bold text-xl text-primary">{trackedShipment.awb}</p>
                            <p className="text-sm text-muted-foreground">
                              Estimated: {trackedShipment.estimated_delivery ? formatDate(trackedShipment.estimated_delivery, 'short') : 'TBD'}
                            </p>
                          </div>
                          <span className={`px-4 py-1.5 rounded-full font-semibold text-sm ${
                            trackedShipment.status === 'delivered' ? 'bg-green-100 text-green-800' :
                            trackedShipment.status?.includes('transit') ? 'bg-blue-100 text-blue-800' :
                            'bg-yellow-100 text-yellow-800'
                          }`}>
                            {(trackedShipment.status || 'pending').replace(/_/g, ' ').toUpperCase()}
                          </span>
                        </div>

                        {/* Step tracker */}
                        <div className="flex items-center justify-between relative">
                          <div className="absolute left-0 right-0 h-0.5 bg-muted top-5 z-0" />
                          <div
                            className="absolute left-0 h-0.5 bg-primary top-5 z-0 transition-all"
                            style={{ width: `${(getStepIndex(trackedShipment.status) / (statusSteps.length - 1)) * 100}%` }}
                          />
                          {statusSteps.map((step, i) => {
                            const stepIndex = getStepIndex(trackedShipment.status);
                            const isCompleted = i <= stepIndex;
                            return (
                              <div key={step.label} className="flex flex-col items-center z-10 gap-2">
                                <div className={`w-10 h-10 rounded-full flex items-center justify-center border-2 transition-all ${
                                  isCompleted ? 'bg-primary border-primary text-white' : 'bg-background border-muted text-muted-foreground'
                                }`}>
                                  {step.icon}
                                </div>
                                <span className={`text-xs font-medium text-center max-w-16 ${isCompleted ? 'text-primary' : 'text-muted-foreground
'}`}>
```

pages/CustomerPortal.tsx

347 lines · 16,786 bytes · Page segment 6 of 9

```
                                {step.label}
                              </span>
                            </div>
                          );
                        })}
                      </div>
                    </div>

                    {/* Shipment Details */}
                    <div className="grid md:grid-cols-2 gap-4">
                      <div className="p-4 border rounded-lg">
                        <p className="text-sm font-medium text-muted-foreground mb-2">Sender</p>
                        <p className="font-medium">{trackedShipment.sender_name || trackedShipment.sender?.name || '-'}</p>
                        <p className="text-sm text-muted-foreground">{trackedShipment.sender_city || trackedShipment.sender?.address?.city || '-'}</p>
                      </div>
                      <div className="p-4 border rounded-lg">
                        <p className="text-sm font-medium text-muted-foreground mb-2">Recipient</p>
                        <p className="font-medium">{trackedShipment.recipient_name || trackedShipment.recipient?.name || '-'}</p>
                        <p className="text-sm text-muted-foreground">{trackedShipment.recipient_city || trackedShipment.recipient?.address?.city || '-'}</p>
                      </div>
                    </div>
                  </div>
                ) : (
                  <div className="text-center py-12 text-muted-foreground">
                    <MapPin className="w-12 h-12 mx-auto mb-2 opacity-20" />
                    <p>Enter your AWB number above to track your package</p>
                  </div>
                )}
              </CardContent>
            </Card>
          </TabsContent>

          {/* History Tab */}
          <TabsContent value="history" className="mt-4">
            <Card>
              <CardHeader>
                <CardTitle>Shipment History</CardTitle>
                <CardDescription>All your past and current deliveries</CardDescription>
```

pages/CustomerPortal.tsx

347 lines · 16,786 bytes · Page segment 7 of 9

```
              </CardHeader>
              <CardContent>
                {isLoading ? (
                  <div className="text-center py-12 text-muted-foreground">Loading shipments...</div>
                ) : shipments.length === 0 ? (
                  <div className="text-center py-12 text-muted-foreground">
                    <Package className="w-16 h-16 mx-auto mb-3 opacity-20" />
                    <p className="text-lg font-medium">No shipments found</p>
                    <p className="text-sm">Your shipment history will appear here.</p>
                  </div>
                ) : (
                  <div className="space-y-3">
                    {shipments.slice(0, 20).map((s: any) => (
                      <motion.div
                        key={s.id}
                        className="flex items-center justify-between p-4 border rounded-lg hover:bg-muted/30"
                        whileHover={{ x: 2 }}
                      >
                        <div>
                          <p className="font-mono font-semibold text-primary">{s.awb || s.id?.slice(0, 8)}</p>
                          <p className="text-sm text-muted-foreground">
                            To: {s.recipient_name || s.recipient?.name || '-'} • {s.recipient_city || s.recipient?.address?.city || '-'}
                          </p>
                          <p className="text-xs text-muted-foreground">{s.created_at ? formatDate(s.created_at, 'short') : '-'}</p>
                        </div>
                        <div className="flex items-center gap-2">
                          <span className={`text-xs px-2 py-1 rounded-full font-medium ${
                            s.status === 'delivered' ? 'bg-green-100 text-green-800' :
                            s.status?.includes('transit') ? 'bg-blue-100 text-blue-800' :
                            'bg-yellow-100 text-yellow-800'
                          }`}>
                            {(s.status || 'pending').replace(/_/g, ' ')}
                          </span>
                          <Button size="sm" variant="outline" onClick={() => { setTrackingAWB(s.awb || ''); setActiveTab('tracking'); }}>
                            <Eye className="w-3 h-3 mr-1" />
                            Track
                          </Button>
                        </div>
                      </motion.div>
                    ))}
```

pages/CustomerPortal.tsx

347 lines · 16,786 bytes · Page segment 8 of 9

```
                  </div>
                )}
              </CardContent>
            </Card>
          </TabsContent>

          {/* Support Tab */}
          <TabsContent value="support" className="mt-4">
            <div className="grid md:grid-cols-2 gap-4">
              <Card>
                <CardHeader>
                  <CardTitle>Contact Support</CardTitle>
                  <CardDescription>Get help with your delivery issues</CardDescription>
                </CardHeader>
                <CardContent className="space-y-3">
                  <div className="p-4 bg-muted/50 rounded-lg">
                    <p className="font-medium mb-1">□ Hotline</p>
                    <p className="text-muted-foreground">+95 9 XXX-XXXXX</p>
                    <p className="text-sm text-muted-foreground">Mon-Sat, 8AM – 6PM</p>
                  </div>
                  <div className="p-4 bg-muted/50 rounded-lg">
                    <p className="font-medium mb-1">□ Email Support</p>
                    <p className="text-muted-foreground">support@britiumexpress.com</p>
                    <p className="text-sm text-muted-foreground">Response within 24 hours</p>
                  </div>
                  <Button className="w-full">
                    <Headphones className="w-4 h-4 mr-2" />
                    Submit a Complaint
                  </Button>
                </CardContent>
              </Card>

              <Card>
                <CardHeader>
                  <CardTitle>My Complaints</CardTitle>
                </CardHeader>
                <CardContent>
                  {complaints.length === 0 ? (
                    <div className="text-center py-8 text-muted-foreground">
                      <Star className="w-10 h-10 mx-auto mb-2 opacity-20" />
```

pages/CustomerPortal.tsx

347 lines · 16,786 bytes · Page segment 9 of 9

```
                        <p className="text-sm">No complaints filed. We're glad everything is going smoothly!</p>
                      </div>
                    ) : (
                      <div className="space-y-2">
                        {complaints.slice(0, 5).map((c: any) => (
                          <div key={c.id} className="p-3 border rounded-lg">
                            <p className="font-medium text-sm">{c.subject || 'Complaint'}</p>
                            <div className="flex items-center justify-between mt-1">
                              <p className="text-xs text-muted-foreground">{c.created_at ? formatDate(c.created_at, 'short') : '-'}</p>
                              <span className={`text-xs px-2 py-0.5 rounded-full ${
                                c.status === 'resolved' ? 'bg-green-100 text-green-800' :
                                c.status === 'in_progress' ? 'bg-blue-100 text-blue-800' :
                                'bg-yellow-100 text-yellow-800'
                              }`}>
                                {c.status}
                              </span>
                            </div>
                          </div>
                        ))}
                      </div>
                    )}
                  </CardContent>
                </Card>
              </div>
            </TabsContent>
          </Tabs>
        </div>
      </div>
    );
  }
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 1 of 16

```
import { useState, useMemo } from 'react';
import { useLocation } from 'react-router-dom';
import { motion } from 'framer-motion';
import {
  Search,
  Filter,
  MessageSquare,
  AlertTriangle,
  CheckCircle,
  Clock,
  Phone,
  Mail,
  User,
  Package,
  TrendingUp,
  TrendingDown,
  Send,
  Paperclip,
  MoreVertical,
} from 'lucide-react';
import {
  ROUTE_PATHS,
  Shipment,
  DeliveryStatus,
  formatStatus,
  formatDate,
  formatCurrency,
} from '@/lib/index';
import { mockShipments, mockDeliveries, mockEmployees } from '@/data/index';
import { IMAGES } from '@/assets/images';
import { MetricCard, StatusBadge, CompactMetric } from '@/components/Stats';
import { DataTable, Column } from '@/components/DataTable';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Badge } from '@/components/ui/badge';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from '@/components/ui/select';
import { Textarea } from '@/components/ui/textarea';
import { ScrollArea } from '@/components/ui/scroll-area';
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 2 of 16

```
import { Separator } from '@/components/ui/separator';
import { Avatar, AvatarFallback } from '@/components/ui/avatar';

interface CustomerRequest {
  id: string;
  type: 'inquiry' | 'complaint' | 'tracking' | 'modification';
  priority: 'low' | 'medium' | 'high' | 'urgent';
  status: 'open' | 'in-progress' | 'resolved' | 'closed';
  customer: {
    name: string;
    phone: string;
    email?: string;
  };
  subject: string;
  description: string;
  shipmentId?: string;
  assignedTo?: string;
  createdAt: string;
  updatedAt: string;
  resolvedAt?: string;
}

interface ChatMessage {
  id: string;
  sender: 'agent' | 'customer';
  message: string;
  timestamp: string;
  attachments?: string[];
}

const mockRequests: CustomerRequest[] = [
  {
    id: 'req-001',
    type: 'tracking',
    priority: 'medium',
    status: 'in-progress',
    customer: {
      name: 'Aye Aye',
      phone: '+95-9-777888999',
      email: 'aye@example.com',
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 3 of 16

```
    },
    subject: 'Where is my package?',
    description: 'I ordered a laptop 3 days ago and tracking shows in-transit. When will it arrive?',
    shipmentId: 'shp-001',
    assignedTo: 'emp-005',
    createdAt: new Date(Date.now() - 2 * 60 * 60 * 1000).toISOString(),
    updatedAt: new Date(Date.now() - 1 * 60 * 60 * 1000).toISOString(),
  },
  {
    id: 'req-002',
    type: 'complaint',
    priority: 'urgent',
    status: 'open',
    customer: {
      name: 'Win Win',
      phone: '+95-9-111222333',
    },
    subject: 'Delivery failed without attempt',
    description: 'Driver marked delivery as failed but never came to my address. This is unacceptable!',
    shipmentId: 'shp-005',
    createdAt: new Date(Date.now() - 30 * 60 * 1000).toISOString(),
    updatedAt: new Date(Date.now() - 30 * 60 * 1000).toISOString(),
  },
  {
    id: 'req-003',
    type: 'modification',
    priority: 'high',
    status: 'in-progress',
    customer: {
      name: 'Thida Thida',
      phone: '+95-9-000111222',
      email: 'thida@example.com',
    },
    subject: 'Change delivery address',
    description: 'Need to change delivery address to my office instead of home.',
    shipmentId: 'shp-004',
    assignedTo: 'emp-005',
    createdAt: new Date(Date.now() - 4 * 60 * 60 * 1000).toISOString(),
    updatedAt: new Date(Date.now() - 1 * 60 * 60 * 1000).toISOString(),
  },
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 4 of 16

```
  {
    id: 'req-004',
    type: 'inquiry',
    priority: 'low',
    status: 'resolved',
    customer: {
      name: 'Zaw Zaw',
      phone: '+95-9-999000111',
    },
    subject: 'Delivery time estimate',
    description: 'What is the estimated delivery time for standard service?',
    createdAt: new Date(Date.now() - 24 * 60 * 60 * 1000).toISOString(),
    updatedAt: new Date(Date.now() - 20 * 60 * 60 * 1000).toISOString(),
    resolvedAt: new Date(Date.now() - 20 * 60 * 60 * 1000).toISOString(),
  },
  {
    id: 'req-005',
    type: 'complaint',
    priority: 'high',
    status: 'open',
    customer: {
      name: 'Mya Mya',
      phone: '+95-9-888999000',
    },
    subject: 'Package damaged on arrival',
    description: 'Received package with visible damage. Box was crushed and contents may be affected.',
    shipmentId: 'shp-002',
    createdAt: new Date(Date.now() - 1 * 60 * 60 * 1000).toISOString(),
    updatedAt: new Date(Date.now() - 1 * 60 * 60 * 1000).toISOString(),
  },
];

const mockChatMessages: ChatMessage[] = [
  {
    id: 'msg-001',
    sender: 'customer',
    message: 'Hello, I need help tracking my package',
    timestamp: new Date(Date.now() - 10 * 60 * 1000).toISOString(),
  },
  {
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 5 of 16

```
    id: 'msg-002',
    sender: 'agent',
    message: 'Hello! I\'d be happy to help you track your package. Could you please provide your tracking number or AWB?',
    timestamp: new Date(Date.now() - 9 * 60 * 1000).toISOString(),
  },
  {
    id: 'msg-003',
    sender: 'customer',
    message: 'BRX12345001',
    timestamp: new Date(Date.now() - 8 * 60 * 1000).toISOString(),
  },
  {
    id: 'msg-004',
    sender: 'agent',
    message: 'Thank you! Let me check that for you. Your package is currently out for delivery and should arrive within the next 2 hours. The driver will call you 15 minutes before arrival.',
    timestamp: new Date(Date.now() - 7 * 60 * 1000).toISOString(),
  },
  {
    id: 'msg-005',
    sender: 'customer',
    message: 'Great! Thank you for the quick response.',
    timestamp: new Date(Date.now() - 6 * 60 * 1000).toISOString(),
  },
];

const agentMetrics = {
  totalRequests: 127,
  resolved: 98,
  pending: 29,
  averageResponseTime: '4.2 min',
  satisfactionRate: 4.8,
  activeChats: 3,
};

export default function CustomerService() {
  const [searchQuery, setSearchQuery] = useState('');
  const location = useLocation();
  const getInitialCSTab = () => {
    if (location.pathname.includes('/chat')) return 'chat';
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 6 of 16

```
    return 'requests';
  };
  const [statusFilter, setStatusFilter] = useState<string>('all');
  const [priorityFilter, setPriorityFilter] = useState<string>('all');
  const [selectedRequest, setSelectedRequest] = useState<CustomerRequest | null>(null);
  const [chatMessage, setChatMessage] = useState('');
  const [activeTab, setActiveTab] = useState(getInitialCSTab());

  const filteredRequests = useMemo(() => {
    return mockRequests.filter((request) => {
      const matchesSearch =
        searchQuery === '' ||
        request.customer.name.toLowerCase().includes(searchQuery.toLowerCase()) ||
        request.subject.toLowerCase().includes(searchQuery.toLowerCase()) ||
        request.shipmentId?.toLowerCase().includes(searchQuery.toLowerCase());

      const matchesStatus = statusFilter === 'all' || request.status === statusFilter;
      const matchesPriority = priorityFilter === 'all' || request.priority === priorityFilter;

      return matchesSearch && matchesStatus && matchesPriority;
    });
  }, [searchQuery, statusFilter, priorityFilter]);

  const urgentAlerts = mockRequests.filter(
    (r) => r.priority === 'urgent' && r.status === 'open'
  );

  const requestColumns: Column<CustomerRequest>[] = [
    {
      id: 'id',
      header: 'Request ID',
      cell: (request) => (
        <span className="font-mono text-sm">{request.id}</span>
      ),
    },
    {
      id: 'customer',
      header: 'Customer',
      cell: (request) => (
        <div>
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 7 of 16

```
          <div className="font-medium">{request.customer.name}</div>
          <div className="text-sm text-muted-foreground">{request.customer.phone}</div>
        </div>
      ),
    },
    {
      id: 'type',
      header: 'Type',
      cell: (request) => (
        <Badge variant="outline" className="capitalize">
          {request.type}
        </Badge>
      ),
    },
    {
      id: 'subject',
      header: 'Subject',
      cell: (request) => (
        <div className="max-w-xs">
          <div className="font-medium truncate">{request.subject}</div>
          <div className="text-sm text-muted-foreground truncate">
            {request.description}
          </div>
        </div>
      ),
    },
    {
      id: 'priority',
      header: 'Priority',
      cell: (request) => {
        const colors = {
          low: 'bg-muted text-muted-foreground',
          medium: 'bg-accent text-accent-foreground',
          high: 'bg-chart-4 text-white',
          urgent: 'bg-destructive text-destructive-foreground',
        };
        return (
          <Badge className={colors[request.priority]}>
            {request.priority}
          </Badge>
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 8 of 16

```
        );
      },
    },
    {
      id: 'status',
      header: 'Status',
      cell: (request) => {
        const colors = {
          open: 'bg-chart-4 text-white',
          'in-progress': 'bg-primary text-primary-foreground',
          resolved: 'bg-chart-3 text-white',
          closed: 'bg-muted text-muted-foreground',
        };
        return (
          <Badge className={colors[request.status]}>
            {request.status}
          </Badge>
        );
      },
    },
    {
      id: 'createdAt',
      header: 'Created',
      cell: (request) => (
        <span className="text-sm">{formatDate(request.createdAt, 'datetime')}</span>
      ),
    },
  ];

  const handleSendMessage = () => {
    if (chatMessage.trim()) {
      console.log('Sending message:', chatMessage);
      setChatMessage('');
    }
  };

  return (
    <div className="min-h-screen bg-background relative">
      <div
        className="absolute inset-0 z-0 opacity-30"
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 9 of 16

```
          style={{
            backgroundImage: `url(${IMAGES.SCREENSHOT_1095_2})`,
            backgroundSize: 'cover',
            backgroundPosition: 'center',
          }}
        />
        <div className="absolute inset-0 bg-gradient-to-b from-background/50 via-transparent to-background/70" />

        <div className="relative z-10 p-6">
        <motion.div
          initial={{ opacity: 0, y: 20 }}
          animate={{ opacity: 1, y: 0 }}
          transition={{ duration: 0.3 }}
        >
          <div className="mb-6">
            <h1 className="text-3xl font-bold tracking-tight">Customer Service Portal</h1>
            <p className="text-muted-foreground mt-1">
              Manage customer inquiries, complaints, and support requests
            </p>
          </div>

          <div className="grid grid-cols-1 lg:grid-cols-4 gap-4 mb-6">
            <MetricCard
              title="Total Requests"
              value={agentMetrics.totalRequests}
              icon={<MessageSquare className="h-5 w-5" />}
              trend={8.2}
            />
            <MetricCard
              title="Resolved Today"
              value={agentMetrics.resolved}
              icon={<CheckCircle className="h-5 w-5" />}
              trend={12.5}
            />
            <MetricCard
              title="Pending"
              value={agentMetrics.pending}
              icon={<Clock className="h-5 w-5" />}
              trend={-5.3}
            />
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 10 of 16

```
360           <MetricCard
361             title="Satisfaction Rate"
362             value={`${agentMetrics.satisfactionRate}/5.0`}
363             icon={<TrendingUp className="h-5 w-5" />}
364             trend={3.1}
365           />
366         </div>
367
368         {urgentAlerts.length > 0 && (
369           <motion.div
370             initial={{ opacity: 0, scale: 0.95 }}
371             animate={{ opacity: 1, scale: 1 }}
372             className="mb-6"
373           >
374             <Card className="border-destructive bg-destructive/5">
375               <CardHeader>
376                 <CardTitle className="flex items-center gap-2 text-destructive">
377                   <AlertTriangle className="h-5 w-5" />
378                   Urgent Alerts ({urgentAlerts.length})
379                 </CardTitle>
380               </CardHeader>
381               <CardContent>
382                 <div className="space-y-3">
383                   {urgentAlerts.map((alert) => (
384                     <div
385                       key={alert.id}
386                       className="flex items-start justify-between p-3 bg-background rounded-lg border"
387                     >
388                       <div className="flex-1">
389                         <div className="font-medium">{alert.subject}</div>
390                         <div className="text-sm text-muted-foreground mt-1">
391                           {alert.customer.name} • {formatDate(alert.createdAt, 'time')}
392                         </div>
393                       </div>
394                       <Button size="sm" variant="destructive">
395                         Handle Now
396                       </Button>
397                     </div>
398                   ))}
399                 </div>
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 11 of 16

```
              </CardContent>
            </Card>
          </motion.div>
        )}

        <div className="grid grid-cols-1 lg:grid-cols-3 gap-6">
          <div className="lg:col-span-2">
            <Card>
              <CardHeader>
                <div className="flex items-center justify-between">
                  <div>
                    <CardTitle>Customer Requests</CardTitle>
                    <CardDescription>Search and manage support requests</CardDescription>
                  </div>
                </div>
              </CardHeader>
              <CardContent>
                <div className="space-y-4">
                  <div className="flex gap-2">
                    <div className="relative flex-1">
                      <Search className="absolute left-3 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
                      <Input
                        placeholder="Search by customer, subject, or AWB..."
                        value={searchQuery}
                        onChange={(e) => setSearchQuery(e.target.value)}
                        className="pl-9"
                      />
                    </div>
                    <Select value={statusFilter} onValueChange={setStatusFilter}>
                      <SelectTrigger className="w-[140px]">
                        <SelectValue placeholder="Status" />
                      </SelectTrigger>
                      <SelectContent>
                        <SelectItem value="all">All Status</SelectItem>
                        <SelectItem value="open">Open</SelectItem>
                        <SelectItem value="in-progress">In Progress</SelectItem>
                        <SelectItem value="resolved">Resolved</SelectItem>
                        <SelectItem value="closed">Closed</SelectItem>
                      </SelectContent>
                    </Select>
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 12 of 16

```
                    <Select value={priorityFilter} onValueChange={setPriorityFilter}>
                      <SelectTrigger className="w-[140px]">
                        <SelectValue placeholder="Priority" />
                      </SelectTrigger>
                      <SelectContent>
                        <SelectItem value="all">All Priority</SelectItem>
                        <SelectItem value="low">Low</SelectItem>
                        <SelectItem value="medium">Medium</SelectItem>
                        <SelectItem value="high">High</SelectItem>
                        <SelectItem value="urgent">Urgent</SelectItem>
                      </SelectContent>
                    </Select>
                  </div>

                  <DataTable
                    columns={requestColumns}
                    data={filteredRequests}
                    searchable={false}
                  />
                </div>
              </CardContent>
            </Card>
          </div>

          <div className="space-y-6">
            <Card>
              <CardHeader>
                <CardTitle>Agent Performance</CardTitle>
                <CardDescription>Your performance metrics today</CardDescription>
              </CardHeader>
              <CardContent>
                <div className="space-y-4">
                  <CompactMetric
                    label="Avg Response Time"
                    value={agentMetrics.averageResponseTime}
                    icon={<Clock className="h-4 w-4" />}
                  />
                  <CompactMetric
                    label="Active Chats"
                    value={agentMetrics.activeChats}
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 13 of 16

```
                    icon={<MessageSquare className="h-4 w-4" />}
                  />
                  <CompactMetric
                    label="Resolution Rate"
                    value={`${Math.round((agentMetrics.resolved / agentMetrics.totalRequests) * 100)}%`}
                    icon={<CheckCircle className="h-4 w-4" />}
                  />
                </div>
              </CardContent>
            </Card>

            <Card>
              <CardHeader>
                <CardTitle>Live Chat</CardTitle>
                <CardDescription>Active customer conversation</CardDescription>
              </CardHeader>
              <CardContent>
                <Tabs value={activeTab} onValueChange={setActiveTab}>
                  <TabsList className="grid w-full grid-cols-2">
                    <TabsTrigger value="requests">Requests</TabsTrigger>
                    <TabsTrigger value="chat">Chat</TabsTrigger>
                  </TabsList>
                  <TabsContent value="requests" className="mt-4">
                    {selectedRequest ? (
                      <div className="space-y-4">
                        <div className="flex items-start justify-between">
                          <div>
                            <h3 className="font-semibold">{selectedRequest.subject}</h3>
                            <p className="text-sm text-muted-foreground mt-1">
                              {selectedRequest.customer.name}
                            </p>
                          </div>
                          <Button size="sm" variant="outline">
                            <MoreVertical className="h-4 w-4" />
                          </Button>
                        </div>
                        <Separator />
                        <div className="space-y-2">
                          <div className="flex items-center gap-2 text-sm">
                            <Phone className="h-4 w-4 text-muted-foreground" />
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 14 of 16

```
                            <span>{selectedRequest.customer.phone}</span>
                          </div>
                          {selectedRequest.customer.email && (
                            <div className="flex items-center gap-2 text-sm">
                              <Mail className="h-4 w-4 text-muted-foreground" />
                              <span>{selectedRequest.customer.email}</span>
                            </div>
                          )}
                          {selectedRequest.shipmentId && (
                            <div className="flex items-center gap-2 text-sm">
                              <Package className="h-4 w-4 text-muted-foreground" />
                              <span className="font-mono">{selectedRequest.shipmentId}</span>
                            </div>
                          )}
                        </div>
                        <Separator />
                        <div>
                          <p className="text-sm">{selectedRequest.description}</p>
                        </div>
                        <div className="flex gap-2">
                          <Button size="sm" className="flex-1">
                            Resolve
                          </Button>
                          <Button size="sm" variant="outline" className="flex-1">
                            Escalate
                          </Button>
                        </div>
                      </div>
                    ) : (
                      <div className="text-center py-8 text-muted-foreground">
                        <MessageSquare className="h-12 w-12 mx-auto mb-2 opacity-50" />
                        <p>Select a request to view details</p>
                      </div>
                    )}
                  </TabsContent>
                  <TabsContent value="chat" className="mt-4">
                    <div className="space-y-4">
                      <ScrollArea className="h-[300px] pr-4">
                        <div className="space-y-4">
                          {mockChatMessages.map((msg) => (
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 15 of 16

```
                              <div
                                key={msg.id}
                                className={`flex gap-2 ${
                                  msg.sender === 'agent' ? 'flex-row-reverse' : ''
                                }`}
                              >
                                <Avatar className="h-8 w-8">
                                  <AvatarFallback>
                                    {msg.sender === 'agent' ? 'A' : 'C'}
                                  </AvatarFallback>
                                </Avatar>
                                <div
                                  className={`flex-1 max-w-[80%] ${
                                    msg.sender === 'agent' ? 'text-right' : ''
                                  }`}
                                >
                                  <div
                                    className={`inline-block p-3 rounded-lg ${
                                      msg.sender === 'agent'
                                        ? 'bg-primary text-primary-foreground'
                                        : 'bg-muted'
                                    }`}
                                  >
                                    <p className="text-sm">{msg.message}</p>
                                  </div>
                                  <p className="text-xs text-muted-foreground mt-1">
                                    {formatDate(msg.timestamp, 'time')}
                                  </p>
                                </div>
                              </div>
                            ))}
                          </div>
                        </ScrollArea>
                        <div className="flex gap-2">
                          <Button size="icon" variant="outline">
                            <Paperclip className="h-4 w-4" />
                          </Button>
                          <Input
                            placeholder="Type your message..."
                            value={chatMessage}
```

pages/CustomerService.tsx

618 lines · 22,852 bytes · Page segment 16 of 16

```
                            onChange={(e) => setChatMessage(e.target.value)}
                            onKeyPress={(e) => e.key === 'Enter' && handleSendMessage()}
                          />
                          <Button size="icon" onClick={handleSendMessage}>
                            <Send className="h-4 w-4" />
                          </Button>
                        </div>
                      </div>
                    </TabsContent>
                  </Tabs>
                </CardContent>
              </Card>
            </div>
          </div>
        </motion.div>
        </div>
      </div>
    );
  }
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 1 of 11

```
import { useState, useEffect } from 'react';
import { Link } from 'react-router-dom';
import { motion } from 'framer-motion';
import {
  Package,
  Clock,
  DollarSign,
  Users,
  TrendingUp,
  TrendingDown,
  Plus,
  UserPlus,
  MapPin,
  Activity,
} from 'lucide-react';
import type { Shipment, DeliveryStatus } from '@/lib/index';
import { Button } from '@/components/ui/button';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { ROUTE_PATHS, calculateDeliveryMetrics, calculateRevenue, formatCurrency } from '@/lib/index';
import { mockShipments, mockDeliveries, mockEmployees, mockWarehouses } from '@/data/index';
import { MetricCard, StatsGrid, StatusBadge } from '@/components/Stats';
import { DeliveryTrendChart, RevenueChart, StatusDistributionChart, FleetActivityChart } from '@/components/Charts';
import { DataTable, Column } from '@/components/DataTable';
import { MapView } from '@/components/MapView';
import { IMAGES } from '@/assets/images';

export default function Dashboard() {
  const [timeRange, setTimeRange] = useState<'today' | 'week' | 'month'>('today');

  const metrics = calculateDeliveryMetrics(mockDeliveries);
  const revenue = calculateRevenue(mockDeliveries, mockShipments);
  const activeDrivers = mockEmployees.filter(e => e.role === 'driver' && e.status === 'active');

  const kpiMetrics = [
    {
      title: 'Total Deliveries',
      value: metrics.total,
      trend: 12.5,
      icon: <Package className="w-5 h-5" />,
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 2 of 11

```
      unit: 'deliveries',
      description: 'All time deliveries',
    },
    {
      title: 'On-Time Rate',
      value: `${metrics.onTimeRate}%`,
      trend: 2.3,
      icon: <Clock className="w-5 h-5" />,
      description: 'Delivered within SLA',
    },
    {
      title: 'Total Revenue',
      value: formatCurrency(revenue.totalRevenue),
      trend: 18.7,
      icon: <DollarSign className="w-5 h-5" />,
      description: 'This month',
    },
    {
      title: 'Active Drivers',
      value: activeDrivers.length,
      trend: 0,
      icon: <Users className="w-5 h-5" />,
      unit: 'drivers',
      description: 'Currently on duty',
    },
  ];

  const recentShipments = mockShipments.slice(0, 5);

  const shipmentColumns: Column<Shipment>[] = [
    {
      id: 'awb',
      header: 'AWB',
      accessor: 'awb',
      cell: (row: Shipment) => (
        <span className="font-mono text-sm font-medium">{row.awb}</span>
      ),
    },
    {
      id: 'recipient',
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 3 of 11

```
      header: 'Recipient',
      accessor: 'recipient',
      cell: (row: Shipment) => (
        <div>
          <div className="font-medium">{row.recipient.name}</div>
          <div className="text-sm text-muted-foreground">{row.recipient.phone}</div>
        </div>
      ),
    },
    {
      id: 'serviceType',
      header: 'Service',
      accessor: 'serviceType',
      cell: (row: Shipment) => (
        <span className="capitalize">{row.serviceType.replace('-', ' ')}</span>
      ),
    },
    {
      id: 'status',
      header: 'Status',
      accessor: 'status',
      cell: (row: Shipment) => <StatusBadge status={row.status} size="sm" />,
    },
    {
      id: 'codAmount',
      header: 'COD Amount',
      accessor: 'codAmount',
      cell: (row: Shipment) => row.codAmount ? formatCurrency(row.codAmount) : '-',
    },
  ];

  const deliveryTrendData = [
    { date: 'Mon', deliveries: 145, completed: 138 },
    { date: 'Tue', deliveries: 168, completed: 162 },
    { date: 'Wed', deliveries: 192, completed: 185 },
    { date: 'Thu', deliveries: 178, completed: 171 },
    { date: 'Fri', deliveries: 205, completed: 198 },
    { date: 'Sat', deliveries: 156, completed: 149 },
    { date: 'Sun', deliveries: 134, completed: 128 },
  ];
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 4 of 11

```

const revenueData = [
  { service: 'Express', revenue: 2800000, deliveries: 350 },
  { service: 'Same Day', revenue: 1920000, deliveries: 160 },
  { service: 'Standard', revenue: 1750000, deliveries: 350 },
  { service: 'Next Day', revenue: 1500000, deliveries: 150 },
  { service: 'Economy', revenue: 900000, deliveries: 300 },
];

const statusData = [
  { status: 'Delivered', count: metrics.delivered, color: 'hsl(var(--chart-3))' },
  { status: 'In Transit', count: Math.floor(metrics.pending * 0.6), color: 'hsl(var(--primary))' },
  { status: 'Pending', count: Math.floor(metrics.pending * 0.3), color: 'hsl(var(--accent))' },
  { status: 'Failed', count: metrics.failed, color: 'hsl(var(--destructive))' },
  { status: 'Other', count: Math.floor(metrics.pending * 0.1), color: 'hsl(var(--muted))' },
];

const fleetData = [
  { time: '00:00', active: 8, idle: 16 },
  { time: '04:00', active: 12, idle: 12 },
  { time: '08:00', active: 20, idle: 4 },
  { time: '12:00', active: 22, idle: 2 },
  { time: '16:00', active: 18, idle: 6 },
  { time: '20:00', active: 14, idle: 10 },
];

return (
  <div className="min-h-screen bg-background">
    <div
      className="absolute inset-0 z-0 opacity-30"
      style={{
        backgroundImage: `url(${IMAGES.SCREENSHOT_10951})`,
        backgroundSize: 'cover',
        backgroundPosition: 'center',
      }}
    />
    <div className="absolute inset-0 bg-gradient-to-b from-background/50 via-transparent to-background/70" />

    <div className="relative z-10">
      <div className="container mx-auto px-4 py-8 space-y-8">
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 5 of 11

```
          <motion.div
            initial={{ opacity: 0, y: 20 }}
            animate={{ opacity: 1, y: 0 }}
            transition={{ duration: 0.5 }}
          >
            <div className="flex flex-col md:flex-row md:items-center md:justify-between gap-4">
              <div>
                <h1 className="text-4xl font-bold tracking-tight">Dashboard</h1>
                <p className="text-muted-foreground mt-2">
                  Real-time overview of your delivery operations
                </p>
              </div>
              <div className="flex gap-3">
                <Button asChild size="lg">
                  <Link to={ROUTE_PATHS.CREATE_DELIVERY}>
                    <Plus className="w-5 h-5 mr-2" />
                    Create Delivery
                  </Link>
                </Button>
                <Button asChild variant="outline" size="lg">
                  <Link to={ROUTE_PATHS.SUPERVISOR}>
                    <UserPlus className="w-5 h-5 mr-2" />
                    Assign Task
                  </Link>
                </Button>
              </div>
            </div>
          </motion.div>

          <motion.div
            initial={{ opacity: 0, y: 20 }}
            animate={{ opacity: 1, y: 0 }}
            transition={{ duration: 0.5, delay: 0.1 }}
          >
            <Tabs value={timeRange} onValueChange={(v) => setTimeRange(v as any)} className="w-full">
              <TabsList className="grid w-full max-w-md grid-cols-3">
                <TabsTrigger value="today">Today</TabsTrigger>
                <TabsTrigger value="week">This Week</TabsTrigger>
                <TabsTrigger value="month">This Month</TabsTrigger>
              </TabsList>
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 6 of 11

```
            </Tabs>
          </motion.div>

          <motion.div
            initial={{ opacity: 0, y: 20 }}
            animate={{ opacity: 1, y: 0 }}
            transition={{ duration: 0.5, delay: 0.2 }}
          >
            <StatsGrid metrics={kpiMetrics} />
          </motion.div>

          <div className="grid grid-cols-1 lg:grid-cols-2 gap-6">
            <motion.div
              initial={{ opacity: 0, x: -20 }}
              animate={{ opacity: 1, x: 0 }}
              transition={{ duration: 0.5, delay: 0.3 }}
            >
              <Card>
                <CardHeader>
                  <CardTitle className="flex items-center gap-2">
                    <TrendingUp className="w-5 h-5 text-primary" />
                    Delivery Trends
                  </CardTitle>
                  <CardDescription>Daily delivery performance over the past week</CardDescription>
                </CardHeader>
                <CardContent>
                  <DeliveryTrendChart data={deliveryTrendData} height={300} />
                </CardContent>
              </Card>
            </motion.div>

            <motion.div
              initial={{ opacity: 0, x: 20 }}
              animate={{ opacity: 1, x: 0 }}
              transition={{ duration: 0.5, delay: 0.3 }}
            >
              <Card>
                <CardHeader>
                  <CardTitle className="flex items-center gap-2">
                    <DollarSign className="w-5 h-5 text-chart-4" />
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 7 of 11

```
                    Revenue by Service
                  </CardTitle>
                  <CardDescription>Revenue breakdown by service type</CardDescription>
                </CardHeader>
                <CardContent>
                  <RevenueChart data={revenueData} height={300} />
                </CardContent>
              </Card>
            </motion.div>
          </div>

          <div className="grid grid-cols-1 lg:grid-cols-3 gap-6">
            <motion.div
              initial={{ opacity: 0, y: 20 }}
              animate={{ opacity: 1, y: 0 }}
              transition={{ duration: 0.5, delay: 0.4 }}
              className="lg:col-span-2"
            >
              <Card>
                <CardHeader>
                  <CardTitle className="flex items-center gap-2">
                    <MapPin className="w-5 h-5 text-primary" />
                    Fleet Activity Map
                  </CardTitle>
                  <CardDescription>Real-time driver locations and delivery routes</CardDescription>
                </CardHeader>
                <CardContent>
                  <div className="h-[400px] rounded-lg overflow-hidden border border-border">
                    <MapView
                      deliveries={mockDeliveries}
                      drivers={activeDrivers}
                      warehouses={mockWarehouses}
                    />
                  </div>
                </CardContent>
              </Card>
            </motion.div>

            <motion.div
              initial={{ opacity: 0, y: 20 }}
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 8 of 11

```
              animate={{ opacity: 1, y: 0 }}
              transition={{ duration: 0.5, delay: 0.4 }}
              className="space-y-6"
            >
              <Card>
                <CardHeader>
                  <CardTitle className="flex items-center gap-2">
                    <Package className="w-5 h-5 text-chart-3" />
                    Status Distribution
                  </CardTitle>
                  <CardDescription>Current delivery status breakdown</CardDescription>
                </CardHeader>
                <CardContent>
                  <StatusDistributionChart data={statusData} height={250} />
                </CardContent>
              </Card>

              <Card>
                <CardHeader>
                  <CardTitle className="flex items-center gap-2">
                    <Activity className="w-5 h-5 text-primary" />
                    Fleet Activity
                  </CardTitle>
                  <CardDescription>Vehicle utilization over 24 hours</CardDescription>
                </CardHeader>
                <CardContent>
                  <FleetActivityChart data={fleetData} height={200} />
                </CardContent>
              </Card>
            </motion.div>
          </div>

          <motion.div
            initial={{ opacity: 0, y: 20 }}
            animate={{ opacity: 1, y: 0 }}
            transition={{ duration: 0.5, delay: 0.5 }}
          >
            <Card>
              <CardHeader>
                <CardTitle className="flex items-center gap-2">
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 9 of 11

```
                  <Package className="w-5 h-5 text-primary" />
                  Recent Shipments
                </CardTitle>
                <CardDescription>Latest shipments and their current status</CardDescription>
              </CardHeader>
              <CardContent>
                <DataTable
                  columns={shipmentColumns}
                  data={recentShipments}
                  searchable
                />
              </CardContent>
            </Card>
          </motion.div>

          <motion.div
            initial={{ opacity: 0, y: 20 }}
            animate={{ opacity: 1, y: 0 }}
            transition={{ duration: 0.5, delay: 0.6 }}
            className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-4 gap-4"
          >
            <Card className="bg-gradient-to-br from-chart-3/10 to-chart-3/5 border-chart-3/20">
              <CardContent className="pt-6">
                <div className="flex items-center justify-between">
                  <div>
                    <p className="text-sm font-medium text-muted-foreground">Success Rate</p>
                    <p className="text-3xl font-bold mt-2">{metrics.successRate}%</p>
                  </div>
                  <div className="w-12 h-12 rounded-full bg-chart-3/20 flex items-center justify-center">
                    <TrendingUp className="w-6 h-6 text-chart-3" />
                  </div>
                </div>
              </CardContent>
            </Card>

            <Card className="bg-gradient-to-br from-primary/10 to-primary/5 border-primary/20">
              <CardContent className="pt-6">
                <div className="flex items-center justify-between">
                  <div>
                    <p className="text-sm font-medium text-muted-foreground">COD Collected</p>
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 10 of 11

```
                    <p className="text-3xl font-bold mt-2">{formatCurrency(revenue.codCollected)}</p>
                  </div>
                  <div className="w-12 h-12 rounded-full bg-primary/20 flex items-center justify-center">
                    <DollarSign className="w-6 h-6 text-primary" />
                  </div>
                </div>
              </CardContent>
            </Card>

            <Card className="bg-gradient-to-br from-chart-4/10 to-chart-4/5 border-chart-4/20">
              <CardContent className="pt-6">
                <div className="flex items-center justify-between">
                  <div>
                    <p className="text-sm font-medium text-muted-foreground">Pending COD</p>
                    <p className="text-3xl font-bold mt-2">{formatCurrency(revenue.pendingCod)}</p>
                  </div>
                  <div className="w-12 h-12 rounded-full bg-chart-4/20 flex items-center justify-center">
                    <Clock className="w-6 h-6 text-chart-4" />
                  </div>
                </div>
              </CardContent>
            </Card>

            <Card className="bg-gradient-to-br from-destructive/10 to-destructive/5 border-destructive/20">
              <CardContent className="pt-6">
                <div className="flex items-center justify-between">
                  <div>
                    <p className="text-sm font-medium text-muted-foreground">Failed Deliveries</p>
                    <p className="text-3xl font-bold mt-2">{metrics.failed}</p>
                  </div>
                  <div className="w-12 h-12 rounded-full bg-destructive/20 flex items-center justify-center">
                    <TrendingDown className="w-6 h-6 text-destructive" />
                  </div>
                </div>
              </CardContent>
            </Card>
          </motion.div>
        </div>
      </div>
    </div>
```

pages/Dashboard.tsx

402 lines · 15,474 bytes · Page segment 11 of 11

```
  );
}
```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 1 of 11

```
import { useState } from 'react';
import { useLocation } from 'react-router-dom';
import { motion } from 'framer-motion';
import {
  Database, Upload, FileText, CheckCircle, AlertTriangle,
  Download, Plus, Search, RefreshCw, Table, Package, Loader2
} from 'lucide-react';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Badge } from '@/components/ui/badge';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from '@/components/ui/select';
import { shipmentsAPI } from '@/api/supabase';
import { useQuery } from '@/hooks/useSupabaseQuery';
import { formatDate } from '@/lib/index';
import { useToast } from '@/hooks/use-toast';

export default function DataEntryPortal() {
  const location = useLocation();
  const getInitialDETab = () => {
    if (location.pathname.includes('/manual')) return 'manual';
    if (location.pathname.includes('/bulk')) return 'bulk';
    if (location.pathname.includes('/templates')) return 'templates';
    if (location.pathname.includes('/records')) return 'records';
    return 'manual';
  };
  const [activeTab, setActiveTab] = useState(getInitialDETab());
  const [searchQuery, setSearchQuery] = useState('');
  const [statusFilter, setStatusFilter] = useState('all');
  const [uploadFile, setUploadFile] = useState<File | null>(null);
  const [isUploading, setIsUploading] = useState(false);
  const { toast } = useToast();

  const { data: shipmentData, isLoading, refetch } = useQuery(() =>
    shipmentsAPI.getAll()
  );

  const shipments = (shipmentData as any[]) || [];

```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 2 of 11

```
41  const filteredShipments = shipments.filter((s: any) => {
42    const matchesSearch = searchQuery === '' ||
43      (s.awb || '').toLowerCase().includes(searchQuery.toLowerCase()) ||
44      (s.recipient_name || '').toLowerCase().includes(searchQuery.toLowerCase()) ||
45      (s.sender_name || '').toLowerCase().includes(searchQuery.toLowerCase());
46    const matchesStatus = statusFilter === 'all' || s.status === statusFilter;
47    return matchesSearch && matchesStatus;
48  });
49
50  const handleFileChange = (e: React.ChangeEvent<HTMLInputElement>) => {
51    const file = e.target.files?.[0];
52    if (file) setUploadFile(file);
53  };
54
55  const handleUpload = async () => {
56    if (!uploadFile) return;
57    setIsUploading(true);
58    // Simulate upload — in production, parse CSV and call shipmentsAPI.create per row
59    await new Promise((r) => setTimeout(r, 1500));
60    setIsUploading(false);
61    setUploadFile(null);
62    toast({ title: 'Upload complete', description: `File "${uploadFile.name}" processed successfully.` });
63    refetch();
64  };
65
66  const downloadTemplate = (type: string) => {
67    const headers =
68      type === 'shipment'
69        ? 'awb,sender_name,sender_phone,sender_city,recipient_name,recipient_phone,recipient_city,service_type,weight,cod_amount\n'
70        : 'driver_name,driver_phone,route,vehicle_plate,date\n';
71    const blob = new Blob([headers], { type: 'text/csv' });
72    const url = URL.createObjectURL(blob);
73    const a = document.createElement('a');
74    a.href = url;
75    a.download = `${type}_template.csv`;
76    a.click();
77    URL.revokeObjectURL(url);
78  };
79
80  const statusBadge = (status: string) => {
```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 3 of 11

```
    const colors: Record<string, string> = {
      pending: 'bg-yellow-100 text-yellow-800',
      delivered: 'bg-green-100 text-green-800',
      in_transit: 'bg-blue-100 text-blue-800',
      failed: 'bg-red-100 text-red-800',
    };
    return colors[status] || 'bg-gray-100 text-gray-800';
  };

  return (
    <div className="min-h-screen bg-background">
      {/* Header */}
      <div className="bg-gradient-to-br from-primary/10 via-background to-accent/10 border-b px-6 py-8">
        <div className="flex items-center justify-between">
          <div>
            <h1 className="text-3xl font-bold flex items-center gap-2">
              <Database className="w-8 h-8 text-primary" />
              Data Entry Portal
            </h1>
            <p className="text-muted-foreground mt-1">Manual entry, bulk CSV upload and shipment data management</p>
          </div>
          <div className="flex gap-2">
            <Button variant="outline" onClick={refetch}>
              <RefreshCw className="w-4 h-4 mr-2" />
              Refresh
            </Button>
          </div>
        </div>
      </div>

      <div className="p-6 space-y-6">
        {/* Stats */}
        <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
          {[
            { label: 'Total Records', value: shipments.length, icon: <Table className="w-4 h-4" />, color: 'text-primary' },
            { label: 'Pending', value: shipments.filter((s: any) => s.status === 'pending').length, icon: <AlertTriangle className="w-4 h-4" />, color: 'text-yellow-600' },
            { label: 'Delivered', value: shipments.filter((s: any) => s.status === 'delivered').length, icon: <CheckCircle className="w-4 h-4" />, color: 'text-green-600' },
            { label: 'In Transit', value: shipments.filter((s: any) => s.status?.includes('transit')).length, icon: <Package className="w-4 h-4"
```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 4 of 11

```
/>, color: 'text-blue-600' },
          ].map((kpi, i) => (
            <motion.div key={i} whileHover={{ scale: 1.02 }}>
              <Card>
                <CardContent className="p-4">
                  <div className={`flex items-center gap-2 mb-1 ${kpi.color}`}>
                    {kpi.icon}
                    <span className="text-xs text-muted-foreground">{kpi.label}</span>
                  </div>
                  <div className="text-2xl font-bold">{kpi.value}</div>
                </CardContent>
              </Card>
            </motion.div>
          ))}
        </div>

        <Tabs value={activeTab} onValueChange={setActiveTab}>
          <TabsList>
            <TabsTrigger value="manual">
              <Plus className="w-4 h-4 mr-2" />
              Manual Entry
            </TabsTrigger>
            <TabsTrigger value="bulk">
              <Upload className="w-4 h-4 mr-2" />
              Bulk Upload
            </TabsTrigger>
            <TabsTrigger value="records">
              <Database className="w-4 h-4 mr-2" />
              All Records
            </TabsTrigger>
            <TabsTrigger value="templates">
              <Download className="w-4 h-4 mr-2" />
              Templates
            </TabsTrigger>
          </TabsList>

          {/* Manual Entry Tab */}
          <TabsContent value="manual" className="mt-4">
            <Card>
              <CardHeader>
```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 5 of 11

```
                  <CardTitle>Create New Shipment</CardTitle>
                  <CardDescription>Manually enter shipment details</CardDescription>
                </CardHeader>
                <CardContent>
                  <div className="grid md:grid-cols-2 gap-4">
                    <div className="space-y-3">
                      <h3 className="font-semibold text-sm text-muted-foreground uppercase tracking-wide">Sender Info</h3>
                      <Input placeholder="Sender Name *" />
                      <Input placeholder="Sender Phone *" />
                      <Input placeholder="Sender City *" />
                      <Input placeholder="Sender Address" />
                    </div>
                    <div className="space-y-3">
                      <h3 className="font-semibold text-sm text-muted-foreground uppercase tracking-wide">Recipient Info</h3>
                      <Input placeholder="Recipient Name *" />
                      <Input placeholder="Recipient Phone *" />
                      <Input placeholder="Recipient City *" />
                      <Input placeholder="Recipient Address *" />
                    </div>
                    <div className="space-y-3">
                      <h3 className="font-semibold text-sm text-muted-foreground uppercase tracking-wide">Package Details</h3>
                      <Select>
                        <SelectTrigger>
                          <SelectValue placeholder="Service Type *" />
                        </SelectTrigger>
                        <SelectContent>
                          <SelectItem value="standard">Standard</SelectItem>
                          <SelectItem value="express">Express</SelectItem>
                          <SelectItem value="same-day">Same Day</SelectItem>
                          <SelectItem value="economy">Economy</SelectItem>
                        </SelectContent>
                      </Select>
                      <Input placeholder="Weight (kg)" type="number" step="0.1" />
                      <Input placeholder="COD Amount (if applicable)" type="number" />
                      <Input placeholder="Package Description" />
                    </div>
                    <div className="space-y-3">
                      <h3 className="font-semibold text-sm text-muted-foreground uppercase tracking-wide">Payment</h3>
                      <Select>
                        <SelectTrigger>
```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 6 of 11

```
                        <SelectValue placeholder="Payment Method *" />
                      </SelectTrigger>
                      <SelectContent>
                        <SelectItem value="cod">Cash on Delivery (COD)</SelectItem>
                        <SelectItem value="prepaid">Prepaid</SelectItem>
                        <SelectItem value="credit">Credit</SelectItem>
                      </SelectContent>
                    </Select>
                    <Input placeholder="Merchant ID (optional)" />
                    <Input placeholder="Notes" />
                  </div>
                </div>
                <div className="mt-6 flex gap-2 justify-end">
                  <Button variant="outline">Reset</Button>
                  <Button>
                    <Plus className="w-4 h-4 mr-2" />
                    Create Shipment
                  </Button>
                </div>
              </CardContent>
            </Card>
          </TabsContent>

          {/* Bulk Upload Tab */}
          <TabsContent value="bulk" className="mt-4">
            <Card>
              <CardHeader>
                <CardTitle>Bulk CSV Upload</CardTitle>
                <CardDescription>Upload multiple shipments at once via CSV file</CardDescription>
              </CardHeader>
              <CardContent className="space-y-4">
                <div
                  className="border-2 border-dashed rounded-xl p-12 text-center hover:border-primary/50 transition-colors cursor-pointer"
                  onClick={() => document.getElementById('csv-input')?.click()}
                >
                  <Upload className="h-12 w-12 mx-auto mb-4 text-muted-foreground" />
                  {uploadFile ? (
                    <div>
                      <p className="text-lg font-medium text-primary">{uploadFile.name}</p>
                      <p className="text-sm text-muted-foreground mt-1">{(uploadFile.size / 1024).toFixed(1)} KB • Ready to upload</p>
```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 7 of 11

```
                    </div>
                  ) : (
                    <div>
                      <p className="text-lg font-medium mb-1">Drop your CSV file here</p>
                      <p className="text-sm text-muted-foreground">or click to browse • Max 10MB</p>
                    </div>
                  )}
                  <input
                    id="csv-input"
                    type="file"
                    accept=".csv"
                    className="hidden"
                    onChange={handleFileChange}
                  />
                </div>

                {uploadFile && (
                  <div className="flex justify-end gap-2">
                    <Button variant="outline" onClick={() => setUploadFile(null)}>Cancel</Button>
                    <Button onClick={handleUpload} disabled={isUploading}>
                      {isUploading ? (
                        <>
                          <Loader2 className="w-4 h-4 mr-2 animate-spin" />
                          Uploading...
                        </>
                      ) : (
                        <>
                          <Upload className="w-4 h-4 mr-2" />
                          Upload & Process
                        </>
                      )}
                    </Button>
                  </div>
                )}

                <div className="p-4 bg-muted/50 rounded-lg">
                  <p className="text-sm font-medium mb-2">CSV Requirements:</p>
                  <ul className="text-sm text-muted-foreground space-y-1 list-disc list-inside">
                    <li>First row must be headers (download template below)</li>
                    <li>Required fields: sender_name, sender_phone, recipient_name, recipient_phone, recipient_city</li>
```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 8 of 11

```
                    <li>Optional: awb (auto-generated if not provided), cod_amount, weight</li>
                    <li>Max 500 rows per upload</li>
                  </ul>
                </div>
              </CardContent>
            </Card>
          </TabsContent>

          {/* All Records Tab */}
          <TabsContent value="records" className="mt-4">
            <Card>
              <CardHeader>
                <div className="flex items-center justify-between flex-wrap gap-3">
                  <CardTitle>All Shipment Records</CardTitle>
                  <div className="flex gap-2 flex-wrap">
                    <div className="relative">
                      <Search className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground" />
                      <Input
                        placeholder="Search AWB, sender, recipient..."
                        className="pl-9 w-64"
                        value={searchQuery}
                        onChange={(e) => setSearchQuery(e.target.value)}
                      />
                    </div>
                    <Select value={statusFilter} onValueChange={setStatusFilter}>
                      <SelectTrigger className="w-36">
                        <SelectValue placeholder="Status" />
                      </SelectTrigger>
                      <SelectContent>
                        <SelectItem value="all">All Status</SelectItem>
                        <SelectItem value="pending">Pending</SelectItem>
                        <SelectItem value="in_transit">In Transit</SelectItem>
                        <SelectItem value="delivered">Delivered</SelectItem>
                        <SelectItem value="failed">Failed</SelectItem>
                      </SelectContent>
                    </Select>
                    <Button variant="outline">
                      <Download className="w-4 h-4 mr-2" />
                      Export
                    </Button>
```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 9 of 11

```
                    </div>
                  </div>
                </CardHeader>
                <CardContent>
                  {isLoading ? (
                    <div className="text-center py-12 text-muted-foreground">Loading records...</div>
                  ) : filteredShipments.length === 0 ? (
                    <div className="text-center py-12 text-muted-foreground">
                      <Database className="w-16 h-16 mx-auto mb-3 opacity-20" />
                      <p className="text-lg font-medium">No records found</p>
                      <p className="text-sm">Shipment records will appear here after data entry.</p>
                    </div>
                  ) : (
                    <div className="overflow-x-auto">
                      <table className="w-full text-sm">
                        <thead>
                          <tr className="border-b text-left text-muted-foreground">
                            <th className="pb-3 pr-4 font-medium">AWB</th>
                            <th className="pb-3 pr-4 font-medium">Sender</th>
                            <th className="pb-3 pr-4 font-medium">Recipient</th>
                            <th className="pb-3 pr-4 font-medium">Destination</th>
                            <th className="pb-3 pr-4 font-medium">Created</th>
                            <th className="pb-3 font-medium">Status</th>
                          </tr>
                        </thead>
                        <tbody className="divide-y">
                          {filteredShipments.slice(0, 50).map((s: any) => (
                            <tr key={s.id} className="hover:bg-muted/30">
                              <td className="py-3 pr-4 font-mono text-primary font-medium">{s.awb || s.id?.slice(0, 8)}</td>
                              <td className="py-3 pr-4">{s.sender_name || s.sender?.name || '-'}</td>
                              <td className="py-3 pr-4">{s.recipient_name || s.recipient?.name || '-'}</td>
                              <td className="py-3 pr-4 text-muted-foreground">{s.recipient_city || s.recipient?.address?.city || '-'}</td>
                              <td class="py-3 pr-4 text-muted-foreground">{s.created_at ? formatDate(s.created_at, 'short') : '-'}</td>
                              <td class="py-3">
                                <span class={`text-xs px-2 py-1 rounded-full font-medium ${statusBadge(s.status)}`}>
                                  {(s.status || 'pending').replace(/_/g, ' ')}
                                </span>
                              </td>
                            </tr>
                          ))}
```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 10 of 11

```
                      </tbody>
                    </table>
                    {filteredShipments.length > 50 && (
                      <p className="text-center text-sm text-muted-foreground mt-4">
                        Showing 50 of {filteredShipments.length} records. Use search or filters to narrow down.
                      </p>
                    )}
                  </div>
                )}
              </CardContent>
            </Card>
          </TabsContent>

          {/* Templates Tab */}
          <TabsContent value="templates" className="mt-4">
            <Card>
              <CardHeader>
                <CardTitle>Download CSV Templates</CardTitle>
                <CardDescription>Use these templates for bulk upload</CardDescription>
              </CardHeader>
              <CardContent>
                <div className="space-y-3">
                  {[
                    { label: 'Shipment Upload Template', desc: 'Create multiple shipments at once', type: 'shipment' },
                    { label: 'Delivery Assignment Template', desc: 'Assign deliveries to drivers in bulk', type: 'delivery' },
                  ].map((t) => (
                    <div key={t.type} className="flex items-center justify-between p-4 border rounded-lg hover:bg-muted/30">
                      <div className="flex items-center gap-3">
                        <FileText className="h-8 w-8 text-primary/50" />
                        <div>
                          <p className="font-medium">{t.label}</p>
                          <p className="text-sm text-muted-foreground">{t.desc}</p>
                        </div>
                      </div>
                      <Button variant="outline" onClick={() => downloadTemplate(t.type)}>
                        <Download className="w-4 h-4 mr-2" />
                        Download
                      </Button>
                    </div>
                  ))}
```

pages/DataEntryPortal.tsx

406 lines · 19,431 bytes · Page segment 11 of 11

```
                  </div>
                </CardContent>
              </Card>
            </TabsContent>
          </Tabs>
        </div>
      </div>
    );
  }
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 1 of 19

```
import { useState, useEffect } from 'react';
import { useLocation } from 'react-router-dom';
import { motion, AnimatePresence } from 'framer-motion';
import {
  Package,
  MapPin,
  Navigation,
  CheckCircle,
  Camera,
  FileSignature,
  Hash,
  Clock,
  DollarSign,
  AlertCircle,
  Phone,
  ChevronRight,
  TrendingUp,
  Award,
  Target,
} from 'lucide-react';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Badge } from '@/components/ui/badge';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { Progress } from '@/components/ui/progress';
import { Separator } from '@/components/ui/separator';
import { ScrollArea } from '@/components/ui/scroll-area';
import { Avatar, AvatarFallback } from '@/components/ui/avatar';
import { IMAGES } from '@/assets/images';
import {
  formatStatus,
  getStatusColor,
  formatDate,
  formatCurrency,
  formatDistance,
  formatDuration,
  type Delivery,
  type Shipment,
  type Manifest,
  type Employee,
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 2 of 19

```
41 } from '@/lib/index';
42 import { mockDeliveries, mockShipments, mockManifests, mockEmployees } from '@/data/index';
43 import { StatusBadge, CompactMetric, ProgressMetric } from '@/components/Stats';
44 import { MapView } from '@/components/MapView';
45 import { springPresets, fadeInUp, staggerContainer, staggerItem } from '@/lib/motion';
46
47 const currentDriverId = 'emp-003';
48
49 export default function DriverPortal() {
50   const location = useLocation();
51   const getInitialDriverTab = () => {
52     if (location.pathname.includes('/jobs')) return 'jobs';
53     if (location.pathname.includes('/route')) return 'route';
54     if (location.pathname.includes('/proof')) return 'proof';
55     return 'jobs';
56     if (location.pathname.includes('/earnings')) return 'earnings';
57   };
58   const [activeTab, setActiveTab] = useState(getInitialDriverTab());
59   const [selectedDelivery, setSelectedDelivery] = useState<string | null>(null);
60   const [currentDriver, setCurrentDriver] = useState<Employee | null>(null);
61   const [activeManifest, setActiveManifest] = useState<Manifest | null>(null);
62   const [myDeliveries, setMyDeliveries] = useState<Delivery[]>([]);
63   const [myShipments, setMyShipments] = useState<Shipment[]>([]);
64
65   useEffect(() => {
66     const driver = mockEmployees.find(e => e.id === currentDriverId);
67     setCurrentDriver(driver || null);
68
69     const manifest = mockManifests.find(m => m.driverId === currentDriverId && m.status === 'active');
70     setActiveManifest(manifest || null);
71
72     const deliveries = mockDeliveries.filter(d => d.driverId === currentDriverId);
73     setMyDeliveries(deliveries);
74
75     const shipmentIds = deliveries.map(d => d.shipmentId);
76     const shipments = mockShipments.filter(s => shipmentIds.includes(s.id));
77     setMyShipments(shipments);
78   }, []);
79
80   const activeDeliveries = myDeliveries.filter(d =>
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 3 of 19

```
    ['assigned', 'picked-up', 'in-transit', 'out-for-delivery'].includes(d.status)
  );

  const completedToday = myDeliveries.filter(d => {
    if (d.status !== 'delivered' || !d.deliveredAt) return false;
    const deliveredDate = new Date(d.deliveredAt);
    const today = new Date();
    return deliveredDate.toDateString() === today.toDateString();
  });

  const todayEarnings = completedToday.reduce((sum, d) => {
    const shipment = myShipments.find(s => s.id === d.shipmentId);
    if (!shipment) return sum;
    const baseRate = 5000;
    return sum + baseRate;
  }, 0);

  const codCollectedToday = completedToday.reduce((sum, d) => sum + (d.codCollected || 0), 0);

  const getShipmentForDelivery = (deliveryId: string) => {
    const delivery = myDeliveries.find(d => d.id === deliveryId);
    if (!delivery) return null;
    return myShipments.find(s => s.id === delivery.shipmentId) || null;
  };

  const handleStartDelivery = (deliveryId: string) => {
    setSelectedDelivery(deliveryId);
    setActiveTab('route');
  };

  const handleCompleteDelivery = (deliveryId: string) => {
    setSelectedDelivery(deliveryId);
    setActiveTab('proof');
  };

  return (
    <div className="min-h-screen bg-background">
      {/* Hero Header */}
      <div className="relative h-64 overflow-hidden">
        <img
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 4 of 19

```
          src={IMAGES.SCREENSHOT_3252_4}
          alt="Driver Portal"
          className="absolute inset-0 w-full h-full object-cover opacity-30"
        />
        <div className="absolute inset-0 bg-gradient-to-b from-background/50 via-transparent to-background/70" />
        <div className="relative h-full flex flex-col justify-end p-8">
          <motion.div
            initial={{ opacity: 0, y: 20 }}
            animate={{ opacity: 1, y: 0 }}
            transition={springPresets.gentle}
          >
            <div className="flex items-center gap-4 mb-4">
              <Avatar className="h-16 w-16 border-2 border-primary">
                <AvatarFallback className="bg-primary text-primary-foreground text-xl font-bold">
                  {currentDriver?.name.split(' ').map(n => n[0]).join('') || 'DR'}
                </AvatarFallback>
              </Avatar>
              <div>
                <h1 className="text-3xl font-bold text-foreground">
                  {currentDriver?.name || 'Driver Portal'}
                </h1>
                <p className="text-muted-foreground">
                  {currentDriver?.vehicleAssignment?.vehicleType.toUpperCase()} •{' '}
                  {currentDriver?.vehicleAssignment?.licensePlate}
                </p>
              </div>
            </div>
          </motion.div>
        </div>
      </div>

      {/* Quick Stats */}
      <div className="px-8 -mt-8 mb-8">
        <motion.div
          variants={staggerContainer}
          initial="hidden"
          animate="visible"
          className="grid grid-cols-1 md:grid-cols-4 gap-4"
        >
          <motion.div variants={staggerItem}>
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 5 of 19

```
            <Card className="bg-card/80 backdrop-blur border-border/50">
              <CardContent className="p-6">
                <div className="flex items-center justify-between">
                  <div>
                    <p className="text-sm text-muted-foreground">Active Jobs</p>
                    <p className="text-3xl font-bold text-foreground">{activeDeliveries.length}</p>
                  </div>
                  <div className="h-12 w-12 rounded-full bg-primary/10 flex items-center justify-center">
                    <Package className="h-6 w-6 text-primary" />
                  </div>
                </div>
              </CardContent>
            </Card>
          </motion.div>

          <motion.div variants={staggerItem}>
            <Card className="bg-card/80 backdrop-blur border-border/50">
              <CardContent className="p-6">
                <div className="flex items-center justify-between">
                  <div>
                    <p className="text-sm text-muted-foreground">Completed Today</p>
                    <p className="text-3xl font-bold text-chart-3">{completedToday.length}</p>
                  </div>
                  <div className="h-12 w-12 rounded-full bg-chart-3/10 flex items-center justify-center">
                    <CheckCircle className="h-6 w-6 text-chart-3" />
                  </div>
                </div>
              </CardContent>
            </Card>
          </motion.div>

          <motion.div variants={staggerItem}>
            <Card className="bg-card/80 backdrop-blur border-border/50">
              <CardContent className="p-6">
                <div className="flex items-center justify-between">
                  <div>
                    <p className="text-sm text-muted-foreground">Today's Earnings</p>
                    <p className="text-3xl font-bold text-chart-4">{formatCurrency(todayEarnings)}</p>
                  </div>
                  <div className="h-12 w-12 rounded-full bg-chart-4/10 flex items-center justify-center">
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 6 of 19

```
                    <DollarSign className="h-6 w-6 text-chart-4" />
                  </div>
                </div>
              </CardContent>
            </Card>
          </motion.div>

          <motion.div variants={staggerItem}>
            <Card className="bg-card/80 backdrop-blur border-border/50">
              <CardContent className="p-6">
                <div className="flex items-center justify-between">
                  <div>
                    <p className="text-sm text-muted-foreground">Success Rate</p>
                    <p className="text-3xl font-bold text-primary">
                      {((currentDriver?.performance?.successRate) ?? 0).toFixed(1)}%
                    </p>
                  </div>
                  <div className="h-12 w-12 rounded-full bg-primary/10 flex items-center justify-center">
                    <Award className="h-6 w-6 text-primary" />
                  </div>
                </div>
              </CardContent>
            </Card>
          </motion.div>
        </motion.div>
      </div>

      {/* Main Content */}
      <div className="px-8 pb-8">
        <Tabs value={activeTab} onValueChange={setActiveTab} className="space-y-6">
          <TabsList className="grid w-full grid-cols-4 lg:w-auto lg:inline-grid">
            <TabsTrigger value="jobs" className="gap-2">
              <Package className="h-4 w-4" />
              Current Jobs
            </TabsTrigger>
            <TabsTrigger value="route" className="gap-2">
              <Navigation className="h-4 w-4" />
              Active Route
            </TabsTrigger>
            <TabsTrigger value="proof" className="gap-2">
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 7 of 19

```
              <CheckCircle className="h-4 w-4" />
              Proof of Delivery
            </TabsTrigger>
            <TabsTrigger value="earnings" className="gap-2">
              <DollarSign className="h-4 w-4" />
              Earnings
            </TabsTrigger>
          </TabsList>

          {/* Current Jobs Tab */}
          <TabsContent value="jobs" className="space-y-6">
            <motion.div
              initial={{ opacity: 0, y: 20 }}
              animate={{ opacity: 1, y: 0 }}
              transition={springPresets.gentle}
            >
              <Card>
                <CardHeader>
                  <CardTitle>Active Deliveries</CardTitle>
                  <CardDescription>
                    {activeDeliveries.length} deliveries in progress
                  </CardDescription>
                </CardHeader>
                <CardContent>
                  <ScrollArea className="h-[600px] pr-4">
                    <div className="space-y-4">
                      {activeDeliveries.map((delivery, index) => {
                        const shipment = getShipmentForDelivery(delivery.id);
                        if (!shipment) return null;

                        return (
                          <motion.div
                            key={delivery.id}
                            initial={{ opacity: 0, x: -20 }}
                            animate={{ opacity: 1, x: 0 }}
                            transition={{ delay: index * 0.1, ...springPresets.snappy }}
                          >
                            <Card className="border-l-4 border-l-primary hover:shadow-lg transition-shadow">
                              <CardContent className="p-6">
                                <div className="flex items-start justify-between mb-4">
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 8 of 19

```
                                  <div className="flex-1">
                                    <div className="flex items-center gap-2 mb-2">
                                      <Badge variant="outline" className="font-mono">
                                        {shipment.awb}
                                      </Badge>
                                      <StatusBadge status={delivery.status} size="sm" />
                                    </div>
                                    <h3 className="font-semibold text-lg mb-1">
                                      {shipment.recipient.name}
                                    </h3>
                                    <div className="flex items-start gap-2 text-sm text-muted-foreground">
                                      <MapPin className="h-4 w-4 mt-0.5 flex-shrink-0" />
                                      <span>
                                        {shipment.recipient.address.street},{' '}
                                        {shipment.recipient.address.city}
                                      </span>
                                    </div>
                                  </div>
                                  <Button
                                    size="sm"
                                    onClick={() => handleStartDelivery(delivery.id)}
                                    className="gap-2"
                                  >
                                    <Navigation className="h-4 w-4" />
                                    Navigate
                                  </Button>
                                </div>

                                <Separator className="my-4" />

                                <div className="grid grid-cols-2 gap-4">
                                  <div className="flex items-center gap-2">
                                    <Phone className="h-4 w-4 text-muted-foreground" />
                                    <span className="text-sm">{shipment.recipient.phone}</span>
                                  </div>
                                  <div className="flex items-center gap-2">
                                    <Package className="h-4 w-4 text-muted-foreground" />
                                    <span className="text-sm">
                                      {shipment.packageDetails.weight} kg
                                    </span>
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 9 of 19

```
                                  </div>
                                  {shipment.codAmount && (
                                    <div className="flex items-center gap-2">
                                      <DollarSign className="h-4 w-4 text-muted-foreground" />
                                      <span className="text-sm font-semibold text-chart-4">
                                        COD: {formatCurrency(shipment.codAmount)}
                                      </span>
                                    </div>
                                  )}
                                  {shipment.specialInstructions && (
                                    <div className="flex items-center gap-2 col-span-2">
                                      <AlertCircle className="h-4 w-4 text-chart-4" />
                                      <span className="text-sm text-chart-4">
                                        {shipment.specialInstructions}
                                      </span>
                                    </div>
                                  )}
                                </div>

                                {delivery.status === 'out-for-delivery' && (
                                  <Button
                                    className="w-full mt-4 gap-2"
                                    onClick={() => handleCompleteDelivery(delivery.id)}
                                  >
                                    <CheckCircle className="h-4 w-4" />
                                    Complete Delivery
                                  </Button>
                                )}
                              </CardContent>
                            </Card>
                          </motion.div>
                        );
                      })}

                      {activeDeliveries.length === 0 && (
                        <div className="text-center py-12">
                          <Package className="h-12 w-12 text-muted-foreground mx-auto mb-4" />
                          <p className="text-muted-foreground">No active deliveries</p>
                        </div>
                      )}
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 10 of 19

```
                    </div>
                  </ScrollArea>
                </CardContent>
              </Card>
            </motion.div>
          </TabsContent>

          {/* Active Route Tab */}
          <TabsContent value="route" className="space-y-6">
            <div className="grid grid-cols-1 lg:grid-cols-3 gap-6">
              <div className="lg:col-span-2">
                <Card>
                  <CardHeader>
                    <CardTitle>Route Map</CardTitle>
                    <CardDescription>
                      Turn-by-turn navigation for your deliveries
                    </CardDescription>
                  </CardHeader>
                  <CardContent>
                    <div className="relative h-[500px] rounded-lg overflow-hidden bg-muted">
                      <img
                        src={IMAGES.ROUTE_MAP_1}
                        alt="Route Map"
                        className="absolute inset-0 w-full h-full object-cover"
                      />
                      <div className="absolute inset-0 bg-gradient-to-t from-background/80 to-transparent" />
                      <div className="absolute bottom-4 left-4 right-4">
                        <Card className="bg-card/90 backdrop-blur">
                          <CardContent className="p-4">
                            <div className="flex items-center justify-between">
                              <div>
                                <p className="text-sm text-muted-foreground">Next Stop</p>
                                <p className="font-semibold">
                                  {activeDeliveries[0] &&
                                    getShipmentForDelivery(activeDeliveries[0].id)?.recipient.name}
                                </p>
                              </div>
                              <div className="text-right">
                                <p className="text-sm text-muted-foreground">ETA</p>
                                <p className="font-semibold">15 min</p>
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 11 of 19

```
                              </div>
                            </div>
                          </CardContent>
                        </Card>
                      </div>
                    </div>
                  </CardContent>
                </Card>
              </div>

              <div>
                <Card>
                  <CardHeader>
                    <CardTitle>Delivery Manifest</CardTitle>
                    <CardDescription>
                      {activeManifest ? `${activeManifest.deliveries.length} stops` : 'No active manifest'}
                    </CardDescription>
                  </CardHeader>
                  <CardContent>
                    {activeManifest ? (
                      <ScrollArea className="h-[500px] pr-4">
                        <div className="space-y-3">
                          {activeManifest.route.waypoints.map((waypoint, index) => {
                            const delivery = myDeliveries.find(d => d.id === waypoint.deliveryId);
                            const shipment = delivery ? getShipmentForDelivery(delivery.id) : null;
                            if (!shipment) return null;

                            const isCompleted = delivery?.status === 'delivered';
                            const isCurrent = index === 0 && !isCompleted;

                            return (
                              <div
                                key={waypoint.deliveryId}
                                className={`flex items-start gap-3 p-3 rounded-lg border ${
                                  isCurrent
                                    ? 'border-primary bg-primary/5'
                                    : isCompleted
                                    ? 'border-chart-3 bg-chart-3/5'
                                    : 'border-border'
                                }`}
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 12 of 19

```
                                >
                                  <div
                                    className={`flex-shrink-0 h-8 w-8 rounded-full flex items-center justify-center font-semibold ${
                                      isCompleted
                                        ? 'bg-chart-3 text-white'
                                        : isCurrent
                                        ? 'bg-primary text-primary-foreground'
                                        : 'bg-muted text-muted-foreground'
                                    }`}
                                  >
                                    {isCompleted ? (
                                      <CheckCircle className="h-4 w-4" />
                                    ) : (
                                      waypoint.sequence
                                    )}
                                  </div>
                                  <div className="flex-1 min-w-0">
                                    <p className="font-medium text-sm truncate">
                                      {shipment.recipient.name}
                                    </p>
                                    <p className="text-xs text-muted-foreground truncate">
                                      {waypoint.address.street}
                                    </p>
                                    {shipment.codAmount && (
                                      <p className="text-xs font-semibold text-chart-4 mt-1">
                                        COD: {formatCurrency(shipment.codAmount)}
                                      </p>
                                    )}
                                  </div>
                                  {isCurrent && (
                                    <ChevronRight className="h-5 w-5 text-primary flex-shrink-0" />
                                  )}
                                </div>
                              );
                            })}
                          </div>
                        </ScrollArea>
                      ) : (
                        <div className="text-center py-12">
                          <Navigation className="h-12 w-12 text-muted-foreground mx-auto mb-4" />
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 13 of 19

```
                        <p className="text-muted-foreground">No active route</p>
                      </div>
                    )}
                  </CardContent>
                </Card>
              </div>
            </div>
          </TabsContent>

          {/* Proof of Delivery Tab */}
          <TabsContent value="proof" className="space-y-6">
            <Card>
              <CardHeader>
                <CardTitle>Proof of Delivery Checklist</CardTitle>
                <CardDescription>
                  Complete all steps to finalize delivery
                </CardDescription>
              </CardHeader>
              <CardContent>
                <div className="max-w-2xl mx-auto space-y-6">
                  {selectedDelivery && (
                    <div className="mb-6">
                      <div className="flex items-center gap-2 mb-2">
                        <Badge variant="outline" className="font-mono">
                          {getShipmentForDelivery(selectedDelivery)?.awb}
                        </Badge>
                      </div>
                      <h3 className="text-lg font-semibold">
                        {getShipmentForDelivery(selectedDelivery)?.recipient.name}
                      </h3>
                      <p className="text-sm text-muted-foreground">
                        {getShipmentForDelivery(selectedDelivery)?.recipient.address.street}
                      </p>
                    </div>
                  )}

                  <Separator />

                  <div className="space-y-4">
                    <div className="flex items-start gap-4 p-4 rounded-lg border border-border hover:border-primary transition-colors">
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 14 of 19

```
                      <div className="h-10 w-10 rounded-full bg-primary/10 flex items-center justify-center flex-shrink-0">
                        <Camera className="h-5 w-5 text-primary" />
                      </div>
                      <div className="flex-1">
                        <h4 className="font-semibold mb-1">Take Photo</h4>
                        <p className="text-sm text-muted-foreground mb-3">
                          Capture photo of delivered package
                        </p>
                        <Button variant="outline" size="sm" className="gap-2">
                          <Camera className="h-4 w-4" />
                          Open Camera
                        </Button>
                      </div>
                    </div>

                    <div className="flex items-start gap-4 p-4 rounded-lg border border-border hover:border-primary transition-colors">
                      <div className="h-10 w-10 rounded-full bg-primary/10 flex items-center justify-center flex-shrink-0">
                        <FileSignature className="h-5 w-5 text-primary" />
                      </div>
                      <div className="flex-1">
                        <h4 className="font-semibold mb-1">Get Signature</h4>
                        <p className="text-sm text-muted-foreground mb-3">
                          Collect recipient's signature
                        </p>
                        <Button variant="outline" size="sm" className="gap-2">
                          <FileSignature className="h-4 w-4" />
                          Signature Pad
                        </Button>
                      </div>
                    </div>

                    <div className="flex items-start gap-4 p-4 rounded-lg border border-border hover:border-primary transition-colors">
                      <div className="h-10 w-10 rounded-full bg-primary/10 flex items-center justify-center flex-shrink-0">
                        <Hash className="h-5 w-5 text-primary" />
                      </div>
                      <div className="flex-1">
                        <h4 className="font-semibold mb-1">Verify OTP</h4>
                        <p className="text-sm text-muted-foreground mb-3">
                          Enter OTP from recipient
                        </p>
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 15 of 19

```
                        <Button variant="outline" size="sm" className="gap-2">
                          <Hash className="h-4 w-4" />
                          Enter OTP
                        </Button>
                      </div>
                    </div>

                    <div className="flex items-start gap-4 p-4 rounded-lg border border-border hover:border-primary transition-colors">
                      <div className="h-10 w-10 rounded-full bg-chart-4/10 flex items-center justify-center flex-shrink-0">
                        <DollarSign className="h-5 w-5 text-chart-4" />
                      </div>
                      <div className="flex-1">
                        <h4 className="font-semibold mb-1">Collect COD</h4>
                        <p className="text-sm text-muted-foreground mb-3">
                          Collect cash on delivery amount
                        </p>
                        <div className="flex items-center gap-2">
                          <span className="text-2xl font-bold text-chart-4">
                            {formatCurrency(
                              getShipmentForDelivery(selectedDelivery || '')?.codAmount || 0
                            )}
                          </span>
                        </div>
                      </div>
                    </div>
                  </div>

                  <Separator />

                  <Button className="w-full gap-2" size="lg">
                    <CheckCircle className="h-5 w-5" />
                    Complete Delivery
                  </Button>
                </div>
              </CardContent>
            </Card>
          </TabsContent>

          {/* Earnings Tab */}
          <TabsContent value="earnings" className="space-y-6">
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 16 of 19

```
            <div className="grid grid-cols-1 md:grid-cols-2 gap-6">
              <Card>
                <CardHeader>
                  <CardTitle>Today's Summary</CardTitle>
                  <CardDescription>{formatDate(new Date(), 'long')}</CardDescription>
                </CardHeader>
                <CardContent className="space-y-6">
                  <div>
                    <div className="flex items-center justify-between mb-2">
                      <span className="text-sm text-muted-foreground">Total Earnings</span>
                      <span className="text-2xl font-bold text-chart-4">
                        {formatCurrency(todayEarnings)}
                      </span>
                    </div>
                    <Progress value={75} className="h-2" />
                  </div>

                  <Separator />

                  <div className="space-y-3">
                    <div className="flex items-center justify-between">
                      <span className="text-sm text-muted-foreground">Deliveries Completed</span>
                      <span className="font-semibold">{completedToday.length}</span>
                    </div>
                    <div className="flex items-center justify-between">
                      <span className="text-sm text-muted-foreground">COD Collected</span>
                      <span className="font-semibold">{formatCurrency(codCollectedToday)}</span>
                    </div>
                    <div className="flex items-center justify-between">
                      <span className="text-sm text-muted-foreground">Average per Delivery</span>
                      <span className="font-semibold">
                        {formatCurrency(
                          completedToday.length > 0 ? todayEarnings / completedToday.length : 0
                        )}
                      </span>
                    </div>
                  </div>
                </CardContent>
              </Card>

```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 17 of 19

```
              <Card>
                <CardHeader>
                  <CardTitle>Performance Metrics</CardTitle>
                  <CardDescription>Your overall statistics</CardDescription>
                </CardHeader>
                <CardContent className="space-y-6">
                  <div className="space-y-4">
                    <div>
                      <div className="flex items-center justify-between mb-2">
                        <span className="text-sm text-muted-foreground">Success Rate</span>
                        <span className="font-semibold">
                          {((currentDriver?.performance?.successRate) ?? 0).toFixed(1)}%
                        </span>
                      </div>
                      <Progress
                        value={currentDriver?.performance?.successRate || 0}
                        className="h-2"
                      />
                    </div>

                    <div>
                      <div className="flex items-center justify-between mb-2">
                        <span className="text-sm text-muted-foreground">On-Time Rate</span>
                        <span className="font-semibold">
                          {((currentDriver?.performance?.onTimeRate) ?? 0).toFixed(1)}%
                        </span>
                      </div>
                      <Progress
                        value={currentDriver?.performance?.onTimeRate || 0}
                        className="h-2"
                      />
                    </div>

                    <div>
                      <div className="flex items-center justify-between mb-2">
                        <span className="text-sm text-muted-foreground">Customer Rating</span>
                        <span className="font-semibold">
                          {((currentDriver?.performance?.averageRating) ?? 0).toFixed(1)}/5.0
                        </span>
                      </div>
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 18 of 19

```
                      <Progress
                        value={(currentDriver?.performance?.averageRating || 0) * 20}
                        className="h-2"
                      />
                    </div>
                  </div>

                  <Separator />

                  <div className="flex items-center justify-between">
                    <span className="text-sm text-muted-foreground">Total Deliveries</span>
                    <span className="text-2xl font-bold">
                      {currentDriver?.performance?.totalDeliveries || 0}
                    </span>
                  </div>
                </CardContent>
              </Card>
            </div>

            <Card>
              <CardHeader>
                <CardTitle>Recent Deliveries</CardTitle>
                <CardDescription>Your completed deliveries today</CardDescription>
              </CardHeader>
              <CardContent>
                <ScrollArea className="h-[400px] pr-4">
                  <div className="space-y-3">
                    {completedToday.map((delivery) => {
                      const shipment = getShipmentForDelivery(delivery.id);
                      if (!shipment) return null;

                      return (
                        <div
                          key={delivery.id}
                          className="flex items-center justify-between p-4 rounded-lg border border-border hover:border-chart-3 transition-colors"
                        >
                          <div className="flex items-center gap-3">
                            <div className="h-10 w-10 rounded-full bg-chart-3/10 flex items-center justify-center">
                              <CheckCircle className="h-5 w-5 text-chart-3" />
```

pages/DriverPortal.tsx

755 lines · 35,018 bytes · Page segment 19 of 19

```
                            </div>
                            <div>
                              <p className="font-medium">{shipment.recipient.name}</p>
                              <p className="text-sm text-muted-foreground">
                                {delivery.deliveredAt && formatDate(delivery.deliveredAt, 'time')}
                              </p>
                            </div>
                          </div>
                          <div className="text-right">
                            <p className="font-semibold">{formatCurrency(5000)}</p>
                            {delivery.codCollected && (
                              <p className="text-sm text-chart-4">
                                COD: {formatCurrency(delivery.codCollected)}
                              </p>
                            )}
                          </div>
                        </div>
                      );
                    })}

                    {completedToday.length === 0 && (
                      <div className="text-center py-12">
                        <DollarSign className="h-12 w-12 text-muted-foreground mx-auto mb-4" />
                        <p className="text-muted-foreground">No completed deliveries today</p>
                      </div>
                    )}
                  </div>
                </ScrollArea>
              </CardContent>
            </Card>
          </TabsContent>
        </Tabs>
      </div>
    </div>
  );
}
```

pages/FinancePortal.tsx

90 lines · 3,834 bytes · Page segment 1 of 3

```
import { DollarSign, TrendingUp, Package, FileText } from 'lucide-react';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Badge } from '@/components/ui/badge';

export default function FinancePortal() {
  return (
    <div className="space-y-6">
      <div>
        <h1 className="text-3xl font-bold">Finance Portal</h1>
        <p className="text-muted-foreground">Financial transactions, COD collections, and invoicing</p>
      </div>

      <div className="grid gap-6 md:grid-cols-4">
        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Total Revenue</CardTitle>
            <DollarSign className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">$45,231</div>
            <p className="text-xs text-muted-foreground">+20.1% from last month</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">COD Collections</CardTitle>
            <Package className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">$12,450</div>
            <p className="text-xs text-muted-foreground">234 transactions</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Pending Invoices</CardTitle>
            <FileText className="h-4 w-4 text-muted-foreground" />
```

pages/FinancePortal.tsx

90 lines · 3,834 bytes · Page segment 2 of 3

```
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">23</div>
            <p className="text-xs text-muted-foreground">$8,920 total</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Profit Margin</CardTitle>
            <TrendingUp className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">32.5%</div>
            <p className="text-xs text-muted-foreground">+2.3% this quarter</p>
          </CardContent>
        </Card>
      </div>

      <Card>
        <CardHeader>
          <CardTitle>Recent Transactions</CardTitle>
          <CardDescription>Latest financial transactions</CardDescription>
        </CardHeader>
        <CardContent>
          <div className="space-y-4">
            {[
              { id: 'TXN-001', type: 'COD Collection', amount: '$450', status: 'Completed' },
              { id: 'TXN-002', type: 'Invoice Payment', amount: '$1,200', status: 'Pending' },
              { id: 'TXN-003', type: 'COD Collection', amount: '$320', status: 'Completed' },
            ].map((txn, i) => (
              <div key={i} className="flex items-center justify-between p-4 border rounded-lg">
                <div>
                  <p className="font-medium">{txn.id}</p>
                  <p className="text-sm text-muted-foreground">{txn.type} • {txn.amount}</p>
                </div>
                <div className="flex items-center gap-2">
                  <Badge variant={txn.status === 'Completed' ? 'default' : 'secondary'}>
                    {txn.status}
                  </Badge>
```

pages/FinancePortal.tsx

90 lines · 3,834 bytes · Page segment 3 of 3

```
                    <Button size="sm" variant="outline">View</Button>
                  </div>
                </div>
              ))}
            </div>
          </CardContent>
        </Card>
      </div>
    );
  }
```

pages/home/components/Demo.tsx

3 lines · 63 bytes · Page segment 1 of 1

```
export const Demo = () => {
  return <div>Hello World</div>;
};
```

pages/home/Index.tsx

13 lines · 364 bytes · Page segment 1 of 1

```
import { Demo } from "./components/Demo";
const Index = () => {
  return (
    <div className="min-h-screen flex items-center justify-center bg-background">
      <div className="text-center">
        <Demo />
        <p className="text-xl text-muted-foreground">Start building your amazing project here!</p>
      </div>
    </div>
  );
};

export default Index;
```

pages/HRPortal.tsx

88 lines · 3,671 bytes · Page segment 1 of 3

```
import { UserCog, Users, Clock, FileText } from 'lucide-react';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Badge } from '@/components/ui/badge';

export default function HRPortal() {
  return (
    <div className="space-y-6">
      <div>
        <h1 className="text-3xl font-bold">HR Management</h1>
        <p className="text-muted-foreground">Employee management, attendance, and leave requests</p>
      </div>

      <div className="grid gap-6 md:grid-cols-4">
        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Total Employees</CardTitle>
            <Users className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">245</div>
            <p className="text-xs text-muted-foreground">+12 this month</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Present Today</CardTitle>
            <Clock className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">232</div>
            <p className="text-xs text-muted-foreground">94.7% attendance</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Leave Requests</CardTitle>
            <FileText className="h-4 w-4 text-muted-foreground" />
```

pages/HRPortal.tsx

88 lines · 3,671 bytes · Page segment 2 of 3

```
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">8</div>
            <p className="text-xs text-muted-foreground">Pending approval</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">New Hires</CardTitle>
            <UserCog className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">5</div>
            <p className="text-xs text-muted-foreground">This week</p>
          </CardContent>
        </Card>
      </div>

      <Card>
        <CardHeader>
          <CardTitle>Pending Leave Requests</CardTitle>
          <CardDescription>Review and approve employee leave requests</CardDescription>
        </CardHeader>
        <CardContent>
          <div className="space-y-4">
            {[
              { name: 'John Doe', type: 'Annual Leave', dates: 'May 15-20, 2026' },
              { name: 'Jane Smith', type: 'Sick Leave', dates: 'May 10, 2026' },
              { name: 'Mike Johnson', type: 'Personal Leave', dates: 'May 25-26, 2026' },
            ].map((request, i) => (
              <div key={i} className="flex items-center justify-between p-4 border rounded-lg">
                <div>
                  <p className="font-medium">{request.name}</p>
                  <p className="text-sm text-muted-foreground">{request.type} • {request.dates}</p>
                </div>
                <div className="flex gap-2">
                  <Button size="sm" variant="outline">Reject</Button>
                  <Button size="sm">Approve</Button>
                </div>
```

pages/HRPortal.tsx

88 lines · 3,671 bytes · Page segment 3 of 3

```
                </div>
              ))}
            </div>
          </CardContent>
        </Card>
      </div>
    );
  }
```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 1 of 11

```
import { useState } from 'react';
import { useNavigate } from 'react-router-dom';
import { motion } from 'framer-motion';
import { Mail, Lock, AlertCircle, Loader2, User, CheckCircle } from 'lucide-react';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Label } from '@/components/ui/label';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Alert, AlertDescription } from '@/components/ui/alert';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { useAuth } from '@/hooks/useAuth';
import { ROUTE_PATHS } from '@/lib/index';
import { supabase } from '@/integrations/supabase/client';

export default function Login() {
  const [email, setEmail] = useState('');
  const [password, setPassword] = useState('');
  const [fullName, setFullName] = useState('');
  const [resetEmail, setResetEmail] = useState('');
  const [error, setError] = useState('');
  const [successMessage, setSuccessMessage] = useState('');
  const [isLoading, setIsLoading] = useState(false);
  const [showForgotPassword, setShowForgotPassword] = useState(false);
  const [activeTab, setActiveTab] = useState<'login' | 'signup'>('login');

  const { login, signup } = useAuth();
  const navigate = useNavigate();

  const handleLogin = async (e: React.FormEvent) => {
    e.preventDefault();
    setError('');
    setSuccessMessage('');
    setIsLoading(true);

    try {
      await login(email, password);
      navigate(ROUTE_PATHS.DASHBOARD);
    } catch (err: any) {
      setError(err?.message || 'Invalid email or password. Please try again.');
    } finally {
```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 2 of 11

```
      setIsLoading(false);
    }
  };

  const handleSignup = async (e: React.FormEvent) => {
    e.preventDefault();
    setError('');
    setSuccessMessage('');
    setIsLoading(true);

    try {
      await signup(email, password, fullName);
      navigate(ROUTE_PATHS.DASHBOARD);
    } catch (err: any) {
      setError(err?.message || 'Failed to create account. Please try again.');
    } finally {
      setIsLoading(false);
    }
  };

  const handleForgotPassword = async (e: React.FormEvent) => {
    e.preventDefault();
    setError('');
    setSuccessMessage('');
    setIsLoading(true);

    try {
      const siteUrl = window.location.origin;

      const { error } = await supabase.auth.resetPasswordForEmail(resetEmail, {
        redirectTo: `${siteUrl}/#/reset-password`,
      });

      if (error) throw error;

      setSuccessMessage('Password reset email sent! Please check your inbox.');
      setResetEmail('');

      setTimeout(() => {
        setShowForgotPassword(false);
```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 3 of 11

```
        setSuccessMessage('');
      }, 5000);
    } catch (err: any) {
      setError(err?.message || 'Failed to send reset email. Please try again.');
    } finally {
      setIsLoading(false);
    }
  };

  return (
    <div className="min-h-screen flex">
      <div className="flex-1 flex items-center justify-center p-8 bg-background">
        <motion.div
          initial={{ opacity: 0, y: 20 }}
          animate={{ opacity: 1, y: 0 }}
          transition={{ duration: 0.5 }}
          className="w-full max-w-md"
        >
          <div className="mb-8 text-center">
            <div className="inline-flex items-center justify-center mb-4">
              <img src="/logo.png" alt="Britium Express" className="h-16 w-auto" />
            </div>
            <h1 className="text-3xl font-bold text-foreground mb-2">Britium Express</h1>
            <p className="text-muted-foreground">Enterprise Delivery Management Platform</p>
          </div>

          <Card>
            <CardHeader>
              <CardTitle>Welcome</CardTitle>
              <CardDescription>Sign in to your account or create a new one</CardDescription>
            </CardHeader>

            <CardContent>
              {showForgotPassword ? (
                <div>
                  <Button
                    variant="ghost"
                    onClick={() => {
                      setShowForgotPassword(false);
                      setError('');
```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 4 of 11

```
                      setSuccessMessage('');
                    }}
                    className="mb-4"
                  >
                    ← Back to Sign In
                  </Button>

                  <form onSubmit={handleForgotPassword} className="space-y-4">
                    <div className="mb-4">
                      <h3 className="text-lg font-semibold">Reset Password</h3>
                      <p className="text-sm text-muted-foreground">
                        Enter your email address and we&apos;ll send you a link to reset your password.
                      </p>
                    </div>

                    {error && (
                      <Alert variant="destructive">
                        <AlertCircle className="h-4 w-4" />
                        <AlertDescription>{error}</AlertDescription>
                      </Alert>
                    )}

                    {successMessage && (
                      <Alert className="border-green-500 bg-green-50 text-green-900">
                        <CheckCircle className="h-4 w-4 text-green-600" />
                        <AlertDescription>{successMessage}</AlertDescription>
                      </Alert>
                    )}

                    <div className="space-y-2">
                      <Label htmlFor="reset-email">Email</Label>
                      <div className="relative">
                        <Mail className="absolute left-3 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
                        <Input
                          id="reset-email"
                          type="email"
                          placeholder="your.email@britiumexpress.com"
                          value={resetEmail}
                          onChange={(e) => setResetEmail(e.target.value)}
                          className="pl-10"
```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 5 of 11

```
                          required
                          disabled={isLoading}
                        />
                      </div>
                    </div>

                    <Button type="submit" className="w-full" disabled={isLoading}>
                      {isLoading ? (
                        <>
                          <Loader2 className="mr-2 h-4 w-4 animate-spin" />
                          Sending reset link...
                        </>
                      ) : (
                        'Send Reset Link'
                      )}
                    </Button>
                  </form>
                </div>
              ) : (
                <Tabs value={activeTab} onValueChange={(v) => setActiveTab(v as 'login' | 'signup')}>
                  <TabsList className="grid w-full grid-cols-2 mb-4">
                    <TabsTrigger value="login">Sign In</TabsTrigger>
                    <TabsTrigger value="signup">Sign Up</TabsTrigger>
                  </TabsList>

                  <TabsContent value="login">
                    <form onSubmit={handleLogin} className="space-y-4">
                      {error && (
                        <Alert variant="destructive">
                          <AlertCircle className="h-4 w-4" />
                          <AlertDescription>{error}</AlertDescription>
                        </Alert>
                      )}

                      <div className="space-y-2">
                        <Label htmlFor="login-email">Email</Label>
                        <div className="relative">
                          <Mail className="absolute left-3 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
                          <Input
                            id="login-email"
```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 6 of 11

```
                            type="email"
                            placeholder="your.email@britiumexpress.com"
                            value={email}
                            onChange={(e) => setEmail(e.target.value)}
                            className="pl-10"
                            required
                            disabled={isLoading}
                          />
                        </div>
                      </div>

                      <div className="space-y-2">
                        <div className="flex items-center justify-between">
                          <Label htmlFor="login-password">Password</Label>
                          <Button
                            type="button"
                            variant="link"
                            className="px-0 text-xs"
                            onClick={() => {
                              setShowForgotPassword(true);
                              setError('');
                              setSuccessMessage('');
                            }}
                          >
                            Forgot password?
                          </Button>
                        </div>

                        <div className="relative">
                          <Lock className="absolute left-3 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
                          <Input
                            id="login-password"
                            type="password"
                            placeholder="Enter your password"
                            value={password}
                            onChange={(e) => setPassword(e.target.value)}
                            className="pl-10"
                            required
                            disabled={isLoading}
                          />
```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 7 of 11

```
                        </div>
                      </div>

                      <Button type="submit" className="w-full" disabled={isLoading}>
                        {isLoading ? (
                          <>
                            <Loader2 className="mr-2 h-4 w-4 animate-spin" />
                            Signing in...
                          </>
                        ) : (
                          'Sign In'
                        )}
                      </Button>
                    </form>
                  </TabsContent>

                  <TabsContent value="signup">
                    <form onSubmit={handleSignup} className="space-y-4">
                      {error && (
                        <Alert variant="destructive">
                          <AlertCircle className="h-4 w-4" />
                          <AlertDescription>{error}</AlertDescription>
                        </Alert>
                      )}

                      <div className="space-y-2">
                        <Label htmlFor="signup-name">Full Name</Label>
                        <div className="relative">
                          <User className="absolute left-3 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
                          <Input
                            id="signup-name"
                            type="text"
                            placeholder="John Doe"
                            value={fullName}
                            onChange={(e) => setFullName(e.target.value)}
                            className="pl-10"
                            required
                            disabled={isLoading}
                          />
                        </div>
```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 8 of 11

```
                        </div>

                        <div className="space-y-2">
                          <Label htmlFor="signup-email">Email</Label>
                          <div className="relative">
                            <Mail className="absolute left-3 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
                            <Input
                              id="signup-email"
                              type="email"
                              placeholder="your.email@britiumexpress.com"
                              value={email}
                              onChange={(e) => setEmail(e.target.value)}
                              className="pl-10"
                              required
                              disabled={isLoading}
                            />
                          </div>
                        </div>

                        <div className="space-y-2">
                          <Label htmlFor="signup-password">Password</Label>
                          <div className="relative">
                            <Lock className="absolute left-3 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
                            <Input
                              id="signup-password"
                              type="password"
                              placeholder="Create a password (min. 6 characters)"
                              value={password}
                              onChange={(e) => setPassword(e.target.value)}
                              className="pl-10"
                              required
                              minLength={6}
                              disabled={isLoading}
                            />
                          </div>
                          <p className="text-xs text-muted-foreground">
                            Password must be at least 6 characters long
                          </p>
                        </div>

```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 9 of 11

```
                      <Button type="submit" className="w-full" disabled={isLoading}>
                        {isLoading ? (
                          <>
                            <Loader2 className="mr-2 h-4 w-4 animate-spin" />
                            Creating account...
                          </>
                        ) : (
                          'Create Account'
                        )}
                      </Button>

                      <p className="text-xs text-center text-muted-foreground">
                        By signing up, you agree to our Terms of Service and Privacy Policy
                      </p>
                    </form>
                  </TabsContent>
                </Tabs>
              )}
            </CardContent>
          </Card>
        </motion.div>
      </div>

      <div className="hidden lg:flex flex-1 relative overflow-hidden">
        <video
          className="absolute inset-0 h-full w-full object-cover"
          autoPlay
          muted
          loop
          playsInline
          preload="auto"
        >
          <source src="/background.mp4" type="video/mp4" />
        </video>

        <div className="absolute inset-0 bg-gradient-to-br from-primary/85 to-primary/65" />

        <div className="relative z-10 flex flex-col justify-center p-12 text-white">
          <motion.div
            initial={{ opacity: 0, x: 20 }}
```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 10 of 11

```
            animate={{ opacity: 1, x: 0 }}
            transition={{ duration: 0.5, delay: 0.2 }}
          >
            <h2 className="text-4xl font-bold mb-6">
              Streamline Your Delivery Operations
            </h2>
            <p className="text-xl mb-8 text-white/90">
              Real-time tracking, route optimization, and comprehensive analytics for modern logistics.
            </p>

            <div className="space-y-4">
              <div className="flex items-start gap-3">
                <div className="w-6 h-6 rounded-full bg-white/20 flex items-center justify-center flex-shrink-0 mt-1">
                  <svg className="w-4 h-4" fill="currentColor" viewBox="0 0 20 20">
                    <path
                      fillRule="evenodd"
                      d="M16.707 5.293a1 1 0 010 1.414l-8 8a1 1 0 01-1.414 0l-4-4a1 1 0 011.414-1.414L8 12.586l7.293-7.293a1 1 0 011.414 0z"
                      clipRule="evenodd"
                    />
                  </svg>
                </div>
                <div>
                  <h3 className="font-semibold text-lg mb-1">Multi-Portal Access</h3>
                  <p className="text-white/80">
                    Specialized interfaces for supervisors, drivers, warehouse staff, and customer service.
                  </p>
                </div>
              </div>

              <div className="flex items-start gap-3">
                <div className="w-6 h-6 rounded-full bg-white/20 flex items-center justify-center flex-shrink-0 mt-1">
                  <svg className="w-4 h-4" fill="currentColor" viewBox="0 0 20 20">
                    <path
                      fillRule="evenodd"
                      d="M16.707 5.293a1 1 0 010 1.414l-8 8a1 1 0 01-1.414 0l-4-4a1 1 0 011.414-1.414L8 12.586l7.293-7.293a1 1 0 011.414 0z"
                      clipRule="evenodd"
                    />
                  </svg>
                </div>
                <div>
```

pages/Login.tsx

431 lines · 17,814 bytes · Page segment 11 of 11

```
                  <h3 className="font-semibold text-lg mb-1">Real-Time Tracking</h3>
                  <p className="text-white/80">
                    Live updates on delivery status, driver locations, and route progress.
                  </p>
                </div>
              </div>

              <div className="flex items-start gap-3">
                <div className="w-6 h-6 rounded-full bg-white/20 flex items-center justify-center flex-shrink-0 mt-1">
                  <svg className="w-4 h-4" fill="currentColor" viewBox="0 0 20 20">
                    <path
                      fillRule="evenodd"
                      d="M16.707 5.293a1 1 0 010 1.414l-8 8a1 1 0 01-1.414 0l-4-4a1 1 0 011.414-1.414L8 12.586l7.293-7.293a1 1 0 011.414 0z"
                      clipRule="evenodd"
                    />
                  </svg>
                </div>
                <div>
                  <h3 className="font-semibold text-lg mb-1">Advanced Analytics</h3>
                  <p className="text-white/80">
                    Comprehensive reports on performance, revenue, and efficiency.
                  </p>
                </div>
              </div>
            </div>
          </motion.div>
        </div>
      </div>
    </div>
  );
}
```

pages/MarketingPortal.tsx

312 lines · 14,887 bytes · Page segment 1 of 8

```
import { useState } from 'react';
import { useLocation } from 'react-router-dom';
import { motion } from 'framer-motion';
import {
  Megaphone, Users, BarChart3, TrendingUp, Plus,
  Mail, MessageSquare, Star, RefreshCw, Eye,
  Target, Gift, Percent, Globe
} from 'lucide-react';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Badge } from '@/components/ui/badge';
import { Input } from '@/components/ui/input';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { analyticsAPI, shipmentsAPI } from '@/api/supabase';
import { useQuery } from '@/hooks/useSupabaseQuery';
import { formatDate } from '@/lib/index';

export default function MarketingPortal() {
  const location = useLocation();
  const getInitialMktTab = () => {
    if (location.pathname.includes('/campaigns')) return 'campaigns';
    if (location.pathname.includes('/merchants')) return 'merchants';
    if (location.pathname.includes('/overview')) return 'overview';
    return 'overview';
  };
  const [activeTab, setActiveTab] = useState(getInitialMktTab());

  const { data: analyticsData, isLoading: analyticsLoading, refetch } = useQuery(() =>
    analyticsAPI.getOverview()
  );
  const { data: shipmentData } = useQuery(() => shipmentsAPI.getAll());

  const raw = (analyticsData as any) || {};
  const stats = {
    total_shipments: raw.shipments?.total || 0,
    delivered_shipments: raw.shipments?.delivered || 0,
    in_transit_shipments: raw.shipments?.in_transit || 0,
    failed_shipments: raw.shipments?.failed || 0,
    delivery_rate: raw.shipments?.total > 0
      ? (raw.shipments.delivered / raw.shipments.total) * 100
```

pages/MarketingPortal.tsx

312 lines · 14,887 bytes · Page segment 2 of 8

```
      : 0,
  };
  const shipments = (shipmentData as any[]) || [];

  // Calculate merchant acquisition metrics from shipments
  const merchantIds = new Set(shipments.map((s: any) => s.merchant_id).filter(Boolean));
  const totalMerchants = merchantIds.size;
  const newMerchantsThisMonth = totalMerchants; // simplified — filter by created_at in production

  const kpis = [
    { label: 'Total Merchants', value: totalMerchants, icon: <Users className="w-5 h-5" />, color: 'text-primary' },
    { label: 'Total Shipments', value: stats.total_shipments || shipments.length, icon: <BarChart3 className="w-5 h-5" />, color: 'text-blue-600' },
    { label: 'Success Rate', value: stats.delivery_rate ? `${stats.delivery_rate.toFixed(1)}%` : '-', icon: <TrendingUp className="w-5 h-5" />, color: 'text-green-600' },
    { label: 'Active Campaigns', value: 0, icon: <Megaphone className="w-5 h-5" />, color: 'text-purple-600' },
  ];

  // Placeholder campaigns (replace with DB data once campaigns table is added)
  const campaigns = [
    { id: 1, name: 'Ramadan Express Promo', type: 'discount', status: 'planned', reach: 0, start: '2026-05-01' },
    { id: 2, name: 'New Merchant Onboarding', type: 'email', status: 'draft', reach: 0, start: '2026-04-20' },
    { id: 3, name: 'Referral Program', type: 'referral', status: 'draft', reach: 0, start: '2026-05-15' },
  ];

  const typeIcon = (type: string) => {
    switch (type) {
      case 'email': return <Mail className="w-4 h-4" />;
      case 'sms': return <MessageSquare className="w-4 h-4" />;
      case 'discount': case 'promo': return <Percent className="w-4 h-4" />;
      case 'referral': return <Gift className="w-4 h-4" />;
      default: return <Globe className="w-4 h-4" />;
    }
  };

  const statusColor = (status: string) => {
    switch (status) {
      case 'active': return 'bg-green-100 text-green-800';
      case 'planned': return 'bg-blue-100 text-blue-800';
      case 'draft': return 'bg-gray-100 text-gray-800';
```

pages/MarketingPortal.tsx

312 lines · 14,887 bytes · Page segment 3 of 8

```
      case 'ended': return 'bg-red-100 text-red-800';
      default: return 'bg-gray-100 text-gray-800';
    }
  };

  return (
    <div className="min-h-screen bg-background">
      {/* Header */}
      <div className="bg-gradient-to-br from-primary/10 via-background to-accent/10 border-b px-6 py-8">
        <div className="flex items-center justify-between">
          <div>
            <h1 className="text-3xl font-bold flex items-center gap-2">
              <Megaphone className="w-8 h-8 text-primary" />
              Marketing Portal
            </h1>
            <p className="text-muted-foreground mt-1">Campaigns, merchant insights, and growth analytics</p>
          </div>
          <div className="flex gap-2">
            <Button variant="outline" onClick={refetch}>
              <RefreshCw className="w-4 h-4 mr-2" />
              Refresh
            </Button>
            <Button>
              <Plus className="w-4 h-4 mr-2" />
              New Campaign
            </Button>
          </div>
        </div>
      </div>

      <div className="p-6 space-y-6">
        {/* KPI Cards */}
        <div className="grid grid-cols-2 md:grid-cols-4 gap-4">
          {kpis.map((kpi, i) => (
            <motion.div key={i} whileHover={{ scale: 1.02 }}>
              <Card>
                <CardContent className="p-5">
                  <div className={`flex items-center gap-2 mb-2 ${kpi.color}`}>
                    {kpi.icon}
                    <span className="text-sm text-muted-foreground">{kpi.label}</span>
```

pages/MarketingPortal.tsx

312 lines · 14,887 bytes · Page segment 4 of 8

```
                  </div>
                  <div className="text-3xl font-bold">{analyticsLoading ? '…' : kpi.value}</div>
                </CardContent>
              </Card>
            </motion.div>
          ))}
        </div>

        <Tabs value={activeTab} onValueChange={setActiveTab}>
          <TabsList>
            <TabsTrigger value="overview">
              <BarChart3 className="w-4 h-4 mr-2" />
              Overview
            </TabsTrigger>
            <TabsTrigger value="campaigns">
              <Megaphone className="w-4 h-4 mr-2" />
              Campaigns
            </TabsTrigger>
            <TabsTrigger value="merchants">
              <Users className="w-4 h-4 mr-2" />
              Merchant Insights
            </TabsTrigger>
          </TabsList>

          {/* Overview Tab */}
          <TabsContent value="overview" className="mt-4">
            <div className="grid md:grid-cols-2 gap-4">
              <Card>
                <CardHeader>
                  <CardTitle>Delivery Performance</CardTitle>
                  <CardDescription>Current platform-wide metrics</CardDescription>
                </CardHeader>
                <CardContent>
                  {analyticsLoading ? (
                    <div className="text-center py-8 text-muted-foreground">Loading...</div>
                  ) : (
                    <div className="space-y-4">
                      {[
                        { label: 'Total Shipments', value: stats.total_shipments || shipments.length, max: Math.max(stats.total_shipments || shipments.length, 1), color: 'bg-primary' },
```

pages/MarketingPortal.tsx

312 lines · 14,887 bytes · Page segment 5 of 8

```
                        { label: 'Delivered', value: stats.delivered_shipments || shipments.filter((s: any) => s.status === 'delivered').length, max: Math.max(stats.total_shipments || shipments.length, 1), color: 'bg-green-500' },
                        { label: 'In Transit', value: stats.in_transit_shipments || shipments.filter((s: any) => s.status?.includes('transit')).length, max: Math.max(stats.total_shipments || shipments.length, 1), color: 'bg-blue-500' },
                        { label: 'Failed', value: stats.failed_shipments || shipments.filter((s: any) => s.status === 'failed').length, max: Math.max(stats.total_shipments || shipments.length, 1), color: 'bg-red-500' },
                      ].map((row) => (
                        <div key={row.label}>
                          <div className="flex justify-between text-sm mb-1">
                            <span>{row.label}</span>
                            <span className="font-medium">{row.value}</span>
                          </div>
                          <div className="w-full bg-muted rounded-full h-2">
                            <div
                              className={`h-2 rounded-full ${row.color}`}
                              style={{ width: `${Math.min((row.value / row.max) * 100, 100)}%` }}
                            />
                          </div>
                        </div>
                      ))}
                    </div>
                  )}
                </CardContent>
              </Card>

              <Card>
                <CardHeader>
                  <CardTitle>Growth Targets</CardTitle>
                  <CardDescription>2026 Q2 marketing objectives</CardDescription>
                </CardHeader>
                <CardContent>
                  <div className="space-y-4">
                    {[
                      { label: 'New Merchant Signups', target: 50, current: totalMerchants, unit: 'merchants' },
                      { label: 'Monthly Shipment Volume', target: 5000, current: shipments.length, unit: 'shipments' },
                      { label: 'Customer Retention Rate', target: 85, current: 0, unit: '%' },
                    ].map((goal) => (
                      <div key={goal.label}>
                        <div className="flex justify-between text-sm mb-1">
                          <span>{goal.label}</span>
```

pages/MarketingPortal.tsx

312 lines · 14,887 bytes · Page segment 6 of 8

```
                          <span className="font-medium text-muted-foreground">{goal.current} / {goal.target} {goal.unit}</span>
                        </div>
                        <div className="w-full bg-muted rounded-full h-2">
                          <div
                            className="h-2 rounded-full bg-primary"
                            style={{ width: `${Math.min((goal.current / goal.target) * 100, 100)}%` }}
                          />
                        </div>
                      </div>
                    ))}
                  </div>
                </CardContent>
              </Card>
            </div>
          </TabsContent>

          {/* Campaigns Tab */}
          <TabsContent value="campaigns" className="mt-4">
            <Card>
              <CardHeader>
                <div className="flex items-center justify-between">
                  <CardTitle>Marketing Campaigns</CardTitle>
                  <Button>
                    <Plus className="w-4 h-4 mr-2" />
                    Create Campaign
                  </Button>
                </div>
              </CardHeader>
              <CardContent>
                <div className="space-y-3">
                  {campaigns.map((c) => (
                    <div key={c.id} className="flex items-center justify-between p-4 border rounded-lg hover:bg-muted/30">
                      <div className="flex items-center gap-3">
                        <div className="p-2 bg-primary/10 rounded-lg text-primary">
                          {typeIcon(c.type)}
                        </div>
                        <div>
                          <p className="font-medium">{c.name}</p>
                          <p className="text-sm text-muted-foreground capitalize">
                            {c.type} campaign • Starts {c.start}
```

pages/MarketingPortal.tsx

312 lines · 14,887 bytes · Page segment 7 of 8

```
                          </p>
                        </div>
                      </div>
                      <div className="flex items-center gap-2">
                        <span className={`text-xs px-2 py-1 rounded-full font-medium ${statusColor(c.status)}`}>
                          {c.status}
                        </span>
                        <Button size="sm" variant="outline">
                          <Eye className="w-3 h-3 mr-1" />
                          View
                        </Button>
                      </div>
                    </div>
                  ))}
                  <div className="text-center pt-4 text-muted-foreground text-sm">
                    <p>Campaign data will be stored in database once the campaigns module is fully enabled.</p>
                  </div>
                </div>
              </CardContent>
            </Card>
          </TabsContent>

          {/* Merchant Insights Tab */}
          <TabsContent value="merchants" className="mt-4">
            <Card>
              <CardHeader>
                <CardTitle>Merchant Insights</CardTitle>
                <CardDescription>Top merchants by shipment volume</CardDescription>
              </CardHeader>
              <CardContent>
                {shipments.length === 0 ? (
                  <div className="text-center py-12 text-muted-foreground">
                    <Users className="w-16 h-16 mx-auto mb-3 opacity-20" />
                    <p className="text-lg font-medium">No merchant data yet</p>
                    <p className="text-sm">Merchant insights will appear as shipments are created.</p>
                  </div>
                ) : (
                  <div className="overflow-x-auto">
                    <table className="w-full text-sm">
                      <thead>
```

pages/MarketingPortal.tsx

312 lines · 14,887 bytes · Page segment 8 of 8

```
                        <tr className="border-b text-left text-muted-foreground">
                          <th className="pb-3 pr-4 font-medium">Merchant ID</th>
                          <th className="pb-3 pr-4 font-medium">Shipments</th>
                          <th className="pb-3 font-medium">Delivery Rate</th>
                        </tr>
                      </thead>
                      <tbody className="divide-y">
                        {Array.from(merchantIds).slice(0, 10).map((mid: unknown) => {
                          const mShipments = shipments.filter((s: any) => s.merchant_id === mid);
                          const mDelivered = mShipments.filter((s: any) => s.status === 'delivered').length;
                          const rate = mShipments.length > 0 ? Math.round((mDelivered / mShipments.length) * 100) : 0;
                          return (
                            <tr key={String(mid)} className="hover:bg-muted/30">
                              <td className="py-3 pr-4 font-mono text-primary">{String(mid).slice(0, 8)}…</td>
                              <td className="py-3 pr-4">{mShipments.length}</td>
                              <td className="py-3">
                                <div className="flex items-center gap-2">
                                  <div className="w-24 bg-muted rounded-full h-1.5">
                                    <div className="h-1.5 rounded-full bg-green-500" style={{ width: `${rate}%` }} />
                                  </div>
                                  <span>{rate}%</span>
                                </div>
                              </td>
                            </tr>
                          );
                        })}
                      </tbody>
                    </table>
                  </div>
                )}
              </CardContent>
            </Card>
          </TabsContent>
        </Tabs>
      </div>
    </div>
  );
}
```

pages/MerchantPortal.tsx

96 lines · 3,932 bytes · Page segment 1 of 3

```
import { Store, Package, PlusCircle, BarChart3 } from 'lucide-react';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Badge } from '@/components/ui/badge';

export default function MerchantPortal() {
  return (
    <div className="space-y-6">
      <div>
        <h1 className="text-3xl font-bold">Merchant Portal</h1>
        <p className="text-muted-foreground">Manage your shipments and deliveries</p>
      </div>

      <div className="grid gap-6 md:grid-cols-4">
        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Total Shipments</CardTitle>
            <Package className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">1,234</div>
            <p className="text-xs text-muted-foreground">+89 this month</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">In Transit</CardTitle>
            <Package className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">45</div>
            <p className="text-xs text-muted-foreground">Active deliveries</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Delivered</CardTitle>
            <Package className="h-4 w-4 text-muted-foreground" />
```

pages/MerchantPortal.tsx

96 lines · 3,932 bytes · Page segment 2 of 3

```
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">1,156</div>
            <p className="text-xs text-muted-foreground">93.7% success rate</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Revenue</CardTitle>
            <BarChart3 className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">$23,450</div>
            <p className="text-xs text-muted-foreground">This month</p>
          </CardContent>
        </Card>
      </div>

      <Card>
        <CardHeader>
          <div className="flex items-center justify-between">
            <div>
              <CardTitle>Recent Shipments</CardTitle>
              <CardDescription>Your latest delivery orders</CardDescription>
            </div>
            <Button>
              <PlusCircle className="mr-2 h-4 w-4" />
              Create Shipment
            </Button>
          </div>
        </CardHeader>
        <CardContent>
          <div className="space-y-4">
            {[
              { awb: 'AWB123456', status: 'In Transit', destination: 'New York, NY' },
              { awb: 'AWB123457', status: 'Out for Delivery', destination: 'Los Angeles, CA' },
              { awb: 'AWB123458', status: 'Delivered', destination: 'Chicago, IL' },
            ].map((shipment, i) => (
              <div key={i} className="flex items-center justify-between p-4 border rounded-lg">
```

pages/MerchantPortal.tsx

96 lines · 3,932 bytes · Page segment 3 of 3

```
                <div>
                  <p className="font-medium font-mono">{shipment.awb}</p>
                  <p className="text-sm text-muted-foreground">{shipment.destination}</p>
                </div>
                <div className="flex items-center gap-2">
                  <Badge>{shipment.status}</Badge>
                  <Button size="sm" variant="outline">Track</Button>
                </div>
              </div>
            ))}
          </div>
        </CardContent>
      </Card>
    </div>
  );
}
```

pages/not-found/Index.tsx

27 lines · 739 bytes · Page segment 1 of 1

```
import { useLocation } from "react-router-dom";
import { useEffect } from "react";

const NotFound = () => {
  const location = useLocation();

  useEffect(() => {
    console.error(
      "404 Error: User attempted to access non-existent route:",
      location.pathname
    );
  }, [location.pathname]);

  return (
    <div className="min-h-screen flex items-center justify-center bg-gray-100">
      <div className="text-center">
        <h1 className="text-4xl font-bold mb-4">404</h1>
        <p className="text-xl text-gray-600 mb-4">Oops! Page not found</p>
        <a href="/" className="text-blue-500 hover:text-blue-700 underline">
          Return to Home
        </a>
      </div>
    </div>
  );
};

export default NotFound;
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 1 of 15

```
// QR Code Management Page
import React, { useState, useEffect } from 'react';
import { Card, CardContent, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Badge } from '@/components/ui/badge';
import { Input } from '@/components/ui/input';
import { Textarea } from '@/components/ui/textarea';
import {
  QrCode,
  Package,
  Truck,
  User,
  Warehouse,
  Scan,
  History,
  CheckCircle,
  Clock,
  AlertTriangle,
  Download,
  Printer,
  Eye,
  Search,
  Filter,
  RefreshCw,
  X,
  Camera
} from 'lucide-react';
import { useLanguage } from '@/hooks/useLanguage';
import { IMAGES } from '@/assets/images';

interface QRCodeData {
  id: string;
  qr_code: string;
  qr_type: 'SHIPMENT' | 'PARCEL' | 'VEHICLE' | 'RIDER' | 'WAREHOUSE';
  reference_id: string;
  reference_type: string;
  status: 'ACTIVE' | 'SCANNED' | 'EXPIRED';
  data: any;
  created_at: string;
  expires_at?: string;
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 2 of 15

```
  scan_count: number;
  last_scanned_at?: string;
  last_scanned_by?: string;
  last_scan_location?: any;
}

interface ScanHistory {
  id: string;
  qr_code_id: string;
  scanned_by: string;
  scanned_at: string;
  scan_location?: any;
  device_info?: any;
  scan_result: 'SUCCESS' | 'FAILED' | 'EXPIRED';
  notes?: string;
}

export default function QRCodeManagement() {
  const { t, language } = useLanguage();
  const [activeTab, setActiveTab] = useState<'GENERATE' | 'SCAN' | 'MANAGE' | 'HISTORY'>('GENERATE');
  const [qrCodes, setQrCodes] = useState<QRCodeData[]>([]);
  const [scanHistory, setScanHistory] = useState<ScanHistory[]>([]);
  const [loading, setLoading] = useState(false);
  const [scannerActive, setScannerActive] = useState(false);
  const [selectedQR, setSelectedQR] = useState<QRCodeData | null>(null);
  const [searchTerm, setSearchTerm] = useState('');
  const [filterType, setFilterType] = useState<string>('ALL');
  const [filterStatus, setFilterStatus] = useState<string>('ALL');

  // Generation form state
  const [generateForm, setGenerateForm] = useState({
    type: 'SHIPMENT',
    reference_id: '',
    reference_type: '',
    expires_in_hours: 24,
    data: {}
  });

  useEffect(() => {
    loadQRCodes();
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 3 of 15

```
    loadScanHistory();
  }, []);

  const loadQRCodes = async () => {
    try {
      setLoading(true);
      // Mock data for demonstration
      const mockQRCodes: QRCodeData[] = [
        {
          id: '1',
          qr_code: 'QR001',
          qr_type: 'SHIPMENT',
          reference_id: 'SHP-2026-001',
          reference_type: 'shipment',
          status: 'ACTIVE',
          data: { weight: '5kg', destination: 'Yangon' },
          created_at: new Date().toISOString(),
          scan_count: 0
        }
      ];
      setQrCodes(mockQRCodes);
    } catch (error) {
      console.error('Error loading QR codes:', error);
    } finally {
      setLoading(false);
    }
  };

  const loadScanHistory = async () => {
    try {
      const mockHistory: ScanHistory[] = [];
      setScanHistory(mockHistory);
    } catch (error) {
      console.error('Error loading scan history:', error);
    }
  };

  const generateQRCode = async () => {
    try {
      setLoading(true);
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 4 of 15

```

      const newQR: QRCodeData = {
        id: Date.now().toString(),
        qr_code: `QR${Date.now()}`,
        qr_type: generateForm.type as any,
        reference_id: generateForm.reference_id,
        reference_type: generateForm.reference_type,
        status: 'ACTIVE',
        data: generateForm.data,
        created_at: new Date().toISOString(),
        expires_at: new Date(Date.now() + generateForm.expires_in_hours * 60 * 60 * 1000).toISOString(),
        scan_count: 0
      };

      setQrCodes([...qrCodes, newQR]);
      setGenerateForm({
        type: 'SHIPMENT',
        reference_id: '',
        reference_type: '',
        expires_in_hours: 24,
        data: {}
      });

      alert(language === 'mm'
        ? 'QR □□□□□□□□ □□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□'
        : 'QR Code generated successfully'
      );
    } catch (error) {
      console.error('Error generating QR code:', error);
      alert(language === 'mm'
        ? 'QR □□□□ □□□□□□□□□□ □□□□□□□□□□□□□□'
        : 'Failed to generate QR code'
      );
    } finally {
      setLoading(false);
    }
  };

  const handleQRScan = async (scanResult: string) => {
    try {
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 5 of 15

```
      setLoading(true);

      const newScan: ScanHistory = {
        id: Date.now().toString(),
        qr_code_id: scanResult,
        scanned_by: 'current_user',
        scanned_at: new Date().toISOString(),
        scan_result: 'SUCCESS'
      };

      setScanHistory([newScan, ...scanHistory]);
      setScannerActive(false);

      alert(language === 'mm'
        ? 'QR □□□□□□□□ □□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□'
        : 'QR Code scanned successfully'
      );
    } catch (error) {
      console.error('Error processing scan:', error);
      alert(language === 'mm'
        ? '□□□□□□□□□□□□□ □□□□□□□□□□□□'
        : 'Scan processing error'
      );
    } finally {
      setLoading(false);
    }
  };

  const getStatusColor = (status: string) => {
    switch (status) {
      case 'ACTIVE': return 'bg-green-100 text-green-800';
      case 'SCANNED': return 'bg-blue-100 text-blue-800';
      case 'EXPIRED': return 'bg-red-100 text-red-800';
      default: return 'bg-gray-100 text-gray-800';
    }
  };

  const getTypeIcon = (type: string) => {
    switch (type) {
      case 'SHIPMENT': return <Package className="w-4 h-4" />;
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 6 of 15

```
      case 'PARCEL': return <Package className="w-4 h-4" />;
      case 'VEHICLE': return <Truck className="w-4 h-4" />;
      case 'RIDER': return <User className="w-4 h-4" />;
      case 'WAREHOUSE': return <Warehouse className="w-4 h-4" />;
      default: return <QrCode className="w-4 h-4" />;
    }
  };

  const filteredQRCodes = qrCodes.filter(qr => {
    const matchesSearch = qr.reference_id.toLowerCase().includes(searchTerm.toLowerCase()) ||
                          qr.qr_code.toLowerCase().includes(searchTerm.toLowerCase());
    const matchesType = filterType === 'ALL' || qr.qr_type === filterType;
    const matchesStatus = filterStatus === 'ALL' || qr.status === filterStatus;
    return matchesSearch && matchesType && matchesStatus;
  });

  const renderGenerateTab = () => (
    <div className="space-y-6">
      <Card>
        <CardHeader>
          <CardTitle className="flex items-center gap-2">
            <QrCode className="w-5 h-5" />
            {t('qr.generate')}
          </CardTitle>
        </CardHeader>
        <CardContent className="space-y-4">
          <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
            <div>
              <label className="block text-sm font-medium mb-2">
                {t('qr.type')}
              </label>
              <select
                value={generateForm.type}
                onChange={(e) => setGenerateForm({...generateForm, type: e.target.value})}
                className="w-full px-3 py-2 border rounded-md"
              >
                <option value="SHIPMENT">{t('qr.shipment')}</option>
                <option value="PARCEL">{t('qr.parcel')}</option>
                <option value="VEHICLE">{t('qr.vehicle')}</option>
                <option value="RIDER">{t('qr.rider')}</option>
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 7 of 15

```
                <option value="WAREHOUSE">{t('qr.warehouse')}</option>
              </select>
            </div>

            <div>
              <label className="block text-sm font-medium mb-2">
                {t('qr.referenceId')}
              </label>
              <Input
                value={generateForm.reference_id}
                onChange={(e) => setGenerateForm({...generateForm, reference_id: e.target.value})}
                placeholder={t('qr.enterReferenceId')}
              />
            </div>

            <div>
              <label className="block text-sm font-medium mb-2">
                {t('qr.referenceType')}
              </label>
              <Input
                value={generateForm.reference_type}
                onChange={(e) => setGenerateForm({...generateForm, reference_type: e.target.value})}
                placeholder={t('qr.enterReferenceType')}
              />
            </div>

            <div>
              <label className="block text-sm font-medium mb-2">
                {t('qr.expiresInHours')}
              </label>
              <Input
                type="number"
                value={generateForm.expires_in_hours}
                onChange={(e) => setGenerateForm({...generateForm, expires_in_hours: parseInt(e.target.value)})}
                min="1"
                max="8760"
              />
            </div>
          </div>

```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 8 of 15

```
          <Button
            onClick={generateQRCode}
            disabled={loading || !generateForm.reference_id}
            className="w-full"
            size="lg"
          >
            {loading ? (
              <RefreshCw className="w-4 h-4 mr-2 animate-spin" />
            ) : (
              <QrCode className="w-4 h-4 mr-2" />
            )}
            {t('qr.generateButton')}
          </Button>
        </CardContent>
      </Card>
    </div>
  );

  const renderScanTab = () => (
    <div className="space-y-6">
      <Card>
        <CardHeader>
          <CardTitle className="flex items-center gap-2">
            <Scan className="w-5 h-5" />
            {t('qr.scanQRCode')}
          </CardTitle>
        </CardHeader>
        <CardContent>
          {scannerActive ? (
            <div className="space-y-4">
              <div className="border-2 border-dashed border-gray-300 rounded-lg p-8 text-center">
                <Camera className="w-16 h-16 mx-auto mb-4 text-gray-400" />
                <p className="text-gray-600 mb-4">{t('qr.scannerActive')}</p>
                <Input
                  placeholder={t('qr.enterQRCode')}
                  onKeyPress={(e) => {
                    if (e.key === 'Enter') {
                      handleQRScan((e.target as HTMLInputElement).value);
                      (e.target as HTMLInputElement).value = '';
                    }
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 9 of 15

```
                  }}
                  className="max-w-md mx-auto"
                />
              </div>
              <Button
                variant="outline"
                onClick={() => setScannerActive(false)}
                className="w-full"
              >
                {t('qr.closeScanner')}
              </Button>
            </div>
          ) : (
            <Button
              onClick={() => setScannerActive(true)}
              className="w-full"
              size="lg"
            >
              <Scan className="w-4 h-4 mr-2" />
              {t('qr.startScanning')}
            </Button>
          )}
        </CardContent>
      </Card>
    </div>
  );

  const renderManageTab = () => (
    <div className="space-y-6">
      <Card>
        <CardContent className="pt-6">
          <div className="grid grid-cols-1 md:grid-cols-3 gap-4">
            <Input
              placeholder={t('common.search')}
              value={searchTerm}
              onChange={(e) => setSearchTerm(e.target.value)}
            />
            <select
              value={filterType}
              onChange={(e) => setFilterType(e.target.value)}
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 10 of 15

```
              className="px-3 py-2 border rounded-md"
            >
              <option value="ALL">{t('qr.allTypes')}</option>
              <option value="SHIPMENT">{t('qr.shipment')}</option>
              <option value="PARCEL">{t('qr.parcel')}</option>
              <option value="VEHICLE">{t('qr.vehicle')}</option>
              <option value="RIDER">{t('qr.rider')}</option>
              <option value="WAREHOUSE">{t('qr.warehouse')}</option>
            </select>
            <select
              value={filterStatus}
              onChange={(e) => setFilterStatus(e.target.value)}
              className="px-3 py-2 border rounded-md"
            >
              <option value="ALL">{t('qr.allStatus')}</option>
              <option value="ACTIVE">{t('qr.active')}</option>
              <option value="SCANNED">{t('qr.scanned')}</option>
              <option value="EXPIRED">{t('qr.expired')}</option>
            </select>
          </div>
        </CardContent>
      </Card>

      <div className="grid gap-4">
        {loading ? (
          <div className="text-center py-8">
            <RefreshCw className="w-8 h-8 animate-spin mx-auto mb-2" />
            <p>{t('common.loading')}</p>
          </div>
        ) : filteredQRCodes.length === 0 ? (
          <Card>
            <CardContent className="text-center py-8">
              <QrCode className="w-12 h-12 text-gray-400 mx-auto mb-4" />
              <p className="text-gray-500">{t('qr.noQRCodes')}</p>
            </CardContent>
          </Card>
        ) : (
          filteredQRCodes.map((qr) => (
            <Card key={qr.id} className="hover:shadow-md transition-shadow">
              <CardContent className="p-4">
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 11 of 15

```
                <div className="flex items-start justify-between">
                  <div className="flex-1">
                    <div className="flex items-center gap-2 mb-2">
                      {getTypeIcon(qr.qr_type)}
                      <span className="font-medium">{qr.reference_id}</span>
                      <Badge className={getStatusColor(qr.status)}>
                        {qr.status}
                      </Badge>
                    </div>

                    <div className="grid grid-cols-2 md:grid-cols-4 gap-2 text-sm text-gray-600">
                      <div>
                        <span className="font-medium">{t('qr.type')}:</span>
                        <span className="ml-1">{qr.qr_type}</span>
                      </div>
                      <div>
                        <span className="font-medium">{t('qr.scans')}:</span>
                        <span className="ml-1">{qr.scan_count}</span>
                      </div>
                      <div>
                        <span className="font-medium">{t('qr.created')}:</span>
                        <span className="ml-1">{new Date(qr.created_at).toLocaleDateString()}</span>
                      </div>
                      {qr.expires_at && (
                        <div>
                          <span className="font-medium">{t('qr.expires')}:</span>
                          <span className="ml-1">{new Date(qr.expires_at).toLocaleDateString()}</span>
                        </div>
                      )}
                    </div>
                  </div>

                  <div className="flex gap-2">
                    <Button
                      size="sm"
                      variant="outline"
                      onClick={() => setSelectedQR(qr)}
                    >
                      <Eye className="w-4 h-4" />
                    </Button>
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 12 of 15

```
                  </div>
                </div>
              </CardContent>
            </Card>
          ))
        )}
      </div>
    </div>
  );

  const renderHistoryTab = () => (
    <div className="space-y-6">
      <Card>
        <CardHeader>
          <CardTitle className="flex items-center gap-2">
            <History className="w-5 h-5" />
            {t('qr.scanHistory')}
          </CardTitle>
        </CardHeader>
        <CardContent>
          <div className="space-y-4">
            {scanHistory.length === 0 ? (
              <div className="text-center py-8">
                <History className="w-12 h-12 text-gray-400 mx-auto mb-4" />
                <p className="text-gray-500">{t('qr.noScanHistory')}</p>
              </div>
            ) : (
              scanHistory.map((scan) => (
                <div key={scan.id} className="flex items-center justify-between p-3 border rounded">
                  <div className="flex-1">
                    <div className="flex items-center gap-2 mb-1">
                      <Badge variant={scan.scan_result === 'SUCCESS' ? 'default' : 'destructive'}>
                        {scan.scan_result}
                      </Badge>
                      <span className="text-sm text-gray-600">
                        {new Date(scan.scanned_at).toLocaleString()}
                      </span>
                    </div>
                    <div className="text-sm">
                      <span className="font-medium">{t('qr.scannedBy')}:</span>
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 13 of 15

```
                      <span className="ml-1">{scan.scanned_by}</span>
                    </div>
                  </div>
                </div>
              ))
            )}
          </div>
        </CardContent>
      </Card>
    </div>
  );

  return (
    <div className="min-h-screen bg-background relative">
      <div
        className="absolute inset-0 z-0 opacity-30"
        style={{
          backgroundImage: `url(${IMAGES.SCREENSHOT_9749})`,
          backgroundSize: 'cover',
          backgroundPosition: 'center',
        }}
      />
      <div className="absolute inset-0 bg-gradient-to-b from-background/50 via-transparent to-background/70" />

      <div className="relative z-10 container mx-auto p-6">
        <div className="flex items-center justify-between mb-6">
          <h1 className="text-3xl font-bold">
            {t('qr.title')}
          </h1>
          <Button onClick={() => { loadQRCodes(); loadScanHistory(); }}>
            <RefreshCw className="w-4 h-4 mr-2" />
            {t('common.refresh')}
          </Button>
        </div>

        <div className="flex space-x-1 mb-6 bg-gray-100 p-1 rounded-lg">
          {[
            { key: 'GENERATE', label: t('qr.generate'), icon: QrCode },
            { key: 'SCAN', label: t('qr.scan'), icon: Scan },
            { key: 'MANAGE', label: t('qr.manage'), icon: Package },
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 14 of 15

```
            { key: 'HISTORY', label: t('qr.history'), icon: History }
          ].map(({ key, label, icon: Icon }) => (
            <button
              key={key}
              onClick={() => setActiveTab(key as any)}
              className={`flex items-center gap-2 px-4 py-2 rounded-md transition-colors ${
                activeTab === key
                  ? 'bg-white text-primary shadow-sm'
                  : 'text-gray-600 hover:text-gray-900'
              }`}
            >
              <Icon className="w-4 h-4" />
              {label}
            </button>
          ))}
        </div>

        {activeTab === 'GENERATE' && renderGenerateTab()}
        {activeTab === 'SCAN' && renderScanTab()}
        {activeTab === 'MANAGE' && renderManageTab()}
        {activeTab === 'HISTORY' && renderHistoryTab()}

        {selectedQR && (
          <div className="fixed inset-0 bg-black bg-opacity-50 flex items-center justify-center p-4 z-50">
            <Card className="w-full max-w-2xl max-h-[90vh] overflow-y-auto">
              <CardHeader>
                <CardTitle className="flex items-center justify-between">
                  <span>{t('qr.details')}</span>
                  <Button variant="ghost" onClick={() => setSelectedQR(null)}>
                    <X className="w-4 h-4" />
                  </Button>
                </CardTitle>
              </CardHeader>
              <CardContent className="space-y-4">
                <div className="grid grid-cols-2 gap-4">
                  <div>
                    <label className="text-sm font-medium text-gray-600">
                      {t('qr.referenceId')}
                    </label>
                    <p className="font-mono">{selectedQR.reference_id}</p>
```

pages/QRCodeManagement.tsx

599 lines · 21,151 bytes · Page segment 15 of 15

```
                    </div>
                    <div>
                      <label className="text-sm font-medium text-gray-600">
                        {t('qr.type')}
                      </label>
                      <p>{selectedQR.qr_type}</p>
                    </div>
                    <div>
                      <label className="text-sm font-medium text-gray-600">
                        {t('qr.status')}
                      </label>
                      <Badge className={getStatusColor(selectedQR.status)}>
                        {selectedQR.status}
                      </Badge>
                    </div>
                    <div>
                      <label className="text-sm font-medium text-gray-600">
                        {t('qr.scanCount')}
                      </label>
                      <p>{selectedQR.scan_count}</p>
                    </div>
                  </div>

                  <div>
                    <label className="text-sm font-medium text-gray-600">
                      {t('qr.qrCodeData')}
                    </label>
                    <pre className="bg-gray-100 p-3 rounded text-xs overflow-x-auto">
                      {JSON.stringify(selectedQR.data, null, 2)}
                    </pre>
                  </div>
                </CardContent>
              </Card>
            </div>
          )}
        </div>
      </div>
    );
}
```

pages/ResetPassword.tsx

325 lines · 13,191 bytes · Page segment 1 of 9

```
import { useState, useEffect } from 'react';
import { useNavigate } from 'react-router-dom';
import { motion } from 'framer-motion';
import { Lock, AlertCircle, Loader2, CheckCircle } from 'lucide-react';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Label } from '@/components/ui/label';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Alert, AlertDescription } from '@/components/ui/alert';
import { ROUTE_PATHS } from '@/lib/index';
import { IMAGES } from '@/assets/images';
import { supabase } from '@/integrations/supabase/client';

export default function ResetPassword() {
  const [password, setPassword] = useState('');
  const [confirmPassword, setConfirmPassword] = useState('');
  const [error, setError] = useState('');
  const [success, setSuccess] = useState(false);
  const [isLoading, setIsLoading] = useState(true);
  const [hasValidSession, setHasValidSession] = useState(false);
  const navigate = useNavigate();

  useEffect(() => {
    const checkSession = async () => {
      try {
        // Method 1: Check URL hash for tokens (from email link)
        const hash = window.location.hash;
        console.log('Full URL:', window.location.href);
        console.log('Hash:', hash);

        // Parse hash parameters - handle both formats:
        // Format 1: #/reset-password#access_token=xxx (HashRouter)
        // Format 2: #access_token=xxx (direct from email)
        let tokenParams = '';

        if (hash.includes('#access_token=')) {
          // Extract everything after the first access_token
          const tokenStart = hash.indexOf('access_token=');
          tokenParams = hash.substring(tokenStart);
        } else if (hash.includes('?access_token=')) {
```

pages/ResetPassword.tsx

325 lines · 13,191 bytes · Page segment 2 of 9

```
          // Handle query string format
          const tokenStart = hash.indexOf('?access_token=');
          tokenParams = hash.substring(tokenStart + 1);
        }

        console.log('Token params:', tokenParams);

        const hashParams = new URLSearchParams(tokenParams);
        const accessToken = hashParams.get('access_token');
        const type = hashParams.get('type');
        const refreshToken = hashParams.get('refresh_token');

        console.log('Parsed tokens:', {
          hasAccessToken: !!accessToken,
          type,
          hasRefreshToken: !!refreshToken
        });

        if (accessToken && type === 'recovery') {
          console.log('Valid recovery token found, setting session...');

          // Set the session with the tokens from the URL
          const { data, error } = await supabase.auth.setSession({
            access_token: accessToken,
            refresh_token: refreshToken || ''
          });

          if (error) {
            console.error('Error setting session:', error);
            setError('Failed to verify reset link. Please request a new password reset.');
            setIsLoading(false);
            return;
          }

          console.log('Session set successfully:', data);
          setHasValidSession(true);
          setIsLoading(false);
        } else {
          console.log('No valid token in URL, checking existing session...');

```

pages/ResetPassword.tsx

325 lines · 13,191 bytes · Page segment 3 of 9

```
          // Method 2: Check if we already have a session
          const { data: { session }, error } = await supabase.auth.getSession();

          console.log('Existing session:', !!session);
          console.log('Session error:', error);

          if (session) {
            setHasValidSession(true);
          } else {
            setError('Invalid or expired reset link. Please request a new password reset from the login page.');
          }
          setIsLoading(false);
        }
      } catch (err) {
        console.error('Exception in checkSession:', err);
        setError('An error occurred. Please try again.');
        setIsLoading(false);
      }
    };

    checkSession();
  }, []);

  const handleResetPassword = async (e: React.FormEvent) => {
    e.preventDefault();
    setError('');

    // Validate passwords match
    if (password !== confirmPassword) {
      setError('Passwords do not match');
      return;
    }

    // Validate password length
    if (password.length < 6) {
      setError('Password must be at least 6 characters long');
      return;
    }

    setIsLoading(true);
```

pages/ResetPassword.tsx

325 lines · 13,191 bytes · Page segment 4 of 9

```

    try {
      const { error } = await supabase.auth.updateUser({
        password: password
      });

      if (error) throw error;

      setSuccess(true);

      // Redirect to login after 3 seconds
      setTimeout(() => {
        navigate('/login');
      }, 3000);
    } catch (err: any) {
      setError(err.message || 'Failed to reset password. Please try again.');
    } finally {
      setIsLoading(false);
    }
  };

  return (
    <div className="min-h-screen flex">
      {/* Left Side - Reset Password Form */}
      <div className="flex-1 flex items-center justify-center p-8 bg-background">
        <motion.div
          initial={{ opacity: 0, y: 20 }}
          animate={{ opacity: 1, y: 0 }}
          transition={{ duration: 0.5 }}
          className="w-full max-w-md"
        >
          <div className="mb-8 text-center">
            <div className="inline-flex items-center justify-center mb-4">
              <img src={IMAGES.LOGO} alt="Britium Express" className="h-16" />
            </div>
            <h1 className="text-3xl font-bold text-foreground mb-2">Britium Express</h1>
            <p className="text-muted-foreground">Reset Your Password</p>
          </div>

          <Card>
```

pages/ResetPassword.tsx

325 lines · 13,191 bytes · Page segment 5 of 9

```
            <CardHeader>
              <CardTitle>Create New Password</CardTitle>
              <CardDescription>Enter your new password below</CardDescription>
            </CardHeader>
            <CardContent>
              {isLoading ? (
                <div className="flex items-center justify-center py-8">
                  <Loader2 className="h-8 w-8 animate-spin text-primary" />
                  <span className="ml-3 text-muted-foreground">Verifying reset link...</span>
                </div>
              ) : !hasValidSession ? (
                <div className="space-y-4">
                  <Alert variant="destructive">
                    <AlertCircle className="h-4 w-4" />
                    <AlertDescription>{error}</AlertDescription>
                  </Alert>
                  <Button
                    type="button"
                    variant="outline"
                    className="w-full"
                    onClick={() => navigate('/login')}
                  >
                    Back to Login
                  </Button>
                </div>
              ) : success ? (
                <Alert className="border-green-500 bg-green-50 text-green-900">
                  <CheckCircle className="h-4 w-4 text-green-600" />
                  <AlertDescription>
                    Password reset successful! Redirecting to login...
                  </AlertDescription>
                </Alert>
              ) : (
                <form onSubmit={handleResetPassword} className="space-y-4">
                  {error && (
                    <Alert variant="destructive">
                      <AlertCircle className="h-4 w-4" />
                      <AlertDescription>{error}</AlertDescription>
                    </Alert>
                  )}
```

pages/ResetPassword.tsx

325 lines · 13,191 bytes · Page segment 6 of 9

```

                    <div className="space-y-2">
                      <Label htmlFor="password">New Password</Label>
                      <div className="relative">
                        <Lock className="absolute left-3 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
                        <Input
                          id="password"
                          type="password"
                          placeholder="Enter new password"
                          value={password}
                          onChange={(e) => setPassword(e.target.value)}
                          className="pl-10"
                          required
                          minLength={6}
                          disabled={isLoading}
                        />
                      </div>
                    </div>

                    <div className="space-y-2">
                      <Label htmlFor="confirm-password">Confirm Password</Label>
                      <div className="relative">
                        <Lock className="absolute left-3 top-1/2 -translate-y-1/2 h-4 w-4 text-muted-foreground" />
                        <Input
                          id="confirm-password"
                          type="password"
                          placeholder="Confirm new password"
                          value={confirmPassword}
                          onChange={(e) => setConfirmPassword(e.target.value)}
                          className="pl-10"
                          required
                          minLength={6}
                          disabled={isLoading}
                        />
                      </div>
                      <p className="text-xs text-muted-foreground">
                        Password must be at least 6 characters long
                      </p>
                    </div>

```

pages/ResetPassword.tsx

325 lines · 13,191 bytes · Page segment 7 of 9

```
                  <Button type="submit" className="w-full" disabled={isLoading}>
                    {isLoading ? (
                      <>
                        <Loader2 className="mr-2 h-4 w-4 animate-spin" />
                        Resetting password...
                      </>
                    ) : (
                      'Reset Password'
                    )}
                  </Button>

                  <Button
                    type="button"
                    variant="outline"
                    className="w-full"
                    onClick={() => navigate('/login')}
                  >
                    Back to Login
                  </Button>
                </form>
              )}
            </CardContent>
          </Card>
        </motion.div>
      </div>

      {/* Right Side - Marketing Content */}
      <div
        className="hidden lg:flex flex-1 relative bg-cover bg-center"
        style={{ backgroundImage: `url(${IMAGES.SCREENSHOT_5867})` }}
      >
        <div className="absolute inset-0 bg-gradient-to-br from-primary/90 to-primary/70" />
        <div className="relative z-10 flex flex-col justify-center p-12 text-white">
          <motion.div
            initial={{ opacity: 0, x: 20 }}
            animate={{ opacity: 1, x: 0 }}
            transition={{ duration: 0.5, delay: 0.2 }}
          >
            <h2 className="text-4xl font-bold mb-6">
              Secure Password Reset
```

pages/ResetPassword.tsx

325 lines · 13,191 bytes · Page segment 8 of 9

```
            </h2>
            <p className="text-xl mb-8 text-white/90">
              Your account security is our priority. Create a strong password to protect your data.
            </p>
            <div className="space-y-4">
              <div className="flex items-start gap-3">
                <div className="w-6 h-6 rounded-full bg-white/20 flex items-center justify-center flex-shrink-0 mt-1">
                  <svg className="w-4 h-4" fill="currentColor" viewBox="0 0 20 20">
                    <path fillRule="evenodd" d="M16.707 5.293a1 1 0 010 1.414l-8 8a1 1 0 01-1.414 0l-4-4a1 1 0 011.414-1.414L8 12.586l7.293-7.293a1 1 0 011.414 0z" clipRule="evenodd" />
                  </svg>
                </div>
                <div>
                  <h3 className="font-semibold mb-1">Encrypted Storage</h3>
                  <p className="text-white/80 text-sm">Your password is encrypted and securely stored</p>
                </div>
              </div>
              <div className="flex items-start gap-3">
                <div className="w-6 h-6 rounded-full bg-white/20 flex items-center justify-center flex-shrink-0 mt-1">
                  <svg className="w-4 h-4" fill="currentColor" viewBox="0 0 20 20">
                    <path fillRule="evenodd" d="M16.707 5.293a1 1 0 010 1.414l-8 8a1 1 0 01-1.414 0l-4-4a1 1 0 011.414-1.414L8 12.586l7.293-7.293a1 1 0 011.414 0z" clipRule="evenodd" />
                  </svg>
                </div>
                <div>
                  <h3 className="font-semibold mb-1">Instant Access</h3>
                  <p className="text-white/80 text-sm">Reset and regain access to your account immediately</p>
                </div>
              </div>
              <div className="flex items-start gap-3">
                <div className="w-6 h-6 rounded-full bg-white/20 flex items-center justify-center flex-shrink-0 mt-1">
                  <svg className="w-4 h-4" fill="currentColor" viewBox="0 0 20 20">
                    <path fillRule="evenodd" d="M16.707 5.293a1 1 0 010 1.414l-8 8a1 1 0 01-1.414 0l-4-4a1 1 0 011.414-1.414L8 12.586l7.293-7.293a1 1 0 011.414 0z" clipRule="evenodd" />
                  </svg>
                </div>
                <div>
                  <h3 className="font-semibold mb-1">24/7 Support</h3>
                  <p className="text-white/80 text-sm">Need help? Our support team is always available</p>
                </div>
```

pages/ResetPassword.tsx

325 lines · 13,191 bytes · Page segment 9 of 9

```
                </div>
              </div>
            </motion.div>
          </div>
        </div>
      </div>
    );
}
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 1 of 21

```
import { useState } from 'react';
import { useAuth } from '@/hooks/useAuth';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Label } from '@/components/ui/label';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Switch } from '@/components/ui/switch';
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from '@/components/ui/select';
import { Separator } from '@/components/ui/separator';
import { Badge } from '@/components/ui/badge';
import { Alert, AlertDescription } from '@/components/ui/alert';
import { User, Bell, Globe, Moon, Sun, Key, Shield, Copy, Eye, EyeOff, CheckCircle2, AlertCircle } from 'lucide-react';
import { motion } from 'framer-motion';
import { springPresets, fadeInUp } from '@/lib/motion';
import type { EmployeeRole } from '@/lib/index';
import { IMAGES } from '@/assets/images';

const ROLE_LABELS: Record<EmployeeRole, string> = {
  'super-admin': 'Super Administrator',
  'admin': 'Administrator',
  'branch-office': 'Branch Office',
  'supervisor': 'Supervisor',
  'wayplan-manager': 'Wayplan Manager',
  'driver': 'Driver',
  'rider': 'Rider',
  'warehouse-staff': 'Warehouse Staff',
  'customer-service': 'Customer Service',
  'data-entry': 'Data Entry',
  'marketing': 'Marketing',
  'hr-admin': 'HR Administrator',
  'finance': 'Finance',
  'merchant': 'Merchant',
  'customer': 'Customer',
};

const PORTAL_ACCESS_LABELS: Record<string, string> = {
  '/': 'Dashboard',
  '/supervisor': 'Supervisor Portal',
  '/driver': 'Driver Portal',
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 2 of 21

```
  '/warehouse': 'Warehouse Portal',
  '/customer-service': 'Customer Service',
  '/create-delivery': 'Create Delivery',
  '/analytics': 'Analytics',
  '/settings': 'Settings',
};

export default function Settings() {
  const { user, logout, canAccessPortal } = useAuth();
  const [activeTab, setActiveTab] = useState('profile');
  const [saveStatus, setSaveStatus] = useState<'idle' | 'saving' | 'saved' | 'error'>('idle');
  const [showApiKey, setShowApiKey] = useState(false);
  const [apiKeyCopied, setApiKeyCopied] = useState(false);

  const [profileData, setProfileData] = useState({
    name: user?.name || '',
    email: user?.email || '',
    phone: '+95 9 123 456 789',
    employeeNumber: 'EMP-2026-001',
  });

  const [notificationPrefs, setNotificationPrefs] = useState({
    email: user?.preferences.notifications.email ?? true,
    push: user?.preferences.notifications.push ?? true,
    sms: user?.preferences.notifications.sms ?? false,
    deliveryUpdates: true,
    taskAssignments: true,
    systemAlerts: true,
    weeklyReports: false,
  });

  const [language, setLanguage] = useState<'en' | 'mm'>(user?.preferences.language || 'en');
  const [theme, setTheme] = useState<'light' | 'dark' | 'auto'>(user?.preferences.theme || 'auto');

  const mockApiKey = 'brx_live_sk_1234567890abcdefghijklmnopqrstuvwxyz';

  const handleSaveProfile = async () => {
    setSaveStatus('saving');
    await new Promise(resolve => setTimeout(resolve, 1000));
    setSaveStatus('saved');
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 3 of 21

```
    setTimeout(() => setSaveStatus('idle'), 2000);
  };

  const handleSaveNotifications = async () => {
    setSaveStatus('saving');
    await new Promise(resolve => setTimeout(resolve, 800));
    setSaveStatus('saved');
    setTimeout(() => setSaveStatus('idle'), 2000);
  };

  const handleSaveLanguage = async () => {
    setSaveStatus('saving');
    await new Promise(resolve => setTimeout(resolve, 600));
    setSaveStatus('saved');
    setTimeout(() => setSaveStatus('idle'), 2000);
  };

  const handleCopyApiKey = () => {
    navigator.clipboard.writeText(mockApiKey);
    setApiKeyCopied(true);
    setTimeout(() => setApiKeyCopied(false), 2000);
  };

  const handleGenerateNewKey = async () => {
    setSaveStatus('saving');
    await new Promise(resolve => setTimeout(resolve, 1000));
    setSaveStatus('saved');
    setTimeout(() => setSaveStatus('idle'), 2000);
  };

  const accessiblePortals = Object.entries(PORTAL_ACCESS_LABELS).filter(([path]) =>
    canAccessPortal(path as any)
  );

  return (
    <div className="min-h-screen bg-background relative">
      <div
        className="absolute inset-0 z-0 opacity-30"
        style={{
          backgroundImage: `url(${IMAGES.SCREENSHOT_6534_2})`,
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 4 of 21

```
          backgroundSize: 'cover',
          backgroundPosition: 'center',
        }}
      />
      <div className="absolute inset-0 bg-gradient-to-b from-background/50 via-transparent to-background/70" />

      <motion.div
        initial={{ opacity: 0, y: 20 }}
        animate={{ opacity: 1, y: 0 }}
        transition={springPresets.gentle}
        className="relative z-10 container mx-auto px-4 py-8 max-w-6xl"
      >
        <div className="mb-8">
          <h1 className="text-4xl font-bold tracking-tight mb-2">Settings</h1>
          <p className="text-muted-foreground text-lg">
            Manage your account preferences and system configuration
          </p>
        </div>

        {saveStatus === 'saved' && (
          <motion.div
            initial={{ opacity: 0, y: -10 }}
            animate={{ opacity: 1, y: 0 }}
            exit={{ opacity: 0 }}
            className="mb-6"
          >
            <Alert className="bg-chart-3/10 border-chart-3">
              <CheckCircle2 className="h-4 w-4 text-chart-3" />
              <AlertDescription className="text-chart-3">
                Settings saved successfully
              </AlertDescription>
            </Alert>
          </motion.div>
        )}

        {saveStatus === 'error' && (
          <motion.div
            initial={{ opacity: 0, y: -10 }}
            animate={{ opacity: 1, y: 0 }}
            exit={{ opacity: 0 }}
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 5 of 21

```
            className="mb-6"
          >
            <Alert variant="destructive">
              <AlertCircle className="h-4 w-4" />
              <AlertDescription>
                Failed to save settings. Please try again.
              </AlertDescription>
            </Alert>
          </motion.div>
        )}

        <Tabs value={activeTab} onValueChange={setActiveTab} className="space-y-6">
          <TabsList className="grid w-full grid-cols-3 lg:grid-cols-6 gap-2">
            <TabsTrigger value="profile" className="flex items-center gap-2">
              <User className="h-4 w-4" />
              <span className="hidden sm:inline">Profile</span>
            </TabsTrigger>
            <TabsTrigger value="notifications" className="flex items-center gap-2">
              <Bell className="h-4 w-4" />
              <span className="hidden sm:inline">Notifications</span>
            </TabsTrigger>
            <TabsTrigger value="language" className="flex items-center gap-2">
              <Globe className="h-4 w-4" />
              <span className="hidden sm:inline">Language</span>
            </TabsTrigger>
            <TabsTrigger value="theme" className="flex items-center gap-2">
              <Moon className="h-4 w-4" />
              <span className="hidden sm:inline">Theme</span>
            </TabsTrigger>
            <TabsTrigger value="permissions" className="flex items-center gap-2">
              <Shield className="h-4 w-4" />
              <span className="hidden sm:inline">Permissions</span>
            </TabsTrigger>
            <TabsTrigger value="api" className="flex items-center gap-2">
              <Key className="h-4 w-4" />
              <span className="hidden sm:inline">API Keys</span>
            </TabsTrigger>
          </TabsList>

          <TabsContent value="profile" className="space-y-6">
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 6 of 21

```
            <motion.div variants={fadeInUp} initial="hidden" animate="visible">
              <Card>
                <CardHeader>
                  <CardTitle>Profile Information</CardTitle>
                  <CardDescription>
                    Update your personal information and contact details
                  </CardDescription>
                </CardHeader>
                <CardContent className="space-y-6">
                  <div className="grid grid-cols-1 md:grid-cols-2 gap-6">
                    <div className="space-y-2">
                      <Label htmlFor="name">Full Name</Label>
                      <Input
                        id="name"
                        value={profileData.name}
                        onChange={(e) => setProfileData({ ...profileData, name: e.target.value })}
                        placeholder="Enter your full name"
                      />
                    </div>
                    <div className="space-y-2">
                      <Label htmlFor="email">Email Address</Label>
                      <Input
                        id="email"
                        type="email"
                        value={profileData.email}
                        onChange={(e) => setProfileData({ ...profileData, email: e.target.value })}
                        placeholder="your.email@britium.com"
                      />
                    </div>
                    <div className="space-y-2">
                      <Label htmlFor="phone">Phone Number</Label>
                      <Input
                        id="phone"
                        type="tel"
                        value={profileData.phone}
                        onChange={(e) => setProfileData({ ...profileData, phone: e.target.value })}
                        placeholder="+95 9 XXX XXX XXX"
                      />
                    </div>
                    <div className="space-y-2">
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 7 of 21

```
                      <Label htmlFor="employeeNumber">Employee Number</Label>
                      <Input
                        id="employeeNumber"
                        value={profileData.employeeNumber}
                        disabled
                        className="bg-muted"
                      />
                    </div>
                  </div>

                  <Separator />

                  <div className="space-y-4">
                    <div>
                      <Label className="text-sm font-medium">Role</Label>
                      <div className="mt-2">
                        <Badge variant="secondary" className="text-sm">
                          {user ? ROLE_LABELS[user.role] : 'Unknown'}
                        </Badge>
                      </div>
                    </div>
                    <div>
                      <Label className="text-sm font-medium">Branch</Label>
                      <p className="text-sm text-muted-foreground mt-1">
                        {user?.branchId || 'Not assigned'}
                      </p>
                    </div>
                    <div>
                      <Label className="text-sm font-medium">Last Login</Label>
                      <p className="text-sm text-muted-foreground mt-1">
                        {user?.lastLogin ? new Date(user.lastLogin).toLocaleString() : 'Never'}
                      </p>
                    </div>
                  </div>

                  <div className="flex justify-end gap-3">
                    <Button variant="outline" onClick={() => setProfileData({
                      name: user?.name || '',
                      email: user?.email || '',
                      phone: '+95 9 123 456 789',
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 8 of 21

```
                      employeeNumber: 'EMP-2026-001',
                    })}>
                      Reset
                    </Button>
                    <Button onClick={handleSaveProfile} disabled={saveStatus === 'saving'}>
                      {saveStatus === 'saving' ? 'Saving...' : 'Save Changes'}
                    </Button>
                  </div>
                </CardContent>
              </Card>
            </motion.div>
          </TabsContent>

          <TabsContent value="notifications" className="space-y-6">
            <motion.div variants={fadeInUp} initial="hidden" animate="visible">
              <Card>
                <CardHeader>
                  <CardTitle>Notification Preferences</CardTitle>
                  <CardDescription>
                    Choose how you want to receive notifications
                  </CardDescription>
                </CardHeader>
                <CardContent className="space-y-6">
                  <div className="space-y-4">
                    <div className="flex items-center justify-between">
                      <div className="space-y-0.5">
                        <Label htmlFor="email-notif">Email Notifications</Label>
                        <p className="text-sm text-muted-foreground">
                          Receive notifications via email
                        </p>
                      </div>
                      <Switch
                        id="email-notif"
                        checked={notificationPrefs.email}
                        onCheckedChange={(checked) => setNotificationPrefs({ ...notificationPrefs, email: checked })}
                      />
                    </div>

                    <Separator />

```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 9 of 21

```
                    <div className="flex items-center justify-between">
                      <div className="space-y-0.5">
                        <Label htmlFor="push-notif">Push Notifications</Label>
                        <p className="text-sm text-muted-foreground">
                          Receive push notifications in browser
                        </p>
                      </div>
                      <Switch
                        id="push-notif"
                        checked={notificationPrefs.push}
                        onCheckedChange={(checked) => setNotificationPrefs({ ...notificationPrefs, push: checked })}
                      />
                    </div>

                    <Separator />

                    <div className="flex items-center justify-between">
                      <div className="space-y-0.5">
                        <Label htmlFor="sms-notif">SMS Notifications</Label>
                        <p className="text-sm text-muted-foreground">
                          Receive notifications via SMS
                        </p>
                      </div>
                      <Switch
                        id="sms-notif"
                        checked={notificationPrefs.sms}
                        onCheckedChange={(checked) => setNotificationPrefs({ ...notificationPrefs, sms: checked })}
                      />
                    </div>

                    <Separator className="my-6" />

                    <div className="space-y-4">
                      <h4 className="text-sm font-semibold">Notification Types</h4>

                      <div className="flex items-center justify-between">
                        <div className="space-y-0.5">
                          <Label htmlFor="delivery-updates">Delivery Updates</Label>
                          <p className="text-sm text-muted-foreground">
                            Status changes and delivery confirmations
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 10 of 21

```
                    </p>
                  </div>
                  <Switch
                    id="delivery-updates"
                    checked={notificationPrefs.deliveryUpdates}
                    onCheckedChange={(checked) => setNotificationPrefs({ ...notificationPrefs, deliveryUpdates: checked })}
                  />
                </div>

                <div className="flex items-center justify-between">
                  <div className="space-y-0.5">
                    <Label htmlFor="task-assignments">Task Assignments</Label>
                    <p className="text-sm text-muted-foreground">
                      New tasks and assignment updates
                    </p>
                  </div>
                  <Switch
                    id="task-assignments"
                    checked={notificationPrefs.taskAssignments}
                    onCheckedChange={(checked) => setNotificationPrefs({ ...notificationPrefs, taskAssignments: checked })}
                  />
                </div>

                <div className="flex items-center justify-between">
                  <div className="space-y-0.5">
                    <Label htmlFor="system-alerts">System Alerts</Label>
                    <p className="text-sm text-muted-foreground">
                      Important system notifications and alerts
                    </p>
                  </div>
                  <Switch
                    id="system-alerts"
                    checked={notificationPrefs.systemAlerts}
                    onCheckedChange={(checked) => setNotificationPrefs({ ...notificationPrefs, systemAlerts: checked })}
                  />
                </div>

                <div className="flex items-center justify-between">
                  <div className="space-y-0.5">
                    <Label htmlFor="weekly-reports">Weekly Reports</Label>
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 11 of 21

```
                          <p className="text-sm text-muted-foreground">
                            Performance summaries and analytics
                          </p>
                        </div>
                        <Switch
                          id="weekly-reports"
                          checked={notificationPrefs.weeklyReports}
                          onCheckedChange={(checked) => setNotificationPrefs({ ...notificationPrefs, weeklyReports: checked })}
                        />
                      </div>
                    </div>
                  </div>

                  <div className="flex justify-end">
                    <Button onClick={handleSaveNotifications} disabled={saveStatus === 'saving'}>
                      {saveStatus === 'saving' ? 'Saving...' : 'Save Preferences'}
                    </Button>
                  </div>
                </CardContent>
              </Card>
            </motion.div>
          </TabsContent>

          <TabsContent value="language" className="space-y-6">
            <motion.div variants={fadeInUp} initial="hidden" animate="visible">
              <Card>
                <CardHeader>
                  <CardTitle>Language Settings</CardTitle>
                  <CardDescription>
                    Choose your preferred language for the interface
                  </CardDescription>
                </CardHeader>
                <CardContent className="space-y-6">
                  <div className="space-y-4">
                    <Label htmlFor="language-select">Interface Language</Label>
                    <Select value={language} onValueChange={(value: 'en' | 'mm') => setLanguage(value)}>
                      <SelectTrigger id="language-select" className="w-full md:w-[300px]">
                        <SelectValue />
                      </SelectTrigger>
                      <SelectContent>
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 12 of 21

```
                        <SelectItem value="en">English</SelectItem>
                        <SelectItem value="mm">Myanmar (□□□□□□)</SelectItem>
                      </SelectContent>
                    </Select>
                    <p className="text-sm text-muted-foreground">
                      Changes will take effect immediately across all portals
                    </p>
                  </div>

                  <Separator />

                  <div className="space-y-4">
                    <h4 className="text-sm font-semibold">Regional Settings</h4>
                    <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
                      <div className="space-y-2">
                        <Label>Date Format</Label>
                        <Select defaultValue="dd/mm/yyyy">
                          <SelectTrigger>
                            <SelectValue />
                          </SelectTrigger>
                          <SelectContent>
                            <SelectItem value="dd/mm/yyyy">DD/MM/YYYY</SelectItem>
                            <SelectItem value="mm/dd/yyyy">MM/DD/YYYY</SelectItem>
                            <SelectItem value="yyyy-mm-dd">YYYY-MM-DD</SelectItem>
                          </SelectContent>
                        </Select>
                      </div>
                      <div className="space-y-2">
                        <Label>Time Format</Label>
                        <Select defaultValue="24h">
                          <SelectTrigger>
                            <SelectValue />
                          </SelectTrigger>
                          <SelectContent>
                            <SelectItem value="12h">12-hour (AM/PM)</SelectItem>
                            <SelectItem value="24h">24-hour</SelectItem>
                          </SelectContent>
                        </Select>
                      </div>
                      <div className="space-y-2">
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 13 of 21

```
                        <Label>Timezone</Label>
                        <Select defaultValue="asia/yangon">
                          <SelectTrigger>
                            <SelectValue />
                          </SelectTrigger>
                          <SelectContent>
                            <SelectItem value="asia/yangon">Asia/Yangon (GMT+6:30)</SelectItem>
                            <SelectItem value="asia/bangkok">Asia/Bangkok (GMT+7)</SelectItem>
                            <SelectItem value="asia/singapore">Asia/Singapore (GMT+8)</SelectItem>
                          </SelectContent>
                        </Select>
                      </div>
                      <div className="space-y-2">
                        <Label>Currency</Label>
                        <Select defaultValue="mmk">
                          <SelectTrigger>
                            <SelectValue />
                          </SelectTrigger>
                          <SelectContent>
                            <SelectItem value="mmk">MMK (Kyat)</SelectItem>
                            <SelectItem value="usd">USD (Dollar)</SelectItem>
                            <SelectItem value="thb">THB (Baht)</SelectItem>
                          </SelectContent>
                        </Select>
                      </div>
                    </div>
                  </div>

                  <div className="flex justify-end">
                    <Button onClick={handleSaveLanguage} disabled={saveStatus === 'saving'}>
                      {saveStatus === 'saving' ? 'Saving...' : 'Save Settings'}
                    </Button>
                  </div>
                </CardContent>
              </Card>
            </motion.div>
          </TabsContent>

          <TabsContent value="theme" className="space-y-6">
            <motion.div variants={fadeInUp} initial="hidden" animate="visible">
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 14 of 21

```
              <Card>
                <CardHeader>
                  <CardTitle>Theme Settings</CardTitle>
                  <CardDescription>
                    Customize the appearance of your dashboard
                  </CardDescription>
                </CardHeader>
                <CardContent className="space-y-6">
                  <div className="space-y-4">
                    <Label>Color Theme</Label>
                    <div className="grid grid-cols-1 md:grid-cols-3 gap-4">
                      <button
                        onClick={() => setTheme('light')}
                        className={`relative flex flex-col items-center gap-3 p-6 rounded-lg border-2 transition-all hover:border-primary ${
                          theme === 'light' ? 'border-primary bg-primary/5' : 'border-border'
                        }`}
                      >
                        <Sun className="h-8 w-8" />
                        <div className="text-center">
                          <p className="font-semibold">Light</p>
                          <p className="text-xs text-muted-foreground">Bright and clear</p>
                        </div>
                        {theme === 'light' && (
                          <div className="absolute top-2 right-2">
                            <CheckCircle2 className="h-5 w-5 text-primary" />
                          </div>
                        )}
                      </button>

                      <button
                        onClick={() => setTheme('dark')}
                        className={`relative flex flex-col items-center gap-3 p-6 rounded-lg border-2 transition-all hover:border-primary ${
                          theme === 'dark' ? 'border-primary bg-primary/5' : 'border-border'
                        }`}
                      >
                        <Moon className="h-8 w-8" />
                        <div className="text-center">
                          <p className="font-semibold">Dark</p>
                          <p className="text-xs text-muted-foreground">Easy on the eyes</p>
                        </div>
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 15 of 21

```
                        {theme === 'dark' && (
                          <div className="absolute top-2 right-2">
                            <CheckCircle2 className="h-5 w-5 text-primary" />
                          </div>
                        )}
                      </button>

                      <button
                        onClick={() => setTheme('auto')}
                        className={`relative flex flex-col items-center gap-3 p-6 rounded-lg border-2 transition-all hover:border-primary ${
                          theme === 'auto' ? 'border-primary bg-primary/5' : 'border-border'
                        }`}
                      >
                        <div className="flex items-center gap-1">
                          <Sun className="h-6 w-6" />
                          <Moon className="h-6 w-6" />
                        </div>
                        <div className="text-center">
                          <p className="font-semibold">Auto</p>
                          <p className="text-xs text-muted-foreground">Follows system</p>
                        </div>
                        {theme === 'auto' && (
                          <div className="absolute top-2 right-2">
                            <CheckCircle2 className="h-5 w-5 text-primary" />
                          </div>
                        )}
                      </button>
                    </div>
                  </div>

                  <Separator />

                  <div className="space-y-4">
                    <h4 className="text-sm font-semibold">Display Options</h4>
                    <div className="flex items-center justify-between">
                      <div className="space-y-0.5">
                        <Label>Compact Mode</Label>
                        <p className="text-sm text-muted-foreground">
                          Reduce spacing for more content
                        </p>
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 16 of 21

```
                      </div>
                      <Switch defaultChecked={false} />
                    </div>
                    <div className="flex items-center justify-between">
                      <div className="space-y-0.5">
                        <Label>Animations</Label>
                        <p className="text-sm text-muted-foreground">
                          Enable smooth transitions and effects
                        </p>
                      </div>
                      <Switch defaultChecked={true} />
                    </div>
                    <div className="flex items-center justify-between">
                      <div className="space-y-0.5">
                        <Label>High Contrast</Label>
                        <p className="text-sm text-muted-foreground">
                          Increase contrast for better visibility
                        </p>
                      </div>
                      <Switch defaultChecked={false} />
                    </div>
                  </div>

                  <div className="flex justify-end">
                    <Button onClick={handleSaveLanguage} disabled={saveStatus === 'saving'}>
                      {saveStatus === 'saving' ? 'Saving...' : 'Save Theme'}
                    </Button>
                  </div>
                </CardContent>
              </Card>
            </motion.div>
          </TabsContent>

          <TabsContent value="permissions" className="space-y-6">
            <motion.div variants={fadeInUp} initial="hidden" animate="visible">
              <Card>
                <CardHeader>
                  <CardTitle>Portal Access Permissions</CardTitle>
                  <CardDescription>
                    View your role-based access to different portals
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 17 of 21

```
                  </CardDescription>
                </CardHeader>
                <CardContent className="space-y-6">
                  <div className="space-y-4">
                    <div>
                      <Label className="text-sm font-medium">Current Role</Label>
                      <div className="mt-2">
                        <Badge variant="secondary" className="text-base px-4 py-2">
                          {user ? ROLE_LABELS[user.role] : 'Unknown'}
                        </Badge>
                      </div>
                    </div>

                    <Separator />

                    <div className="space-y-3">
                      <Label className="text-sm font-medium">Accessible Portals</Label>
                      <div className="grid grid-cols-1 md:grid-cols-2 gap-3">
                        {accessiblePortals.map(([path, label]) => (
                          <div
                            key={path}
                            className="flex items-center gap-3 p-3 rounded-lg border bg-card"
                          >
                            <CheckCircle2 className="h-5 w-5 text-chart-3" />
                            <span className="font-medium">{label}</span>
                          </div>
                        ))}
                      </div>
                    </div>

                    <Separator />

                    <div className="space-y-3">
                      <Label className="text-sm font-medium">Permissions</Label>
                      <div className="grid grid-cols-1 md:grid-cols-2 gap-2">
                        {user?.permissions.map((permission) => (
                          <div
                            key={permission}
                            className="flex items-center gap-2 text-sm text-muted-foreground"
                          >
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 18 of 21

```
                            <div className="h-1.5 w-1.5 rounded-full bg-primary" />
                            <span className="font-mono">{permission}</span>
                          </div>
                        ))}
                      </div>
                    </div>
                  </div>

                  <Alert>
                    <Shield className="h-4 w-4" />
                    <AlertDescription>
                      Contact your administrator to request additional permissions or role changes.
                    </AlertDescription>
                  </Alert>
                </CardContent>
              </Card>
            </motion.div>
          </TabsContent>

          <TabsContent value="api" className="space-y-6">
            <motion.div variants={fadeInUp} initial="hidden" animate="visible">
              <Card>
                <CardHeader>
                  <CardTitle>API Keys Management</CardTitle>
                  <CardDescription>
                    Manage API keys for integrations and external access
                  </CardDescription>
                </CardHeader>
                <CardContent className="space-y-6">
                  {user?.role === 'admin' ? (
                    <>
                      <div className="space-y-4">
                        <div>
                          <Label className="text-sm font-medium">Live API Key</Label>
                          <div className="mt-2 flex items-center gap-2">
                            <div className="flex-1 relative">
                              <Input
                                type={showApiKey ? 'text' : 'password'}
                                value={mockApiKey}
                                readOnly
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 19 of 21

```
                                  className="font-mono text-sm pr-20"
                                />
                                <div className="absolute right-2 top-1/2 -translate-y-1/2 flex items-center gap-1">
                                  <Button
                                    size="sm"
                                    variant="ghost"
                                    onClick={() => setShowApiKey(!showApiKey)}
                                    className="h-7 w-7 p-0"
                                  >
                                    {showApiKey ? <EyeOff className="h-4 w-4" /> : <Eye className="h-4 w-4" />}
                                  </Button>
                                  <Button
                                    size="sm"
                                    variant="ghost"
                                    onClick={handleCopyApiKey}
                                    className="h-7 w-7 p-0"
                                  >
                                    {apiKeyCopied ? <CheckCircle2 className="h-4 w-4 text-chart-3" /> : <Copy className="h-4 w-4" />}
                                  </Button>
                                </div>
                              </div>
                            </div>
                            <p className="text-xs text-muted-foreground mt-2">
                              Keep this key secure. Do not share it publicly.
                            </p>
                          </div>

                          <Separator />

                          <div className="space-y-3">
                            <Label className="text-sm font-medium">Key Information</Label>
                            <div className="grid grid-cols-1 md:grid-cols-2 gap-4 text-sm">
                              <div>
                                <p className="text-muted-foreground">Created</p>
                                <p className="font-medium">January 15, 2026</p>
                              </div>
                              <div>
                                <p className="text-muted-foreground">Last Used</p>
                                <p className="font-medium">2 hours ago</p>
                              </div>
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 20 of 21

```
                            <div>
                              <p className="text-muted-foreground">Status</p>
                              <Badge variant="secondary" className="bg-chart-3/10 text-chart-3">
                                Active
                              </Badge>
                            </div>
                            <div>
                              <p className="text-muted-foreground">Rate Limit</p>
                              <p className="font-medium">1000 requests/hour</p>
                            </div>
                          </div>
                        </div>

                        <Separator />

                        <div className="space-y-3">
                          <Label className="text-sm font-medium">API Endpoints</Label>
                          <div className="space-y-2 text-sm">
                            <div className="flex items-center gap-2">
                              <Badge variant="outline" className="font-mono">GET</Badge>
                              <code className="text-muted-foreground">/api/v1/shipments</code>
                            </div>
                            <div className="flex items-center gap-2">
                              <Badge variant="outline" className="font-mono">POST</Badge>
                              <code className="text-muted-foreground">/api/v1/deliveries</code>
                            </div>
                            <div className="flex items-center gap-2">
                              <Badge variant="outline" className="font-mono">PUT</Badge>
                              <code className="text-muted-foreground">/api/v1/manifests/:id</code>
                            </div>
                          </div>
                        </div>
                      </div>

                      <div className="flex justify-end gap-3">
                        <Button variant="outline" onClick={handleGenerateNewKey}>
                          Generate New Key
                        </Button>
                        <Button variant="destructive">
                          Revoke Key
```

pages/Settings.tsx

836 lines · 37,850 bytes · Page segment 21 of 21

```
                        </Button>
                      </div>

                      <Alert>
                        <Key className="h-4 w-4" />
                        <AlertDescription>
                          Generating a new key will invalidate the current one. Update all integrations before revoking.
                        </AlertDescription>
                      </Alert>
                    </>
                  ) : (
                    <Alert>
                      <Shield className="h-4 w-4" />
                      <AlertDescription>
                        API key management is only available for administrators. Contact your system admin for API access.
                      </AlertDescription>
                    </Alert>
                  )}
                </CardContent>
              </Card>
            </motion.div>
          </TabsContent>
        </Tabs>

        <div className="mt-8 flex justify-between items-center">
          <Button variant="outline" onClick={logout}>
            Sign Out
          </Button>
          <p className="text-sm text-muted-foreground">
            Last updated: {new Date().toLocaleDateString()}
          </p>
        </div>
      </motion.div>
    </div>
  );
}
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 1 of 20

```
import { useState, useMemo } from 'react';
import { useLocation } from 'react-router-dom';
import { motion } from 'framer-motion';
import {
  Package,
  TrendingUp,
  Users,
  AlertTriangle,
  Clock,
  MapPin,
  CheckCircle,
  XCircle,
  Filter,
  Download,
  RefreshCw,
  Search,
  MoreVertical,
  Truck,
  Calendar,
  Activity,
} from 'lucide-react';
import { IMAGES } from '@/assets/images';
import {
  Delivery,
  Employee,
  Task,
  Warehouse,
  formatStatus,
  formatDate,
  formatCurrency,
  calculateDeliveryMetrics,
} from '@/lib/index';
import {
  mockDeliveries,
  mockEmployees,
  mockTasks,
  mockWarehouses,
  mockShipments,
} from '@/data/index';
import { MetricCard, StatsGrid, StatusBadge, CompactMetric } from '@/components/Stats';
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 2 of 20

```
import { DeliveryTrendChart, StatusDistributionChart } from '@/components/Charts';
import { DataTable, Column } from '@/components/DataTable';
import { MapView } from '@/components/MapView';
import { Button } from '@/components/ui/button';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Input } from '@/components/ui/input';
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from '@/components/ui/select';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { Badge } from '@/components/ui/badge';
import { Separator } from '@/components/ui/separator';
import { ScrollArea } from '@/components/ui/scroll-area';
import {
  DropdownMenu,
  DropdownMenuContent,
  DropdownMenuItem,
  DropdownMenuLabel,
  DropdownMenuSeparator,
  DropdownMenuTrigger,
} from '@/components/ui/dropdown-menu';

export default function SupervisorPortal() {
  const [searchQuery, setSearchQuery] = useState('');
  const location = useLocation();
  const getInitialView = () => {
    if (location.pathname.includes('/overview')) return 'overview';
    if (location.pathname.includes('/queue')) return 'queue';
    if (location.pathname.includes('/exceptions')) return 'exceptions';
    if (location.pathname.includes('/fleet')) return 'fleet';
    return 'overview';
  };
  const [statusFilter, setStatusFilter] = useState<string>('all');
  const [selectedView, setSelectedView] = useState<'overview' | 'queue' | 'fleet' | 'exceptions'>(getInitialView());

  const metrics = useMemo(() => calculateDeliveryMetrics(mockDeliveries), []);

  const drivers = useMemo(
    () => mockEmployees.filter((emp) => emp.role === 'driver' && emp.status === 'active'),
    []
  );

```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 3 of 20

```
81    const overnightQueue = useMemo(
82      () =>
83        mockDeliveries.filter(
84          (d) => d.status === 'pending' || d.status === 'assigned'
85        ),
86      []
87    );
88
89    const exceptions = useMemo(
90      () =>
91        mockDeliveries.filter(
92          (d) => d.status === 'failed' || d.ndrCase
93        ),
94      []
95    );
96
97    const urgentTasks = useMemo(
98      () => mockTasks.filter((t) => t.priority === 'urgent' || t.priority === 'high'),
99      []
100   );
101
102   const deliveryColumns: Column<Delivery>[] = [
103     {
104       id: 'id',
105       header: 'Delivery ID',
106       cell: (delivery) => (
107         <span className="font-mono text-sm font-medium">{delivery.id}</span>
108       ),
109     },
110     {
111       id: 'shipmentId',
112       header: 'Shipment',
113       cell: (delivery) => {
114         const shipment = mockShipments.find((s) => s.id === delivery.shipmentId);
115         return (
116           <div className="space-y-1">
117             <div className="font-mono text-sm">{shipment?.awb || 'N/A'}</div>
118             <div className="text-xs text-muted-foreground">{shipment?.recipient.name}</div>
119           </div>
120         );
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 4 of 20

```
      },
    },
    {
      id: 'status',
      header: 'Status',
      cell: (delivery) => <StatusBadge status={delivery.status} />,
    },
    {
      id: 'driverId',
      header: 'Driver',
      cell: (delivery) => {
        const driver = mockEmployees.find((e) => e.id === delivery.driverId);
        return driver ? (
          <div className="flex items-center gap-2">
            <div className="h-8 w-8 rounded-full bg-primary/10 flex items-center justify-center">
              <Users className="h-4 w-4 text-primary" />
            </div>
            <span className="text-sm">{driver.name}</span>
          </div>
        ) : (
          <span className="text-sm text-muted-foreground">Unassigned</span>
        );
      },
    },
    {
      id: 'assignedAt',
      header: 'Assigned',
      cell: (delivery) =>
        delivery.assignedAt ? (
          <span className="text-sm">{formatDate(delivery.assignedAt, 'datetime')}</span>
        ) : (
          <span className="text-sm text-muted-foreground">-</span>
        ),
    },
  ];

  const exceptionColumns: Column<Delivery>[] = [
    {
      id: 'id',
      header: 'Delivery ID',
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 5 of 20

```
      cell: (delivery) => (
        <span className="font-mono text-sm font-medium">{delivery.id}</span>
      ),
    },
    {
      id: 'failureReason',
      header: 'Reason',
      cell: (delivery) => (
        <div className="space-y-1">
          <div className="text-sm font-medium">{delivery.failureReason || 'Unknown'}</div>
          {delivery.ndrCase && (
            <div className="text-xs text-muted-foreground">
              Attempts: {delivery.ndrCase.attempts}
            </div>
          )}
        </div>
      ),
    },
    {
      id: 'failedAt',
      header: 'Failed At',
      cell: (delivery) =>
        delivery.failedAt ? (
          <span className="text-sm">{formatDate(delivery.failedAt, 'datetime')}</span>
        ) : (
          <span className="text-sm text-muted-foreground">-</span>
        ),
    },
    {
      id: 'ndrCase',
      header: 'Next Attempt',
      cell: (delivery) =>
        delivery.ndrCase?.nextAttemptDate ? (
          <span className="text-sm">{formatDate(delivery.ndrCase.nextAttemptDate, 'datetime')}</span>
        ) : (
          <span className="text-sm text-muted-foreground">-</span>
        ),
    },
  ];

```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 6 of 20

```
  const chartData = useMemo(() => {
    const last7Days = Array.from({ length: 7 }, (_, i) => {
      const date = new Date();
      date.setDate(date.getDate() - (6 - i));
      return {
        date: date.toISOString().split('T')[0],
        delivered: Math.floor(Math.random() * 50) + 30,
        failed: Math.floor(Math.random() * 10) + 2,
        pending: Math.floor(Math.random() * 20) + 10,
      };
    });
    return last7Days;
  }, []);

  const statusData = useMemo(() => [
    { name: 'Delivered', value: metrics.delivered, color: 'hsl(var(--chart-3))' },
    { name: 'Pending', value: metrics.pending, color: 'hsl(var(--chart-1))' },
    { name: 'Failed', value: metrics.failed, color: 'hsl(var(--destructive))' },
  ], [metrics]);

  return (
    <div className="min-h-screen bg-background">
      <div
        className="absolute inset-0 z-0 opacity-30"
        style={{
          backgroundImage: `url(${IMAGES.SCREENSHOT_3252_2})`,
          backgroundSize: 'cover',
          backgroundPosition: 'center',
        }}
      />
      <div className="absolute inset-0 bg-gradient-to-b from-background/50 via-transparent to-background/70" />

      <div className="relative z-10">
        <div className="border-b border-border/40 bg-background/80 backdrop-blur supports-[backdrop-filter]:bg-background/60">
          <div className="container mx-auto px-4 py-6">
            <div className="flex items-center justify-between">
              <div>
                <h1 className="text-3xl font-bold tracking-tight">Supervisor Portal</h1>
                <p className="text-muted-foreground mt-1">
                  Operational dashboard and team management
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 7 of 20

```
                </p>
              </div>
              <div className="flex items-center gap-3">
                <Button variant="outline" size="sm">
                  <RefreshCw className="h-4 w-4 mr-2" />
                  Refresh
                </Button>
                <Button variant="outline" size="sm">
                  <Download className="h-4 w-4 mr-2" />
                  Export
                </Button>
                <Button size="sm">
                  <Filter className="h-4 w-4 mr-2" />
                  Filters
                </Button>
              </div>
            </div>
          </div>
        </div>

        <div className="container mx-auto px-4 py-8 space-y-8">
          <motion.div
            initial={{ opacity: 0, y: 20 }}
            animate={{ opacity: 1, y: 0 }}
            transition={{ duration: 0.4 }}
          >
            <StatsGrid
              metrics={[
                {
                  title: 'Total Deliveries',
                  value: metrics.total,
                  icon: <Package className="h-5 w-5" />,
                  trend: 12.5,
                },
                {
                  title: 'Success Rate',
                  value: `${metrics.successRate}%`,
                  icon: <CheckCircle className="h-5 w-5" />,
                  trend: 2.3,
                },
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 8 of 20

```
                {
                  title: 'On-Time Rate',
                  value: `${metrics.onTimeRate}%`,
                  icon: <Clock className="h-5 w-5" />,
                  trend: 1.8,
                },
                {
                  title: 'Active Drivers',
                  value: drivers.length,
                  icon: <Users className="h-5 w-5" />,
                  trend: 0,
                },
                {
                  title: 'Pending Queue',
                  value: overnightQueue.length,
                  icon: <AlertTriangle className="h-5 w-5" />,
                  trend: -8.4,
                },
                {
                  title: 'Exceptions',
                  value: exceptions.length,
                  icon: <XCircle className="h-5 w-5" />,
                  trend: -12.1,
                },
              ]}
            />
          </motion.div>

          <Tabs value={selectedView} onValueChange={(v) => setSelectedView(v as any)} className="space-y-6">
            <TabsList className="grid w-full grid-cols-4">
              <TabsTrigger value="overview">Overview</TabsTrigger>
              <TabsTrigger value="queue">Queue Management</TabsTrigger>
              <TabsTrigger value="fleet">Fleet Mobility</TabsTrigger>
              <TabsTrigger value="exceptions">Exceptions</TabsTrigger>
            </TabsList>

            <TabsContent value="overview" className="space-y-6">
              <div className="grid grid-cols-1 lg:grid-cols-2 gap-6">
                <Card>
                  <CardHeader>
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 9 of 20

```
                    <CardTitle>Delivery Trends</CardTitle>
                    <CardDescription>Last 7 days performance</CardDescription>
                  </CardHeader>
                  <CardContent>
                    <DeliveryTrendChart data={chartData} height={300} />
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle>Status Distribution</CardTitle>
                    <CardDescription>Current delivery status breakdown</CardDescription>
                  </CardHeader>
                  <CardContent>
                    <StatusDistributionChart data={statusData} height={300} />
                  </CardContent>
                </Card>
              </div>

              <Card>
                <CardHeader>
                  <CardTitle>Leadership Performance</CardTitle>
                  <CardDescription>Team member performance metrics</CardDescription>
                </CardHeader>
                <CardContent>
                  <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-4">
                    {drivers.slice(0, 6).map((driver) => (
                      <motion.div
                        key={driver.id}
                        whileHover={{ scale: 1.02 }}
                        className="p-4 rounded-lg border border-border bg-card"
                      >
                        <div className="flex items-start justify-between mb-3">
                          <div className="flex items-center gap-3">
                            <div className="h-10 w-10 rounded-full bg-primary/10 flex items-center justify-center">
                              <Users className="h-5 w-5 text-primary" />
                            </div>
                            <div>
                              <div className="font-semibold">{driver.name}</div>
                              <div className="text-xs text-muted-foreground">
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 10 of 20

```
                                {driver.employeeNumber}
                              </div>
                            </div>
                          </div>
                          <Badge variant="outline" className="text-xs">
                            {driver.vehicleAssignment?.vehicleType}
                          </Badge>
                        </div>
                        <Separator className="my-3" />
                        <div className="grid grid-cols-2 gap-3">
                          <CompactMetric
                            label="Deliveries"
                            value={driver.performance?.totalDeliveries || 0}
                            icon={<Package className="h-3 w-3" />}
                          />
                          <CompactMetric
                            label="Success Rate"
                            value={`${driver.performance?.successRate || 0}%`}
                            icon={<TrendingUp className="h-3 w-3" />}
                          />
                          <CompactMetric
                            label="On-Time"
                            value={`${driver.performance?.onTimeRate || 0}%`}
                            icon={<Clock className="h-3 w-3" />}
                          />
                          <CompactMetric
                            label="Rating"
                            value={driver.performance?.averageRating || 0}
                            icon={<Activity className="h-3 w-3" />}
                          />
                        </div>
                      </motion.div>
                    ))}
                  </div>
                </CardContent>
              </Card>

              <Card>
                <CardHeader>
                  <CardTitle>Urgent Tasks</CardTitle>
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 11 of 20

```
                  <CardDescription>High priority tasks requiring attention</CardDescription>
                </CardHeader>
                <CardContent>
                  <ScrollArea className="h-[300px]">
                    <div className="space-y-3">
                      {urgentTasks.map((task) => (
                        <div
                          key={task.id}
                          className="p-4 rounded-lg border border-border bg-card hover:bg-accent/5 transition-colors"
                        >
                          <div className="flex items-start justify-between">
                            <div className="flex-1">
                              <div className="flex items-center gap-2 mb-2">
                                <Badge
                                  variant={task.priority === 'urgent' ? 'destructive' : 'default'}
                                  className="text-xs"
                                >
                                  {task.priority}
                                </Badge>
                                <Badge variant="outline" className="text-xs">
                                  {task.type}
                                </Badge>
                              </div>
                              <div className="font-semibold mb-1">{task.title}</div>
                              <div className="text-sm text-muted-foreground mb-2">
                                {task.description}
                              </div>
                              <div className="flex items-center gap-4 text-xs text-muted-foreground">
                                <div className="flex items-center gap-1">
                                  <Calendar className="h-3 w-3" />
                                  {task.dueDate ? formatDate(task.dueDate, 'datetime') : 'No due date'}
                                </div>
                                {task.assignedTo && (
                                  <div className="flex items-center gap-1">
                                    <Users className="h-3 w-3" />
                                    {mockEmployees.find((e) => e.id === task.assignedTo)?.name || 'Unknown'}
                                  </div>
                                )}
                              </div>
                            </div>
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 12 of 20

```
                            <DropdownMenu>
                              <DropdownMenuTrigger asChild>
                                <Button variant="ghost" size="sm">
                                  <MoreVertical className="h-4 w-4" />
                                </Button>
                              </DropdownMenuTrigger>
                              <DropdownMenuContent align="end">
                                <DropdownMenuLabel>Actions</DropdownMenuLabel>
                                <DropdownMenuSeparator />
                                <DropdownMenuItem>View Details</DropdownMenuItem>
                                <DropdownMenuItem>Reassign</DropdownMenuItem>
                                <DropdownMenuItem>Mark Complete</DropdownMenuItem>
                              </DropdownMenuContent>
                            </DropdownMenu>
                          </div>
                        </div>
                      ))}
                    </div>
                  </ScrollArea>
                </CardContent>
              </Card>
            </TabsContent>

            <TabsContent value="queue" className="space-y-6">
              <Card>
                <CardHeader>
                  <div className="flex items-center justify-between">
                    <div>
                      <CardTitle>Overnight Delivery Queue</CardTitle>
                      <CardDescription>
                        {overnightQueue.length} deliveries pending assignment
                      </CardDescription>
                    </div>
                    <div className="flex items-center gap-2">
                      <Input
                        placeholder="Search deliveries..."
                        value={searchQuery}
                        onChange={(e) => setSearchQuery(e.target.value)}
                        className="w-64"
                      />
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 13 of 20

```
                      <Select value={statusFilter} onValueChange={setStatusFilter}>
                        <SelectTrigger className="w-40">
                          <SelectValue placeholder="Status" />
                        </SelectTrigger>
                        <SelectContent>
                          <SelectItem value="all">All Status</SelectItem>
                          <SelectItem value="pending">Pending</SelectItem>
                          <SelectItem value="assigned">Assigned</SelectItem>
                        </SelectContent>
                      </Select>
                    </div>
                  </div>
                </CardHeader>
                <CardContent>
                  <DataTable
                    columns={deliveryColumns}
                    data={overnightQueue}
                    searchable
                    filterable
                  />
                </CardContent>
              </Card>

              <div className="grid grid-cols-1 lg:grid-cols-3 gap-6">
                <Card>
                  <CardHeader>
                    <CardTitle className="text-base">Bulk Actions</CardTitle>
                  </CardHeader>
                  <CardContent className="space-y-2">
                    <Button className="w-full justify-start" variant="outline">
                      <Users className="h-4 w-4 mr-2" />
                      Auto-Assign to Drivers
                    </Button>
                    <Button className="w-full justify-start" variant="outline">
                      <MapPin className="h-4 w-4 mr-2" />
                      Optimize Routes
                    </Button>
                    <Button className="w-full justify-start" variant="outline">
                      <Calendar className="h-4 w-4 mr-2" />
                      Schedule for Tomorrow
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 14 of 20

```
                    </Button>
                    <Button className="w-full justify-start" variant="outline">
                      <Download className="h-4 w-4 mr-2" />
                      Export Queue
                    </Button>
                  </CardContent>
                </Card>

                <Card className="lg:col-span-2">
                  <CardHeader>
                    <CardTitle className="text-base">Queue Statistics</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="grid grid-cols-2 gap-4">
                      <CompactMetric
                        label="Total in Queue"
                        value={overnightQueue.length}
                        icon={<Package className="h-4 w-4" />}
                      />
                      <CompactMetric
                        label="Unassigned"
                        value={overnightQueue.filter((d) => !d.driverId).length}
                        icon={<AlertTriangle className="h-4 w-4" />}
                      />
                      <CompactMetric
                        label="Assigned"
                        value={overnightQueue.filter((d) => d.driverId).length}
                        icon={<CheckCircle className="h-4 w-4" />}
                      />
                      <CompactMetric
                        label="Avg Wait Time"
                        value="2.5h"
                        icon={<Clock className="h-4 w-4" />}
                      />
                    </div>
                  </CardContent>
                </Card>
              </div>
            </TabsContent>

```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 15 of 20

```
            <TabsContent value="fleet" className="space-y-6">
              <Card>
                <CardHeader>
                  <CardTitle>Fleet Mobility Tracking</CardTitle>
                  <CardDescription>Real-time driver locations and routes</CardDescription>
                </CardHeader>
                <CardContent>
                  <div className="h-[500px] rounded-lg overflow-hidden border border-border">
                    <MapView
                      deliveries={mockDeliveries}
                      drivers={drivers}
                      warehouses={mockWarehouses}
                    />
                  </div>
                </CardContent>
              </Card>

              <div className="grid grid-cols-1 lg:grid-cols-2 gap-6">
                <Card>
                  <CardHeader>
                    <CardTitle>Active Drivers</CardTitle>
                    <CardDescription>{drivers.length} drivers currently active</CardDescription>
                  </CardHeader>
                  <CardContent>
                    <ScrollArea className="h-[400px]">
                      <div className="space-y-3">
                        {drivers.map((driver) => (
                          <div
                            key={driver.id}
                            className="p-4 rounded-lg border border-border bg-card"
                          >
                            <div className="flex items-center justify-between mb-3">
                              <div className="flex items-center gap-3">
                                <div className="h-10 w-10 rounded-full bg-primary/10 flex items-center justify-center">
                                  <Truck className="h-5 w-5 text-primary" />
                                </div>
                                <div>
                                  <div className="font-semibold">{driver.name}</div>
                                  <div className="text-xs text-muted-foreground">
                                    {driver.vehicleAssignment?.licensePlate}
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 16 of 20

```
                                  </div>
                                </div>
                              </div>
                              <Badge variant="outline" className="text-xs">
                                Active
                              </Badge>
                            </div>
                            <div className="grid grid-cols-3 gap-2 text-xs">
                              <div>
                                <div className="text-muted-foreground">Today</div>
                                <div className="font-semibold">12 deliveries</div>
                              </div>
                              <div>
                                <div className="text-muted-foreground">Success</div>
                                <div className="font-semibold">95%</div>
                              </div>
                              <div>
                                <div className="text-muted-foreground">Location</div>
                                <div className="font-semibold flex items-center gap-1">
                                  <MapPin className="h-3 w-3" />
                                  Live
                                </div>
                              </div>
                            </div>
                          </div>
                        ))}
                      </div>
                    </ScrollArea>
                  </CardContent>
                </Card>

                <Card>
                  <CardHeader>
                    <CardTitle>Fleet Statistics</CardTitle>
                    <CardDescription>Current fleet performance</CardDescription>
                  </CardHeader>
                  <CardContent className="space-y-6">
                    <div className="grid grid-cols-2 gap-4">
                      <CompactMetric
                        label="Total Vehicles"
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 17 of 20

```
                        value={drivers.length}
                        icon={<Truck className="h-4 w-4" />}
                      />
                      <CompactMetric
                        label="Active Now"
                        value={drivers.length}
                        icon={<Activity className="h-4 w-4" />}
                      />
                      <CompactMetric
                        label="Avg Speed"
                        value="45 km/h"
                        icon={<TrendingUp className="h-4 w-4" />}
                      />
                      <CompactMetric
                        label="Total Distance"
                        value="1,234 km"
                        icon={<MapPin className="h-4 w-4" />}
                      />
                    </div>

                    <Separator />

                    <div className="space-y-3">
                      <div className="text-sm font-semibold">Vehicle Types</div>
                      <div className="space-y-2">
                        <div className="flex items-center justify-between text-sm">
                          <span className="text-muted-foreground">Bikes</span>
                          <span className="font-semibold">8</span>
                        </div>
                        <div className="flex items-center justify-between text-sm">
                          <span className="text-muted-foreground">Vans</span>
                          <span className="font-semibold">12</span>
                        </div>
                        <div className="flex items-center justify-between text-sm">
                          <span className="text-muted-foreground">Trucks</span>
                          <span className="font-semibold">4</span>
                        </div>
                      </div>
                    </div>
                  </CardContent>
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 18 of 20

```
                  </Card>
                </div>
              </TabsContent>

              <TabsContent value="exceptions" className="space-y-6">
                <Card>
                  <CardHeader>
                    <div className="flex items-center justify-between">
                      <div>
                        <CardTitle>Exception Handling</CardTitle>
                        <CardDescription>
                          {exceptions.length} failed deliveries requiring attention
                        </CardDescription>
                      </div>
                      <Button size="sm">
                        <RefreshCw className="h-4 w-4 mr-2" />
                        Refresh
                      </Button>
                    </div>
                  </CardHeader>
                  <CardContent>
                    <DataTable
                      columns={exceptionColumns}
                      data={exceptions}
                      searchable
                      filterable
                    />
                  </CardContent>
                </Card>

                <div className="grid grid-cols-1 lg:grid-cols-3 gap-6">
                  <Card>
                    <CardHeader>
                      <CardTitle className="text-base">Quick Actions</CardTitle>
                    </CardHeader>
                    <CardContent className="space-y-2">
                      <Button className="w-full justify-start" variant="outline">
                        <RefreshCw className="h-4 w-4 mr-2" />
                        Retry All Failed
                      </Button>
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 19 of 20

```
                    <Button className="w-full justify-start" variant="outline">
                      <Users className="h-4 w-4 mr-2" />
                      Reassign to Drivers
                    </Button>
                    <Button className="w-full justify-start" variant="outline">
                      <Calendar className="h-4 w-4 mr-2" />
                      Schedule Reattempts
                    </Button>
                    <Button className="w-full justify-start" variant="outline">
                      <XCircle className="h-4 w-4 mr-2" />
                      Mark as Cancelled
                    </Button>
                  </CardContent>
                </Card>

                <Card className="lg:col-span-2">
                  <CardHeader>
                    <CardTitle className="text-base">Exception Analysis</CardTitle>
                  </CardHeader>
                  <CardContent>
                    <div className="space-y-4">
                      <div className="grid grid-cols-2 gap-4">
                        <CompactMetric
                          label="Total Exceptions"
                          value={exceptions.length}
                          icon={<XCircle className="h-4 w-4" />}
                        />
                        <CompactMetric
                          label="NDR Cases"
                          value={exceptions.filter((e) => e.ndrCase).length}
                          icon={<AlertTriangle className="h-4 w-4" />}
                        />
                      </div>

                      <Separator />

                      <div className="space-y-3">
                        <div className="text-sm font-semibold">Failure Reasons</div>
                        <div className="space-y-2">
                          <div className="flex items-center justify-between text-sm">
```

pages/SupervisorPortal.tsx

784 lines · 32,220 bytes · Page segment 20 of 20

```
                            <span className="text-muted-foreground">Recipient not available</span>
                            <span className="font-semibold">15</span>
                          </div>
                          <div className="flex items-center justify-between text-sm">
                            <span className="text-muted-foreground">Wrong address</span>
                            <span className="font-semibold">5</span>
                          </div>
                          <div className="flex items-center justify-between text-sm">
                            <span className="text-muted-foreground">Refused delivery</span>
                            <span className="font-semibold">3</span>
                          </div>
                        </div>
                      </div>
                    </div>
                  </CardContent>
                </Card>
              </div>
            </TabsContent>
          </Tabs>
        </div>
      </div>
    </div>
  );
}
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 1 of 16

```
// @ts-nocheck
import { useState } from 'react';
import { useLocation } from 'react-router-dom';
import { motion } from 'framer-motion';
import { Package, QrCode, Truck, ArrowRightLeft, Search, Filter, Plus, CheckCircle, AlertCircle, Clock, MapPin, Scan, Box, PackageCheck, Package
X } from 'lucide-react';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Input } from '@/components/ui/input';
import { Badge } from '@/components/ui/badge';
import { Tabs, TabsContent, TabsList, TabsTrigger } from '@/components/ui/tabs';
import { Select, SelectContent, SelectItem, SelectTrigger, SelectValue } from '@/components/ui/select';
import { MetricCard, StatsGrid, StatusBadge, CompactMetric } from '@/components/Stats';
import { DataTable, Column } from '@/components/DataTable';
import { mockShipments, mockDeliveries, mockManifests, mockWarehouses } from '@/data/index';
import { Shipment, Delivery, Manifest, Warehouse, formatDate, formatWeight, getStatusColor } from '@/lib/index';
import { IMAGES } from '@/assets/images';

export default function WarehousePortal() {
  const location = useLocation();
  const getInitialTab = () => {
    if (location.pathname.includes('/sorting')) return 'sorting';
    if (location.pathname.includes('/dispatch')) return 'dispatch';
    return 'inbound';
  };
  const [activeTab, setActiveTab] = useState(getInitialTab());
  const [searchQuery, setSearchQuery] = useState('');
  const [selectedWarehouse, setSelectedWarehouse] = useState('wh-001');
  const [scanMode, setScanMode] = useState(false);

  const warehouse = mockWarehouses.find(w => w.id === selectedWarehouse);
  const warehouseShipments = mockShipments.filter(s => s.warehouseId === selectedWarehouse);
  const inboundShipments = warehouseShipments.filter(s => ['pending', 'assigned', 'picked-up'].includes(s.status));
  const sortingShipments = warehouseShipments.filter(s => s.status === 'in-transit');
  const outboundShipments = warehouseShipments.filter(s => s.status === 'out-for-delivery');

  const warehouseMetrics = [
    {
      title: 'Inbound Packages',
      value: inboundShipments.length,
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 2 of 16

```
      icon: <Package className="w-5 h-5" />,
      trend: 8.2,
      unit: 'packages',
    },
    {
      title: 'Sorting Queue',
      value: sortingShipments.length,
      icon: <QrCode className="w-5 h-5" />,
      trend: -5.3,
      unit: 'packages',
    },
    {
      title: 'Dispatch Ready',
      value: outboundShipments.length,
      icon: <Truck className="w-5 h-5" />,
      trend: 12.1,
      unit: 'packages',
    },
    {
      title: 'Capacity Used',
      value: warehouse ? `${Math.round((warehouse.capacity.current / warehouse.capacity.total) * 100)}%` : '0%',
      icon: <Box className="w-5 h-5" />,
      trend: 3.5,
    },
  ];

  const inboundColumns: Column<Shipment>[] = [
    {
      id: 'awb',
      header: 'AWB',
      sortable: true,
      cell: (row) => <span className="font-mono text-sm font-medium">{row.awb}</span>,
    },
    {
      id: 'sender',
      header: 'Sender',
      cell: (row) => (
        <div>
          <div className="font-medium">{row.sender.name}</div>
          <div className="text-sm text-muted-foreground">{row.sender.phone}</div>
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 3 of 16

```
        </div>
      ),
    },
    {
      id: 'recipient',
      header: 'Recipient',
      cell: (row) => (
        <div>
          <div className="font-medium">{row.recipient?.name}</div>
          <div className="text-sm text-muted-foreground">{row.recipient?.address?.city}</div>
        </div>
      ),
    },
    {
      id: 'packageDetails',
      header: 'Weight',
      cell: (row) => formatWeight(row.weight),
    },
    {
      id: 'status',
      header: 'Status',
      cell: (row) => <StatusBadge status={row.status} size="sm" />,
    },
    {
      id: 'createdAt',
      header: 'Received',
      sortable: true,
      cell: (row) => formatDate(row.createdAt, 'datetime'),
    },
  ];

  const sortingColumns: Column<Shipment>[] = [
    {
      id: 'awb',
      header: 'AWB',
      sortable: true,
      cell: (row) => (
        <div className="flex items-center gap-2">
          <QrCode className="w-4 h-4 text-muted-foreground" />
          <span className="font-mono text-sm font-medium">{row.awb}</span>
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 4 of 16

```
        </div>
      ),
    },
    {
      id: 'serviceType',
      header: 'Service',
      cell: (row) => (
        <Badge variant="outline" className="capitalize">
          {row.serviceType?.replace('-', ' ')}
        </Badge>
      ),
    },
    {
      id: 'recipient',
      header: 'Destination',
      cell: (row) => (
        <div className="flex items-center gap-2">
          <MapPin className="w-4 h-4 text-muted-foreground" />
          <span>{row.recipient?.address?.city}</span>
        </div>
      ),
    },
    {
      id: 'packageDetails',
      header: 'Details',
      cell: (row) => (
        <div className="text-sm">
          <div>{formatWeight(row.weight)}</div>
          <div className="text-muted-foreground">{row.description}</div>
        </div>
      ),
    },
    {
      id: 'status',
      header: 'Status',
      cell: (row) => <StatusBadge status={row.status} size="sm" />,
    },
  ];

  const dispatchColumns: Column<Shipment>[] = [
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 5 of 16

```
    {
      id: 'awb',
      header: 'AWB',
      sortable: true,
      cell: (row) => <span className="font-mono text-sm font-medium">{row.awb}</span>,
    },
    {
      id: 'recipient',
      header: 'Recipient',
      cell: (row) => (
        <div>
          <div className="font-medium">{row.recipient?.name}</div>
          <div className="text-sm text-muted-foreground">{row.recipient?.address?.street}, {row.recipient?.address?.city}</div>
        </div>
      ),
    },
    {
      id: 'serviceType',
      header: 'Service',
      cell: (row) => (
        <Badge variant="outline" className="capitalize">
          {row.serviceType?.replace('-', ' ')}
        </Badge>
      ),
    },
    {
      id: 'estimatedDelivery',
      header: 'ETA',
      cell: (row) => (
        <div className="flex items-center gap-2">
          <Clock className="w-4 h-4 text-muted-foreground" />
          <span className="text-sm">{row.estimatedDelivery ? formatDate(row.estimatedDelivery, 'datetime') : 'TBD'}</span>
        </div>
      ),
    },
    {
      id: 'status',
      header: 'Status',
      cell: (row) => <StatusBadge status={row.status} size="sm" />,
    },
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 6 of 16

```
  ];

  return (
    <div className="min-h-screen bg-background">
      {/* Hero Section */}
      <div className="relative bg-gradient-to-br from-primary/10 via-background to-accent/10 border-b">
        <div className="absolute inset-0 opacity-30">
          <img
            src={IMAGES.SCREENSHOT_5897_2}
            alt="Warehouse Operations"
            className="w-full h-full object-cover"
          />
        </div>
        <div className="absolute inset-0 bg-gradient-to-b from-background/50 via-transparent to-background/70" />

        <div className="relative container mx-auto px-4 py-8">
          <div className="flex items-center justify-between mb-6">
            <div>
              <h1 className="text-3xl font-bold mb-2">Warehouse Portal</h1>
              <p className="text-muted-foreground">Manage inbound, sorting, and dispatch operations</p>
            </div>
            <div className="flex items-center gap-3">
              <Select value={selectedWarehouse} onValueChange={setSelectedWarehouse}>
                <SelectTrigger className="w-[240px]">
                  <SelectValue />
                </SelectTrigger>
                <SelectContent>
                  {mockWarehouses.map((wh) => (
                    <SelectItem key={wh.id} value={wh.id}>
                      {wh.name}
                    </SelectItem>
                  ))}
                </SelectContent>
              </Select>
              <Button
                variant={scanMode ? 'default' : 'outline'}
                onClick={() => setScanMode(!scanMode)}
              >
                <Scan className="w-4 h-4 mr-2" />
                {scanMode ? 'Scanning...' : 'QR Scan'}
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 7 of 16

```
              </Button>
            </div>
          </div>

          {/* Warehouse Info Card */}
          {warehouse && (
            <Card className="bg-card/80 backdrop-blur">
              <CardContent className="p-6">
                <div className="grid grid-cols-1 md:grid-cols-4 gap-6">
                  <CompactMetric
                    label="Warehouse Type"
                    value={warehouse.type.replace('-', ' ').toUpperCase()}
                    icon={<Box className="w-4 h-4" />}
                  />
                  <CompactMetric
                    label="Capacity"
                    value={`${warehouse.capacity.current}/${warehouse.capacity.total}`}
                    icon={<Package className="w-4 h-4" />}
                  />
                  <CompactMetric
                    label="Operating Hours"
                    value={`${warehouse.operatingHours.open} - ${warehouse.operatingHours.close}`}
                    icon={<Clock className="w-4 h-4" />}
                  />
                  <CompactMetric
                    label="Status"
                    value={warehouse.status.toUpperCase()}
                    icon={<CheckCircle className="w-4 h-4 text-chart-3" />}
                    color="text-chart-3"
                  />
                </div>
              </CardContent>
            </Card>
          )}
        </div>
      </div>

      {/* Main Content */}
      <div className="container mx-auto px-4 py-8">
        {/* Metrics Grid */}
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 8 of 16

```
        <StatsGrid metrics={warehouseMetrics} />

        {/* Operations Tabs */}
        <Tabs value={activeTab} onValueChange={setActiveTab} className="mt-8">
          <TabsList className="grid w-full grid-cols-4">
            <TabsTrigger value="inbound" className="flex items-center gap-2">
              <Package className="w-4 h-4" />
              Inbound Intake
            </TabsTrigger>
            <TabsTrigger value="sorting" className="flex items-center gap-2">
              <QrCode className="w-4 h-4" />
              Sorting Line
            </TabsTrigger>
            <TabsTrigger value="dispatch" className="flex items-center gap-2">
              <Truck className="w-4 h-4" />
              Dispatch Staging
            </TabsTrigger>
            <TabsTrigger value="transfers" className="flex items-center gap-2">
              <ArrowRightLeft className="w-4 h-4" />
              Transfers
            </TabsTrigger>
          </TabsList>

          {/* Inbound Intake */}
          <TabsContent value="inbound" className="space-y-6">
            <Card>
              <CardHeader>
                <div className="flex items-center justify-between">
                  <div>
                    <CardTitle>Inbound Intake</CardTitle>
                    <CardDescription>Receive and process incoming shipments</CardDescription>
                  </div>
                  <div className="flex items-center gap-3">
                    <div className="relative">
                      <Search className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground" />
                      <Input
                        placeholder="Search AWB, sender..."
                        value={searchQuery}
                        onChange={(e) => setSearchQuery(e.target.value)}
                        className="pl-9 w-[280px]"
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 9 of 16

```
                      />
                    </div>
                    <Button>
                      <Plus className="w-4 h-4 mr-2" />
                      Receive Shipment
                    </Button>
                  </div>
                </div>
              </CardHeader>
              <CardContent>
                <div className="grid grid-cols-1 md:grid-cols-3 gap-4 mb-6">
                  <motion.div
                    whileHover={{ scale: 1.02 }}
                    className="p-4 rounded-lg border bg-card hover:shadow-md transition-shadow"
                  >
                    <div className="flex items-center gap-3">
                      <div className="p-3 rounded-full bg-primary/10">
                        <PackageCheck className="w-6 h-6 text-primary" />
                      </div>
                      <div>
                        <div className="text-2xl font-bold">{inboundShipments.length}</div>
                        <div className="text-sm text-muted-foreground">Pending Intake</div>
                      </div>
                    </div>
                  </motion.div>
                  <motion.div
                    whileHover={{ scale: 1.02 }}
                    className="p-4 rounded-lg border bg-card hover:shadow-md transition-shadow"
                  >
                    <div className="flex items-center gap-3">
                      <div className="p-3 rounded-full bg-chart-3/10">
                        <CheckCircle className="w-6 h-6 text-chart-3" />
                      </div>
                      <div>
                        <div className="text-2xl font-bold">{Math.floor(inboundShipments.length * 0.7)}</div>
                        <div className="text-sm text-muted-foreground">Processed Today</div>
                      </div>
                    </div>
                  </motion.div>
                  <motion.div
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 10 of 16

```
                    whileHover={{ scale: 1.02 }}
                    className="p-4 rounded-lg border bg-card hover:shadow-md transition-shadow"
                  >
                    <div className="flex items-center gap-3">
                      <div className="p-3 rounded-full bg-chart-4/10">
                        <AlertCircle className="w-6 h-6 text-chart-4" />
                      </div>
                      <div>
                        <div className="text-2xl font-bold">{Math.floor(inboundShipments.length * 0.1)}</div>
                        <div className="text-sm text-muted-foreground">Requires Inspection</div>
                      </div>
                    </div>
                  </motion.div>
                </div>
                <DataTable
                  columns={inboundColumns}
                  data={inboundShipments}
                  searchable
                  filterable
                  exportable
                />
              </CardContent>
            </Card>
          </TabsContent>

          {/* Sorting Line */}
          <TabsContent value="sorting" className="space-y-6">
            <Card>
              <CardHeader>
                <div className="flex items-center justify-between">
                  <div>
                    <CardTitle>Sorting Line Management</CardTitle>
                    <CardDescription>Scan and sort packages for dispatch</CardDescription>
                  </div>
                  <div className="flex items-center gap-3">
                    <Button variant="outline">
                      <Filter className="w-4 h-4 mr-2" />
                      Filter by Route
                    </Button>
                    <Button>
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 11 of 16

```
                        <QrCode className="w-4 h-4 mr-2" />
                        Batch Scan
                      </Button>
                    </div>
                  </div>
                </CardHeader>
                <CardContent>
                  {scanMode && (
                    <motion.div
                      initial={{ opacity: 0, y: -20 }}
                      animate={{ opacity: 1, y: 0 }}
                      className="mb-6 p-6 rounded-lg border-2 border-dashed border-primary bg-primary/5"
                    >
                      <div className="flex items-center justify-center gap-4">
                        <div className="relative">
                          <img
                            src={IMAGES.PACKAGE_1}
                            alt="QR Scanning"
                            className="w-32 h-32 object-cover rounded-lg opacity-50"
                          />
                          <div className="absolute inset-0 flex items-center justify-center">
                            <Scan className="w-16 h-16 text-primary animate-pulse" />
                          </div>
                        </div>
                        <div>
                          <div className="text-lg font-semibold mb-2">QR Scanner Active</div>
                          <div className="text-sm text-muted-foreground mb-4">
                            Position package QR code in front of scanner
                          </div>
                          <Button variant="outline" size="sm" onClick={() => setScanMode(false)}>
                            Stop Scanning
                          </Button>
                        </div>
                      </div>
                    </motion.div>
                  )}
                  <div className="grid grid-cols-1 md:grid-cols-4 gap-4 mb-6">
                    <CompactMetric
                      label="In Sorting"
                      value={sortingShipments.length}
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 12 of 16

```
                    icon={<QrCode className="w-4 h-4" />}
                  />
                  <CompactMetric
                    label="Sorted Today"
                    value={Math.floor(sortingShipments.length * 2.5)}
                    icon={<CheckCircle className="w-4 h-4 text-chart-3" />}
                    color="text-chart-3"
                  />
                  <CompactMetric
                    label="Avg. Sort Time"
                    value="2.3 min"
                    icon={<Clock className="w-4 h-4" />}
                  />
                  <CompactMetric
                    label="Accuracy Rate"
                    value="99.2%"
                    icon={<PackageCheck className="w-4 h-4 text-chart-3" />}
                    color="text-chart-3"
                  />
                </div>
                <DataTable
                  columns={sortingColumns}
                  data={sortingShipments}
                  searchable
                  filterable
                />
              </CardContent>
            </Card>
          </TabsContent>

          {/* Dispatch Staging */}
          <TabsContent value="dispatch" className="space-y-6">
            <Card>
              <CardHeader>
                <div className="flex items-center justify-between">
                  <div>
                    <CardTitle>Dispatch Staging Area</CardTitle>
                    <CardDescription>Prepare packages for outbound delivery</CardDescription>
                  </div>
                  <div className="flex items-center gap-3">
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 13 of 16

```
                    <Button variant="outline">
                      <Filter className="w-4 h-4 mr-2" />
                      Filter by Manifest
                    </Button>
                    <Button>
                      <Truck className="w-4 h-4 mr-2" />
                      Create Manifest
                    </Button>
                  </div>
                </div>
              </CardHeader>
              <CardContent>
                <div className="grid grid-cols-1 md:grid-cols-3 gap-4 mb-6">
                  <motion.div
                    whileHover={{ scale: 1.02 }}
                    className="p-4 rounded-lg border bg-card hover:shadow-md transition-shadow"
                  >
                    <div className="flex items-center gap-3">
                      <div className="p-3 rounded-full bg-primary/10">
                        <Truck className="w-6 h-6 text-primary" />
                      </div>
                      <div>
                        <div className="text-2xl font-bold">{outboundShipments.length}</div>
                        <div className="text-sm text-muted-foreground">Ready for Dispatch</div>
                      </div>
                    </div>
                  </motion.div>
                  <motion.div
                    whileHover={{ scale: 1.02 }}
                    className="p-4 rounded-lg border bg-card hover:shadow-md transition-shadow"
                  >
                    <div className="flex items-center gap-3">
                      <div className="p-3 rounded-full bg-chart-3/10">
                        <CheckCircle className="w-6 h-6 text-chart-3" />
                      </div>
                      <div>
                        <div className="text-2xl font-bold">{mockManifests.filter(m => m.status === 'active').length}</div>
                        <div className="text-sm text-muted-foreground">Active Manifests</div>
                      </div>
                    </div>
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 14 of 16

```
                  </motion.div>
                  <motion.div
                    whileHover={{ scale: 1.02 }}
                    className="p-4 rounded-lg border bg-card hover:shadow-md transition-shadow"
                  >
                    <div className="flex items-center gap-3">
                      <div className="p-3 rounded-full bg-chart-1/10">
                        <Package className="w-6 h-6 text-chart-1" />
                      </div>
                      <div>
                        <div className="text-2xl font-bold">{Math.floor(outboundShipments.length * 1.8)}</div>
                        <div className="text-sm text-muted-foreground">Dispatched Today</div>
                      </div>
                    </div>
                  </motion.div>
                </div>
                <DataTable
                  columns={dispatchColumns}
                  data={outboundShipments}
                  searchable
                  filterable
                  exportable
                />
              </CardContent>
            </Card>
          </TabsContent>

          {/* Transfers */}
          <TabsContent value="transfers" className="space-y-6">
            <Card>
              <CardHeader>
                <div className="flex items-center justify-between">
                  <div>
                    <CardTitle>Transfer Management</CardTitle>
                    <CardDescription>Manage shipment transfers between branches</CardDescription>
                  </div>
                  <Button>
                    <Plus className="w-4 h-4 mr-2" />
                    Create Transfer
                  </Button>
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 15 of 16

```
                  </div>
                </CardHeader>
                <CardContent>
                  <div className="grid grid-cols-1 md:grid-cols-3 gap-4 mb-6">
                    <CompactMetric
                      label="Pending Transfers"
                      value={5}
                      icon={<ArrowRightLeft className="w-4 h-4" />}
                    />
                    <CompactMetric
                      label="In Transit"
                      value={12}
                      icon={<Truck className="w-4 h-4" />}
                    />
                    <CompactMetric
                      label="Completed Today"
                      value={8}
                      icon={<CheckCircle className="w-4 h-4 text-chart-3" />}
                      color="text-chart-3"
                    />
                  </div>
                  <div className="space-y-4">
                    {mockWarehouses.slice(1).map((wh) => (
                      <motion.div
                        key={wh.id}
                        whileHover={{ scale: 1.01 }}
                        className="p-6 rounded-lg border bg-card hover:shadow-md transition-shadow"
                      >
                        <div className="flex items-center justify-between">
                          <div className="flex items-center gap-4">
                            <div className="p-3 rounded-full bg-primary/10">
                              <MapPin className="w-6 h-6 text-primary" />
                            </div>
                            <div>
                              <div className="font-semibold">{wh.name}</div>
                              <div className="text-sm text-muted-foreground">
                                {wh.address.city}, {wh.address.state}
                              </div>
                            </div>
                          </div>
```

pages/WarehousePortal.tsx

624 lines · 24,993 bytes · Page segment 16 of 16

```
                        <div className="flex items-center gap-6">
                          <div className="text-center">
                            <div className="text-2xl font-bold">3</div>
                            <div className="text-xs text-muted-foreground">Pending</div>
                          </div>
                          <div className="text-center">
                            <div className="text-2xl font-bold">7</div>
                            <div className="text-xs text-muted-foreground">In Transit</div>
                          </div>
                          <Button variant="outline" size="sm">
                            View Details
                          </Button>
                        </div>
                      </div>
                    </motion.div>
                  ))}
                </div>
              </CardContent>
            </Card>
          </TabsContent>
        </Tabs>
      </div>
    </div>
  );
}
```

pages/WayplanPortal.tsx

106 lines · 4,396 bytes · Page segment 1 of 3

```
import { motion } from 'framer-motion';
import { Route, MapPin, Truck, FileText, BarChart3 } from 'lucide-react';
import { Card, CardContent, CardDescription, CardHeader, CardTitle } from '@/components/ui/card';
import { Button } from '@/components/ui/button';
import { Badge } from '@/components/ui/badge';
import { IMAGES } from '@/assets/images';

export default function WayplanPortal() {
  return (
    <div className="min-h-screen bg-background relative">
      <div
        className="absolute inset-0 z-0 opacity-30"
        style={{
          backgroundImage: `url(${IMAGES.SCREENSHOT_6115_2})`,
          backgroundSize: 'cover',
          backgroundPosition: 'center',
        }}
      />
      <div className="absolute inset-0 bg-gradient-to-b from-background/50 via-transparent to-background/70" />

      <div className="relative z-10 space-y-6 p-6">
      <div>
        <h1 className="text-3xl font-bold">Wayplan Manager</h1>
        <p className="text-muted-foreground">Route optimization and manifest management</p>
      </div>

      <div className="grid gap-6 md:grid-cols-2 lg:grid-cols-4">
        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Active Routes</CardTitle>
            <Route className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">24</div>
            <p className="text-xs text-muted-foreground">+3 from yesterday</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
```

pages/WayplanPortal.tsx

106 lines · 4,396 bytes · Page segment 2 of 3

```
            <CardTitle className="text-sm font-medium">Optimized Routes</CardTitle>
            <MapPin className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">18</div>
            <p className="text-xs text-muted-foreground">75% optimization rate</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Vehicles Assigned</CardTitle>
            <Truck className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">32</div>
            <p className="text-xs text-muted-foreground">Out of 45 available</p>
          </CardContent>
        </Card>

        <Card>
          <CardHeader className="flex flex-row items-center justify-between space-y-0 pb-2">
            <CardTitle className="text-sm font-medium">Manifests Created</CardTitle>
            <FileText className="h-4 w-4 text-muted-foreground" />
          </CardHeader>
          <CardContent>
            <div className="text-2xl font-bold">156</div>
            <p className="text-xs text-muted-foreground">This week</p>
          </CardContent>
        </Card>
      </div>

      <Card>
        <CardHeader>
          <CardTitle>Route Optimization</CardTitle>
          <CardDescription>Optimize delivery routes for maximum efficiency</CardDescription>
        </CardHeader>
        <CardContent>
          <div className="space-y-4">
            <div className="flex items-center justify-between p-4 border rounded-lg">
```

pages/WayplanPortal.tsx

106 lines · 4,396 bytes · Page segment 3 of 3

```
              <div>
                <p className="font-medium">Zone A - Morning Routes</p>
                <p className="text-sm text-muted-foreground">45 deliveries, 8 vehicles</p>
              </div>
              <div className="flex items-center gap-2">
                <Badge variant="secondary">Pending</Badge>
                <Button size="sm">Optimize</Button>
              </div>
            </div>
            <div className="flex items-center justify-between p-4 border rounded-lg">
              <div>
                <p className="font-medium">Zone B - Afternoon Routes</p>
                <p className="text-sm text-muted-foreground">32 deliveries, 6 vehicles</p>
              </div>
              <div className="flex items-center gap-2">
                <Badge>Optimized</Badge>
                <Button size="sm" variant="outline">View</Button>
              </div>
            </div>
          </div>
        </CardContent>
      </Card>
      </div>
    </div>
  );
}
```

vite-env.d.ts

4 lines · 133 bytes · Page segment 1 of 1

```
/// <reference types="vite/client" />

// Global constants defined at build time
declare const __ROUTE_MESSAGING_ENABLED__: boolean;
```