

# HW1

---

Kyle Morgenstein

kjm 3887

---

---



①

$$I \ddot{\varphi}_1 + MgL \sin \varphi_1 + k(\varphi_1 - \varphi_2) = 0$$

$$J \ddot{\varphi}_2 - k(\varphi_1 - \varphi_2) = u$$

$\Downarrow$

$$\ddot{\varphi}_1 = -I^{-1}(MgL \sin \varphi_1 + k(\varphi_1 - \varphi_2))$$

$$\ddot{\varphi}_2 = J^{-1}(u - k(\varphi_1 - \varphi_2))$$


State Variables

$$q = [\varphi_1, \varphi_2, \dot{\varphi}_1, \dot{\varphi}_2]$$


$$\dot{q} = [\dot{\varphi}_1, \dot{\varphi}_2, \ddot{\varphi}_1, \ddot{\varphi}_2]$$

$$\dot{q} = f(q), \quad f(q) = \begin{bmatrix} \dot{\varphi}_1 \\ \dot{\varphi}_2 \\ -I^{-1}(MgL \sin \varphi_1 + k(\varphi_1 - \varphi_2)) \\ J^{-1}(u - k(\varphi_1 - \varphi_2)) \end{bmatrix}$$

②



$$i = h(v)$$



$$i_C + i_L + i_{\text{active}} = 0$$

$$i_C = C \dot{v} \quad i_{\text{active}} = h(v)$$

$$v = L \dot{i}_L$$

$$C \dot{v} + i_L + h(v) = 0$$

$$\frac{d}{dt} [C \dot{v} + i_L + h(v)]$$

$$C \ddot{v} + \dot{i}_L + h'(v) \dot{v} = 0$$

$$C \ddot{v} + v/L + h'(v) \dot{v} = 0$$

$$LC \ddot{v} + v + h'(v) \dot{v} = 0$$

$$x = \begin{bmatrix} v \\ \dot{v} \end{bmatrix}$$

$$\dot{x} = \begin{bmatrix} \dot{v} \\ \ddot{v} \end{bmatrix} = \begin{bmatrix} \dot{v} \\ -v/LC - h'(v) \dot{v} \end{bmatrix}$$

③

$$x = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$$

$$\dot{x} = \begin{bmatrix} x_2 \\ -x_1 + \frac{1}{16} x_1^5 - x_2 \end{bmatrix}$$

a) Equilibrium points:  $\dot{x} = 0 \rightarrow x_2 = 0, x_1^5/16 - x_1 = 0$

i)  $x_1 = \pm 2, x_2 = 0 \rightarrow$  saddle

$$x_1^4/16 - 1 = 0$$

ii)  $x_1 = 0, x_2 = 0 \rightarrow$  stable node

$$(x_1^2/4 - 1)(x_1^2/4 + 1) = 0$$

iii)  $x_1 = \pm 2i, x_2 = 0 \rightarrow$  circular

$$(x_1/2 - 1)(x_1/2 + 1)(x_1^2/4 + 1) = 0$$

$$x_1 = \pm 2, \pm 2i, 0$$

b) phase portrait

see notebook below

④

$$\ddot{y} + k_y + c\dot{y} + \eta(y, \dot{y}) = 0$$

$$\eta(y, \dot{y}) = \begin{cases} m_k m_g \sin(\dot{y}) \\ -k_y \\ -m_s m_g \sin(y) \end{cases}$$

$$|\dot{y}| > 0$$

$$\dot{y} = 0, |\dot{y}| \leq m_s m_g / k$$

$$\dot{y} = 0, |\dot{y}| > m_s m_g / k$$

$$x = \begin{bmatrix} y \\ \dot{y} \end{bmatrix} \quad \dot{x} = \begin{bmatrix} \dot{y} \\ \ddot{y} \end{bmatrix}$$

$$\ddot{y} = -k_y - c\dot{y} - \eta(y, \dot{y})$$

see notebook below

⑤

$$\dot{x} = \begin{bmatrix} x_2 \\ u \end{bmatrix}, \quad u \in \{-1, 1\}$$

$$x_1 = x$$

$$x_2 = v$$

$$\dot{x}_1 = v$$

$$\dot{x}_2 = a$$

$$x(t) = x_0 + v_0 t + v t + \frac{1}{2} a t^2$$

see notebook below

# hw1

September 10, 2025

## 1 Homework 1

due 09/10/2025 23:59

```
[28]: # deps
from typing import Callable
import numpy as np
import matplotlib.pyplot as plt
from scipy.integrate import solve_ivp

from utils import phase_portrait
```

### 1.1 Problem 3

1) Find equilibrium points for


$$\dot{x}_1 = x_2 \tag{1}$$

$$\dot{x}_2 = -x_1 + \frac{1}{16}x_1^5 - x_2 \tag{2}$$

2) Plot the phase portrait

```
[29]: def dynamics(
    t: float | None,
    state: list,
) -> list:
    x1, x2 = state
    dx1 = x2
    dx2 = -x1 + x1**5/16 - x2
    return [dx1, dx2]

phase_portrait(x_max=4, n_pts=100, dynamics=dynamics, save=True)
```



## 1.2 Problem 4

- 1) Sketch the phase portrait for

$$\dot{x}_1 = x_2 \quad (3)$$

$$\dot{x}_2 = -kx_1 - cx_2 - \eta(x_1, x_2) \quad (4)$$

- 2) Describe the behavior qualitatively

The phase portrait has an unstable node at the origin, with circular orbits on either side of the  $x_1$  plane. The behavior is disjoint about  $x_2$  given the sign function in the dynamics.

```
[30]: def sign(n):
      return np.where(
          n > 0,
          1,
          np.where(
```

```


        n < 0,
        -1,
        0
    )
)

def eta(
    state: list,
    k: float,
    m: float,
    g: float,
    mu_k: float,
    mu_s: float,
):
    x1, x2 = state
    return np.where(
        np.abs(x2) > 0,
        mu_k * m * g * sign(x2),
        np.where(
            np.abs(x1) <= mu_s * m * g / k,
            -k * x1,
            mu_s * m * g * sign(x1)
        )
    )

def dynamics(
    t: float | None,
    state: list,
    k: float = 2.0,
    c: float = 1.0,
    m: float = 1.0,
    g: float = -9.8,
    mu_k: float = 0.5,
    mu_s: float = 0.5,
) -> list:
    x1, x2 = state
    dx1 = x2
    dx2 = -k * x1 - c * x2 - eta(state, k, m, g, mu_k, mu_s)
    return [dx1, dx2]

phase_portrait(x_max=4, n_pts=100, dynamics=dynamics, save=True)

```



### 1.3 Problem 5

- 1) Sketch phase portraits for  $u = 1$  and  $u = -1$

$$\dot{x}_1 = x_2 \quad (5)$$

$$\dot{x}_2 = u \quad (6)$$

- 2) Develop graphical control strategy

Define switching curve  $x_1 = \pm \frac{x_2^2}{2}$ . Then, from anywhere in  $x_1 - x_2$  plane, the origin can be obtained by following the corresponding curve. When above the curve, apply negative control input; when below the curve, apply positive control input. This is a “bang bang” controller.

```
[31]: def dynamics(
    t: float | None,
    state: list,
    u: float,
```



```

) -> list:
    x1, x2 = state
    dx1 = x2
    dx2 = u * np.ones_like(x2)
    return [dx1, dx2]

def set_u(u) -> Callable[..., list]:
    def wrapped_dynamics(t, state):# -> list:
        return dynamics(t, state, u)
    return wrapped_dynamics

dynamics_plus = set_u(1)
dynamics_minus = set_u(-1)

phase_portrait(x_max=4, n_pts=100, dynamics=dynamics_plus, save=True)
phase_portrait(x_max=4, n_pts=100, dynamics=dynamics_minus, save=True)

```

