Capstone Proposal

From Skills to KSAs: A Tool-Agnostic Framework for Military-to-Civilian Translation

Proposed by: Kyle Hall

Email: Kyle.hall@gwu.edu Advisor: Amir Jafari

The George Washington University, Washington DC

Data Science Program

1. Objective

Demonstrate an end-to-end data science capstone by building a **tool-agnostic KSA extraction pipeline** for selected **USAF AFSCs**, aligning the results to **civilian skill frameworks (ESCO/O*NET)**, and publishing a **graph network** with a **lightweight**, **static website** that lets users search an AFSC and view KSAs (with provenance). Optionally, incorporate a **preference-learning (RL-light) re-ranker** trained on small batches of SME feedback to improve KSA-to-standard alignment ordering.

Specific objectives (plain language):

- 1. Pull KSAs from unclassified Air Force documents (AFOCD/AFECD, CFETPs, fact sheets, syllabi) and **keep the page/section** for every item.
- 2. Turn results into a tidy **K/S/A table** with a short description, type (K|S|A), deduped phrasing, provenance, **ESCO/O*NET** links, and a confidence score.
- 3. **Publish a graph export** (AFSC ↔ KSA ↔ ESCO/O*NET ↔ SourceDoc) and a **per-AFSC static JSON** bundle that powers a web demo.
- 4. Ship a **searchable static site** (GitHub Pages/Netlify) where a user selects an AFSC → sees K/S/A tabs, simple filters, evidence toggle, and an **optional** interactive graph view for that AFSC's subgraph.
- 5. (Optional) Collect ~150–200 SME preferences and train a **pairwise re-ranker** to improve top-k alignment ordering (report uplift with NDCG@10, P@5).
- 6. Publish a lightweight web application that lets users search AFSCs and view extracted KSAs with evidence, using prebuilt JSON exports from the pipeline.

Success criteria: usable AFSC search; evidence-backed KSAs; importable graph exports; and measurable accuracy on a small labeled set (see §5).

2. Dataset

- Sources (unclassified): AFOCD/AFECD (e.g., current public releases), CFETPs, fact sheets, training syllabi.
- **Coverage (initial):** 6–8 AFSCs across 2–3 families (e.g., Operations / Intelligence / Maintenance). Pipeline and site are designed to scale to "most AFSCs" later by adding more documents.

- **Parsing:** structure-aware (headings/sections/pages) to support precise **provenance** for each extracted item
- Civilian standards for alignment: ESCO (public), O*NET (local copy).
- **Availability:** All datasets are **publicly accessible**; any restricted materials will be excluded or reduced to derived metadata only.
- **Provenance captured:** document title/date, section/page, character offsets (when feasible), and a short evidence quote.

3 Rationale

The DoD lacks a unified, machine-readable KSA layer that ties AFSC-specific competencies to civilian frameworks. This project delivers an **evidence-bearing**, **queryable KSA graph** and **simple web access**, enabling service members to translate experience, and enabling educators and planners to align curricula and workforce needs.

- **Operational impact:** A reusable KSA layer with provenance reduces manual curation time for career translation, curriculum updates, and program evaluation.
- **Framework bridging:** Dual alignment (ESCO/O*NET) maximizes interoperability with civilian ecosystems.
- **Demonstrable value:** A working web demo + importable graph artifacts show end-to-end feasibility within a capstone timeline.

4. Method

4.1 Pipeline Overview

- 1. Ingest: Collect AFSC-relevant documents; extract text with layout cues; segment by section/page.
- Candidate KSA Extraction: Hybrid approach—pattern cues + POS/NER, embedding-based retrieval, and LLM prompts specialized for K/S/A.
- 3. Normalization & Deduplication: Cluster semantically similar items; canonicalize phrasing; tag K|S|A.
- 4. **Alignment to ESCO/O*NET:** Vector similarity + lexical overlap + concept heuristics; keep top-k with scores.
- 5. **Provenance & QA:** Attach (doc_id, section/page, evidence snippet); add sanity checks to reduce ability/skill conflation.
- Graph Build & Exports: Emit GraphML, Neo4j CSV, and per-AFSC JSON bundles used by the web demo.

4.2 Graph Schema (typed)

Nodes:

- AFSC (id, title, family)
- KSA (id, normalized_text, type ∈ {K,S,A})
- SourceDoc (id, title, ref)
- Standard (id, type ∈ {ESCO,O*NET}, label)

Edges:

proposal group6 Final.md 2025-09-23

- AFSC—[HAS_K|HAS_S|HAS_A]→KSA
- KSA—[SUPPORTED_BY {page, section, quote}] → SourceDoc
- KSA—[ALIGNS_TO {score}]→Standard

4.3 Web Demo (static-first)

- Stack: Vite/React, Fuse.js for client-side search, Cytoscape.js for the optional graph tab.
- Data: afsc_index.json for search + afsc/<AFSC>.json subgraphs (built offline by the pipeline).
- UX: AFSC search → K/S/A tabs with counts → filter by type / alignment / confidence → toggle evidence
 → optional Graph tab → Download JSON/CSV.
- **Hosting:** GitHub Pages/Netlify (no backend). If live DB queries are later required, add a minimal FastAPI service.

4.4 Preference-Learning Re-Ranker (RL-light, optional)

- **Goal:** Improve the ordering of KSA→Standard alignments.
- Data: ~150–200 SME binary/pairwise judgments (A vs B).
- Model: Pairwise logistic (Bradley-Terry) or LambdaMART (XGBoost).
- Features: cosine sim, lexical overlap, doc frequency, cue-phrase flags, evidence heuristics.
- Metrics: NDCG@10, P@5 uplift vs baseline; SME "useful" rate.

4.5 Web Application (Static Demo)

Scope (MVP):

- AFSC search bar + filters for Operations / Intelligence / Maintenance
- Results list with K/S/A label, statement text, evidence snippet, source (AFOCD/AFECD/manual) and optional page
- Count badges per AFSC (e.g., K:12 S:9 A:7)
- Client-side CSV download of current results
- (Optional, if time allows) Small graph preview (AFSC node with K/S/A leaves)

Goal: Provide a simple, tool-agnostic interface for exploring results: search an AFSC, view KSAs grouped by Knowledge/Skill/Ability, and see short evidence snippets with source/page when available.

4.6 Methods & Techniques — Prioritized (Top 10)

- 1. **Ingest & Provenance:** Structure-aware parsing of AFSC documents with page/section capture (pdfminer.six / unstructured.io).
- 2. **Pattern-Based KSA Spotting:** Cue-phrase mining + POS/NER to extract candidate K/S/A spans.
- 3. **Semantic Retrieval for Candidates:** Dense embeddings (sentence-transformers) + FAISS to surface KSA-salient sentences.
- 4. **LLM Typing & Canonicalization:** Few-shot prompts at low temperature to assign K/S/A labels and paraphrase to a clean form.
- 5. **De-duplication & Clustering:** Embedding-similarity thresholding and light clustering to merge near-duplicates.
- 6. **Hybrid Alignment Scoring:** BM25 (lexical) + cosine (dense) fusion to rank ESCO/O*NET matches (retain top-k).
- 7. **Evidence & QA:** Snippet extraction with page refs plus quardrail heuristics to reduce K/S/A conflation.

- 8. **Graph Build & Exports:** networkx → GraphML / Neo4j CSV; emit per-AFSC JSON bundles for the site.
- 9. Static Web Search UX: React + Fuse.js with simple filters; optional Cytoscape.js graph tab.
- 10. **Preference Re-ranking (RL-light):** Pairwise logistic or LambdaMART trained on quick SME preferences; report NDCG@10 uplift.

Estimated order reflects pipeline flow; items 9-10 can proceed in parallel once data artifacts exist.

5. Evaluation

- **Gold set:** label ~100–150 KSA items across AFSCs with validity, type, and alignment.
- Extraction: Precision/Recall/F1 (target F1 ≥ 0.70 on the labeled set).
- Alignment: Accuracy@k (target @5 ≥ 70%).
- Web usability: Task success (find 3 KSAs) and time-to-answer; brief SUS survey.
- Re-ranker (if used): NDCG@10 uplift ≥ +5% vs baseline on held-out AFSCs.

6. Deliverables

- Data: normalized KSA table; alignment table with scores; evidence snippets.
- Graph: GraphML, Neo4j CSV, per-AFSC JSON bundles.
- Web Demo (static): AFSC search + filters; evidence toggle; optional graph tab; download.
- Re-Ranker (optional): model file + short results note.
- Web demo (static site): AFSC search → K/S/A results with evidence; hosted on GitHub Pages/Netlify; data file afsc_ksas.json under demo/site/public/data/.
- Final Write-Up: methods, evaluation, limitations, and ethics considerations.

7. Timeline (indicative, Fall 2025)

- W1-2: finalize AFSC list; gather documents; repo + schema.
- W3-4: extraction (pattern + embeddings + prompts); normalization.
- W5: ESCO/O*NET alignment; evidence pipeline; first labeled set.
- W6: graph build + exports (GraphML/Neo4j CSV/JSON).
- **W7:** web MVP (search + K/S/A tabs + evidence toggle).
- W8: optional graph tab; polish; accessibility pass.
- **W9:** preference collection (SME).
- W10: train re-ranker; measure uplift; finalize demo & report.

8. Risks & Descoping

- **Doc access/quality:** expand to adjacent curriculum docs; if needed, omit quotes but keep page refs.
- **Time/compute:** cache embeddings; CPU-friendly models; narrow AFSCs (4–5) or ship web MVP without graph tab.
- Data variance: rules to reduce false positives; maintain error log and spot checks.

9. Ethics & Responsible Use

- Use only unclassified sources; store derived metadata + page refs, not restricted documents.
- Document limitations (LLM hallucinations; K/S/A boundary ambiguity).
- Anonymize SME judgments and make preference data opt-in.

Appendix — Mini-Glossary

- KSA Knowledge, Skills, and Abilities (competency structure used in DoD)
- **AFSC** Air Force Specialty Code (job family)
- **ESCO / O*NET** Civilian skill/occupation frameworks used for alignment
- Provenance Doc title/date, section/page, and a short quote showing the evidence for each item
- CFETP / AFOCD / AFECD Unclassified Air Force classification/training documents

Contact

• Author: Amir Jafari

• Email: ajafari@gwu.edu

• GitHub: amir-jafari/Capstone