



Level 2

Challenge B



Directions:

In the `Haskell_Challenges.hs` file, create a function called `concatStrsAtIndices` that does the following:

The function will take in a list of strings and a list of ints. The list of ints is to be used as indices into the list of strings. The function should return a single string that is the result of concatenating all strings at the given indices. The indices given will always be valid (i.e. between 0 and length - 1 of the string list). The string list will never be empty.

Although this isn't required, try to come up with two solutions. One that manually uses recursion on one or both lists and another solution that doesn't use any manual recursion (only built-in functions that may use recursion themselves). Either one should pass this challenge, but which one was easier to write?

You will need to figure out an appropriate data type for this function.

Examples:

```
{- call -} concatStrsAtIndices ["a","b","c"] [0,1,2]
{- returns -} "abc"

{- call -} concatStrsAtIndices ["a","b","c"] [2,1,0]
{- returns -} "cba"

{- call -} concatStrsAtIndices ["a","b","c"] [0,0,2,1,2,0]
{- returns -} "aacbca"

{- call -} concatStrsAtIndices ["0","1","2","3","4","5"] [5,3,3,1]
{- returns -} "5331"

{- call -} concatStrsAtIndices ["hey "] [0,0,0,0]
{- returns -} "hey hey hey hey "
```