Lens Radome for 80 GHz Radar Level Sensor Module

Threaded plastic housing with lens that extends the 20 m board to 30 m

Overview

A threaded plastic housing with a built-in lens for the 20 m version of the Kymopsis 80 GHz radar level sensor board. The board mounts on the back with four screws, antenna facing the lens. The lens narrows the beam and, per the module maker, extends the range from 20 m to up to 30 m. The outer thread and flange let you mount it through a tank or lid opening.

Applications

- Longer range and narrower beam for the 20 m 80 GHz level radar board
- Through-lid or through-wall mounting of the board
- Radome and lens tests at 76–81 GHz

Specifications

Frequency	76–81 GHz (for the 80 GHz level radar board, 20 m version)
Range with lens	Up to 30 m (module maker figure; depends on target and scene)
Construction	Plastic housing with outer thread and flange; board fixed with 4 screws

Values are typical or maximum figures stated in the manufacturer's datasheet, not a Kymopsis lab report. Ask us for the manufacturer's test data where one exists.

Notes

- Fits the 20 m version of the Kymopsis 80 GHz radar level sensor board only.

Passive RF component for laboratory, development and integration use. It does not transmit on its own and carries no FCC, CE or other equipment certification claim.

Kymopsis · kymopsis.com · support@kymopsis.com. Specifications may change without notice. Custom lengths, connectors and bands: kymopsis.com/b2b/