OMRON

EtherNet/IP™

NJ/NX/NY Series, CS/CJ Series

High-speed High-capacity Industrial Ethernet
Global Standard
Integration of Controls and Information
Convenience of the Universal Ethernet

The Global Standard Network controls and information.

Data links between PLCs, between PLCs and multivendor devices, and communications between PTs and PLCs are realized with Universal Ethernet.

The global-standard network EtherNet/IP™ integrates controls and information using the latest Universal Ethernet technology and is supported by a wide range of OMRON products: PLCs, Machine Automation Controllers, HMIs, Vision sensors, Displacement Sensors, and Safety. The CJ2/NJ/NX CPU Units and NY Industrial PC Platform provide a built-in EtherNet/IP port.

Global Standard

- Highly open global standard for the FA industry with high future potential.
- No need for separate information and control networks.
- Improved efficiency with common Support Software operations.
- Safety systems can be monitored.

Convenience of the Universal Ethernet Right in Your Hands

EtherNet/IP™

Global Standard

that integrates

Ethernet Technology

- Data communications with higher capacity, **9 times** higher than previous OMRON models.
- Low cost expansion for each line.
- Reduced network construction cost.
- Easy mobile communications with FA wireless LAN.

Integration of Controls and Information

- High-speed data links at optimal cycle, **30 times** faster than previous OMRON models
- FTP communications, data links, and Support Software can be used simultaneously with a single port.
- Memory map management is not required with the NJ/NX/NY-Series and CJ CPU Units.

Industrial Protocol

EtherNet/IP™

EtherNet/IP is a Global Standard for Industrial Ethernet promoted by the ODVA(ODVA,Inc.).

Open Standard

Many companies around the world, including the main manufacturers of control devices, are marketing compatible devices.

Independence

EtherNet/IP specifications are managed by the independent organization ODVA, which promotes the world-wide spread of open networks such as DeviceNet and CompoNet. It does not belong to a specific manufacturer.

High Future Potential

EtherNet/IP has already been implemented in many places internationally. Its use is expected to spread further as the number of compatible devices increases.

What Is CIP?

CIP is a Common Industrial Protocol in the OSI application layer. Routing between networks that use CIP as their base is easy. For this reason, transparent networks from sensors to host devices can be constructed easily.

Global Standard

Highly Open Global Standard for FA Industry with High Future Potential

The ODVA promotes the spread of Industrial Ethernet all over the world.

EtherNet/IP can be used to communicate with many devices from various companies around the world in addition to OMRON components (such as Temperature Controllers and Sensors). The use of EtherNet/IP will rapidly increase the development of an EtherNet/IP multivendor environment (including robots and safety devices).

Integrated Information and Control Network

Seamless communications on the control line and information monitoring line with EtherNet/IP

Using the global standard open protocol (CIP), an independent network system can be created with seamless data flow between the control line and the information monitoring line.
OMRON FINS message communications can also be used on the same network because it is a standard LAN.

Improved operation efficiency with common Support Software operation

Use the same operating procedures for both EtherNet/IP and DeviceNet Support Software.

The same Support Software procedures can be used from a remote location for device configuration, monitoring, and program transfer for the DeviceNet and EtherNet/IP networks.

Monitor Safety Systems

Safety systems can be monitored through the EtherNet/IP.

The safety system can be monitored from a PLC by using a modular designed Safety Control Unit with a EtherNet/IP Coupler Unit.

NX Series Ether/Net Coupler Unit

NX Series Safety CPU Unit Safety I/O Unit

Flexibility System Construction and Easy Expansion

Convenience of the Universal Ethernet Right in Your Hands

Higher Data Link Capacity

9 times the capacity of previous OMRON models

High-capacity communications with high-speed high-capacity bus

All types of data, from process interlocks and manufacturing recipes to production data, can be exchanged at high speed and with optimal timing. The ability to communicate is incomparably better than previous networks, such as the Controller Link and FL-net.

Data link capacity (total)	EtherNet/IP	180,000 words	**9**times
	Controller Link	20,000 words	
	FL-net(OMRON)	8,704 words	

Data link capacity (Unit)	EtherNet/IP	180,000 words	**45**times
	Controller Link	4,000words	
	FL-net(OMRON)	8,704words	

Number of Units connected via data links	EtherNet/IP	256units	**4**times
	Controller Link	62units	
	FL-net(OMRON)	128units	

Note: Using a built-in EtherNet/IP port on CJ2H and EtherNet/IP Units.

Low Cost Expansion for Each Line

Flexible topology with the Ethernet switch

Flexible wiring and expansion are possible with Ethernet switches. This means that there will be no total network crashes caused by communications path errors, ensuring high network performance and security.

- Joining and leaving the network is possible during communications.

Nodes can leave the network during operation, enabling easy maintenance for error detection, separation, and restoration.

- Unpredictable delays caused by data collisions are minimum.
- Problems caused by wiring errors are minimized to each line.

Host application

NS-series PT

Communications packets are delivered only to recipients that need them.

Switch

Switch

EtherNet/IP

Switch

Networks don't collapse even if there is a wiring error.

Nodes can join or leave the network during operation.

Star topology using Ethernet switch technology

Reduced Network Facility and Wiring Costs

Generic LAN cables can be used.

- Metal cables of category 5, 5e, or higher can be used as LAN cables.
- Generic RJ-45 connectors can be used.

Standard wireless LAN can be used because EtherNet/IP is also Universal Ethernet.

There is no need to rewire even when layout has been changed.

- EtherNet/IP can be made wireless using the standard wireless LAN.
- High-speed Smart Roaming communications can be used for mobile units with the WE70 FA Wireless LAN. The communications range can be expanded by relaying communications between access points.

EtherNet/IP

Smart Roaming

Smart Roaming

EtherNet/IP

EtherNet/IP

EtherNet/IP

AGV and Facilities

AGV and Facilities

AGV and Facilities

From Host to Field Level over Ethernet

Integration of Control and Information Networks

High-speed Data Links with Optimal Cycles for Applications

### Flexible and high-speed cyclic communications

- Grouping can be used in data link tables to create multiple sections.

    Data link table can be divided into up to 256 groups (= connections).
    The optimum communications cycle for the application can be set for each group.

- Cyclic synchronization can be set for each group.

    The communications cycle can be set to between 0.5 ms and 10 s in 0.5-ms increments.
    Data concurrency is maintained for each connection. The communications cycle does not change even if the number of nodes increases. The communications performance is 30 times better than that of the Controller Link.
    Example:
    Data link refresh cycle for 25 linked Unit and 20,000 words/network is reduced from 300 ms to 10 ms.

- Facilities can be easily expanded.

    When expanding facilities, all you need to do is make additions to the tables. Expansion is possible with little time and low cost.
    Note: Using a built-in EtherNet/IP port on CJ2H and EtherNet/IP Units.

Previous

PLC for production management and instructions

Process A Process B Process C

All of them are slow at 50 ms with only one set of data links.

With the EtherNet/IP

PLC for production management and instructions

Process A Process B Process C

High-speed 3-ms data links for process interlocks

Low-speed 20-ms data links for status (inspection results, processing status, etc.)

The communications cycle can be optimized for the application.

FTP, Data Links, and Support Software Can Be Used Simultaneously with One Port

With the multipurpose EtherNet/IP port, an Ethernet Unit is not required for expansion.

Using the multipurpose EtherNet/IP port built into a CJ/NJ/NX/NY Unit, a single port can be used for data link communications between PLCs, messages between PLCs, and Universal Ethernet communications, such as FTP transfers while connecting Support Software. An EtherNet/IP Unit can be added to any CS/CJ-series PLC to achieve the same functions.


PT

Host application

EtherNet/IP

Message communication

FTP

Message communication Data link Data link

Using a CJ/NJ/NX/NY CPU Unit...

Memory Map Management Becomes Unnecessary.

Freed from memory map by tags

The transmission/reception area can be specified with normal names called tag names instead of addresses for communication on data links between devices or when communication with the host application.
The efficiency of design, startup, maintenance, and upgrading are improved.

- PT and host applications can be developed in parallel.

    Network symbols defined in CJ/NJ/NX/NY Units can be used as tags when designing the PT screen.
    Design is easy: Just decide on the tag names for the information and control departments.
    Changes to allocated addresses is not needed later in development.

- Easier facility upgrading and maintenance

    Even if physical addresses change in the PLC, there is no need to make any changes in the data link settings, in the PT, or in the host application.

NS-series PT

Programmable Terminal screen

Host application

Application Developed using tag name

Production_data

Production_data

EtherNet/IP

Accessed by tag name

Accessed by tag name

PLC ladder program
Developed using tag name

NJ CPU

Production_data

Data links using tag name

CJ2 CPU

Design data links.
Allocated using tag names

Tags are managed in the CJ2 CPU Unit.

Symbols table

Tag name	Physical address
Production_data	D100
Production_target	D200
⋮	⋮

EtherNet/IP Communications Specifications (CS/CJ/NJ/NX/NY Series)

Item Model			Machine Automation Controller Built-in EtherNet/IP port on NX701-□□□□	Machine Automation Controller Built-in EtherNet/IP port on NJ501-□□□□ or NJ301-□□□□ or NJ101-□□□□	Machine Automation Controller Built-in EtherNet/IP port on NX1P2	Industrial PC Platform IPC Machine Controller Built-in EtherNet/IP port on NY5□□-1	Programmable Controller Built-in EtherNet/IP port on CJ2H-CPU□□-EIP CS/CJ EtherNet/IP Unit CJ1W-EIP21/ CS1W-EIP21	Programmable Controller Built in EtherNet/IP Port on CJ2M-CPU3□
Number of port			2	1	1	1	1	1
Transfer Specifications	Media access Method		CSMA/CD					
	Modulation method		Baseband					
	Transmission paths		Star form					
	Baud rate		1G bit/s (1000BASE-T)	100M bit/s (100BASE-TX)		1G bit/s (1000BASE-T)	100M bit/s (100BASE-TX)	
	Transmission media		Shielded twisted-pair (STP) cable Category: 5, 5e or higher					
	Transmission distance		100 m (distance between hub and node)					
CIP service	Tag data links (Cyclic communications)	Number of connections	256 / port total 512	32	32	128	256	32
		Packet interval (refresh cycle)	0.5 to 10,000 ms (in 0.5-ms units)	1 to 10,000 ms *1 (in 1-ms units)	2 to 10,000 ms (in 1-ms units)	1 to 10,000 ms (in 1-ms units)	0.5 to 10,000 ms (in 0.5-ms units)	1 to 10,000 ms (in 0.5-ms units)
		Maximum allowed communications bandwidth per Unit	40,000 pps *2 *3	3,000 pps *1 *2		20,000 pps*2	6,000 to 12,000 pps *2 *4	3,000 pps *2
		Maximum link data size per Node (total size of all tags)	369,664 bytes (Total in 2 ports 739,328 byte)	19,200 bytes (9,600 words)		184,832 bytes (92,416 words)	369,664 bytes (184,832 words)	1,280 bytes (640 words)
		Maximum data size per connection	1,444 bytes (722 words) *5	600 bytes (300 words) *5		1,444 bytes (722 words) *5	1,444 bytes (722 words) or 504 bytes (252 words) *5	1,280 bytes (640 words) *4 *6
		Changing tag data link parameters during operation	Supported. *7					
		Multicast packet filter function *8	Supported.					
	Explicit Messaging	Class 3 (connected)	Supported.					
		UCMM (unconnected)	Supported.					
		CIP routing	Supported.					
FINS service	FINS/UDP		Not upported.				Supported.	
	FINS/TCP		Not upported.				Supported.	

*1. Use NJ-series CPU Unit with version 1.03 or later and Sysmac Studio with version 1.04 or later.
    When using the CPU Unit version 1.02 or earlier, the Packet interval is 10 to 10,000 ms in 1.0-ms increments and the Maximum allowed communications bandwidth per Unit is 1,000 pps.
*2. In this case, pps means "packets per second" and indicates the number of packets that can be processed in one second.
*3. If the two built-in EtherNet/IP ports are used simultaneously, the maximum communications data size for two ports in total will be reached.
*4. When using the EtherNet/IP Unit with version 3.0 or later. When using the EtherNet/IP Unit with version 2.1 or earlier, the maximum allowed communications bandwidth per Unit is 6,000 pps. When using the EtherNet/IP Unit with version 3.0 or later, the Network Configurator with version 3.57 or higher is required.
*5. To use 505 to 1,444 bytes as the data size, the system must support the Large Forward Open standard (an optional CIP specification).
    NJ/NX/NY-series, CS/CJ-series Units support this standard, but other companies' devices may not support it.
*6. Unit version 2.0 of built-in EtherNet/IP section: 20 words.
*7. If parameters are changed, the target EtherNet/IP Unit will restart. When other nodes communicating with the target node, the affected data willtemporarily timeout and automatically recover later.
*8. Since the EtherNet/IP Unit is equipped with an IGMP client, unnecessary multicast packets can be filtered by using a switching hub that supports IGMP snooping.

Ordering Information

■NX-series CPU Units

Product name	Specifications			Current (Power) consumption	Model	Standards
	Program capacity	Memory capacity for variables	Number of motion axes			
NX701 CPU Units	80 MB	4 MB: Retained during power interruption 256 MB: Not retained during power interruption	256	40 W (including SD Memory Card and End Cover)	NX701-1700	UC1, RCM, CE, KC
			128		NX701-1600	

■NJ-series CPU Units

Product name	Specifications							Current consumption (A)		Model	Standards
	I/O capacity / maximum umber of configuration Units (Expansion Racks)	Program capacity	Memory capacity for variables	Number of motion axes	Database Connection function	SECS/GEM Communication function	Number of controlled robots	5 VDC	24 VDC		
NJ501 CPU Units		20MB	2 MB: Retained during power interruption 4 MB: Not retained during power interruption	64	No	No	—	1.90	—	NJ501-1500	UC1, N, L, CE, RCM, KC
				32						NJ501-1400	
				16						NJ501-1300	
NJ301 CPU Units		5MB	0.5 MB: Retained during power interruption 2 MB: Not retained during power interruption	8						NJ301-1200	
				4						NJ301-1100	
NJ101 CPU Units	2,560 points / 40 Units (3 Expansion Racks)	3MB		2						NJ101-1000	
				0						NJ101-9000	
NJ-series Database Connection CPU Units		20MB	2 MB: Retained during power interruption 4 MB: Not retained during power interruption	64	Yes					NJ501-1520	
				32						NJ501-1420	
				16						NJ501-1320	
		3MB	0.5 MB: Retained during power interruption 2 MB: Not retained during power interruption	2						NJ101-1020	
				0						NJ101-9020	
NJ-series SECS/GEM CPU Unit			2 MB: Retained during power interruption 4 MB: Not retained during power interruption	16		Yes				NJ501-1340	
NJ-series NJ Robotics CPU Units		20MB		64	No	No	8 max.*			NJ501-4500	
				32						NJ501-4400	
				16						NJ501-4300	
							1			NJ501-4310	
					Yes		8 max.*			NJ501-4320	

* The number of controlled robots varies according to the number of axes used for the system.

■ NX-series NX1P2 CPU Units

Product name	Specifications							Model	Standards
	Program capacity	Memory capacity for variables	Maximum number of used real axes		Total of built-in Inputs				
			Number of motion axes	Single-axis position control axes	Inputs	Outputs			
NX1P2 CPU Units	1.5 MB	32 kB: Retained during power interruption 2 MB: Not retained during power interruption	8	4	4	40	24	16, NPN transistor	NX1P2-1140DT	UC1, CE, RCM, KC
								16, PNP transistor *	NX1P2-1140DT1	
			6	2	4			16, NPN transistor	NX1P2-1040DT	
								16, PNP transistor *	NX1P2-1040DT1	
			4	0	4	24	14	10, NPN transistor	NX1P2-9024DT	
								10, PNP transistor *	NX1P2-9024DT1	

Note: NX1P2 includes 1 End Cover (NX-END02).

* With load short-circuit protection.

■Industrial PC Platform NY-series IPC Machine Controller

The industrial PC Platform has extended configuration possibilities to meet your requirements, below an overview of the most used and recommended models. Selecting one of the models below will bring the benefit of faster delivery times.
In case your preferred model is not listed below, please contact your Omron representative to discuss the possibilities.

Product name	Specifications						Model	Standards
	OS	CPU type	Number of motion axes	RAM memory (non-ECC type)	Storage size	Interface option		
Industrial Box PC	Windows Embedded Standard 7 - 64bit	Intel® Core™ i7-4700EQ	64	8 GB	64GB SSD (SLC)	RS-232C	NY512-1500-1XX21391X	CE, KC, RCM
					320GB HDD		NY512-1500-1XX213C1X	
			32		64GB SSD (SLC)		NY512-1400-1XX21391X	
					320GB HDD		NY512-1400-1XX213C1X	
			16		64GB SSD (SLC)		NY512-1300-1XX21391X	
					320GB HDD		NY512-1300-1XX213C1X	
Industrial Panel PC			64		64GB SSD (SLC)		NY532-1500-111213910	
					320GB HDD		NY532-1500-111213C10	
			32		64GB SSD (SLC)		NY532-1400-111213910	
					320GB HDD		NY532-1400-111213C10	
			16		64GB SSD (SLC)		NY532-1300-111213910	
					320GB HDD		NY532-1300-111213C10	

■CJ2H CPU Units (with Built-in EtherNet/IP)

Product name	I/O capacity/No. of Configuration Units (maximum No. of Expansion Racks)	Program capacity	Data memory capacity	LD instruction execution time	Current consumption (A)		Model	Standards
					5V	24V		
CJ2H CPU Units (with Built-in EtherNet/IP)	2560 points/40 Units (3 Expansion Racks max.)	400 Ksteps	832 K words (DM: 32 K words, EM: 32 K words × 25 banks)	0.016 μs	0.82 *	—	CJ2H-CPU68-EIP	UC1, N, L, CE
		250 Ksteps	512 K words (DM: 32 K words, EM: 32 K words × 15 banks)				CJ2H-CPU67-EIP	
		150 Ksteps	352 K words (DM: 32 K words, EM: 32 K words × 10 banks)				CJ2H-CPU66-EIP	
		100 Ksteps	160 K words (DM: 32 K words, EM: 32 K words × 4 banks)				CJ2H-CPU65-EIP	
		50 Ksteps	160 K words (DM: 32 K words, EM: 32 K words × 4 banks)				CJ2H-CPU64-EIP	

* Add 0.15 A per Adapter when using NT-AL001 RS-232C/RS-422A Adapters. Add 0.04 A per Adapter when using CJ1W-CIF11 RS-422A Adapters.
  Add 0.20A/Unit when using NV3W-M□20L(-V1) Programmable Terminals. Refer to the CJ2 CPU Unit Catalog (Cat. No. P059) for details.

■CJ2M CPU Units (with Built-in EtherNet/IP)

Product name	Specifications						Current consumption (A)		Model	Standards
	I/O capacity/ Mountable Units (Expansion Racks)	Program capacity	Data memory capacity	LD instruction execution time	EtherNet/IP function	Option board slot	5 V	24 V		
CJ2M (with Built-in EtherNet/IP) CPU Units	2,560 points/ 40 Units (3 Expansion Racks max.)	60K steps	160K words (DM: 32K words, EM: 32K words × 4 banks)	0.04 μs	YES	YES	0.7*	—	CJ2M-CPU35	UC1, N, L, CE
		30K steps							CJ2M-CPU34	
		20K steps	64K words (DM: 32K words, EM: 32K words × 1 bank)						CJ2M-CPU33	
		10K steps							CJ2M-CPU32	
		5K steps							CJ2M-CPU31	

* Add 0.005A, 0.030A, and 0.075A when using Serial Communications Option Boards (CP1W-CIF01/11/12), respectively.
  Add 0.15A/Unit when using NT-AL001 RS-232C/RS-422A Adapters. Add 0.04A/Unit when using CJ1W-CIF11 RS-422A Adapters.
  Add 0.20A/Unit when using NV3W-M□20L(-V1) Programmable Terminals. Refer to the CJ2 CPU Unit Catalog (Cat. No. P059) for details.

■EtherNet/IP Units

Unit type	Product name	Specifications			No. of unit numbers allocated	Current consumption (A)			Model	Standards
		Communications cable	Communications type	Max. Units mountable per CPU Unit		5V	24V	26V		
CJ CPU Bus Unit	EtherNet/IP Unit	Shielded twisted-pair cable (STP), category 5, 5e or higher	Tag data links and message communications	8 *1	1	0.41	—		CJ1W-EIP21 *2*3	UC1, N, L, CE
CS CPU Bus Unit	EtherNet/IP Unit			8	1	0.41		—	CS1W-EIP21 *4	

*1. Up to four EtherNet/IP Units can be connected to a NJ CPU Unit. Up to seven EtherNet/IP Units can be connected to a CJ2H-CPU6□-EIP.
   Up to two EtherNet/IP Units can be connected to a CJ2M CPU Unit.
*2. The EtherNet/IP Units can be used in CJ-series (CJ1 and CJ2), CP1H, NSJ-series and NJ-series PLCs.
   EtherNet/IP Unit with unit version 2.1 or later is required to connect C1JW-EIP21 to NJ-series CPU Unit. Use NJ-series CPU Unit with version 1.01 or later and
   Sysmac Studio with version 1.02 or later.
*3. You cannot use the following functions if you connect to the NJ-series CPU Unit through an EtherNet/IP Unit.
   • Going online with a CPU Unit from the Sysmac Studio. (However, you can go online from the Network Configurator.)
   • Troubleshooting from an NS-series PT.
*4. The EtherNet/IP Units can be used in CS-series PLCs.

■NX-series EtherNet/IP Coupler Unit

Unit type	Product name	Current consumption	Maximum I/O power supply current	Model	Standards
NX Series Communication Coupler Unit	EtherNet/IP Coupler Unit	1.60 W or lower	10 A	**NX-EIC202**	UC1, CE, RCM, KC

Note: For details, refer to the NX-EIC202 datasheet, visit our Web site (www.ia.omron.com/).

■Programmable Terminals

Product name	Specifications	Model
NA Series	15.4 inch wide screen TFT, 1280 x 800 dots, Frame color: Black *1	**NA5-15W101B**
	12.1 inch wide screen TFT, 1280 x 800 dots, Frame color: Black *1	**NA5-12W101B**
	9 inch wide screen TFT, 800 x 480 dots, Frame color: Black *1	**NA5-9W001B**
	7 inch wide screen TFT, 800 x 480 dots, Frame color: Black *1	**NA5-7W001B**
NS Series	15-inch TFT, 1,024 x 768 dots, Frame color: Silver	**NS15-TX01S-V2**
	15-inch TFT, 1,024 x 768 dots, Frame color: Black *2	**NS15-TX01B-V2**
	12.1-inch TFT, 800 x 600 dots, Frame color: Black *2	**NS12-TS01B-V2**
	10.4-inch TFT, 640 x 480 dots, Frame color: Black *2	**NS10-TV01B-V2**
	8.4-inch TFT, 640 x 480 dots, Frame color: Black *2	**NS8-TV01B-V2**
	5.7-inch High-luminance TFTT, 320 x 240 dots, Frame color: Black *2	**NS5-TQ11B-V2**
	5.7-inch TFT, 320 x 240 dots, Frame color: Black *2	**NS5-SQ11B-V2**

*1. The PTs are also available with silver colored frames. For details, refer to the NA Series Catalog (Cat. No. V413).
*2. The PTs are also available with ivory colored frames. For details, refer to the NS Series Catalog (Cat. No. V405).

■FA Wireless LAN Units

Product name	Applicable area	Type	Model	Standards
FA Wireless LAN Units	Japan	Access point (master)	**WE70-AP**	—
		Client (slave)	**WE70-CL**	

Note: 1. Includes Pencil Antenna, Mounting Magnet, and Mounting Screws.
2. Always use a model applicable for your area.
There are applicable products for other areas, such as Europe, USA, Canada, and China. For details, refer to the FA Wireless LAN Unit Datasheet (Cat. No. N154).

■Vision Sensor

Product name	Specifications	Model	Standards
Vision System FH Series	High-speed Controllers (4 core)	**FH-3050(-□□)**	CE
	Standard Controllers (2 core)	**FH-1050(-□□)**	
	Lite Controllers (2 core)	**FH-L550(-□□)**	
Vision System FZ5 Series	High-speed Controllers	**FZ5-110□(-10)**	
	Standard Controllers	**FZ5-60□(-10)**	
	Lite Controllers	**FZ5-L35□(-10)**	
PC Vision System FJ Series	Core i5 2.4GHZ CPU Controllers	**FJ-(H)300□(-10)**	CE
Smart Camera FQ2 Series	All Sensors	**FQ2-S□**	CE
Optical Character Recognition Sensor FQ2-CH Series	All Sensors	**FQ2-CH□**	CE

Note: For detail,refer to the Vision System FH Series Catalog (Cat. No. Q197), Vision System FZ5 Series Catalog (Cat. No. Q203), PC Vision System FJ Series Datasheet (Cat. No. Q184), Smart Camera FQ2 Series Catalog (Cat. No. Q193).

■Displacement Sensor

Product name	Type	Model	Standards
Displacement Sensor ZW-7000 Series	All Controllers	**ZW-7000T**	CE
Displacement Sensor ZW Series	Controller with EtherCAT and EtherNet/IP	**ZW-CE1□T**	CE

* For detail,refer to the Confocal Fiber Displacement Sensor with White LED ZW-7000 Series Catalog (Cat. No. Q250), the Confocal Fiber Displacement Sensor ZW Series Catalog (Cat. No. E421).

■Safety Network Controller

Product name	No. of I/O points			Model	Unit version
	Safety inputs	Test outputs	Safety outputs		
Safety Network Controller	16	4	8	**NE1A-SCPU01-EIP**	Ver. 1.1
	40	8	8	**NE1A-SCPU02-EIP**	Ver. 1.1

Note: For detail,refer to the website at:http://www.ia.omron.com/.

■Safety Laser Scanner

Product name	Specifications		Model
		Max. Operating Range (Safety Zone)	
Safety Laser Scanner	OS32C with EtherNet/IP and back location cable entry	3m	**OS32C-BP-DM**
		4m	**OS32C-BP-DM-4M**
	OS32C with EtherNet/IP and side location cable entry *	3m	**OS32C-SP1-DM**
		4m	**OS32C-SP1-DM-4M**

* For OS32C-SP1(-DM), each connector is located on the left as viewed from the back of the I/O block.
Note1: CD-ROM (Configuration tool)
OS supported: Windows 2000, Windows XP (32-bit version, Service Pack 3 or later) Windows Vista (32-bit version), Windows 7 (32-bit version/ 64-bit version)
Note2: For details, Refer to the Safety Laser Scanner OS32C Catalog (Cat. No. Z298).

■RFID System

Product name	Size	Model
RFID System V680S series Reader/Writer	50 × 50 × 30 mm	**V680S-HMD63-EIP**
	75 × 75 × 40 mm	**V680S-HMD64-EIP**
	120 × 120 × 40 mm	**V680S-HMD66-EIP**

Note: For details, Refer to the RFID System V680S Series Catalog (Cat. No. Q196)

■Industrial Switching Hubs

Product name	Specifications			Accessories	Current consumption (A)	Model	Standards
	Functions	No. of ports	Failure detection				
Industrial Switching Hubs	Quality of Service (QoS): EtherNet/IP control data priority Failure detection: Broadcast Storm and LSI error detection 10/100Base-TX, Auto-negotiation	3	No	•Power supply connector	0.22	**W4S1-03B**	UC, CE
		5	No		0.22	**W4S1-05B**	UC, CE
		5	Yes	•Power supply connector •Connector for informing error	0.22	**W4S1-05C**	CE

■Software

How to Select Required Support Software for Your Controller

The required Support Software depends on the Controller to connect. Please check the following table when purchasing the Support Software.

Controller	Software
NJ/NX/NY-series	Automation Software Sysmac Studio
CS, CJ, CP, and other series	FA Integrated Tool Package CX-One

Automation Software Sysmac Studio

Please purchase a DVD and required number of licenses the first time you purchase the Sysmac Studio. DVDs and licenses are available individually. Each model of licenses does not include any DVD.

Product name	Specifications	Number of licenses	Media	Model	Standards
Sysmac Studio Standard Edition Ver.1.□□	The Sysmac Studio is the software that provides an integrated environment for setting, programming, debugging and maintenance of machine automation controllers including the NJ/NX-series CPU Units, NY-series Industrial PC, EtherCAT Slave, and the HMI. Sysmac Studio runs on the following OS. Windows 7 (32-bit/64-bit version)/Windows 8 (32-bit/64-bit version)/ Windows 8.1 (32-bit/64-bit version)/Windows 10(32-bit/64-bit version)	— (Media only)	DVD	**SYSMAC-SE200D**	—
	The Sysmac Studio Standard Edition DVD includes Support Software to set up EtherNet/IP Units, DeviceNet slaves, Serial Communications Units, and Support Software for creating screens on HMIs (CX-Designer). For details, refer to the Sysmac Integrated Catalogue (P072).	1 license *	—	**SYSMAC-SE201L**	—

* Multi licenses are available for the Sysmac Studio (3, 10, 30, or 50 licenses).

FA Integrated Tool Package CX-One

Product name	Specifications	Number of licenses	Media	Model	Standards
FA Integrated Tool Package CX-One Ver. 4.□	The CX-One is a comprehensive software package that integrates Support Software for OMRON PLCs and components. CX-One runs on the following OS. Windows XP (Service Pack 3 or higher, 32-bit version)/ Windows Vista (32-bit/64-bit version)/Windows 7 (32-bit/64-bit version)/ Windows 8 (32-bit/64-bit version)/Windows 8.1 (32-bit/64-bit version)/ Windows 10 (32-bit/64-bit version) CX-One Ver. 4.□ includes Network-Configurator. For details, refer to the CX-One Catalog (Cat. No. R134).	1 license*	DVD	**CXONE-AL01D-V4**	—

* Multi licenses are available for the CX-One (3, 10, 30, or 50 licenses). Site licenses are available for users who will run CX-One on multiple computers.

■FA Communications Software (EtherNet/IP Compatible)

Name	Specifications	Model	Standards
CX- Compolet *	Software components that can make it easy to create programs for communications between a computer and controllers. This packaged product bundles CX-Compolet and SYSMAC Gateway with 1 license each. Supported execution environment: .NET Framework (2.0, 3.0, 3.5, 4.0 or 4.5.1) Development environment: Visual Studio 2005/2008/2010/2012/2013/2015 Development languages: Visual Basic, C# Supported communications: Equal to SYSMAC Gateway.	**WS02-CPLC1**	—
SYSMAC Gateway *	Communications middleware for personal computers running Windows. Supports CIP communications and tag data links (EtherNet/IP) in addition to FinsGateway functions. This package includes SYSMAC Gateway with 1 licence. (Fins Gateway is also included.) Supported communications: RS-232C, USB, Controller Link, SYSMAC LINK, Ethernet, EtherNet/IP	**WS02-SGWC1**	—

Supported OS: Microsoft Windows XP (32bit)/Windows Vista (32bit)/Windows 7 (32bit/64bit)/Windows 8 (32bit/64bit)/Windows 8.1 (32bit/64bit)/Windows 10 (32-bit/64-bit version) Windows Server 2003 (32bit)/Windows Server 2008 (32bit/64bit)/Windows Server 2008 R2 (64bit)/ Windows Server 2012 (64bit)/Windows Server 2012 R2 (64bit)

* One license is required per computer.
Note: 1. When .NET Framework version 1.1 (Visual Studio 2003) is used for development, only the specifications of CX-Compolet version 1.5 are available.
Note: 2. For details, Refer to the FA Communications Software Catalog (Cat. No. V302).

MEMO

MEMO

MEMO

Note: Do not use this ducument to operate the Unit.